

## Description of Permissive Change

This report is prepared for FCC class II permissive change. Difference compared with the original report is listed as below, therefore Conducted and Radiated Emission Measurements had been re-tested.

ITEM	ORIGINAL DESCRIPTION	ITEM	CLASS II CHANE DESCRIPTION																				
1	Patch antenna with UFL connector Dipole antenna with R-SMA connector	1	Adding Patch antenna with UFL connector																				
2	<b>Adapter:</b> <table border="1"> <tr> <td><b>Brand</b></td><td>MEAN WELL</td></tr> <tr> <td><b>Model</b></td><td>ES18U48-P1J</td></tr> <tr> <td><b>Input Power</b></td><td>100-240Vac, 50-60Hz, 0.5A</td></tr> <tr> <td><b>Output Power</b></td><td>48Vdc, 0.375A, 18W</td></tr> <tr> <td><b>Power Cord</b></td><td>DC 1.8m non-shielded cable with one core</td></tr> </table>	<b>Brand</b>	MEAN WELL	<b>Model</b>	ES18U48-P1J	<b>Input Power</b>	100-240Vac, 50-60Hz, 0.5A	<b>Output Power</b>	48Vdc, 0.375A, 18W	<b>Power Cord</b>	DC 1.8m non-shielded cable with one core	2	<b>Adapter:</b> <table border="1"> <tr> <td><b>Brand</b></td><td>MEAN WELL</td></tr> <tr> <td><b>Model</b></td><td>ES25U48-480</td></tr> <tr> <td><b>Input Power</b></td><td>100-240Vac, 50-60Hz, 0.7A</td></tr> <tr> <td><b>Output Power</b></td><td>48Vdc, 0.52A, 25W</td></tr> <tr> <td><b>Power Cord</b></td><td>DC 1.8m non-shielded cable with one core</td></tr> </table>	<b>Brand</b>	MEAN WELL	<b>Model</b>	ES25U48-480	<b>Input Power</b>	100-240Vac, 50-60Hz, 0.7A	<b>Output Power</b>	48Vdc, 0.52A, 25W	<b>Power Cord</b>	DC 1.8m non-shielded cable with one core
<b>Brand</b>	MEAN WELL																						
<b>Model</b>	ES18U48-P1J																						
<b>Input Power</b>	100-240Vac, 50-60Hz, 0.5A																						
<b>Output Power</b>	48Vdc, 0.375A, 18W																						
<b>Power Cord</b>	DC 1.8m non-shielded cable with one core																						
<b>Brand</b>	MEAN WELL																						
<b>Model</b>	ES25U48-480																						
<b>Input Power</b>	100-240Vac, 50-60Hz, 0.7A																						
<b>Output Power</b>	48Vdc, 0.52A, 25W																						
<b>Power Cord</b>	DC 1.8m non-shielded cable with one core																						