

FCC TEST REPORT

REPORT NO.: RF930817L09A

MODEL NO.: SP-922

RECEIVED: NA

TESTED: Aug. 28 ~ Oct. 28, 2004

ISSUED: Apr. 28, 2005

APPLICANT: SENAO INTERNATIONAL CO., LTD.

ADDRESS: 2F, NO. 531 CHUNG CHENG RD., HSIN-TIEN, TAIPEI, TAIWAN, R. O. C.

ISSUED BY: Advance Data Technology Corporation

LAB ADDRESS: No. 47, 14th Ling, Chia Pau Tsuen, Lin Kou Hsiang 244, Taipei Hsien, Taiwan, R.O.C.

TEST LOCATION: No. 19, Hwa Ya 2nd Rd., Wen Hwa Tsuen, Kwei Shan Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.

This test report consists of 86 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by CNLA, A2LA or any government agencies. The test results in the report only apply to the tested sample.



0528
ILAC MRA



No. 2177-01

Table of Contents

1	CERTIFICATION	4
2	SUMMARY OF TEST RESULTS	5
2.1	GENERAL DESCRIPTION OF EUT	6
3	GENERAL INFORMATION	7
3.1	GENERAL DESCRIPTION OF EUT	7
3.2	DESCRIPTION OF TEST MODES	8
3.2.1	CONFIGURATION OF SYSTEM UNDER TEST	9
3.2.2	TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL:	10
3.3	GENERAL DESCRIPTION OF APPLIED STANDARDS	12
3.4	DESCRIPTION OF SUPPORT UNITS	12
4	TEST TYPES AND RESULTS	13
4.1	CONDUCTED EMISSION MEASUREMENT	13
4.1.1	LIMITS OF CONDUCTED EMISSION MEASUREMENT	13
4.1.2	TEST INSTRUMENTS	13
4.1.3	TEST PROCEDURES	14
4.1.4	DEVIATION FROM TEST STANDARD	14
4.1.5	TEST SETUP	15
4.1.6	EUT OPERATING CONDITIONS	15
4.1.7	TEST RESULTS	16
4.2	NUMBER OF HOPPING FREQUENCY USED	28
4.2.1	LIMIT OF HOPPING FREQUENCY USED	28
4.2.2	TEST INSTRUMENTS	28
4.2.3	TEST PROCEDURES	29
4.2.4	DEVIATION FROM TEST STANDARD	29
4.2.5	TEST SETUP	30
4.2.6	TEST RESULTS	30
4.3	DWELL TIME ON EACH CHANNEL	32
4.3.1	LIMIT OF DWELL TIME USED	32
4.3.2	TEST INSTRUMENTS	32
4.3.3	TEST PROCEDURES	33
4.3.4	DEVIATION FROM TEST STANDARD	33
4.3.5	TEST SETUP	33
4.3.6	TEST RESULTS	34
4.4	CHANNEL BANDWIDTH	36
4.4.1	LIMITS OF CHANNEL BANDWIDTH	36
4.4.2	TEST INSTRUMENTS	36
4.4.3	TEST PROCEDURE	37
4.4.4	DEVIATION FROM TEST STANDARD	37

4.4.5	TEST SETUP.....	37
4.4.6	EUT OPERATING CONDITION	37
4.4.7	TEST RESULTS	38
4.5	HOPPING CHANNEL SEPARATION	41
4.5.1	LIMIT OF HOPPING CHANNEL SEPARATION	41
4.5.2	TEST INSTRUMENTS.....	41
4.5.3	TEST PROCEDURES	42
4.5.4	DEVIATION FROM TEST STANDARD	42
4.5.5	TEST SETUP.....	42
4.5.6	TEST RESULTS	43
4.6	MAXIMUM PEAK OUTPUT POWER	46
4.6.1	LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT	46
4.6.2	INSTRUMENTS.....	46
4.6.3	TEST PROCEDURES	47
4.6.4	DEVIATION FROM TEST STANDARD	47
4.6.5	TEST SETUP.....	48
4.6.6	EUT OPERATING CONDITION	48
4.6.7	TEST RESULTS	49
4.7	RADIATED EMISSION MEASUREMENT	52
4.7.1	LIMITS OF RADIATED EMISSION MEASUREMENT	52
4.7.2	TEST INSTRUMENTS.....	53
4.7.3	TEST PROCEDURES	54
4.7.4	DEVIATION FROM TEST STANDARD	54
4.7.5	TEST SETUP.....	55
4.7.6	EUT OPERATING CONDITIONS	55
4.7.7	TEST RESULTS	56
4.8	BAND EDGES MEASUREMENT	77
4.8.1	LIMITS OF BAND EDGES MEASUREMENT.....	77
4.8.2	TEST INSTRUMENTS.....	77
4.8.3	TEST PROCEDURE.....	77
4.8.4	DEVIATION FROM TEST STANDARD	77
4.8.5	EUT OPERATING CONDITION	78
4.8.6	TEST RESULTS	78
4.9	ANTENNA REQUIREMENT	81
4.9.1	STANDARD APPLICABLE	81
4.9.2	ANTENNA CONNECTED CONSTRUCTION	81
5	PHOTOGRAPHS OF THE TEST CONFIGURATION.....	82
6	INFORMATION ON THE TESTING LABORATORIES	86



1 CERTIFICATION

PRODUCT : Digital 4-line cordless phone system
MODEL NO. : SP-922
BRAND NAME : EnGenius
APPLICANT : SENAO INTERNATIONAL CO., LTD.
TESTED : Aug. 28 ~ Oct. 28, 2004
TEST SAMPLE : ENGINEERING SAMPLE
STANDARDS : FCC Part 15, Subpart C (Section 15.247),
ANSI C63.4-2003

The above equipment (model no.: SP-922) is identical to model no.: SN-1302B & SN-1302H, which has been tested by **Advance Data Technology Corporation** from Aug. 28 ~ Oct. 28, 2004, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : Candice Chen, **DATE:** Apr. 28, 2005
(Candice Chen)

TECHNICAL
ACCEPTANCE : Garly Chang, **DATE:** Apr. 28, 2005
Responsible for RF (Garly Chang)

APPROVED BY : Cody Chang, **DATE:** Apr. 28, 2005
(Cody Chang, Deputy Manager)

2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 15, Subpart C			
Standard Section	Test Type and Limit	Result	REMARK
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit Minimum passing margin is -2.46dB at 0.170 MHz
15.247(a)(1)(i)-(ii)	Number of Hopping Frequency Used Spec.: At least 50 channels	PASS	Meet the requirement of limit
15.247(a)(1)(i)	Dwell Time on Each Channel Spec. : Max. 0.4 second within 20 second	PASS	Meet the requirement of limit
15.247(a)(1)(i)	Hopping Channel Separation Spec. : Min. 25 kHz or 20 dB bandwidth, which ever is greater	PASS	Meet the requirement of limit
15.247(a)(1)	Spectrum Bandwidth of a Frequency Hopping Sequence Spread Spectrum System Spec.: Max. 500 kHz	PASS	Meet the requirement of limit
15.247(b)(2)	Maximum Peak Output Power Spec.: max. 30dBm	PASS	Meet the requirement of limit
15.247(d)	Transmitter Radiated Emissions Spec.: Table 15.209	PASS	Meet the requirement of limit Minimum passing margin is -1.46dB at 657.88MHz
15.247(d)	Band Edge Measurement	PASS	Meet the requirement of limit

2.1 GENERAL DESCRIPTION OF EUT

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	9kHz~30MHz	2.44 dB
Radiated emissions	30MHz ~ 200MHz	3.55 dB
	200MHz ~1000MHz	3.58 dB
	1GHz ~ 18GHz	2.20 dB
	18GHz ~ 40GHz	1.88 dB

3 GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

PRODUCT	Digital 4-line cordless phone system
MODEL NO.	SP-922
POWER SUPPLY	5.5Vdc from power adapter for the cradle 3.7Vdc from battery for the phone
MODULATION TYPE	MSK
FREQUENCY RANGE	902.5155MHz ~ 927.5972MHz
NUMBER OF CHANNEL	50
OUTPUT POWER	587.489mW
ANTENNA TYPE	Dipole antenna with 2.0dBi gain for the Phone and Cradle
DATA CABLE	NA
I/O PORTS	RJ11, Audio-In
ASSOCIATED DEVICES	NA

NOTE:

1. This is a duplicate report of RF930817L09. Everything is same as before except for the model designation, and the main engine which was collocated.
2. The EUT included the Phone. The Phone have both Transmission and Receiver function.
3. The Phone + Cradle was powered by the following adapter:

BRAND:	BASE POWER TECHNOLOGY CO. LTD.
MODEL :	A602-0307-551
INPUT :	100-240Vac, 0.5A, 47-63Hz
OUTPUT :	5.5Vdc, 1.5A

4. The above EUT information was declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.


3.2 DESCRIPTION OF TEST MODES

There are 50 channels provided to this EUT.


CH	Frequency	CH	Frequency	CH	Frequency
1	902.5155	8	905.7519	20	912.2245
2	902.9200	19	911.8200	43	924.3608
4	903.7291	42	923.9563	36	920.7199
10	906.9655	34	919.9109	24	914.2473
23	913.4382	21	912.6291	3	903.3246
50	927.5972	46	925.5745	7	905.3473
49	927.1926	41	923.1472	16	910.2018
48	926.7881	33	919.5063	35	920.3154
45	925.1699	18	911.0109	22	913.0336
40	922.7427	39	922.3381	47	926.3836
31	917.8881	30	917.4836	44	924.7654
14	909.3927	12	907.7746	37	921.5290
15	909.7973	25	915.0563	26	915.4609
32	919.1018	5	904.5382	6	904.9428
17	910.6064	13	908.1791	29	917.0791
38	921.9336	28	916.6745	11	907.3700
27	915.8654	9	906.1564		

3.2.1 CONFIGURATION OF SYSTEM UNDER TEST

For Test Mode A



For Test Mode B



3.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL:

EUT configure mode	Applicable to				Description
	PLC	RE<1G	RE≥1G	APCM	
A	X	X	Note 1	X	The Phone + Cradle with charger function
B	X	X	Note 1	X	The Phone + Earphone only with charger function

Where PLC: Power Line Conducted Emission

RE<1G RE: Radiated Emission below 1GHz

RE≥1G: Radiated Emission above 1GHz

APCM: Antenna Port Conducted Measurement

Note 1: No effect on Radiated Emission above 1GHz.

Power Line Conducted Emission Test:

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations.
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT configure mode	Available Channel	Tested Channel	Modulation Type
A	1 to 50	1, 25, 50	MSK
B	1 to 50	1, 25, 50	MSK

Radiated Emission Test (Below 1 GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations.
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT configure mode	Available Channel	Tested Channel	Modulation Type
A	50	1, 25, 50	MSK
B	50	1, 25, 50	MSK

Radiated Emission Test (Above 1 GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations.
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT configure mode	Available Channel	Tested Channel	Modulation Type
B	1 to 50	1, 25, 50	MSK

**Bandedge Measurement:**

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations.
- ☒ Following channel(s) was (were) selected for the final test as listed below.

Available Channel	Tested Channel	Modulation Type
1 to 50	1, 25, 50	MSK

Antenna Port Conducted Measurement:

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations.
- ☒ Following channel(s) was (were) selected for the final test as listed below.

Available Channel	Tested Channel	Modulation Type
1 to 50	1, 25, 50	MSK

3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a Digital 4-line cordless phone system. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C. (15.247)

ANSI C63.4- 2003

All test items have been performed and recorded as per the above standards.

3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	TELEPHONE	WONDER	WD-303	1F01024	N/A
2	MINE CASSETTE RECORDER	PANASONIC	RQ-L11	C1-010040	N/A
3	Telephone/Network Simulator	ASUS	PTT5102	L508A3629	N/A

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	NA
2	NA
3	NA

NOTE: 1. All power cords of the above support units are non shielded (1.8m).
2. Item 1 act as a communication partner to transfer data.

4 TEST TYPES AND RESULTS

4.1 CONDUCTED EMISSION MEASUREMENT

4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

- NOTE:**
1. The lower limit shall apply at the transition frequencies.
 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.
 3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

4.1.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
Test Receiver ROHDE & SCHWARZ	ESCS30	100291	Dec. 12, 2004
RF signal cable Woken	5D-FB	Cable-HYC01-01	Mar. 02, 2005
LISN ROHDE & SCHWARZ	ESH3-Z5	100312	Mar. 03, 2005
LISN ROHDE & SCHWARZ	ESH2-Z5	100104	Mar. 02, 2005
Software ADT	ADT_Cond_V3	NA	NA

- NOTE:**
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 2. The test was performed in HwaYa Shielded Room 1.
 3. The VCCI Site Registration No. is C-2040.




4.1.3 TEST PROCEDURES

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150 kHz to 30 MHz was searched. Emission levels (Limit -20dB) was not recorded.

4.1.4 DEVIATION FROM TEST STANDARD

No deviation

4.1.5 TEST SETUP



- Note:**
1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

4.1.6 EUT OPERATING CONDITIONS

For Test Mode A

- a. Placed the EUT on the testing table.
- b. EUT is under the charger function.

For Test Mode B

- a. Placed the EUT on the testing table.
- b. Run the test program (provided by manufacturer) to enable EUT under transmission/receiving condition continuously channel frequency.
- c. EUT is under the charger function.

4.1.7 TEST RESULTS

Conducted Worst-Case Data

EUT	Digital 4-line cordless phone system	MEASUREMENT DETAIL	
MODEL	SP-922	PHASE	Line 1
CHANNEL	Channel 1	6dB BANDWIDTH	9 kHz
MODULATION TYPE	MSK	ENVIRONMENTAL CONDITIONS	26deg. C, 68%RH, 991hPa
TESTED BY	Kent Chen	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TEST MODE	A		

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.188	0.12	49.76	-	49.88	-	64.10	54.10	-14.23	-
2	0.382	0.13	45.33	-	45.46	-	58.23	48.23	-12.77	-
3	0.947	0.15	47.04	37.88	47.19	38.03	56.00	46.00	-8.81	-7.97
4	1.352	0.15	46.60	33.29	46.75	33.44	56.00	46.00	-9.25	-12.56
5	1.910	0.16	45.31	-	45.47	-	56.00	46.00	-10.53	-
6	2.458	0.17	49.50	36.10	49.67	36.27	56.00	46.00	-6.33	-9.73

*(The test data is in accordance with ADT Report No.: RF930817L09.)

REMARKS: 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.


2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.

3. The emission levels of other frequencies were very low against the limit.

4. Margin value = Emission level - Limit value

5. Correction factor = Insertion loss + Cable loss

6. Emission Level = Correction Factor + Reading Value.




EUT	Digital 4-line cordless phone system	MEASUREMENT DETAIL	
MODEL	SP-922	PHASE	Line 2
CHANNEL	Channel 1	6dB BANDWIDTH	9 kHz
MODULATION TYPE	MSK	ENVIRONMENTAL CONDITIONS	26deg. C, 68%RH, 991hPa
TESTED BY	Kent Chen	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TEST MODE	A		

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.170	0.10	56.49	52.42	56.59	52.52	64.98	54.98	-8.39	-2.46
2	0.345	0.11	44.93	-	45.04	-	59.08	49.08	-14.04	-
3	0.857	0.14	45.80	-	45.94	-	56.00	46.00	-10.06	-
4	1.391	0.15	47.62	35.16	47.77	35.31	56.00	46.00	-8.23	-10.69
5	2.211	0.16	51.35	34.74	51.51	34.90	56.00	46.00	-4.49	-11.10
6	2.436	0.17	50.00	34.86	50.17	35.03	56.00	46.00	-5.83	-10.97

*(The test data is in accordance with ADT Report No.: RF930817L09.)

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.




EUT	Digital 4-line cordless phone system	MEASUREMENT DETAIL	
MODEL	SP-922	PHASE	Line 1
CHANNEL	Channel 25	6dB BANDWIDTH	9 kHz
MODULATION TYPE	MSK	ENVIRONMENTAL CONDITIONS	26deg. C, 68%RH, 991hPa
TESTED BY	Kent Chen	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TEST MODE	A		

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.189	0.12	49.77	-	49.89	-	64.08	54.08	-14.19	-
2	0.377	0.13	44.50	-	44.63	-	58.35	48.35	-13.73	-
3	0.955	0.15	46.55	37.27	46.70	37.42	56.00	46.00	-9.30	-8.58
4	1.531	0.16	46.90	34.33	47.06	34.49	56.00	46.00	-8.94	-11.51
5	2.117	0.16	50.71	36.84	50.87	37.00	56.00	46.00	-5.13	-9.00
6	2.449	0.17	51.38	33.97	51.55	34.14	56.00	46.00	-4.45	-11.86

*(The test data is in accordance with ADT Report No.: RF930817L09.)

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.




EUT	Digital 4-line cordless phone system	MEASUREMENT DETAIL	
MODEL	SP-922	PHASE	Line 2
CHANNEL	Channel 25	6dB BANDWIDTH	9 kHz
MODULATION TYPE	MSK	ENVIRONMENTAL CONDITIONS	26deg. C, 68%RH, 991hPa
TESTED BY	Kent Chen	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TEST MODE	A		

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.189	0.11	53.03	-	53.14	-	64.08	54.08	-10.94	-
2	0.384	0.12	46.12	-	46.24	-	58.18	48.18	-11.95	-
3	0.955	0.15	46.69	37.87	46.84	38.02	56.00	46.00	-9.16	-7.98
4	1.535	0.16	47.30	34.84	47.46	35.00	56.00	46.00	-8.54	-11.00
5	2.121	0.16	51.27	36.26	51.43	36.42	56.00	46.00	-4.57	-9.58
6	2.477	0.17	50.28	36.12	50.45	36.29	56.00	46.00	-5.55	-9.71

*(The test data is in accordance with ADT Report No.: RF930817L09.)

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.




EUT	Digital 4-line cordless phone system	MEASUREMENT DETAIL	
MODEL	SP-922	PHASE	Line 1
CHANNEL	Channel 50	6dB BANDWIDTH	9 kHz
MODULATION TYPE	MSK	ENVIRONMENTAL CONDITIONS	26deg. C, 68%RH, 991hPa
TESTED BY	Kent Chen	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TEST MODE	A		

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.189	0.12	49.57	-	49.69	-	64.08	54.08	-14.39	-
2	0.382	0.13	45.90	-	46.03	-	58.23	48.23	-12.21	-
3	0.947	0.15	46.26	37.46	46.41	37.61	56.00	46.00	-9.59	-8.39
4	1.535	0.16	49.36	35.23	49.52	35.39	56.00	46.00	-6.48	-10.61
5	2.112	0.16	51.50	35.82	51.66	35.98	56.00	46.00	-4.34	-10.02
6	2.457	0.17	50.45	36.58	50.62	36.75	56.00	46.00	-5.38	-9.25

*(The test data is in accordance with ADT Report No.: RF930817L09.)

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.




EUT	Digital 4-line cordless phone system	MEASUREMENT DETAIL	
MODEL	SP-922	PHASE	Line 2
CHANNEL	Channel 50	6dB BANDWIDTH	9 kHz
MODULATION TYPE	MSK	ENVIRONMENTAL CONDITIONS	26deg. C, 68%RH, 991hPa
TESTED BY	Kent Chen	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TEST MODE	A		

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.196	0.11	51.82	-	51.93	-	63.80	53.80	-11.87	-
2	0.377	0.12	44.52	-	44.64	-	58.35	48.35	-13.72	-
3	0.966	0.15	48.93	35.06	49.08	35.21	56.00	46.00	-6.92	-10.79
4	1.527	0.16	46.27	34.75	46.43	34.91	56.00	46.00	-9.57	-11.09
5	2.113	0.16	49.23	35.45	49.39	35.61	56.00	46.00	-6.61	-10.39
6	2.492	0.17	48.01	33.79	48.18	33.96	56.00	46.00	-7.82	-12.04

*(The test data is in accordance with ADT Report No.: RF930817L09.)

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.




EUT	Digital 4-line cordless phone system	MEASUREMENT DETAIL	
MODEL	SP-922	PHASE	Line 1
CHANNEL	Channel 1	6dB BANDWIDTH	9 kHz
MODULATION TYPE	MSK	ENVIRONMENTAL CONDITIONS	26deg. C, 68%RH, 991hPa
TESTED BY	Kent Chen	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TEST MODE	B		

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.197	0.12	50.76	-	50.88	-	63.74	53.74	-12.86	-
2	0.392	0.13	46.69	-	46.82	-	58.02	48.02	-11.21	-
3	0.982	0.15	48.87	38.06	49.02	38.21	56.00	46.00	-6.98	-7.79
4	1.574	0.16	49.94	35.99	50.10	36.15	56.00	46.00	-5.90	-9.85
5	2.164	0.16	52.00	37.55	52.16	37.71	56.00	46.00	-3.84	-8.29
6	2.503	0.17	51.68	35.59	51.85	35.76	56.00	46.00	-4.15	-10.24

*(The test data is in accordance with ADT Report No.: RF930817L09.)

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.




EUT	Digital 4-line cordless phone system	MEASUREMENT DETAIL	
MODEL	SP-922	PHASE	Line 2
CHANNEL	Channel 1	6dB BANDWIDTH	9 kHz
MODULATION TYPE	MSK	ENVIRONMENTAL CONDITIONS	26deg. C, 68%RH, 991hPa
TESTED BY	Kent Chen	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TEST MODE	B		

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.193	0.11	53.55	-	53.66	-	63.91	53.91	-10.25	-
2	0.388	0.12	45.54	-	45.66	-	58.10	48.10	-12.44	-
3	0.978	0.15	48.48	38.75	48.63	38.90	56.00	46.00	-7.37	-7.10
4	1.574	0.16	50.36	34.94	50.52	35.10	56.00	46.00	-5.48	-10.90
5	2.164	0.16	52.61	36.77	52.77	36.93	56.00	46.00	-3.23	-9.07
6	2.521	0.17	51.97	37.98	52.14	38.15	56.00	46.00	-3.86	-7.85

*(The test data is in accordance with ADT Report No.: RF930817L09.)

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.




EUT	Digital 4-line cordless phone system	MEASUREMENT DETAIL	
MODEL	SP-922	PHASE	Line 1
CHANNEL	Channel 25	6dB BANDWIDTH	9 kHz
MODULATION TYPE	MSK	ENVIRONMENTAL CONDITIONS	26deg. C, 68%RH, 991hPa
TESTED BY	Kent Chen	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TEST MODE	B		

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.194	0.12	49.96	-	50.08	-	63.85	53.85	-13.77	-
2	0.394	0.13	46.99	-	47.12	-	57.99	47.99	-10.87	-
3	0.970	0.15	47.44	39.63	47.59	39.78	56.00	46.00	-8.41	-6.22
4	1.570	0.16	48.61	36.28	48.77	36.44	56.00	46.00	-7.23	-9.56
5	2.164	0.16	52.00	37.80	52.16	37.96	56.00	46.00	-3.84	-8.04
6	2.535	0.17	48.19	34.74	48.36	34.91	56.00	46.00	-7.64	-11.09

*(The test data is in accordance with ADT Report No.: RF930817L09.)

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.




EUT	Digital 4-line cordless phone system	MEASUREMENT DETAIL	
MODEL	SP-922	PHASE	Line 2
CHANNEL	Channel 25	6dB BANDWIDTH	9 kHz
MODULATION TYPE	MSK	ENVIRONMENTAL CONDITIONS	26deg. C, 68%RH, 991hPa
TESTED BY	Kent Chen	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TEST MODE	B		

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.193	0.11	53.56	-	53.67	-	63.89	53.89	-10.22	-
2	0.392	0.12	46.75	-	46.87	-	58.02	48.02	-11.15	-
3	0.970	0.15	47.67	39.86	47.82	40.01	56.00	46.00	-8.18	-5.99
4	1.576	0.16	50.17	33.81	50.33	33.97	56.00	46.00	-5.67	-12.03
5	2.164	0.16	52.48	36.78	52.64	36.94	56.00	46.00	-3.36	-9.06
6	2.508	0.17	50.36	37.14	50.53	37.31	56.00	46.00	-5.47	-8.69

*(The test data is in accordance with ADT Report No.: RF930817L09.)

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.




EUT	Digital 4-line cordless phone system	MEASUREMENT DETAIL	
MODEL	SP-922	PHASE	Line 1
CHANNEL	Channel 50	6dB BANDWIDTH	9 kHz
MODULATION TYPE	MSK	ENVIRONMENTAL CONDITIONS	26deg. C, 68%RH, 991hPa
TESTED BY	Kent Chen	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TEST MODE	B		

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.197	0.12	49.92	-	50.04	-	63.74	53.74	-13.70	-
2	0.391	0.13	46.24	-	46.37	-	58.04	48.04	-11.68	-
3	0.975	0.15	47.42	38.38	47.57	38.53	56.00	46.00	-8.43	-7.47
4	1.566	0.16	47.98	35.25	48.14	35.41	56.00	46.00	-7.86	-10.59
5	2.160	0.16	50.80	37.08	50.96	37.24	56.00	46.00	-5.04	-8.76
6	2.508	0.17	50.62	36.43	50.79	36.60	56.00	46.00	-5.21	-9.40

*(The test data is in accordance with ADT Report No.: RF930817L09.)

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.




EUT	Digital 4-line cordless phone system	MEASUREMENT DETAIL	
MODEL	SP-922	PHASE	Line 2
CHANNEL	Channel 50	6dB BANDWIDTH	9 kHz
MODULATION TYPE	MSK	ENVIRONMENTAL CONDITIONS	26deg. C, 68%RH, 991hPa
TESTED BY	Kent Chen	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TEST MODE	B		

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.193	0.11	53.11	-	53.22	-	63.91	53.91	-10.69	-
2	0.384	0.12	45.15	-	45.27	-	58.18	48.18	-12.92	-
3	0.982	0.15	49.49	38.22	49.64	38.37	56.00	46.00	-6.36	-7.63
4	1.578	0.16	49.32	31.77	49.48	31.93	56.00	46.00	-6.52	-14.07
5	2.168	0.16	52.25	34.40	52.41	34.56	56.00	46.00	-3.59	-11.44
6	2.527	0.17	50.79	36.71	50.96	36.88	56.00	46.00	-5.04	-9.12

*(The test data is in accordance with ADT Report No.: RF930817L09.)

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



4.2 NUMBER OF HOPPING FREQUENCY USED

4.2.1 LIMIT OF HOPPING FREQUENCY USED

The system shall use at least 50 hopping frequencies.

4.2.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
SPECTRUM ANALYZER	FSEK30	100049	Aug. 12, 2005

NOTE:

The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to NML/ROC and NIST/USA.


4.2.3 TEST PROCEDURES

1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
2. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
3. Set the SA on MaxHold Mode, and then keep the EUT in hopping mode. Record all the signals from each channel until each one has been recorded.
4. Set the SA on View mode and then plot the result on SA screen.
5. Repeat above procedures until all frequencies measured were complete.

4.2.4 DEVIATION FROM TEST STANDARD


No deviation

4.2.5 TEST SETUP



4.2.6 TEST RESULTS

There are 50 hopping frequencies in the hopping mode. Please refer to following page for the test result. On the plots, it shows that the hopping frequencies are equally spaced.



4.3 DWELL TIME ON EACH CHANNEL

4.3.1 LIMIT OF DWELL TIME USED

The average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 20 second period.

4.3.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
SPECTRUM ANALYZER	FSEK30	100049	Aug. 12, 2005

NOTES:

The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to NML/ROC and NIST/USA.


4.3.3 TEST PROCEDURES

1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
2. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
3. Adjust the center frequency of SA on any frequency be measured and set SA to zero span mode. And then, set RBW and VBW of spectrum analyzer to proper value.
4. Measure the time duration of one transmission on the measured frequency. And then plot the result with time difference of this time duration.
5. Repeat above procedures until all frequencies measured were complete.

4.3.4 DEVIATION FROM TEST STANDARD

No deviation

4.3.5 TEST SETUP





4.3.6 TEST RESULTS

For Test Mode A (for cradle phone)

Number of transmission in a 20 (50Hopping*0.4)	Length of transmission time (msec)	Result (msec)	Limit (msec)
40 (times / 5 sec)	1.28	51.20	400

*(The test data is in accordance with ADT Report No.: RF930817L09.)

Test plots of the transmitting time slot are shown on the following 2 pages.



4.4 CHANNEL BANDWIDTH

4.4.1 LIMITS OF CHANNEL BANDWIDTH

The maximum allowed 20dB bandwidth of the hopping channel is 500kHz.

4.4.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
SPECTRUM ANALYZER	FSEK30	100049	Aug. 12, 2005

NOTES:

- 1.The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to NML/ROC and NIST/USA.


4.4.3 TEST PROCEDURE

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

4.4.4 DEVIATION FROM TEST STANDARD

No deviation

4.4.5 TEST SETUP



4.4.6 EUT OPERATING CONDITION



The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.


4.4.7 TEST RESULTS

EUT	Digital 4-line cordless phone system	MODEL	SP-922
INPUT POWER (SYSTEM)	120Vac, 60 Hz	MODULATION TYPE	MSK
ENVIRONMENTAL CONDITIONS	23deg. C, 65%RH, 991 hPa	TEST MODE	A
TESTED BY	Leo Hung		

CHANNEL	CHANNEL FREQUENCY (MHz)	20dB BANDWIDTH (kHz)	MAXIMUM LIMIT (kHz)	PASS/FAIL
1	902.5155	234.469	250	PASS
25	915.8654	240.481	250	PASS
50	927.5972	240.481	250	PASS

*(The test data is in accordance with ADT Report No.: RF930817L09.)

Channel 1**Channel 25**

Channel 50

4.5 HOPPING CHANNEL SEPARATION

4.5.1 LIMIT OF HOPPING CHANNEL SEPARATION

At least 25kHz or 20dB bandwidth (whichever is greater).

4.5.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
SPECTRUM ANALYZER	FSEK30	100049	Aug. 12, 2005

NOTES:

The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to NML/ROC and NIST/USA.


4.5.3 TEST PROCEDURES

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range.
3. By using the MaxHold function record the separation of two adjacent channels.
4. Measure the frequency difference of these two adjacent channels by SA MARK function. And then plot the result on SA screen.
5. Repeat above procedures until all frequencies measured were complete.

4.5.4 DEVIATION FROM TEST STANDARD

No deviation

4.5.5 TEST SETUP








4.5.6 TEST RESULTS

EUT	Digital 4-line cordless phone system	MODEL	SP-922
INPUT POWER (SYSTEM)	120Vac, 60 Hz	MODULATION TYPE	MSK
ENVIRONMENTAL CONDITIONS	23deg. C, 65%RH, 991 hPa	TEST MODE	A
TESTED BY	Leo Hung		

Channel	Frequency (MHz)	Adjacent Channel Separation	Minimum Limit (kHz)	Pass / Fail
1	902.5155	400.802kHz	279.559	PASS
25	915.8654	404.810kHz	270.541	PASS
50	927.5972	402.807kHz	276.553	PASS

*(The test data is in accordance with ADT Report No.: RF930817L09.)

Channel 1**Channel 25**

Channel 50

4.6 MAXIMUM PEAK OUTPUT POWER

4.6.1 LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT

The Maximum Peak Output Power Measurement is 30dBm.

4.6.2 INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
SPECTRUM ANALYSEER	FSEK30	100049	Aug. 12, 2005

NOTE: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.




4.6.3 TEST PROCEDURES

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. The center frequency of the spectrum analyzer is set to the fundamental frequency and using 3 MHz RBW and 3 MHz VBW.
4. Measure the frequency difference of two frequencies that were attenuated 20dB from the reference level. Record the frequency difference as the emission bandwidth.
5. Repeat above procedures until all frequencies measured were complete.

4.6.4 DEVIATION FROM TEST STANDARD

No deviation

4.6.5 TEST SETUP



For the actual test configuration, please refer to the related Item – Photographs of the Test Configuration.

4.6.6 EUT OPERATING CONDITION



The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.


4.6.7 TEST RESULTS

EUT	Digital 4-line cordless phone system	MODEL	SP-922
INPUT POWER (SYSTEM)	120Vac, 60 Hz	MODULATION TYPE	MSK
ENVIRONMENTAL CONDITIONS	23deg. C, 65%RH, 991 hPa	TEST MODE	A
TESTED BY	Leo Hung		

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (mW)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (dBm)	PASS/FAIL
1	902.5155	558.470	27.47	30	PASS
25	915.8654	587.489	27.69	30	PASS
50	927.5972	574.116	27.59	30	PASS

*(The test data is in accordance with ADT Report No.: RF930817L09.)

Channel 1**Channel 25**

Channel 50

4.7 RADIATED EMISSION MEASUREMENT

4.7.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209 as following:

Frequencies (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

4.7.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
Test Receiver ROHDE & SCHWARZ	ESI7	100033	Jun, 08, 2005
Spectrum Analyzer ROHDE & SCHWARZ	FSP40	100040	Dec. 15, 2004
BILOG Antenna SCHWARZBECK	VULB9168	9168-153	Feb. 03, 2005
HORN Antenna SCHWARZBECK	9120D	9120D-408	Feb. 03, 2005
HORN Antenna SCHWARZBECK	BBHA 9170	BBHA 9170243	Feb. 23, 2005
Preamplifier Agilent	8447D	2944A10633	Jan. 15, 2005
Preamplifier Agilent	8449B	3008A01964	Jan. 27, 2005
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	218183/4	Mar. 05, 2005
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	218195/4	Mar. 05, 2005
Software ADT.	ADT_Radiated_V5.14	NA	NA
Antenna Tower inn-co GmbH	MA 4000	013303	NA
Antenna Tower Controller inn-co GmbH	CO2000	017303	NA
Turn Table ADT.	TT100.	TT93021703	NA
Turn Table Controller ADT.	SC100.	SC93021703	NA

- NOTE:** 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in HwaYa Chamber 2.
3. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
4. The IC Site Registration No. is IC4924-3.

4.7.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10 dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.


NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Peak detection (PK) and Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz for Peak detection at frequency above 1GHz.

4.7.4 DEVIATION FROM TEST STANDARD

No deviation

4.7.5 TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

4.7.6 EUT OPERATING CONDITIONS

Same as 4.1.6

4.7.7 TEST RESULTS

Below 1GHz Worst-Case Data (The Phone + Cradle with charger function)

EUT	Digital 4-line cordless phone system	MEASUREMENT DETAIL	
MODEL	SP-922	FREQUENCY RANGE	Below 1000MHz
CHANNEL	Channel 50	DETECTOR FUNCTION	Quasi-Peak
MODULATION TYPE	MSK	ENVIRONMENTAL CONDITIONS	25 deg. C, 58% RH, 991 hPa
TESTED BY	Long Chen	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TEST MODE	A		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	45.55	28.44 QP	40.00	-11.56	2.00 H	46	12.53	15.91
2	127.19	26.74 QP	43.50	-16.76	3.00 H	115	13.43	13.31
3	232.16	25.63 QP	46.00	-20.37	1.50 H	289	12.89	12.74
4	393.51	29.09 QP	46.00	-16.91	1.00 H	61	12.27	16.82
5	589.84	25.63 QP	46.00	-20.37	1.50 H	199	4.67	20.96
6	677.31	26.35 QP	46.00	-19.65	1.00 H	70	4.09	22.25
7	902.81	27.49 QP	46.00	-18.51	4.00 H	295	2.22	25.27
8	943.63	28.12 QP	46.00	-17.88	1.50 H	220	2.37	25.75

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	45.55	25.43 QP	40.00	-14.57	1.00 V	214	9.53	15.91
2	131.08	20.79 QP	43.50	-22.71	1.00 V	58	7.24	13.55
3	393.51	26.50 QP	46.00	-19.50	1.00 V	76	9.69	16.82
4	673.43	28.64 QP	46.00	-17.36	1.50 V	97	6.43	22.21
5	712.30	28.87 QP	46.00	-17.13	1.50 V	304	6.07	22.80
6	786.17	28.58 QP	46.00	-17.42	1.50 V	169	4.84	23.75
7	914.47	36.81 QP	46.00	-9.19	1.50 V	298	11.40	25.41
8	955.29	26.52 QP	46.00	-19.48	1.00 V	265	0.68	25.85

*(The test data is in accordance with ADT Report No.: RF930817L09.)

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.

Below 1GHz Worst-Case Data (The Phone + Earphone only with charger function)

EUT	Digital 4-line cordless phone system	MEASUREMENT DETAIL	
MODEL	SP-922	FREQUENCY RANGE	Below 1000MHz
CHANNEL	Channel 50	DETECTOR FUNCTION	Quasi-Peak
MODULATION TYPE	MSK	ENVIRONMENTAL CONDITIONS	25 deg. C, 58% RH, 991 hPa
TESTED BY	Long Chen	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TEST MODE	B	AXIS	X

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	35.83	28.22 QP	40.00	-11.78	1.50 H	46	13.10	15.12
2	78.60	36.63 QP	40.00	-3.37	2.00 H	181	25.79	10.85
3	193.29	35.38 QP	43.50	-8.12	1.50 H	136	23.41	11.97
4	307.98	39.03 QP	46.00	-6.97	1.00 H	127	24.05	14.98
5	393.23	42.55 QP	46.00	-3.45	1.00 H	27	25.74	16.81
6	488.76	33.72 QP	46.00	-12.28	1.50 H	118	15.14	18.58
7	589.84	38.44 QP	46.00	-7.56	1.00 H	115	17.48	20.96

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	33.89	31.59 QP	40.00	-8.41	1.00 V	127	16.78	14.81
2	78.60	23.44 QP	40.00	-16.56	2.50 V	103	12.60	10.85
3	193.29	19.34 QP	43.50	-24.16	1.50 V	43	7.36	11.97
4	393.51	25.98 QP	46.00	-20.02	2.00 V	106	9.16	16.82
5	488.76	18.44 QP	46.00	-27.56	1.50 V	64	-0.14	18.58
6	589.84	23.75 QP	46.00	-22.25	1.00 V	85	2.80	20.96
7	737.58	22.05 QP	46.00	-23.95	1.50 V	43	-1.34	23.39

*(The test data is in accordance with ADT Report No.: RF930817L09.)

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.

EUT	Digital 4-line cordless phone system	MEASUREMENT DETAIL	
MODEL	SP-922	FREQUENCY RANGE	Below 1000MHz
CHANNEL	Channel 50	DETECTOR FUNCTION	Quasi-Peak
MODULATION TYPE	MSK	ENVIRONMENTAL CONDITIONS	25 deg. C, 58% RH, 991 hPa
TESTED BY	Long Chen	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TEST MODE	B	AXIS	Y

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	82.48	34.65 QP	40.00	-5.35	2.00 H	340	24.72	9.92
2	193.29	37.68 QP	43.50	-5.82	1.50 H	271	25.87	11.82
3	317.70	39.42 QP	46.00	-6.58	1.00 H	253	24.62	14.80
4	393.51	37.69 QP	46.00	-8.31	2.00 H	310	21.12	16.57
5	434.33	33.40 QP	46.00	-12.60	2.00 H	298	15.80	17.60
6	589.84	35.50 QP	46.00	-10.50	1.50 H	307	14.95	20.55
7	712.30	34.21 QP	46.00	-11.79	1.00 H	289	11.90	22.31
8	737.58	35.26 QP	46.00	-10.74	1.00 H	319	12.33	22.93
9	786.17	32.14 QP	46.00	-13.86	1.00 H	322	8.74	23.40

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	35.83	37.66 QP	40.00	-2.34	1.00 V	313	22.99	14.67
2	82.48	34.00 QP	40.00	-6.00	2.00 V	298	24.07	9.92
3	193.29	32.21 QP	43.50	-11.29	1.00 V	319	20.39	11.82
4	317.70	31.80 QP	46.00	-14.20	1.00 V	58	17.00	14.80
5	393.51	35.46 QP	46.00	-10.54	1.00 V	286	18.89	16.57
6	589.84	31.15 QP	46.00	-14.85	1.50 V	202	10.60	20.55
7	657.88	29.04 QP	46.00	-16.96	1.50 V	349	7.48	21.56
8	712.30	28.26 QP	46.00	-17.74	1.00 V	4	5.94	22.31

*(The test data is in accordance with ADT Report No.: RF930817L09.)

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.

EUT	Digital 4-line cordless phone system	MEASUREMENT DETAIL	
MODEL	SP-922	FREQUENCY RANGE	Below 1000MHz
CHANNEL	Channel 50	DETECTOR FUNCTION	Quasi-Peak
MODULATION TYPE	MSK	ENVIRONMENTAL CONDITIONS	25 deg. C, 58% RH, 991 hPa
TESTED BY	Long Chen	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TEST MODE	B	AXIS	Z

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	35.83	29.79 QP	40.00	-10.21	2.00 H	304	15.12	14.67
2	82.48	34.33 QP	40.00	-5.67	4.00 H	193	24.40	9.92
3	193.29	36.77 QP	43.50	-6.73	1.50 H	289	24.96	11.82
4	321.58	39.78 QP	46.00	-6.22	1.00 H	244	24.89	14.89
5	393.51	35.00 QP	46.00	-11.00	2.00 H	238	18.43	16.57
6	434.33	33.69 QP	46.00	-12.31	2.00 H	295	16.08	17.60
7	589.84	34.59 QP	46.00	-11.41	1.00 H	256	14.04	20.55
8	657.88	31.73 QP	46.00	-14.27	1.00 H	10	10.18	21.56
9	737.58	33.69 QP	46.00	-12.31	1.00 H	295	10.76	22.93

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	35.83	37.07 QP	40.00	-2.93	1.00 V	250	22.41	14.67
2	82.48	33.74 QP	40.00	-6.26	2.00 V	298	23.82	9.92
3	193.29	33.94 QP	43.50	-9.56	1.00 V	301	22.13	11.82
4	317.70	33.59 QP	46.00	-12.41	1.00 V	304	18.79	14.80
5	393.51	35.68 QP	46.00	-10.32	1.00 V	301	19.11	16.57
6	434.33	31.40 QP	46.00	-14.60	1.00 V	286	13.80	17.60
7	589.84	31.24 QP	46.00	-14.76	1.00 V	130	10.69	20.55
8	737.58	30.60 QP	46.00	-15.40	1.50 V	205	7.67	22.93

*(The test data is in accordance with ADT Report No.: RF930817L09.)

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.

EUT	Digital 4-line cordless phone system	MEASUREMENT DETAIL	
MODEL	SP-922	FREQUENCY RANGE	1~25 GHz
CHANNEL	Channel 1	DETECTOR FUNCTION	Peak (PK) Average (AV)
MODULATION TYPE	MSK	ENVIRONMENTAL CONDITIONS	25 deg. C, 60% RH, 991 hPa
TESTED BY	Long Chen	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TEST MODE	B	AXIS	X

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*902.27	125.56 PK			1.00 H	122	100.29	25.27
1	*902.27	122.71 AV			1.00 H	122	97.44	25.27

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*902.27	123.81 PK			1.58 V	237	98.54	25.27
1	*902.27	121.85 AV			1.58 V	237	96.58	25.27

*(The test data is in accordance with ADT Report No.: RF930817L09.)

REMARKS:

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * ” : Fundamental frequency

EUT	Digital 4-line cordless phone system	MEASUREMENT DETAIL	
MODEL	SP-922	FREQUENCY RANGE	1~25 GHz
CHANNEL	Channel 1	DETECTOR FUNCTION	Peak (PK) Average (AV)
MODULATION TYPE	MSK	ENVIRONMENTAL CONDITIONS	25 deg. C, 60% RH, 991 hPa
TESTED BY	Long Chen	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TEST MODE	B	AXIS	Y

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*902.27	124.50 PK			1.61 H	23	99.23	25.27
1	*902.27	121.80 AV			1.61 H	23	96.53	25.27

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*902.27	122.92 PK			1.61 V	2	97.65	25.27
1	*902.27	120.73 AV			1.61 V	2	95.46	25.27

*(The test data is in accordance with ADT Report No.: RF930817L09.)

REMARKS:

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * ” : Fundamental frequency

EUT	Digital 4-line cordless phone system	MEASUREMENT DETAIL	
MODEL	SP-922	FREQUENCY RANGE	1~25 GHz
CHANNEL	Channel 1	DETECTOR FUNCTION	Peak (PK) Average (AV)
MODULATION TYPE	MSK	ENVIRONMENTAL CONDITIONS	25 deg. C, 60% RH, 991 hPa
TESTED BY	Long Chen	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TEST MODE	B	AXIS	Z

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*902.27	119.51 PK			1.28 H	319	94.24	25.27
1	*902.27	117.20 AV			1.28 H	319	91.93	25.27

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*902.27	123.92 PK			1.58 V	237	98.65	25.27
1	*902.27	121.15 AV			1.58 V	237	95.88	25.27

*(The test data is in accordance with ADT Report No.: RF930817L09.)

REMARKS:

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * ” : Fundamental frequency

EUT	Digital 4-line cordless phone system	MEASUREMENT DETAIL	
MODEL	SP-922	FREQUENCY RANGE	1~25 GHz
CHANNEL	Channel 25	DETECTOR FUNCTION	Peak (PK) Average (AV)
MODULATION TYPE	MSK	ENVIRONMENTAL CONDITIONS	25 deg. C, 60% RH, 991 hPa
TESTED BY	Long Chen	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TEST MODE	B	AXIS	X

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*915.19	126.73 PK			1.00 H	148	101.31	25.42
1	*915.19	123.85 AV			1.00 H	148	98.43	25.42

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*915.19	123.62 PK			1.52 V	248	98.20	25.42
1	*915.19	121.53 AV			1.52 V	248	96.11	25.42

*(The test data is in accordance with ADT Report No.: RF930817L09.)

REMARKS:

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * ” : Fundamental frequency

EUT	Digital 4-line cordless phone system	MEASUREMENT DETAIL	
MODEL	SP-922	FREQUENCY RANGE	1~25 GHz
CHANNEL	Channel 25	DETECTOR FUNCTION	Peak (PK) Average (AV)
MODULATION TYPE	MSK	ENVIRONMENTAL CONDITIONS	25 deg. C, 60% RH, 991 hPa
TESTED BY	Long Chen	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TEST MODE	B	AXIS	Y

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*915.19	124.85 PK			1.62 H	28	99.43	25.42
1	*915.19	122.36 AV			1.62 H	28	96.94	25.42

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*915.19	122.74 PK			1.68 V	354	97.32	25.42
1	*915.19	120.12 AV			1.68 V	354	94.70	25.42

*(The test data is in accordance with ADT Report No.: RF930817L09.)

REMARKS:

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * ” : Fundamental frequency

EUT	Digital 4-line cordless phone system	MEASUREMENT DETAIL	
MODEL	SP-922	FREQUENCY RANGE	1~25 GHz
CHANNEL	Channel 25	DETECTOR FUNCTION	Peak (PK) Average (AV)
MODULATION TYPE	MSK	ENVIRONMENTAL CONDITIONS	25 deg. C, 60% RH, 991 hPa
TESTED BY	Long Chen	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TEST MODE	B	AXIS	Z

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*915.19	119.20 PK			1.24 H	289	93.78	25.42
1	*915.19	116.13 AV			1.24 H	289	90.71	25.42

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*915.19	124.82 PK			1.72 V	248	99.40	25.42
1	*915.19	121.94 AV			1.72 V	248	96.52	25.42

*(The test data is in accordance with ADT Report No.: RF930817L09.)

REMARKS:

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * ” : Fundamental frequency

EUT	Digital 4-line cordless phone system	MEASUREMENT DETAIL	
MODEL	SP-922	FREQUENCY RANGE	1~25 GHz
CHANNEL	Channel 50	DETECTOR FUNCTION	Peak (PK) Average (AV)
MODULATION TYPE	MSK	ENVIRONMENTAL CONDITIONS	25 deg. C, 60% RH, 991 hPa
TESTED BY	Long Chen	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TEST MODE	B	AXIS	X

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*927.84	124.25 PK			1.05 H	124	98.69	25.56
1	*927.84	121.94 AV			1.05 H	124	96.38	25.56

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*927.84	122.43 PK			1.50 V	215	96.87	25.56
1	*927.84	120.71 AV			1.50 V	215	95.15	25.56

*(The test data is in accordance with ADT Report No.: RF930817L09.)

REMARKS:

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * ” : Fundamental frequency

EUT	Digital 4-line cordless phone system	MEASUREMENT DETAIL	
MODEL	SP-922	FREQUENCY RANGE	1~25 GHz
CHANNEL	Channel 50	DETECTOR FUNCTION	Peak (PK) Average (AV)
MODULATION TYPE	MSK	ENVIRONMENTAL CONDITIONS	25 deg. C, 60% RH, 991 hPa
TESTED BY	Long Chen	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TEST MODE	B	AXIS	Y

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*927.84	123.42 PK			1.17 H	148	97.86	25.56
1	*927.84	121.24 AV			1.17 H	148	95.68	25.56

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*927.84	122.01 PK			1.48 V	229	96.45	25.56
1	*927.84	119.24 AV			1.48 V	229	93.68	25.56

*(The test data is in accordance with ADT Report No.: RF930817L09.)

REMARKS:

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * ” : Fundamental frequency

EUT	Digital 4-line cordless phone system	MEASUREMENT DETAIL	
MODEL	SP-922	FREQUENCY RANGE	1~25 GHz
CHANNEL	Channel 50	DETECTOR FUNCTION	Peak (PK) Average (AV)
MODULATION TYPE	MSK	ENVIRONMENTAL CONDITIONS	25 deg. C, 60% RH, 991 hPa
TESTED BY	Long Chen	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TEST MODE	B	AXIS	Z

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*927.84	121.42 PK			1.13 H	269	95.86	25.56
1	*927.84	119.10 AV			1.13 H	269	93.54	25.56

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*927.84	123.05 PK			1.33 V	187	97.49	25.56
1	*927.84	119.11 AV			1.33 V	187	93.55	25.56

*(The test data is in accordance with ADT Report No.: RF930817L09.)

REMARKS:

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * ” : Fundamental frequency

EUT	Digital 4-line cordless phone system	MEASUREMENT DETAIL	
MODEL	SP-922	FREQUENCY RANGE	1~25 GHz
CHANNEL	Channel 1	DETECTOR FUNCTION	Peak (PK) Average (AV)
MODULATION TYPE	MSK	ENVIRONMENTAL CONDITIONS	25 deg. C, 60% RH, 991 hPa
TESTED BY	Long Chen	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TEST MODE	B	AXIS	X

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1804.00	49.88 PK	74.00	-24.12	1.07 H	79	21.08	28.79
2	2706.00	46.93 PK	74.00	-27.07	1.82 H	81	14.18	32.75
3	3608.00	49.32 PK	74.00	-24.68	1.00 H	241	14.52	34.80
4	4510.00	49.62 PK	74.00	-24.38	1.53 H	114	12.61	37.01
5	5412.00	56.95 PK	74.00	-17.05	1.03 H	169	18.43	38.52
5	5412.00	49.84 AV	54.00	-4.16	1.03 H	169	11.32	38.52

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1804.00	46.90 PK	74.00	-27.10	1.00 V	89	18.10	28.79
2	2706.00	44.88 PK	74.00	-29.12	1.69 V	292	12.13	32.75
3	3608.00	47.77 PK	74.00	-26.23	1.00 V	102	12.97	34.80
4	4510.00	47.21 PK	74.00	-26.79	1.24 V	348	10.20	37.01
5	5412.00	54.00 PK	74.00	-20.00	1.02 V	352	15.48	38.52
5	5412.00	47.84 AV	54.00	-6.16	1.02 V	352	9.32	38.52

*(The test data is in accordance with ADT Report No.: RF930817L09.)

REMARKS:

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.

EUT	Digital 4-line cordless phone system	MEASUREMENT DETAIL	
MODEL	SP-922	FREQUENCY RANGE	1~25 GHz
CHANNEL	Channel 1	DETECTOR FUNCTION	Peak (PK) Average (AV)
MODULATION TYPE	MSK	ENVIRONMENTAL CONDITIONS	25 deg. C, 60% RH, 991 hPa
TESTED BY	Long Chen	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TEST MODE	B	AXIS	Z

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1804.00	49.76 PK	74.00	-24.24	1.29 H	296	20.97	28.79
2	2706.00	43.58 PK	74.00	-30.42	1.24 H	147	10.83	32.75
3	3608.00	46.29 PK	74.00	-27.71	1.42 H	229	11.49	34.80
4	4510.00	46.81 PK	74.00	-27.19	1.16 H	285	9.80	37.01
5	5412.00	51.28 PK	74.00	-22.72	1.24 H	358	12.76	38.52
5	5412.00	40.92 AV	54.00	-13.08	1.24 H	358	2.40	38.52

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1804.00	54.34 PK	74.00	-19.66	1.08 V	56	25.55	28.79
1	1804.00	50.29 AV	54.00	-3.71	1.08 V	56	21.50	28.79
2	2706.00	46.92 PK	74.00	-27.08	1.18 V	246	14.17	32.75
3	3608.00	47.89 PK	74.00	-26.11	1.14 V	142	13.09	34.80
4	4510.00	48.58 PK	74.00	-25.42	1.32 V	338	11.57	37.01
5	5412.00	53.54 PK	74.00	-20.46	1.22 V	301	15.02	38.52
5	5412.00	46.10 AV	54.00	-7.90	1.22 V	301	7.58	38.52

*(The test data is in accordance with ADT Report No.: RF930817L09.)

REMARKS:

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.

EUT	Digital 4-line cordless phone system	MEASUREMENT DETAIL	
MODEL	SP-922	FREQUENCY RANGE	1~25 GHz
CHANNEL	Channel 25	DETECTOR FUNCTION	Peak (PK) Average (AV)
MODULATION TYPE	MSK	ENVIRONMENTAL CONDITIONS	25 deg. C, 60% RH, 991 hPa
TESTED BY	Long Chen	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TEST MODE	B	AXIS	X

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1830.00	51.41 PK	74.00	-22.59	1.07 H	125	22.52	28.89
1	1830.00	48.93 AV	54.00	-5.07	1.07 H	125	20.04	28.89
2	2744.40	45.21 PK	74.00	-28.79	1.00 H	135	12.34	32.87
3	3659.50	48.95 PK	74.00	-25.05	1.12 H	258	14.02	34.93
4	4574.40	48.91 PK	74.00	-25.09	1.22 H	341	11.79	37.12
5	5489.20	54.53 PK	74.00	-19.47	1.00 H	41	15.72	38.81
5	5489.20	48.42 AV	54.00	-5.58	1.00 H	41	9.61	38.81

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1829.70	49.57 PK	74.00	-24.43	1.00 V	80	20.68	28.89
2	2744.40	43.88 PK	74.00	-30.12	1.12 V	287	11.01	32.87
3	3659.50	46.51 PK	74.00	-27.49	1.25 V	118	11.58	34.93
4	4574.40	46.85 PK	74.00	-27.15	1.18 V	339	9.73	37.12
5	5489.20	53.71 PK	74.00	-20.29	1.05 V	338	14.90	38.81
5	5489.20	46.58 AV	54.00	-7.42	1.05 V	338	7.77	38.81

*(The test data is in accordance with ADT Report No.: RF930817L09.)

REMARKS:

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.

EUT	Digital 4-line cordless phone system	MEASUREMENT DETAIL	
MODEL	SP-922	FREQUENCY RANGE	1~25 GHz
CHANNEL	Channel 25	DETECTOR FUNCTION	Peak (PK) Average (AV)
MODULATION TYPE	MSK	ENVIRONMENTAL CONDITIONS	25 deg. C, 60% RH, 991 hPa
TESTED BY	Long Chen	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TEST MODE	B	AXIS	Y

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1829.00	60.40 PK	103.42	-43.02	1.07 H	226	31.51	28.88
1	1829.00	57.09 AV	101.24	-44.15	1.07 H	226	28.20	28.88
2	2744.50	50.17 PK	74.00	-23.83	1.12 H	64	17.30	32.87
3	3659.30	47.79 PK	74.00	-26.21	1.00 H	287	12.86	34.93
4	4574.10	49.03 PK	74.00	-24.97	1.29 H	224	11.91	37.12
5	5489.30	52.83 PK	74.00	-21.17	1.00 H	78	14.02	38.81
5	5489.30	43.71 AV	54.00	-10.29	1.00 H	78	4.90	38.81

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1829.70	56.20 PK	102.01	-45.81	1.00 V	207	27.31	28.89
1	1829.70	54.40 AV	99.24	-44.84	1.00 V	207	27.31	28.89
2	2744.50	47.19 PK	74.00	-26.81	1.01 V	231	14.32	32.87
3	3659.30	46.16 PK	74.00	-27.84	1.24 V	228	11.23	34.93
4	4574.10	47.99 PK	74.00	-26.01	1.42 V	228	10.87	37.12
5	5489.30	50.45 PK	74.00	-23.55	1.00 V	78	11.64	38.81

*(The test data is in accordance with ADT Report No.: RF930817L09.)

REMARKS:

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.

EUT	Digital 4-line cordless phone system	MEASUREMENT DETAIL	
MODEL	SP-922	FREQUENCY RANGE	1~25 GHz
CHANNEL	Channel 25	DETECTOR FUNCTION	Peak (PK) Average (AV)
MODULATION TYPE	MSK	ENVIRONMENTAL CONDITIONS	25 deg. C, 60% RH, 991 hPa
TESTED BY	Long Chen	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TEST MODE	B	AXIS	Z

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1830.00	50.03 PK	74.00	-23.97	1.00 H	306	21.14	28.89
2	2744.40	43.82 PK	74.00	-30.18	1.22 H	142	10.95	32.87
3	3659.80	45.79 PK	74.00	-28.21	1.15 H	281	10.86	34.93
4	4574.60	46.89 PK	74.00	-27.11	1.24 H	114	9.77	37.12
5	5489.20	51.32 PK	74.00	-22.68	1.11 H	19	12.51	38.81
5	5489.20	41.51 AV	54.00	-12.49	1.11 H	19	2.70	38.81

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1830.00	51.94 PK	74.00	-22.06	1.07 V	53	23.05	28.89
1	1830.00	49.90 AV	54.00	-4.10	1.07 V	53	21.01	28.89
2	2744.40	45.67 PK	74.00	-28.33	1.35 V	7	12.80	32.87
3	3659.80	48.62 PK	74.00	-25.38	1.06 V	114	13.69	34.93
4	4574.60	48.76 PK	74.00	-25.24	1.42 V	305	11.64	37.12
5	5489.20	53.51 PK	74.00	-20.49	1.13 V	307	14.70	38.81
5	5489.20	45.28 AV	54.00	-8.72	1.13 V	307	6.47	38.81

*(The test data is in accordance with ADT Report No.: RF930817L09.)

REMARKS:

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.

EUT	Digital 4-line cordless phone system	MEASUREMENT DETAIL	
MODEL	SP-922	FREQUENCY RANGE	1~25 GHz
CHANNEL	Channel 50	DETECTOR FUNCTION	Peak (PK) Average (AV)
MODULATION TYPE	MSK	ENVIRONMENTAL CONDITIONS	25 deg. C, 60% RH, 991 hPa
TESTED BY	Long Chen	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TEST MODE	B	AXIS	X

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1855.20	52.91 PK	74.00	-21.09	1.05 H	56	23.93	28.98
1	1855.20	50.94 AV	54.00	-3.06	1.05 H	56	21.96	28.98
2	2782.80	46.51 PK	74.00	-27.49	1.00 H	133	13.52	32.99
3	3710.40	48.75 PK	74.00	-25.25	1.14 H	229	13.73	35.02
4	4638.00	49.62 PK	74.00	-24.38	1.42 H	338	12.37	37.25
5	5565.60	54.87 PK	74.00	-19.13	1.13 H	28	15.97	38.90
5	5565.60	47.82 AV	54.00	-6.18	1.13 H	28	8.92	38.90

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1855.20	49.18 PK	74.00	-24.82	1.00 V	78	20.20	28.98
2	2784.30	44.38 PK	74.00	-29.62	1.10 V	287	11.39	32.99
3	3710.40	46.25 PK	74.00	-27.75	1.12 V	125	11.23	35.02
4	4638.00	46.78 PK	74.00	-27.22	1.42 V	352	9.53	37.25
5	5565.60	52.18 PK	74.00	-21.82	1.04 V	345	13.28	38.90
5	5565.60	45.27 AV	54.00	-8.73	1.04 V	345	6.37	38.90

*(The test data is in accordance with ADT Report No.: RF930817L09.)

REMARKS:

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.

EUT	Digital 4-line cordless phone system	MEASUREMENT DETAIL	
MODEL	SP-922	FREQUENCY RANGE	1~25 GHz
CHANNEL	Channel 50	DETECTOR FUNCTION	Peak (PK) Average (AV)
MODULATION TYPE	MSK	ENVIRONMENTAL CONDITIONS	25 deg. C, 60% RH, 991 hPa
TESTED BY	Long Chen	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TEST MODE	B	AXIS	Y

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1855.00	59.37 PK	103.42	-44.05	1.03 H	220	28.51	30.85
1	1855.00	57.80 AV	101.24	-43.44	1.03 H	220	28.51	30.85
2	2782.00	46.61 PK	74.00	-27.39	1.09 H	211	11.52	35.09
3	3710.00	48.09 PK	74.00	-25.91	1.38 H	274	10.56	37.52
4	4638.00	49.57 PK	74.00	-24.43	1.54 H	262	9.53	40.05
5	5565.00	54.63 PK	74.00	-19.37	1.00 H	335	12.28	42.35
5	5565.00	42.77 AV	54.00	-11.23	1.00 H	335	0.42	42.35

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1855.00	69.20 PK	102.01	-32.81	1.00 V	256	38.34	30.85
1	1855.00	68.24 AV	99.24	-31.00	1.00 V	256	38.34	30.85
2	2782.00	46.80 PK	74.00	-27.20	1.00 V	178	11.71	35.09
3	3710.00	48.71 PK	74.00	-25.29	1.46 V	17	11.18	37.52
4	4638.00	49.78 PK	74.00	-24.22	1.02 V	15	9.74	40.05
5	5565.00	51.91 PK	74.00	-22.09	1.00 V	20	9.56	42.35
5	5565.00	37.87 AV	54.00	-16.13	1.00 V	20	-4.48	42.35

*(The test data is in accordance with ADT Report No.: RF930817L09.)

REMARKS:

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.

EUT	Digital 4-line cordless phone system	MEASUREMENT DETAIL	
MODEL	SP-922	FREQUENCY RANGE	1~25 GHz
CHANNEL	Channel 50	DETECTOR FUNCTION	Peak (PK) Average (AV)
MODULATION TYPE	MSK	ENVIRONMENTAL CONDITIONS	25 deg. C, 60% RH, 991 hPa
TESTED BY	Long Chen	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TEST MODE	B	AXIS	Z

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1855.20	51.06 PK	74.00	-22.94	1.02 H	10	22.08	28.98
1	1855.20	49.78 AV	54.00	-4.22	1.02 H	10	20.80	28.98
2	2782.80	44.28 PK	74.00	-29.72	1.48 H	116	11.29	32.99
3	3710.40	45.38 PK	74.00	-28.62	1.14 H	262	10.36	35.02
4	4638.00	46.62 PK	74.00	-27.38	1.00 H	229	9.37	37.25
5	5565.60	51.41 PK	74.00	-22.59	1.14 H	294	12.51	38.90
5	5565.60	38.57 AV	54.00	-15.43	1.14 H	294	-0.33	38.90

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1855.20	52.76 PK	74.00	-21.24	1.36 V	104	23.78	28.98
1	1855.20	51.14 AV	54.00	-2.86	1.36 V	104	22.16	28.98
2	2782.80	46.32 PK	74.00	-27.68	1.81 V	324	13.33	32.99
3	3710.40	47.62 PK	74.00	-26.38	1.04 V	30	12.60	35.02
4	4638.00	48.95 PK	74.00	-25.05	1.12 V	328	11.70	37.25
5	5565.60	53.07 PK	74.00	-20.93	1.04 V	10	14.17	38.90
5	5565.60	44.49 AV	54.00	-9.51	1.04 V	10	5.59	38.90

*(The test data is in accordance with ADT Report No.: RF930817L09.)

REMARKS:

6. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
7. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
8. The other emission levels were very low against the limit.
9. Margin value = Emission level – Limit value.

4.8 BAND EDGES MEASUREMENT

4.8.1 LIMITS OF BAND EDGES MEASUREMENT

Below -20dB of the highest emission level of operating band (in 100KHz RBW).

4.8.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
SPECTRUM ANALYZER	FSEK30	100049	Aug. 12, 2005

NOTES:

The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to NML/ROC and NIST/USA.

4.8.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer via a low loss cable. Set both RBW and VBW of spectrum analyzer to 100 kHz with suitable frequency span including 100 MHz bandwidth from band edge. The band edges were measured and recorded.

4.8.4 DEVIATION FROM TEST STANDARD

No deviation

4.8.5 EUT OPERATING CONDITION

The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.

4.8.6 TEST RESULTS

The spectrum plots are attached on the following 8 images. D2 line indicates the highest level, D1 line indicates the 20dB offset below D2. It shows compliance with the requirement in part 15.247(d).

MSK modulation

Test Mode B:



NOTE 1: The band edge emission plot on page 79 show 49.54dBc delta between carrier maximum power and local maximum emission in band edge (902.00GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.7.7 is 124.50dBuV/m (Peak), so the maximum field strength in restrict band is $124.50 - 49.54 = 74.96$ dBuV/m which is under the 20dB of Fundamental frequency.



The band edge emission plot on page 79 show 42.38dBc delta between carrier maximum power and local maximum emission in band edge (928.00GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.7.7 is 122.71dBuV/m (Average), so the maximum field strength in restrict band is $122.71 - 42.38 = 80.33$ dBuV/m which is under the 20dB of Fundamental frequency.

NOTE 2: The band edge emission plot on the page 80 show 49.54dBc delta between carrier maximum power and local maximum emission in band edge (902.00GHz). The emission of carrier strength list in the test result of channel 50 at the item 4.7.7 is 124.25dBuV/m (Peak), so the maximum field strength in band edge is $124.25 - 49.54 = 74.71$ dBuV/m which is under the 20dB of Fundamental frequency.

The band edge emission plot on the page 80 show 42.38dBc delta between carrier maximum power and local maximum emission in band edge (928.00GHz). The emission of carrier strength list in the test result of channel 50 at the item 4.7.7 is 121.94dBuV/m (Average), so the maximum field strength in restrict band is $121.94 - 42.38 = 79.56$ dBuV/m which is under the 20dB of Fundamental frequency.

*(The test data is in accordance with ADT Report No.: RF930817L09.)







4.9 ANTENNA REQUIREMENT

4.9.1 STANDARD APPLICABLE

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

4.9.2 ANTENNA CONNECTED CONSTRUCTION

The antenna used in this product is Dipole Antenna with Reverse TNC/SMA antenna connector. The maximum Gain of this antenna is only 2.0dBi.

5 PHOTOGRAPHS OF THE TEST CONFIGURATION



CONDUCTED EMISSION TEST (Test Mode A)




(Test Mode B)



RADIATED EMISSION TEST
(Test Mode A)



(Test Mode B)



6 INFORMATION ON THE TESTING LABORATORIES

We, ADT Corp., were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025.

USA	FCC, NVLAP, UL, A2LA
Germany	TUV Rheinland
Japan	VCCI
Norway	NEMKO
Canada	INDUSTRY CANADA , CSA
R.O.C.	CNLA, BSMI, DGT
Netherlands	Telefication
Singapore	PSB , GOST-ASIA(MOU)
Russia	CERTIS(MOU)

Copies of accreditation certificates of our laboratories obtained from approval agencies can be downloaded from our web site:

www.adt.com.tw/index.5/phtml. If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab:

Tel: 886-2-26052180

Fax: 886-2-26052943

Hsin Chu EMC/RF Lab:

Tel: 886-3-5935343

Fax: 886-3-5935342

Hwa Ya EMC/RF/Safety/Telecom Lab:

Tel: 886-3-3183232

Fax: 886-3-3185050

Linko RF Lab.

Tel: 886-3-3270910

Fax: 886-3-3270892

Web Site: www.adt.com.tw

The address and road map of all our labs can be found in our web site also.