



Wintecronics Co., Ltd.

2F, No.7-1, Ming Lee Street, Chung Ho City, Taipei Hsien, 236, Taiwan

Tel: 886-2-22496046 Fax: 886-2-22496172

Web-site: <http://www.wintec.com.tw> E-mail: wintec@ptle5.seed.net.tw

L520BFA Operational Description

The 2 way pager is a low-powered transmitter device used in monitoring the automobile security status as well as in remotely arming/disarming car security system and other optional features. Its features and functions are described in the separate attached sheet.

The transmission is powered by DC 5 V and works on 433.92 Mhz single fixed frequency. Details of circuit diagram and its block diagram are shown on the attached sheets.

The automobile's sensor will trigger the digital control signals and modulate the carrier signal. The carrier signal is generated by a crystal oscillator/amplifier circuit of a 434 MH crystal and a npn transmitter. The modulated output of the RF amplifier stage is coupled to the coil.

All the tuning and verification are done by manufacturer during the production process and no adjustment is allowed by any consumer. No external ground is needed in such device.

The transmitter is manually operated by the buttons pushed and will automatically deactivate within 3 seconds after the button being released. This feature is incorporated by the Crystal (Undersurface 48.2133MHz) internally.

All tuning and verification are performed by the manufacture and there are no adjustments can be made by the user. No external ground is required or used with this transmitter.