



NVLAP LAB CODE 200707-0



## FCC PART 15D

### MEASUREMENT AND TEST REPORT

For

**MACKARL ENTERPRISES INC.**

16960 Gale Ave., City of Industry,  
CA 91745, USA

**FCC ID: NK63123X**

<b>Report Type:</b> Original Report	<b>Product Type:</b> DECT 6.0 Cordless Phone(Handset)
<b>Test Engineer:</b> <u>Bruce Zhang</u> <i>Bruce Zhang</i>	
<b>Report Number:</b> <u>RSZ09100903-Handset</u>	
<b>Report Date:</b> <u>2009-11-11</u>	
<b>Reviewed By:</b> <u>EMC Engineer</u> <i>Merry Zhao</i> <i>Merry, Zhao</i>	
<b>Prepared By:</b> Bay Area Compliance Laboratories Corp. (Shenzhen) 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008	

**Note:** This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Shenzhen). This report **must not** be used by the customer to claim product certification, approval, or endorsement by NVLAP\*, NIST, or any agency of the Federal Government.

\* This report may contain data that are not covered by the NVLAP accreditation and are marked with an asterisk “\*” Rev.2

## **TABLE OF CONTENTS**

<b>GENERAL INFORMATION.....</b>	<b>4</b>
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) .....	4
OBJECTIVE .....	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY .....	4
TEST FACILITY .....	5
<b>SYSTEM TEST CONFIGURATION.....</b>	<b>6</b>
DESCRIPTION OF TEST CONFIGURATION .....	6
EQUIPMENT MODIFICATIONS .....	6
LOCAL SUPPORT EQUIPMENT LIST AND DETAILS .....	6
CONFIGURATION OF TEST SETUP .....	6
BLOCK DIAGRAM OF TEST SETUP .....	7
<b>SUMMARY OF TEST RESULTS .....</b>	<b>8</b>
<b>FCC §15.319(I) &amp; §2.1093 - RF EXPOSURE .....</b>	<b>9</b>
<b>FCC §15.317 &amp; §15.203 - ANTENNA REQUIREMENT .....</b>	<b>10</b>
STANDARD APPLICABLE .....	10
ANTENNA CONNECTOR CONSTRUCTION .....	10
<b>FCC §15.319(E) - ANTENNA GAIN .....</b>	<b>11</b>
STANDARD APPLICABLE .....	11
<b>FCC §15.315 &amp; §15.207 - CONDUCTED EMISSIONS.....</b>	<b>12</b>
MEASUREMENT UNCERTAINTY.....	12
EUT SETUP .....	12
EMI TEST RECEIVER SETUP.....	13
TEST EQUIPMENT LIST AND DETAILS.....	13
TEST PROCEDURE .....	13
TEST RESULTS SUMMARY .....	13
TEST DATA .....	14
PLOT(S) OF TEST DATA .....	14
<b>FCC §15.323(A) - EMISSION BANDWIDTH.....</b>	<b>16</b>
STANDARD APPLICABLE .....	16
TEST EQUIPMENT LIST AND DETAILS.....	16
TEST PROCEDURE .....	16
TEST DATA .....	17
<b>FCC §15.319(C) - PEAK TRANSMIT POWER.....</b>	<b>19</b>
STANDARD APPLICABLE .....	19
TEST EQUIPMENT LIST AND DETAILS.....	19
TEST PROCEDURE .....	19
TEST DATA .....	19
<b>FCC §15.319(D) - POWER SPECTRAL DENSITY .....</b>	<b>22</b>
STANDARD APPLICABLE .....	22
TEST EQUIPMENT LIST AND DETAILS.....	22
TEST PROCEDURE .....	22
TEST DATA .....	22

<b>FCC §15.323(D) - EMISSION INSIDE AND OUTSIDE THE SUB-BAND.....</b>	<b>27</b>
STANDARD APPLICABLE .....	27
TEST EQUIPMENT LIST AND DETAILS.....	27
TEST DATA .....	27
<b>FCC §15.319(G) - RADIATED EMISSIONS.....</b>	<b>36</b>
MEASUREMENT UNCERTAINTY .....	36
EUT SETUP .....	36
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP .....	37
TEST EQUIPMENT LIST AND DETAILS.....	37
TEST PROCEDURE .....	37
CORRECTED AMPLITUDE & MARGIN CALCULATION .....	37
TEST RESULTS SUMMARY .....	38
TEST DATA .....	38
<b>FCC §15.323(F) - FREQUENCY STABILITY.....</b>	<b>43</b>
STANDARD APPLICABLE .....	43
TEST PROCEDURE .....	43
TEST EQUIPMENT LIST AND DETAILS.....	43
TEST DATA .....	43
<b>FCC §15.323(C)(E) &amp; §15.319(F) – SPECIFIC REQUIREMENTS FOR UPCS DEVICE.....</b>	<b>45</b>
<b>DECLARATION LETTER .....</b>	<b>51</b>

## GENERAL INFORMATION

### Product Description for Equipment Under Test (EUT)

The *MACKARL ENTERPRISES INC.* 's product, model number: *31231(Handset)(FCC ID:NK63123X)* or the "EUT" as referred to in this report is a Base for *DECT 6.0 Cordless Phone*, which measures approximately: 14.9 cm L x 4.5 cm W x 2.1 cm H, input voltage: DC 2.4V battery .

Battery information of handset  
BYD-AAA500B\*2 2.4V 500mAh

*\*Note: The series products, model 3123X (Where X: can be 0 (extra HS), 1 (Single HS), 2 (Two HS), 3 (Three HS) - Version), we select 31231 to test, the all model are electrically identical, only their model names have differences, which was explained in the attached Declaration Letter.*

*\* All measurement and test data in this report was gathered from production sample serial number: 0910002 (Assigned by BACL, Shenzhen). The EUT was received on 2009-10-12.*

### Objective

This document is a test report based on the Electromagnetic Interference (EMI) tests performed on the EUT. The EMI measurements were performed according to the measurement procedure described in ANSI C63.17 - 2006, and ANSI C64.3 2003.

The tests were performed in order to determine compliance with FCC Part 15, Subpart D, and section 15.203, 15.315, 15.317, 15.319 and 15.323 rules.

### Related Submittal(s)/Grant(s)

FCC ID: NK63123X, FCC Part 15D submission of Base portion.

### Test Methodology

All measurements contained in this report were conducted with ANSI C63.17 - 2006, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz. All radiated and conducted emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

**Test Facility**

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located in the 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China.

Test site at Bay Area Compliance Laboratories Corp. (Shenzhen) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on November 21, 2007. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2003.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 382179. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

Additionally, Bay Area Compliance Laboratories Corp. (Shenzhen) is a National Institute of Standards and Technology (NIST) accredited laboratory, under the National Voluntary Laboratory Accredited Program (Lab Code 200707-0).



The current scope of accreditations can be found at <http://ts.nist.gov/Standards/scopes/2007070.htm>

## SYSTEM TEST CONFIGURATION

### Description of Test Configuration

The system was configured for testing in a typical fashion (as normally used by a typical user).

### Equipment Modifications


No modification was made to the unit tested.

### Local Support Equipment List and Details


Manufacturer	Description	Model	Serial Number	FCC ID
R & S	Digital Radio-Communication Tester	CMD60	829902/026	DoC
MACKARL	DECT 6.0 Cordless Phone (Base)	31231	N/A	N/A

### Configuration of Test Setup

For conducted emission: EUT means charger and handset




For radiation emission:




**Block Diagram of Test Setup**

For conducted emission: EUT means charger and handset



For radiation emission:



## SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§ 15.319 (i); §2.1093	RF Radiation Exposure (SAR)	Compliant*
§ 15.317 § 15.203	Antenna Requirement	Compliant
§ 15.319 (e)	Antenna Gain	Compliant
§ 15.315 § 15.207	Conducted Emission	Compliant
§ 15.323 (a)	Emission Bandwidth	Compliant
§ 15.319 (c)	Peak Transmit Power	Compliant
§ 15.319 (d)	Power Spectral Density	Compliant
§ 15.323 (d)	Emission Inside and Outside the sub-band	Compliant
§ 15.319 (g)	Radiated Emission	Compliant
§ 15.323 (f)	Frequency Stability Handset	Compliant
§ 15.323 (c)(e) § 15.319 (f)	Specific Requirements for UPSCS	Compliant

**Note:** \* Please refer to SAR report RSZ09100903-SAR

## **FCC §15.319(i) & §2.1093 - RF EXPOSURE**

### **Standard Applicable**

According to FCC Part15.319 (i), Unlicensed PCS devices are subject to the radiofrequency radiation exposure requirements specified in§1.1307(b) and 2.1093 of this chapter, as appropriate. All equipment shall be considered to operate in a “general population/uncontrolled” environment. Applications for equipment authorization of devices operating under this section must contain a statement confirming compliance with these requirements for both fundamental emissions and unwanted emissions. Technical information showing the basis for this statement must be submitted to the Commission upon request.

### **Result:**

Please refer to SAR test report RSZ09100903-SAR.

## **FCC §15.317 & §15.203 - ANTENNA REQUIREMENT**

### **Standard Applicable**

According to CFR47 § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

### **Antenna Connector Construction**

This product has two integrated antennas arrangement, one is vertical polarity, the other is horizontal polarity, please refer to the internal photos. Their maximum gains are 0 dBi, fulfill the requirement of this section.

**Result:** Compliant.

---

## FCC §15.319(e) - ANTENNA GAIN

---

### Standard Applicable

According to CFR 47 §15.319 (e):

The peak transmit power shall be reduced by the amount in decibels that the maximum directional gain of the antenna exceeds 3 dBi.

**Result:** The antenna gain is less than 0 dBi provided by manufacturer.


## FCC §15.315 & §15.207 - CONDUCTED EMISSIONS

### Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, and LISN.

Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of any conducted emissions measurement at Bay Area Compliance Laboratories Corp. (Shenzhen) is  $\pm 2.4$  dB.

### EUT Setup



**Note:** 1. Support units were connected to second LISN.  
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.4-2003 measurement procedure. The specification used was with the FCC Part 15 Class B limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The adapter was connected to a 120 VAC/60 Hz power source.

## EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

<b><i>Frequency Range</i></b>	<b><i>IF B/W</i></b>
150 kHz – 30 MHz	9 kHz

## Test Equipment List and Details

<b>Manufacturer</b>	<b>Description</b>	<b>Model</b>	<b>Serial Number</b>	<b>Calibration Date</b>	<b>Calibration Due Date</b>
Com-Power	L.I.S.N.	LI-200	12005	N/A	N/A
Com-Power	L.I.S.N.	LI-200	12208	N/A	N/A
Rohde & Schwarz	EMI Test Receiver	ESCS30	830245/006	2009-04-28	2010-04-27
Rohde & Schwarz	L.I.S.N.	ESH2-Z5	892107/021	2009-04-28	2010-04-27

\* Com-Power's LISN were used as the supporting equipment.

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

## Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the LISN

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

## Test Results Summary

According to the recorded data in following table, the EUT complied with the [FCC Part 15.207](#), with the worst margin reading of:

**15.30 dB at 29.5400 MHz in the Neutral conductor mode**

## Test Data

### Environmental Conditions

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	100.0 kPa

The testing was performed by Vicent Kang on 2009-10-14.


Test Mode: Operating & Charging

Line Conducted Emissions				FCC Part 15.207	
Frequency (MHz)	Amplitude (dB $\mu$ V)	Detector (QP/AV)	Conductor (Line/ Neutral)	Limit (dB $\mu$ V)	Margin (dB)
29.5400	44.70	QP	Neutral	60.00	15.30
29.8250	44.00	QP	Line	60.00	16.00
29.5550	32.80	AV	Neutral	50.00	17.20
29.8850	32.30	AV	Line	50.00	17.70
22.5250	31.40	QP	Line	60.00	28.60
22.9950	30.80	QP	Neutral	60.00	29.20
22.4800	18.10	AV	Line	50.00	31.90
22.9950	17.90	AV	Neutral	50.00	32.10
0.5100	21.00	QP	Neutral	56.00	35.00
0.7200	19.90	QP	Neutral	56.00	36.10
0.5250	19.60	QP	Line	56.00	36.40
0.5300	9.60	AV	Neutral	46.00	36.40
0.7300	9.30	AV	Line	46.00	36.70
1.2850	9.00	AV	Neutral	46.00	37.00
1.2900	18.90	QP	Neutral	56.00	37.10
14.3150	22.40	QP	Line	60.00	37.60
1.2850	8.40	AV	Line	46.00	37.60
1.2850	17.90	QP	Line	56.00	38.10
0.7200	7.90	AV	Neutral	46.00	38.10
14.5750	21.70	QP	Neutral	60.00	38.30
0.7300	16.80	QP	Line	56.00	39.20
14.4500	10.60	AV	Line	50.00	39.40
0.5250	5.90	AV	Line	46.00	40.10
14.5750	9.60	AV	Neutral	50.00	40.40


### Plot(s) of Test Data

Plot(s) of Test Data is presented hereinafter as reference.

## Line:



## Neutral:




## FCC §15.323(a) - EMISSION BANDWIDTH

### Standard Applicable

The emission bandwidth is measured in accordance with ANSI C63.17 sub-clause 6.1.3 using the setup below

Test Setup 1:



The width, in Hz, of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, that is 26 dB down relative to the maximum level of the modulated carrier. It is based on the use of measurement instrumentation employing a peak detector function with an instrument resolution bandwidth approximately equal to 1% of the emission band-width of the device under measurement. [Extraction from 47 CFR 15, subpart D, 15.303 (C)].

### Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCS30	830245/006	2009-04-28	2010-04-27

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (ShenZhen) attests that all calibrations have been performed per the NVLAP requirements, traceable to NIST.

### Test Procedure

Using the manufacturer's information on occupied bandwidth set the spectrum analyzer as follows:

Resolution bandwidth	1.0% of the emission bandwidth (as close as possible)
Video bandwidth	>3 times the resolution bandwidth
Number of sweeps	sufficient to stability the trace
Detection mode	peak detection with maximum hold

## Test Data

### Environmental Conditions

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	100.8 kPa


The testing was performed by Bruce Zhang on 2009-10-23.

Test Mode: Transmitting

Channel	Center Frequency (MHz)	26 dB Bandwidth (MHz)	Limit
Low	1921.536	1.49	50kHz < OBW < 2.5MHz
Middle	1924.992	1.49	50kHz < OBW < 2.5MHz
High	1928.448	1.49	50kHz < OBW < 2.5MHz


Test Result: Pass, please refer to the attached plots.

### Low Channel




Date: 23.OCT.2009 14:24:17

## Middle Channel



Date: 23.OCT.2009 14:18:44

## High Channel



Date: 23.OCT.2009 14:21:36

## FCC §15.319(c) - PEAK TRANSMIT POWER

### Standard Applicable

The peak power output as measured over an interval of time equal to the transmission-burst duration of the device under all conditions of modulation. [47 CFR 15, subpart D, 15.303 (f)].

#### Part 15.323(a) & Part 15.319(c) Peak Transmit Power:

The limit for Peak Transmit Power (PTP) is calculated using the following formula:

$$PTP = 100 \mu W \times (EBW)^{1/2}$$

EBW is the transmit emission bandwidth in Hz determined in the other test item:

$$EBW = 1490000Hz$$

$$PTP = 100 \mu W \times (1490000)^{1/2}$$

$$PTP = 122.07mW = 20.87dBm$$

The peak transmitter power is measured in accordance with ANSI C63.17-2006 Clause 6.1.2.

### Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCS30	830245/006	2009-04-28	2010-04-27

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (ShenZhen) attests that all calibrations have been performed per the NVLAP requirements, traceable to NIST.

### Test Procedure

Using the manufacturer's information on occupied bandwidth set the spectrum analyzer as follows:

RBW	$\geq$ Emission bandwidth
Video bandwidth	$\geq$ RBW
Span	Zero
Center frequency	Nominal center frequency of channels
Amplitude scale	Log (linear may be used if analyzer has sufficient linear dynamic range and accuracy)
Detection	Peak detection
Trigger	Video
Sweep rate	Sufficiently rapid to permit the transmit pulse to be resolved accurately

### Test Data

#### Environmental Conditions


Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	100.8 kPa

The testing was performed by Bruce Zhang on 2009-10-23.


**Test Result:** Pass

Refer to the attached plots.


Frequency (MHz)	Peak Transmit Power (dBm)	Limit (dBm)
1921.536	18.10	20.87
1924.992	18.03	20.87
1928.448	17.92	20.87

**Low Channel**

Date: 23.OCT.2009 14:11:35

**Middle Channel**

Date: 23.OCT.2009 14:10:27

**High Channel**

Date: 23.OCT.2009 14:09:16

## FCC §15.319(d) - POWER SPECTRAL DENSITY

### Standard Applicable

The average pulse energy in a 3 kHz bandwidth is divided by the pulse duration.

The power spectral density shall not exceed 3mW in any 3 kHz bandwidth as measured with a spectrum analyzer having a resolution bandwidth of 3 kHz.

The power spectral density is measured in accordance with ANSI C63.17.2006 Clause 6.1.5.

### Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCS30	830245/006	2009-04-28	2010-04-27

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed per the NVLAP requirements, traceable to NIST.

### Test Procedure

Using the manufacturer's information on occupied bandwidth set the spectrum analyzer as follows:

RBW	3kHz
Video bandwidth	$\geq 3 \times$ RBW
Span	Zero span at frequency with the maximum level (frequency determined in 6.1.3 if the same type of signal (continuous versus burst) was used in 6.1.3)
Center frequency	Spectral peak as determined in 6.1.3
Sweep time	For burst signals, sufficient to include essentially all of the maximum length burst at the output of a 3 kHz filter (e.g., maximum input burst duration plus 600 $\mu$ s). For continuous signals, 20 ms.
Amplitude scale	Log power
Detection	Sample detection and averaged for a minimum of 100 sweeps
Trigger	External or internal

### Test Data

#### Environmental Conditions

<b>Temperature:</b>	25 °C
<b>Relative Humidity:</b>	56 %
<b>ATM Pressure:</b>	100.8 kPa

The testing was performed by Bruce Zhang on 2009-10-22 to 2009-10-23.


Test Mode: Transmitting

**Test Result:** Compliant.


Please refer to following tables and plots

Frequency (MHz)	Power Spectral Density		Limit (mW/3kHz)	Result
	(dBm/3kHz)	(mW/3kHz)		
1921.536	-1.30	0.74	3	Pass
1924.992	-1.57	0.70	3	Pass
1928.448	-1.91	0.64	3	Pass

## Low Channel




Date: 23.OCT.2009 14:30:30




Date: 23.OCT.2009 14:42:09

## Middle Channel




Date: 23.OCT.2009 14:46:45




Date: 23.OCT.2009 14:49:02

## High Channel



Date: 23.OCT.2009 14:52:40



Date: 23.OCT.2009 14:54:26

**FCC §15.323(d) - EMISSION INSIDE AND OUTSIDE THE SUB-BAND****Standard Applicable**

Emissions inside the sub-band must comply with the following emission mask:

1. In the bands between 1B and 2B measured from the center of the emission bandwidth the total power emitted by the device shall be at least 30 dB below the transmit power permitted for that device;
2. in the bands between 2B and 3B measured from the center of the emission bandwidth the total power emitted by an intentional radiator shall be at least 50 dB below the transmit power permitted for that radiator;
3. in the bands between 3B and the sub-band edge the total power emitted by an intentional radiator in the measurement bandwidth shall be at least 60 dB below the transmit power permitted for that radiator.

Where B = emission bandwidth

Emission Outside the sub-band shall be attenuated below a reference power of 112 mw (20.5 dBm) as follows:

1. 30 dB between the sub-band and 1.25 MHz above or below the sub-band;
2. 50 dB between 1.25 and 2.5 MHz above or below the sub-band;
3. 60 dB at 2.5 MHz or greater above or below the sub-band.

**Test Equipment List and Details**

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCS30	830245/006	2009-04-28	2010-04-27

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (ShenZhen) attests that all calibrations have been performed per the NVLAP requirements, traceable to NIST.

**Test Data****Environmental Conditions**


Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	100.8 kPa

*The testing was performed by Bruce Zhang on 2009-10-23 to 2009-10-26.*


*Test Mode: Transmitting*

**Test Result:** Compliant.

Please refer to following tables and plots


**Low Channel (Unwanted Emission inside the Sub-band)**

Date: 23.OCT.2009 15:15:08

**Middle Channel (Unwanted Emission inside the Sub-band)**


Date: 23.OCT.2009 15:10:37

### High Channel (Unwanted Emission inside the Sub-band)




Date: 23.OCT.2009 15:12:41


### Low Channels (Unwanted Emission outside the Sub-band)




Date: 26.OCT.2009 10:32:20




Date: 23.OCT.2009 15:28:06




Date: 23.OCT.2009 15:31:50




### Middle Channels (Unwanted Emission outside the Sub-band)







Date: 23.OCT.2009 15:35:36




Date: 23.OCT.2009 15:36:58




### High Channels (Unwanted Emission outside the Sub-band)






Date: 23.OCT.2009 15:40:42



Date: 23.OCT.2009 15:39:00




## FCC §15.319(g) - RADIATED EMISSIONS

### Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.

Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of a radiation emissions measurement at Bay Area Compliance Laboratories Corp. (Shenzhen) is  $\pm 4.0$  dB.

### EUT Setup



The radiated emission tests were performed in the 3 meters chamber B test site, using the setup accordance with the ANSI C63.17 - 2006. The specification used was the FCC 15.209 and FCC 15.319(g) limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

## EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W
30MHz – 1000 MHz	100 kHz	300 kHz
Above 1 GHz	1 MHz	3 MHz

## Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
HP	Amplifier	HP8447D	2944A09795	2009-08-02	2010-08-02
Rohde & Schwarz	EMI Test Receiver	ESCI	100035	2008-11-07	2009-11-06
Sunol Sciences	Broadband Antenna	JB1	A040904-1	2009-03-11	2010-03-11
HP	Amplifier	8449B	3008A00277	2009-09-12	2010-09-11
Sunol Sciences	Horn Antenna	DRH-118	A052604	2009-05-05	2010-05-04
Rohde & Schwarz	Spectrum Analyzer	FSEM30	849720/019	2009-07-08	2010-07-07

**\* Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

## Test Procedure

For the radiated emissions test, the adapter was connected to the AC floor outlet.

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30MHz-1GHz and peak and Average detection modes for frequencies above 1GHz.

## Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

## Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC 15.209 and 15.319 (g), with the worst margin reading of:

### Transmitting mode (30 – 1000 MHz):

**5.9 dB at 55.713250 MHz** in the **Vertical** polarization

### Transmitting mode (Above 1 GHz):

**2.75 dB at 7686.144 MHz** in the **Horizontal** polarization (**Low Channel**)

**2.27 dB at 9642.24 MHz** in the **Horizontal** polarization (**High Channel**)


## Test Data

### Environmental Conditions

<b>Temperature:</b>	25 °C
<b>Relative Humidity:</b>	56 %
<b>ATM Pressure:</b>	100.9 kPa

*The testing was performed by Bruce Zhang on 2009-10-25.*

*Test Mode: Transmitting*



Frequency (MHz)	Corrected Amplitude (dB $\mu$ V/m)	Antenna Height (cm)	Ant. Polarity (H/V)	Turntable Position (deg)	Correction Factor (dB)	Limit (dB $\mu$ V/m)	Margin (dB)
55.713250	34.1	100.0	V	1.0	-19.5	40.0	5.9
32.202750	31.7	101.0	V	136.0	-7.7	40.0	8.3
511.486000	36.6	100.0	V	84.0	-10.1	46.0	9.4
208.004500	32.3	157.0	H	1.0	-15.2	43.5	11.2
42.910250	27.6	100.0	V	35.0	-15.1	40.0	12.4
449.989250	32.7	100.0	V	123.0	-11.4	46.0	13.3

*Test Mode: Transmitting (Above 1GHz)*

Freq. (MHz)	Meter Reading (dB $\mu$ V)	Detector PK/QP/AV	Direction Degree	Antenna			Cable Loss (dB)	Pre- Amp. Gain (dB)	Corrected Amplitude (dB $\mu$ V/m)	FCC Part 15.319/209		
				Height (m)	Polar (H/V)	Factor (dB/m)				Limit (dB $\mu$ V/m)	Margin (dB)	Remarks
<b>Low Channel</b>												
7686.144	52.29	PK	282	1.0	H	36.3	12.16	29.5	71.25	74	2.75*	Harmonic
9607.68	49.53	PK	205	1.0	V	39.1	12.81	30.2	71.24	74	2.76*	Harmonic
9607.68	49.52	PK	295	1.0	H	38.5	12.81	30.2	70.63	74	3.37*	Harmonic
5764.608	56.06	PK	325	1.5	H	34.5	9.69	32.6	67.65	74	6.35	Harmonic
7686.144	46.96	PK	275	1.0	V	37.0	12.16	29.5	66.62	74	7.38	Harmonic
3843.072	55.17	PK	275	1.4	H	32.1	7.56	31.6	63.23	74	10.77	Harmonic
3843.072	54.71	PK	335	1.4	V	32.1	7.56	31.6	62.77	74	11.23	Harmonic
5764.608	48.68	PK	265	1.5	V	34.5	9.69	32.6	60.27	74	13.73	Harmonic
1813.1	52.84	PK	218	1.2	V	28.6	4.88	32.6	53.72	74	20.28	Spurious
1813.1	47.71	PK	200	1.0	H	28.3	4.88	32.6	48.29	74	25.71	Spurious
<b>High Channel</b>												
9642.24	50.62	PK	292	1.1	H	38.5	12.81	30.2	71.73	74	2.27*	Harmonic
7713.792	52.76	PK	286	1.2	H	36.3	12.16	29.5	71.72	74	2.28*	Harmonic
9642.24	49.35	PK	210	1.4	V	39.1	12.81	30.2	71.06	74	2.94*	Harmonic
5785.344	56.04	PK	340	1.3	H	34.5	9.69	32.6	67.63	74	6.37	Harmonic
7713.792	46.45	PK	350	1.0	V	37.0	12.16	29.5	66.11	74	7.89	Harmonic
3856.896	53.43	PK	335	1.0	V	32.1	7.56	31.6	61.49	74	12.51	Harmonic
3856.896	53.26	PK	275	1.5	H	32.1	7.56	31.6	61.32	74	12.68	Harmonic
5785.344	48.98	PK	265	1.0	V	34.5	9.69	32.6	60.57	74	13.43	Harmonic
1818.6	53.24	PK	240	1.5	V	28.6	4.88	32.6	54.12	74	19.88	Spurious
1818.6	47.78	PK	170	1.5	H	28.3	4.88	32.6	48.36	74	25.64	Spurious

\* Within measurement uncertainty.


Frequency (MHz)	Peak Cord. Amp. @3m (dB $\mu$ V/m)	Ant. Polar (H/V)	Duty Cycle Factor (dB)	Cord. Amp. (dB $\mu$ V/m)	FCC 15.319(g)		Comment
					Limit (dB $\mu$ V/m)	Margin (dB)	
Low Channel							
7686.144	71.25	H	-28.1	43.15	54	10.85	Harmonic
9607.68	71.24	V	-28.1	43.14	54	10.86	Harmonic
9607.68	70.63	H	-28.1	42.53	54	11.47	Harmonic
5764.608	67.65	H	-28.1	39.55	54	14.45	Harmonic
7686.144	66.62	V	-28.1	38.52	54	15.48	Harmonic
3843.072	63.23	H	-28.1	35.13	54	18.87	Harmonic
3843.072	62.77	V	-28.1	34.67	54	19.33	Harmonic
5764.608	60.27	V	-28.1	32.17	54	21.83	Harmonic
1813.1	53.72	V	-28.1	25.62	54	28.38	Spurious
1813.1	48.29	H	-28.1	20.19	54	33.81	Spurious
High Channel							
9642.24	71.73	H	-28.1	43.63	54	10.37	Harmonic
7713.792	71.72	H	-28.1	43.62	54	10.38	Harmonic
9642.24	71.06	V	-28.1	42.96	54	11.04	Harmonic
5785.344	67.63	H	-28.1	39.53	54	14.47	Harmonic
7713.792	66.11	V	-28.1	38.01	54	15.99	Harmonic
3856.896	61.49	V	-28.1	33.39	54	20.61	Harmonic
3856.896	61.32	H	-28.1	33.22	54	20.78	Harmonic
5785.344	60.57	V	-28.1	32.47	54	21.53	Harmonic
1818.6	54.12	V	-28.1	26.02	54	27.98	Spurious
1818.6	48.36	H	-28.1	20.26	54	33.74	Spurious

Note: Duty Cycle=Ton/Tp\*100%

Ton=394 $\mu$ s =0.394ms, Tp=10ms, Duty Cycle=3.94%, Duty cycle factor = 20lg (Duty Cycle) = -28.1 dB


Average = Peak + Duty Cycle

Ton:



Date: 25.OCT.2009 14:48:16

Tp:



Date: 25.OCT.2009 14:47:29

## FCC §15.323(f) - FREQUENCY STABILITY

### Standard Applicable

Per §15.323(f), the frequency stability of the carrier frequency of the intentional radiator shall be maintained within  $\pm 10$  ppm over 1 hour or the interval between channel access monitoring, whichever is shorter. The frequency stability shall be maintained over a temperature variation of  $-20^{\circ}$  to  $+50^{\circ}$  C at normal supply voltage, and over a variation in the primary supply voltage of 85 percent to 115 percent of the rated supply voltage at a temperature of  $20^{\circ}$  C. For equipment that is capable only of operating from a battery, the frequency stability tests shall be performed using a new battery without any further requirement to vary supply voltage

### Test Procedure

This procedure should be carried out for each of the following test cases:

Temperature	Supply Voltage
$20^{\circ}$ C	85-115% or new batteries
$-20^{\circ}$ C <sup>a</sup>	Normal
$+50^{\circ}$ C	Normal

<sup>a</sup> Use the lowest temperature at which the EUT is specified to operate if it is above  $-20^{\circ}$  C.

Using the mean carrier frequency at  $20^{\circ}$  C and at nominal supply voltage as the reference, the mean carrier frequency shall be maintained within  $\pm 10$  ppm at the two extreme temperatures (or as declared by the manufacturer) and at normal temperature (typically  $20^{\circ}$  C) at the two extreme supply voltages. This test does not apply to an EUT that is capable only of operating from a battery.

### Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
WUHUAN	Temperature & Humidity Chamber	HTP205	20021115	N/A	N/A
R&S	Digital Radio-Communication Tester	CMD60	829902/026	2009-9-26	2010-9-25

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (ShenZhen) attests that all calibrations have been performed per the NVLAP requirements, traceable to NIST.

### Test Data

#### Environmental Conditions

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	100.8 kPa

The testing was performed by Bruce Zhang on 2009-10-26

*Test Mode: Transmitting*

**Test Result:** Compliant.

Temperature (°C)	Voltage (Vdc)	Channel Frequency (MHz)	Measured Frequency Offset (kHz)	Measured Frequency Offset (ppm)	Limit (ppm)
20	2.4	1924.992	-6	-3.12	±10
-20	2.4	1924.992	-5	-2.60	±10
50	2.4	1924.992	-6	-3.12	±10

## FCC §15.323(c)(e) & §15.319(f) – SPECIFIC REQUIREMENTS FOR UPCS DEVICE

### Automatic Discontinuation of Transmission, FCC Part 15.319(f)

The device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. The provisions in this section are not intended to preclude transmission of control and signaling information or use of repetitive codes used by certain digital technologies to complete frame or burst intervals.

#### Test Procedure:

Please refer to the declaration provided by manufacturer.

#### Test result:

Meet the requirement

### Monitoring Time FCC 15.323 (c) (1)

Immediately prior to initiating transmission, devices must monitor the combined time and spectrum window in which they intend to transmit. For a period of at least 10 milliseconds for systems designed to use a 10 milliseconds or shorter frame period or at least 20 milliseconds for systems designed to use a 20 milliseconds frame period

#### Test procedure:

Measurement method according to ANSI C63.17 2006 clause 7.3.4

#### Test result:

EUT monitors the combined time and spectrum window prior to initiation of transmission. Test result please according to FCC15.323(c) (4).

### Lower Monitoring Threshold Part15.323 (c)(2)

The monitoring threshold must not be more than 30 dB above the thermal noise power for a bandwidth equivalent to the emission bandwidth used by the device.

#### Test procedure:

Measurement method according to ANSI C63.17 2006 clause 7.3.1

#### Test result:

Not Apply

### Maximum Transmit Period FCC Part15.323 (c) (3)

If no signal above the threshold level is detected, transmission may commence and continue with the same emission bandwidth in the monitored time and spectrum windows without further monitoring. However, occupation of the same combined time and spectrum windows by a device or group of cooperating devices continuously over a period of time longer than 8 hours is not permitted without repeating the access criteria.

**Test procedure:**

Measurement method according to ANSI C63.17 2006 clause 8.2.2

**Test result:**

Repetition of Access Criteria	Measured Maximum Transmission Time (Second)	Limit (Second)	Results
First	900	28,800	Pass
Second	900	28,800	Pass

**System Acknowledgement, FCC Part15.323 (c) (4)**

Once access to specific combined time and spectrum windows is obtained an acknowledgment from a system participant must be received by the initiating transmitter within one second or transmission must cease. Periodic acknowledgments must be received at least every 30 seconds or transmission must cease. Channels used exclusively for control and signaling information may transmit continuously for 30 seconds without receiving an acknowledgment, at which time the access criteria must be repeated.

**Test procedure:**

Measurement method according to ANSI C63.17 2006 clause 8.1.1, 8.2.1

**Test result:**

Test	Time taken (second)	Limit (second)	Result
Connection acknowledgement	0.0050	1	Pass
Change of access criteria for control information	N/A	30	Pass
Transmission cease time	5.00	30	Pass
Pulse length	0.01	0.01	Pass

Note: N/A=Not Applicable

**Least Interfered Channel (LIC) Selection, FCC Part15.323 (c) (5)**

If access to spectrum is not available as determined by the above, and a minimum of 40 duplex system access channels are defined for the system, the time and spectrum windows with the lowest power level below a monitoring threshold of 50 dB above the thermal noise power determined for the emission bandwidth may be accessed.

Calculation of monitoring threshold limits for isochroous devices:

Lower threshold:  $T_L = -174 + 10 \log_{10} B + M_u + P_{MAX} - P_{EUT}$  (dBm)

Upper threshold:  $T_U = -174 + 10 \log_{10} B + M_u + P_{MAX} - P_{EUT}$  (dBm)

Where: B=Emission bandwidth (Hz)

$M_u$  =dB the threshold may exceed thermal noise (30 for  $T_L$  & 50 for  $T_U$ )

$P_{MAX} = 5 \log_{10} B - 10$  (dBm)

$P_{EUT}$  =Transmitted power (dBm)

**Limit:**

Monitor Threshold	B (MHz)	M <sub>U</sub> (dB)	P <sub>MAX</sub> (dBm)	P <sub>EUT</sub> (dBm)	Threshold (dBm)
T <sub>L</sub>	1.49	30	20.87	19.32	-80.72
T <sub>U</sub>	1.49	50	20.87	19.32	-60.72

The EUT must not transmit until the interference level is less than or equal to:

Measured Threshold Level  $\leq T_U$

Where: T<sub>U</sub> =Upper threshold level

**Test procedure:**

Measurement method according to ANSI C63.17 clause 7.3.2, 7.3.3, 7.3.4

**Test result:**

Monitor threshold	Measured Threshold Level	Limit (dBm)
Lower Threshold(dBm)	N/A	-80.72
Upper Threshold(dBm)	N/A	-60.72

Note: The upper threshold is applicable as the EUT utilizes more than 40 duplex system channels

**Random waiting FCC 15.323(c) (6)**

If the selected combined time and spectrum windows are unavailable, the device may either monitor and select different windows or seek to use the same window after waiting an amount of time, randomly chosen from a uniform random distribution between 10 and 150 milliseconds, commencing when the channel becomes available.

**Test procedure:**

Measurement method according to ANSI C63.17 2006 clause 8.1.3

**Test result:**

The manufacturer declares that this provision is not utilized by the EUT.

**Monitoring Bandwidth, FCC Part 15.323 (c) (7)**

The monitoring system bandwidth must be equal to or greater than the emission bandwidth of the intended transmission and have a maximum reaction time less than  $50 \times \text{SQRT}(1.25/\text{emission bandwidth in MHz})$  microseconds for signals at the applicable threshold level but shall not be required to be less than 50 microseconds

**Test procedure:**

Measurement method according to ANSI C63.17 2006 clause 7.5

**Test result:**

Test Equation ( $\mu$ s)	B (bandwidth) (MHz)	Pulse width $\mu$ s)	Limit ( $\mu$ s)	Result
$50 (1.25/B)^{1/2}$	1.49	45.80	50	Pass
$35 (1.25/B)^{1/2}$	1.49	32.06	35	Pass

**Monitoring Antenna, FCC Part15.323 (c) (8)**

The monitoring system shall use the same antenna used for transmission, or an antenna that yields equivalent reception at that location.

**Test procedure:**

Measurement method according to ANSI C63.17 2006 paragraph 4

**Test result:**

The antenna of the EUT used for transmission is the same interior antenna that used for monitoring.

**Monitoring threshold relation FCC 15.323(c) (9)**

Devices that have a power output lower than the maximum permitted under the rules can increase their monitoring detection threshold by one decibel for each one decibel that the transmitter power is below the maximum permitted.

**Test procedure:**

Measurement method according to ANSI C63.17 2006 paragraph 4

**Test result:**

Not apply based on 15.323 (c)(5)

**Duplex Connections, FCC Part15.323 (c) (10)**

An initiating device may attempt to establish a duplex connection by monitors both its intended transmit and receive time and spectrum windows. If both the intended transmit and receive time and spectrum windows meet the access criteria, then the initiating device can initiate a transmission in the intended transmit time and spectrum window. If the power detected by the responding device can be decoded as a duplex connection signal from the initiating device, then the responding device may immediately begin transmitting on the receive time and spectrum window monitored by the initiating device.

**Test procedure:**

Measurement method according to ANSI C63.17 clause 8.3

**Test result:**

The manufacturer declares that this provision is not utilized by the EUT.

**Alternative monitoring interval for co-located devices, FCC Part 15.323 (c) (11)**

An initiating device that is prevented from monitoring during its intended transmit window due to monitoring system blocking from the transmissions of a co-located (within one meter) transmitter of the same system, may monitor the portions of the time and spectrum windows in which they intend to receive over a period of at least 10 milliseconds. The monitored time and spectrum window must total at least 50 percent of the 10 millisecond frame interval and the monitored spectrum must be within 1.25 MHz of the center frequency of channel(s) already occupied by that device or co-located co-operating devices. If the access criteria is met for the intended receive time and spectrum window under the above conditions, then transmission in the intended transmit window by the initiating device may commence.

**Test procedure:**

Measurement method according to ANSI C63.17 2006 clause 8.4

**Test result:**

The manufacturer declares that this provision is not utilized by the EUT.

**Fair Access, FCC Part 15.323 (c) (12)**

The provisions of FCC Part15.323(c)(10) or (c)(11) shall not be used to extend the range of spectrum occupied over space or time for the purpose of denying fair access to spectrum to other devices.

**Test result:**

The manufacturer declares that this device does not use any mechanisms as provided by Part15.323 (c) (10) or (c) (11) to extend the range of spectrum occupied over space or time for the purpose of denying fair access to spectrum to other device.

**Frame Repetition Stability, Part15 .323 (e)**

The frame period (a set of consecutive time slots in which the position of each time slot can be identified by reference to a synchronizing source) of an intentional radiator operating in these sub-bands shall be 20 milliseconds or 10 milliseconds/X where X is a positive whole number.

**Test procedure:**

Measurement method according to ANSI C63.17 2006 clause 6.2.2, 6.2.3

**Test result:**

Frame Repetition Stability:

Frame Repetition Stability (ppm)	Limit (ppm)	Result (Pass/Fail)
3.12	10	Pass

Frame Period and Jitter:

Max. Pos. jitter (us)	Max. Neg. jitter (us)	Frame Period	Limit	
			Frame Period (ms)	Jitter ( $\mu$ s)
0.17	-0.31	10.00000	2or10/X	25 us

Note: X is a positive whole number.

**DECALARATION LETTER****MACKARL ENTERPRISES, INC.**

16960 Gale Avenue, City of Industry, CA 91745 Tel (626) 912-2166 Fax (626) 912-2258

**Product Similarity Declaration**

To Whom It May Concern;

We, MACKARL ENTERPRISES INC., hereby declare that our DECT 6.0 Cordless Phone, Model Number: 3123X (Where X: can be 0 (extra HS), 1 (Single HS), 2 (Two HS), 3 (Three HS) - Version), it means that – 31230 (one handset, one charger unit) can be added to any of the other model series i.e. 31231, 31232, 31233;

31231 (one handset, one base) can be expanded by adding 31230;  
31233 (three handsets, one base) can be expanded by adding 31230;  
31232 (two handsets, one base) can be expanded by adding 31230;

So 31230, 31233, 31232 are electrically identical with the Model Number: 31231 that was certified by BACL, they are named differently and have different quantity of handset due to marketing purposes and only for FCC Part 68 test, we add one receiver to the product, no other change are made to them.

Please contact me if you have any question.

Sincerely Yours;

Alvin Po  
Project Manager

Date: 2009-11-04

**\*\*\*\*\* END OF REPORT \*\*\*\*\***