

RF Exposure Report

Maximum Possible Exposure based on FCC OET Bulletin 65

FCC ID: NK73186795

Band: 2100 MHz

Type: Occupational/Controlled. Authorized use by trained professionals only.

Description: Cellular Transceiver System connected to magnetic mount omni-directional antenna (Laird TRAB806/17103) positioned on a vehicle roof. Antenna is connected with a 10 ft coax cable.

Date: July 20, 2010

Input Data

Frequency at mid-band	2132.5	MHz
Pout to Antenna	0.008	Watts
Antenna Gain	0.0	dBi
Antenna Gain	1.00	(non-log)
Distance to Antenna Center	20	cm

Results of Calculations

Power Density Calculated	0.0016	mW/cm ²
FCC Limit Occupational	5	mW/cm ²
FCC Limit General Public	1	mW/cm ²

Reference Data

Duty Cycle	100	%
------------	-----	---

Notes:

- 1) Cable loss for standard 10 ft coax cable is included in Antenna Gain calculation.
- 2) Valid only between 300 MHz - 100,000 MHz.
- 3) Calculations are sufficient for determining antenna safe distance for mobile antennas provided that calculated ERP < 1.5 watts for frequencies equal to or below 1.5 GHz, and calculated ERP < 3 watts for frequencies above 1.5 GHz.