



PEP Testing Laboratory

RFI / EMI TEST REPORT

APPLICANT : MAXTRONIC INTERNATIONAL CO., LTD.

E. U. T. : DISK ARRAY SYSTEM

TRADE NAME : N/A

FCC ID : NKF-SILVER

REGULATION : CFR 47, Part 15 Subpart B, Class B

TEST SITE : PEP Testing Laboratory

TEST ENGINEER : *Jason Gong*

TEST DATE : *9/1/1998*

ISSUED DATE : SEP. / 07 / 1998

REPORT No. : 980466



PEP Testing Laboratory

VERIFICATION

WE HEREBY VERIFY THAT:

The E. U. T. listed below has completed RFI testing by PEP Testing Laboratory and the interference emissions can pass **FCC Class B** limitations.

The tested configurations and the facility complies with the radiated and AC line conducted test site criteria in ANSI C63.4-1992.


Any data in this RFI report is "reference" "only".

APPLICANT : MAXTRONIC INTERNATIONAL CO., LTD.*

PRODUCT : DISK ARRAY SYSTEM*

FCC ID : NKF-SILVER*

MODEL : Arena Silver*



M. Y. TSUI
Manager

PEP Testing Laboratory
12-3FL., NO. 27-1, Lane 169, Kang-Ning St.,
Hsi-Chi, Taipei Hsien, Taiwan, R. O. C.
TEL: 886-2-6922097 FAX: 886-2-6956236



PEP Testing Laboratory

TABLE OF CONTENTS

1. GENERAL

1.1 General Information	1
1.2 Place of Measurement	1
1.3 Labeling Requirements	2
1.4 Information to User	3

2. CONDUCTED EMISSIONS TEST

2.1 Setup of the Test Facilities	4
2.2 Test Procedures	5

3. RADIATED EMISSIONS TEST

3.1 Setup of the Test Facilities	6
3.2 Test Procedures	7

4. DESCRIPTION FOR EUT TESTING CINFIGURATION

5. SUPPORTING DEVICES TO TEST

6. TEST CONFIGURATION

** Conducted Emission Test Photo. and Data

** Radiated Emission Test Photo. and Data

7. APPENDIX

A. Photos of EUT Appearance	10
-----------------------------	----



PEP Testing Laboratory

1. GENERAL

1.1 GENERAL INFORMATION:

APPLICANT : MAXTRONIC INTERNATIONAL CO., LTD.

4FL., NO. 529, CHUNG CHENG RD.,
HSIN TIEN CITY, TAIPEI, TAIWAN
R. O. C.

MANUFACTURER : MAXTRONIC INTERNATIONAL CO., LTD.

4FL., NO. 529, CHUNG CHENG RD.,
HSIN TIEN CITY, TAIPEI, TAIWAN
R. O. C.

MEASUREMENT PROCEDURE : ANSI C63,4 - 1992

TESTED FOR COMPLIANCE WITH : Title 47 of CFR
Part 15, Subpart B, Class B

1.2 PLACE OF MEASUREMENT


PEP Testing Laboratory



PEP Testing Laboratory

1.3 LABELING REQUIREMENT

A FCC ID label shall be permanently attached and conspicuously located on the equipment:





PEP Testing Laboratory

1.4 INFORMATION TO THE USER

The following FCC statement should be declared in a conspicuous location in the user's manual.

Federal Communications Commission (FCC) Statement

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instruction, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio / TV technician for help.

Warning : A shielded-type power cord is required in order to meet FCC emission limits and also to prevent interference to the nearby radio and television reception. It is essential that only the supplied power cord be used.

Use only shielded cables to connect I/O devices to this equipment.


You are cautioned that changes or modifications not expressly approved by the party responsible for compliance could void your authority to operate the equipment.



PEP Testing Laboratory

2. CONDUCTION EMISSIONS TEST

2.1 GENERAL SETUP OF THE TEST FACILITIES





PEP Testing Laboratory

2.2 TEST PROCEDURES

The system was setup as described above, with the EMI diagnostic software.

Both the line of power cord, hot and neutral, were run with the EMI tests software.

To get the maximum power line conducted emission, we changed the configuration by varying the monitor power cord fed from floor outlet and from the outlet on the power supply of this computer.


The highest emissions were recorded in the RFI test report.



PEP Testing Laboratory

3. RADIATED EMISSIONS TEST

3.1 GENERAL SETUP OF THE FACILITIES





PEP Testing Laboratory

3.2 TEST PROCEDURES

Radiated emissions test was carried out by **PEP Testing Laboratory** at the open field test site authorized by FCC.

The EUT and supporting equipments were setup with the EMI diagnostic software .

- a. setting up the EUT under normally position , and scanning it from 30 MHz to 1000 MHz , then recording those narrow band noises which cannot be 6 dBuV below lower bound . Both horizontal and vertical antenna are measured from 1 meter height to 4.0 meter height , and turntable rotate 360 degrees .
- b. fixing the EUT rear face to antenna and antenna 1.0 meter height . We adjusted I/O cables to find the highest coupling noise and moved the height of antenna from 1 to 4 meters , then rotated the turntable simultaneously .
- c. checking following step b. all points which were recorded in step a.
- d. changing the peripherals position , and routine steps a. b. c.

The highest emissions were recorded in the RFI test report .



PEP Testing Laboratory

4. DESCRIPTION FOR EUT TESTING CONFIGURATION

**** TEST PROCESURE -----**

- (A) The EUT was disk array system , FCC ID:NKF-SILVER , with six hard disk ,
for more detail information about the EUT , please refer user's manual .
- (B) The EUT executed disk copy program between HDD inside PC and ZIP via EUT during
the test .
- (C) After the EUT was set up , we did the conducted emission test in the shielded room and
the worst case placement finding as the ANSI C63.4 requirement ; similarly , the
radiated emission test was done at the open field site .
- (D) If the peak value of the noise can't under Non-consumer equipment limit 3 dBuV more ,
we'll change Biconical antenna or Log-periodic antenna for Dipole antenna and record its
Quasi-Peak value , making sure it can under 6 dBuV at least .
- (E) In the RFI test report , we provided the worst conducted emission testing data in page
C-1.*
For the radiated emission test , the worst data recorded in the page R-1.*

**** I/O DATA CABLES INFORMATIONS ---**

Please refer the page 9 .



PEP Testing Laboratory

5. SUPPORTING DEVICES TO TEST

SUPPORT UNIT 1. ---- PERSONAL COMPUTER

Manufacturer : Jm Computer Inc.
Model Number : C486SDX-SDT
Power Supply Type : Switching
Power Cord : Shielded, Detachable, 1.2m
Data Cable : Shielded, Detachable, 1.2m
FCC ID : K25C486SDX-SDT

SUPPORT UNIT 2. ---- MONITOR

Manufacturer : Acer Peripherals Inc.
Model Number : 7134T
Power Supply Type : Switching
Power Cord : Shielded, Detachable, 1.2m
Data Cable : Shielded, Undetachable, 1m
FCC ID : JVP7134T

SUPPORT UNIT 3. ---- PRINTER

Manufacturer : Hewlett-Packard Singapore Pte Ltd.
Model Number : HP 2225C⁺
Power Supply Type : Linear
Power Cord : Non-Shielded, Detachable, 1.2m
Data Cable : Shielded, Detachable, 1m. 2464
FCC ID : DSI6XU2225



PEP Testing Laboratory

SUPPORT UNIT 4. ----MODEM

Manufacturer : ACEEX

Model Number : 1414

Power Supply Type : Linear

Power Cord : Non-Shielded, Detachable, 1.2m

Data Cable : Shielded, Detachable, 1m

FCC ID : IFAXDM1414

SUPPORT UNIT 5. ---- KEYBOARD

Manufacturer : Acer Inc.

Model Number : 6011

Power Supply Type : N/A

Power Cord : N/A

Data Cable : Shielded, Undetachable, 1m

FCC ID : GQ86011A

SUPPORT UNIT 6. ---- ZIP (SCSI)

Manufacturer : ZPSION

Model Number : ZP-100

Power Supply Type : N/A

Power Cord : N/A

Data Cable : N/A

FCC ID : N/A



PEP Testing Laboratory

SUPPORT UNIT 7. ---- SCSI CARD

Manufacturer : ADAPTEL

Model Number : AIC-7880P

Power Supply Type : N/A

Power Cord : N/A

Data Cable : N/A

FCC ID : N/A

SUPPORT UNIT 8. ---- HARD DISK

Manufacturer : SEAGATE

Model Number : ST32122A

Power Supply Type : N/A

Power Cord : N/A

Data Cable : N/A

FCC ID : N/A



PEP Testing Laboratory

EQUIPMENT UNDER TEST ---- DISK ARRAY SYSTEM

Manufacturer : MAXTRONIC INTERNATIONAL CO., LTD.
Model Number : Arena Silver
Data Cable : Shielded, Undetachable, 1.2m
FCC ID : NKF-SILVER



PEP Testing Laboratory

6. TEST CONFIGURATION

Radiated emission detector function :

- (1) 30MHZ~1GHZ : Quasi-Peak Value
Resolution BW : 120KHZ Video BW : 300KHZ
- (2) above 1GHZ : Quasi-Peak value and Average Value
Resolution BW : 1MHZ Video BW : 1MHZ
* either Q. P. or average value will be recorded
in the report

Conducted emission detector function :

- (1) 450KHZ~30MHZ : Quasi-Peak Value
Resolution BW : 9KHZ Video BW : 30KHZ

The else descriptions : Both SCSI I/O cables will be sold along with the EUT
and two ferrite cores mounted on each cable .

Conducted Emission Test Photo. : Page C-1

- Test Data : Hot C-1.1
- Neutral C-1.2

Radiated Emission Test Photo. : Page R-1

- Test Data : Horizontal R-1.1
- Vertical R-1.2



PEP Testing Laboratory

CONDUCTED EMISSIONS TEST DATA

Note : HOT LINE TEST

Freq. (MHz)	Level (dB)	Over Limit (dB)	Limit Line (dB)	Read Level (dB)	Probe Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)
9.079	24.81	-23.19	48.00	22.47	0.47	1.87	0.00
10.615	25.54	-22.46	48.00	23.19	0.53	1.82	0.00
11.502	25.26	-22.74	48.00	22.86	0.57	1.83	0.00
12.920	23.01	-24.99	48.00	20.53	0.63	1.85	0.00
15.048	24.59	-23.41	48.00	21.99	0.70	1.90	0.00
22.583	25.23	-22.77	48.00	22.30	0.86	2.07	0.00
23.706	28.21	-19.79	48.00	25.22	0.88	2.11	0.00
24.888	27.77	-20.23	48.00	24.72	0.90	2.15	0.00
26.424	26.07	-21.93	48.00	22.77	1.11	2.18	0.00
28.729	29.76	-18.24	48.00	26.11	1.42	2.23	0.00

Note :

1. Level = Read Level + Probe Factor + Cable Loss - Preamp Factor
2. Over Limit = Level - Limit Line



PEP Testing Laboratory

CONDUCTED EMISSIONS TEST DATA

Note : NEUTRAL LINE TEST

Freq. (MHz)	Level (dB)	Over Limit (dB)	Limit Line (dB)	Read Level (dB)	Probe Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)
7.956	23.31	-24.69	48.00	21.04	0.42	1.85	0.00
10.261	23.75	-24.25	48.00	21.43	0.51	1.81	0.00
10.556	24.61	-23.39	48.00	22.26	0.53	1.82	0.00
12.684	22.00	-26.00	48.00	19.54	0.62	1.84	0.00
20.071	21.15	-26.85	48.00	18.33	0.80	2.02	0.00
23.469	25.03	-22.97	48.00	22.06	0.87	2.09	0.00
24.445	28.92	-19.08	48.00	25.90	0.89	2.13	0.00
25.095	30.89	-17.11	48.00	27.80	0.93	2.16	0.00
26.218	28.41	-19.59	48.00	25.15	1.08	2.18	0.00
28.729	29.60	-18.40	48.00	25.95	1.42	2.23	0.00

Note :

1. Level = Read Level + Probe Factor + Cable Loss - Preamp Factor
2. Over Limit = Level - Limit Line



PEP Testing Laboratory

RADIATED EMISSIONS TEST DATA

Antenna polarization : HORIZONTAL ; Test distance : 3 m ;

Freq. (MHz)	Level (dB)	Over Limit (dB)	Limit Line (dB)	Read Level (dB)	Probe Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)
57.540	18.92	-21.08	40.00	38.47	-0.80	1.25	20.00
71.990	24.10	-15.90	40.00	46.59	-3.94	1.44	20.00
108.030	21.25	-22.25	43.50	37.57	1.88	1.80	20.00
129.280	18.88	-24.62	43.50	35.88	0.94	2.06	20.00
180.280	27.59	-15.91	43.50	40.88	4.30	2.41	20.00
203.200	24.74	-18.76	43.50	37.62	4.40	2.72	20.00
241.600	24.69	-21.31	46.00	39.77	1.89	3.04	20.00
265.600	29.47	-16.53	46.00	43.58	2.63	3.26	20.00
303.200	24.45	-21.55	46.00	37.89	2.95	3.61	20.00
467.200	24.98	-21.02	46.00	34.69	5.98	4.32	20.00

$$\begin{array}{r} 1 \\ 23.4 \\ + 2.6 \\ + 3.3 \\ \hline 29.3 \end{array} \checkmark$$

Note :

1. Level = Read Level + Probe Factor + Cable Loss - Preamp Factor
2. Over Limit = Level - Limit Line



PEP Testing Laboratory

RADIATED EMISSIONS TEST DATA

Antenna polarization : VERTICAL ; Test distance : 3 m ;

Freq. (MHz)	Level (dB)	Over Limit (dB)	Limit Line (dB)	Read Level (dB)	Probe Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)
57.540	19.61	-20.39	40.00	39.16	-0.80	1.25	20.00
92.390	18.27	-25.23	43.50	37.61	-0.88	1.54	20.00
120.440	17.04	-26.46	43.50	33.44	1.65	1.95	20.00
157.840	20.14	-23.36	43.50	35.37	2.39	2.38	20.00
241.600	21.84	-24.16	46.00	33.92	4.89	3.04	20.00
264.800	24.13	-21.87	46.00	35.29	5.59	3.25	20.00
265.600	28.91	-17.09	46.00	40.02	5.63	3.26	20.00
301.600	25.26	-20.74	46.00	35.80	5.85	3.61	20.00
317.600	24.52	-21.48	46.00	34.82	6.05	3.66	20.00
469.600	25.24	-20.76	46.00	31.88	9.03	4.33	20.00

$$\begin{array}{r} 39.16 \\ -20.8 \\ +1.25 \\ \hline 19.61 \end{array} \qquad \begin{array}{r} 40.41 \\ -20.8 \\ \hline 19.61 \end{array}$$

Note :

1. Level = Read Level + Probe Factor + Cable Loss - Preamp Factor
2. Over Limit = Level - Limit Line



PEP Testing Laboratory

List of Test Equipment

Instrument	Model No.	Cal. Due Date	S/N
R&S Receiver	ESVS30(30M~1GHZ)	Apr. 21, 1999	863342/012
R&S Receiver	ESBI (20~5GHZ)	Feb. 12, 1999	845658/003
Spectrum Analyzer	HP8591A(9K~1.8GHZ)	Jan. 31, 1999	3225A03039
Spectrum Analyzer	R3261A (9K~2.6GHZ)	Dec. 03 1998	91720076
EMCO L.I.S.N.	3825/2 (10K~30MHZ)	Oct. 31, 1998	9311-2150
L.I.S.N.	KNW-242(10K~30MHZ)	Jan. 31, 1999	8-837-7
R & S L.I.S.N.	ESH3-Z5(9K~30MHZ)	Feb. 12, 1999	844982/039
Anritsu Pre-Amp.	MH648A(100K~1.4GHZ)	Nov. 9, 1998	M40076
R & S Pre-Amp.	ESMI-Z7(20M~7GHZ)	Feb. 12, 1999	6/2278/011
Chase bi-Log Antenna	CBL6111B(30M~1GHZ)	Aug. 05, 1999	1968
COM-Power Horn Antenna	AH-118 (1G~18GHZ)		10056
EMCO Dipole Antenna	3121C (20M~1GHZ)	May. 22, 1999	9611-1230
EMCO Biconical Antenna	3110B (30M~300M)	Mar. 10, 1999	2932
EMCO Log-Periodic Antenna	3146A (300M~1GHZ)	Apr. 14, 1999	1384