

Red-M

Neptune House · Mercury Park · Wycombe Lane · Wooburn Green · Bucks · HP10 0HH

Tel: +44 (0)1628 819700 Fax: +44 (0)1628 819701

www.red-m.com



26/03/02

To Whom It May Concern,

Below is a declaration of the differences between the Madge Networks Smart Wireless Access Server and the Red-M 3000AS.

1. The Smart Wireless Access Server has a small backplane fitted to the PCI connector of the server motherboard.
2. The Smart Wireless Access Server has a Madge Networks Token Ring network interface card (NIC) fitted to the backplane, listed in 1 above, to allow connection of the server to Token Ring networks.
3. The Smart Wireless Access Server operating system detects the presence of the Token Ring NIC and automatically disables the 10/100 Office LAN Ethernet port.
4. The Smart Wireless Access Server plastic mouldings will be coloured silver with a red stripe and will be printed with the name Madge Networks, in red.

All other components in the Madge Networks Smart Wireless Access Server are identical to the Red-M 3000AS. No modifications have been made to the Bluetooth radio module from the version previously filed under FCC ID PEY3000AS2.

Yours sincerely,

A handwritten signature in black ink, appearing to read "Mark Bailey".

Mark Bailey
Senior Approvals Engineer
Red-M (Communications) Ltd.