

RF Exposure Report

Report No.: SABGSN-WTW-P20080589

FCC ID: NKS-PA1

Test Model: Trimble Gateway-PA1

Received Date: Aug. 29, 2020

Date of Evaluation: Oct. 28, 2020

Issued Date: Nov. 03, 2020

Applicant: PeopleNet Communications Corporation

Address: 4400 Baker Road, Minnetonka Minnesota 55343-8684 United States

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Lin Kou Laboratories

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City
33383, TAIWAN

**FCC Registration /
Designation Number:** 788550 / TW0003



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

Table of Contents

Release Control Record	3
1 Certificate of Conformity.....	4
2 General Information.....	5
3 RF Exposure.....	6
3.1 Limits for Maximum Permissible Exposure (MPE).....	6
3.2 MPE Calculation Formula	6
3.3 Classification	6
3.4 Calculation Result of Maximum Conducted Power.....	7

Release Control Record

Issue No.	Description	Date Issued
SABGSN-WTW-P20080589	Original Release	Nov. 03, 2020

1 Certificate of Conformity

Product: Trimble Gateway NA

Brand: Trimble

Test Model: Trimble Gateway-PA1

Sample Status: Engineering Sample

Applicant: PeopleNet Communications Corporation

Date of Evaluation: Oct. 28, 2020

Standards: FCC Part 2 (Section 2.1091)

References Test Guidance : KDB 447498 D01 General RF Exposure Guidance v06
IEEE C95.3 -2002

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

Prepared by : Vera Huang, **Date:** Nov. 03, 2020
Vera Huang / Specialist

Approved by : Dylan Chiou, **Date:** Nov. 03, 2020
Dylan Chiou / Senior Project Engineer

2 General Information

1. The information of module collocated in this EUT is listed as below.

Product	Brand Name	Model Name
BT/WLAN Module	msi	BM25
WWAN Module	Quectel	EC25-A
AH Module	silex	SX-NEWAH

2. The antenna information is listed as below.

WWAN Antenna								
Ant.	Brand	Model	Antenna Type	Antenna Gain (dBi)				Remark
				WDM II/LTE 2	WCDMA IV/LTE 4	WCDMA V	LTE 12	
1	TAOGLAS	PCS.06.A	SMD Antenna	3.58	3.82	0.53	-0.03	Internal, Main Antenna
2	TAOGLAS	PCS.06.B	SMD Antenna	3.81	4.04	0.75	0.06	Internal, Aux. Antenna
3	TAOGLAS	MA240.LBI.001	Adhesive Mount Combination Antenna	2.51	1.93	0.94	1.6	External, Main Antenna
4	TAOGLAS	MA240.LBI.001	Adhesive Mount Combination Antenna	1.77	1.2	1	1.2	External, Aux. Antenna

*the maximum antenna gain is chosen for final test.

WLAN Antenna						
Brand	Model	Antenna Type	Antenna Gain (dBi)			
			BT/WLAN 2.4 GHz	WLAN 5.15~5.35 GHz	WLAN 5.47~5.725 GHz	WLAN 5.725~5.85 GHz
TAOGLAS	FXP826.07.0120C	FPC Antenna	0.75	1.22	3.58	3.52

3. The above Antenna information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications, the laboratory shall not be held responsible.

3 RF Exposure

3.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	...	...	f/1500	30
1500-100,000	...	...	1.0	30

f = Frequency in MHz ; *Plane-wave equivalent power density

3.2 MPE Calculation Formula

$$Pd = (P_{out} * G) / (4 * \pi * r^2)$$

where

Pd = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

pi = 3.1416

r = distance between observation point and center of the radiator in cm

3.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

3.4 Calculation Result of Maximum Conducted Power

Band	Frequency Band (MHz)	Max Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
WCDMA II	1850-1910	22.66	3.81	20	0.088	1.00
WCDMA IV	1710-1755	22.57	4.04	20	0.091	1.00
WCDMA V	824-849	23.11	1	20	0.051	0.55
LTE 2	1850-1910	22.37	3.81	20	0.083	1.00
LTE 4	1710-1755	22.62	4.04	20	0.092	1.00
LTE 12	699-716	22.56	1.6	20	0.052	0.47
WLAN	2412-2462	18.45	0.75	20	0.017	1.00
	5180-5240	17.72	1.22	20	0.016	1.00
	5260-5320	17.83	1.22	20	0.016	1.00
	5500-5700	17.65	3.58	20	0.026	1.00
	5745-5825	17.56	3.52	20	0.026	1.00
BT	2402-2480	4.64	0.75	20	0.001	1.00

Note:

- Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

Conclusion:

The formula of calculated the MPE is:

$$CPD1 / LPD1 + CPD2 / LPD2 + \dots \text{etc.} < 1$$

CPD = Calculation power density

LPD = Limit of power density

$$WLAN\ 2.4GHz + WLAN\ 5GHz + BT + WWAN = 0.017/1 + 0.026/1 + 0.001/1 + 0.052/0.47 = 0.155$$

Therefore the maximum calculations of above situations are less than the “1” limit.

--- END ---