

Produkte
Products

Prüfbericht-Nr.: <i>Test Report No.:</i>	CN216EN7 001	Auftrags-Nr.: <i>Order No.:</i>	158225730	Seite 1 von 14 <i>Page 1 of 14</i>
Kunden-Referenz-Nr.: <i>Client Reference No.:</i>	N/A	Auftragsdatum: <i>Order date:</i>	20.01.2021	
Auftraggeber: <i>Client:</i>	Dickie Spielzeug GmbH & Co. KG Werkstrasse 1, D-90765 Fuerth, Germany			
Prüfgegenstand: <i>Test item:</i>	Short Range Device - Radio Controlled Toy Transmitter (2.4GHz)			
Bezeichnung / Typ-Nr.: <i>Identification / Type No.:</i>	24068			
Auftrags-Inhalt: <i>Order content:</i>	FCC Certification			
Prüfgrundlage: <i>Test specification:</i>	FCC Part 15 Subpart C, ANSI C63.10-2013			
Wareneingangsdatum: <i>Date of receipt:</i>	20.01.2021			
Prüfmuster-Nr.: <i>Test sample No.:</i>	A002986149-012			
Prüfzeitraum: <i>Testing period:</i>	20.01.2021– 24.03.2021			
Ort der Prüfung: <i>Place of testing:</i>	Hong Kong			
Prüflaboratorium: <i>Testing laboratory:</i>	TÜV Rheinland Hong Kong Ltd.			
Prüfergebnis*: <i>Test result*:</i>	Pass			
geprüft von / tested by:		kontrolliert von / reviewed by:		
 17.05.2021 Felicia Chan / Assistant Engineer		 17.05.2021 Sharon Li / Senior Manager		
Datum <i>Date</i>	Name / Stellung <i>Name / Position</i>	Unterschrift <i>Signature</i>	Datum <i>Date</i>	Name / Stellung <i>Name / Position</i>
Sonstiges / Other: FCC ID: NLB24068TX				
Zustand des Prüfgegenstandes bei Anlieferung: Prüfmuster vollständig und unbeschädigt <i>Condition of the test item at delivery:</i> Test item complete and undamaged				
* Legende: 1 = sehr gut 2 = gut 3 = befriedigend 4 = ausreichend 5 = mangelhaft P(ass) = entspricht o.g. Prüfgrundlage(n) F(ail) = entspricht nicht o.g. Prüfgrundlage(n) N/A = nicht anwendbar N/T = nicht getestet Legend: 1 = very good 2 = good 3 = satisfactory 4 = sufficient 5 = poor P(ass) = passed a.m. test specification(s) F(ail) = failed a.m. test specification(s) N/A = not applicable N/T = not tested				
Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens. <i>This test report only relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</i>				

Table of Content

Page

Cover Page	1
Table of Content	2
Product information	4
Manufacturers declarations	4
Product function and intended use	4
Submitted documents	4
Independent Operation Modes	4
Related Submittal(s) Grants	4
Remark	4
Test Set-up and Operation Mode	5
Principle of Configuration Selection	5
Test Operation and Test Software	5
Special Accessories and Auxiliary Equipment	5
Countermeasures to achieve EMC Compliance	5
Test Methodology	6
Radiated Emission	6
Field Strength Calculation	6
Test Setup Diagram	7
Test Facility	8
Test Laboratory Information	8
List of Test and Measurement Instruments	9
Measurement Uncertainty	10
Results FCC Part 15 – Subpart C	11
FCC 15.203 – Antenna Requirement 1	Pass 11
FCC 15.204 – Antenna Requirement 2	Pass 11
FCC 15.207 – Conducted Emission on AC Mains	N/A 11
Subclause 15.215 (c) – 20 dB Bandwidth	Pass 11
Subclause 15.249(a) – Field Strength of Fundamental and Harmonics	Pass 12
Subclause 15.249(d),15.205 – Out Of Band Radiated Emission	Pass 14
Appendix 1 – Test protocols	3 pages
Appendix 2 – Test setup	3 pages
Appendix 3 – EUT External Photos	2 pages

Appendix 4 – EUT Internal Photos 3 pages

Appendix 5 – RF exposure information..... 2 pages

Product information

Manufacturers declarations

	Transmitter
Operating frequency range	2410 - 2473MHz
Type of modulation	GFSK
Number of channels	3
Type of antenna	Integral Antenna
Power level	fix
Connection to public utility power line	No
Nominal voltage	3.0V DC

Product function and intended use

The equipment under test (EUT) is a radio control toy transmitter operating at 2.4GHz. It is powered by 2 x 1.5V AA batteries only.

FCC ID: NLB24068TX

Models	Product description
24068	Short Range Device - Radio Controlled Toy Transmitter (2.4GHz)

Submitted documents

Circuit Diagram
Block Diagram
Technical Description
User manual
Label

Independent Operation Modes

The basic operation modes are:

- Transmitting mode.-

For further information refer to User Manual

Related Submittal(s) Grants

This is a single application for certification of the transmitter.

Remark

The test results in this test report are only relevant to the tested sample and does not involve any assessment in the production.

Test Set-up and Operation Mode

Principle of Configuration Selection

Emission: The equipment under test (EUT) was configured to measure its highest possible radiation level. The test modes were adapted accordingly in reference to the instructions for use.

Test Operation and Test Software

Test operation should refer to test methodology.

- Test mode samples with maximum RF output power and duty cycle and capable to transmit continuously at the lowest, middle and highest frequency channels is provided by the applicant for the testing.

Special Accessories and Auxiliary Equipment

The product has been tested together with the following additional accessories:

- None

Countermeasures to achieve EMC Compliance

- None

Test Methodology

Radiated Emission

The radiated emission measurements of the transmitter part were performed according to the procedures in ANSI C63.10-2013.

For measurement below 1GHz - the equipment under test (EUT) was placed at the middle of the 80 cm height turntable. For measurement above 1GHz - the EUT was placed at the middle of the 1.5 m height turntable and RF absorbing material was placed on ground plane between turntable and measuring antenna. During the testing, the EUT was operated standalone and arranged for maximum emissions. The EUT was tested in three orthogonal planes.

The investigation is performed with the EUT rotated 360 °, the antenna height scanned between 1m and 4m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations. Repeat the measurement steps until the maximum emissions were obtained.

All radiated tests were performed at an antenna to EUT with 3 meters distance, unless stated otherwise in particular parts of this test report.

Field Strength Calculation

The field strength at 3 m was established by adding the meter reading of the spectrum analyzer to the factors associated with antenna correction factor, cable loss, preamplifiers and filter attenuation.

The equation is expressed as follow:


$$FS = R + AF + CF + FA - PA$$

Where FS = Field Strength in dBuV/m at 3 meters.
R = Reading of Spectrum Analyzer in dBuV.
AF = Antenna Factor in dB.
CF = Cable Attenuation Factor in dB.
FA = Filter Attenuation Factor in dB.
PA = Preamplifier Factor in dB.

FA and PA are only be used for the measuring frequency above 1 GHz.


Test Setup Diagram

Diagram of Measurement Configuration for Radiation Test



Note: Measurements above 1 GHz are done with a table height of 1.5m. In addition, there is RF absorbing material on the floor of the test site for above 1GHz measurement.

Diagram of Measurement Equipment Configuration for Mains Conduction Measurement (if applicable)



Test Facility

Test Laboratory Information

TÜV Rheinland Hong Kong Ltd.

Address: 3-4, 11/F., Fou Wah Industrial Building, 10-16 Pun Shan Street, Tsuen Wan, N.T., Hong Kong

Tel.: +852 2192 1000

Fax: +852 2192 1001

Email service-gc@tuv.com

Web: www.tuv.com

The test facility is recognized or accredited by the following organizations:

FCC

Type	: Accredited Test Firm
Designation Number	: HK0013
Test Firm Registration Number	: 371735
Scope	: Intentional Radiators

List of Test and Measurement Instruments

Radiated Emission

Equipment	Manufacturer	Type	Cal. Date	Due Date
Multi-functional Anechoic Chamber (SVSWR)	Albatross	N/A	04 Jan 21	04 Jan 22
Standard Gain Horn	ETS-Lindgren	3160-07	24 Nov 20	24 Nov 22
Standard Gain Horn	ETS-Lindgren	3160-08	24 Nov 20	24 Nov 22
Standard Gain Horn	ETS-Lindgren	3160-10	30 Nov 20	30 Nov 22
Double-Ridged Waveguide Horn	EMCO	3116	30 Nov 20	30 Nov 22
Double-Ridged Waveguide Horn	EMCO	3117	11 Nov 20	11 Nov 22
Test Receiver	R & S	ESU26	07 Oct 20	07 Oct 21
Coaxial cable	Huber+Suhner	SF118/11N/11N/12000MM	07 Jan 21	07 Jan 23
Microwave Preamplifier	COM-POWER Corporation	PAM-118A	06Mar 20	06 Mar 21
Preamplifier 18GHz to 40GHz with cable	A.H. Systems, Inc.	PAM-1840VH	29 Jan 21	29 Jan 22
High Pass Filter (cutoff freq. =1000MHz)	Trilithic	23042	30 Oct 19	30 Oct 21
High Frequency Cable	Pasternack	PE3VNA4001-3M	29 Jan 21	29 Jan 23
Multi-functional Anechoic Chamber (NSA)	Albatross	Nil	6-Jan-21	6-Jan-22
Bi-conical Antenna	R & S	HK116	15-Sep-20	15-Sep-22
Log Periodic Antenna	R & S	HL223	15-Sep-20	15-Sep-22
Coaxial cable	Huber+Suhner	SF118/11N/11N/12000MM	7-Jan-21	7-Jan-23
Active Loop Antenna	EMCO	6502	3-Nov-20	3-Nov-22

Radio Test

Equipment	Manufacturer	Type	Cal. Date	Due Date
Spectrum Analyzer	R & S	FSV40	21 Jan 21	21 Jan 22

Measurement Uncertainty

The estimated combined standard uncertainty for power-line conducted emissions measurements is $\pm 2.42\text{dB}$.

The estimated combined standard uncertainty for radiated emissions measurements is $\pm 4.81\text{dB}$ (9kHz to 30MHz) and $\pm 4.62\text{dB}$ (30MHz to 200MHz) and $\pm 5.67\text{dB}$ (200MHz to 1000MHz) and is $\pm 5.07\text{dB}$ (1GHz to 8.2GHz) and $\pm 4.58\text{dB}$ (8.2GHz to 12.4GHz) and $\pm 4.78\text{dB}$ (12.4GHz to 18GHz)

The reported expanded uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor of $k=2$, which for the level of confidence is approximately 95%.

Results FCC Part 15 – Subpart C

FCC 15.203 – Antenna Requirement 1		Pass
FCC Requirement: No antenna other than that furnished by the responsible party shall be used with the device		
Results:	a) Antenna type: Fixed Integral wire antenna b) Manufacturer and model no: N/A c) Peak Gain: 0 dBi	
Verdict:	Pass	

FCC 15.204 – Antenna Requirement 2		Pass
FCC Requirement: An intentional radiator may be operated only with the antenna with which it is authorized. If an antenna is marketed with the intentional radiator, it shall be of a type which is authorized with the intentional radiator.		
Results:	Only one integral antenna can be used.	
Verdict:	N/A	

FCC 15.207 – Conducted Emission on AC Mains		N/A
There is no AC power input or output ports on the EUT.		

Subclause 15.215 (c) – 20 dB Bandwidth				Pass
Test Specification : ANSI C63.10 – 2013 Test date : 24.03.2021 Mode of operation : Tx mode Port of testing : Antenna port Supply voltage : 3.0V DC Temperature : 23°C Humidity : 50%				
Requirement:		The intentional radiators must be designed to ensure that the 20dB bandwidth of the emission, is contained within the frequency band designated in the rule section under which the equipment is operated.		
Results:		Pre-scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and packet types. For test protocols refer to Appendix 1.		
Frequency (MHz)	20 dB left (MHz)	Limit (MHz)	20 dB right (MHz)	Limit (MHz)
2410	2409.31	> 2400	2410.74	< 2483.5
2442	2441.27	> 2400	2442.74	< 2483.5
2473	2472.26	> 2400	2473.76	< 2483.5

Subclause 15.249(a) – Field Strength of Fundamental and Harmonics			Pass
Test Specification : ANSI C63.10 – 2013 Test date : 20.01.2021, 27.01.2021 Mode of operation : Tx mode Port of testing : Enclosure Frequency range : 9kHz – 25GHz Supply voltage : 3.0V DC Temperature : 25°C Humidity : 56%			
Requirement: The field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following limit.			
Results: PASS.			
Fundamental Frequency 2410MHz		Vertical Polarization	
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m	
2410.001	66.2	114.0 / PK	
2410.001	66.0	94.0 / AV	
Fundamental Frequency 2410MHz		Horizontal Polarization	
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m	
2410.003	64.2	114.0 / PK	
2410.003	63.9	94.0 / AV	
Harmonics 2410MHz		Vertical Polarization	
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m	
4820.007	48.1	74.0 / PK	
4820.007	43.2	54.0 / AV	
Harmonics 2410MHz		Horizontal Polarization	
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m	
4820.007	49.4	74.0 / PK	
4820.007	46.5	54.0 / AV	
Fundamental Frequency 2442MHz		Vertical Polarization	
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m	
2442.003	67.0	114.0 / PK	
2442.003	66.8	94.0 / AV	
Fundamental Frequency 2442MHz		Horizontal Polarization	
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m	
2443.003	51.5	114.0 / PK	
2443.003	48.7	94.0 / AV	
Harmonics 2442MHz		Vertical Polarization	
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m	
4884.003	48.4	74.0 / PK	

4884.003	43.4	54.0 / AV
Harmonics 2442MHz Horizontal Polarization		
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
4884.004	51.5	74.0 / PK
4884.004	48.7	54.0 / AV
Fundamental Frequency 2473MHz Vertical Polarization		
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
2473.003	68.8	114.0 / PK
2473.003	68.6	94.0 / AV
Fundamental Frequency 2473MHz Horizontal Polarization		
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
2473.003	64.9	114.0 / PK
2473.003	64.6	94.0 / AV
Harmonics 2473MHz Vertical Polarization		
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
4946.007	48.6	74.0 / PK
4946.007	44.2	54.0 / AV
Harmonics 2473MHz Horizontal Polarization		
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
4946.008	52.1	74.0 / PK
4946.008	49.5	54.0 / AV

Subclause 15.249(d), 15.205 – Out Of Band Radiated Emission		Pass
Test Specification : ANSI C63.10 – 2013 Test date : 20.01.2021, 27.01.2021 Mode of operation : Tx mode Port of testing : Enclosure Frequency range : 9kHz – 25GHz Supply voltage : 3.0V DC Temperature : 25°C Humidity : 56%		
Requirement: Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation.		
Results: All three transmit frequency modes comply with the field strength limit of section 15.209. There is no spurious found below 30MHz.		
Tx frequency 2410MHz Vertical Polarization		
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
2390.000	39.6	74.0 / PK
2390.000	25.4	54.0 / AV
2400.000	38.8	74.0 / PK
2400.000	25.3	54.0 / AV
Tx frequency 2410MHz Horizontal Polarization		
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
2390.000	38.9	74.0 / PK
2390.000	25.6	54.0 / AV
2400.000	38.8	74.0 / PK
2400.000	25.4	54.0 / AV
Tx frequency 2442MHz Vertical Polarization		
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
No peak found	---	74.0 / PK
No peak found	---	54.0 / AV
Tx frequency 2442MHz Horizontal Polarization		
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
No peak found	---	74.0 / PK
No peak found	---	54.0 / AV
Tx frequency 2473MHz Vertical Polarization		
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
2483.500	39.0	74.0 / PK
2483.500	25.5	54.0 / AV
Tx frequency 2473MHz Horizontal Polarization		
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
2483.500	39.5	74.0 / PK
2483.500	25.8	54.0 / AV