

Produkte
Products

Prüfbericht - Nr.: 14031620 001

Test Report No.:

Seite 1 von 10

Page 1 of 10

Auftraggeber: **Dickie Toys Hong Kong Ltd.**

Client:

19/F., Prudential Tower, The Gateway, Harbour City, 21 Canton Road,
Tsimshatsui, Kowloon, Hong Kong

Gegenstand der Prüfung: **Short Range Device - RC Toy Walkie Talkie (27.145MHz)**

Test Item:

Bezeichnung: Please refer to "Models" on
Identification: page 5 **Serien-Nr.:** **Engineering sample**

Wareneingangs-Nr.: 00121112184-001 **Eingangsdatum:** 12.11.2012
Receipt No.: *Date of Receipt:*

Zustand des Prüfgegenstandes bei Anlieferung: Test samples received are sufficient for testing
Condition of test item at delivery: and not damaged.

Prüfort: **TÜV Rheinland Hong Kong Ltd.**
Testing Location: 8/F., First Group Centre, 14 Wang Tai Road, Kowloon Bay, Kowloon, Hong Kong
Hong Kong Productivity Council
HKPC Building, 78 Tat Chee Avenue, Kowloon, Hong Kong

Prüfgrundlage: **FCC Part 15, Subpart C**
Test Specification: **ANSI C63.4-2003**
CISPR 22:1997

Prüfergebnis: **Der Prüfgegenstand entspricht oben genannter Prüfgrundlage(n).**
Test Result: The test item passed the test specification(s).

Prüflaboratorium: **TÜV Rheinland Hong Kong Ltd.**
Testing Laboratory: 8 - 10/F., Goldin Financial Global Square, 7 Wang Tai Road, Kowloon Bay,
Kowloon, Hong Kong

geprüft / tested by: **kontrolliert / reviewed by:**

25.11.2013 Joey Leung
Project Engineer



25.11.2013 Sharon Li
Section Manager



Datum **Name/Stellung** **Unterschrift** **Datum** **Name/Stellung** **Unterschrift**
Date *Name/Position* *Signature* *Date* *Name/Position* *Signature*

Sonstiges / Other Aspects:

FCC ID: NLB27073TX-RX

Abkürzungen: **P(pass)** = entspricht Prüfgrundlage
F(fail) = entspricht nicht Prüfgrundlage
N/A = nicht anwendbar
N/T = nicht getestet

Abbreviations: **P(pass)** = passed
F(fail) = failed
N/A = not applicable
N/T = not tested

Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens.
This test report relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any safety mark on this or similar products.

Contents

List of Test and Measurement Instruments.....	3
General Product Information	4
Product Function and Intended Use.....	4
Ratings and System Details.....	4
Independent Operation Modes.....	5
Submitted Documents	5
Related Submittal(s) Grants	5
Test Set-up and Operation Mode.....	6
Principle of Configuration Selection	6
Test Operation and Test Software	6
Special Accessories and Auxiliary Equipment	6
Countermeasures to achieve EMC Compliance	6
Test Methodology	7
Radiated Emission.....	7
Field Strength Calculation	7
Test Results	8
Subclause 15.203 – Antenna Requirement	Pass8
Subclause 15.215(c) – Bandwidth Measurement	Pass8
Subclause 15.227(a) – Radiated Emission of Carrier Frequency.....	Pass9
Subclause 15.227(b) – Spurious Radiated Emissions	Pass10

Appendix 1 Test Protocol

Appendix 2 Test Setup

Appendix 3 EUT External Photo

Appendix 4 EUT Internal Photo

Appendix 5 FCCID Label, Block Diagram, Schematics, BOM and User manual

List of Test and Measurement Instruments

Hong Kong Productivity Council (Registration number: 90656)

Radiated Emission

Equipment used	Manufacturer	Model No.	S/N	Due Date
Semi-anechoic Chamber	Frankonia	Nil	Nil	12 Apr 2014
New Fully Anechoic Chamber	TDK	N/A	N/A	30 Apr 2014
Cable	Hubersuhner	SUCOFLEX 104	72799 /6	30 Mar 2014
Test Receiver	R & S	ESU40	100190	19 Feb 2014
Bi-conical Antenna	R & S	HK116	100242	11 Jun 2015
Log Periodic Antenna	R & S	HL223	841516/020	10 Jun 2015
Coaxial cable 50ohm	Rosenberger	RTK081-05S-05S-10m	LA2-001-10M / 001	15 Nov 2015
Microwave amplifier 0.5-26.5GHz, 25dB gain	HP	83017A	3123A00437	03 Oct 2015
High Pass Filter (cutoff freq. =1000MHz)	Trilithic	23042	9829213	28 Oct 2015
Horn Antenna	EMCO	3115	9002-3351	11 Jun 2015
Active Loop Antenna	EMCO	6502	9107-2651	21 Dec 2013
FSP 30 Spectrum Analyser	R & S	FSP 30	100007/030	03 Dec 2014

General Product Information

Product Function and Intended Use

The equipment under test (EUT) is a RC toy walkie talkie operating at 27.145MHz. The EUT has a rotational switch and 3 push buttons.

FCC ID: NLB27073TX-RX

Models	Product description
20 111 8175, 20 945 9317	Radio Control Toy Walkie Talkie

Ratings and System Details

	Transmitter
Frequency range	: 27.145MHz
Number of channels	: 1
Type of antenna	: External Permanent Antenna
Power supply	: Battery operated 9V
Ports	: none
Protection Class	: III

www.tuv.com

Independent Operation Modes

The basic operation modes are:

- Transmitting voice for the RC toy Walkie Talkie.

For further information refer to User Manual

Submitted Documents

The submitted documents are listed as follow:

- Circuit diagram
- Block diagram
- User manual
- Label artwork
- Bill of material

Related Submittal(s) Grants

This is a single application for certification of the transmitter.

Test Set-up and Operation Mode

Principle of Configuration Selection

Emission: The equipment under test (EUT) was configured to measure its highest possible radiation level. The test modes were adapted accordingly in reference to the instructions for use.

Test Operation and Test Software

Test operation should refer to test methodology.

- There was no special software to exercise the device.

Special Accessories and Auxiliary Equipment

The product has been tested together with the following additional accessories:

- none

Countermeasures to achieve EMC Compliance

- none

Test Methodology

Radiated Emission

The radiated emission measurements were performed according to the procedures in ANSI C63.4-2003.

The equipment under test (EUT) was placed at the middle of the 80 cm height turntable, and the turntable is 3 meters far from the measuring antenna. During the testing, the EUT was operated standalone and arranged for maximum emissions. The EUT was tested in three orthogonal planes.

The investigation is performed with the EUT rotated 360 °, the antenna height scanned between 1m and 4m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations. Repeat the measurement steps until the maximum emissions were obtained.

All radiated tests were performed at an antenna to EUT with 3 meters distance, unless stated otherwise in particular parts of this test report.

Field Strength Calculation

The field strength at 3 m was established by adding the meter reading of the spectrum analyzer to the factors associated with antenna correction factor, cable loss, preamplifiers and filter attenuation.

The equation is expressed as follow:

$$FS = R + AF + CF + FA - PA$$

Where FS = Field Strength in dBuV/m at 3 meters.

R = Reading of Spectrum Analyzer in dBuV.

AF = Antenna Factor in dB.

CF = Cable Attenuation Factor in dB.

FA = Filter Attenuation Factor in dB.

PA = Preamplifier Factor in dB.

FA and PA are only be used for the measuring frequency above 1 GHz.

www.tuv.com

Test Results

Subclause 15.203 – Antenna Requirement Pass

Requirement : No antenna other than that furnished by the responsible party shall be used with the device

Result : Permanent attached antenna

Subclause 15.215(c) – Bandwidth Measurement Pass

Port of Testing : Antenna port
Detector Function : Peak
Supply Voltage : DC 9V

The field strength of any emissions appearing at the lower edge 26.96 MHz and upper edge 27.28 MHz are 68.92 dB and 67.65 dB below the carrier respectively.

For test results refer to Appendix 1.

Subclause 15.227(a) – Radiated Emission of Carrier Frequency
Pass

Test Specification	:	FCC Part 15 Subclause 15.227(a)
Test Method	:	ANSI 63.4-2003
Measurement Location	:	Semi Anechoic Chamber
Measurement Distance	:	3m
Detector Function	:	Peak and Average
Measurement BW	:	120 kHz
Supply Voltage	:	DC 9V

Polarization: Vertical

Detector function	Frequency (MHz)	Measured Field strength at 3m (dB μ V/m)	Delta to Limit (dB)
Peak	27.144	70.3	-29.7
Average	27.144	70.1	-9.9

Polarization: Horizontal

Detector function	Frequency (MHz)	Measured Field strength at 3m (dB μ V/m)	Delta to Limit (dB)
Peak	27.144	48.4	-51.6
Average	27.144	48.1	-31.9

Limit
Subclause 15.227(a)

Frequency within the band	Peak Emission		Average Emission	
	(μ V/m)	dB μ V/m	(μ V/m)	dB μ V/m
26.96-27.28 MHz	100,000	100.0	10,000	80.0

According to section 15.35(b), when average radiated emission measurements are specified in this part, including average emission measurements below 1000 MHz, there also is a limit on the peak level of the radio frequency emissions. Unless otherwise specified, the limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit applicable to the equipment under test.

Subclause 15.227(b) – Spurious Radiated Emissions
Pass

Test Specification	:	FCC Part 15 Subclause 15.209
Test Method	:	ANSI 63.4-2003
Measurement Location	:	Semi Anechoic Chamber
Measurement Distance	:	3m
Detector Function	:	Quasi Peak
Measurement BW	:	120 kHz
Supply Voltage	:	DC 9V
Measuring Frequency Range	:	30-1000MHz

Polarization: Vertical

Frequency (MHz)	Field strength at 3m (dB _u V/m)	Limit at 3m (dB _u V/m)	Delta to Limit (dB)
No peak found	---	40.0	---

Polarization: Horizontal

Frequency (MHz)	Field strength at 3m (dB _u V/m)	Limit at 3m (dB _u V/m)	Delta to Limit (dB)
No peak found	---	40.0	---

Remark: (1) ‘*’ indicates the frequency of the emissions fall into the restricted band as defined in Section 15.205(a). They comply with the radiated emission limits specified in Section 15.209.
 (2) There is no spurious emission found between lowest oscillating frequency to 30 MHz.

Limit
Subclause 15.209

Radiated emissions, which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209.

Limit for Radiated Emission under Section 15.209:

Frequency (MHz)	Field strength (μ V/m)	Field strength (dB μ V/m)	Measurement distance (m)
30-88	100	$20 \log(100) = 40.0$	3
88-216	150	$20 \log(150) = 43.5$	3
216-960	200	$20 \log(200) = 46.0$	3
960-2500	500	$20 \log(500) = 54.0$	3

The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector and above 1000 MHz are based on the measurements employing an average detector.