

## TABLE OF CONTENTS

APPLICANT: TOYMAX INC.

FCC ID: NLKTM13308027

### TEST REPORT CONTAINING:

PAGE 1.....TEST EQUIPMENT LIST AND TEST PROCEDURE  
PAGE 2.....TEST PROCEDURE CONTD.  
PAGE 3.....RADIATION INTERFERENCE TEST DATA  
PAGE 4.....OCCUPIED BANDWIDTH TEST DATA  
PAGE 5.....OCCUPIED BANDWIDTH PLOT

### EXHIBITS CONTAINING:

EXHIBIT 1.....BLOCK DIAGRAM  
EXHIBIT 2.....SCHEMATIC  
EXHIBIT 3A-B.....INSTRUCTION MANUAL  
EXHIBIT 4.....SAMPLE OF FCC ID LABEL  
EXHIBIT 5.....LOCATION OF FCC ID LABEL  
EXHIBIT 6.....EXTERNAL PHOTO - FRONT SIDE  
EXHIBIT 7.....EXTERNAL PHOTO - BACK SIDE  
EXHIBIT 8.....INTERNAL PHOTO - COMPONENT SIDE  
EXHIBIT 9.....INTERNAL PHOTO - COPPER SIDE  
EXHIBIT 10.....CIRCUIT DESCRIPTION  
EXHIBIT 11.....TEST SETUP PHOTO

APPLICANT: TOYMAX INC.

FCC ID: NLKTM13308027

REPORT #: T\TOYMAX\490U1\490U1RPT.doc

PAGE: TABLE OF CONTENTS LIST

APPLICANT: TOYMAX INC.  
FCC ID: NLKTM13308027

#### TEST EQUIPMENT LIST

1. X Spectrum Analyzer: HP 8566B-Opt 462, S/N 3138A07786, w/  
preselector HP 85685A, S/N 3221A01400, Quasi-Peak Adapter  
HP 85650A, S/N 3303A01690 & Preamplifier HP 8449B-OPT H02,  
S/N 3008A00372 Cal. 10/17/99
2. X Biconnical Antenna: Eaton Model 94455-1, S/N 1057
3.    Biconnical Antenna: Electro-Metrics Model BIA-25, S/N 1171
4. X Log-Periodic Antenna: Electro-Metrics Model EM-6950, S/N 632
5.    Log-Periodic Antenna: Electro-Metrics Model LPA-30, S/N 409
6.    Double-Ridged Horn Antenna: Electro-Metrics Model RGA-180,  
1-18 GHz, S/N 2319
7.    18-26.3GHz Systron Donner Standard Gain Horn #DBE-520-20
8.    Horn 40-60GHz: ATM Part #19-443-6R
9.    Line Impedance Stabilization Network: Electro-Metrics Model  
ANS-25/2, S/N 2604 Cal. 2/9/00
10.    Temperature Chamber: Tenney Engineering Model TTRC, S/N 11717-7
11.    Frequency Counter: HP Model 5385A, S/N 3242A07460 Cal 10/6/99
12.    Peak Power Meter: HP Model 8900C, S/N 2131A00545
13. X Open Area Test Site #1-3meters Cal. 12/22/99
14.    Signal Generator: HP 8640B, S/N 2308A21464 Cal. 9/23/99
15.    Signal Generator: HP 8614A, S/N 2015A07428
16.    Passive Loop Antenna: EMCO Model 6512, 9KHz to 30MHz, S/N  
9706-1211 Cal. 6/10/00
17.    Dipole Antenna Kit: Electro-Metrics Model TDA-30/1-4, S/N 153  
Cal. 11/24/99
18.    AC Voltmeter: HP Model 400FL, S/N 2213A14499 Cal. 9/21/99
19.    Digital Multimeter: Fluke Model 8012A, S/N 4810047 Cal 9/21/99
20.    Digital Multimeter: Fluke Model 77, S/N 43850817 Cal 9/21/99
21.    Oscilloscope: Tektronix Model 2230, S/N 300572 Cal 9/23/99

#### TEST PROCEDURE

GENERAL: This report shall NOT be reproduced except in full without  
the written approval of TIMCO ENGINEERING, INC.

RADIATION INTERFERENCE: The test procedure used was ANSI STANDARD C63.4-1992 using a HEWLETT PACKARD spectrum analyzer with a preselector. The bandwidth of the spectrum analyzer was 100 kHz with an appropriate sweep speed. The analyzer was calibrated in dB above a microvolt at the output of the antenna. The resolution bandwidth was 100KHz and the video bandwidth was 300KHz. The ambient temperature of the UUT was 80° with a humidity of 45%.

APPLICANT: TOYMAX INC.  
FCC ID: NLKTM13308027  
REPORT #: T\TOYMAX\490U1\490U1RPT.doc  
PAGE #: 1

APPLICANT: TOYMAX INC.  
FCC ID: NLKTM13308027

TEST PROCEDURES CONTINUED

FORMULA OF CONVERSION FACTORS: The Field Strength at 3m was established by adding the meter reading of the spectrum analyzer (which is set to read in units of dBuV) to the antenna correction factor supplied by the antenna manufacturer. The antenna correction factors are stated in terms of dB. The gain of the Preselector was accounted for in the Spectrum Analyzer Meter Reading.

Example:

Freq (MHz) METER READING + ACF = FS  
33 20 dBuV + 10.36 dB = 30.36 dBuV/m @ 3m

ANSI STANDARD C63.4-1992 10.1.7 MEASUREMENT PROCEDURES: The unit under test was placed on a table 80 cm high and with dimensions of 1m by 1.5m. The table used for radiated measurements is capable of continuous rotation.

When an emission was found, the table was rotated to produce the maximum signal strength. At this point, the antenna was raised and lowered from 1m to 4m. The antenna was placed in both the horizontal and vertical planes.

APPLICANT: TOYMAX INC.

FCC ID: NLKTM13308027

NAME OF TEST: RADIATION INTERFERENCE

RULES PART NO.: 15.227

REQUIREMENTS: CARRIER FREQUENCY WILL NOT EXCEED 80 dBuV/m AT 3M.  
OUT-OF-BAND EMISSIONS SHALL NOT EXCEED:

30 - 88 MHz	40.0 dBuV/M	MEASURED AT 3 METERS
88 - 216 MHz	43.5 dBuV/M	
216 - 960 MHz	46.0 dBuV/M	
ABOVE 960 MHz	54.0 dBuV/M	

TEST DATA:

Emission Frequency MHz	Meter Reading dBuv	Ant. Polarity	Coax Loss dB	Correction Factor dB	Field Strength dBuV/m	Margin dB
27.1	56.5	V	0.60	10.25	67.35	12.65
54.3	15.5	V	0.90	7.75	23.75	16.25
81.4	19.1	V	1.10	12.90	33.10	6.90
108.6	6.5	V	1.30	11.35	19.15	24.35
135.7	10.7	H	1.40	16.90	29.00	14.50
162.9	8.5	V	1.60	16.67	26.77	16.73
190.0	11.3	V	1.80	12.60	25.70	17.80
244.3	5.8	V	2.00	13.77	21.57	24.43
271.4	3.9	V	2.20	15.50	21.60	24.40

SAMPLE CALCULATION:  $FSdBuV/m = MR(dBuV) + ACFdB$ .

TEST PROCEDURE: The procedure used was ANSI STANDARD C63.4-1992. The spectrum was scanned from 30 MHz to 1000 MHz. When an emission was found, the table was rotated to produce the maximum signal strength. The antenna was placed in both the horizontal and vertical planes and the worse case emissions were reported. The UUT was tested in 3 orthogonal planes.

TEST RESULTS: THE UNIT DOES MEET THE FCC REQUIREMENTS.

PERFORMED BY: JOSEPH SCOGLIO

DATE: MAY 9, 2001

APPLICANT: TOYMAX INC.  
FCC ID: NLKTM13308027  
REPORT #: T\TOYMAX\490U1\490U1RPT.doc  
PAGE #: 3

APPLICANT: TOYMAX INC.

FCC ID: NLKTM13308027

NAME OF TEST: Occupied Bandwidth

RULES PART NO.: 15.227

REQUIREMENTS: The field strength of any emissions appearing outside the 26.96-27.28 MHz band shall not exceed the general radiated emission limits in (15.209).

THE GRAPH ON THE FOLLOWING PAGE REPRESENTS THE WORSE CASE OCCUPIED BANDWIDTH EMISSIONS FOR THIS DEVICE.

METHOD OF MEASUREMENT: A small sample of the transmitter output was fed into the spectrum analyzer and the attached plot was taken. The vertical scale is set to -10 dBm per division. The horizontal scale is set to 5 kHz per division.

TEST RESULTS: The unit DOES meet the FCC requirements.

PERFORMED BY: JOSEPH SCOGLIO

APPLICANT: TOYMAX INC.  
FCC ID: NLKTM13308027  
REPORT #: T\TOYMAX\490U1\490U1RPT.doc  
PAGE #: 4


HP

REF 57.3 dB $\mu$ V

ATTEN 10 dB +0 dB

10 dB/

OFFSET  
-20.0  
dB



CENTER 27.14500 MHz

RES BW 300 Hz

VBW 100 kHz

MKR 27.14520 MHz

57.30 dB $\mu$ V

TOYMAX INC

JOB #: 490U1

FCC ID : NLKTM13308027

PAGE : 5

SPAN 50.00 kHz

SWP 1.0 sec