

TABLE OF CONTENTS LIST

APPLICANT: TOYMAX, INC.

FCC ID: NLKTM18089927

TEST REPORT CONTAINING:

PAGE 1-2.....TEST PROCEDURE

PAGE 3.....CIRCUIT DESCRIPTION

PAGE 4.....RADIATION INTERFERENCE TEST DATA

PAGE 5.....OCCUPIED BANDWIDTH TEST DATA

EXHIBIT ATTACHMENTS

EXHIBIT 1.....POWER OF ATTORNEY LETTER

EXHIBIT 2.....BLOCK DIAGRAM

EXHIBIT 3.....SCHEMATIC

EXHIBIT 4.....PARTS LIST

EXHIBIT 5.....SAMPLE OF FCC ID LABEL

EXHIBIT 6.....LOCATION OF FCC ID LABEL

EXHIBIT 7A-7B.....INSTRUCTION MANUAL

EXHIBIT 8.....FRONT VIEW EXTERNAL PHOTOGRAPH

EXHIBIT 9.....BACK VIEW EXTERNAL PHOTOGRAPH

EXHIBIT 10.....COMPONENT SIDE INTERNAL PHOTOGRAPH

EXHIBIT 11.....COPPER SIDE INTERNAL PHOTOGRAPH

EXHIBIT 12.....OCCUPIED BANDWIDTH PLOT - CW

EXHIBIT 13.....OCCUPIED BANDWIDTH PLOT - LOUD VOICE

EXHIBIT 14.....OCCUPIED BANDWIDTH PLOT - MODULATION

REPORT #: F:\CUS\T\TOYMAX\TOY140U8.RPT

PAGE: TABLE OF CONTENTS

APPLICANT: TOYMAX, INC.
FCC ID: NLKTM18089927

TEST EQUIPMENT LIST

1. Spectrum Analyzer: Hewlett Packard 8566B, with preselector HP 85685A, & Quasi-Peak Adapter HP 85650A, & HP 8449B OPT H02
Cal. 9/30/97
2. Eaton Biconnical Antenna Model 94455-1
20-200 MHz Serial No. 0997 Cal. 9/17/97
3. Electro-Metric Dipole Kit, 20-1000 MHz, Model TDA 25 cal. 5/15/97
4. Electro-Metric Horn 1-18 GHz, Model RGA-180, Cal. 9/24/97
5. Electro-Metric Antennas Model TDS-25-1, TDS-25-2, 9/3/97
6. Electro-Metric Line Impedance Stabilization Network Model
No. EM-7821, Serial No. 101; 100KHz-30MHz 50uH. 9/30/97
7. Electro-Metric Line Impedance Stabilization Network Model
No. EM-7820, Serial No. 2682; 10KHz-30MHz 50uH. 9/30/97

TEST PROCEDURE

GENERAL: This report shall NOT be reproduced except in full without the written approval of TIMCO ENGINEERING, INC.

RADIATION INTERFERENCE: The test procedure used was ANSI STANDARD C63.4-1992 using a HEWLETT PACKARD spectrum analyzer with a preselector. The bandwidth of the spectrum analyzer was 100 kHz with an appropriate sweep speed. The analyzer was calibrated in dB above a microvolt at the output of the antenna. The resolution bandwidth was 100KHz and the video bandwidth was 300KHz. The ambient temperature of the UUT was 81.9% with a humidity of 57%.

FORMULA OF CONVERSION FACTORS: The Field Strength at 3m was established by adding the meter reading of the spectrum analyzer (which is set to read in units of dBuV) to the antenna correction factor supplied by the antenna manufacturer. The antenna correction factors are stated in terms of dB. The gain of the Preselector was accounted for in the Spectrum Analyzer Meter Reading.

Example:

Freq (MHz) METER READING + ACF = FS
33 20 dBuV + 10.36 dB = 30.36 dBuV/m @ 3m

APPLICANT: TOYMAX, INC.
FCC ID: NLKTM18089927
REPORT #: F:\CUS\T\TOYMAX\TOY140U8.RPT
PAGE #: 1

TEST PROCEDURES CONTINUED

APPLICANT: TOYMAX, INC.
FCC ID: NLKTMI8089927

ANSI STANDARD C63.4-1992 10.1.7 MEASUREMENT PROCEDURES: The unit under test was placed on a table 80 cm high and with dimensions of 1m by 1.5m. The table used for radiated measurements is capable of continuous rotation.

When an emission was found, the table was rotated to produce the maximum signal strength. At this point, the antenna was raised and lowered from 1m to 4m. The antenna was placed in both the horizontal and vertical planes.

The situation was similar for the conducted measurement except that the table did not rotate. The EUT was setup as described in ANSIC63.4-1992 with the EUT 40 cm from the vertical ground wall.

APPLICANT: TOYMAX, INC.
FCC ID: NLKTMI8089927
REPORT #: F:\CUS\T\TOYMAX\TOY140U8.RPT
PAGE #: 2

APPLICANT: TOYMAX, INC.

FCC ID: NLKTM18089927

CIRCUIT DESCRIPTION:

In the transmit mode the momentary switches SW2, SW3, SW4, SW5, SW6, SW7, SW8, SW9, SW10, & SW11 provide input to the encoder integrated circuit - U1. The output of U1 modulates the RF output stage Q2 & Q3 by varying the emitter current. The crystal oscillator Q2 is coupled to the modulated stage Q3 via C5/C6. From Q2 the signal is fed through a doubled tuned circuit consisting of L1, L2, C13 & C15 and then to the filter made up of C8, C10, C11, L3 & L4. The output of the filter is connected to the antenna.

ANTENNA AND GROUND CIRCUITRY

This unit makes use of a external 10" whip antenna. The antenna is inductively coupled. This unit is powered from a 9.0V battery.

No ground connection is provided. The unit relies on the ground tract of the printed circuit board.

APPLICANT: TOYMAX, INC.
FCC ID: NLKTM18089927
REPORT #: F:\CUS\T\TOYMAX\TOY140U8.RPT
PAGE #: 3

APPLICANT: TOYMAX, INC.

FCC ID: NLKTM18089927

NAME OF TEST: RADIATION INTERFERENCE

RULES PART NO.: 15.227

REQUIREMENTS: CARRIER FREQUENCY WILL NOT EXCEED 80 dBuV/m AT 3M.
OUT-OF-BAND EMISSIONS SHALL NOT EXCEED:

30 - 88 MHz	40.0 dBuV/M MEASURED AT 3 METERS
88 - 216 MHz	43.5 dBuV/M
216 - 960 MHz	46.0 dBuV/M
ABOVE 960 MHz	54.0 dBuV/M

TEST DATA:

EMISSION FREQUENCY MHz	METER READING AT 3 METERS dBuV	COAX LOSS dB	ANTENNA CORRECTION FACTOR dB	FIELD STRENGTH dBuV/m@3m	MARGIN dB	ANT. POL.
27.15	54.90	0.20	11.75	66.85	13.15	V
54.29	19.70	0.80	9.61	30.11	9.89	H
81.44	23.70	0.80	12.13	39.43	0.57	H
108.58	12.80	0.80	8.38	21.98	21.52	H
135.73	14.70	0.80	15.32	30.82	12.68	H
162.87	8.60	0.90	17.17	26.67	16.83	H
190.02	9.10	0.90	13.67	23.67	19.83	H
217.16	22.10	1.20	12.42	35.72	10.28	H
244.31	21.90	1.20	13.21	36.31	9.69	H
271.45	16.60	1.40	14.00	32.00	14.00	H
298.60	15.00	1.40	15.61	32.01	13.99	H
325.74	9.90	1.40	14.85	26.15	19.85	H
352.89	6.10	1.40	15.63	23.13	22.87	H
380.03	4.60	1.40	16.42	22.42	23.58	V
407.18	6.10	1.60	17.17	24.87	21.13	V

SAMPLE CALCULATION:

$F_{SdBuV/m} = MR(dBuV) + ACFdB$.

TEST PROCEDURE: The procedure used was ANSI STANDARD C63.4-1992. The spectrum was scanned from 30 MHz to 1000 MHz. When an emission was found, the table was rotated to produce the maximum signal strength. The antenna was placed in both the horizontal and vertical planes and the worse case emissions were reported. The UUT was tested in 3 orthogonal planes.

TEST RESULTS: THE UNIT DOES MEET THE FCC REQUIREMENTS.

PERFORMED BY: S. S. SANDERS

DATE: JUNE 10, 1998

REPORT #: F:\CUS\T\TOYMAX\TOY140U8.RPT

PAGE #: 4

APPLICANT: TOYMAX, INC.
FCC ID: NLKTM18089927
NAME OF TEST: Occupied Bandwidth
RULES PART NO.: 15.227
REQUIREMENTS: The field strength of any emissions appearing between the band edges and up to 10 kHz above and below the band edges shall be attenuated at least 26 dB below the level of the unmodulated carrier or to the general limits of 15.209, whichever permits the higher emission levels.

THE PLOTS IN EXHIBITS 13-15 REPRESENT THE EMISSIONS TAKEN FOR THE DEVICE.

METHOD OF MEASUREMENT: A small sample of the transmitter output was fed into the spectrum analyzer and the attached plot was taken. The vertical scale is set to -10 dBm per division. The horizontal scale is set to 5 kHz per division.

TEST RESULTS: The unit DOES meet the FCC requirements.

PERFORMED BY: S. S. SANDERS

JUNE 10, 1998

APPLICANT: TOYMAX, INC.
FCC ID: NLKTM18089927
REPORT #: F:\CUS\T\TOYMAX\TOY140U8.RPT
PAGE #: 5