



# FCC TEST REPORT (PART 22)

**REPORT NO.:** RF150324C14  
**MODEL NAME:** 0PM9110  
**FCC ID:** NM80PM9110  
**RECEIVED:** Mar. 24, 2015  
**TESTED:** Apr. 03, 2015 ~ May 15, 2015  
**ISSUED:** May 22, 2015

**APPLICANT:** HTC Corporation

**ADDRESS:** 1F, 6-3 Baoqiang Road, Xindian District, New Taipei City, Taiwan 231

**ISSUED BY:** Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

**LAB ADDRESS:** No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan ( R.O.C. )

**TEST LOCATION:** No. 19, Hwa Ya 2nd Rd, Wen Hwa Vil., Kwei Shan Dist., Taoyuan City 333, Taiwan, R.O.C.

This report should not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification

## TABLE OF CONTENTS

RELEASE CONTROL RECORD.....	3
1 CERTIFICATION .....	4
2 SUMMARY OF TEST RESULTS.....	5
2.1 MEASUREMENT UNCERTAINTY .....	5
2.2 TEST SITE AND INSTRUMENTS .....	6
3 GENERAL INFORMATION .....	7
3.1 GENERAL DESCRIPTION OF EUT .....	7
3.2 CONFIGURATION OF SYSTEM UNDER TEST .....	9
3.3 DESCRIPTION OF SUPPORT UNITS .....	9
3.4 TEST ITEM AND TEST CONFIGURATION .....	10
3.5 EUT OPERATING CONDITIONS .....	12
3.6 GENERAL DESCRIPTION OF APPLIED STANDARDS .....	12
4 TEST TYPES AND RESULTS.....	13
4.1 OUTPUT POWER MEASUREMENT .....	13
4.1.1 LIMITS OF OUTPUT POWER MEASUREMENT .....	13
4.1.2 TEST PROCEDURES .....	13
4.1.3 TEST SETUP .....	14
4.1.4 TEST RESULTS .....	15
4.2 FREQUENCY STABILITY MEASUREMENT .....	22
4.2.1 LIMITS OF FREQUENCY STABILITY MEASUREMENT .....	22
4.2.2 TEST PROCEDURE .....	22
4.2.3 TEST SETUP .....	22
4.2.4 TEST RESULTS .....	23
4.3 OCCUPIED BANDWIDTH MEASUREMENT .....	24
4.3.1 TEST PROCEDURES .....	24
4.3.2 TEST SETUP .....	24
4.3.3 TEST RESULTS .....	25
4.4 BAND EDGE MEASUREMENT .....	28
4.4.1 LIMITS OF BAND EDGE MEASUREMENT .....	28
4.4.2 TEST SETUP .....	28
4.4.3 TEST PROCEDURES .....	28
4.4.4 TEST RESULTS .....	29
4.5 CONDUCTED SPURIOUS EMISSIONS.....	34
4.5.1 LIMITS OF CONDUCTED SPURIOUS EMISSIONS MEASUREMENT.....	34
4.5.2 TEST PROCEDURE .....	34
4.5.3 TEST SETUP .....	34
4.5.4 TEST RESULTS .....	35
4.6 RADIATED EMISSION MEASUREMENT .....	37
4.6.1 LIMITS OF RADIATED EMISSION MEASUREMENT .....	37
4.6.2 TEST PROCEDURES .....	37
4.6.3 DEVIATION FROM TEST STANDARD .....	37
4.6.4 TEST SETUP .....	38
4.6.5 TEST RESULTS .....	39
5 PHOTOGRAPHS OF THE TEST CONFIGURATION .....	51
6 INFORMATION ON THE TESTING LABORATORIES .....	52
7 APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB.....	53



A D T

## RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF150324C14	Original release	May 22, 2015



# 1 CERTIFICATION

**PRODUCT:** Smartphone

**MODEL:** OPM9110

**BRAND:** HTC

**APPLICANT:** HTC Corporation

**TESTED:** Apr. 03, 2015 ~ May 15, 2015

**TEST SAMPLE:** Production Unit

**STANDARDS:** FCC PART 22, Subpart H

The above equipment (model: OPM9110) has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

**PREPARED BY** : Ivonne Wu , **DATE** : May 22, 2015  
Ivonne Wu / Supervisor

**APPROVED BY** : Sam Chen , **DATE** : May 22, 2015  
Sam Chen / Senior Project Engineer

## 2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 22 & Part 2			
STANDARD SECTION	TEST TYPE	RESULT	REMARK
2.1046 22.913 (a)	Effective Radiated Power	PASS	Meet the requirement of limit.
2.1055 22.355	Frequency Stability	PASS	Meet the requirement of limit.
2.1049	Occupied Bandwidth	PASS	Meet the requirement of limit.
22.917	Band Edge Measurements	PASS	Meet the requirement of limit.
2.1051 22.917	Conducted Spurious Emissions	PASS	Meet the requirement of limit.
2.1053 22.917	Radiated Spurious Emissions	PASS	Meet the requirement of limit. Minimum passing margin is -9.75dB at 2509.20MHz.

### 2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	9kHz~30MHz	2.44 dB
Radiated emissions	30MHz ~ 200MHz	2.93 dB
	200MHz ~1000MHz	2.95 dB
	1GHz ~ 18GHz	2.26 dB
	18GHz ~ 40GHz	1.94 dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

## 2.2 TEST SITE AND INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF CALIBRATION	DUE DATE OF CALIBRATION
Test Receiver Agilent	N9038A	MY51210203	Jan. 21, 2015	Jan. 21, 2016
Spectrum Analyzer Agilent	N9010A	MY52220314	Sep. 03, 2014	Sep. 02, 2015
Spectrum Analyzer ROHDE & SCHWARZ	FSU43	101261	Dec. 10, 2014	Dec. 09, 2015
BILOG Antenna SCHWARZBECK	VULB9168	9168-472	Feb. 04, 2015	Feb. 04, 2016
HORN Antenna SCHWARZBECK	BBHA 9120 D	9120D-969	Feb. 09, 2015	Feb. 09, 2016
HORN Antenna SCHWARZBECK	BBHA 9170	9170-480	Feb. 04, 2015	Feb. 04, 2016
Preamplifier EMCI	EMC 012645	980115	Dec. 12, 2014	Dec. 11, 2015
Preamplifier EMCI	EMC 184045	980116	Jan. 09, 2015	Jan. 08, 2016
Preamplifier EMCI	EMC 330H	980112	Dec. 27, 2014	Dec. 26, 2015
Power Meter Anritsu	ML2495A	1232002	Sep. 17, 2014	Sep. 16, 2015
Power Sensor Anritsu	MA2411B	1207325	Sep. 17, 2014	Sep. 16, 2015
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	309219/4 2950114	Oct. 18, 2014	Oct. 17, 2015
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	250130/4	Oct. 18, 2014	Oct. 17, 2015
RF Coaxial Cable Worken	8D-FB	Cable-Ch10-01	Nov. 07, 2014	Nov. 06, 2015
Software BV ADT	E3 6.120103	NA	NA	NA
Antenna Tower MF	MFA-440H	NA	NA	NA
Turn Table MF	MFT-201SS	NA	NA	NA
Antenna Tower & Turn Table Controller MF	MF-7802	NA	NA	NA
Radio Communication Analyzer	MT8820C	6201300640	Aug. 01, 2013	Jul. 31, 2015

- NOTE:**
1. The calibration interval of the above test instruments is 12 / 24 months and the calibrations are traceable to NML/ROC and NIST/USA.
  2. The test was performed in HwaYa Chamber 10.
  3. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
  4. The FCC Site Registration No. is 690701.
  5. The IC Site Registration No. is IC 7450F-10.

### 3 GENERAL INFORMATION

#### 3.1 GENERAL DESCRIPTION OF EUT

<b>EUT</b>	Smartphone	
<b>MODEL NAME</b>	0PM9110	
<b>POWER SUPPLY</b>	5.0Vdc (adapter or host equipment) 3.85Vdc or 3.8Vdc (battery)	
<b>MODULATION TYPE</b>	<b>GSM/GPRS</b>	GMSK
	<b>EDGE</b>	GMSK, 8PSK
	<b>WCDMA</b>	BPSK
	<b>LTE</b>	QPSK, 16QAM
<b>FREQUENCY RANGE</b>	<b>GSM/GPRS/EDGE</b>	824.2MHz ~ 848.8MHz
	<b>WCDMA</b>	826.4MHz ~ 846.6MHz
	<b>LTE 5 (Channel Bandwidth: 1.4MHz)</b>	824.7MHz ~ 848.3MHz
	<b>LTE 5 (Channel Bandwidth: 3MHz)</b>	825.5MHz ~ 847.5MHz
	<b>LTE 5 (Channel Bandwidth: 5MHz)</b>	826.5MHz ~ 846.5MHz
	<b>LTE 5 (Channel Bandwidth: 10MHz)</b>	829MHz ~ 844MHz
<b>MAX. ERP POWER</b>	<b>GSM</b>	979.94mW
	<b>EDGE</b>	212.81mW
	<b>WCDMA</b>	87.66mW
	<b>LTE 5 (Channel Bandwidth: 1.4MHz)</b>	73.42mW
	<b>LTE 5 (Channel Bandwidth: 3MHz)</b>	82.57mW
	<b>LTE 5 (Channel Bandwidth: 5MHz)</b>	79.21mW
	<b>LTE 5 (Channel Bandwidth: 10MHz)</b>	86.46mW
<b>EMISSION DESIGNATOR</b>	<b>GSM</b>	246KGXW
	<b>EDGE</b>	247KG7W
	<b>WCDMA</b>	4M16F9W
	<b>LTE 5 (Channel Bandwidth: 1.4MHz)</b>	1M09W7D
	<b>LTE 5 (Channel Bandwidth: 3MHz)</b>	2M70G7D
	<b>LTE 5 (Channel Bandwidth: 5MHz)</b>	4M50G7D
	<b>LTE 5 (Channel Bandwidth: 10MHz)</b>	8M98W7D
<b>ANTENNA TYPE</b>	Fixed Internal Antenna	
<b>I/O PORTS</b>	Refer to users' manual	
<b>DATA CABLE</b>	Refer to NOTE as below	
<b>ACCESSORY DEVICES</b>	Refer to NOTE as below	



A D T

**NOTE:**

1. There're 2 configurations for the EUT listed as below.

Main sample (A): Phone + Battery 1 + LCD Panel 1


2<sup>nd</sup> sample (B): Phone + Battery 2 + LCD Panel 2

✧ Only the worst test data was presented in the report.


2. The EUT's accessories list refers to Ext. Pho.
3. The above EUT information was declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.

### 3.2 CONFIGURATION OF SYSTEM UNDER TEST

#### FOR RADIATION EMISSION TEST



#### FOR E.R.P. TEST



### 3.3 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units.

### 3.4 TEST ITEM AND TEST CONFIGURATION

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports. The worst case was found as the list below. Following channel(s) was (were) selected for the final test as listed below:

EUT CONFIGURE MODE	DESCRIPTION
A	Main sample
B	2 <sup>nd</sup> sample

EUT CONFIGURE MODE	ERP	RADIATED EMISSION
A	Y-plane	Y-axis
B	Y-plane	Y-axis (GSM) Z-axis (LTE)

#### GSM MODE

EUT CONFIGURE MODE	TEST ITEM	AVAILABLE CHANNEL	TESTED CHANNEL	MODE
A	ERP	128 to 251	128, 189, 251	GSM, EDGE
B	ERP	128 to 251	128, 189, 251	GSM
A	FREQUENCY STABILITY	128 to 251	189	GSM, EDGE
A	OCCUPIED BANDWIDTH	128 to 251	128, 189, 251	GSM, EDGE
A	BAND EDGE	128 to 251	128, 251	GSM, EDGE
A	CONDUCTED EMISSION	128 to 251	189	GSM, EDGE
A	RADIATED EMISSION	128 to 251	189	GSM, EDGE
B	RADIATED EMISSION	128 to 251	189	GSM

#### WCDMA MODE

EUT CONFIGURE MODE	TEST ITEM	AVAILABLE CHANNEL	TESTED CHANNEL	MODE
A	ERP	4132 to 4233	4132, 4182, 4233	WCDMA
A	FREQUENCY STABILITY	4132 to 4233	4182	WCDMA
A	OCCUPIED BANDWIDTH	4132 to 4233	4132, 4182, 4233	WCDMA
A	BAND EDGE	4132 to 4233	4132, 4233	WCDMA
A	CONDUCTED EMISSION	4132 to 4233	4182	WCDMA
A	RADIATED EMISSION	4132 to 4233	4182	WCDMA



**LTE BAND 5 MODE**

EUT CONFIGURE MODE	TEST ITEM	AVAILABLE CHANNEL	TESTED CHANNEL	CHANNEL BANDWIDTH	MODULATION	MODE
A	ERP	20407 to 20643	20407, 20525, 20643	1.4MHz	QPSK, 16QAM	1 RB / 2 RB Offset
		20415 to 20635	20415, 20525, 20635	3MHz	QPSK, 16QAM	1 RB / 7 RB Offset
		20425 to 20625	20425, 20525, 20625	5MHz	QPSK, 16QAM	1 RB / 12 RB Offset
		20450 to 20600	20450, 20525, 20600	10MHz	QPSK, 16QAM	1 RB / 24 RB Offset
B	ERP	20450 to 20600	20450, 20525, 20600	10MHz	QPSK, 16QAM	1 RB / 24 RB Offset
A	FREQUENCY STABILITY	20407 to 20643	20525	1.4MHz	QPSK	1 RB / 2 RB Offset
		20415 to 20635	20525	3MHz	QPSK	1 RB / 7 RB Offset
		20425 to 20625	20525	5MHz	QPSK	1 RB / 12 RB Offset
		20450 to 20600	20525	10MHz	QPSK	1 RB / 24 RB Offset
A	OCCUPIED BANDWIDTH	20407 to 20643	20407, 20525, 20643	1.4MHz	QPSK, 16QAM	6 RB / 0 RB Offset
		20415 to 20635	20415, 20525, 20635	3MHz	QPSK, 16QAM	15 RB / 0 RB Offset
		20425 to 20625	20425, 20525, 20625	5MHz	QPSK, 16QAM	25 RB / 0 RB Offset
		20450 to 20600	20450, 20525, 20600	10MHz	QPSK, 16QAM	50 RB / 0 RB Offset
A	BAND EDGE	20407 to 20643	20407	1.4MHz	QPSK	1 RB / 0 RB Offset
						6 RB / 0 RB Offset
			20643	1.4MHz	QPSK	1 RB / 5 RB Offset
						6 RB / 0 RB Offset
		20415 to 20635	20415	3MHz	QPSK	1 RB / 0 RB Offset
						15 RB / 0 RB Offset
			20635	3MHz	QPSK	1 RB / 14 RB Offset
						15 RB / 0 RB Offset
		20425 to 20626	20425	5MHz	QPSK	1 RB / 0 RB Offset
						25 RB / 0 RB Offset
			20600	5MHz	QPSK	1 RB / 24 RB Offset
						25 RB / 0 RB Offset
20450 to 20600	20450	10MHz	QPSK	1 RB / 0 RB Offset		
				50 RB / 0 RB Offset		
	20600	10MHz	QPSK	1 RB / 49 RB Offset		
				50 RB / 0 RB Offset		
A	CONDUCTED EMISSION	20407 to 20643	20525	1.4MHz	QPSK	1 RB / 2 RB Offset
		20415 to 20635	20525	3MHz	QPSK	1 RB / 7 RB Offset
		20425 to 20625	20525	5MHz	QPSK	1 RB / 12 RB Offset
		20450 to 20600	20525	10MHz	QPSK	1 RB / 24 RB Offset
A, B	RADIATED EMISSION	20450 to 20600	20525	10MHz	QPSK	1 RB / 24 RB Offset

**Note:** This device was tested under all bandwidths, RB configurations and modulations. The worst case was found in QPSK modulation.



### **TEST CONDITION:**

TEST ITEM	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
ERP	26deg. C, 58%RH	3.8Vdc	Karl Lee
FREQUENCY STABILITY	26deg. C, 58%RH	3.8Vdc	Taylor Liu
OCCUPIED BANDWIDTH	26deg. C, 58%RH	3.8Vdc	Taylor Liu
BAND EDGE	26deg. C, 58%RH	3.8Vdc	Taylor Liu
CONDUCTED EMISSION	26deg. C, 58%RH	3.8Vdc	Taylor Liu
RADIATED EMISSION	25deg. C, 65%RH	120Vac, 60Hz	Karl Lee / Charles Hsiao

### **3.5 EUT OPERATING CONDITIONS**

The EUT makes a call to the communication simulator. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency

### **3.6 GENERAL DESCRIPTION OF APPLIED STANDARDS**

The EUT is a RF product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

**FCC 47 CFR Part 2**

**FCC 47 CFR Part 22**

**ANSI/TIA/EIA-603-C 2004**

**NOTE:** All test items have been performed and recorded as per the above standards.



## 4 TEST TYPES AND RESULTS

### 4.1 OUTPUT POWER MEASUREMENT

#### 4.1.1 LIMITS OF OUTPUT POWER MEASUREMENT

Mobile / Portable station are limited to 7 watts e.r.p.

#### 4.1.2 TEST PROCEDURES

##### EIRP / ERP MEASUREMENT:


- a. All measurements were done at low, middle and high operational frequency range. RBW and VBW is 1MHz for GSM, GPRS & EDGE, 5MHz for WCDMA, and 10MHz for LTE mode.
- b. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
- c. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a tx cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to "Read Value" of step b. Record the power level of S.G
- d.  $EIRP = \text{Output power level of S.G} - \text{TX cable loss} + \text{Antenna gain of substitution horn}$ . E.R.P power can be calculated form E.I.R.P power by subtracting the gain of dipole,  $E.R.P \text{ power} = E.I.R.P \text{ power} - 2.15\text{dBi}$ .

##### CONDUCTED POWER MEASUREMENT:

The EUT was set up for the maximum power with GSM, GPRS, EDGE, WCDMA & LTE link data modulation and link up with simulator. Set the EUT to transmit under low, middle and high channel and record the power level shown on simulator.

### 4.1.3 TEST SETUP

#### EIRP / ERP MEASUREMENT:



#### CONDUCTED POWER MEASUREMENT:



#### 4.1.4 TEST RESULTS

##### CONDUCTED OUTPUT POWER (dBm)

Band	GSM850		
Channel	128	189	251
Frequency (MHz)	824.2	836.4	848.8
GSM (1 Uplink)	32.10	32.43	32.07
GPRS 8 (GMSK, 1 slot)	32.12	<b>32.45</b>	32.09
GPRS 10 (GMSK, 2 slot)	29.95	30.28	29.92
GPRS 11 (GMSK, 3 slot)	28.10	28.43	28.07
GPRS 12 (GMSK, 4 slot)	27.09	27.42	27.06
EDGE 8 (8PSK, 1 Uplink)	26.20	26.50	26.17
EDGE 10 (8PSK, 2 Uplink)	25.36	25.69	25.33
EDGE 11 (8PSK, 3 Uplink)	25.27	25.50	25.24
EDGE 12 (8PSK, 4 Uplink)	24.39	24.72	24.36

Band	WCDMA V		
Channel	4132	4182	4233
Frequency (MHz)	826.4	836.4	846.6
RMC 12.2K	<b>22.61</b>	22.55	22.56
HSDPA Subtest-1	21.56	21.50	21.51
HSDPA Subtest-2	21.66	21.60	21.61
HSDPA Subtest-3	21.09	21.03	21.04
HSDPA Subtest-4	21.00	20.94	20.95
HSUPA Subtest-1	21.27	21.21	21.22
HSUPA Subtest-2	19.86	19.77	19.91
HSUPA Subtest-3	20.47	20.41	20.42
HSUPA Subtest-4	19.88	19.81	19.84
HSUPA Subtest-5	21.54	21.48	21.49



A D T

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 20407	Mid CH 20525	High CH 20643		Low CH 20407	Mid CH 20525	High CH 20643	
			824.7 MHz	836.5 MHz	848.3 MHz		824.7 MHz	836.5 MHz	848.3 MHz	
5 / 1.4M	1	0	22.25	21.98	22.04	0	22.17	21.90	21.96	1
	1	2	22.40	22.13	22.19	0	22.32	22.05	22.11	1
	1	5	22.14	21.87	21.93	0	22.06	21.79	21.85	1
	3	0	21.28	21.01	21.07	0	21.20	20.93	20.99	1
	3	1	21.18	20.91	20.97	0	21.10	20.83	20.89	1
	3	3	21.15	20.88	20.94	0	21.07	20.80	20.86	1
	6	0	21.30	21.03	21.09	1	21.22	20.95	21.01	2

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 20415	Mid CH 20525	High CH 20635		Low CH 20415	Mid CH 20525	High CH 20635	
			825.5 MHz	836.5 MHz	847.5 MHz		825.5 MHz	836.5 MHz	847.5 MHz	
5 / 3M	1	0	22.34	22.07	22.13	0	22.26	21.99	22.05	1
	1	7	22.49	22.22	22.28	0	22.41	22.14	22.20	1
	1	14	22.23	21.96	22.02	0	22.15	21.88	21.94	1
	8	0	21.37	21.10	21.16	1	21.29	21.02	21.08	2
	8	3	21.27	21.00	21.06	1	21.19	20.92	20.98	2
	8	7	21.24	20.97	21.03	1	21.16	20.89	20.95	2
	15	0	21.39	21.12	21.18	1	21.31	21.04	21.10	2

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 20425	Mid CH 20525	High CH 20625		Low CH 20425	Mid CH 20525	High CH 20625	
			826.5 MHz	836.5 MHz	846.5 MHz		826.5 MHz	836.5 MHz	846.5 MHz	
5 / 5M	1	0	22.45	22.18	22.24	0	22.37	22.10	22.16	1
	1	12	22.60	22.33	22.39	0	22.52	22.25	22.31	1
	1	24	22.34	22.07	22.13	0	22.26	21.99	22.05	1
	12	0	21.48	21.21	21.27	1	21.40	21.13	21.19	2
	12	6	21.38	21.11	21.17	1	21.30	21.03	21.09	2
	12	13	21.35	21.08	21.14	1	21.27	21.00	21.06	2
	25	0	21.50	21.23	21.29	1	21.42	21.15	21.21	2

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 20450	Mid CH 20525	High CH 20600		Low CH 20450	Mid CH 20525	High CH 20600	
			829.0 MHz	836.5 MHz	844.0 MHz		829.0 MHz	836.5 MHz	844.0 MHz	
5 / 10M	1	0	22.52	22.25	22.31	0	22.44	22.17	22.23	1
	1	24	22.67	22.40	22.46	0	22.59	22.32	22.38	1
	1	49	22.41	22.14	22.20	0	22.33	22.06	22.12	1
	25	0	21.55	21.28	21.34	1	21.47	21.20	21.26	2
	25	12	21.45	21.18	21.24	1	21.37	21.10	21.16	2
	25	25	21.42	21.15	21.21	1	21.34	21.07	21.13	2
	50	0	21.57	21.30	21.36	1	21.49	21.22	21.28	2

**ERP POWER (dBm)**

**MODE A**

GSM							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)
Y	128	824.2	0.37	31.208	29.43	876.60	H
	189	836.4	0.55	31.3	29.70	933.25	H
	251	848.8	0.14	31.222	29.21	834.07	H
	128	824.2	-7.23	31.504	22.12	163.08	V
	189	836.4	-6.14	31.117	22.83	191.73	V
	251	848.8	-7.18	31.922	22.59	181.64	V

EDGE							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)
Y	128	824.2	-6.11	31.208	22.95	197.15	H
	189	836.4	-5.87	31.3	23.28	212.81	H
	251	848.8	-5.99	31.222	23.08	203.33	H
	128	824.2	-12.39	31.504	16.96	49.70	V
	189	836.4	-12.65	31.117	16.32	42.83	V
	251	848.8	-13.21	31.922	16.56	45.31	V

WCDMA							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)
Y	4132	826.4	-9.63	31.208	19.43	87.66	H
	4182	836.4	-9.94	31.3	19.21	83.37	H
	4233	846.6	-9.71	31.222	19.36	86.34	H
	4132	826.4	-17.03	31.504	12.32	17.08	V
	4182	836.4	-16.58	31.117	12.39	17.33	V
	4233	846.6	-17.10	31.922	12.67	18.50	V



A D T

LTE Band 5							
Channel Bandwidth: 1.4MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)
Y	20407	824.7	-10.40	31.208	18.66	73.42	H
	20525	836.5	-10.64	31.3	18.51	70.96	H
	20643	848.3	-10.25	31.222	18.82	76.24	H
	20407	824.7	-16.53	31.504	12.82	19.16	V
	20525	836.5	-16.77	31.117	12.20	16.58	V
	20643	848.3	-16.73	31.922	13.04	20.15	V

LTE Band 5							
Channel Bandwidth: 1.4MHz / 16QAM							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)
Y	20407	824.7	-11.12	31.208	17.94	62.20	H
	20525	836.5	-12.00	31.3	17.15	51.88	H
	20643	848.3	-11.33	31.222	17.74	59.46	H
	20407	824.7	-17.35	31.504	12.00	15.86	V
	20525	836.5	-17.51	31.117	11.46	13.99	V
	20643	848.3	-17.59	31.922	12.18	16.53	V

LTE Band 5							
Channel Bandwidth: 3MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)
Y	20415	825.5	-9.89	31.208	19.17	82.57	H
	20525	836.5	-10.28	31.3	18.87	77.09	H
	20635	847.5	-10.29	31.222	18.78	75.54	H
	20415	825.5	-16.32	31.504	13.03	20.11	V
	20525	836.5	-16.69	31.117	12.28	16.89	V
	20635	847.5	-16.64	31.922	13.13	20.57	V



A D T

LTE Band 5							
Channel Bandwidth: 3MHz / 16QAM							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)
Y	20415	825.5	-11.77	31.208	17.29	53.55	H
	20525	836.5	-11.74	31.3	17.41	55.08	H
	20635	847.5	-11.17	31.222	17.90	61.69	H
	20415	825.5	-17.66	31.504	11.69	14.77	V
	20525	836.5	-17.13	31.117	11.84	15.27	V
	20635	847.5	-18.12	31.922	11.65	14.63	V

LTE Band 5							
Channel Bandwidth: 5MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)
Y	20425	826.5	-10.07	31.208	18.99	79.21	H
	20525	836.5	-10.33	31.3	18.82	76.21	H
	20625	846.5	-10.26	31.222	18.81	76.07	H
	20425	826.5	-16.07	31.504	13.28	21.30	V
	20525	836.5	-16.33	31.117	12.64	18.35	V
	20625	846.5	-16.45	31.922	13.32	21.49	V

LTE Band 5							
Channel Bandwidth: 5MHz / 16QAM							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)
Y	20425	826.5	-11.51	31.208	17.55	56.86	H
	20525	836.5	-11.34	31.3	17.81	60.39	H
	20625	846.5	-11.55	31.222	17.52	56.52	H
	20425	826.5	-17.49	31.504	11.86	15.36	V
	20525	836.5	-17.50	31.117	11.47	14.02	V
	20625	846.5	-18.34	31.922	11.43	13.91	V



A D T

LTE Band 5							
Channel Bandwidth: 10MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)
Y	20450	829.0	-9.69	31.208	19.37	86.46	H
	20525	836.5	-10.10	31.3	19.05	80.35	H
	20600	844.0	-9.98	31.222	19.09	81.13	H
	20450	829.0	-16.90	31.504	12.45	17.60	V
	20525	836.5	-16.22	31.117	12.75	18.82	V
	20600	844.0	-16.42	31.922	13.35	21.64	V

LTE Band 5							
Channel Bandwidth: 10MHz / 16QAM							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)
Y	20450	829.0	-11.71	31.208	17.35	54.30	H
	20525	836.5	-11.45	31.3	17.70	58.88	H
	20600	844.0	-10.88	31.222	18.19	65.95	H
	20450	829.0	-17.46	31.504	11.89	15.47	V
	20525	836.5	-17.38	31.117	11.59	14.41	V
	20600	844.0	-17.94	31.922	11.83	15.25	V



A D T

**MODE B**

GSM							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)
Y	128	824.2	0.61	31.208	29.67	926.40	H
	189	836.4	0.68	31.3	29.83	961.61	H
	251	848.8	0.84	31.222	29.91	979.94	H
	128	824.2	-6.78	31.504	22.57	180.88	V
	189	836.4	-6.29	31.117	22.68	185.23	V
	251	848.8	-6.96	31.922	22.81	191.07	V

LTE Band 5							
Channel Bandwidth: 10MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)
Y	20450	829.0	-10.13	31.208	18.93	78.13	H
	20525	836.5	-10.02	31.3	19.13	81.85	H
	20600	844.0	-9.78	31.222	19.29	84.96	H
	20450	829.0	-16.48	31.504	12.87	19.38	V
	20525	836.5	-16.57	31.117	12.40	17.37	V
	20600	844.0	-16.68	31.922	13.09	20.38	V

LTE Band 5							
Channel Bandwidth: 10MHz / 16QAM							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)
Y	20450	829.0	-11.43	31.208	17.63	57.92	H
	20525	836.5	-11.37	31.3	17.78	59.98	H
	20600	844.0	-11.63	31.222	17.44	55.49	H
	20450	829.0	-17.40	31.504	11.95	15.68	V
	20525	836.5	-17.13	31.117	11.84	15.27	V
	20600	844.0	-17.70	31.922	12.07	16.11	V

## 4.2 FREQUENCY STABILITY MEASUREMENT

### 4.2.1 LIMITS OF FREQUENCY STABILITY MEASUREMENT


1.5 ppm is for base and fixed station. 2.5 ppm is for mobile station.

### 4.2.2 TEST PROCEDURE

- a. Device is placed at the oven room. The oven room could control the temperatures and humidity. Power warm up is at least 15 min and power applied should perform before recording frequency error.
- b. EUT is connected the external power supply to control the DC input power. The test voltage range is from minimum to maximum working voltage. Each step shall be record the frequency error rate.
- c. The temperature range step is 10 degrees in this test items. All temperature levels shall be hold the  $\pm 0.5^{\circ}\text{C}$  during the measurement testing. The each temperature step shall be at least 0.5 hours, consider the EUT could be test under the stability condition.

**NOTE:** The frequency error was recorded frequency error from the communication simulator.

### 4.2.3 TEST SETUP



#### 4.2.4 TEST RESULTS

##### FREQUENCY ERROR vs. VOLTAGE

VOLTAGE (Volts)	FREQUENCY ERROR (ppm)							LIMIT (ppm)
	GSM	EDGE	WCDMA	LTE Band 5				
				1.4MHz	3MHz	5MHz	10MHz	
3.8	0.003	0.003	0.002	0.004	0.002	0.002	0.004	2.5
3.6	0.002	0.002	0.003	0.003	0.003	0.003	0.002	2.5
4.4	0.004	0.004	0.004	0.002	0.003	0.004	0.003	2.5

**NOTE:** The applicant defined the normal working voltage of the battery is from 3.6Vdc to 4.4Vdc.

##### FREQUENCY ERROR vs. TEMPERATURE


TEMP. (°C)	FREQUENCY ERROR (ppm)							LIMIT (ppm)
	GSM	EDGE	WCDMA	LTE Band 5				
				1.4MHz	3MHz	5MHz	10MHz	
-30	0.004	0.003	-0.002	0.003	0.005	-0.004	-0.003	2.5
-20	0.002	0.001	0.003	0.002	0.001	0.003	0.003	2.5
-10	0.003	-0.003	0.001	0.003	0.003	-0.004	0.002	2.5
0	-0.002	-0.004	0.004	-0.003	0.005	-0.003	-0.004	2.5
10	-0.003	-0.002	-0.005	-0.003	0.003	-0.001	-0.003	2.5
20	-0.002	-0.003	-0.003	-0.005	-0.004	-0.005	-0.001	2.5
30	-0.004	-0.004	-0.002	-0.001	-0.002	-0.004	-0.002	2.5
40	-0.003	0.005	-0.003	-0.003	-0.003	0.003	0.004	2.5
50	0.001	0.002	-0.002	0.002	-0.003	0.005	0.003	2.5
55	0.004	0.003	0.003	0.002	0.004	0.003	0.002	2.5

## 4.3 OCCUPIED BANDWIDTH MEASUREMENT

### 4.3.1 TEST PROCEDURES

The EUT makes a call to the communication simulator. All measurements were done at low, middle and high operational frequency range. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency. Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth.

### 4.3.2 TEST SETUP






A D T

### 4.3.3 TEST RESULTS


CHANNEL	FREQUENCY (MHz)	99% OCCUPIED BANDWIDTH (kHz)		CHANNEL	FREQUENCY (MHz)	99% OCCUPIED BANDWIDTH (MHz)
		GSM	EDGE			
128	824.2	245.75	246.75	4132	826.4	4.1596
189	836.4	243.89	241.89	4182	836.4	4.1596
251	848.8	245.76	244.64	4233	846.6	4.1500
CHANNEL	FREQUENCY (MHz)	26dB BANDWIDTH (kHz)		CHANNEL	FREQUENCY (MHz)	26dB BANDWIDTH (MHz)
		GSM	EDGE			
128	824.2	318.60	316.60	4132	826.4	4.725
189	836.4	312.80	298.70	4182	836.4	4.745
251	848.8	315.40	307.80	4233	846.6	4.729





A D T

LTE BAND 5							
CHANNEL BANDWIDTH: 1.4MHz				CHANNEL BANDWIDTH: 3MHz			
CHANNEL	FREQUENCY (MHz)	99% OCCUPIED BANDWIDTH (MHz)		CHANNEL	FREQUENCY (MHz)	99% OCCUPIED BANDWIDTH (MHz)	
		QPSK	16QAM			QPSK	16QAM
20407	824.7	1.0892	1.0898	20415	825.5	2.7037	2.6979
20525	836.5	1.0878	1.0881	20525	836.5	2.7024	2.6976
20643	848.3	1.0880	1.0887	20635	847.5	2.7001	2.6981
CHANNEL	FREQUENCY (MHz)	26dB BANDWIDTH (MHz)		CHANNEL	FREQUENCY (MHz)	26dB BANDWIDTH (MHz)	
		QPSK	16QAM			QPSK	16QAM
20407	824.7	1.250	1.246	20415	825.5	2.921	2.927
20525	836.5	1.255	1.251	20525	836.5	2.928	2.909
20643	848.3	1.252	1.254	20635	847.5	2.915	2.917







A D T

LTE BAND 5							
CHANNEL BANDWIDTH: 5MHz				CHANNEL BANDWIDTH: 10MHz			
CHANNEL	FREQUENCY (MHz)	99% OCCUPIED BANDWIDTH (MHz)		CHANNEL	FREQUENCY (MHz)	99% OCCUPIED BANDWIDTH (MHz)	
		QPSK	16QAM			QPSK	16QAM
20425	826.5	4.5015	4.4960	20450	829.0	8.9675	8.9635
20525	836.5	4.4963	4.4946	20525	836.5	8.9419	8.9430
20625	846.5	4.4998	4.4948	20600	844.0	8.9747	8.9766
CHANNEL	FREQUENCY (MHz)	26dB BANDWIDTH (MHz)		CHANNEL	FREQUENCY (MHz)	26dB BANDWIDTH (MHz)	
		QPSK	16QAM			QPSK	16QAM
20425	826.5	4.840	4.803	20450	829.0	9.544	9.517
20525	836.5	4.833	4.812	20525	836.5	9.511	9.507
20625	846.5	4.844	4.827	20600	844.0	9.527	9.544

**SPECTRUM PLOT OF WORST VALUE**




## 4.4 BAND EDGE MEASUREMENT

### 4.4.1 LIMITS OF BAND EDGE MEASUREMENT

Power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB. In the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

### 4.4.2 TEST SETUP




### 4.4.3 TEST PROCEDURES

- All measurements were done at low and high operational frequency range.
- The center frequency of spectrum is the band edge frequency and span is 1MHz. RB of the spectrum is 3.9kHz and VB of the spectrum is 12kHz (GSM/GPRS/EDGE).
- The center frequency of spectrum is the band edge frequency and span is 5MHz. RB of the spectrum is 100kHz and VB of the spectrum is 300kHz (WCDMA).
- The center frequency of spectrum is the band edge frequency and span is 1MHz. RB of the spectrum is 13kHz and VB of the spectrum is 51kHz (LTE Bandwidth 1.4MHz).
- The center frequency of spectrum is the band edge frequency and span is 1MHz. RB of the spectrum is 30kHz and VB of the spectrum is 100kHz (LTE Bandwidth 3MHz/5MHz).
- The center frequency of spectrum is the band edge frequency and span is 1MHz. RB of the spectrum is 100kHz and VB of the spectrum is 300kHz (LTE Bandwidth 10MHz).
- Record the max trace plot into the test report.




A D T

### 4.4.4 TEST RESULTS






A D T






A D T






A D T





A D T



## 4.5 CONDUCTED SPURIOUS EMISSIONS


### 4.5.1 LIMITS OF CONDUCTED SPURIOUS EMISSIONS MEASUREMENT

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB. The emission limit is equal to -13dBm.

### 4.5.2 TEST PROCEDURE

- a. The EUT makes a phone call to the communication simulator. All measurements were done at low, middle and high operational frequency range.
- b. Measuring frequency range is from 30 MHz to 9GHz. 10dB attenuation pad is connected with spectrum. RBW=1MHz and VBW=3MHz is used for conducted emission measurement.


### 4.5.3 TEST SETUP






A D T

### 4.5.4 TEST RESULTS





A D T



## 4.6 RADIATED EMISSION MEASUREMENT

### 4.6.1 LIMITS OF RADIATED EMISSION MEASUREMENT

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB. The emission limit is equal to -13dBm.

### 4.6.2 TEST PROCEDURES


- a. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
- b. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a TX cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to "Read Value" of step a. Record the power level of S.G
- c. EIRP = Output power level of S.G - TX cable loss + Antenna gain of substitution horn.
- d. E.R.P power can be calculated form E.I.R.P power by subtracting the gain of dipole, E.R.P power = E.I.R.P power - 2.15dBi.

**NOTE:** The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1MHz/3MHz.

### 4.6.3 DEVIATION FROM TEST STANDARD

No deviation

#### 4.6.4 TEST SETUP



For the actual test configuration, please refer to the attached file (Test Setup Photo).

### 4.6.5 TEST RESULTS

MODE A

GSM:




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 9

Date: 2015-04-29



Site : 966 chamber 1  
 Condition: PART 22/24 3m Horizontal  
 Remark : GSM 850\_LINK\_CH189  
 Tested by: Karl Lee  
 Plane : Y

	Freq	Level	Read Level	Limit	Over	Factor	Remark
	MHz	dBm/m	dBm	dBm/m	dB	dB/m	
1	82.38	-43.14	-31.59	-13.00	-30.14	-11.55	Peak
2	181.47	-41.83	-36.24	-13.00	-28.83	-5.59	Peak
3	291.90	-38.41	-32.52	-13.00	-25.41	-5.89	Peak
4	315.40	-47.32	-41.54	-13.00	-34.32	-5.78	Peak
5	442.10	-49.18	-45.50	-13.00	-36.18	-3.68	Peak
6	678.70	-60.45	-60.18	-13.00	-47.45	-0.27	Peak
7	1672.80	-32.18	-40.09	-13.00	-19.18	7.91	Peak
8 pp	2509.20	-22.75	-34.03	-13.00	-9.75	11.28	Peak
9	3345.60	-30.39	-44.84	-13.00	-17.39	14.45	Peak
10	4182.00	-26.31	-43.44	-13.00	-13.31	17.13	Peak
11	5018.40	-45.85	-64.93	-13.00	-32.85	19.08	Peak
12	5854.80	-38.07	-58.85	-13.00	-25.07	20.78	Peak




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 10

Date: 2015-04-29



Site : 966 chamber 1  
 Condition: PART 22/24 3m Vertical  
 Remark : GSM 850\_LINK\_CH189  
 Tested by: Karl Lee  
 Plane : Y

	Freq	Level	Read Level	Limit	Over	Factor	Remark
	MHz	dBm/m	dBm	dBm/m	dB	dB/m	
1	47.55	-41.98	-28.87	-13.00	-28.98	-13.11	Peak
2	159.87	-39.89	-32.22	-13.00	-26.89	-7.67	Peak
3	224.67	-39.19	-33.34	-13.00	-26.19	-5.85	Peak
4	408.50	-67.28	-64.35	-13.00	-54.28	-2.93	Peak
5	585.60	-68.69	-68.51	-13.00	-55.69	-0.18	Peak
6	642.30	-68.27	-68.22	-13.00	-55.27	-0.05	Peak
7	1672.80	-31.33	-39.24	-13.00	-18.33	7.91	Peak
8 pp	2509.20	-23.06	-34.34	-13.00	-10.06	11.28	Peak
9	3345.60	-30.40	-44.85	-13.00	-17.40	14.45	Peak
10	4182.00	-33.41	-50.54	-13.00	-20.41	17.13	Peak
11	5018.40	-42.54	-61.62	-13.00	-29.54	19.08	Peak
12	5854.80	-38.15	-58.93	-13.00	-25.15	20.78	Peak



A D T

EDGE:




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 5

Date: 2015-04-18



Site : 966 chamber 1  
 Condition: PART 22/24 3m Horizontal  
 Remark : EDGE 850\_LINK\_CH189  
 Tested by: Karl Lee  
 Plane : Y


	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm/m	dBm	dBm/m	dB	dB/m	
1	1672.80	-44.13	-52.04	-13.00	-31.13	7.91	Peak
2 pp	2509.20	-41.35	-52.63	-13.00	-28.35	11.28	Peak



A D T

Data: 6

Date: 2015-04-18



Site : 966 chamber 1  
 Condition: PART 22/24 3m Vertical  
 Remark : EDGE 850\_LINK\_CH189  
 Tested by: Karl Lee  
 Plane : Y

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm/m	dBm	dBm/m	dB	dB/m	
1	1672.80	-41.58	-49.49	-13.00	-28.58	7.91	Peak
2 pp	2509.20	-41.49	-52.77	-13.00	-28.49	11.28	Peak

WCDMA:




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 5

Date: 2015-04-18



Site : 966 chamber 1  
 Condition: PART 22/24 3m Horizontal  
 Remark : Band V\_Link\_CH4182  
 Tested by: Karl Lee  
 Plane : Y


	Read	Limit	Over		
Freq	Level	Level	Line	Limit	Factor Remark
MHz	dBm/m	dBm	dBm/m	dB	dB/m
1 pp 1672.80	-56.91	-64.82	-13.00	-43.91	7.91 Peak



A D T

Data: 6

Date: 2015-04-18



Site : 966 chamber 1  
 Condition: PART 22/24 3m Vertical  
 Remark : Band V\_Link\_CH4182  
 Tested by: Karl Lee  
 Plane : Y

Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
MHz	dBm/m	dBm	dBm/m	dB	dB/m	
1 pp 1672.80	-57.69	-65.60	-13.00	-44.69	7.91	Peak



A D T

LTE BAND 5  
CHANNEL BANDWIDTH: 10MHz / QPSK




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 9

Date: 2015-04-18



Site : 966 chamber 1  
 Condition: PART 22/24 3m Horizontal  
 Remark : LTE\_Band 5\_QPSK(1,24)\_10M\_CH20525  
 Tested by: Karl Lee  
 Plane : Y

	Read	Limit	Over				
Freq	Level	Level	Line	Limit	Factor	Remark	
MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	59.16	-49.85	-35.79	-13.00	-36.85	-14.06	Peak
2	pp 135.84	-47.71	-40.04	-13.00	-34.71	-7.67	Peak
3	217.92	-49.70	-43.76	-13.00	-36.70	-5.94	Peak
4	415.50	-66.19	-63.11	-13.00	-53.19	-3.08	Peak
5	617.80	-68.17	-68.40	-13.00	-55.17	0.23	Peak
6	762.70	-67.12	-66.64	-13.00	-54.12	-0.48	Peak
7	1673.00	-57.45	-65.36	-13.00	-44.45	7.91	Peak




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 10

Date: 2015-04-18



Site : 966 chamber 1  
 Condition: PART 22/24 3m Vertical  
 Remark : LTE\_Band 5\_QPSK(1,24)\_10M\_CH20525  
 Tested by: Karl Lee  
 Plane : Y

	Freq	Level	Read Level	Limit	Over	Factor	Remark
	MHz	dBm/m	dBm	dBm/m	dB	dB/m	
1	61.05	-50.39	-36.46	-13.00	-37.39	-13.93	Peak
2	146.91	-46.96	-39.08	-13.00	-33.96	-7.88	Peak
3	215.76	-55.38	-49.42	-13.00	-42.38	-5.96	Peak
4	411.30	-68.24	-65.24	-13.00	-55.24	-3.00	Peak
5	631.10	-68.23	-68.30	-13.00	-55.23	0.07	Peak
6	790.00	-62.88	-64.25	-13.00	-49.88	1.37	Peak
7	1673.00	-58.09	-66.00	-13.00	-45.09	7.91	Peak


**MODE B**

**GSM:**



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T



Site : 966 chamber 1  
 Condition: PART 22/24 3m Horizontal  
 Remark : GSM 850\_Link\_CH189  
 Tested by: Charles Hsiao  
 Plane : Y

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm/m	dBm	dBm/m	dB	dB/m	
1	97.50	-48.75	-38.52	-13.00	-35.75	-10.23	Peak
2	137.46	-41.55	-33.87	-13.00	-28.55	-7.68	Peak
3	217.65	-50.47	-44.52	-13.00	-37.47	-5.95	Peak
4	431.60	-64.96	-61.52	-13.00	-51.96	-3.44	Peak
5	626.90	-68.28	-68.41	-13.00	-55.28	0.13	Peak
6	960.10	-64.11	-69.25	-13.00	-51.11	5.14	Peak
7	1672.80	-41.11	-49.02	-13.00	-28.11	7.91	Peak
8 pp	2509.20	-31.54	-42.82	-13.00	-18.54	11.28	Peak
9	4182.00	-47.02	-64.15	-13.00	-34.02	17.13	Peak




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 10

Date: 2015-05-14



Site : 966 chamber 1  
 Condition: PART 22/24 3m Vertical  
 Remark : GSM 850\_Link\_CH189  
 Tested by: Charles Hsiao  
 Plane : Y

	Freq	Level	Read Level	Limit	Over	Factor	Remark
	MHz	dBm/m	dBm	dBm/m	dB	dB/m	
1	31.35	-39.95	-29.30	-13.00	-26.95	-10.65	Peak
2	61.05	-51.04	-37.11	-13.00	-38.04	-13.93	Peak
3	137.46	-45.68	-38.00	-13.00	-32.68	-7.68	Peak
4	395.90	-64.86	-61.91	-13.00	-51.86	-2.95	Peak
5	584.20	-67.61	-67.35	-13.00	-54.61	-0.26	Peak
6	986.00	-64.41	-69.63	-13.00	-51.41	5.22	Peak
7	1672.80	-42.40	-50.31	-13.00	-29.40	7.91	Peak
8 pp	2509.20	-29.95	-41.23	-13.00	-16.95	11.28	Peak



A D T

LTE BAND 5  
CHANNEL BANDWIDTH: 10MHz / QPSK




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 9

Date: 2015-05-14



Site : 966 chamber 1  
 Condition: PART 22/24 3m Horizontal  
 Remark : LTE\_Band 5\_QPSK(1,24)\_10M\_CH20525  
 Tested by: Charles Hsiao  
 Plane : Z

		Read	Limit	Over			
	Freq	Level	Level	Line	Limit	Factor	Remark
	MHz	dBm/m	dBm	dBm/m	dB	dB/m	
1	97.50	-49.32	-39.09	-13.00	-36.32	-10.23	Peak
2	pp 139.08	-42.85	-35.16	-13.00	-29.85	-7.69	Peak
3	207.93	-51.30	-45.22	-13.00	-38.30	-6.08	Peak
4	313.30	-64.70	-58.90	-13.00	-51.70	-5.80	Peak
5	769.70	-67.89	-67.92	-13.00	-54.89	0.03	Peak
6	972.00	-64.07	-69.25	-13.00	-51.07	5.18	Peak
7	1673.00	-57.55	-65.46	-13.00	-44.55	7.91	Peak




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 10

Date: 2015-05-14



Site : 966 chamber 1  
 Condition: PART 22/24 3m Vertical  
 Remark : LTE\_Band 5\_QPSK(1,24)\_10M\_CH20525  
 Tested by: Charles Hsiao  
 Plane : Z

	Freq	Level	Read Level	Limit	Over	Factor	Remark
	MHz	dBm/m	dBm	dBm/m	dB	dB/m	
1 pp	31.35	-40.26	-29.61	-13.00	-27.26	-10.65	Peak
2	138.27	-47.25	-39.56	-13.00	-34.25	-7.69	Peak
3	204.69	-57.49	-51.37	-13.00	-44.49	-6.12	Peak
4	396.60	-65.16	-62.26	-13.00	-52.16	-2.90	Peak
5	698.30	-68.24	-67.87	-13.00	-55.24	-0.37	Peak
6	974.10	-64.20	-69.38	-13.00	-51.20	5.18	Peak
7	1673.00	-58.19	-66.10	-13.00	-45.19	7.91	Peak



A D T

## 5 PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).



## 6 INFORMATION ON THE TESTING LABORATORIES

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

**Linko EMC/RF Lab:**

Tel: 886-2-26052180

Fax: 886-2-26051924

**Hsin Chu EMC/RF/Telecom Lab:**

Tel: 886-3-5935343

Fax: 886-3-5935342

**Hwa Ya EMC/RF/Safety Lab:**

Tel: 886-3-3183232

Fax: 886-3-3270892

**Email:** [service.adt@tw.bureauveritas.com](mailto:service.adt@tw.bureauveritas.com)

**Web Site:** [www.bureauveritas-adt.com](http://www.bureauveritas-adt.com)

The address and road map of all our labs can be found in our web site also.



A D T

## **7 APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB**

No any modifications were made to the EUT by the lab during the test.

**---END---**