




FCC Test Report

According to

47 CFR Part 22H, 24E

Equipment : PDA Phone
Model No. : DIAM110
FCC ID : NM8DM
Tx Frequency Range : GSM850 : 824.2 ~ 848.8MHz
GSM1900 : 1850.2 ~ 1909.8 MHz
WCDMA Band V : 826.4 ~ 846.6 MHz
WCDMA Band II : 1852.4 ~ 1907.6 MHz
Max. ERP/EIRP Power : GSM850(GSM) : 0.93 W
GSM850(EDGE) : 0.22 W
GSM1900(GSM) : 0.62 W
GSM1900(EDGE) : 0.26 W
WCDMA Band V : 0.09 W
WCDMA Band V(HSUPA) : 0.08 W
WCDMA Band II : 0.17 W
WCDMA Band II(HSUPA) : 0.19 W
Emission Designator : GSM : 300KGXW
EDGE : 300KG7W
WCDMA : 4M22F9W
Applicant : **High Tech Computer Corp.**
23 Xinghua Rd., Taoyuan 330, Taiwan

- The test result refers exclusively to the test presented test model / sample.
- Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.
- **Certificate or Test Report must not be used by the applicant to claim the product in this test report endorsement by NVLAP or any agency of U.S. government.**
- The data shown in this test report were carried out on Jun. 20, 2008 at **Sporton International Inc. LAB.**
- Report No.: FG832620B, Report Version: Rev. 01.



Roy Wu
Manager

SPORTON International Inc.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.

SPORTON International Inc.

TEL : 886-3-327-3456

FAX : 886-3-328-4978

Report Version: Rev. 01



Table of Contents

History of This Test Report ii

1. General Information 1

1.1 Applicant..... 1

1.2 Manufacturer 1

1.3 Basic Description of Equipment under Test..... 1

1.4 Feature of Equipment under Test..... 2

1.5 Report Date 2

2. Test Configuration of Equipment under Test 3

2.1 Test Manner 3

2.2 Test Mode 3

2.3 Connection Diagram of Test System 3

2.4 Ancillary Equipment List 3

3. General Information of Test Site..... 4

3.1 Test Voltage 4

3.2 Test Compliance..... 4

3.3 Frequency Range 4

3.4 Test Distance..... 4

4. Test Data and Test Result 5

4.1 List of Measurements and Examinations 5

4.2 RF Output Power 6

4.3 ERP / EIRP Measurement 9

4.4 Occupied Bandwidth and Band Edge Measurement 15

4.5 Conducted Emission..... 80

4.6 Field Strength of Spurious Radiation 117

4.7 Frequency Stability (Temperature Variation) 137

4.8 Frequency Stability (Voltage Variation) 141

5. List of Measurement Equipments 143

6. Uncertainty Evaluation 144

Appendix A. Photographs of EUT

Appendix B. Setup Photographs



1. General Information

1.1 Applicant

High Tech Computer Corp.
23 Xinghua Rd., Taoyuan 330, Taiwan

1.2 Manufacturer

High Tech Computer Corp.
23 Xinghua Rd., Taoyuan 330, Taiwan

1.3 Basic Description of Equipment under Test

Sample A	PDA Phone with LCD Panel 1 + Photo Camera 1 + Video Camera 1
Sample B	PDA Phone with LCD Panel 2 + Photo Camera 2 + Video Camera 2
Sample C	PDA Phone with LCD Panel 1 + Photo Camera 1
Sample D	PDA Phone with LCD Panel 2 + Photo Camera 2



1.4 Feature of Equipment under Test

Product Feature & Specification	
DUT Type :	PDA Phone
Model Name :	DIAM110
FCC ID :	NM8DM
Tx Frequency :	GSM850 : 824 MHz ~ 849 MHz GSM1900 : 1850 MHz ~ 1910 MHz WCDMA Band V : 824 MHz ~ 849 MHz WCDMA Band II : 1850 MHz ~ 1910 MHz
Rx Frequency :	GSM850 : 869 MHz ~ 894 MHz GSM1900 : 1930 MHz ~ 1990 MHz WCDMA Band V : 869 MHz ~ 894 MHz WCDMA Band II : 1930 MHz ~ 1990 MHz
Maximum Output Power to Antenna :	GSM850 : 33.26 dBm GSM1900 : 29.71 dBm WCDMA Band V : 24.25 dBm WCDMA Band II : 23.27 dBm
Maximum ERP/EIRP :	GSM850(GSM) : 0.93 W (29.68 dBm) GSM850(EDGE) : 0.22 W (23.52 dBm) GSM1900(GSM) : 0.62 W (27.93 dBm) GSM1900(EDGE) : 0.26 W (24.17 dBm) WCDMA Band V : 0.09 W (19.60 dBm) WCDMA Band V(HSUPA) : 0.08 W (18.97 dBm) WCDMA Band II : 0.17 W (22.29 dBm) WCDMA Band II(HSUPA) : 0.19 W (22.78 dBm)
Antenna Type :	Fixed Internal
GPRS / EGPRS Multislot class :	12
Type of Modulation :	GSM / GPRS : GMSK EDGE : 8PSK WCDMA / HSDPA / HSUPA : QPSK
Type of Emission :	GSM : 300KGXW EDGE : 300KG7W WCDMA : 4M22F9W
DUT Stage :	Identical Prototype

1.5 Report Date

EUT Received : Mar. 26, 2008

Report Date : Jun. 20, 2008

2. Test Configuration of Equipment under Test


2.1 Test Manner

1. The spurious emission measurements were carried out in semi-anechoic chamber with 3-meter test range.
2. During all testings, EUT is in link mode with base station emulator at maximum power level.
3. Frequency range investigated: radiated emission 30 MHz to 9000 MHz for GSM850 and WCDMA Band V; 30MHz to 19000 MHz for GSM1900 and WCDMA Band II.

2.2 Test Mode

Application	GSM850	GSM1900	WCDMA Band V	WCDMA Band II
Radiated Emission	<input checked="" type="checkbox"/> Mode 1: GSM Link	<input checked="" type="checkbox"/> Mode 3: GSM Link	<input checked="" type="checkbox"/> Mode 5: WCDMA Link	<input checked="" type="checkbox"/> Mode 7: WCDMA Link
	<input checked="" type="checkbox"/> Mode 2: EDGE Link	<input checked="" type="checkbox"/> Mode 4: EDGE Link	<input checked="" type="checkbox"/> Mode 6: HSUPA Link	<input checked="" type="checkbox"/> Mode 8: HSUPA Link
	<input checked="" type="checkbox"/> Mode 9: GSM Link + WLAN Link			
Conducted Measurement	<input checked="" type="checkbox"/> Mode 1: GSM Link	<input checked="" type="checkbox"/> Mode 3: GSM Link	<input checked="" type="checkbox"/> Mode 5: WCDMA Link	<input checked="" type="checkbox"/> Mode 7: WCDMA Link
	<input checked="" type="checkbox"/> Mode 2: EDGE Link	<input checked="" type="checkbox"/> Mode 4: EDGE Link	<input checked="" type="checkbox"/> Mode 6: HSUPA Link	<input checked="" type="checkbox"/> Mode 8: HSUPA Link

2.3 Connection Diagram of Test System



2.4 Ancillary Equipment List

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Code
1.	GSM Base Station	R&S	CMU200	N/A	N/A	Unshielded, 1.8m



3. General Information of Test Site

Test Site Location : No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park,
Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.
TEL : 886-3-327-3456
FAX : 886-3-328-4978
Test Site No : 03CH07-HY, TH02-HY
FCC Designation No : TW1022

The chamber meets the characteristics of ANSI C63.4-2003. This site is on file with the FCC.

3.1 Test Voltage

AC 120V / 60Hz

3.2 Test Compliance

47 CFR Part 22H, 24E, Part 2

Preliminary Guidance for Receiving Applications for Certification of 3G Device. May 9, 2006.

3.3 Frequency Range

- a. Radiation: from 30MHz to 9000MHz for GSM850 and WCDMA Band V.
- b. Radiation: from 30 MHz to 19000 MHz for GSM1900 and WCDMA Band II.

3.4 Test Distance

The test distance of radiated emission from antenna to EUT is 3 m.



4. Test Data and Test Result

4.1 List of Measurements and Examinations

FCC Rule	Description of Test	Result	Section
§2.1046	RF Output Power	Passed	4.2
§22.913 §24.232	ERP / EIRP	Passed	4.3
§2.1049, §22.917, §24.238(b)	Occupied Bandwidth & Band Edge Measurement	Passed	4.4
§2.1051	Conducted Emission	Passed	4.5
§2.1053	Field Strength of Spurious Radiation	Passed	4.6
§2.1055, §22.355, §24.235	Frequency Stability vs. Temperature	Passed	4.7
§2.1055, §22.355, §24.235	Frequency Stability vs. Voltage	Passed	4.8

4.2 RF Output Power


4.2.1 Measurement Instruments

As described in chapter 5 of this test report.

4.2.2 Test Procedure

- a. The transmitter output was connected to power meter and base station through power divider.
- b. Set the EUT at maximum power through base station by using below setting
 - b.1 PCL=5 for GSM850, PCL=0 for PCS1900.
 - b.2 TPC with All Up Bits for WCDMA.
- c. Select lowest, middle, and highest channels for each band.

4.2.3 Test Setup Layout





4.2.4 Test Result

Bands	Channel	Frequency (MHz)	Conducted Power (dBm)	Conducted Power (Watts)
GSM850 (GSM)	128	824.2 (Low)	32.29	1.694
	189	836.4 (Mid)	33.26	2.118
	251	848.8 (High)	33.06	2.023
GSM850 (EDGE)	128	824.2 (Low)	27.30	0.537
	189	836.4 (Mid)	27.33	0.541
	251	848.8 (High)	27.28	0.535
GSM1900 (GSM)	512	1850.2 (Low)	29.68	0.929
	661	1880.0 (Mid)	29.66	0.925
	810	1909.8 (High)	29.71	0.935
GSM1900 (EDGE)	512	1850.2 (Low)	25.88	0.387
	661	1880.0 (Mid)	25.84	0.384
	810	1909.8 (High)	25.94	0.393
WCDMA Band V (12.2k bps)	4132	826.4 (Low)	23.48	0.223
	4182	836.4 (Mid)	23.68	0.233
	4233	846.6 (High)	23.50	0.224
WCDMA Band V (64k bps)	4132	826.4 (Low)	23.60	0.229
	4182	836.4 (Mid)	23.73	0.236
	4233	846.6 (High)	23.60	0.229
WCDMA Band V (144k bps)	4132	826.4 (Low)	23.61	0.230
	4182	836.4 (Mid)	23.78	0.239
	4233	846.6 (High)	23.61	0.230
WCDMA Band V (384k bps)	4132	826.4 (Low)	23.61	0.230
	4182	836.4 (Mid)	23.57	0.228
	4233	846.6 (High)	23.63	0.231
WCDMA Band V (AMR)	4132	826.4 (Low)	23.52	0.225
	4182	836.4 (Mid)	23.51	0.224
	4233	846.6 (High)	23.39	0.218
WCDMA Band V (HSDPA)	4132	826.4 (Low)	22.85	0.193
	4182	836.4 (Mid)	22.86	0.193
	4233	846.6 (High)	22.88	0.194
WCDMA Band V (HSUPA)	4132	826.4 (Low)	23.96	0.249
	4182	836.4 (Mid)	24.25	0.266
	4233	846.6 (High)	23.86	0.243



Bands	Channel	Frequency (MHz)	Conducted Power (dBm)	Conducted Power (Watts)
WCDMA Band II (12.2k bps)	9262	1852.4 (Low)	22.55	0.180
	9400	1880.0 (Mid)	22.65	0.184
	9538	1907.6 (High)	22.46	0.176
WCDMA Band II (64k bps)	9262	1852.4 (Low)	22.60	0.182
	9400	1880.0 (Mid)	22.54	0.179
	9538	1907.6 (High)	22.33	0.171
WCDMA Band II (144k bps)	9262	1852.4 (Low)	22.57	0.181
	9400	1880.0 (Mid)	22.72	0.187
	9538	1907.6 (High)	22.40	0.174
WCDMA Band II (384k bps)	9262	1852.4 (Low)	22.59	0.182
	9400	1880.0 (Mid)	22.74	0.188
	9538	1907.6 (High)	22.43	0.175
WCDMA Band II (AMR)	9262	1852.4 (Low)	22.31	0.170
	9400	1880.0 (Mid)	22.55	0.180
	9538	1907.6 (High)	22.25	0.168
WCDMA Band II (HSDPA)	9262	1852.4 (Low)	21.74	0.149
	9400	1880.0 (Mid)	21.99	0.158
	9538	1907.6 (High)	21.85	0.153
WCDMA Band II (HSUPA)	9262	1852.4 (Low)	22.86	0.193
	9400	1880.0 (Mid)	23.27	0.212
	9538	1907.6 (High)	22.95	0.197



4.3 ERP / EIRP Measurement

Equivalent isotropic radiated power measurements by substitution method according to ANSI/TIA/EIA-603-C.

4.3.1 Measurement Instruments

As described in chapter 5 of this test report.

4.3.2 Test Procedure

- a. The EUT was placed on a table with 1.0 meter height in an fully anechoic chamber.
- b. The EUT was set 1.2 meters from the receiving antenna which was mounted on the antenna tower.
- c. The table was rotated 360 degrees to determine the position of the highest radiated power.
- d. The height of the receiving antenna is also kept at 1.0M height.
- e. Taking the record of maximum ERP/EIRP.
- f. A dipole antenna was substituted in place of the EUT and was driven by a signal generator.
- g. The conducted power at the terminal of the dipole antenna is measured.
- h. Repeat step 3 to step 5 to get the maximum ERP/EIRP of the substitution antenna.
- i. $ERP/EIRP = P_s + E_t - E_s + G_s = P_s + R_t - R_s + G_s$

P_s (dBm) : Input power to substitution antenna.

G_s (dBi or dBd) : Substitution antenna Gain.

$E_t = R_t + AF$


$E_s = R_s + AF$

AF (dB/m) : Receive antenna factor

R_t : The highest received signal in Spectrum Analyzer for EUT.

R_s : The highest received signal in spectrum analyzer for substitution antenna.

4.3.3 Test Setup Layout of ERP/EIRP





4.3.4 Test Result

GSM850 (GSM) Radiated Power ERP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
824.20	-32.58	-48.12	0.00	-1.08	14.46	0.03
836.40	-32.07	-48.28	0.00	-0.93	15.28	0.03
848.80	-33.33	-48.35	0.00	-0.76	14.26	0.03
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
824.20	-18.28	-47.97	0.00	-1.08	28.61	0.73
836.40	-17.40	-48.01	0.00	-0.93	29.68	0.93
848.80	-18.70	-48.05	0.00	-0.76	28.59	0.72

GSM850 (EDGE) Radiated Power ERP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
824.20	-38.58	-48.12	0.00	-1.08	8.46	0.01
836.40	-38.25	-48.28	0.00	-0.93	9.10	0.01
848.80	-39.28	-48.35	0.00	-0.76	8.31	0.01
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
824.20	-24.21	-47.97	0.00	-1.08	22.68	0.19
836.40	-23.56	-48.01	0.00	-0.93	23.52	0.22
848.80	-24.49	-48.05	0.00	-0.76	22.80	0.19



GSM1900 (GSM) Radiated Power EIRP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-26.90	-51.88	0.00	1.96	26.94	0.49
1880.00	-28.76	-52.99	0.00	2.00	26.23	0.42
1909.80	-30.13	-54.28	0.00	1.98	26.13	0.41
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-26.16	-52.13	0.00	1.96	27.93	0.62
1880.00	-27.44	-53.17	0.00	2.00	27.73	0.59
1909.80	-28.46	-54.13	0.00	1.98	27.65	0.58

GSM1900 (EDGE) Radiated Power EIRP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-30.70	-51.88	0.00	1.96	23.14	0.21
1880.00	-32.55	-52.99	0.00	2.00	22.44	0.18
1909.80	-33.95	-54.28	0.00	1.98	22.31	0.17
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-29.92	-52.13	0.00	1.96	24.17	0.26
1880.00	-31.24	-53.17	0.00	2.00	23.93	0.25
1909.80	-32.31	-54.13	0.00	1.98	23.80	0.24



WCDMA Band V Radiated Power ERP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
826.40	-43.09	-48.12	0.00	-1.08	3.95	0.00
836.40	-42.74	-48.28	0.00	-0.93	4.61	0.00
846.60	-42.53	-48.35	0.00	-0.76	5.06	0.00
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
826.40	-28.67	-47.97	0.00	-1.08	18.22	0.07
836.40	-28.02	-48.01	0.00	-0.93	19.06	0.08
846.60	-27.69	-48.05	0.00	-0.76	19.60	0.09

WCDMA Band V (HSUPA) Radiated Power ERP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
826.40	-40.60	-48.12	0.00	-1.08	6.44	0.00
836.40	-41.01	-48.28	0.00	-0.93	6.34	0.00
846.60	-40.55	-48.35	0.00	-0.76	7.04	0.01
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
826.40	-27.96	-47.97	0.00	-1.08	18.93	0.08
836.40	-28.12	-48.01	0.00	-0.93	18.96	0.08
846.60	-28.32	-48.05	0.00	-0.76	18.97	0.08



WCDMA Band II Radiated Power EIRP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1852.40	-32.48	-51.88	0.00	1.96	21.36	0.14
1880.00	-34.54	-52.99	0.00	2.00	20.45	0.11
1907.60	-36.32	-54.28	0.00	1.98	19.94	0.10
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1852.40	-31.80	-52.13	0.00	1.96	22.29	0.17
1880.00	-33.24	-53.17	0.00	2.00	21.93	0.16
1907.60	-34.72	-54.13	0.00	1.98	21.39	0.14

WCDMA Band II (HSUPA) Radiated Power EIRP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1852.40	-31.94	-51.88	0.00	1.96	21.90	0.15
1880.00	-34.24	-52.99	0.00	2.00	20.75	0.12
1907.60	-36.05	-54.28	0.00	1.98	20.21	0.10
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1852.40	-31.31	-52.13	0.00	1.96	22.78	0.19
1880.00	-33.33	-53.17	0.00	2.00	21.84	0.15
1907.60	-34.86	-54.13	0.00	1.98	21.25	0.13

4.4 Occupied Bandwidth and Band Edge Measurement


4.4.1 Measurement Instruments

As described in chapter 5 of this test report.

4.4.2 Test Procedure

- a. The EUT was connected to Spectrum Analyzer and Base Station via power divider.
- b. The 99% occupied bandwidth of middle channel for the highest and lowest RF powers were measured.
- c. The bandedge of low and high channels for the highest RF powers within the transmitting frequency band were measured. Setting RBW as roughly $BW/100$.


4.4.3 Test Setup Layout





4.4.4 Test Result


- Mode 1
- Test Mode : GSM850 (GSM) CH128 Lower Band Edge
- Power State : High



Date: 18.APR.2008 00:40:21




- Test Mode : GSM850 (GSM) CH189 99% Occupied Bandwidth
- Power State : High



Date: 18.APR.2008 00:38:46



- Test Mode : GSM850 (GSM) CH 251 99% Occupid Bandwidth
- Power State : High




Date: 18.APR.2008 00:37:34



- Test Mode : GSM850 (GSM) CH128 26dB Bandwidth
- Power State : High



Ref 30 dBm *Att 30 dB *RBW 3 kHz Delta 2 [T1]
 *VBW 10 kHz -2.01 dB
 *SWT 300 ms 312.000000000 kHz




Date: 18.APR.2008 00:34:26



- Test Mode : GSM850 (GSM) CH 251 26dB Bandwidth
- Power State : High




Ref 30 dBm *Att 30 dB *RBW 3 kHz Delta 2 [T1]
 *VBW 10 kHz -1.10 dB
 *SWT 300 ms 316.000000000 kHz



Date: 18.APR.2008 00:36:48




- Test Mode : GSM850 (GSM) CH251 Higher Band Edge
- Power State : High



Date: 18.APR.2008 00:40:57



- Test Mode : GSM850 (EDGE) CH128 99% Occupied Bandwidth
- Power State : High




Date: 18.APR.2008 00:12:10



- Test Mode : GSM850 (EDGE) CH 251 99% Occupied Bandwidth
- Power State : High




Ref 30 dBm *Att 30 dB *RBW 3 kHz Marker 1 [T1]
 *VBW 10 kHz 19.11 dBm
 *SWT 300 ms 848.748000000 MHz



Date: 18.APR.2008 00:11:12



- Test Mode : GSM850 (EDGE) CH128 26dB Bandwidth
- Power State : High




Date: 18.APR.2008 00:04:55



- Test Mode : GSM850 (EDGE) CH189 26dB Bandwidth
- Power State : High




*RBW 3 kHz Delta 2 [T1]
 *VBW 10 kHz 0.05 dB
 *SWT 300 ms 296.00000000 kHz
 Ref 30 dBm *Att 30 dB



Date: 18.APR.2008 00:06:31




- Test Mode : GSM850 (EDGE) CH 251 26dB Bandwidth
- Power State : High



Date: 18.APR.2008 00:08:22




- Test Mode : GSM850 (EDGE) CH251 Higher Band Edge
- Power State : High



Date: 18.APR.2008 00:23:57




- Mode 3
- Test Mode : GSM1900 (GSM) CH512 Lower Band Edge
- Power State : High



Date: 18.APR.2008 01:23:28



- Test Mode : GSM1900 (GSM) CH512 99% Occupied Bandwidth
- Power State : High




Date: 18.APR.2008 01:19:33



- Test Mode : GSM1900 (GSM) CH661 99% Occupied Bandwidth
- Power State : High



*RBW 3 kHz Marker 1 [T1]
 *VBW 10 kHz 22.77 dBm
 *SWT 300 ms 1.880012000 GHz
 Ref 30 dBm *Att 30 dB




Date: 18.APR.2008 01:20:56



- Test Mode : GSM1900 (GSM) CH810 99% Occupied Bandwidth
- Power State : High



*RBW 3 kHz Marker 1 [T1]
 *VBW 10 kHz 22.04 dBm
 *SWT 300 ms 1.909784000 GHz
 Ref 30 dBm *Att 30 dB




Date: 18.APR.2008 01:18:28



- Test Mode : GSM1900 (GSM) CH512 26dB Bandwidth
- Power State : High



*RBW 3 kHz Delta 2 [T1]
 *VBW 10 kHz 1.75 dB
 *Att 30 dB *SWT 300 ms 314.00000000 kHz
 Ref 30 dBm Offset 18.5 dB




Date: 18.APR.2008 01:12:45



- Test Mode : GSM1900 (GSM) CH661 26dB Bandwidth
- Power State : High



Ref 30 dBm *Att 30 dB *RBW 3 kHz Delta 2 [T1] 1.16 dB
 *VBW 10 kHz 312.00000000 kHz
 *SWT 300 ms




Date: 18.APR.2008 01:13:46



- Test Mode : GSM1900 (GSM) CH810 26dB Bandwidth
- Power State : High



*RBW 3 kHz Delta 2 [T1]
 *VBW 10 kHz 0.76 dB
 *Att 30 dB *SWT 300 ms 310.00000000 kHz
 Ref 30 dBm Offset 18.5 dB



Date: 18.APR.2008 01:17:39



- Test Mode : GSM1900 (GSM) CH810 Higher Band Edge
- Power State : High




*RBW 3 kHz Marker 1 [T1]
*VBW 3 kHz -20.56 dBm
*SWT 300 ms 1.910024000 GHz

Ref 30 dBm

*Att 30 dB

1 AV *
VIEW



Center 1.91 GHz


100 kHz/

Span 1 MHz

Date: 18.APR.2008 01:24:41



- Mode 4
- Test Mode : GSM1900 (EDGE) CH512 Lower Band Edge
- Power State : High




Date: 18.APR.2008 01:51:32



- Test Mode : GSM1900 (EDGE) CH512 99% Occupied Bandwidth
- Power State : High



*RBW 3 kHz Marker 1 [T1]
 *VBW 10 kHz 17.51 dBm
 *SWT 300 ms 1.850164000 GHz
 Ref 30 dBm *Att 30 dB




Date: 18.APR.2008 01:48:01



- Test Mode : GSM1900 (EDGE) CH661 99% Occupied Bandwidth
- Power State : High



*RBW 3 kHz Marker 1 [T1]
 *VBW 10 kHz 19.18 dBm
 *SWT 300 ms 1.879932000 GHz
 Ref 30 dBm *Att 30 dB




Date: 18.APR.2008 01:48:57



- Test Mode : GSM1900 (EDGE) CH810 99% Occupied Bandwidth
- Power State : High



*RBW 3 kHz Marker 1 [T1]
 *VBW 10 kHz 20.17 dBm
 *SWT 300 ms 1.909780000 GHz
 Ref 30 dBm *Att 30 dB



Date: 18.APR.2008 01:47:21



- Test Mode : GSM1900 (EDGE) CH512 26dB Bandwidth
- Power State : High




*RBW 3 kHz Delta 2 [T1]
 *VBW 10 kHz 0.44 dB
 *SWT 300 ms 302.00000000 kHz

Ref 30 dBm

*Att 30 dB

1 PK VIEW



Center 1.8502 GHz

100 kHz/

Span 1 MHz


Date: 18.APR.2008 01:42:11



- Test Mode : GSM1900 (EDGE) CH661 26dB Bandwidth
- Power State : High



Ref 30 dBm *Att 30 dB *RBW 3 kHz Delta 2 [T1] -0.19 dB
 *VBW 10 kHz 312.000000000 kHz
 *SWT 300 ms




Date: 18.APR.2008 01:45:08



- Test Mode : GSM1900 (EDGE) CH810 26dB Bandwidth
- Power State : High



Ref 30 dBm *Att 30 dB *RBW 3 kHz Delta 2 [T1]
 *VBW 10 kHz -0.26 dB
 *SWT 300 ms 296.000000000 kHz



Date: 18.APR.2008 01:46:31



- Test Mode : GSM1900(EDGE) CH810 Higher Band Edge
- Power State : High




*RBW 3 kHz Marker 1 [T1]
*VBW 3 kHz -26.35 dBm
*SWT 300 ms 1.910014000 GHz

Ref 30 dBm

*Att 30 dB

1 AV *
VIEW



Center 1.91 GHz


100 kHz/

Span 1 MHz

Date: 18.APR.2008 01:52:18




- Mode 5
- Test Mode : WCDMA Band V CH4132 Lower Band Edge
- Power State : High



Date: 21.APR.2008 19:46:46



- Test Mode : WCDMA Band V CH4132 26dB Bandwidth
- Power State : High



Date: 21.APR.2008 19:21:54



- Test Mode : WCDMA Band V CH4182 26dB Bandwidth
- Power State : High




*RBW 100 kHz Delta 2 [T1]
 *VBW 300 kHz -0.40 dB
 *SWT 300 ms 4.680000000 MHz

Ref 30 dBm

*Att 30 dB

1 PK VIEW



Date: 21.APR.2008 19:22:52



- Test Mode : WCDMA Band V CH4233 26dB Bandwidth
- Power State : High




*RBW 100 kHz Delta 2 [T1]
 *VBW 300 kHz -0.04 dB
 *SWT 300 ms 4.660000000 MHz

Ref 30 dBm

*Att 30 dB

1 PK VIEW



Center 846.6 MHz


1 MHz/

Span 10 MHz

Date: 21.APR.2008 19:27:00




- Test Mode : WCDMA Band V CH4233 Higher Band Edge
- Power State : High



Date: 21.APR.2008 19:58:02



- Mode 6
- Test Mode : WCDMA Band V (HSUPA) CH4132 Lower Band Edge
- Power State : High



Date: 18.JUN.2008 18:15:57




- Test Mode : WCDMA Band V (HSUPA) CH4132 99% Occupied Bandwidth
- Power State : High



*RBW 100 kHz Marker 1 [T1]
 *VBW 300 kHz 19.57 dBm
 *SWT 300 ms 827.080000000 MHz

Ref 30 dBm


*Att 30 dB



Date: 18.JUN.2008 18:01:48



- Test Mode : WCDMA Band V (HSUPA) CH4132 26dB Bandwidth
- Power State : High




Date: 18.JUN.2008 18:00:50



- Test Mode : WCDMA Band V (HSUPA) CH4182 26dB Bandwidth
- Power State : High



Ref 30 dBm *Att 30 dB *RBW 100 kHz Delta 2 [T1]
 *VBW 300 kHz -1.81 dB
 *SWT 300 ms 4.680000000 MHz



Date: 18.JUN.2008 17:59:26




- Test Mode : WCDMA Band V (HSUPA) CH4233 26dB Bandwidth
- Power State : High



*RBW 100 kHz Delta 2 [T1]
 *VBW 300 kHz -0.22 dB
 *SWT 300 ms 4.660000000 MHz

Ref 30 dBm

*Att 30 dB



Date: 18.JUN.2008 17:57:54



- Test Mode : WCDMA Band V (HSUPA) CH4233 Higher Band Edge
- Power State : High




*RBW 100 kHz Marker 1 [T1]
 *VBW 100 kHz -28.93 dBm
 *SWT 300 ms 849.00000000 MHz

Ref 30 dBm

*Att 30 dB


1 AV*
VIEW



Date: 18.JUN.2008 18:15:26




- Mode 7
- Test Mode : WCDMA Band II CH9262 Lower Band Edge
- Power State : High



Date: 21.APR.2008 21:37:57



- Test Mode : WCDMA Band II CH9262 99% Occupied Bandwidth
- Power State : High



Date: 18.APR.2008 03:05:02




- Test Mode : WCDMA Band II CH9400 99% Occupied Bandwidth
- Power State : High



*RBW 100 kHz Marker 1 [T1]
 *VBW 300 kHz 19.63 dBm
 *SWT 300 ms 1.879160000 GHz

Ref 30 dBm

*Att 30 dB



Center 1.88 GHz

1 MHz/

Span 10 MHz


Date: 18.APR.2008 03:05:29



- Test Mode : WCDMA Band II CH9538 99% Occupied Bandwidth
- Power State : High



Ref 30 dBm *Att 30 dB *RBW 100 kHz Marker 1 [T1]
 *VBW 300 kHz 19.61 dBm
 *SWT 300 ms 1.906740000 GHz



Date: 18.APR.2008 03:04:32



- Test Mode : WCDMA Band II CH9262 26dB Bandwidth
- Power State : High




*RBW 100 kHz Delta 2 [T1]
 *VBW 300 kHz -1.61 dB
 *SWT 300 ms 4.660000000 MHz

Ref 30 dBm

*Att 30 dB

1 PK VIEW



Center 1.8524 GHz

1 MHz/

Span 10 MHz

Date: 18.APR.2008 03:01:13



- Test Mode : WCDMA Band II CH9400 26dB Bandwidth
- Power State : High




*RBW 100 kHz Delta 2 [T1]
 *VBW 300 kHz 0.04 dB
 *SWT 300 ms 4.680000000 MHz

Ref 30 dBm

*Att 30 dB

1 PK VIEW




Date: 18.APR.2008 03:02:01



- Test Mode : WCDMA Band II CH9538 26dB Bandwidth
- Power State : High




Ref 30 dBm *Att 30 dB *RBW 100 kHz Delta 2 [T1]
 *VBW 300 kHz 0.72 dB
 *SWT 300 ms 4.680000000 MHz



Date: 18.APR.2008 03:03:34




- Test Mode : WCDMA Band II CH9538 Higher Band Edge
- Power State : High



Date: 21.APR.2008 20:15:46




- Mode 8
- Test Mode : WCDMA Band II (HSUPA) CH9262 Lower Band Edge
- Power State : High



Date: 18.JUN.2008 18:31:28



- Test Mode : WCDMA Band II (HSUPA) CH9262 99% Occupid Bandwidth
- Power State : High



Date: 18.JUN.2008 18:50:24




- Test Mode : WCDMA Band II (HSUPA) CH9400 99% Occupid Bandwidth
- Power State : High



*RBW 100 kHz Marker 1 [T1]
 *VBW 300 kHz 19.57 dBm
 *SWT 300 ms 1.880700000 GHz

Ref 30 dBm


*Att 30 dB



Date: 18.JUN.2008 18:51:26



- Test Mode : WCDMA Band II (HSUPA) CH9538 99% Occupid Bandwidth
- Power State : High



Date: 18.JUN.2008 18:49:19



- Test Mode : WCDMA Band II (HSUPA) CH9262 26dB Bandwidth
- Power State : High




*RBW 100 kHz Delta 2 [T1]
 *VBW 300 kHz 0.22 dB
 *SWT 300 ms 4.680000000 MHz

Ref 30 dBm

*Att 30 dB

1 PK VIEW



Center 1.8524 GHz


1 MHz/

Span 10 MHz

Date: 18.JUN.2008 18:24:22



- Test Mode : WCDMA Band II (HSUPA) CH9400 26dB Bandwidth
- Power State : High



Date: 18.JUN.2008 18:26:08



- Test Mode : WCDMA Band II (HSUPA) CH9538 26dB Bandwidth
- Power State : High




*RBW 100 kHz Delta 2 [T1]
 *VBW 300 kHz 0.02 dB
 *SWT 300 ms 4.680000000 MHz

Ref 30 dBm

*Att 30 dB

1 PK VIEW



Center 1.9076 GHz


1 MHz/

Span 10 MHz

Date: 18.JUN.2008 18:27:25



- Test Mode : WCDMA Band II (HSUPA) CH9538 Higher Band Edge
- Power State : High



Date: 18.JUN.2008 18:32:03

4.5 Conducted Emission


4.5.1 Measurement Instruments

As described in chapter 5 of this test report.

4.5.2 Test Procedure

- a. The EUT was connected to Spectrum Analyzer and Base Station via power divider.
- b. The middle channel for the highest RF power within the transmitting frequency was measured.
- c. The conducted spurious emission for the whole frequency range was taken.


4.5.3 Test Setup Layout





4.5.4 Test Result


- Mode 1
- Test Mode : GSM850 (GSM) CH189
- Frequency Range : 30M-1G



Date: 21.APR.2008 10:18:54




- Test Mode : GSM850 (GSM) CH189
- Frequency Range : 1G-3G



Date: 18.APR.2008 02:34:18



- Test Mode : GSM850 (GSM) CH189
- Frequency Range : 3G-7G



Date: 18.APR.2008 02:35:01



- Test Mode : GSM850 (GSM) CH189
- Frequency Range : 7G-9G




*RBW 1 MHz Marker 1 [T1]
 *VBW 3 MHz -50.63 dBm
 *SWT 500 ms 7.012000000 GHz

Ref 0 dBm

*Att 0 dB

1 PK
VIEW



Start 7 GHz


200 MHz/

Stop 9 GHz

Date: 18.APR.2008 02:37:08



- Mode 2
- Test Mode : GSM850 (EDGE) CH189
- Frequency Range : 30M-1G




Date: 21.APR.2008 10:25:23



- Test Mode : GSM850 (EDGE) CH189
- Frequency Range : 1G-3G




Ref 0 dBm *Att 0 dB *RBW 1 MHz Marker 2 [T1]
 *VBW 3 MHz -51.27 dBm
 *SWT 500 ms 1.672000000 GHz



Date: 18.APR.2008 02:33:36




- Test Mode : GSM850 (EDGE) CH189
- Frequency Range : 3G-7G



Date: 18.APR.2008 02:35:38



- Test Mode : GSM850 (EDGE) CH189
- Frequency Range : 7G-9G



Date: 18.APR.2008 02:36:14




- Mode 3
- Test Mode : GSM1900 (GSM) CH661
- Frequency Range : 30M-1G



*RBW 1 MHz Marker 1 [T1]
 *VBW 3 MHz -25.68 dBm
 *SWT 500 ms 148.34000000 MHz

Ref 30 dBm


*Att 30 dB



Date: 18.APR.2008 02:12:54




- Test Mode : GSM1900 (GSM) CH661
- Frequency Range : 1G-3G



Date: 21.APR.2008 11:16:12



- Test Mode : GSM1900 (GSM) CH661
- Frequency Range : 3G-7G




Date: 18.APR.2008 02:24:11



- Test Mode : GSM1900 (GSM) CH661
- Frequency Range : 7G-13.6G




Ref 0 dBm *Att 0 dB *RBW 1 MHz Marker 2 [T1]
 *VBW 3 MHz -44.54 dBm
 *SWT 500 ms 9.402400000 GHz



Date: 18.APR.2008 02:25:55




- Test Mode : GSM1900 (GSM) CH661
- Frequency Range : 13.6G-19.1G



Date: 18.APR.2008 02:27:45



- Mode 4
- Test Mode : GSM1900 (EDGE) CH661
- Frequency Range : 30M-1G




Date: 18.APR.2008 02:11:47



- Test Mode : GSM1900 (EDGE) CH661
- Frequency Range : 1G-3G




Ref 35 dBm *Att 30 dB *RBW 1 MHz Marker 2 [T1]
 *VBW 3 MHz -31.21 dBm
 *SWT 500 ms 2.968000000 GHz



Date: 21.APR.2008 11:15:01



- Test Mode : GSM1900 (EDGE) CH661
- Frequency Range : 3G-7G




Date: 18.APR.2008 02:23:34



- Test Mode : GSM1900 (EDGE) CH661
- Frequency Range : 7G-13.6G




Ref 0 dBm *Att 0 dB *RBW 1 MHz Marker 2 [T1]
 *VBW 3 MHz -46.18 dBm
 *SWT 500 ms 9.402400000 GHz



Date: 18.APR.2008 02:26:35




- Test Mode : GSM1900 (EDGE) CH661
- Frequency Range : 13.6G-19.1G



Date: 18.APR.2008 02:27:14



- Mode 5
- Test Mode : WCDMA Band V CH4182
- Frequency Range : 30M-1G




Date: 21.APR.2008 11:53:59



- Test Mode : WCDMA Band V CH4182
- Frequency Range : 1G-3G



Ref 0 dBm *Att 0 dB *RBW 1 MHz Marker 2 [T1]
 *VBW 3 MHz -60.42 dBm
 *SWT 500 ms 2.508000000 GHz



Date: 18.APR.2008 03:52:34



- Test Mode : WCDMA Band V CH4182
- Frequency Range : 3G-7G




*RBW 1 MHz Marker 1 [T1]
 *VBW 3 MHz -51.48 dBm
 *SWT 500 ms 3.128000000 GHz

Ref 0 dBm

*Att 0 dB


1 PK VIEW



Date: 18.APR.2008 03:53:12




- Test Mode : WCDMA Band V CH4182
- Frequency Range : 7G-9G



Date: 18.APR.2008 03:53:38




- Mode 6
- Test Mode : WCDMA Band V (HSUPA) CH4182
- Frequency Range : 30M-1G



Date: 18.JUN.2008 19:04:45




- Test Mode : WCDMA Band V (HSUPA) CH4182
- Frequency Range : 1G-3G



Date: 18.JUN.2008 19:13:01




- Test Mode : WCDMA Band V (HSUPA) CH4182
- Frequency Range : 3G-7G



Date: 18.JUN.2008 19:24:41




- Test Mode : WCDMA Band V (HSUPA) CH4182
- Frequency Range : 7G-9G



Date: 18.JUN.2008 19:39:14




- Mode 7
- Test Mode : WCDMA Band II CH9400
- Frequency Range : 30M-1G



Date: 18.APR.2008 03:58:56




- Test Mode : WCDMA Band II CH9400
- Frequency Range : 1G-3G



Date: 21.APR.2008 11:56:39



- Test Mode : WCDMA Band II CH9400
- Frequency Range : 3G-7G



Date: 18.APR.2008 04:00:50



- Test Mode : WCDMA Band II CH9400
- Frequency Range : 7G-13.6G




*RBW 1 MHz Marker 1 [T1]
 *VBW 3 MHz -48.48 dBm
 *SWT 500 ms 13.60000000 GHz

Ref 0 dBm

*Att 0 dB

1 PK
VIEW



Start 7 GHz

660 MHz/

Stop 13.6 GHz

Date: 18.APR.2008 04:01:23



- Test Mode : WCDMA Band II CH9400
- Frequency Range : 13.6G-19.1G




*RBW 1 MHz Marker 1 [T1]
 *VBW 3 MHz -32.89 dBm
 *SWT 500 ms 15.58000000 GHz

Ref 0 dBm

*Att 0 dB

1 PK VIEW



Start 13.6 GHz


550 MHz/

Stop 19.1 GHz

Date: 18.APR.2008 04:02:03




- Mode 8
- Test Mode : WCDMA Band II (HSUPA) CH9400
- Frequency Range : 30M-1G



Date: 18.JUN.2008 19:04:08




- Test Mode : WCDMA Band II (HSUPA) CH9400
- Frequency Range : 1G-3G



Date: 18.JUN.2008 19:16:33




- Test Mode : WCDMA Band II (HSUPA) CH9400
- Frequency Range : 3G-7G



Date: 18.JUN.2008 19:24:21




- Test Mode : WCDMA Band II (HSUPA) CH9400
- Frequency Range : 7G-13.6G



Date: 18.JUN.2008 19:20:48



- Test Mode : WCDMA Band II (HSUPA) CH9400
- Frequency Range : 13.6G-19.1G



Date: 18.JUN.2008 19:21:45



4.6 Field Strength of Spurious Radiation

Equivalent isotropic radiated Power Measurements by substitution method according to ANSI/TIA/EIA-603-C.


4.6.1 Measurement Instruments

As described in chapter 5 of this test report.

4.6.2 Test Procedure

- a. The EUT was placed on a rotatable wooden table with 0.8 meter about ground.
- b. The EUT was set 3 meters from the receiving antenna which was mounted on the antenna tower.
- c. The table was rotated 360 degrees to determine the position of the highest spurious emission.
- d. The height of the receiving antenna is varied between one meter and four meters to reach the maximum spurious emission for both horizontal and vertical polarizations.
- e. Taking the record of maximum spurious emission.
- f. A Horn antenna was substituted in place of the EUT and was driven by a signal generator.
- g. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
- h. Taking the record of output power at antenna port.
- i. Repeat step 7 to step 8 for another polarization.
- j. Emission level (dBm) = output power + substitution Gain.


4.6.3 Test Setup Layout





4.6.4 Test Data

- Mode 1
- Horizontal Polarization



Site : 03CH07-HY
 Condition : FCC PART22/24 HF-EIRP(080306) HORIZONTAL
 EUT : Smart Phone WCDMA? GSM/GPRS/EDGE
 Power : 120Wac/60Hz
 Model : FG 832620
 Mode : GSM 850 Link Mode ; Ch189 + Adaptor
 Plane : H
 IMEI : 35755901003066001


Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1669	-54.89	-13	-41.89	-58.71	-53.9	3.39	4.55	H	Pass
2509	-50.54	-13	-37.54	-57.63	-50.6	3.71	5.92	H	Pass
5850	-53.25	-13	-40.25	-67.67	-55.7	4.38	8.98	H	Pass

Remark : Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



Vertical Polarization
Level (dBm)

Date: 2008-04-08



Trace: (Discrete)


Site : 03CH07-HY
 Condition : FCC PART22/24 HF-EIRP(080306) VERTICAL
 EUT : Smart Phone WCDMA? GSM/GPRS/EDGE
 Power : 120Vac/60Hz
 Model : FG 832620
 Mode : GSM 850 Link Mode ; Ch189 + Adaptor
 Plane : H
 IMEI : 35755901003066001

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1669	-55.48	-13	-42.48	-59.64	-54.1	3.39	4.16	V	Pass
2509	-41.54	-13	-28.54	-52.72	-41.4	3.71	5.72	V	Pass
5850	-49.01	-13	-36.01	-64.18	-52.5	4.38	10.02	V	Pass

Remark : Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



- Mode 2
- Horizontal Polarization




Site : 03CH07-HY
 Condition : FCC PART22/24 HF-EIRP(080306) HORIZONTAL
 EUT : Smart Phone WCDMA? GSM/GPRS/EDGE
 Power : 120Vac/60Hz
 Model : FG 832620
 Mode : EDGE Link Mode ; Ch189 + Adaptor
 Plane : H
 IMEI : 35755901003066001

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1669	-53.69	-13	-40.69	-58.51	-52.7	3.39	4.55	H	Pass
2509	-48.14	-13	-35.14	-55.98	-48.2	3.71	5.92	H	Pass
5850	-52.75	-13	-39.75	-65.56	-55.2	4.38	8.98	H	Pass

Remark : Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



Vertical Polarization



Date: 2008-04-08


Site : 03CH07-HY
 Condition : FCC PART22/24 HF-EIRP(080306) VERTICAL
 EUT : Smart Phone WCDMA? GSM/GPRS/EDGE
 Power : 120Vac/60Hz
 Model : FG 832620
 Mode : EDGE Link Mode ; Ch189 + Adaptor
 Plane : H
 IMEI : 35755901003066001

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1669	-51.98	-13	-38.98	-57.44	-50.6	3.39	4.16	V	Pass
2509	-44.04	-13	-31.04	-54.86	-43.9	3.71	5.72	V	Pass
5850	-49.61	-13	-36.61	-63.94	-53.1	4.38	10.02	V	Pass

Remark : Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



- Mode 3
- Horizontal Polarization




Site : 03CH07-HY
 Condition : FCC PART22/24 HF-EIRP(080306) HORIZONTAL
 EUT : Smart Phone WCDMA? GSM/GPRS/EDGE
 Power : 120Wac/60Hz
 Model : FG 832620
 Mode : PCS 1900 Link Mode ; Ch661 + Adaptor
 Plane : H
 IMEI : 35755901003066001

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-52.43	-13	-39.43	-61.28	-55.8	4.03	7.40	H	Pass
5636	-41.36	-13	-28.36	-58.16	-46.3	3.87	8.81	H	Pass
7520	-37.92	-13	-24.92	-57.39	-41.8	5.83	9.71	H	Pass
9396	-45.70	-13	-32.70	-64.9	-50.4	6.02	10.72	H	Pass

Remark : Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



Vertical Polarization




Site : 03CH07-HY
 Condition : FCC PART22/24 HF-EIRP(080306) VERTICAL
 EUT : Smart Phone WCDMA? GSM/GPRS/EDGE
 Power : 120Wac/60Hz
 Model : FG 832620
 Mode : PCS 1900 Link Mode ; Ch661 + Adaptor
 Plane : H
 IMEI : 35755901003066001

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-51.62	-13	-38.62	-61.85	-55.5	4.03	7.91	V	Pass
5636	-37.60	-13	-24.60	-55.99	-43.5	3.87	9.77	V	Pass
7520	-42.92	-13	-29.92	-63.08	-47.9	5.83	10.81	V	Pass
9396	-47.80	-13	-34.80	-66.62	-53.3	6.02	11.52	V	Pass

Remark : Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



- Mode 4
- Horizontal Polarization




Site : 03CH07-HY
 Condition : FCC PART22/24 HF-EIRP(080306) HORIZONTAL
 EUT : Smart Phone WCDMA? GSM/GPRS/EDGE
 Power : 120Vac/60Hz
 Model : FG 832620
 Mode : EDGE Link Mode ; Ch661 + Adaptor
 Plane : H
 IMEI : 35755901003066001

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-55.73	-13	-42.73	-63.96	-59.1	4.03	7.40	H	Pass
5636	-37.06	-13	-24.06	-55.35	-42	3.87	8.81	H	Pass
7520	-38.62	-13	-25.62	-59.09	-42.5	5.83	9.71	H	Pass

Remark : Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



Vertical Polarization



Date: 2008-04-08

Trace: (Discrete)


Site : 03CH07-HY
 Condition : FCC PART22/24 HF-EIRP(080306) VERTICAL
 EUT : Smart Phone WCDMA? GSM/GPRS/EDGE
 Power : 120Vac/60Hz
 Model : FG 832620
 Mode : EDGE Link Mode ; Ch661 + Adaptor
 Plane : H
 IMEI : 35755901003066001

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
5636	-34.40	-13	-21.40	-53.35	-40.3	3.87	9.77	V	Pass
7520	-42.32	-13	-29.32	-62.59	-47.3	5.83	10.81	V	Pass

Remark : Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



- Mode 5
- Horizontal Polarization




Trace: (Discrete)
 Site : 03CH07-HY
 Condition : FCC PART22/24 HF-EIRP(080306) HORIZONTAL
 EUT : Smart Phone WCDMA? GSM/GPRS/EDGE
 Power : 120Vac/60Hz
 Model : FG 832620
 Mode : WCDMA Band V Link ; Ch4182 + Adaptor
 Plane : H
 IMEI : 35755901003066001

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
2506	-54.84	-13	-41.84	-60.92	-54.9	3.71	5.92	H	Pass

Remark : Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



Vertical Polarization



Date: 2008-04-08

Trace: (Discrete)


Site : 03CH07-HY
 Condition : FCC PART22/24 HF-EIRP(080306) VERTICAL
 EUT : Smart Phone WCDMA? GSM/GPRS/EDGE
 Power : 120Vac/60Hz
 Model : FG 832620
 Mode : WCDMA Band V Link ; Ch4182 + Adaptor
 Plane : H
 IMEI : 35255901003066001

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
2509	-44.74	-13	-31.74	-55.66	-44.6	3.71	5.72	V	Pass

Remark : Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



- Mode 6
- Horizontal Polarization




Trace: (Discrete)
 Site : 03CH07-HY
 Condition : HF-EIRP(080306) HORIZONTAL
 EUT : PDA PHONE WCDMA (Band II/V)
 : + GSM/GPRS/EDGE(850/1800/1900)
 Power : 120Vac/60Hz
 Model : FG832620-02
 Memo : HSUPA Link + Adaptor
 Plane : H
 IMEI : 353176020010238

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
2506	-52.42	-13	-39.42	-62.56	-52.48	3.71	5.92	H	Pass

Remark : Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



Vertical Polarization




Trace: (Discrete)
 Site : 03CH07-HY
 Condition : HF-EIRP(080306) VERTICAL
 EUT : PDA PHONE WCDMA (Band II/V)
 : + GSM/GPRS/EDGE(850/1800/1900)
 Power : 120Vac/60Hz
 Model : FG832620-02
 Memo : HSUPA Link + Adaptor
 Plane : H
 IMEI : 353176020010238

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
2506	-54.32	-13	-41.32	-64.91	-54.18	3.71	5.72	V	Pass

Remark : Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



- Mode 7
- Horizontal Polarization




Trace: (Discrete)
 Site : 03CH07-HY
 Condition : FCC PART22/24 HF-EIRP(080306) HORIZONTAL
 EUT : Smart Phone WCDMA? GSM/GPRS/EDGE
 Power : 120Vac/60Hz
 Model : FG 832620
 Mode : WCDMA Band II Link ; Ch9400 + Adaptor
 Plane : H
 IMEI : 35755901003066001

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-44.73	-13	-31.73	-56.75	-48.1	4.03	7.40	H	Pass
5648	-43.46	-13	-30.46	-59.58	-48.4	3.87	8.81	H	Pass

Remark : Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



Vertical Polarization



Date: 2008-04-08

Trace: (Discrete)


Site : 03CH07-HY
 Condition : FCC PART22/24 HF-EIRP(080306) VERTICAL
 EUT : Smart Phone WCDMA? GSM/GPRS/EDGE
 Power : 120Vac/60Hz
 Model : FG 832620
 Mode : WCDMA Band II Link ; Ch9400 + Adaptor
 Plane : H
 IMEI : 35755901003066001

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-48.42	-13	-35.42	-60.01	-52.3	4.03	7.91	V	Pass
5636	-46.30	-13	-33.30	-60.21	-52.2	3.87	9.77	V	Pass

Remark : Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



- Mode 8
- Horizontal Polarization




Site : 03CH07-HY
 Condition : HF-EIRP(080306) HORIZONTAL
 EUT : PDA PHONE WCDMA (Band II/V)
 : + GSM/GPRS/EDGE(850/1800/1900)
 Power : 120Vac/60Hz
 Model : FG832620-02
 Memo : HSUPA Link + Adaptor
 Plane : H
 IMEI : 353176020010238

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1838	-48.86	-13	-35.86	-57.65	-48.92	4.16	4.22	H	Pass
1916	-57.16	-13	-44.16	-66.30	-56.92	4.31	4.07	H	Pass

Remark : Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



Vertical Polarization



Trace: (Discrete)


Site : 03CH07-HY
 Condition : HF-EIRP(080306) VERTICAL
 EUT : PDA PHONE WCDMA (Band II/V)
 : + GSM/GPRS/EDGE(850/1800/1900)
 Power : 120Vac/60Hz
 Model : FG832620-02
 Memo : HSUPA Link + Adaptor
 Plane : H
 IMEI : 353176020010238

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1836	-45.21	-13	-32.21	-56.21	-44.98	4.16	3.93	V	Pass
1916	-53.48	-13	-40.48	-64.95	-52.99	4.31	3.82	V	Pass

Remark : Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



- Mode 9
- Horizontal Polarization




Site : 03CH07-HY
 Condition : HF-EIRP(080306) HORIZONTAL
 EUT : Smart Phone WCDMA? GSM/GPRS/EDGE
 Power : 120Vac/60Hz
 Model : FG 832620
 Mode : GSM 850 Link Mode ; Ch189 + Adaptor
 : + 11b Tx_Ch06
 Plane : H
 IMEI : 35755901003066001

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1669	-53.79	-13	-40.79	-57.61	-52.8	3.39	4.55	H	Pass
1918	-53.77	-13	-40.77	-60.13	-52.2	3.48	4.06	H	Pass
2509	-48.54	-13	-35.54	-56.45	-48.6	3.71	5.92	H	Pass
5850	-53.15	-13	-40.15	-67.05	-55.6	4.38	8.98	H	Pass

Remark : Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



Vertical Polarization



Trace: (Discrete)
 Site : 03CH07-HY
 Condition : HF-EIRP(080306) VERTICAL
 EUT : Smart Phone WCDMA? GSM/GPRS/EDGE
 Power : 120Vac/60Hz
 Model : FG 832620
 Mode : GSM 850 Link Mode ; Ch189 + Adaptor
 : + 11b Tx_Ch06
 Plane : H
 IMEI : 35755901003066001

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1669	-54.18	-13	-41.18	-58.67	-52.8	3.39	4.16	V	Pass
1918	-51.82	-13	-38.82	-60.87	-50	3.48	3.81	V	Pass
2509	-45.44	-13	-32.44	-56.43	-45.3	3.71	5.72	V	Pass
5850	-49.31	-13	-36.31	-64.03	-52.8	4.38	10.02	V	Pass

Remark : Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

4.7 Frequency Stability (Temperature Variation)


4.7.1 Measurement Instrument

As described in chapter 5 of this test report.

4.7.2 Test Procedure

- a. The EUT and test equipment were set up as shown on the following section.
- b. With all power removed, the temperature was decreased to -30°C and permitted to stabilize for three hours. Power was applied and the maximum change in frequency was noted within one minute.
- c. With power OFF, the temperature was raised in 10°C steps. The sample was permitted to stabilize at each step for at least one-half hour. Power was applied and the maximum frequency change was noted within one minute.
- d. The temperature tests were performed for the worst case.
- e. Test data was recorded.

4.7.3 Test Setup Layout





4.7.4 Test Result

• Test Mode : GSM850 (GSM) CH189

Temperature()	Change (Hz)	Change (ppm)	Limit (ppm)	Result
-30	23	0.01	2.5	Passed
-20	27	0.03		
-10	11	0.01		
0	13	0.02		
10	32	0.04		
20	32	0.04		
30	37	0.04		
40	45	0.05		
50	22	0.03		

• Test Mode : GSM850 (EDGE) CH189

Temperature()	Change (Hz)	Change (ppm)	Limit (ppm)	Result
-30	-34	-0.02	2.5	Passed
-20	11	0.01		
-10	19	0.02		
0	12	0.01		
10	41	0.05		
20	-26	-0.03		
30	13	0.02		
40	27	0.03		
50	54	0.06		

• Test Mode : GSM1900 (GSM) CH661

Temperature()	Change (Hz)	Change (ppm)	Limit (ppm)	Result
-30	46	0.02	2.5	Passed
-20	32	0.02		
-10	-22	-0.01		
0	30	0.02		
10	86	0.05		
20	49	0.03		
30	36	0.02		
40	41	0.02		
50	28	0.01		



• Test Mode : GSM1900 (EDGE) CH661

Temperature()	Change (Hz)	Change (ppm)	Limit (ppm)	Result
-30	127	0.07	2.5	Passed
-20	53	0.03		
-10	47	0.02		
0	41	0.02		
10	52	0.03		
20	33	0.02		
30	34	0.02		
40	26	0.01		
50	11	0.01		

• Test Mode : WCDMA Band V CH4182

Temperature()	Change (Hz)	Change (ppm)	Limit (ppm)	Result
-30	-13	-0.02	2.5	Passed
-20	-23	-0.03		
-10	-15	-0.02		
0	10	0.01		
10	-22	-0.03		
20	-12	-0.01		
30	-17	-0.02		
40	8	0.01		
50	12	0.01		

• Test Mode : WCDMA Band V (HSUPA) CH4182

Temperature()	Change (Hz)	Change (ppm)	Limit (ppm)	Result
-30	32	0.04	2.5	Passed
-20	-27	-0.03		
-10	24	0.03		
0	33	0.04		
10	-36	-0.04		
20	42	0.05		
30	37	0.04		
40	31	0.04		
50	-35	-0.04		



• Test Mode : WCDMA Band II CH9400

Temperature()	Change (Hz)	Change (ppm)	Limit (ppm)	Result
-30	22	0.01	2.5	Passed
-20	36	0.02		
-10	-25	-0.01		
0	-33	-0.02		
10	-59	-0.03		
20	-29	-0.02		
30	-51	-0.03		
40	-22	-0.01		
50	-37	-0.02		

• Test Mode : WCDMA Band II (HSUPA) CH9400

Temperature()	Change (Hz)	Change (ppm)	Limit (ppm)	Result
-30	44	0.02	2.5	Passed
-20	35	0.02		
-10	38	0.02		
0	-42	-0.02		
10	-37	-0.02		
20	-33	-0.02		
30	39	0.02		
40	42	0.02		
50	-54	-0.03		

4.8 Frequency Stability (Voltage Variation)


4.8.1 Measurement Instrument

As described in chapter 5 of this test report.

4.8.2 Test Procedure

- a. The EUT was placed in a temperature chamber at $25\pm 5^{\circ}\text{C}$ and connected as the following section.
- b. The power supply voltage to the EUT was varied from BEP to 115% of the nominal value measured at the input to the EUT.
- c. The variation in frequency was measured for the worst case.

4.8.3 Test Setup Layout



4.8.4 Test Result

- Test Mode : GSM850 (GSM) CH189

Voltage(Volt)	Change (Hz)	Change (ppm)	Limit (ppm)	Result
3.7	32.0	0.04	2.5	Passed
BEP	-73.0	-0.09		
4.2	48.0	0.06		

- Test Mode : GSM850 (EDGE) CH189

Voltage(Volt)	Change (Hz)	Change (ppm)	Limit (ppm)	Result
3.7	-26.0	-0.03	2.5	Passed
BEP	-97.0	-0.11		
4.2	-9.0	-0.01		



- Test Mode : GSM1900 (GSM) CH661

Voltage(Volt)	Change (Hz)	Change (ppm)	Limit (ppm)	Result
3.7	49.0	0.03	2.5	Passed
BEP	-100.0	-0.05		
4.2	80.0	0.04		

- Test Mode : GSM1900 (EDGE) CH661

Voltage(Volt)	Change (Hz)	Change (ppm)	Limit (ppm)	Result
3.7	33.0	0.02	2.5	Passed
BEP	-44.0	-0.02		
4.2	57.0	0.03		

- Test Mode : WCDMA Band V CH4182

Voltage(Volt)	Change (Hz)	Change (ppm)	Limit (ppm)	Result
3.7	-12	-0.01	2.5	Passed
BEP	-96	-0.11		
4.2	34	0.04		

- Test Mode : WCDMA Band V (HSUPA) CH4182

Voltage(Volt)	Change (Hz)	Change (ppm)	Limit (ppm)	Result
3.7	32	0.04	2.5	Passed
BEP	-35	-0.04		
4.2	37	0.04		

- Test Mode : WCDMA Band II CH9400

Voltage(Volt)	Change (Hz)	Change (ppm)	Limit (ppm)	Result
3.7	-29	-0.02	2.5	Passed
BEP	-105	-0.06		
4.2	11	0.01		

- Test Mode : WCDMA Band II (HSUPA) CH9400

Voltage(Volt)	Change (Hz)	Change (ppm)	Limit (ppm)	Result
3.7	-43	-0.02	2.5	Passed
BEP	-40	-0.02		
4.2	-50	-0.03		

Remark:

- Normal Voltage= 3.7V.
- Battery End Point (BEP)= 3.2 V.



5. List of Measurement Equipments

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Due Date	Remark
Thermal Chamber	Tenyi technology	TTH-D35P	TBN-930701	N/A	Aug. 02, 2007	Aug. 01, 2008	Conducted (TH02-HY)
Spectrum	R&S	FSP40	100055	9KHz~40GHz	Jun. 25, 2007	Jun. 24, 2008	Conducted (TH02-HY)
Bluetooth Test	ANRITSU	MT8852A	6K00003939	N/A	N/A	N/A	Conducted (TH02-HY)
Power Divider	ARRA	5200-1	3871	N/A	Oct. 01, 2007	Sep. 30, 2008	Conducted (TH02-HY)
DC Power Supply	TOPWARD	3303D	740889	N/A	May 25, 2007	May 24, 2009	Conducted (TH02-HY)
Power Meter	Agilent	E4416A	GB41292344	N/A	Feb. 21, 2008	Feb. 20, 2009	Conducted (TH02-HY)
Power Sensor	Agilent	E9327A	US40441548	N/A	Feb. 21, 2008	Feb. 20, 2009	Conducted (TH02-HY)
Spectrum Analyzer	Agilent	E4408B	MY44211028	9KHz-26.5GHz	Oct. 17, 2007	Oct. 16, 2008	Radiation (03CH07-HY)
EMI Test Receiver	R&S	ESCS30	100356	9KHz-2.75GHz	Jul. 26, 2007	Jul. 25, 2008	Radiation (03CH07-HY)
Bilog Antenna	SCHAFFNER	CBL6112B	2885	30MHz -2GHz	Dec. 01, 2007	Nov. 30, 2008	Radiation (03CH07-HY)
Double Ridge Horn Antenna	Com-Power	AH118	071025	1G~18G	Jun. 04, 2007	Jun. 03, 2008	Radiation (03CH07-HY)
SHF-EHF Horn	SCHWARZBEC K	BBHA 9170	9170-251	14G - 40G	Oct. 17, 2007	Oct. 16, 2008	Radiation (03CH07-HY)
Pre Amplifier	Agilent	8449B	3008A01917	1G - 26.5G	Nov. 22, 2007	Nov. 21, 2008	Radiation (03CH07-HY)
Pre Amplifier	EMEC	PA303	PA303-SMA-	100K~3GHz	Nov. 26, 2007	Nov. 25, 2008	Radiation (03CH07-HY)
Base Station Simulator	R & S	CMU200	103937	Third-Band	Oct. 19, 2007	Oct. 18, 2008	Radiation (03CH07-HY)

6. Uncertainty Evaluation

Uncertainty of Radiated Emission Measurement (30MHz ~ 1000MHz)

Contribution	Uncertainty of x_i		$u(x_i)$
	dB	Probability Distribution	
Receiver reading	0.41	Normal(k=2)	0.21
Antenna factor calibration	0.83	Normal(k=2)	0.42
Cable loss calibration	0.25	Normal(k=2)	0.13
Pre Amplifier Gain calibration	0.27	Normal(k=2)	0.14
RCV/SPA specification	2.50	Rectangular	0.72
Antenna Factor Interpolation for Frequency	1.00	Rectangular	0.29
Site imperfection	1.43	Rectangular	0.83
Mismatch	+0.39/-0.41	U-shaped	0.28
Combined standard uncertainty Uc(y)	1.27		
Measuring uncertainty for a level of confidence of 95% U=2Uc(y)	2.54		

Uncertainty of Radiated Emission Measurement (1GHz ~ 40GHz)

Contribution	Uncertainty of x_i		$u(x_i)$	C_i	$C_i * u(x_i)$
	dB	Probability Distribution			
Receiver reading	±0.10	Normal(k=1)	0.10	1	0.10
Antenna factor calibration	±1.70	Normal(k=2)	0.85	1	0.85
Cable loss calibration	±0.50	Normal(k=2)	0.25	1	0.25
Receiver Correction	±2.00	Rectangular	1.15	1	1.15
Antenna Factor Directional	±1.50	Rectangular	0.87	1	0.87
Site imperfection	±2.80	Triangular	1.14	1	1.14
Mismatch Receiver VSWR $\Gamma_1 = 0.197$ Antenna VSWR $\Gamma_2 = 0.194$ Uncertainty = $20 \log(1 - \Gamma_1 * \Gamma_2 * \Gamma_3)$	+0.34/-0.35	U-shaped	0.244	1	0.244
Combined standard uncertainty Uc(y)	2.36				
Measuring uncertainty for a level of confidence of 95% U=2Uc(y)	4.72				

END OF TEST REPORT



Appendix A. Photographs of EUT

Please refer to Sporton report number EP832620 as below.