



# FCC SAR Test Report

**APPLICANT** : HTC Coporation  
**EQUIPMENT** : Smartphone  
**MODEL NAME** : PC36100  
**FCC ID** : NM8PC36100  
**STANDARD** : FCC 47 CFR Part 2 (2.1093)  
IEEE C95.1-1999  
IEEE 1528-2003  
FCC OET Bulletin 65 Supplement C (Edition 01-01)

The product was received on May 06, 2010 and completely tested on May 09, 2010. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the procedures and shown the compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by:

Roy Wu / Manager



**SPORTON INTERNATIONAL INC.**

No. 52, Hwa Ya 1<sup>st</sup> Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.



Table of Contents

Revision History..... 3
1. Statement of Compliance ..... 4
2. Administration Data ..... 5
2.1 Testing Laboratory ..... 5
2.2 Applicant..... 5
2.3 Manufacturer ..... 5
2.4 Application Details ..... 5
3. General Information ..... 6
3.1 Description of Device Under Test (DUT)..... 6
3.2 Product Photos ..... 6
3.3 Applied Standards ..... 6
3.4 Device Category and SAR Limits ..... 6
3.5 Test Conditions ..... 7
3.5.1 Ambient Condition ..... 7
3.5.2 Test Configuration..... 7
4. Specific Absorption Rate (SAR).....11
4.1 Introduction ..... 11
4.2 SAR Definition ..... 11
5. SAR Measurement System.....12
5.1 E-Field Probe.....13
5.1.1 E-Field Probe Specification ..... 13
5.1.2 E-Field Probe Calibration..... 14
5.2 Data Acquisition Electronics (DAE).....14
5.3 Robot.....14
5.4 Measurement Server .....15
5.5 Phantom .....16
5.6 Device Holder .....17
5.7 Data Storage and Evaluation.....19
5.7.1 Data Storage ..... 19
5.7.2 Data Evaluation ..... 19
5.8 Test Equipment List .....21
6. Tissue Simulating Liquids.....22
7. Uncertainty Assessment .....24
8. SAR Measurement Evaluation .....27
8.1 Purpose of System Performance check .....27
8.2 System Setup .....27
8.3 Validation Results .....28
9. DUT Testing Position .....29
10. Measurement Procedures .....32
10.1 Spatial Peak SAR Evaluation .....32
10.2 Scan Procedures.....33
10.3 SAR Averaged Methods .....33
10.4 Power Drift Monitoring.....33
11. SAR Test Results .....34
11.1 Conducted Power (Unit: dBm).....34
11.2 Scaling Factor Deriving .....35
11.3 Test Records for Head SAR Test .....37
11.4 Test Records for Body SAR Test .....38
11.5 Linearity Response Check.....39
11.6 Compare with Different Scan Resolution .....41
12. References.....42

Appendix A. Plots of System Performance Check

Appendix B. Plots of SAR Measurement

Appendix C. DASy Calibration Certificate

Appendix D. Product Photos

Appendix E. Test Setup Photos

Appendix F. Plots of Duty Cycle





**1. Statement of Compliance**

The maximum result of Specific Absorption Rate (SAR) found during testing for **HTC Coporation Smartphone PC36100** are follows (with expanded uncertainty 21.4 % for 300 MHz to 3 GHz, and 25.6 % for 3 GHz to 6 GHz).

<b>Band</b>	<b>Position</b>	<b>Measured SAR<sub>1g</sub> (W/kg)</b>	<b>Scaled SAR<sub>1g</sub> (W/kg)</b>
<b>802.16e</b>	<b>Head</b>	<b>0.293</b>	<b>0.328</b>
	<b>Body</b>	<b>0.416</b>	<b>0.470</b>

They are in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6 W/kg) specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1999, and had been tested in accordance with the measurement methods and procedures specified in IEEE 1528-2003 and FCC OET Bulletin 65 Supplement C (Edition 01-01).



## 2. Administration Data

### 2.1 Testing Laboratory

Test Site	SPORTON INTERNATIONAL INC.
Test Site Location	No. 52, Hwa Ya 1 <sup>st</sup> Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL: +886-3-327-3456 FAX: +886-3-328-4978
Test Site No.	<b>Sporton Site No. :</b> SAR01-HY

### 2.2 Applicant

Company Name	HTC Coporation
Address	6-3, Baoquang Rd., Xindian City, Taipei County, Taiwan

### 2.3 Manufacturer

Company Name	HTC Coporation
Address	6-3, Baoquang Rd., Xindian City, Taipei County, Taiwan

### 2.4 Application Details

Date of Receipt of Application	May 06, 2010
Date of Start during the Test	May 06, 2010
Date of End during the Test	May 09, 2010

**3. General Information**

**3.1 Description of Device Under Test (DUT)**

Product Feature & Specification	
DUT Type	Smartphone
Model Name	PC36100
FCC ID	NM8PC36100
Tx Frequency	2496 MHz ~ 2690 MHz
Rx Frequency	2496 MHz ~ 2690 MHz
Maximum Output Power to Antenna	BW 5M : 23.71 dBm BW 10M : 23.68 dBm
Antenna Type	PIFA Antenna
Type of Modulation	Uplink : OFDMA (QPSK / 16QAM)
DUT Stage	Production Unit

**Remark:** The above DUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

**3.2 Product Photos**

Please refer to Appendix D.

**3.3 Applied Standards**

The Specific Absorption Rate (SAR) testing specification, method and procedure for this Smartphone is in accordance with the following standards:

- FCC 47 CFR Part 2 (2.1093)
- IEEE C95.1-1999
- IEEE 1528-2003
- FCC OET Bulletin 65 Supplement C (Edition 01-01)
- FCC KDB 615223 D01 v01
- FCC KDB 648474 D01 v01r05
- 2010 TCB Workshop RF Exposure Procedures-Review

**3.4 Device Category and SAR Limits**

This device belongs to portable device category because its radiating structure is allowed to be used within 20 centimeters of the body of the user. Limit for General Population/Uncontrolled exposure should be applied for this device, it is 1.6 W/kg as averaged over any 1 gram of tissue.



### 3.5 Test Conditions

#### 3.5.1 Ambient Condition

Ambient Temperature	20 to 24 °C
Humidity	< 60 %

#### 3.5.2 Test Configuration

The test device is a 2.6 GHz WiMAX transceiver. It provides one completed transmitter and two receivers. This Smartphone has two built-in antennas and it supports Tx antenna diversity function. Only one transmitting antenna can be used simultaneously.

The device only transmits by PUSC zone type. The other zone types, AMC, and FUSC, are not available on this device. The maximum DL:UL (downlink-to-uplink) symbol ratio is determined according to the PUSC requirements. The system transmits an odd number of symbols using DL-PUSC, consisting of even multiples of traffic and control symbols, plus one symbol for the preamble. The device transmits in multiples of three symbols using UL-PUSC. The OFDMA symbol time allows up to 48 downlink and uplink symbols to be transmitted in each 5 ms frame. The system transmits on 5 ms frames using 5 MHz and 10 MHz channels. TTG and RTG are also included in each frame as DL/UL transmission gaps; therefore, the system can only allow 47 or less symbols per frame. The maximum DL:UL symbol ratio allowed for this device and determined according to these PUSC parameters is 29:18.

For PUSC zone type, the 10 MHz channel bandwidth uses 1024 sub-carriers and 35 sub-channels, with 184 spare/safeguard sub-carriers and 840 available for transmission, consisting of 560 data and 280 pilot sub-carriers. The 5 MHz channel bandwidth uses 512 sub-carriers and 17 sub-channels, with 104 spare/safeguard sub-carriers and 408 available for transmission, consisting 272 data and 136 pilot sub-carriers.

Control signals are transmitted in the first 3 symbols of each uplink burst. The rest of the uplink sub-frame contains normal traffic data bursts. The first 3 symbols are also used for ranging, which is shared with other users. During normal operation, the control symbols are transmitted at reduced power and the traffic symbols may transmit at maximum power. For SAR testing purposes, the configuration of control symbols is dependent on the test software and test equipment setup. The uplink allows a maximum of 15 traffic and 3 control symbols, 18 total, per frame. These conditions are applicable to both 5 and 10 MHz channel configurations used by this device.



The 802.16e/WiMAX device and system operating parameters is as below.

Description	Parameter		Comment
FCC ID	NM8PC36100		Identify all related FCC ID
Radio Service	Part 27 Subpart M		Rule parts
Transmit Frequency Range (MHz)	2496 MHz to 2690 MHz		System parameter
System/Channel Bandwidth (MHz)	5 MHz	10 MHz	System parameter
System Profile	Revision 1.7.0		Defined by WiMAX Forum
Modulation Schemes	QPSK, 16QAM		Identify all applicable UL modulations
Sampling Factor	28/25		System parameter
Sampling Frequency (MHz)	5.6 MHz	11.2 MHz	(F <sub>s</sub> )
Sample Time (ns)	178.581 ns	89.3 ns	(1/F <sub>s</sub> )
FFT Size (N <sub>FFT</sub> )	512	1024	(N <sub>FFT</sub> )
Sub-Carrier Spacing (kHz)	10.9375 kHz		(Δ f)
Useful Symbol Time (μs)	91.43 μs		(T <sub>b</sub> =1/Δ f)
Guard Time (μs)	11.43 μs		(T <sub>g</sub> =T <sub>b</sub> /cp); cp = cyclic prefix
OFDMA Symbol Time (μs)	102.86 μs		(T <sub>s</sub> =T <sub>b</sub> +T <sub>g</sub> )
Frame Size (ms)	5 ms		System parameter
TTG + RTG (μs or number of symbols)	165.7143 μs		Idle time, system parameter
Number of DL OFDMA Symbols per Frame	29		Identify the allowed & maximum symbols, including both traffic & control symbols
Number of UL OFDMA Symbols per Frame	18		
DL:UL Symbol Ratios	29:18		For determining UL duty factor
Power Class (dBm)	Power Class 2, 23±1 dBm		Identify power class and tolerance
Wave1 / Wave2	Wave2, 2 antenna with receive MRC DL MIMO matrix A and B		Describe antenna diversity info and MIMO requirements separately
UL Zone Types (FUSC, PUSC, OFUSC, OPUSC, AMC, TUSC1, TUSC2)	Segmented PUSC Unsegmented PUSC		Describe separately the symbol and sub-carrier/sub-channel structures applicable to each zone type
Maximum Number of UL Sub-Carriers	409	841	Identify the allowed and tested / to be tested parameters; include separate explanations on the types of control symbols and how the power levels are determined
Measured UL Burst Maximum Average Conducted Power	23.71 dBm	23.68 dBm	
UL Control Symbol Configuration	3 PUSC symbols (used for ranging, CQICH and ACK/NACK)		
UL Control Symbol Maximum Conducted Average Power	73.88 mW	35.88 mW	
UL Burst Peak-to-Average (Conducted) Power Ratio (PAPR)	PAPR is between 7.15 ~ 9.82 dB A Anritus wideband power meter was used to measure this item. Average, peak and PAPR are measured simultaneously. The test records please refer to section 11.1 of this report.		Identify the expected range and measured/tested PAR; explain separately the methods used / to be used to address SAR probe calibration and measurement error issues
Frame Averaged UL Transmission Duty Factor (%)	Duty cycle was measured by a spectrum. The measured duty cycle is 31.3 % to 31.5 %. Theoretical duty cycle is 15 x 102.857 μs / 5000 μs = 30.86 %. cf = 1/(duty cycle) = 3.24. This cf was used for SAR evaluation.		Show calculations separately and explain how the applicable CF ( <i>crest factor</i> ) used / to be use in the SAR measurements is derived and how the control symbols are accounted for



Time Vector Plots and Duty Cycle

The plot below shows the waveform characteristics of the signal used in the SAR measurement. The pulse duration corresponds to a DL:UL symbol ratio of 29:18 and control symbols are not active.

The plots of time vector and calculation of duty cycle can be referred to appendix F. The plot A is used to get the frame length of test signal and the plot B is used to get the time of UL data symbols. Since there was no energy in the control symbols, the effective power is only across 15 data symbols. The calculation of duty cycle is as below:

Duty Cycle = 15 data symbols UL time / Frame Length x 100 %

Summary table is shown as below.

Table with 6 columns: Zone Type, Modulation, Coding Rate, Frequency (MHz), Duty Cycle (%), Crest Factor (%). It lists various test configurations for PUSC and QPSK modulation schemes across different frequencies and coding rates.

Note: Crest Factor = 1 / Duty Cycle.



**Test Software Details**

The DUT use the HyperTerminal (AT Command) installed on a host laptop computer to configure the DUT into the engineering mode. In engineering mode, the transmitter parameters for antenna, BW, modulation, frequency and transmitting maximum power can be set, and the DUT can receive control signal from system simulator, Agilent E6651A, to keep transmitting WiMAX signal. The uplink transmission (signal characteristics such as BW, modulation, frequency and DL:UL ratio) is maintained at a stable condition by the FCH, UL-MAP and DL-MAP information transmitted over the air from the Agilent E6651A. This enables the DUT to transmit at maximum power with a constant duty factor according to the maximum DL:UL symbol ratio 29:18, using a specific modulation, zone type, sub-channel configuration and other operating requirements. The test software for this device serves only one purpose, to configure the DUT into engineering mode during the SAR measurements.

**Communication Test Set Details**

A system simulator, Agilent E6651A, is used in conjunction with DUT engineering mode to configure the DUT for the SAR measurements. The Agilent E6651A is configured to transmit the downlink signals, containing the respective FCH, DL-MAP and UL-MAP required by the DUT to configure the DUT uplink transmissions. The waveform is configured for a DL:UL symbol ratio of 29:18. The DUT can synchronize itself to the signals received from the Agilent E6651A, both in frequency and time. It then demodulates the DL-MAP and UL-MAP transmitted in each downlink sub-frame and determines the DL:UL symbol ratio (29:18). This downlink burst is repeated in each frame, every 5 ms, to simulate the transmission from a WiMax base station. The UL-MAP received by the DUT is used to configure the uplink burst with all data (traffic) symbols and sub-channels active.

In fact, the DUT have not linked with Agilent E6651A. The DUT only receive the control signal from Agilent E6651A and then transmitting maximum power on the specific configuration. Therefore, no control channel transmissions are requested by the system simulator. SAR measurement were taken in this configuration with the DUT transmitting using the 29:18 ratio, but since there was no energy in the control symbols, the effective power is only across 15 data symbols.

The steps for system simulator setup are as below

1. Set the appropriate source amplitude and attenuation
2. Load the system profile of bandwidth 5M or 10M
3. Set the operating frequency
4. Set the UL modulation to operating mode
5. Set the test mode to UL padding test
6. Set and send the RNG-RSP message
7. Set the run test on

## **4. Specific Absorption Rate (SAR)**

### **4.1 Introduction**

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

### **4.2 SAR Definition**

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density ( $\rho$ ). The equation description is as below:

$$\text{SAR} = \frac{d}{dt} \left( \frac{dW}{dm} \right) = \frac{d}{dt} \left( \frac{dW}{\rho dv} \right)$$

SAR is expressed in units of Watts per kilogram (W/kg)

SAR measurement can be either related to the temperature elevation in tissue by

$$\text{SAR} = C \left( \frac{\delta T}{\delta t} \right)$$


Where: C is the specific heat capacity,  $\delta T$  is the temperature rise and  $\delta t$  is the exposure duration, or related to the electrical field in the tissue by

$$\text{SAR} = \frac{\sigma |E|^2}{\rho}$$

Where:  $\sigma$  is the conductivity of the tissue,  $\rho$  is the mass density of the tissue and E is the RMS electrical field strength.

However for evaluating SAR of low power transmitter, electrical field measurement is typically applied.

## 5. SAR Measurement System



**Fig 5.1 SPEAG DASY4 System Configurations**

The DASY4 system for performance compliance tests is illustrated above graphically. This system consists of the following items:

- A standard high precision 6-axis robot with controller, a teach pendant and software
- A data acquisition electronic (DAE) attached to the robot arm extension
- A dosimetric probe equipped with an optical surface detector system
- The electro-optical converter (ECO) performs the conversion between optical and electrical signals
- A measurement server performs the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- A probe alignment unit which improves the accuracy of the probe positioning
- A computer operating Windows XP
- DASY4 software
- Remote control with teach pendant and additional circuitry for robot safety such as warning lamps, etc.
- The SAM twin phantom
- A device holder
- Tissue simulating liquid
- Dipole for evaluating the proper functioning of the system

Some of the components are described in details in the following sub-sections.


**5.1 E-Field Probe**

The SAR measurement is conducted with the dosimetric probe (manufactured by SPEAG). The probe is specially designed and calibrated for use in liquid with high permittivity. The dosimetric probe has special calibration in liquid at different frequency. This probe has a built in optical surface detection system to prevent from collision with phantom.

**5.1.1 E-Field Probe Specification**

**<ET3DV6>**


<b>Construction</b>	Symmetrical design with triangular core Built-in optical fiber for surface detection system. Built-in shielding against static charges. PEEK enclosure material (resistant to organic solvents, e.g., DGBE)
<b>Frequency</b>	10 MHz to 3 GHz; Linearity: $\pm 0.2$ dB
<b>Directivity</b>	$\pm 0.2$ dB in HSL (rotation around probe axis) $\pm 0.4$ dB in HSL (rotation normal to probe axis)
<b>Dynamic Range</b>	5 $\mu$ W/g to 100 mW/g; Linearity: $\pm 0.2$ dB
<b>Dimensions</b>	Overall length: 330 mm (Tip: 16 mm) Tip diameter: 6.8 mm (Body: 12 mm) Distance from probe tip to dipole centers: 2.7 mm



**Fig 5.2 Photo of ET3DV6**

**<EX3DV3 Probe>**

<b>Construction</b>	Symmetrical design with triangular core Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)
<b>Frequency</b>	10 MHz to 6 GHz; Linearity: $\pm 0.2$ dB
<b>Directivity</b>	$\pm 0.3$ dB in HSL (rotation around probe axis) $\pm 0.5$ dB in tissue material (rotation normal to probe axis)
<b>Dynamic Range</b>	10 $\mu$ W/g to 100 mW/g; Linearity: $\pm 0.2$ dB (noise: typically $< 1$ $\mu$ W/g)
<b>Dimensions</b>	Overall length: 330 mm (Tip: 20 mm) Tip diameter: 2.5 mm (Body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm



**Fig 5.3 Photo of EX3DV3**

### 5.1.2 E-Field Probe Calibration

Each probe needs to be calibrated according to a dosimetric assessment procedure with accuracy better than  $\pm 10\%$ . The spherical isotropy shall be evaluated and within  $\pm 0.25$  dB. The sensitivity parameters (NormX, NormY, and NormZ), the diode compression parameter (DCP) and the conversion factor (ConvF) of the probe are tested. The calibration data can be referred to appendix C of this report.

### 5.2 Data Acquisition Electronics (DAE)

The data acquisition electronics (DAE) consists of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder and control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information as well as an optical uplink for commands and the clock. The input impedance of the DAE is 200 MOhm; the inputs are symmetrical and floating. Common mode rejection is above 80 dB.



Fig 5.4 Photo of DAE

### 5.3 Robot

The SPEAG DASY system uses the high precision robots (DASY4: RX90BL) type from Stäubli SA (France). For the 6-axis controller system, the robot controller version (DASY4: CS7MB) from Stäubli is used. The Stäubli robot series have many features that are important for our application:

- High precision (repeatability  $\pm 0.035$  mm)
- High reliability (industrial design)
- Jerk-free straight movements
- Low ELF interference (the closed metallic construction shields against motor control fields)




Fig 5.5 Photo of DASY4

### **5.4 Measurement Server**

The measurement server is based on a PC/104 CPU board with CPU (DASY4: 166 MHz, Intel Pentium), chipdisk (DASY4: 32 MB), RAM (DASY4: 64 MB). The necessary circuits for communication with the DAE electronic box, as well as the 16 bit AD converter system for optical detection and digital I/O interface are contained on the DASY I/O board, which is directly connected to the PC/104 bus of the CPU board.

The measurement server performs all the real-time data evaluation for field measurements and surface detection, controls robot movements and handles safety operations.



**Fig 5.6 Photo of Server for DASY4**

### 5.5 Phantom

#### <SAM Twin Phantom>

<b>Shell Thickness</b>	2 ± 0.2 mm; Center ear point: 6 ± 0.2 mm
<b>Filling Volume</b>	Approx. 25 liters
<b>Dimensions</b>	Length: 1000 mm; Width: 500 mm; Height: adjustable feet
<b>Measurement Areas</b>	Left Hand, Right Hand, Flat Phantom



Fig 5.7 Photo of SAM Phantom

The bottom plate contains three pair of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections. A white cover is provided to tap the phantom during off-periods to prevent water evaporation and changes in the liquid parameters. On the phantom top, three reference markers are provided to identify the phantom position with respect to the robot.

#### <ELI4 Phantom>

<b>Shell Thickness</b>	2 ± 0.2 mm (sagging: <1%)
<b>Filling Volume</b>	Approx. 30 liters
<b>Dimensions</b>	Major ellipse axis: 600 mm Minor axis: 400 mm



Fig 5.8 Photo of ELI4 Phantom

The ELI4 phantom is intended for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI4 is fully compatible with standard and all known tissue simulating liquids.

## 5.6 Device Holder

### <Device Holder for SAM Twin Phantom>

The SAR in the phantom is approximately inversely proportional to the square of the distance between the source and the liquid surface. For a source at 5 mm distance, a positioning uncertainty of  $\pm 0.5$  mm would produce a SAR uncertainty of  $\pm 20$  %. Accurate device positioning is therefore crucial for accurate and repeatable measurements. The positions in which the devices must be measured are defined by the standards.

The DASY device holder is designed to cope with different positions given in the standard. It has two scales for the device rotation (with respect to the body axis) and the device inclination (with respect to the line between the ear reference points). The rotation center for both scales is the ear reference point (EPR). Thus the device needs no repositioning when changing the angles.


The DASY device holder is constructed of low-loss POM material having the following dielectric parameters: relative permittivity  $\epsilon = 3$  and loss tangent  $\delta = 0.02$ . The amount of dielectric material has been reduced in the closest vicinity of the device, since measurements have suggested that the influence of the clamp on the test results could thus be lowered.



Fig 5.9 Device Holder

**<Laptop Extension Kit>**

The extension is lightweight and made of POM, acrylic glass and foam. It fits easily on the upper part of the mounting device in place of the phone positioned. The extension is fully compatible with the SAM Twin and ELI phantoms.



**Fig 5.10 Laptop Extension Kit**



## 5.7 Data Storage and Evaluation

### 5.7.1 Data Storage

The DASY software stores the assessed data from the data acquisition electronics as raw data (in microvolt readings from the probe sensors), together with all the necessary software parameters for the data evaluation (probe calibration data, liquid parameters and device frequency and modulation data) in measurement files. The post-processing software evaluates the desired unit and format for output each time the data is visualized or exported. This allows verification of the complete software setup even after the measurement and allows correction of erroneous parameter settings. For example, if a measurement has been performed with an incorrect crest factor parameter in the device setup, the parameter can be corrected afterwards and the data can be reevaluated.

The measured data can be visualized or exported in different units or formats, depending on the selected probe type (e.g., [V/m], [A/m], [mW/g]). Some of these units are not available in certain situations or give meaningless results, e.g., a SAR-output in a non-lose media, will always be zero. Raw data can also be exported to perform the evaluation with other software packages.

### 5.7.2 Data Evaluation

The DASY post-processing software (SEMCAD) automatically executes the following procedures to calculate the field units from the microvolt readings at the probe connector. The parameters used in the evaluation are stored in the configuration modules of the software :

<b>Probe parameters :</b>	- Sensitivity	Norm <sub>i</sub> , a <sub>10</sub> , a <sub>11</sub> , a <sub>12</sub>
	- Conversion factor	ConvF <sub>i</sub>
	- Diode compression point	dcp <sub>i</sub>
<b>Device parameters :</b>	- Frequency	f
	- Crest factor	cf
<b>Media parameters :</b>	- Conductivity	σ
	- Density	ρ

These parameters must be set correctly in the software. They can be found in the component documents or they can be imported into the software from the configuration files issued for the DASY components. In the direct measuring mode of the multi-meter option, the parameters of the actual system setup are used. In the scan visualization and export modes, the parameters stored in the corresponding document files are used.

The first step of the evaluation is a linearization of the filtered input signal to account for the compression characteristics of the detector diode. The compensation depends on the input signal, the diode type and the DC-transmission factor from the diode to the evaluation electronics. If the exciting field is pulsed, the crest factor of the signal must be known to correctly compensate for peak power.

The formula for each channel can be given as :

$$V_i = U_i + U_i^2 \cdot \frac{cf}{dcp_i}$$

with  $V_i$  = compensated signal of channel i, (i = x, y, z)  
 $U_i$  = input signal of channel i, (i = x, y, z)  
 cf = crest factor of exciting field (DASY parameter)  
 dcp<sub>i</sub> = diode compression point (DASY parameter)

From the compensated input signals, the primary field data for each channel can be evaluated :

$$\text{E-field Probes : } E_i = \sqrt{\frac{V_i}{\text{Norm}_i \cdot \text{ConvF}}}$$

$$\text{H-field Probes : } H_i = \sqrt{V_i} \cdot \frac{a_{i0} + a_{i1}f + a_{i2}f^2}{f}$$

with  $V_i$  = compensated signal of channel i, (i = x, y, z)  
 $\text{Norm}_i$  = sensor sensitivity of channel i, (i = x, y, z),  $\mu\text{V}/(\text{V/m})^2$  for E-field Probes  
 ConvF = sensitivity enhancement in solution  
 $a_{ij}$  = sensor sensitivity factors for H-field probes  
 f = carrier frequency [GHz]  
 $E_i$  = electric field strength of channel i in V/m  
 $H_i$  = magnetic field strength of channel i in A/m

The RSS value of the field components gives the total field strength (Hermitian magnitude) :

$$E_{\text{tot}} = \sqrt{E_x^2 + E_y^2 + E_z^2}$$

The primary field data are used to calculate the derived field units.

$$\text{SAR} = E_{\text{tot}}^2 \cdot \frac{\sigma}{\rho \cdot 1000}$$

with SAR = local specific absorption rate in mW/g  
 $E_{\text{tot}}$  = total field strength in V/m  
 $\sigma$  = conductivity in [mho/m] or [Siemens/m]  
 $\rho$  = equivalent tissue density in  $\text{g/cm}^3$

Note that the density is set to 1, to account for actual head tissue density rather than the density of the tissue simulating liquid.



5.8 Test Equipment List

Manufacturer	Name of Equipment	Type/Model	Serial Number	Calibration	
				Last Cal.	Due Date
SPEAG	Dosimetric E-Field Probe	EX3DV3	3514	Jan. 26, 2010	Jan. 25, 2011
SPEAG	2600MHz System Validation Kit	D2600V2	1008	Sep. 24, 2009	Sep. 23, 2011
SPEAG	Data Acquisition Electronics	DAE3	577	Aug. 24, 2009	Aug. 23, 2010
SPEAG	Device Holder	N/A	N/A	NCR	NCR
SPEAG	SAM Phantom	QD 000 P40 C	TP-1303	NCR	NCR
SPEAG	SAM Phantom	QD 000 P40 C	TP-1383	NCR	NCR
SPEAG	SAM Phantom	QD 000 P40 C	TP-1446	NCR	NCR
SPEAG	SAM Phantom	QD 000 P40 C	TP-1477	NCR	NCR
SPEAG	ELI4 Phantom	QD 0VA 001 BB	1026	NCR	NCR
SPEAG	ELI4 Phantom	QD 0VA 001 BA	1029	NCR	NCR
Agilent	Network Analyzer	E5071B	MY42403579	May 26, 2009	May 25, 2010
Agilent	WiMAX Communication Test Set	E6651A	MY47310158	Sep. 23, 2008	Sep. 22, 2010
Agilent	Dielectric Probe Kit	85070D	US01440205	NCR	NCR
Agilent	Dual Directional Coupler	778D	50422	NCR	NCR
AR	Power Amplifier	5S1G4M2	0328767	NCR	NCR
R&S	Spectrum Analyzer	FSP7	101131	Mar. 05, 2010	Mar. 04, 2011
Anritsu	Power Meter	ML2495A	0932001	Sep. 17, 2009	Sep. 16, 2010
Anritsu	Power Sensor	MA2411B	0846202	Sep. 10, 2009	Sep. 09, 2010

Table 5.1 Test Equipment List

Note: The calibration certificate of DASy can be referred to appendix C of this report.

## 6. Tissue Simulating Liquids

For the measurement of the field distribution inside the SAM phantom with DASY, the phantom must be filled with around 25 liters of homogeneous body tissue simulating liquid. For head SAR testing, the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm, which is shown in Fig. 6.1. For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15 cm, which is shown in Fig. 6.2.




Fig 6.1 Photo of Liquid Height for Head SAR



Fig 6.2 Photo of Liquid Height for Body SAR

The following table gives the targets for tissue simulating liquid.

Frequency (MHz)	Liquid Type	Conductivity ( $\sigma$ )	$\pm 5\%$ Range	Permittivity ( $\epsilon_r$ )	$\pm 5\%$ Range
2600	Head	1.96	1.87 ~ 2.06	39.0	37.1 ~ 41.0
2600	Body	2.16	2.05 ~ 2.27	52.5	49.9 ~ 55.1

Table 6.1 Targets of Tissue Simulating Liquid

The dielectric parameters of the liquids were verified prior to the SAR evaluation using an Agilent 85070D Dielectric Probe Kit and an Agilent Network Analyzer.



The following table shows the measuring results for simulating liquid.

Frequency (MHz)	Liquid Type	Temperature (°C)	Conductivity ( $\sigma$ )	Permittivity ( $\epsilon_r$ )	Measurement Date
2600	Head	21.5	1.97	38.2	May 06, 2010
2600	Head	21.3	1.96	38.1	May 07, 2010
2600	Head	21.6	1.93	37.9	May 09, 2010
2600	Body	21.5	2.21	51.1	May 06, 2010
2600	Body	21.5	2.17	53.8	May 07, 2010
2600	Body	21.4	2.19	51.0	May 09, 2010

Table 6.2 Measuring Results for Simulating Liquid

## **7. Uncertainty Assessment**

The component of uncertainty may generally be categorized according to the methods used to evaluate them. The evaluation of uncertainty by the statistical analysis of a series of observations is termed a Type A evaluation of uncertainty. The evaluation of uncertainty by means other than the statistical analysis of a series of observations is termed a Type B evaluation of uncertainty. Each component of uncertainty, however evaluated, is represented by an estimated standard deviation, termed standard uncertainty, which is determined by the positive square root of the estimated variance.

A Type A evaluation of standard uncertainty may be based on any valid statistical method for treating data. This includes calculating the standard deviation of the mean of a series of independent observations; using the method of least squares to fit a curve to the data in order to estimate the parameter of the curve and their standard deviations; or carrying out an analysis of variance in order to identify and quantify random effects in certain kinds of measurement.

A type B evaluation of standard uncertainty is typically based on scientific judgment using all of the relevant information available. These may include previous measurement data, experience and knowledge of the behavior and properties of relevant materials and instruments, manufacturer's specification, data provided in calibration reports and uncertainties assigned to reference data taken from handbooks. Broadly speaking, the uncertainty is either obtained from an outdoor source or obtained from an assumed distribution, such as the normal distribution, rectangular or triangular distributions indicated in Table 7.1

<b>Uncertainty Distributions</b>	<b>Normal</b>	<b>Rectangular</b>	<b>Triangular</b>	<b>U-Shape</b>
Multi-plying Factor <sup>(a)</sup>	1/k <sup>(b)</sup>	1/√3	1/√6	1/√2

(a) standard uncertainty is determined as the product of the multiplying factor and the estimated range of variations in the measured quantity

(b)  $\kappa$  is the coverage factor

**Table 7.1 Standard Uncertainty for Assumed Distribution**

The combined standard uncertainty of the measurement result represents the estimated standard deviation of the result. It is obtained by combining the individual standard uncertainties of both Type A and Type B evaluation using the usual "root-sum-squares" (RSS) methods of combining standard deviations by taking the positive square root of the estimated variances.

Expanded uncertainty is a measure of uncertainty that defines an interval about the measurement result within which the measured value is confidently believed to lie. It is obtained by multiplying the combined standard uncertainty by a coverage factor. Typically, the coverage factor ranges from 2 to 3. Using a coverage factor allows the true value of a measured quantity to be specified with a defined probability within the specified uncertainty range. For purpose of this document, a coverage factor two is used, which corresponds to confidence interval of about 95 %. The DASY uncertainty Budget is showed in Table 7.2 and Table 7.3.



Error Description	Uncertainty Value (±%)	Probability Distribution	Divisor	Ci (1g)	Standard Uncertainty (1g)
<b>Measurement System</b>					
Probe Calibration	5.5	Normal	1	1	± 5.5 %
Axial Isotropy	4.7	Rectangular	√3	0.7	± 1.9 %
Hemispherical Isotropy	9.6	Rectangular	√3	0.7	± 3.9 %
Boundary Effects	1.0	Rectangular	√3	1	± 0.6 %
Linearity	4.7	Rectangular	√3	1	± 2.7 %
System Detection Limits	1.0	Rectangular	√3	1	± 0.6 %
Readout Electronics	0.3	Normal	1	1	± 0.3 %
Response Time	0.8	Rectangular	√3	1	± 0.5 %
Integration Time	2.6	Rectangular	√3	1	± 1.5 %
RF Ambient Noise	3.0	Rectangular	√3	1	± 1.7 %
RF Ambient Reflections	3.0	Rectangular	√3	1	± 1.7 %
Probe Positioner	0.4	Rectangular	√3	1	± 0.2 %
Probe Positioning	2.9	Rectangular	√3	1	± 1.7 %
Max. SAR Eval.	1.0	Rectangular	√3	1	± 0.6 %
<b>Test Sample Related</b>					
Device Positioning	2.9	Normal	1	1	± 2.9 %
Device Holder	3.6	Normal	1	1	± 3.6 %
Power Drift	5.0	Rectangular	√3	1	± 2.9 %
<b>Phantom and Setup</b>					
Phantom Uncertainty	4.0	Rectangular	√3	1	± 2.3 %
Liquid Conductivity (Target)	5.0	Rectangular	√3	0.64	± 1.8 %
Liquid Conductivity (Meas.)	2.5	Normal	1	0.64	± 1.6 %
Liquid Permittivity (Target)	5.0	Rectangular	√3	0.6	± 1.7 %
Liquid Permittivity (Meas.)	2.5	Normal	1	0.6	± 1.5 %
<b>Combined Standard Uncertainty</b>					± 10.7 %
<b>Coverage Factor for 95 %</b>					K = 2
<b>Expanded Uncertainty</b>					± 21.4 %

Table 7.2 Uncertainty Budget of DASY for frequency range 300 MHz to 3 GHz



Error Description	Uncertainty Value (±%)	Probability Distribution	Divisor	Ci (1g)	Standard Uncertainty (1g)
<b>Measurement System</b>					
Probe Calibration	6.55	Normal	1	1	± 6.55 %
Axial Isotropy	4.7	Rectangular	√3	0.7	± 1.9 %
Hemispherical Isotropy	9.6	Rectangular	√3	0.7	± 3.9 %
Boundary Effects	2.0	Rectangular	√3	1	± 1.2 %
Linearity	4.7	Rectangular	√3	1	± 2.7 %
System Detection Limits	1.0	Rectangular	√3	1	± 0.6 %
Readout Electronics	0.3	Normal	1	1	± 0.3 %
Response Time	0.8	Rectangular	√3	1	± 0.5 %
Integration Time	2.6	Rectangular	√3	1	± 1.5 %
RF Ambient Noise	3.0	Rectangular	√3	1	± 1.7 %
RF Ambient Reflections	3.0	Rectangular	√3	1	± 1.7 %
Probe Positioner	0.8	Rectangular	√3	1	± 0.5 %
Probe Positioning	9.9	Rectangular	√3	1	± 5.7 %
Max. SAR Eval.	4.0	Rectangular	√3	1	± 2.3 %
<b>Test Sample Related</b>					
Device Positioning	2.9	Normal	1	1	± 2.9 %
Device Holder	3.6	Normal	1	1	± 3.6 %
Power Drift	5.0	Rectangular	√3	1	± 2.9 %
<b>Phantom and Setup</b>					
Phantom Uncertainty	4.0	Rectangular	√3	1	± 2.3 %
Liquid Conductivity (Target)	5.0	Rectangular	√3	0.43	± 1.8 %
Liquid Conductivity (Meas.)	2.5	Normal	1	0.43	± 1.6 %
Liquid Permittivity (Target)	5.0	Rectangular	√3	0.49	± 1.7 %
Liquid Permittivity (Meas.)	2.5	Normal	1	0.49	± 1.5 %
<b>Combined Standard Uncertainty</b>					± 12.8 %
<b>Coverage Factor for 95 %</b>					K = 2
<b>Expanded Uncertainty</b>					± 25.6 %

Table 7.3 Uncertainty Budget of DASY for frequency range 3 GHz to 6 GHz

## 8. SAR Measurement Evaluation

Each DASY system is equipped with one or more system validation kits. These units, together with the predefined measurement procedures within the DASY software, enable the user to conduct the system performance check and system validation. System validation kit includes a dipole, tripod holder to fix it underneath the flat phantom and a corresponding distance holder.

### 8.1 Purpose of System Performance check

The system performance check verifies that the system operates within its specifications. System and operator errors can be detected and corrected. It is recommended that the system performance check be performed prior to any usage of the system in order to guarantee reproducible results. The system performance check uses normal SAR measurements in a simplified setup with a well characterized source. This setup was selected to give a high sensitivity to all parameters that might fail or vary over time. The system check does not intend to replace the calibration of the components, but indicates situations where the system uncertainty is exceeded due to drift or failure.

### 8.2 System Setup

In the simplified setup for system evaluation, the DUT is replaced by a calibrated dipole and the power source is replaced by a continuous wave that comes from a signal generator. The calibrated dipole must be placed beneath the flat phantom section of the SAM twin phantom with the correct distance holder. The distance holder should touch the phantom surface with a light pressure at the reference marking and be oriented parallel to the long side of the phantom. The equipment setup is shown below:





Fig 8.1 System Setup for System Evaluation

1. Signal Generator
2. Amplifier
3. Directional Coupler
4. Power Meter
5. Calibrated Dipole

The output power on dipole port must be calibrated to 20 dBm (100 mW) before dipole is connected.



**Fig 8.2 Photo of Dipole Setup**

**8.3 Validation Results**

Comparing to the original SAR value provided by SPEAG, the validation data should be within its specification of 10 %. Table 8.1 shows the target SAR and measured SAR after normalized to 1W input power. The table below indicates the system performance check can meet the variation criterion and the plots can be referred to Appendix A of this report.

Measurement Date	Liquid Type	Frequency (MHz)	Targeted SAR <sub>1g</sub> (W/kg)	Measured SAR <sub>1g</sub> (W/kg)	Deviation (%)
May 06, 2010	Head	2600	58.50	55.20	-5.64
May 07, 2010	Head	2600	58.50	53.20	-9.06
May 09, 2010	Head	2600	58.50	55.20	-5.64
May 06, 2010	Body	2600	57.90	58.70	1.38
May 09, 2010	Body	2600	57.90	58.50	1.04

**Table 8.1 Target and Measurement SAR after Normalized**

## 9. DUT Testing Position

This DUT was tested in six different positions. They are right cheek, right tilted, left cheek, left tilted, face of the DUT with phantom 1.5 cm gap, and bottom of the DUT with phantom 1.5 cm gap as illustrated below:

### 1. Define two imaginary lines on the handset

- (a) The vertical centerline passes through two points on the front side of the handset - the midpoint of the width  $w_t$  of the handset at the level of the acoustic output, and the midpoint of the width  $w_b$  of the bottom of the handset.
- (b) The horizontal line is perpendicular to the vertical centerline and passes through the center of the acoustic output. The horizontal line is also tangential to the face of the handset at point A.
- (c) The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output; however, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical centerline is not necessarily parallel to the front face of the handset, especially for clamshell handsets, handsets with flip covers, and other irregularly shaped handsets.





Fig 9.1 Illustration for Handset Vertical and Horizontal Reference Lines

**2. Cheek Position**


- (a) To position the device with the vertical center line of the body of the device and the horizontal line crossing the center piece in a plane parallel to the sagittal plane of the phantom. While maintaining the device in this plane, align the vertical center line with the reference plane containing the three ear and mouth reference point (M: Mouth, RE: Right Ear, and LE: Left Ear) and align the center of the ear piece with the line RE-LE.
- (b) To move the device towards the phantom with the ear piece aligned with the line LE-RE until the phone touched the ear. While maintaining the device in the reference plane and maintaining the phone contact with the ear, move the bottom of the phone until any point on the front side is in contact with the cheek of the phantom or until contact with the ear is lost (see Fig. 9.2).



**Fig 9.2 Illustration for Cheek Position**

**3. Tilted Position**


- (a) To position the device in the “cheek” position described above.
- (b) While maintaining the device the reference plane described above and pivoting against the ear, moves it outward away from the mouth by an angle of 15 degrees or until contact with the ear is lost (see Fig. 9.3).



**Fig 9.3 Illustration for Tilted Position**

#### 4. Body Worn Position

- (a) To position the device parallel to the phantom surface with either keypad up or down.
- (b) To adjust the device parallel to the flat phantom.
- (c) To adjust the distance between the device surface and the flat phantom to 1.5 cm.



**Fig 9.4 Illustration for Body Worn Position**

#### 5. DUT Setup Photos

Please refer to Appendix E for the test setup photos.

## **10. Measurement Procedures**

The measurement procedures are as follows:

- (a) Set WiMAX system simulator to allow DUT to radiate maximum output power
- (b) Measure output power through RF cable and power meter
- (c) Place the DUT in the positions described in the last section
- (d) Set scan area, grid size and other setting on the DASY software
- (e) Taking data for the middle channel on each testing position
- (f) Find out the largest SAR result on these testing positions of each band
- (g) Measure SAR results for the lowest and highest channels in worst SAR testing position

According to the test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- (a) Power reference measurement
- (b) Area scan
- (c) Zoom scan
- (d) Power drift measurement

### **10.1 Spatial Peak SAR Evaluation**

The procedure for spatial peak SAR evaluation has been implemented according to the test standard. It can be conducted for 1g and 10g, as well as for user-specific masses. The DASY software includes all numerical procedures necessary to evaluate the spatial peak SAR value.

The base for the evaluation is a "cube" measurement. The measured volume must include the 1g and 10g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan.

The entire evaluation of the spatial peak values is performed within the post-processing engine (SEMCAD). The system always gives the maximum values for the 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

- (a) Extraction of the measured data (grid and values) from the Zoom Scan
- (b) Calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters)
- (c) Generation of a high-resolution mesh within the measured volume
- (d) Interpolation of all measured values from the measurement grid to the high-resolution grid
- (e) Extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface
- (f) Calculation of the averaged SAR within masses of 1g and 10g



## **10.2 Scan Procedures**

First Area Scan is used to locate the approximate location(s) of the local peak SAR value(s). The measurement grid within an Area Scan is defined by the grid extent, grid step size and grid offset. Next, in order to determine the EM field distribution in a three-dimensional spatial extension, Zoom Scan is required. The Zoom Scan measures 5x5x7 points with step size 8, 8 and 5 mm for 300 MHz to 3 GHz, and 8x8x8 points with step size 4, 4 and 2.5 mm for 3 GHz to 6 GHz. The Zoom Scan is performed around the highest E-field value to determine the averaged SAR-distribution over 10 g.

## **10.3 SAR Averaged Methods**

In DASy, the interpolation and extrapolation are both based on the modified Quadratic Shepard's method. The interpolation scheme combines a least-square fitted function method and a weighted average method which are the two basic types of computational interpolation and approximation.

Extrapolation routines are used to obtain SAR values between the lowest measurement points and the inner phantom surface. The extrapolation distance is determined by the surface detection distance and the probe sensor offset. The uncertainty increases with the extrapolation distance. To keep the uncertainty within 1% for the 1 g and 10 g cubes, the extrapolation distance should not be larger than 5 mm.

## **10.4 Power Drift Monitoring**

All SAR testing is under the DUT install full charged battery and transmit maximum output power. In DASy measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of DUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in dB. If the power drift more than 5%, the SAR will be retested.



## 11. SAR Test Results

### 11.1 Conducted Power (Unit: dBm)

Zone Type	Modulation	Coding Rate	Frequency	Main Antenna			Aux. Antenna		
				Peak Power	Average Power	PAPR	Peak Power	Average Power	PAPR
PUSC	QPSK (BW 5MHz)	1/2	2498.5	31.81	22.01	9.80	31.69	22.41	9.28
			2593.0	31.42	23.71	7.71	31.34	23.65	7.69
			2687.5	31.50	23.55	7.95	30.71	23.56	7.15
		3/4	2498.5	31.83	22.02	9.81	31.40	22.30	9.10
			2593.0	32.07	23.68	8.39	31.10	23.63	7.47
			2687.5	31.33	23.61	7.72	31.22	23.54	7.68
	16QAM (BW 5MHz)	1/2	2498.5	31.80	22.03	9.77	31.83	22.08	9.75
			2593.0	32.06	23.69	8.37	31.11	23.61	7.50
			2687.5	31.37	23.58	7.79	30.68	23.47	7.21
		3/4	2498.5	31.74	22.03	9.71	31.78	22.39	9.39
			2593.0	31.36	23.67	7.69	31.24	23.60	7.64
			2687.5	31.28	23.59	7.69	30.60	23.26	7.34
	QPSK (BW 10MHz)	1/2	2501.0	31.94	22.49	9.45	31.71	22.78	8.93
			2593.0	31.38	23.68	7.70	31.33	23.67	7.66
			2685.0	31.48	23.64	7.84	30.94	23.63	7.31
		3/4	2501.0	32.00	22.42	9.58	31.73	22.72	9.01
			2593.0	31.51	23.60	7.91	31.31	23.65	7.66
			2685.0	31.47	23.65	7.82	30.91	23.61	7.30
	16QAM (BW 10MHz)	1/2	2501.0	31.44	22.42	9.02	31.70	22.78	8.92
			2593.0	31.51	23.68	7.83	31.42	23.64	7.78
			2685.0	31.36	23.66	7.70	30.84	23.03	7.81
		3/4	2501.0	32.08	22.26	9.82	31.93	22.63	9.30
			2593.0	31.58	23.62	7.96	31.55	23.60	7.95
			2685.0	31.28	23.60	7.68	30.91	23.45	7.46

**Note:** An Anritus wideband power meter was used for measuring the conducted power.

**11.2 Scaling Factor Deriving**

The testing was done at DL:UL symbol ratio, 29:18 as this is the maximum achievable ratio for the product. The 18 indicates the number of uplink symbols. Inside the uplink, 15 of the symbols are used for data, and 3 of the symbols are used for sending control information to the network. During the testing, the control symbols contained no information, so did not contribute to the total energy transmitted. To compensate for the maximum energy which may presented in the 3 control symbols, following scheme is used for the up scaling.

**<Scaling Factor for 5MHz BW>**

This device is power class 2 device and the maximum power tolerance is 23±1 dBm.

The maximum rated output power of 5M BW is 24.00 dBm (251.19 mW).

Maximum power in 5M control traffic is 73.88 mW (5/17 of 251.19 mW).

$$\text{Scaling Factor} = (3 * 73.88 + 15 * 251.19) / (15 * \text{max. measured power of the channel tested})$$

$$= 3989.47 / (15 * \text{max. measured power of the channel tested})$$

**For Main Antenna**

Zone Type	Modulation	Coding Rate	Frequency (MHz)	Average Power for Main Antenna		Scaling Factor
				(dBm)	(mW)	
PUSC	QPSK (BW 5MHz)	1/2	2498.5	22.01	158.97	1.67
			2593.0	23.71	235.13	1.13
			2687.5	23.55	226.63	1.17
		3/4	2498.5	22.02	159.34	1.67
			2593.0	23.68	233.51	1.14
			2687.5	23.61	229.78	1.16
	16QAM (BW 5MHz)	1/2	2498.5	22.03	159.70	1.67
			2593.0	23.69	234.05	1.14
			2687.5	23.58	228.20	1.17
		3/4	2498.5	22.03	159.70	1.67
			2593.0	23.67	232.98	1.14
			2687.5	23.59	228.72	1.16

**For Aux. Antenna**

Zone Type	Modulation	Coding Rate	Frequency (MHz)	Average Power for Aux. Antenna		Scaling Factor
				(dBm)	(mW)	
PUSC	QPSK (BW 5MHz)	1/2	2498.5	22.41	174.31	1.53
			2593.0	23.65	231.91	1.15
			2687.5	23.56	227.15	1.17
		3/4	2498.5	22.30	169.95	1.56
			2593.0	23.63	230.84	1.15
			2687.5	23.54	226.11	1.18
	16QAM (BW 5MHz)	1/2	2498.5	22.08	161.55	1.65
			2593.0	23.61	229.78	1.16
			2687.5	23.47	222.49	1.20
		3/4	2498.5	22.39	173.51	1.53
			2593.0	23.60	229.25	1.16
			2687.5	23.26	211.99	1.25

**<Scaling Factor for 10MHz BW>**

This device is power class 2 device and the maximum power tolerance is 23±1 dBm.

The maximum rated output power of 10M BW is 24.00 dBm (251.19 mW).

Maximum power in 10M control traffic is 35.88 mW (5/35 of 251.19 mW).

$$\text{Scaling Factor} = (3 * 35.88 + 15 * 251.19) / (15 * \text{max. measured power of the channel tested})$$

$$= 3875.48 / (15 * \text{max. measured power of the channel tested})$$

**For Main Antenna**

Zone Type	Modulation	Coding Rate	Frequency (MHz)	Average Power for Main Antenna		Scaling Factor
				(dBm)	(mW)	
PUSC	QPSK (BW 10MHz)	1/2	2501.0	22.49	177.55	1.46
			2593.0	23.68	233.51	1.11
			2685.0	23.64	231.37	1.12
		3/4	2501.0	22.42	174.71	1.48
			2593.0	23.60	229.25	1.13
			2685.0	23.65	231.91	1.11
	16QAM (BW 10MHz)	1/2	2501.0	22.42	174.71	1.48
			2593.0	23.68	233.51	1.11
			2685.0	23.66	232.44	1.11
		3/4	2501.0	22.26	168.39	1.53
			2593.0	23.62	230.31	1.12
			2685.0	23.60	229.25	1.13

**For Aux. Antenna**

Zone Type	Modulation	Coding Rate	Frequency (MHz)	Average Power for Aux. Antenna		Scaling Factor
				(dBm)	(mW)	
PUSC	QPSK (BW 10MHz)	1/2	2501.0	22.78	189.81	1.36
			2593.0	23.67	232.98	1.11
			2685.0	23.63	230.84	1.12
		3/4	2501.0	22.72	187.20	1.38
			2593.0	23.65	231.91	1.11
			2685.0	23.61	229.78	1.12
	16QAM (BW 10MHz)	1/2	2501.0	22.78	189.81	1.36
			2593.0	23.64	231.37	1.12
			2685.0	23.03	201.05	1.29
		3/4	2501.0	22.63	183.36	1.41
			2593.0	23.60	229.25	1.13
			2685.0	23.45	221.47	1.17

**<Scaling Up SAR>**

Calculating used follow scheme for scale up SAR.

$$\text{Scaled SAR} = \text{Measured SAR} * \text{Scaling Factor}$$



11.3 Test Records for Head SAR Test

Plot No.	Modulation	Coding Rate	BW (MHz)	Frequency (MHz)	Test Position	Ant.	SAR <sub>1g</sub> (W/kg)	Scaling Factor	Scaling SAR
#25	QPSK	1/2	5	2593.0	Right Cheek	Main	0.075	1.13	0.085
#26	QPSK	1/2	5	2593.0	Right Tilted	Main	0.02	1.13	0.023
#27	QPSK	1/2	5	2593.0	Left Cheek	Main	0.223	1.13	0.252
#28	QPSK	1/2	5	2593.0	Left Tilted	Main	0.029	1.13	0.033
#29	QPSK	1/2	5	2498.5	Left Cheek	Main	0.114	1.67	0.190
#30	QPSK	1/2	5	2687.5	Left Cheek	Main	0.091	1.17	0.106
#31	16QAM	1/2	5	2593.0	Right Cheek	Main	0.08	1.14	0.091
#32	16QAM	1/2	5	2593.0	Right Tilted	Main	0.016	1.14	0.018
#33	16QAM	1/2	5	2593.0	Left Cheek	Main	0.178	1.14	0.203
#34	16QAM	1/2	5	2593.0	Left Tilted	Main	0.025	1.14	0.029
#35	QPSK	1/2	10	2593.0	Right Cheek	Main	0.073	1.11	0.081
#36	QPSK	1/2	10	2593.0	Right Tilted	Main	0.016	1.11	0.018
#37	QPSK	1/2	10	2593.0	Left Cheek	Main	0.146	1.11	0.162
#38	QPSK	1/2	10	2593.0	Left Tilted	Main	0.021	1.11	0.023
#39	QPSK	1/2	10	2501.0	Left Cheek	Main	0.113	1.46	0.165
#40	QPSK	1/2	10	2685.0	Left Cheek	Main	0.089	1.12	0.100
#41	16QAM	1/2	10	2593.0	Right Cheek	Main	0.085	1.11	0.094
#42	16QAM	1/2	10	2593.0	Right Tilted	Main	0.018	1.11	0.020
#43	16QAM	1/2	10	2593.0	Left Cheek	Main	0.165	1.11	0.183
#44	16QAM	1/2	10	2593.0	Left Tilted	Main	0.023	1.11	0.026
#45	QPSK	1/2	5	2593.0	Right Cheek	Aux	0.175	1.15	0.201
#46	QPSK	1/2	5	2593.0	Right Tilted	Aux	0.06	1.15	0.069
#47	QPSK	1/2	5	2593.0	Left Cheek	Aux	0.127	1.15	0.146
#48	QPSK	1/2	5	2593.0	Left Tilted	Aux	0.031	1.15	0.036
#49	QPSK	1/2	5	2498.5	Right Cheek	Aux	0.179	1.53	0.274
#50	QPSK	1/2	5	2687.5	Right Cheek	Aux	0.215	1.17	0.252
#51	16QAM	1/2	5	2593.0	Right Cheek	Aux	0.166	1.16	0.193
#52	16QAM	1/2	5	2593.0	Right Tilted	Aux	0.057	1.16	0.066
#53	16QAM	1/2	5	2593.0	Left Cheek	Aux	0.135	1.16	0.157
#54	16QAM	1/2	5	2593.0	Left Tilted	Aux	0.033	1.16	0.038
#55	QPSK	1/2	10	2593.0	Right Cheek	Aux	0.152	1.11	0.169
#56	QPSK	1/2	10	2593.0	Right Tilted	Aux	0.053	1.11	0.059
#57	QPSK	1/2	10	2593.0	Left Cheek	Aux	0.127	1.11	0.141
#58	QPSK	1/2	10	2593.0	Left Tilted	Aux	0.029	1.11	0.032
#59	QPSK	1/2	10	2501.0	Right Cheek	Aux	0.188	1.36	0.256
#60	QPSK	1/2	10	2685.0	Right Cheek	Aux	0.293	1.12	0.328
#61	16QAM	1/2	10	2593.0	Right Cheek	Aux	0.169	1.12	0.189
#62	16QAM	1/2	10	2593.0	Right Tilted	Aux	0.058	1.12	0.065
#63	16QAM	1/2	10	2593.0	Left Cheek	Aux	0.147	1.12	0.165
#64	16QAM	1/2	10	2593.0	Left Tilted	Aux	0.033	1.12	0.037

Remark:

- The WiMAX SAR test reduction is referred 2010 TCB Workshop RF Exposure Procedures-Review.
- Use the lowest coding rate for each modulation when the same rated maximum output applies to all coding rates in a modulation
  - Test higher coding rates only if the rated maximum output is higher
  - Use the scaled SAR to determine test reduction (< 0.8 W/kg etc.)
  - For each channel bandwidth, if QPSK SAR is < 0.8 W/kg and maximum power > 16QAM, test highest output channel for 16QAM



### 11.4 Test Records for Body SAR Test

Plot No.	Modulation	Coding Rate	BW (MHz)	Frequency (MHz)	Test Position	Separation Distance	Ant.	SAR <sub>1g</sub> (W/kg)	Scaling Factor	Scaling SAR
#01	QPSK	1/2	5	2593.0	Face	1.5	Main	0.038	1.13	0.043
#02	QPSK	1/2	5	2593.0	Bottom	1.5	Main	0.416	1.13	0.470
#03	QPSK	1/2	5	2498.5	Bottom	1.5	Main	0.184	1.67	0.307
#04	QPSK	1/2	5	2687.5	Bottom	1.5	Main	0.259	1.17	0.303
#05	16QAM	1/2	5	2593.0	Face	1.5	Main	0.038	1.14	0.043
#06	16QAM	1/2	5	2593.0	Bottom	1.5	Main	0.404	1.14	0.461
#07	QPSK	1/2	10	2593.0	Face	1.5	Main	0.033	1.11	0.037
#08	QPSK	1/2	10	2593.0	Bottom	1.5	Main	0.374	1.11	0.415
#09	QPSK	1/2	10	2501.0	Bottom	1.5	Main	0.164	1.46	0.239
#10	QPSK	1/2	10	2685.0	Bottom	1.5	Main	0.274	1.12	0.307
#11	16QAM	1/2	10	2593.0	Face	1.5	Main	0.031	1.11	0.034
#12	16QAM	1/2	10	2593.0	Bottom	1.5	Main	0.388	1.11	0.431
#13	QPSK	1/2	5	2593.0	Face	1.5	Aux	0.034	1.15	0.039
#14	QPSK	1/2	5	2593.0	Bottom	1.5	Aux	0.132	1.15	0.152
#15	QPSK	1/2	5	2498.5	Bottom	1.5	Aux	0.104	1.53	0.159
#16	QPSK	1/2	5	2687.5	Bottom	1.5	Aux	0.18	1.17	0.211
#17	16QAM	1/2	5	2593.0	Face	1.5	Aux	0.037	1.16	0.043
#18	16QAM	1/2	5	2593.0	Bottom	1.5	Aux	0.134	1.16	0.155
#19	QPSK	1/2	10	2593.0	Face	1.5	Aux	0.036	1.11	0.040
#20	QPSK	1/2	10	2593.0	Bottom	1.5	Aux	0.12	1.11	0.133
#21	QPSK	1/2	10	2501.0	Bottom	1.5	Aux	0.099	1.36	0.135
#22	QPSK	1/2	10	2685.0	Bottom	1.5	Aux	0.167	1.12	0.187
#23	16QAM	1/2	10	2593.0	Face	1.5	Aux	0.047	1.12	0.053
#24	16QAM	1/2	10	2593.0	Bottom	1.5	Aux	0.112	1.12	0.125

**Remark:**

The WiMAX SAR test reduction is referred 2010 TCB Workshop RF Exposure Procedures-Review.

- Use the lowest coding rate for each modulation when the same rated maximum output applies to all coding rates in a modulation
- Test higher coding rates only if the rated maximum output is higher
- Use the scaled SAR to determine test reduction (< 0.8 W/kg etc.)
- For each channel bandwidth, if QPSK SAR is < 0.8 W/kg and maximum power > 16QAM, test highest output channel for 16QAM

Test Engineer : Gordon Lin and A-Rod Chen

**11.5 Linearity Response Check**

**<Setup and Calculation Procedure>**

Set up the DUT in the position of the worst SAR, i.e. Bottom of DUT, and keep the separation distance as 1.5 cm. The channel of maximum SAR for each Modulation/Bandwidth is chosen for single point peak SAR testing. Using the same setup as complete 1g SAR and set the Agilent E6651A to configure the device to transmit at specified power and check by Anritus wideband power meter.

The reference line is based on the SAR at the power of 12.5 mW, and the proportional SARs of its multiples of 12.5 mW. The measured SAR at different multiple power of 12.5 mW is also plotted. The deviation is the difference between the reference line and the measured SAR.

The example for 16QAM 1/2, BW 5M, 2687.5MHz is as below:

Base value = SAR measured at power of 12.5 mW = 0.029

2<sup>nd</sup> point (25 mW) = SAR value of  $0.029 * (25 / 12.5) = 0.058$


3<sup>rd</sup> point (50 mW) = SAR value of  $0.029 * (50 / 12.5) = 0.116$

4<sup>th</sup> point (100 mW) = SAR value of  $0.029 * (100 / 12.5) = 0.232$

5<sup>th</sup> point (200 mW) = SAR value of  $0.029 * (200 / 12.5) = 0.464$


**<For 16QAM, 1/2, BW 5M, 2593.0MHz, Bottom, Main Ant, Configuration #06>**

Average Power (mW)	12.5	25	50	100	200
Single Point SAR (W/kg)	0.029	0.061	0.12	0.239	0.477
Reference Line (W/kg)	0.029	0.058	0.116	0.232	0.464
Deviation (%)	0.00%	5.17%	3.45%	3.02%	2.80%




**<For 16QAM, 1/2, BW 10M, 2593.0MHz, Bottom, Main Ant, Configuration #12>**

<b>Average Power (mW)</b>	12.5	25	50	100	200
<b>Single Point SAR (W/kg)</b>	0.027	0.057	0.114	0.222	0.45
<b>Reference Line (W/kg)</b>	0.027	0.054	0.108	0.216	0.432
<b>Deviation (%)</b>	<b>0.00%</b>	<b>5.56%</b>	<b>5.56%</b>	<b>2.78%</b>	<b>4.17%</b>




**<For QPSK, 1/2, BW 5M, 2593.0MHz, Bottom, Main Ant, Configuration #02>**

<b>Average Power (mW)</b>	12.5	25	50	100	200
<b>Single Point SAR (W/kg)</b>	0.03	0.064	0.123	0.245	0.486
<b>Reference Line (W/kg)</b>	0.03	0.06	0.12	0.24	0.48
<b>Deviation (%)</b>	<b>0.00%</b>	<b>6.67%</b>	<b>2.50%</b>	<b>2.08%</b>	<b>1.25%</b>



**<For QPSK, 1/2, BW 10M, 2593.0MHz, Bottom, Main Ant, Configuration #08>**

<b>Average Power (mW)</b>	12.5	25	50	100	200
<b>Single Point SAR (W/kg)</b>	0.027	0.058	0.115	0.23	0.441
<b>Reference Line (W/kg)</b>	0.027	0.054	0.108	0.216	0.432
<b>Deviation (%)</b>	<b>0.00%</b>	<b>7.41%</b>	<b>6.48%</b>	<b>6.48%</b>	<b>2.08%</b>



**<Conclusion>**

From the above test results, the SAR probe can measure SAR correctly under high PAPR of OFDM/OFDMA, and the pretest SAR is not underestimated.

**11.6 Compare with Different Scan Resolution**

Retest the maximum raw 1g SAR with the same DUT setting on the different scan resolution. The test results are shown as below.

<b>Scan Resolution (mm)</b>	<b>Measured SAR<sub>1g</sub> (W/kg)</b>
5.0	0.416
2.5	0.428

**<Conclusion>**

From the above test results, the different scan resolution has no significant change.



## **12. References**

- [1] FCC 47 CFR Part 2 “Frequency Allocations and Radio Treaty Matters; General Rules and Regulations”
- [2] IEEE Std. C95.1-1999, “IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz”, 1999
- [3] IEEE Std. 1528-2003, “Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques”, December 2003
- [4] FCC OET Bulletin 65 (Edition 97-01) Supplement C (Edition 01-01), “Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields”, June 2001
- [5] SPEAG DASY System Handbook
- [6] FCC KDB 248227 D01 v01r02, “SAR Measurement Procedures for 802.11 a/b/g Transmitters”, May 2007
- [7] FCC KDB 447498 D01 v04, “Mobile and Portable Device RF Exposure Procedures and Equipment Authorization Policies”, November 2009
- [8] FCC KDB 447498 D02 v02, “SAR Measurement Procedures for USB Dongle Transmitters”, November 2009
- [9] FCC KDB 616217 D01 v01r01, “SAR Evaluation Considerations for Laptop Computers with Antennas Built-in on Display Screens”, November 2009
- [10] FCC KDB 616217 D03 v01, “SAR Evaluation Considerations for Laptop/Notebook/Netbook and Tablet Computers”, November 2009
- [11] FCC KDB 648474 D01 v01r05, “SAR Evaluation Considerations for Handsets with Multiple Transmitters and Antennas”, September 2008
- [12] FCC KDB 941225 D01 v02, “SAR Measurement Procedures for 3G Devices – CDMA 2000 / Ev-Do / WCDMA / HSDPA / HSPA”, October 2007
- [13] FCC KDB 941225 D03 v01, “Recommended SAR Test Reduction Procedures for GSM / GPRS / EDGE”, December 2008



## ***Appendix A. Plots of System Performance Check***

The plots are shown as follows.

### System Check\_Head\_2600MHz\_100506

#### DUT: Dipole 2600 MHz

Communication System: CW; Frequency: 2600 MHz; Duty Cycle: 1:1

Medium: HSL\_2600\_100506 Medium parameters used:  $f = 2600$  MHz;  $\sigma = 1.97$  mho/m;  $\epsilon_r = 38.2$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.5 °C; Liquid Temperature : 21.5 °C

#### DASY4 Configuration:

- Probe: EX3DV3 - SN3514; ConvF(7.45, 7.45, 7.45); Calibrated: 2010/1/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2009/8/24
- Phantom: SAM-Right; Type: QD 000 P40 C; Serial: TP-1383
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Pin=100mW/Area Scan (91x91x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 6.09 mW/g


**Pin=100mW/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 48.6 V/m; Power Drift = -0.125 dB

Peak SAR (extrapolated) = 12.7 W/kg

**SAR(1 g) = 5.52 mW/g; SAR(10 g) = 2.39 mW/g**

Maximum value of SAR (measured) = 6.31 mW/g



0 dB = 6.31mW/g

### System Check\_Head\_2600MHz\_100507

#### DUT: Dipole 2600 MHz

Communication System: CW; Frequency: 2600 MHz; Duty Cycle: 1:1

Medium: HSL\_2600\_0507 Medium parameters used:  $f = 2600$  MHz;  $\sigma = 1.96$  mho/m;  $\epsilon_r = 38.1$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.5 °C; Liquid Temperature : 21.3 °C

DASY4 Configuration:

- Probe: EX3DV3 - SN3514; ConvF(7.45, 7.45, 7.45); Calibrated: 2010/1/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2009/8/24
- Phantom: SAM-Right; Type: QD 000 P40 C; Serial: TP-1383
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Pin=100mW/Area Scan (91x91x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 6.21 mW/g


**Pin=100mW/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 55.5 V/m; Power Drift = 0.028 dB

Peak SAR (extrapolated) = 11.5 W/kg

**SAR(1 g) = 5.32 mW/g; SAR(10 g) = 2.35 mW/g**

Maximum value of SAR (measured) = 6.11 mW/g



0 dB = 6.11mW/g

### System Check\_Head\_2600MHz\_100509

#### DUT: Dipole 2600 MHz

Communication System: CW; Frequency: 2600 MHz; Duty Cycle: 1:1

Medium: HSL\_2600\_100509 Medium parameters used:  $f = 2600$  MHz;  $\sigma = 1.93$  mho/m;  $\epsilon_r = 37.9$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.6 °C; Liquid Temperature : 21.6 °C

#### DASY4 Configuration:

- Probe: EX3DV3 - SN3514; ConvF(7.45, 7.45, 7.45); Calibrated: 2010/1/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2009/8/24
- Phantom: SAM-Right; Type: QD 000 P40 C; Serial: TP-1383
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Pin=100mW/Area Scan (91x91x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 6.36 mW/g


**Pin=100mW/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 50.0 V/m; Power Drift = -0.129 dB

Peak SAR (extrapolated) = 12.6 W/kg

**SAR(1 g) = 5.52 mW/g; SAR(10 g) = 2.39 mW/g**

Maximum value of SAR (measured) = 6.29 mW/g



0 dB = 6.29mW/g

### System Check\_Body\_2600MHz\_100506

#### DUT: Dipole 2600 MHz

Communication System: CW; Frequency: 2600 MHz; Duty Cycle: 1:1

Medium: MSL\_2600\_100506 Medium parameters used:  $f = 2600 \text{ MHz}$ ;  $\sigma = 2.21 \text{ mho/m}$ ;  $\epsilon_r = 51.1$ ;  $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature : 22.4 °C ; Liquid Temperature : 21.5 °C

#### DASY4 Configuration:

- Probe: EX3DV3 - SN3514; ConvF(7.54, 7.54, 7.54); Calibrated: 2010/1/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2009/8/24
- Phantom: SAM-Left; Type: QD 000 P40 C; Serial: TP-1477
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Pin=100mW/Area Scan (91x91x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 6.86 mW/g


**Pin=100mW/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 54.9 V/m; Power Drift = 0.029 dB

Peak SAR (extrapolated) = 12.8 W/kg

**SAR(1 g) = 5.87 mW/g; SAR(10 g) = 2.59 mW/g**

Maximum value of SAR (measured) = 6.73 mW/g



## System Check\_Body\_2600MHz\_100509

### DUT: Dipole 2600 MHz

Communication System: CW; Frequency: 2600 MHz; Duty Cycle: 1:1

Medium: MSL\_2600\_100509 Medium parameters used:  $f = 2600$  MHz;  $\sigma = 2.19$  mho/m;  $\epsilon_r = 51$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.6 °C ; Liquid Temperature : 21.4 °C

DASY4 Configuration:

- Probe: EX3DV3 - SN3514; ConvF(7.54, 7.54, 7.54); Calibrated: 2010/1/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2009/8/24
- Phantom: SAM-Left; Type: QD 000 P40 C; Serial: TP-1477
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Pin=100mW/Area Scan (91x91x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 6.79 mW/g


**Pin=100mW/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 54.9 V/m; Power Drift = 0.032 dB

Peak SAR (extrapolated) = 12.7 W/kg

**SAR(1 g) = 5.85 mW/g; SAR(10 g) = 2.58 mW/g**

Maximum value of SAR (measured) = 6.72 mW/g



0 dB = 6.72mW/g



## ***Appendix B. Plots of SAR Measurement***

The plots are shown as follows.

## #25 WiMAX\_5M\_QPSK 1/2\_Right Cheek\_Ch1\_Main Ant

**DUT: 050618**

Communication System: Wimax; Frequency: 2593 MHz; Duty Cycle: 1:3.24

Medium: HSL\_2600\_0506 Medium parameters used:  $f = 2593$  MHz;  $\sigma = 1.97$  mho/m;  $\epsilon_r = 38.2$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.5 °C ; Liquid Temperature : 21.5 °C

DASY4 Configuration:

- Probe: EX3DV3 - SN3514; ConvF(7.45, 7.45, 7.45); Calibrated: 2010/1/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2009/8/24
- Phantom: SAM-Right; Type: QD 000 P40 C; Serial: TP-1383
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch1/Area Scan (51x71x1):** Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.073 mW/g

**Ch1/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 2.48 V/m; Power Drift = 0.114 dB

Peak SAR (extrapolated) = 0.156 W/kg

**SAR(1 g) = 0.075 mW/g; SAR(10 g) = 0.038 mW/g**

Maximum value of SAR (measured) = 0.077 mW/g


**Ch1/Zoom Scan (5x5x7)/Cube 1:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 2.48 V/m; Power Drift = 0.114 dB

Peak SAR (extrapolated) = 0.106 W/kg

**SAR(1 g) = 0.048 mW/g; SAR(10 g) = 0.027 mW/g**

Maximum value of SAR (measured) = 0.061 mW/g



0 dB = 0.061mW/g

## #26 WiMAX\_5M\_QPSK 1/2\_Right Tilted\_Ch1\_Main Ant

**DUT: 050618**

Communication System: Wimax; Frequency: 2593 MHz; Duty Cycle: 1:3.24

Medium: HSL\_2600\_0506 Medium parameters used:  $f = 2593$  MHz;  $\sigma = 1.97$  mho/m;  $\epsilon_r = 38.2$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.6 °C ; Liquid Temperature : 21.5 °C

DASY4 Configuration:

- Probe: EX3DV3 - SN3514; ConvF(7.45, 7.45, 7.45); Calibrated: 2010/1/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2009/8/24
- Phantom: SAM-Right; Type: QD 000 P40 C; Serial: TP-1383
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch1/Area Scan (51x71x1):** Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.021 mW/g

**Ch1/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 2.21 V/m; Power Drift = 0.114 dB

Peak SAR (extrapolated) = 0.039 W/kg

**SAR(1 g) = 0.020 mW/g; SAR(10 g) = 0.011 mW/g**

Maximum value of SAR (measured) = 0.022 mW/g


**Ch1/Zoom Scan (5x5x7)/Cube 1:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 2.21 V/m; Power Drift = 0.114 dB

Peak SAR (extrapolated) = 0.027 W/kg

**SAR(1 g) = 0.015 mW/g; SAR(10 g) = 0.00865 mW/g**

Maximum value of SAR (measured) = 0.016 mW/g



0 dB = 0.016mW/g

### #27 WiMAX\_5M\_QPSK 1/2\_Left Cheek\_Ch1\_Main Ant

**DUT: 050618**

Communication System: Wimax; Frequency: 2593 MHz; Duty Cycle: 1:3.24

Medium: HSL\_2600\_0506 Medium parameters used:  $f = 2593$  MHz;  $\sigma = 1.97$  mho/m;  $\epsilon_r = 38.2$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.5 °C ; Liquid Temperature : 21.5 °C

DASY4 Configuration:

- Probe: EX3DV3 - SN3514; ConvF(7.45, 7.45, 7.45); Calibrated: 2010/1/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2009/8/24
- Phantom: SAM-Right; Type: QD 000 P40 C; Serial: TP-1383
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch1/Area Scan (51x71x1):** Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.252 mW/g


**Ch1/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 2.01 V/m; Power Drift = 0.084 dB

Peak SAR (extrapolated) = 0.512 W/kg

**SAR(1 g) = 0.223 mW/g; SAR(10 g) = 0.100 mW/g**

Maximum value of SAR (measured) = 0.251 mW/g



0 dB = 0.251mW/g

## #28 WiMAX\_5M\_QPSK 1/2\_Left Tilted\_Ch1\_Main Ant

**DUT: 050618**

Communication System: Wimax; Frequency: 2593 MHz; Duty Cycle: 1:3.24

Medium: HSL\_2600\_0506 Medium parameters used:  $f = 2593$  MHz;  $\sigma = 1.97$  mho/m;  $\epsilon_r = 38.2$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.4 °C ; Liquid Temperature : 21.5 °C

DASY4 Configuration:

- Probe: EX3DV3 - SN3514; ConvF(7.45, 7.45, 7.45); Calibrated: 2010/1/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2009/8/24
- Phantom: SAM-Right; Type: QD 000 P40 C; Serial: TP-1383
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch1/Area Scan (51x71x1):** Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.028 mW/g

**Ch1/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 1.84 V/m; Power Drift = 0.125 dB

Peak SAR (extrapolated) = 0.053 W/kg

**SAR(1 g) = 0.029 mW/g; SAR(10 g) = 0.014 mW/g**

Maximum value of SAR (measured) = 0.029 mW/g


**Ch1/Zoom Scan (5x5x7)/Cube 1:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 1.84 V/m; Power Drift = 0.125 dB

Peak SAR (extrapolated) = 0.043 W/kg

**SAR(1 g) = 0.021 mW/g; SAR(10 g) = 0.00956 mW/g**

Maximum value of SAR (measured) = 0.022 mW/g



0 dB = 0.022mW/g

### #31 WiMAX\_5M\_16QAM 1/2\_Right Cheek\_Ch1\_Main Ant

**DUT: 050618**

Communication System: Wimax; Frequency: 2593 MHz; Duty Cycle: 1:3.24

Medium: HSL\_2600\_0506 Medium parameters used:  $f = 2593$  MHz;  $\sigma = 1.97$  mho/m;  $\epsilon_r = 38.2$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.4 °C ; Liquid Temperature : 21.5 °C

DASY4 Configuration:

- Probe: EX3DV3 - SN3514; ConvF(7.45, 7.45, 7.45); Calibrated: 2010/1/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2009/8/24
- Phantom: SAM-Right; Type: QD 000 P40 C; Serial: TP-1383
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch1/Area Scan (51x71x1):** Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.079 mW/g

**Ch1/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 2.34 V/m; Power Drift = 0.136 dB

Peak SAR (extrapolated) = 0.168 W/kg

**SAR(1 g) = 0.080 mW/g; SAR(10 g) = 0.041 mW/g**

Maximum value of SAR (measured) = 0.083 mW/g


**Ch1/Zoom Scan (5x5x7)/Cube 1:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 2.34 V/m; Power Drift = 0.136 dB

Peak SAR (extrapolated) = 0.102 W/kg

**SAR(1 g) = 0.050 mW/g; SAR(10 g) = 0.028 mW/g**

Maximum value of SAR (measured) = 0.060 mW/g



0 dB = 0.060mW/g

### #32 WiMAX\_5M\_16QAM 1/2\_Right Tilted\_Ch1\_Main Ant

**DUT: 050618**

Communication System: Wimax; Frequency: 2593 MHz; Duty Cycle: 1:3.24

Medium: HSL\_2600\_0506 Medium parameters used:  $f = 2593$  MHz;  $\sigma = 1.97$  mho/m;  $\epsilon_r = 38.2$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.4 °C; Liquid Temperature : 21.5 °C

DASY4 Configuration:

- Probe: EX3DV3 - SN3514; ConvF(7.45, 7.45, 7.45); Calibrated: 2010/1/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2009/8/24
- Phantom: SAM-Right; Type: QD 000 P40 C; Serial: TP-1383
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch1/Area Scan (61x71x1):** Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.017 mW/g

**Ch1/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 2.28 V/m; Power Drift = -0.014 dB

Peak SAR (extrapolated) = 0.028 W/kg

**SAR(1 g) = 0.016 mW/g; SAR(10 g) = 0.00817 mW/g**

Maximum value of SAR (measured) = 0.017 mW/g


**Ch1/Zoom Scan (5x5x7)/Cube 1:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 2.28 V/m; Power Drift = -0.014 dB

Peak SAR (extrapolated) = 0.027 W/kg

**SAR(1 g) = 0.015 mW/g; SAR(10 g) = 0.00897 mW/g**

Maximum value of SAR (measured) = 0.016 mW/g



0 dB = 0.016mW/g

### #33 WiMAX\_5M\_16QAM 1/2\_Left Cheek\_Ch1\_Main Ant

**DUT: 050618**

Communication System: Wimax; Frequency: 2593 MHz; Duty Cycle: 1:3.24

Medium: HSL\_2600\_0506 Medium parameters used:  $f = 2593$  MHz;  $\sigma = 1.97$  mho/m;  $\epsilon_r = 38.2$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.5 °C ; Liquid Temperature : 21.5 °C

DASY4 Configuration:

- Probe: EX3DV3 - SN3514; ConvF(7.45, 7.45, 7.45); Calibrated: 2010/1/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2009/8/24
- Phantom: SAM-Right; Type: QD 000 P40 C; Serial: TP-1383
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch1/Area Scan (51x71x1):** Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.209 mW/g


**Ch1/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 1.93 V/m; Power Drift = -0.108 dB

Peak SAR (extrapolated) = 0.381 W/kg

**SAR(1 g) = 0.178 mW/g; SAR(10 g) = 0.080 mW/g**

Maximum value of SAR (measured) = 0.189 mW/g



### #34 WiMAX\_5M\_16QAM 1/2\_Left Tilted\_Ch1\_Main Ant

**DUT: 050618**

Communication System: Wimax; Frequency: 2593 MHz; Duty Cycle: 1:3.24

Medium: HSL\_2600\_0506 Medium parameters used:  $f = 2593$  MHz;  $\sigma = 1.97$  mho/m;  $\epsilon_r = 38.2$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.4 °C; Liquid Temperature : 21.5 °C

DASY4 Configuration:

- Probe: EX3DV3 - SN3514; ConvF(7.45, 7.45, 7.45); Calibrated: 2010/1/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2009/8/24
- Phantom: SAM-Right; Type: QD 000 P40 C; Serial: TP-1383
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch1/Area Scan (51x71x1):** Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.027 mW/g

**Ch1/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 2.03 V/m; Power Drift = -0.148 dB

Peak SAR (extrapolated) = 0.045 W/kg

**SAR(1 g) = 0.025 mW/g; SAR(10 g) = 0.013 mW/g**

Maximum value of SAR (measured) = 0.026 mW/g


**Ch1/Zoom Scan (5x5x7)/Cube 1:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 2.03 V/m; Power Drift = -0.148 dB

Peak SAR (extrapolated) = 0.039 W/kg

**SAR(1 g) = 0.020 mW/g; SAR(10 g) = 0.00916 mW/g**

Maximum value of SAR (measured) = 0.022 mW/g



### #35 WiMAX\_10M\_QPSK 1/2\_Right Cheek\_Ch1\_Main Ant

**DUT: 050618**

Communication System: Wimax; Frequency: 2593 MHz; Duty Cycle: 1:3.24

Medium: HSL\_2600\_0506 Medium parameters used:  $f = 2593$  MHz;  $\sigma = 1.97$  mho/m;  $\epsilon_r = 38.2$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.6 °C ; Liquid Temperature : 21.5°C

DASY4 Configuration:

- Probe: EX3DV3 - SN3514; ConvF(7.45, 7.45, 7.45); Calibrated: 2010/1/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2009/8/24
- Phantom: SAM-Right; Type: QD 000 P40 C; Serial: TP-1383
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch1/Area Scan (51x71x1):** Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.092 mW/g

**Ch1/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 1.59 V/m; Power Drift = 0.101 dB

Peak SAR (extrapolated) = 0.153 W/kg

**SAR(1 g) = 0.073 mW/g; SAR(10 g) = 0.037 mW/g**

Maximum value of SAR (measured) = 0.079 mW/g


**Ch1/Zoom Scan (5x5x7)/Cube 1:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 1.59 V/m; Power Drift = 0.101 dB

Peak SAR (extrapolated) = 0.095 W/kg

**SAR(1 g) = 0.048 mW/g; SAR(10 g) = 0.026 mW/g**

Maximum value of SAR (measured) = 0.056 mW/g



0 dB = 0.056mW/g

### #36 WiMAX\_10M\_QPSK 1/2\_Right Tilted\_Ch1\_Main Ant

**DUT: 050618**

Communication System: Wimax; Frequency: 2593 MHz; Duty Cycle: 1:3.24

Medium: HSL\_2600\_0506 Medium parameters used:  $f = 2593$  MHz;  $\sigma = 1.97$  mho/m;  $\epsilon_r = 38.2$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.4 °C ; Liquid Temperature : 21.5 °C

DASY4 Configuration:

- Probe: EX3DV3 - SN3514; ConvF(7.45, 7.45, 7.45); Calibrated: 2010/1/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2009/8/24
- Phantom: SAM-Right; Type: QD 000 P40 C; Serial: TP-1383
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch1/Area Scan (61x71x1):** Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.018 mW/g

**Ch1/Zoom Scan (5x5x7)/Cube 1:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 1.77 V/m; Power Drift = 0.155 dB

Peak SAR (extrapolated) = 0.030 W/kg

**SAR(1 g) = 0.016 mW/g; SAR(10 g) = 0.00889 mW/g**


Maximum value of SAR (measured) = 0.016 mW/g

**Ch1/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 1.77 V/m; Power Drift = 0.155 dB

Peak SAR (extrapolated) = 0.025 W/kg

**SAR(1 g) = 0.015 mW/g; SAR(10 g) = 0.00877 mW/g**



0 dB = 0.016mW/g

### #37 WiMAX\_10M\_QPSK 1/2\_Left Cheek\_Ch1\_Main Ant

**DUT: 050618**

Communication System: Wimax; Frequency: 2593 MHz; Duty Cycle: 1:3.24

Medium: HSL\_2600\_0506 Medium parameters used:  $f = 2593$  MHz;  $\sigma = 1.97$  mho/m;  $\epsilon_r = 38.2$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.6 °C ; Liquid Temperature : 21.5 °C

DASY4 Configuration:

- Probe: EX3DV3 - SN3514; ConvF(7.45, 7.45, 7.45); Calibrated: 2010/1/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2009/8/24
- Phantom: SAM-Right; Type: QD 000 P40 C; Serial: TP-1383
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch1/Area Scan (61x71x1):** Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.156 mW/g


**Ch1/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 2.07 V/m; Power Drift = 0.110 dB

Peak SAR (extrapolated) = 0.330 W/kg

**SAR(1 g) = 0.146 mW/g; SAR(10 g) = 0.065 mW/g**

Maximum value of SAR (measured) = 0.158 mW/g



0 dB = 0.158mW/g

### #38 WiMAX\_10M\_QPSK 1/2\_Left Tilted\_Ch1\_Main Ant

**DUT: 050618**

Communication System: Wimax; Frequency: 2593 MHz; Duty Cycle: 1:3.24

Medium: HSL\_2600\_0506 Medium parameters used:  $f = 2593$  MHz;  $\sigma = 1.97$  mho/m;  $\epsilon_r = 38.2$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.6 °C ; Liquid Temperature : 21.5 °C

DASY4 Configuration:

- Probe: EX3DV3 - SN3514; ConvF(7.45, 7.45, 7.45); Calibrated: 2010/1/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2009/8/24
- Phantom: SAM-Right; Type: QD 000 P40 C; Serial: TP-1383
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch1/Area Scan (61x71x1):** Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.021 mW/g

**Ch1/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 2.05 V/m; Power Drift = 0.128 dB

Peak SAR (extrapolated) = 0.036 W/kg

**SAR(1 g) = 0.021 mW/g; SAR(10 g) = 0.011 mW/g**

Maximum value of SAR (measured) = 0.021 mW/g


**Ch1/Zoom Scan (5x5x7)/Cube 1:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 2.05 V/m; Power Drift = 0.328 dB

Peak SAR (extrapolated) = 0.030 W/kg

**SAR(1 g) = 0.018 mW/g; SAR(10 g) = 0.00861 mW/g**

Maximum value of SAR (measured) = 0.019 mW/g



0 dB = 0.019mW/g

### #41 WiMAX\_10M\_16QAM 1/2\_Right Cheek\_Ch1\_Main Ant

**DUT: 050618**

Communication System: Wimax; Frequency: 2593 MHz; Duty Cycle: 1:3.24

Medium: HSL\_2600\_0509 Medium parameters used:  $f = 2593$  MHz;  $\sigma = 1.93$  mho/m;  $\epsilon_r = 38$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.5 °C ; Liquid Temperature : 21.6 °C

DASY4 Configuration:

- Probe: EX3DV3 - SN3514; ConvF(7.45, 7.45, 7.45); Calibrated: 2010/1/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2009/8/24
- Phantom: SAM-Right; Type: QD 000 P40 C; Serial: TP-1383
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch1/Area Scan (51x71x1):** Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.087 mW/g


**Ch1/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 1.41 V/m; Power Drift = -0.134 dB

Peak SAR (extrapolated) = 0.173 W/kg

**SAR(1 g) = 0.085 mW/g; SAR(10 g) = 0.043 mW/g**

Maximum value of SAR (measured) = 0.094 mW/g



0 dB = 0.094mW/g

### #42 WiMAX\_10M\_16QAM 1/2\_Right Tilted\_Ch1\_Main Ant

**DUT: 050618**

Communication System: Wimax; Frequency: 2593 MHz; Duty Cycle: 1:3.24

Medium: HSL\_2600\_0509 Medium parameters used:  $f = 2593$  MHz;  $\sigma = 1.93$  mho/m;  $\epsilon_r = 38$ ;  $\rho =$

$1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.5 °C; Liquid Temperature : 21.6 °C

DASY4 Configuration:

- Probe: EX3DV3 - SN3514; ConvF(7.45, 7.45, 7.45); Calibrated: 2010/1/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2009/8/24
- Phantom: SAM-Right; Type: QD 000 P40 C; Serial: TP-1383
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch1/Area Scan (61x71x1):** Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.023 mW/g

**Ch1/Zoom Scan (5x5x7)/Cube 1:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 1.71 V/m; Power Drift = -0.180 dB

Peak SAR (extrapolated) = 0.035 W/kg

**SAR(1 g) = 0.018 mW/g; SAR(10 g) = 0.00934 mW/g**

Maximum value of SAR (measured) = 0.019 mW/g


**Ch1/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 1.71 V/m; Power Drift = -0.180 dB

Peak SAR (extrapolated) = 0.030 W/kg

**SAR(1 g) = 0.015 mW/g; SAR(10 g) = 0.0085 mW/g**

Maximum value of SAR (measured) = 0.016 mW/g



0 dB = 0.016mW/g

### #43 WiMAX\_10M\_16QAM 1/2\_Left Cheek\_Ch1\_Main Ant

**DUT: 050618**

Communication System: Wimax; Frequency: 2593 MHz; Duty Cycle: 1:3.24

Medium: HSL\_2600\_0509 Medium parameters used:  $f = 2593$  MHz;  $\sigma = 1.93$  mho/m;  $\epsilon_r = 38$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.4 °C ; Liquid Temperature : 21.6 °C

DASY4 Configuration:

- Probe: EX3DV3 - SN3514; ConvF(7.45, 7.45, 7.45); Calibrated: 2010/1/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2009/8/24
- Phantom: SAM-Right; Type: QD 000 P40 C; Serial: TP-1383
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch1/Area Scan (61x71x1):** Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.202 mW/g


**Ch1/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 2.00 V/m; Power Drift = -0.174 dB

Peak SAR (extrapolated) = 0.387 W/kg

**SAR(1 g) = 0.165 mW/g; SAR(10 g) = 0.075 mW/g**

Maximum value of SAR (measured) = 0.187 mW/g



0 dB = 0.187mW/g

### #44 WiMAX\_10M\_16QAM 1/2\_Left Tilted\_Ch1\_Main Ant

**DUT: 050618**

Communication System: Wimax; Frequency: 2593 MHz; Duty Cycle: 1:3.24

Medium: HSL\_2600\_0509 Medium parameters used:  $f = 2593$  MHz;  $\sigma = 1.93$  mho/m;  $\epsilon_r = 38$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.5 °C ; Liquid Temperature : 21.6 °C

DASY4 Configuration:

- Probe: EX3DV3 - SN3514; ConvF(7.45, 7.45, 7.45); Calibrated: 2010/1/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2009/8/24
- Phantom: SAM-Right; Type: QD 000 P40 C; Serial: TP-1383
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch1/Area Scan (61x71x1):** Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.026 mW/g

**Ch1/Zoom Scan (5x5x7)/Cube 1:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 2.03 V/m; Power Drift = 0.126 dB

Peak SAR (extrapolated) = 0.042 W/kg

**SAR(1 g) = 0.023 mW/g; SAR(10 g) = 0.012 mW/g**

Maximum value of SAR (measured) = 0.022 mW/g


**Ch1/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 2.03 V/m; Power Drift = 0.126 dB

Peak SAR (extrapolated) = 0.045 W/kg

**SAR(1 g) = 0.023 mW/g; SAR(10 g) = 0.011 mW/g**

Maximum value of SAR (measured) = 0.025 mW/g



0 dB = 0.025mW/g

### #46 WiMAX\_5M\_QPSK 1/2\_Right Tilted\_Ch1\_Aux Ant

**DUT: 050618**

Communication System: Wimax; Frequency: 2593 MHz; Duty Cycle: 1:3.24

Medium: HSL\_2600\_0507 Medium parameters used:  $f = 2593$  MHz;  $\sigma = 1.95$  mho/m;  $\epsilon_r = 38.1$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.4 °C ; Liquid Temperature : 21.3 °C

DASY4 Configuration:

- Probe: EX3DV3 - SN3514; ConvF(7.45, 7.45, 7.45); Calibrated: 2010/1/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2009/8/24
- Phantom: SAM-Right; Type: QD 000 P40 C; Serial: TP-1383
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch1/Area Scan (51x71x1):** Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.068 mW/g


**Ch1/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 1.50 V/m; Power Drift = 0.092 dB

Peak SAR (extrapolated) = 0.117 W/kg

**SAR(1 g) = 0.060 mW/g; SAR(10 g) = 0.032 mW/g**

Maximum value of SAR (measured) = 0.066 mW/g



0 dB = 0.066mW/g

### #47 WiMAX\_5M\_QPSK 1/2\_Left Cheek\_Ch1\_Aux Ant

**DUT: 050618**

Communication System: Wimax; Frequency: 2593 MHz; Duty Cycle: 1:3.24

Medium: HSL\_2600\_0507 Medium parameters used:  $f = 2593$  MHz;  $\sigma = 1.95$  mho/m;  $\epsilon_r = 38.1$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.6 °C ; Liquid Temperature : 21.3 °C

DASY4 Configuration:

- Probe: EX3DV3 - SN3514; ConvF(7.45, 7.45, 7.45); Calibrated: 2010/1/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2009/8/24
- Phantom: SAM-Right; Type: QD 000 P40 C; Serial: TP-1383
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch1/Area Scan (51x71x1):** Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.157 mW/g


**Ch1/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 2.11 V/m; Power Drift = 0.177 dB

Peak SAR (extrapolated) = 0.277 W/kg

**SAR(1 g) = 0.127 mW/g; SAR(10 g) = 0.062 mW/g**

Maximum value of SAR (measured) = 0.136 mW/g



0 dB = 0.136mW/g

### #48 WiMAX\_5M\_QPSK 1/2\_Left Tilted\_Ch1\_Aux Ant

**DUT: 050618**

Communication System: Wimax; Frequency: 2593 MHz; Duty Cycle: 1:3.24

Medium: HSL\_2600\_0507 Medium parameters used:  $f = 2593$  MHz;  $\sigma = 1.95$  mho/m;  $\epsilon_r = 38.1$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.5 °C ; Liquid Temperature : 21.3 °C

DASY4 Configuration:

- Probe: EX3DV3 - SN3514; ConvF(7.45, 7.45, 7.45); Calibrated: 2010/1/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2009/8/24
- Phantom: SAM-Right; Type: QD 000 P40 C; Serial: TP-1383
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch1/Area Scan (51x71x1):** Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.033 mW/g


**Ch1/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 1.55 V/m; Power Drift = 0.140 dB

Peak SAR (extrapolated) = 0.059 W/kg

**SAR(1 g) = 0.031 mW/g; SAR(10 g) = 0.018 mW/g**

Maximum value of SAR (measured) = 0.033 mW/g



0 dB = 0.033mW/g

## #50 WiMAX\_5M\_QPSK 1/2\_Right Cheek\_Ch2\_Aux Ant

**DUT: 050618**

Communication System: Wimax; Frequency: 2687.5 MHz; Duty Cycle: 1:3.24

Medium: HSL\_2600\_0507 Medium parameters used:  $f = 2687.5$  MHz;  $\sigma = 2.04$  mho/m;  $\epsilon_r = 37.8$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.6 °C ; Liquid Temperature : 21.3 °C

DASY4 Configuration:

- Probe: EX3DV3 - SN3514; ConvF(7.45, 7.45, 7.45); Calibrated: 2010/1/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2009/8/24
- Phantom: SAM-Right; Type: QD 000 P40 C; Serial: TP-1383
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch2/Area Scan (51x71x1):** Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.294 mW/g


**Ch2/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 1.28 V/m; Power Drift = 0.165 dB

Peak SAR (extrapolated) = 0.499 W/kg

**SAR(1 g) = 0.215 mW/g; SAR(10 g) = 0.103 mW/g**

Maximum value of SAR (measured) = 0.224 mW/g



0 dB = 0.224mW/g

### #51 WiMAX\_5M\_16QAM 1/2\_Right Cheek\_Ch1\_Aux Ant

**DUT: 050618**

Communication System: Wimax; Frequency: 2593 MHz; Duty Cycle: 1:3.24

Medium: HSL\_2600\_0507 Medium parameters used:  $f = 2593$  MHz;  $\sigma = 1.95$  mho/m;  $\epsilon_r = 38.1$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.5 °C ; Liquid Temperature : 21.3 °C

DASY4 Configuration:

- Probe: EX3DV3 - SN3514; ConvF(7.45, 7.45, 7.45); Calibrated: 2010/1/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2009/8/24
- Phantom: SAM-Right; Type: QD 000 P40 C; Serial: TP-1383
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch1/Area Scan (51x71x1):** Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.204 mW/g


**Ch1/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 1.42 V/m; Power Drift = -0.165 dB

Peak SAR (extrapolated) = 0.376 W/kg

**SAR(1 g) = 0.166 mW/g; SAR(10 g) = 0.080 mW/g**

Maximum value of SAR (measured) = 0.183 mW/g



0 dB = 0.183mW/g

### #52 WiMAX\_5M\_16QAM 1/2\_Right Tilted\_Ch1\_Aux Ant

**DUT: 050618**

Communication System: Wimax; Frequency: 2593 MHz; Duty Cycle: 1:3.24

Medium: HSL\_2600\_0507 Medium parameters used:  $f = 2593$  MHz;  $\sigma = 1.95$  mho/m;  $\epsilon_r = 38.1$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.5 °C ; Liquid Temperature : 21.3 °C

DASY4 Configuration:

- Probe: EX3DV3 - SN3514; ConvF(7.45, 7.45, 7.45); Calibrated: 2010/1/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2009/8/24
- Phantom: SAM-Right; Type: QD 000 P40 C; Serial: TP-1383
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch1/Area Scan (51x71x1):** Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.062 mW/g


**Ch1/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 1.45 V/m; Power Drift = 0.104 dB

Peak SAR (extrapolated) = 0.108 W/kg

**SAR(1 g) = 0.057 mW/g; SAR(10 g) = 0.030 mW/g**

Maximum value of SAR (measured) = 0.063 mW/g



0 dB = 0.063mW/g

### #53 WiMAX\_5M\_16QAM 1/2\_Left Cheek\_Ch1\_Aux Ant

**DUT: 050618**

Communication System: Wimax; Frequency: 2593 MHz; Duty Cycle: 1:3.24

Medium: HSL\_2600\_0507 Medium parameters used:  $f = 2593$  MHz;  $\sigma = 1.95$  mho/m;  $\epsilon_r = 38.1$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.6 °C ; Liquid Temperature : 21.3 °C

DASY4 Configuration:

- Probe: EX3DV3 - SN3514; ConvF(7.45, 7.45, 7.45); Calibrated: 2010/1/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2009/8/24
- Phantom: SAM-Right; Type: QD 000 P40 C; Serial: TP-1383
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch1/Area Scan (51x71x1):** Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.165 mW/g


**Ch1/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 2.15 V/m; Power Drift = 0.172 dB

Peak SAR (extrapolated) = 0.294 W/kg

**SAR(1 g) = 0.135 mW/g; SAR(10 g) = 0.066 mW/g**

Maximum value of SAR (measured) = 0.143 mW/g



0 dB = 0.143mW/g

### #54 WiMAX\_5M\_16QAM 1/2\_Left Tilted\_Ch1\_Aux Ant

**DUT: 050618**

Communication System: Wimax; Frequency: 2593 MHz; Duty Cycle: 1:3.24

Medium: HSL\_2600\_0507 Medium parameters used:  $f = 2593$  MHz;  $\sigma = 1.95$  mho/m;  $\epsilon_r = 38.1$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.5 °C ; Liquid Temperature : 21.3 °C

DASY4 Configuration:

- Probe: EX3DV3 - SN3514; ConvF(7.45, 7.45, 7.45); Calibrated: 2010/1/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2009/8/24
- Phantom: SAM-Right; Type: QD 000 P40 C; Serial: TP-1383
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch1/Area Scan (51x71x1):** Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.036 mW/g

**Ch1/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 1.74 V/m; Power Drift = 0.146 dB

Peak SAR (extrapolated) = 0.063 W/kg

**SAR(1 g) = 0.033 mW/g; SAR(10 g) = 0.018 mW/g**

Maximum value of SAR (measured) = 0.035 mW/g


**Ch1/Zoom Scan (5x5x7)/Cube 1:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 1.74 V/m; Power Drift = 0.146 dB

Peak SAR (extrapolated) = 0.058 W/kg

**SAR(1 g) = 0.030 mW/g; SAR(10 g) = 0.016 mW/g**

Maximum value of SAR (measured) = 0.032 mW/g



0 dB = 0.032mW/g

### #56 WiMAX\_10M\_QPSK 1/2\_Right Tilted\_Ch1\_Aux Ant

**DUT: 050618**

Communication System: Wimax; Frequency: 2593 MHz; Duty Cycle: 1:3.24

Medium: HSL\_2600\_0507 Medium parameters used:  $f = 2593$  MHz;  $\sigma = 1.95$  mho/m;  $\epsilon_r = 38.1$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.5 °C ; Liquid Temperature : 21.3 °C

DASY4 Configuration:

- Probe: EX3DV3 - SN3514; ConvF(7.45, 7.45, 7.45); Calibrated: 2010/1/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2009/8/24
- Phantom: SAM-Right; Type: QD 000 P40 C; Serial: TP-1383
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch1/Area Scan (51x71x1):** Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.060 mW/g


**Ch1/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 1.35 V/m; Power Drift = 0.165 dB

Peak SAR (extrapolated) = 0.102 W/kg

**SAR(1 g) = 0.053 mW/g; SAR(10 g) = 0.028 mW/g**

Maximum value of SAR (measured) = 0.058 mW/g



0 dB = 0.058mW/g

### #57 WiMAX\_10M\_QPSK 1/2\_Left Cheek\_Ch1\_Aux Ant

**DUT: 050618**

Communication System: Wimax; Frequency: 2593 MHz; Duty Cycle: 1:3.24

Medium: HSL\_2600\_0507 Medium parameters used:  $f = 2593$  MHz;  $\sigma = 1.95$  mho/m;  $\epsilon_r = 38.1$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.4 °C ; Liquid Temperature : 21.3 °C

DASY4 Configuration:

- Probe: EX3DV3 - SN3514; ConvF(7.45, 7.45, 7.45); Calibrated: 2010/1/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2009/8/24
- Phantom: SAM-Right; Type: QD 000 P40 C; Serial: TP-1383
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch1/Area Scan (51x71x1):** Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.154 mW/g


**Ch1/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 1.95 V/m; Power Drift = 0.147 dB

Peak SAR (extrapolated) = 0.273 W/kg

**SAR(1 g) = 0.127 mW/g; SAR(10 g) = 0.062 mW/g**

Maximum value of SAR (measured) = 0.139 mW/g



0 dB = 0.139mW/g

### #58 WiMAX\_10M\_QPSK 1/2\_Left Tilted\_Ch1\_Aux Ant

**DUT: 050618**

Communication System: Wimax; Frequency: 2593 MHz; Duty Cycle: 1:3.24

Medium: HSL\_2600\_0507 Medium parameters used:  $f = 2593$  MHz;  $\sigma = 1.95$  mho/m;  $\epsilon_r = 38.1$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.4 °C; Liquid Temperature : 21.3 °C

DASY4 Configuration:

- Probe: EX3DV3 - SN3514; ConvF(7.45, 7.45, 7.45); Calibrated: 2010/1/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2009/8/24
- Phantom: SAM-Right; Type: QD 000 P40 C; Serial: TP-1383
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch1/Area Scan (51x71x1):** Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.030 mW/g

**Ch1/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 1.67 V/m; Power Drift = 0.123 dB

Peak SAR (extrapolated) = 0.056 W/kg

**SAR(1 g) = 0.029 mW/g; SAR(10 g) = 0.016 mW/g**

Maximum value of SAR (measured) = 0.032 mW/g


**Ch1/Zoom Scan (5x5x7)/Cube 1:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 1.67 V/m; Power Drift = 0.123 dB

Peak SAR (extrapolated) = 0.053 W/kg

**SAR(1 g) = 0.028 mW/g; SAR(10 g) = 0.015 mW/g**

Maximum value of SAR (measured) = 0.030 mW/g



0 dB = 0.030mW/g

### #60 WiMAX\_10M\_QPSK 1/2\_Right Cheek\_Ch2\_Aux Ant

**DUT: 050618**

Communication System: Wimax; Frequency: 2685 MHz; Duty Cycle: 1:3.24

Medium: HSL\_2600\_0507 Medium parameters used:  $f = 2685$  MHz;  $\sigma = 2.04$  mho/m;  $\epsilon_r = 37.8$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.6 °C ; Liquid Temperature : 21.5 °C

ASY4 Configuration:

- Probe: EX3DV3 - SN3514; ConvF(7.45, 7.45, 7.45); Calibrated: 2010/1/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2009/8/24
- Phantom: SAM-Right; Type: QD 000 P40 C; Serial: TP-1383
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch2/Area Scan (51x71x1):** Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.388 mW/g


**Ch2/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 2.41 V/m; Power Drift = -0.005 dB

Peak SAR (extrapolated) = 0.701 W/kg

**SAR(1 g) = 0.293 mW/g; SAR(10 g) = 0.139 mW/g**

Maximum value of SAR (measured) = 0.308 mW/g



0 dB = 0.308mW/g

### #60 WiMAX\_10M\_QPSK 1/2\_Right Cheek\_Ch2\_Aux Ant\_2D

**DUT: 050618**

Communication System: Wimax; Frequency: 2685 MHz; Duty Cycle: 1:3.24

Medium: HSL\_2600\_0507 Medium parameters used:  $f = 2685$  MHz;  $\sigma = 2.04$  mho/m;  $\epsilon_r = 37.8$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.6 °C ; Liquid Temperature : 21.5 °C

DASY4 Configuration:

- Probe: EX3DV3 - SN3514; ConvF(7.45, 7.45, 7.45); Calibrated: 2010/1/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2009/8/24
- Phantom: SAM-Right; Type: QD 000 P40 C; Serial: TP-1383
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch2/Area Scan (51x71x1):** Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.388 mW/g


**Ch2/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 2.41 V/m; Power Drift = -0.005 dB

Peak SAR (extrapolated) = 0.701 W/kg

**SAR(1 g) = 0.293 mW/g; SAR(10 g) = 0.139 mW/g**

Maximum value of SAR (measured) = 0.308 mW/g



### #61 WiMAX\_10M\_16QAM 1/2\_Right Cheek\_Ch1\_Aux Ant

**DUT: 050618**

Communication System: Wimax; Frequency: 2593 MHz; Duty Cycle: 1:3.24

Medium: HSL\_2600\_0507 Medium parameters used:  $f = 2593$  MHz;  $\sigma = 1.95$  mho/m;  $\epsilon_r = 38.1$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.5 °C ; Liquid Temperature : 21.3 °C

DASY4 Configuration:

- Probe: EX3DV3 - SN3514; ConvF(7.45, 7.45, 7.45); Calibrated: 2010/1/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2009/8/24
- Phantom: SAM-Right; Type: QD 000 P40 C; Serial: TP-1383
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch1/Area Scan (51x71x1):** Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.221 mW/g


**Ch1/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 1.58 V/m; Power Drift = -0.144 dB

Peak SAR (extrapolated) = 0.385 W/kg

**SAR(1 g) = 0.169 mW/g; SAR(10 g) = 0.080 mW/g**

Maximum value of SAR (measured) = 0.181 mW/g



0 dB = 0.181mW/g

### #62 WiMAX\_10M\_16QAM 1/2\_Right Tilted\_Ch1\_Aux Ant

**DUT: 050618**

Communication System: Wimax; Frequency: 2593 MHz; Duty Cycle: 1:3.24

Medium: HSL\_2600\_0507 Medium parameters used:  $f = 2593$  MHz;  $\sigma = 1.95$  mho/m;  $\epsilon_r = 38.1$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.4 °C ; Liquid Temperature : 21.3 °C

DASY4 Configuration:

- Probe: EX3DV3 - SN3514; ConvF(7.45, 7.45, 7.45); Calibrated: 2010/1/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2009/8/24
- Phantom: SAM-Right; Type: QD 000 P40 C; Serial: TP-1383
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch1/Area Scan (51x71x1):** Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.064 mW/g


**Ch1/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 1.42 V/m; Power Drift = 0.170 dB

Peak SAR (extrapolated) = 0.114 W/kg

**SAR(1 g) = 0.058 mW/g; SAR(10 g) = 0.030 mW/g**

Maximum value of SAR (measured) = 0.065 mW/g



0 dB = 0.065mW/g

### #63 WiMAX\_10M\_16QAM 1/2\_Left Cheek\_Ch1\_Aux Ant

**DUT: 050618**

Communication System: Wimax; Frequency: 2593 MHz; Duty Cycle: 1:3.24

Medium: HSL\_2600\_0507 Medium parameters used:  $f = 2593$  MHz;  $\sigma = 1.95$  mho/m;  $\epsilon_r = 38.1$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.4 °C ; Liquid Temperature : 21.3 °C

DASY4 Configuration:

- Probe: EX3DV3 - SN3514; ConvF(7.45, 7.45, 7.45); Calibrated: 2010/1/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2009/8/24
- Phantom: SAM-Right; Type: QD 000 P40 C; Serial: TP-1383
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch1/Area Scan (51x71x1):** Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.176 mW/g


**Ch1/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 2.19 V/m; Power Drift = 0.144 dB

Peak SAR (extrapolated) = 0.317 W/kg

**SAR(1 g) = 0.147 mW/g; SAR(10 g) = 0.071 mW/g**

Maximum value of SAR (measured) = 0.161 mW/g



0 dB = 0.161mW/g

### #64 WiMAX\_10M\_16QAM 1/2\_Left Tilted\_Ch1\_Aux Ant

**DUT: 050618**

Communication System: Wimax; Frequency: 2593 MHz; Duty Cycle: 1:3.24

Medium: HSL\_2600\_0507 Medium parameters used:  $f = 2593$  MHz;  $\sigma = 1.95$  mho/m;  $\epsilon_r = 38.1$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.6 °C ; Liquid Temperature : 21.3 °C

DASY4 Configuration:

- Probe: EX3DV3 - SN3514; ConvF(7.45, 7.45, 7.45); Calibrated: 2010/1/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2009/8/24
- Phantom: SAM-Right; Type: QD 000 P40 C; Serial: TP-1383
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch1/Area Scan (51x71x1):** Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.036 mW/g

**Ch1/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 1.71 V/m; Power Drift = 0.197 dB

Peak SAR (extrapolated) = 0.062 W/kg

**SAR(1 g) = 0.033 mW/g; SAR(10 g) = 0.018 mW/g**

Maximum value of SAR (measured) = 0.036 mW/g


**Ch1/Zoom Scan (5x5x7)/Cube 1:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 1.71 V/m; Power Drift = 0.197 dB

Peak SAR (extrapolated) = 0.055 W/kg

**SAR(1 g) = 0.029 mW/g; SAR(10 g) = 0.016 mW/g**

Maximum value of SAR (measured) = 0.030 mW/g



0 dB = 0.030mW/g

### #01 WiMAX\_5M\_QPSK 1/2\_Face\_1.5cm\_Ch1\_Main Ant

**DUT: 050618**

Communication System: Wimax; Frequency: 2593 MHz; Duty Cycle: 1:3.24

Medium: MSL\_2600\_100505 Medium parameters used:  $f = 2593$  MHz;  $\sigma = 2.2$  mho/m;  $\epsilon_r = 51.1$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.4 °C ; Liquid Temperature : 21.5 °C

DASY4 Configuration:

- Probe: EX3DV3 - SN3514; ConvF(7.54, 7.54, 7.54); Calibrated: 2010/1/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2009/8/24
- Phantom: SAM-Left; Type: QD 000 P40 C; Serial: TP-1477
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch1/Area Scan (61x71x1):** Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.036 mW/g

**Ch1/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 1.23 V/m; Power Drift = -0.183 dB

Peak SAR (extrapolated) = 0.071 W/kg

**SAR(1 g) = 0.038 mW/g; SAR(10 g) = 0.021 mW/g**

Maximum value of SAR (measured) = 0.041 mW/g


**Ch1/Zoom Scan (5x5x7)/Cube 1:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 1.23 V/m; Power Drift = -0.183 dB

Peak SAR (extrapolated) = 0.041 W/kg

**SAR(1 g) = 0.024 mW/g; SAR(10 g) = 0.013 mW/g**

Maximum value of SAR (measured) = 0.026 mW/g



0 dB = 0.026mW/g

## #02 WiMAX\_5M\_QPSK 1/2\_Bottom\_1.5cm\_Ch1\_Main Ant

**DUT: 050618**

Communication System: Wimax; Frequency: 2593 MHz; Duty Cycle: 1:3.24

Medium: MSL\_2600\_100506 Medium parameters used:  $f = 2593$  MHz;  $\sigma = 2.2$  mho/m;  $\epsilon_r = 51.1$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.3 °C ; Liquid Temperature : 21.5 °C

DASY4 Configuration:

- Probe: EX3DV3 - SN3514; ConvF(7.54, 7.54, 7.54); Calibrated: 2010/1/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2009/8/24
- Phantom: SAM-Left; Type: QD 000 P40 C; Serial: TP-1477
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch1/Area Scan (51x71x1):** Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.415 mW/g


**Ch1/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 1.29 V/m; Power Drift = 0.079 dB

Peak SAR (extrapolated) = 0.824 W/kg

**SAR(1 g) = 0.416 mW/g; SAR(10 g) = 0.197 mW/g**

Maximum value of SAR (measured) = 0.471 mW/g



0 dB = 0.471mW/g

### #02 WiMAX\_5M\_QPSK 1/2\_Bottom\_1.5cm\_Ch1\_Main Ant\_2D

**DUT: 050618**

Communication System: Wimax; Frequency: 2593 MHz; Duty Cycle: 1:3.24

Medium: MSL\_2600\_100506 Medium parameters used:  $f = 2593$  MHz;  $\sigma = 2.2$  mho/m;  $\epsilon_r = 51.1$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.3 °C ; Liquid Temperature : 21.5 °C

DASY4 Configuration:

- Probe: EX3DV3 - SN3514; ConvF(7.54, 7.54, 7.54); Calibrated: 2010/1/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2009/8/24
- Phantom: SAM-Left; Type: QD 000 P40 C; Serial: TP-1477
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch1/Area Scan (51x71x1):** Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.415 mW/g


**Ch1/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 1.29 V/m; Power Drift = 0.079 dB

Peak SAR (extrapolated) = 0.824 W/kg

**SAR(1 g) = 0.416 mW/g; SAR(10 g) = 0.197 mW/g**

Maximum value of SAR (measured) = 0.471 mW/g



### #05 WiMAX\_5M\_16QAM 1/2\_Face\_1.5cm\_Ch1\_Main Ant

**DUT: 050618**

Communication System: Wimax; Frequency: 2593 MHz; Duty Cycle: 1:3.24

Medium: MSL\_2600\_100505 Medium parameters used:  $f = 2593$  MHz;  $\sigma = 2.2$  mho/m;  $\epsilon_r = 51.1$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.4 °C; Liquid Temperature : 21.5 °C

DASY4 Configuration:

- Probe: EX3DV3 - SN3514; ConvF(7.54, 7.54, 7.54); Calibrated: 2010/1/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2009/8/24
- Phantom: SAM-Left; Type: QD 000 P40 C; Serial: TP-1477
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch1/Area Scan (61x71x1):** Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.037 mW/g

**Ch1/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 1.50 V/m; Power Drift = 0.111 dB

Peak SAR (extrapolated) = 0.069 W/kg

**SAR(1 g) = 0.038 mW/g; SAR(10 g) = 0.022 mW/g**

Maximum value of SAR (measured) = 0.041 mW/g


**Ch1/Zoom Scan (5x5x7)/Cube 1:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 1.50 V/m; Power Drift = 0.111 dB

Peak SAR (extrapolated) = 0.051 W/kg

**SAR(1 g) = 0.028 mW/g; SAR(10 g) = 0.016 mW/g**

Maximum value of SAR (measured) = 0.029 mW/g



0 dB = 0.029mW/g

### #06 WiMAX\_5M\_16QAM 1/2\_Bottom\_1.5cm\_Ch1\_Main Ant

**DUT: 050618**

Communication System: Wimax; Frequency: 2593 MHz; Duty Cycle: 1:3.24

Medium: MSL\_2600\_100506 Medium parameters used:  $f = 2593$  MHz;  $\sigma = 2.2$  mho/m;  $\epsilon_r = 51.1$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.4 °C ; Liquid Temperature : 21.5 °C

DASY4 Configuration:

- Probe: EX3DV3 - SN3514; ConvF(7.54, 7.54, 7.54); Calibrated: 2010/1/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2009/8/24
- Phantom: SAM-Left; Type: QD 000 P40 C; Serial: TP-1477
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch1/Area Scan (51x71x1):** Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.399 mW/g


**Ch1/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 1.11 V/m; Power Drift = -0.154 dB

Peak SAR (extrapolated) = 0.803 W/kg

**SAR(1 g) = 0.404 mW/g; SAR(10 g) = 0.190 mW/g**

Maximum value of SAR (measured) = 0.442 mW/g



0 dB = 0.442mW/g

### #07 WiMAX\_10M\_QPSK 1/2\_Face\_1.5cm\_Ch1\_Main Ant

**DUT: 050618**

Communication System: Wimax; Frequency: 2593 MHz; Duty Cycle: 1:3.24

Medium: MSL\_2600\_100506 Medium parameters used:  $f = 2593$  MHz;  $\sigma = 2.2$  mho/m;  $\epsilon_r = 51.1$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.5 °C ; Liquid Temperature : 21.5 °C

DASY4 Configuration:

- Probe: EX3DV3 - SN3514; ConvF(7.54, 7.54, 7.54); Calibrated: 2010/1/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2009/8/24
- Phantom: SAM-Left; Type: QD 000 P40 C; Serial: TP-1477
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch1/Area Scan (61x71x1):** Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.036 mW/g


**Ch1/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 1.28 V/m; Power Drift = 0.176 dB

Peak SAR (extrapolated) = 0.061 W/kg

**SAR(1 g) = 0.033 mW/g; SAR(10 g) = 0.019 mW/g**

Maximum value of SAR (measured) = 0.034 mW/g



0 dB = 0.034mW/g

### #08 WiMAX\_10M\_QPSK 1/2\_Bottom\_1.5cm\_Ch1\_Main Ant

**DUT: 050618**

Communication System: Wimax; Frequency: 2593 MHz; Duty Cycle: 1:3.24

Medium: MSL\_2600\_100506 Medium parameters used:  $f = 2593$  MHz;  $\sigma = 2.2$  mho/m;  $\epsilon_r = 51.1$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.5 °C ; Liquid Temperature : 21.5 °C

DASY4 Configuration:

- Probe: EX3DV3 - SN3514; ConvF(7.54, 7.54, 7.54); Calibrated: 2010/1/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2009/8/24
- Phantom: SAM-Left; Type: QD 000 P40 C; Serial: TP-1477
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch1/Area Scan (61x71x1):** Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.402 mW/g


**Ch1/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 1.12 V/m; Power Drift = -0.103 dB

Peak SAR (extrapolated) = 0.734 W/kg

**SAR(1 g) = 0.374 mW/g; SAR(10 g) = 0.177 mW/g**

Maximum value of SAR (measured) = 0.400 mW/g



0 dB = 0.400mW/g

### #11 WiMAX\_10M\_16QAM 1/2\_Face\_1.5cm\_Ch1\_Main Ant

**DUT: 050618**

Communication System: Wimax; Frequency: 2593 MHz; Duty Cycle: 1:3.24

Medium: MSL\_2600\_100509 Medium parameters used:  $f = 2593$  MHz;  $\sigma = 2.18$  mho/m;  $\epsilon_r = 51$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.5 °C ; Liquid Temperature : 21.4 °C

DASY4 Configuration:

- Probe: EX3DV3 - SN3514; ConvF(7.54, 7.54, 7.54); Calibrated: 2010/1/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2009/8/24
- Phantom: SAM-Left; Type: QD 000 P40 C; Serial: TP-1477
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch1/Area Scan (61x71x1):** Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.034 mW/g

**Ch1/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 1.20 V/m; Power Drift = 0.168 dB

Peak SAR (extrapolated) = 0.057 W/kg

**SAR(1 g) = 0.031 mW/g; SAR(10 g) = 0.017 mW/g**

Maximum value of SAR (measured) = 0.033 mW/g


**Ch1/Zoom Scan (5x5x7)/Cube 1:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 1.20 V/m; Power Drift = 0.168 dB

Peak SAR (extrapolated) = 0.043 W/kg

**SAR(1 g) = 0.023 mW/g; SAR(10 g) = 0.013 mW/g**

Maximum value of SAR (measured) = 0.025 mW/g



### #12 WiMAX\_10M\_16QAM 1/2\_Bottom\_1.5cm\_Ch1\_Main Ant

**DUT: 050618**

Communication System: Wimax; Frequency: 2593 MHz; Duty Cycle: 1:3.24

Medium: MSL\_2600\_100509 Medium parameters used:  $f = 2593$  MHz;  $\sigma = 2.18$  mho/m;  $\epsilon_r = 51$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.6 °C ; Liquid Temperature : 21.4 °C

DASY4 Configuration:

- Probe: EX3DV3 - SN3514; ConvF(7.54, 7.54, 7.54); Calibrated: 2010/1/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2009/8/24
- Phantom: SAM-Left; Type: QD 000 P40 C; Serial: TP-1477
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch1/Area Scan (61x71x1):** Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.466 mW/g


**Ch1/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 1.23 V/m; Power Drift = -0.126 dB

Peak SAR (extrapolated) = 0.759 W/kg

**SAR(1 g) = 0.388 mW/g; SAR(10 g) = 0.186 mW/g**

Maximum value of SAR (measured) = 0.436 mW/g



0 dB = 0.436mW/g

### #13 WiMAX\_5M\_QPSK 1/2\_Face\_1.5cm\_Ch1\_Aux Ant

**DUT: 050618**

Communication System: Wimax; Frequency: 2593 MHz; Duty Cycle: 1:3.24

Medium: MSL\_2600\_100506 Medium parameters used:  $f = 2593$  MHz;  $\sigma = 2.2$  mho/m;  $\epsilon_r = 51.1$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.6 °C ; Liquid Temperature : 21.5 °C

DASY4 Configuration:

- Probe: EX3DV3 - SN3514; ConvF(7.54, 7.54, 7.54); Calibrated: 2010/1/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2009/8/24
- Phantom: SAM-Left; Type: QD 000 P40 C; Serial: TP-1477
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch1/Area Scan (61x71x1):** Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.038 mW/g


**Ch1/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 1.97 V/m; Power Drift = -0.196 dB

Peak SAR (extrapolated) = 0.061 W/kg

**SAR(1 g) = 0.034 mW/g; SAR(10 g) = 0.019 mW/g**

Maximum value of SAR (measured) = 0.037 mW/g



0 dB = 0.037mW/g

### #16 WiMAX\_5M\_QPSK 1/2\_Bottom\_1.5cm\_Ch2\_Aux Ant

**DUT: 050618**

Communication System: Wimax; Frequency: 2687.5 MHz; Duty Cycle: 1:3.24

Medium: MSL\_2600\_100506 Medium parameters used:  $f = 2687.5$  MHz;  $\sigma = 2.26$  mho/m;  $\epsilon_r = 50.9$ ;

$\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.4 °C ; Liquid Temperature : 21.5 °C

DASY4 Configuration:

- Probe: EX3DV3 - SN3514; ConvF(7.54, 7.54, 7.54); Calibrated: 2010/1/26

- Sensor-Surface: 4mm (Mechanical Surface Detection)

- Electronics: DAE3 Sn577; Calibrated: 2009/8/24

- Phantom: SAM-Left; Type: QD 000 P40 C; Serial: TP-1477

- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch2/Area Scan (51x71x1):** Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.183 mW/g


**Ch2/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 2.49 V/m; Power Drift = -0.187 dB

Peak SAR (extrapolated) = 0.349 W/kg

**SAR(1 g) = 0.180 mW/g; SAR(10 g) = 0.092 mW/g**

Maximum value of SAR (measured) = 0.203 mW/g



0 dB = 0.203mW/g

### #17 WiMAX\_5M\_16QAM 1/2\_Face\_1.5cm\_Ch1\_Aux Ant

**DUT: 050618**

Communication System: Wimax; Frequency: 2593 MHz; Duty Cycle: 1:3.24

Medium: MSL\_2600\_100506 Medium parameters used:  $f = 2593$  MHz;  $\sigma = 2.2$  mho/m;  $\epsilon_r = 51.1$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.5 °C ; Liquid Temperature : 21.5 °C

DASY4 Configuration:

- Probe: EX3DV3 - SN3514; ConvF(7.54, 7.54, 7.54); Calibrated: 2010/1/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2009/8/24
- Phantom: SAM-Left; Type: QD 000 P40 C; Serial: TP-1477
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch1/Area Scan (61x71x1):** Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.040 mW/g


**Ch1/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 1.81 V/m; Power Drift = 0.118 dB

Peak SAR (extrapolated) = 0.067 W/kg

**SAR(1 g) = 0.037 mW/g; SAR(10 g) = 0.021 mW/g**

Maximum value of SAR (measured) = 0.041 mW/g



### #18 WiMAX\_5M\_16QAM 1/2\_Bottom\_1.5cm\_Ch1\_Aux Ant

**DUT: 050618**

Communication System: Wimax; Frequency: 2593 MHz; Duty Cycle: 1:3.24

Medium: MSL\_2600\_100506 Medium parameters used:  $f = 2593$  MHz;  $\sigma = 2.2$  mho/m;  $\epsilon_r = 51.1$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.6 °C ; Liquid Temperature : 21.5 °C

DASY4 Configuration:

- Probe: EX3DV3 - SN3514; ConvF(7.54, 7.54, 7.54); Calibrated: 2010/1/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2009/8/24
- Phantom: SAM-Left; Type: QD 000 P40 C; Serial: TP-1477
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch1/Area Scan (51x71x1):** Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.133 mW/g


**Ch1/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 1.75 V/m; Power Drift = 0.157 dB

Peak SAR (extrapolated) = 0.256 W/kg

**SAR(1 g) = 0.134 mW/g; SAR(10 g) = 0.067 mW/g**

Maximum value of SAR (measured) = 0.143 mW/g



0 dB = 0.143mW/g

### #19 WiMAX\_10M\_QPSK 1/2\_Face\_1.5cm\_Ch1\_Aux Ant

**DUT: 050618**

Communication System: Wimax; Frequency: 2593 MHz; Duty Cycle: 1:3.24

Medium: MSL\_2600\_100506 Medium parameters used:  $f = 2593$  MHz;  $\sigma = 2.2$  mho/m;  $\epsilon_r = 51.1$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.5 °C ; Liquid Temperature : 21.5 °C

DASY4 Configuration:

- Probe: EX3DV3 - SN3514; ConvF(7.54, 7.54, 7.54); Calibrated: 2010/1/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2009/8/24
- Phantom: SAM-Left; Type: QD 000 P40 C; Serial: TP-1477
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch1/Area Scan (61x71x1):** Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.037 mW/g


**Ch1/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 1.84 V/m; Power Drift = 0.154 dB

Peak SAR (extrapolated) = 0.065 W/kg

**SAR(1 g) = 0.036 mW/g; SAR(10 g) = 0.020 mW/g**

Maximum value of SAR (measured) = 0.039 mW/g



0 dB = 0.039mW/g

## #22 WiMAX\_10M\_QPSK 1/2\_Bottom\_1.5cm\_Ch2\_Aux Ant

**DUT: 050618**

Communication System: Wimax; Frequency: 2685 MHz; Duty Cycle: 1:3.24

Medium: MSL\_2600\_100506 Medium parameters used:  $f = 2685$  MHz;  $\sigma = 2.25$  mho/m;  $\epsilon_r = 50.9$ ;  $\rho$

$= 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.4 °C ; Liquid Temperature : 21.5 °C

DASY4 Configuration:

- Probe: EX3DV3 - SN3514; ConvF(7.54, 7.54, 7.54); Calibrated: 2010/1/26

- Sensor-Surface: 4mm (Mechanical Surface Detection)

- Electronics: DAE3 Sn577; Calibrated: 2009/8/24

- Phantom: SAM-Left; Type: QD 000 P40 C; Serial: TP-1477

- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch2/Area Scan (51x71x1):** Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.173 mW/g


**Ch2/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 2.45 V/m; Power Drift = -0.183 dB

Peak SAR (extrapolated) = 0.323 W/kg

**SAR(1 g) = 0.167 mW/g; SAR(10 g) = 0.085 mW/g**

Maximum value of SAR (measured) = 0.184 mW/g



0 dB = 0.184mW/g

### #23 WiMAX\_10M\_16QAM 1/2\_Face\_1.5cm\_Ch1\_Aux Ant

**DUT: 050618**

Communication System: Wimax; Frequency: 2593 MHz; Duty Cycle: 1:3.24

Medium: MSL\_2600\_100506 Medium parameters used:  $f = 2593$  MHz;  $\sigma = 2.2$  mho/m;  $\epsilon_r = 51.1$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.6 °C ; Liquid Temperature : 21.5 °C

DASY4 Configuration:

- Probe: EX3DV3 - SN3514; ConvF(7.54, 7.54, 7.54); Calibrated: 2010/1/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2009/8/24
- Phantom: SAM-Left; Type: QD 000 P40 C; Serial: TP-1477
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch1/Area Scan (61x71x1):** Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.052 mW/g


**Ch1/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 2.42 V/m; Power Drift = 0.117 dB

Peak SAR (extrapolated) = 0.084 W/kg

**SAR(1 g) = 0.047 mW/g; SAR(10 g) = 0.027 mW/g**

Maximum value of SAR (measured) = 0.050 mW/g



### #24 WiMAX\_10M\_16QAM 1/2\_Bottom\_1.5cm\_Ch1\_Aux Ant

**DUT: 050618**

Communication System: Wimax; Frequency: 2593 MHz; Duty Cycle: 1:3.24

Medium: MSL\_2600\_100506 Medium parameters used:  $f = 2593$  MHz;  $\sigma = 2.2$  mho/m;  $\epsilon_r = 51.1$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.6 °C ; Liquid Temperature : 21.4 °C

DASY4 Configuration:

- Probe: EX3DV3 - SN3514; ConvF(7.54, 7.54, 7.54); Calibrated: 2010/1/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2009/8/24
- Phantom: SAM-Left; Type: QD 000 P40 C; Serial: TP-1477
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch1/Area Scan (51x71x1):** Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.137 mW/g

**Ch1/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 2.59 V/m; Power Drift = 0.059 dB

Peak SAR (extrapolated) = 0.202 W/kg

**SAR(1 g) = 0.112 mW/g; SAR(10 g) = 0.061 mW/g**

Maximum value of SAR (measured) = 0.121 mW/g

