

### #145 802.11b\_Right Cheek\_Ch1\_Slide Off\_Battery 2

**DUT: 073004**

Communication System: 802.11b ; Frequency: 2412 MHz;Duty Cycle: 1:1.09

Medium: HSL\_2450\_100826 Medium parameters used:  $f = 2412$  MHz;  $\sigma = 1.8$  mho/m;  $\epsilon_r = 38.7$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.5 °C; Liquid Temperature : 21.5 °C

DASY4 Configuration:

- Probe: ET3DV6 - SN1787; ConvF(4.5, 4.5, 4.5); Calibrated: 2010/5/18
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn910; Calibrated: 2009/9/18
- Phantom: SAM-Right; Type: QD 000 P40 C; Serial: TP-1383
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch1/Area Scan (51x71x1):** Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.123 mW/g


**Ch1/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 2.21 V/m; Power Drift = 0.110 dB

Peak SAR (extrapolated) = 0.272 W/kg

**SAR(1 g) = 0.116 mW/g; SAR(10 g) = 0.053 mW/g**

Maximum value of SAR (measured) = 0.134 mW/g



0 dB = 0.134mW/g

### #145 802.11b\_Right Cheek\_Ch1\_Slide Off\_Battery 2\_2D

**DUT: 073004**

Communication System: 802.11b ; Frequency: 2412 MHz;Duty Cycle: 1:1.09

Medium: HSL\_2450\_100826 Medium parameters used:  $f = 2412$  MHz;  $\sigma = 1.8$  mho/m;  $\epsilon_r = 38.7$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.5 °C; Liquid Temperature : 21.5 °C

DASY4 Configuration:

- Probe: ET3DV6 - SN1787; ConvF(4.5, 4.5, 4.5); Calibrated: 2010/5/18
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn910; Calibrated: 2009/9/18
- Phantom: SAM-Right; Type: QD 000 P40 C; Serial: TP-1383
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch1/Area Scan (51x71x1):** Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.123 mW/g


**Ch1/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 2.21 V/m; Power Drift = 0.110 dB

Peak SAR (extrapolated) = 0.272 W/kg

**SAR(1 g) = 0.116 mW/g; SAR(10 g) = 0.053 mW/g**

Maximum value of SAR (measured) = 0.134 mW/g



### #140 802.11b\_Right Tilted\_Ch1\_Slide Off\_Battery 1

**DUT: 073004**

Communication System: 802.11b ; Frequency: 2412 MHz; Duty Cycle: 1:1.09

Medium: HSL\_2450\_100826 Medium parameters used:  $f = 2412$  MHz;  $\sigma = 1.8$  mho/m;  $\epsilon_r = 38.7$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.5 °C; Liquid Temperature : 21.5 °C

DASY4 Configuration:

- Probe: ET3DV6 - SN1787; ConvF(4.5, 4.5, 4.5); Calibrated: 2010/5/18
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn910; Calibrated: 2009/9/18
- Phantom: SAM-Right; Type: QD 000 P40 C; Serial: TP-1383
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch1/Area Scan (51x71x1):** Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.029 mW/g


**Ch1/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 2.92 V/m; Power Drift = -0.009 dB

Peak SAR (extrapolated) = 0.046 W/kg

**SAR(1 g) = 0.022 mW/g; SAR(10 g) = 0.010 mW/g**

Maximum value of SAR (measured) = 0.028 mW/g



0 dB = 0.028mW/g

## #141 802.11b\_Left Cheek\_Ch1\_Slide Off\_Battery 1

**DUT: 073004**

Communication System: 802.11b ; Frequency: 2412 MHz; Duty Cycle: 1:1.09

Medium: HSL\_2450\_100826 Medium parameters used:  $f = 2412$  MHz;  $\sigma = 1.8$  mho/m;  $\epsilon_r = 38.7$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.5 °C; Liquid Temperature : 21.5 °C

DASY4 Configuration:

- Probe: ET3DV6 - SN1787; ConvF(4.5, 4.5, 4.5); Calibrated: 2010/5/18
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn910; Calibrated: 2009/9/18
- Phantom: SAM-Right; Type: QD 000 P40 C; Serial: TP-1383
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch1/Area Scan (51x71x1):** Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.067 mW/g

**Ch1/Zoom Scan (5x5x7)/Cube 1:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 2.08 V/m; Power Drift = -0.179 dB

Peak SAR (extrapolated) = 0.156 W/kg

**SAR(1 g) = 0.065 mW/g; SAR(10 g) = 0.026 mW/g**

Maximum value of SAR (measured) = 0.075 mW/g



**Ch1/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 2.08 V/m; Power Drift = -0.179 dB

Peak SAR (extrapolated) = 0.138 W/kg

**SAR(1 g) = 0.059 mW/g; SAR(10 g) = 0.028 mW/g**

Maximum value of SAR (measured) = 0.065 mW/g



0 dB = 0.065mW/g

## #142 802.11b\_Left Tilted\_Ch1\_Slide Off\_Battery 1

**DUT: 073004**

Communication System: 802.11b ; Frequency: 2412 MHz;Duty Cycle: 1:1.09

Medium: HSL\_2450\_100826 Medium parameters used:  $f = 2412$  MHz;  $\sigma = 1.8$  mho/m;  $\epsilon_r = 38.7$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.5 °C; Liquid Temperature : 21.5 °C

DASY4 Configuration:

- Probe: ET3DV6 - SN1787; ConvF(4.5, 4.5, 4.5); Calibrated: 2010/5/18
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn910; Calibrated: 2009/9/18
- Phantom: SAM-Right; Type: QD 000 P40 C; Serial: TP-1383
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch1/Area Scan (51x71x1):** Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.002 mW/g

**Ch1/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 0.419 V/m; Power Drift = -0.150 dB

Peak SAR (extrapolated) = 0.005 W/kg

**SAR(1 g) = 0.0011 mW/g; SAR(10 g) = 0.000518 mW/g**

Maximum value of SAR (measured) = 0.003 mW/g



**Ch1/Zoom Scan (5x5x7)/Cube 1:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 0.419 V/m; Power Drift = -0.150 dB

Peak SAR (extrapolated) = 0.002 W/kg

**SAR(1 g) = 0.000608 mW/g; SAR(10 g) = 0.00012 mW/g**

Maximum value of SAR (measured) = 0.001 mW/g



0 dB = 0.001mW/g

**#173 802.11b\_HttpvFace\_1cm\_Ch1\_Slide Off\_Battery 1**

**DUT: 073004**

Communication System: 802.11b ; Frequency: 2412 MHz;Duty Cycle: 1:1.09

Medium: MSL\_2450\_101106 Medium parameters used:  $f = 2412$  MHz;  $\sigma = 1.91$  mho/m;  $\epsilon_r = 53$ ;  $\rho = 1000$

kg/m<sup>3</sup>

Ambient Temperature : 22.5 ; Liquid Temperature : 21.4

DASY5 Configuration:

- Probe: ET3DV6 - SN1787; ConvF(4.03, 4.03, 4.03); Calibrated: 2010/5/18
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2010/8/18
- Phantom: SAM-Back; Type: QD 000 P40 C; Serial: TP-1383
- Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**Ch1/Area Scan (61x71x1):** Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.024 mW/g

**Ch1/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 2.94 V/m; Power Drift = -0.103 dB

Peak SAR (extrapolated) = 0.047 W/kg

**SAR(1 g) = 0.022 mW/g; SAR(10 g) = 0.013 mW/g**

Maximum value of SAR (measured) = 0.032 mW/g


**Ch1/Zoom Scan (5x5x7)/Cube 1:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 2.94 V/m; Power Drift = -0.103 dB

Peak SAR (extrapolated) = 0.039 W/kg

**SAR(1 g) = 0.019 mW/g; SAR(10 g) = 0.00976 mW/g**

Maximum value of SAR (measured) = 0.021 mW/g



0 dB = 0.021mW/g

**#174 802.11b\_Tgct Hceg\_1cm\_Ch1\_Slide Off\_Battery 1**

**DUT: 073004**

Communication System: 802.11b ; Frequency: 2412 MHz;Duty Cycle: 1:1.09

Medium: MSL\_2450\_101106 Medium parameters used:  $f = 2412$  MHz;  $\sigma = 1.91$  mho/m;  $\epsilon_r = 53$ ;  $\rho = 1000$

kg/m<sup>3</sup>

Ambient Temperature : 22.5 ; Liquid Temperature : 21.4

DASY5 Configuration:

- Probe: ET3DV6 - SN1787; ConvF(4.03, 4.03, 4.03); Calibrated: 2010/5/18
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2010/8/18
- Phantom: SAM-Back; Type: QD 000 P40 C; Serial: TP-1383
- Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**Ch1/Area Scan (51x71x1):** Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.131 mW/g


**Ch1/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 3.98 V/m; Power Drift = 0.028 dB

Peak SAR (extrapolated) = 0.329 W/kg

**SAR(1 g) = 0.144 mW/g; SAR(10 g) = 0.070 mW/g**

Maximum value of SAR (measured) = 0.230 mW/g



0 dB = 0.230mW/g

#174 802.11b\_Tgct'Hceg\_1cm\_Ch1\_Slide Off\_Battery 1\_2D

DUT: 073004

Communication System: 802.11b ; Frequency: 2412 MHz;Duty Cycle: 1:1.09

Medium: MSL\_2450\_101106 Medium parameters used:  $f = 2412$  MHz;  $\sigma = 1.91$  mho/m;  $\epsilon_r = 53$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.5 ; Liquid Temperature : 21.4

DASY5 Configuration:

- Probe: ET3DV6 - SN1787; ConvF(4.03, 4.03, 4.03); Calibrated: 2010/5/18
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2010/8/18
- Phantom: SAM-Back; Type: QD 000 P40 C; Serial: TP-1383
- Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**Ch1/Area Scan (51x71x1):** Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.131 mW/g


**Ch1/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 3.98 V/m; Power Drift = 0.028 dB

Peak SAR (extrapolated) = 0.329 W/kg

**SAR(1 g) = 0.144 mW/g; SAR(10 g) = 0.070 mW/g**

Maximum value of SAR (measured) = 0.230 mW/g



**#175 802.11b\_Vqr'Uf g\_1cm\_Ch1\_Slide Off\_Battery 1**

**DUT: 073004**

Communication System: 802.11b ; Frequency: 2412 MHz;Duty Cycle: 1:1.09

Medium: MSL\_2450\_101106 Medium parameters used:  $f = 2412$  MHz;  $\sigma = 1.91$  mho/m;  $\epsilon_r = 52.8$ ;  $\rho = 1000$

kg/m<sup>3</sup>

Ambient Temperature : 22.5 ; Liquid Temperature : 21.4

DASY5 Configuration:

- Probe: ET3DV6 - SN1787; ConvF(4.03, 4.03, 4.03); Calibrated: 2010/5/18
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2010/8/18
- Phantom: SAM-Back; Type: QD 000 P40 C; Serial: TP-1383
- Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**Ch1/Area Scan (41x61x1):** Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.020 mW/g


**Ch1/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 2.74 V/m; Power Drift = -0.147 dB

Peak SAR (extrapolated) = 0.251 W/kg

**SAR(1 g) = 0.031 mW/g; SAR(10 g) = 0.014 mW/g**

Maximum value of SAR (measured) = 0.179 mW/g



0 dB = 0.179mW/g

**#176 802.11b\_Dqwqo 'Uf g\_1cm\_Ch1\_Slide Off\_Battery 1**

**DUT: 073004**

Communication System: 802.11b ; Frequency: 2412 MHz;Duty Cycle: 1:1.09

Medium: MSL\_2450\_101106 Medium parameters used:  $f = 2412$  MHz;  $\sigma = 1.91$  mho/m;  $\epsilon_r = 53$ ;  $\rho = 1000$

kg/m<sup>3</sup>

Ambient Temperature : 22.5 ; Liquid Temperature : 21.4

DASY5 Configuration:

- Probe: ET3DV6 - SN1787; ConvF(4.03, 4.03, 4.03); Calibrated: 2010/5/18
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2010/8/18
- Phantom: SAM-Back; Type: QD 000 P40 C; Serial: TP-1383
- Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**Ch1/Area Scan (51x61x1):** Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.016 mW/g

**Ch1/Zoom Scan (5x5x7)/Cube 1:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 2.33 V/m; Power Drift = -0.045 dB

Peak SAR (extrapolated) = 0.032 W/kg

**SAR(1 g) = 0.015 mW/g; SAR(10 g) = 0.00841 mW/g**


Maximum value of SAR (measured) = 0.016 mW/g

**Ch1/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 2.33 V/m; Power Drift = -0.045 dB

Peak SAR (extrapolated) = 0.026 W/kg

**SAR(1 g) = 0.014 mW/g; SAR(10 g) = 0.00754 mW/g**



0 dB = 0.016mW/g

**#177 802.11b\_Tk j vUf g\_Ch1\_Slide Off\_Battery 1**

**DUT: 073004**

Communication System: 802.11b ; Frequency: 2412 MHz; Duty Cycle: 1:1.09

Medium: MSL\_2450\_101106 Medium parameters used:  $f = 2412$  MHz;  $\sigma = 1.91$  mho/m;  $\epsilon_r = 53$ ;  $\rho = 1000$

kg/m<sup>3</sup>

Ambient Temperature : 22.5 ; Liquid Temperature : 21.4

DASY5 Configuration:

- Probe: ET3DV6 - SN1787; ConvF(4.03, 4.03, 4.03); Calibrated: 2010/5/18
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2010/8/18
- Phantom: SAM-Back; Type: QD 000 P40 C; Serial: TP-1383
- Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**Ch1/Area Scan (61x71x1):** Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.015 mW/g


**Ch1/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 0.894 V/m; Power Drift = -0.132 dB

Peak SAR (extrapolated) = 0.018 W/kg

**SAR(1 g) = 0.00872 mW/g; SAR(10 g) = 0.00396 mW/g**

Maximum value of SAR (measured) = 0.0099 mW/g



0 dB = 0.0099mW/g

**#178 802.11b\_Ngh'Uf g\_Ch1\_Slide Off\_Battery 1**

**DUT: 073004**

Communication System: 802.11b ; Frequency: 2412 MHz;Duty Cycle: 1:1.09

Medium: MSL\_2450\_101106 Medium parameters used:  $f = 2412$  MHz;  $\sigma = 1.91$  mho/m;  $\epsilon_r = 53$ ;  $\rho = 1000$

kg/m<sup>3</sup>

Ambient Temperature : 22.5 ; Liquid Temperature : 21.4

DASY5 Configuration:

- Probe: ET3DV6 - SN1787; ConvF(4.03, 4.03, 4.03); Calibrated: 2010/5/18
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2010/8/18
- Phantom: SAM-Back; Type: QD 000 P40 C; Serial: TP-1383
- Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**Ch1/Area Scan (61x71x1):** Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.096 mW/g


**Ch1/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 3.8 V/m; Power Drift = 0.170 dB

Peak SAR (extrapolated) = 0.267 W/kg

**SAR(1 g) = 0.110 mW/g; SAR(10 g) = 0.053 mW/g**

Maximum value of SAR (measured) = 0.110 mW/g



**#181 802.11b\_Rear Face\_Ch1\_Slide Off\_Battery 2**

**DUT: 073004**

Communication System: 802.11b ; Frequency: 2412 MHz;Duty Cycle: 1:1

Medium: MSL\_2450\_101106 Medium parameters used:  $f = 2412$  MHz;  $\sigma = 1.91$  mho/m;  $\epsilon_r = 53$ ;  $\rho = 1000$

kg/m<sup>3</sup>

Ambient Temperature : 22.5 ; Liquid Temperature : 21.4

DASY5 Configuration:

- Probe: ET3DV6 - SN1787; ConvF(4.03, 4.03, 4.03); Calibrated: 2010/5/18
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2010/8/18
- Phantom: SAM-Back; Type: QD 000 P40 C; Serial: TP-1383
- Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**Ch1/Area Scan (51x71x1):** Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.077 mW/g


**Ch1/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 3.09 V/m; Power Drift = 0.169 dB

Peak SAR (extrapolated) = 0.213 W/kg

**SAR(1 g) = 0.089 mW/g; SAR(10 g) = 0.042 mW/g**

Maximum value of SAR (measured) = 0.099 mW/g



0 dB = 0.099mW/g

**#189 802.11b\_Rear Face\_1cm\_Ch1\_Slide Off\_Battery 1**

**DUT: 073004**

Communication System: 802.11b ; Frequency: 2412 MHz;Duty Cycle: 1:1.09

Medium: MSL\_2450\_101109 Medium parameters used:  $f = 2412$  MHz;  $\sigma = 1.88$  mho/m;  $\epsilon_r = 53.7$ ;  $\rho = 1000$

kg/m<sup>3</sup>

Ambient Temperature : 22.5 ; Liquid Temperature : 21.4

DASY5 Configuration:

- Probe: ET3DV6 - SN1787; ConvF(4.03, 4.03, 4.03); Calibrated: 2010/5/18
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2010/8/18
- Phantom: SAM-Back; Type: QD 000 P40 C; Serial: TP-1383
- Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**Ch1/Area Scan (51x71x1):** Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.140 mW/g

**Ch1/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 4.85 V/m; Power Drift = 0.189 dB

Peak SAR (extrapolated) = 0.286 W/kg

**SAR(1 g) = 0.119 mW/g; SAR(10 g) = 0.056 mW/g**

Maximum value of SAR (measured) = 0.138 mW/g


**Ch1/Zoom Scan (5x5x7)/Cube 1:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 4.85 V/m; Power Drift = 0.189 dB

Peak SAR (extrapolated) = 0.248 W/kg

**SAR(1 g) = 0.114 mW/g; SAR(10 g) = 0.065 mW/g**

Maximum value of SAR (measured) = 0.118 mW/g



0 dB = 0.118mW/g