



Appendix E. FCC 3G SAR Measurement Procedures

Conducted Output Power:


The EUT was tested according to the requirements of the FCC 3G procedures and the 3.1.2.3.4.

A detailed analysis of the output power verification is provided as the table below:

Function Type	Reverse Traffic Channel	Test Mode	Radio Configuration		Service Option	Data Rates	Power Control	Low Ch	Mid. Ch	High Ch
			Forward Traffic Channel (Fwd)	Reverse Traffic Channel (Rvs)				1013	384	777
CDMA2000 Cellular	FCH	1	1	1	55	Full	All Up	24.02	24.00	23.97
		3	3	3	55	Full	All Up	24.05	24.14	24.00
		3	3	3	32	Full	All Up	24.02	24.09	23.90
	SCH	3	3	3	32	FCH:Full,SCH 9.6	All Up	24.00	24.01	23.87
	EVDO Rev.0	Subtype:0				RTAP 153.6	All Up	24.13	24.13	24.05
	EVDO Rev.A	Subtype:0				RETAP 4096	All Up	24.09	24.13	24.10

Function Type	Reverse Traffic Channel	Test Mode	Radio Configuration		Service Option	Data Rates	Power Control	Low Ch	Mid. Ch	High Ch
			Forward Traffic Channel (Fwd)	Reverse Traffic Channel (Rvs)				25	600	1175
CDMA2000 PCS	FCH	1	1	1	55	Full	All Up	24.10	24.19	23.95
		3	3	3	55	Full	All Up	24.12	24.24	24.09
		3	3	3	32	Full	All Up	24.08	24.23	23.97
	SCH	3	3	3	32	FCH:Full,SCH 9.6	All Up	23.06	23.24	23.96
	EVDO Rev.0	Subtype:0				RTAP 153.6	All Up	24.19	23.23	24.05
	EVDO Rev.A	Subtype:0				RETAP 4096	All Up	24.11	24.23	24.12

CDMA2000 Setup Configuration:



Setup Configuration

1. The EUT was connected to System Simulator, Agilent 8960. Refer to the drawing of Setup Configuration.
2. The RF path losses were compensated into the measurements.
3. A call was established between EUT and System Simulator with following setting:
 - a. For 1xRTT, set the Radio Configuration and the Service Option
 - b. For 1xEV-DO, set the Protocol Release and Data Rate
 - c. Set the Power Control to All Up Bits
4. The transmitted maximum output power was recorded.

Call Setup Screen									
Call Control		Active Cell Operating Mode						Call Parms	
Mobile Station Information ESN (Hex): ESN (Dec): NCC: NMC: MSIN: Slot Class: Slot Cycle Index: ----- Protocol Revision:								Cell Power	
								-86.00	
								dBm/1.23 MHz	
								Cell Band	
								US PCS	
								Channel	
								1175	
								Protocol Rev	
								6 (IS-2000-0)	
								Radio Config	
						(Fud1, Rvs1)			
						S055 (Loopback)			
Close Menu								FCH Service Option Setup	
								1 of 4	

1xRTT setting for Radio Configuration 1 with Service Option 55

Call Setup Screen									
Call Control		Active Cell Operating Mode						Call Parms	
Mobile Station Information ESN (Hex): ESN (Dec): NCC: NMC: NSIN: Slot Class: Slot Cycle Index: ---- Protocol Revision:								Cell Power	
								-86.00	
								dBm/1.23 MHz	
								Cell Band	
								US PCS	
								Channel	
								1175	
								Protocol Rev	
								6 (IS-2000-0)	
								Radio Config	
						(Fud3, Rvs3)			
						S055 (Loopback)			
Close Menu		FCH Service Option Setup				Value		FCH Service Option Setup	
		Service Option S01 (Voice) S02 (Loopback) S03 (Voice) S06 (SMS) S055 (Loopback) S032 (+ F-SCH)				S055 (Loopback) S09 (Loopback) S055 (Loopback) S055 (Loopback) S055 (Loopback)			
		Active Cell				Sys Type: IS-2000			
		Idle							
		IntRef Offset							
								1 of 4	

1xRTT setting for Radio Configuration 3 with Service Option 55

Call Setup Screen									
Call Control		Active Cell Operating Mode						Call Parms	
Mobile Station Information ESN (Hex): ESN (Dec): NCC: NMC: NSIN: Slot Class: Slot Cycle Index: ----- Protocol Revision: FCH Service Option Setup Service Option for Fud3 Bus Service Option for Fud3 Bus Service Option for Fud3 Bus Service Option for Fud3 Bus Service Option for Fud3 Bus Service Option for Fud3 Bus Service Option for Fud3 Bus Service Option for Fud3 Bus Service Option for Fud3 Bus Service Option for Fud3 Bus Service Option S02 (Loopback) S03 (Voice) S06 (SMS) S055 (Loopback) S032 (+ F-SCH) S032 (+ SCH) S055 (Loopback) S09 (Loopback) S032 (+ SCH) S055 (Loopback) S055 (Loopback)		Cell Power -86.00 dBm/1.23 MHz Cell Band US PCS Channel 1175 Protocol Rev 6 (IS-2000-0) Radio Config (Fud3, Rvs3) S032 (+ SCH) FCH Service Option Setup							
		Close Menu		Active Cell		Sys Type: IS-2000			
				Idle					
				IntRef		Offset			
								1 of 4	

1xRTT setting for Radio Configuration 3 with Service Option 32



Call Setup Screen									
Call Control		Active Cell Operating Mode						Call Params	
Operating Mode	Active Cell	Access Terminal Information (AT Reported) Session Seed: Hardware ID Type (Hex): Hardware ID (Hex): Hardware ID (Decimal):						Rvs Power Ctrl	Active bits
Start Data Connection		Access Terminal Information (AN Assigned) UATI 024: ---- UATI Color Code: ---- NAC Index: ----						Pur Ctrl Step	1.0 dB
Close Session		Protocol Release Session App: 0 (1xEV-DO) Test Applica: A (1xEV-DO-A) Limited TAP: B (1xEV-DO-B) AT Directed: DRC Value Fi: ACK Channel:						Call Drop Timer	On
Handoff Setup								Call Limit Mode	Off
AT Max Power	23 dBm/1.23MHz							Protocol Rel	0 (1xEV-DO)
		Active Cell		Sys Type: IS-856					
		Idle							
1 of 3		IntRef	Offset	PLSub0	RTAP	2 of 3			

1xEV-DO setting for Protocol Release (Rev.0 or Rev.A)

Call Setup Screen									
Call Control		Active Cell Operating Mode						Call Params	
Operating Mode	Active Cell	Access Terminal Information (AT Reported) Session Seed: Hardware ID Type (Hex): Hardware ID (Hex): Hardware ID (Decimal):						Cell Power	-86.00
Start Data Connection		Access Terminal Information (AN Assigned) UATI 024: ---- UATI Color Code: ---- NAC Index: ----						dBm/1.23 MHz	
Close Session		RTAP Rate Session App: 9.6 kbps Test Applica: 19.2 kbps Limited TAP: 38.4 kbps AT Directed: 76.8 kbps DRC Value Fi: 153.6 kbps ACK Channel:						Cell Band	US PCS
Handoff Setup								Channel	1175
AT Max Power	23 dBm/1.23MHz							Application Config	
		Active Cell		Sys Type: IS-856				FTAP Rate	307.2 kbps
		Idle						(2 Slot, QPSK)	
1 of 3		IntRef	Offset	PLSub0	RTAP	1 of 3		RTAP Rate	9.6 kbps

1xEV-DO setting for RTAP data rate (153.6 kbps)



Call Setup Screen						
Call Control		Active Cell Operating Mode			Call Params	
Operating Mode	Active Cell	Access Terminal Information (AT Reported)			Cell Power	
		Session Seed:			-86.00	
		Hardware ID Type (Hex):			dBm/1.23 MHz	
		Hardware ID (Hex):			Cell Band	
		Hardware ID (Decimal):			US PCS	
		Access Terminal Information (AN Assigned)			Channel	
		UATI 024: ----			1175	
Start Data Connection		UATI Color Code: ----				
		MAC Index: ----				
		Application Configuration			Application Config	
Close Session		Session App: R-Data Packet Size			Application	
		Enhanced Te: 128			AP	
		AT Directed: 256			Z	
		DRC Value Fi: 512				
Handoff Setup		ACK Channel: 768			Capacity	
		ACK Channel: 768			kbps	
		Reverse Data: 1024				
AT Max Power		Expected En: 1536			bits	
23 dBm/1.23MHz						
		Active Cell			Sys Type: IS-856	
		Idle				
1 of 3			IntRef	Offset	PLSub0	RETAP
						1 of 3

1xEV-DO setting for RETAP data rate (4096 bits)



Reference:

- [1] SAR Measurement Procedures for 3G Devices CDMA 2000/Ev-Do/WCDMA/HSDPA, June 2006
Laboratory Division Office of Engineering and Technology Federal Communications Commission
- [2] 3.1.2.3.4 Maximum RF Output Power 3GPP2 C.S0033-0 Version 2.0, Date: 12 December 2003
Recommended Minimum Performance Standards for cdma2000 High Rate Packet Data Access
Terminal