

#01 GSM850_Right Cheek_Ch251_Battery4

DUT: 190794

Communication System: GSM850; Frequency: 848.8 MHz; Duty Cycle: 1:8.3

Medium: HSL_850_110910 Medium parameters used: $f = 849$ MHz; $\sigma = 0.898$ mho/m; $\epsilon_r = 41.4$; $\rho = 1000$ kg/m³

Ambient Temperature : 22.6 °C ; Liquid Temperature : 21.6 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3661; ConvF(9.58, 9.58, 9.58); Calibrated: 2011/1/24
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn495; Calibrated: 2011/4/28
- Phantom: SAM-Right; Type: QD 000 P40 C; Serial: TP-1383
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Ch251/Area Scan (41x81x1): Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.476 mW/g


Ch251/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 8.50 V/m; Power Drift = 0.152 dB

Peak SAR (extrapolated) = 0.568 W/kg

SAR(1 g) = 0.445 mW/g; SAR(10 g) = 0.330 mW/g

Maximum value of SAR (measured) = 0.464 mW/g



0 dB = 0.464mW/g

#01 GSM850_Right Cheek_Ch251_Battery4_2D

DUT: 190794

Communication System: GSM850; Frequency: 848.8 MHz; Duty Cycle: 1:8.3

Medium: HSL_850_110910 Medium parameters used: $f = 849$ MHz; $\sigma = 0.898$ mho/m; $\epsilon_r = 41.4$; $\rho = 1000$ kg/m³

Ambient Temperature : 22.6 °C ; Liquid Temperature : 21.6 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3661; ConvF(9.58, 9.58, 9.58); Calibrated: 2011/1/24
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn495; Calibrated: 2011/4/28
- Phantom: SAM-Right; Type: QD 000 P40 C; Serial: TP-1383
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Ch251/Area Scan (41x81x1): Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.476 mW/g


Ch251/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 8.50 V/m; Power Drift = 0.152 dB

Peak SAR (extrapolated) = 0.568 W/kg

SAR(1 g) = 0.445 mW/g; SAR(10 g) = 0.330 mW/g

Maximum value of SAR (measured) = 0.464 mW/g



#02 GSM1900_Right Cheek_Ch810_Battery4

DUT: 190794

Communication System: PCS; Frequency: 1909.8 MHz; Duty Cycle: 1:8.3

Medium: HSL_1900_110910 Medium parameters used: $f = 1910$ MHz; $\sigma = 1.44$ mho/m; $\epsilon_r = 38.8$; $\rho = 1000$ kg/m³

Ambient Temperature : 22.4 °C ; Liquid Temperature : 21.4 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3661; ConvF(8.68, 8.68, 8.68); Calibrated: 2011/1/24
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn495; Calibrated: 2011/4/28
- Phantom: SAM-Left; Type: QD 000 P40 C; Serial: TP-1478
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Ch810/Area Scan (41x81x1): Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.299 mW/g


Ch810/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 5.31 V/m; Power Drift = -0.081 dB

Peak SAR (extrapolated) = 0.467 W/kg

SAR(1 g) = 0.285 mW/g; SAR(10 g) = 0.167 mW/g

Maximum value of SAR (measured) = 0.306 mW/g



0 dB = 0.306mW/g

#02 GSM1900_Right Cheek_Ch810_Battery4_2D

DUT: 190794

Communication System: PCS; Frequency: 1909.8 MHz; Duty Cycle: 1:8.3

Medium: HSL_1900_110910 Medium parameters used: $f = 1910$ MHz; $\sigma = 1.44$ mho/m; $\epsilon_r = 38.8$; $\rho = 1000$ kg/m³

Ambient Temperature : 22.4 °C; Liquid Temperature : 21.4 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3661; ConvF(8.68, 8.68, 8.68); Calibrated: 2011/1/24
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn495; Calibrated: 2011/4/28
- Phantom: SAM-Left; Type: QD 000 P40 C; Serial: TP-1478
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Ch810/Area Scan (41x81x1): Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.299 mW/g


Ch810/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 5.31 V/m; Power Drift = -0.081 dB

Peak SAR (extrapolated) = 0.467 W/kg

SAR(1 g) = 0.285 mW/g; SAR(10 g) = 0.167 mW/g

Maximum value of SAR (measured) = 0.306 mW/g



#03 WCDMA W_RMC12.2K_Right Cheek_Ch1413_Battery4

DUT: 190794

Communication System: WCDMA; Frequency: 1732.6 MHz; Duty Cycle: 1:1

Medium: HSL_1800_110910 Medium parameters used: $f = 1733$ MHz; $\sigma = 1.38$ mho/m; $\epsilon_r = 40.6$; $\rho = 1000$ kg/m³

Ambient Temperature : 22.5°C; Liquid Temperature : 21.5 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3661; ConvF(9.05, 9.05, 9.05); Calibrated: 2011/1/24
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn495; Calibrated: 2011/4/28
- Phantom: SAM-Left; Type: QD 000 P40 C; Serial: TP-1478
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Ch1413/Area Scan (41x81x1): Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.665 mW/g


Ch1413/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 7.57 V/m; Power Drift = 0.104 dB

Peak SAR (extrapolated) = 0.957 W/kg

SAR(1 g) = 0.615 mW/g; SAR(10 g) = 0.378 mW/g

Maximum value of SAR (measured) = 0.666 mW/g



0 dB = 0.666mW/g

#03 WCDMA K_RMC12.2K_Right Cheek_Ch1413_Battery4_2D

DUT: 190794

Communication System: WCDMA; Frequency: 1732.6 MHz; Duty Cycle: 1:1

Medium: HSL_1800_110910 Medium parameters used: $f = 1733$ MHz; $\sigma = 1.38$ mho/m; $\epsilon_r = 40.6$; $\rho = 1000$ kg/m³

Ambient Temperature : 22.5 °C; Liquid Temperature : 21.5 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3661; ConvF(9.05, 9.05, 9.05); Calibrated: 2011/1/24
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn495; Calibrated: 2011/4/28
- Phantom: SAM-Left; Type: QD 000 P40 C; Serial: TP-1478
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Ch1413/Area Scan (41x81x1): Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.665 mW/g


Ch1413/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 7.57 V/m; Power Drift = 0.104 dB

Peak SAR (extrapolated) = 0.957 W/kg

SAR(1 g) = 0.615 mW/g; SAR(10 g) = 0.378 mW/g

Maximum value of SAR (measured) = 0.666 mW/g



#04 802.11b_Left Cheek_Ch6_Battery4

DUT: 190794

Communication System: 802.11b ; Frequency: 2437 MHz;Duty Cycle: 1:1

Medium: HSL_2450_110910 Medium parameters used: $f = 2437$ MHz; $\sigma = 1.8$ mho/m; $\epsilon_r = 37.5$; $\rho = 1000$ kg/m³

Ambient Temperature : 22.3 °C ; Liquid Temperature : 21.3 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3661; ConvF(7.8, 7.8, 7.8); Calibrated: 2011/1/24
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn495; Calibrated: 2011/4/28
- Phantom: SAM-Left; Type: QD 000 P40 C; Serial: TP-1478
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Ch6/Area Scan (41x81x1): Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.327 mW/g

Ch6/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 8.47 V/m; Power Drift = 0.132 dB

Peak SAR (extrapolated) = 0.518 W/kg

SAR(1 g) = 0.269 mW/g; SAR(10 g) = 0.130 mW/g

Maximum value of SAR (measured) = 0.305 mW/g



0 dB = 0.305mW/g

#04 802.11b_Left Cheek_Ch6_Battery4_2D

DUT: 190794

Communication System: 802.11b ; Frequency: 2437 MHz;Duty Cycle: 1:1

Medium: HSL_2450_110910 Medium parameters used: $f = 2437 \text{ MHz}$; $\sigma = 1.8 \text{ mho/m}$; $\epsilon_r = 37.5$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature : 22.3 °C ; Liquid Temperature : 21.3 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3661; ConvF(7.8, 7.8, 7.8); Calibrated: 2011/1/24
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn495; Calibrated: 2011/4/28
- Phantom: SAM-Left; Type: QD 000 P40 C; Serial: TP-1478
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Ch6/Area Scan (41x81x1): Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.327 mW/g


Ch6/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 8.47 V/m; Power Drift = 0.132 dB

Peak SAR (extrapolated) = 0.518 W/kg

SAR(1 g) = 0.269 mW/g; SAR(10 g) = 0.130 mW/g

Maximum value of SAR (measured) = 0.305 mW/g



#05 GSM850_GPRS10_Back_1cm_Ch251_Battery4

DUT: 190794

Communication System: GSM850; Frequency: 848.8 MHz; Duty Cycle: 1:4

Medium: MSL_850_110910 Medium parameters used: $f = 849$ MHz; $\sigma = 1.01$ mho/m; $\epsilon_r = 54.6$; $\rho = 1000$ kg/m³

Ambient Temperature : 22.3 °C ; Liquid Temperature : 21.3 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3661; ConvF(9.58, 9.58, 9.58); Calibrated: 2011/1/24
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn495; Calibrated: 2011/4/28
- Phantom: ELI 4.0_Front; Type: QDOVA001BB; Serial: 1026
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Ch251/Area Scan (41x81x1): Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 1.11 mW/g

Ch251/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 33.5 V/m; Power Drift = -0.164 dB

Peak SAR (extrapolated) = 1.41 W/kg

SAR(1 g) = 1.06 mW/g; SAR(10 g) = 0.787 mW/g



Maximum value of SAR (measured) = 1.11 mW/g

Ch251/Zoom Scan (5x5x7)/Cube 1: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 33.5 V/m; Power Drift = -0.164 dB

Peak SAR (extrapolated) = 1.66 W/kg

SAR(1 g) = 1.03 mW/g; SAR(10 g) = 0.704 mW/g



0 dB = 1.11mW/g

#05 GSM850_GPRS10_Back_1cm_Ch251_Battery4_2D

DUT: 190794

Communication System: GSM850; Frequency: 848.8 MHz; Duty Cycle: 1:4

Medium: MSL_850_110910 Medium parameters used: $f = 849$ MHz; $\sigma = 1.01$ mho/m; $\epsilon_r = 54.6$; $\rho = 1000$ kg/m³

Ambient Temperature : 22.3 °C; Liquid Temperature : 21.3 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3661; ConvF(9.58, 9.58, 9.58); Calibrated: 2011/1/24
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn495; Calibrated: 2011/4/28
- Phantom: ELI 4.0_Front; Type: QDOVA001BB; Serial: 1026
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Ch251/Area Scan (41x81x1): Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 1.11 mW/g

Ch251/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 33.5 V/m; Power Drift = -0.164 dB

Peak SAR (extrapolated) = 1.41 W/kg

SAR(1 g) = 1.06 mW/g; SAR(10 g) = 0.787 mW/g

Maximum value of SAR (measured) = 1.11 mW/g

Ch251/Zoom Scan (5x5x7)/Cube 1: Measurement grid: dx=8mm, dy=8mm, dz=5mm


Reference Value = 33.5 V/m; Power Drift = -0.164 dB

Peak SAR (extrapolated) = 1.66 W/kg

SAR(1 g) = 1.03 mW/g; SAR(10 g) = 0.704 mW/g

1g/10g Averaged SAR

SAR; Zoom Scan: Value Along Z, X=2, Y=2



#11 GSM850_GPRS10_Back_1cm_Ch128_Battery4

DUT: 190794

Communication System: GSM850; Frequency: 824.2 MHz; Duty Cycle: 1:4

Medium: MSL_850_110910 Medium parameters used: $f = 824.2$ MHz; $\sigma = 0.983$ mho/m; $\epsilon_r = 54.8$; $\rho = 1000$ kg/m³

Ambient Temperature : 22.3 °C ; Liquid Temperature : 21.3 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3661; ConvF(9.58, 9.58, 9.58); Calibrated: 2011/1/24
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn495; Calibrated: 2011/4/28
- Phantom: ELI 4.0_Front; Type: QDOVA001BB; Serial: 1026
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Ch128/Area Scan (41x81x1): Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.898 mW/g


Ch128/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 28.2 V/m; Power Drift = -0.170 dB

Peak SAR (extrapolated) = 1.21 W/kg

SAR(1 g) = 0.770 mW/g; SAR(10 g) = 0.559 mW/g

Maximum value of SAR (measured) = 0.817 mW/g



0 dB = 0.817mW/g

#12 GSM850_GPRS10_Back_1cm_Ch189_Battery4

DUT: 190794

Communication System: GSM850; Frequency: 836.4 MHz; Duty Cycle: 1:4
Medium: MSL_850_110910 Medium parameters used (interpolated): $f = 836.4$ MHz; $\sigma = 0.995$ mho/m; $\epsilon_r = 54.7$; $\rho = 1000$ kg/m³
Ambient Temperature : 22.3 °C ; Liquid Temperature : 21.3 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3661; ConvF(9.58, 9.58, 9.58); Calibrated: 2011/1/24
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn495; Calibrated: 2011/4/28
- Phantom: ELI 4.0_Front; Type: QDOVA001BB; Serial: 1026
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Ch189/Area Scan (41x81x1): Measurement grid: dx=20mm, dy=20mm
Maximum value of SAR (interpolated) = 1.08 mW/g

Ch189/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 30.9 V/m; Power Drift = -0.033 dB
Peak SAR (extrapolated) = 2.27 W/kg
SAR(1 g) = 0.957 mW/g; SAR(10 g) = 0.689 mW/g
Maximum value of SAR (measured) = 1.00 mW/g



0 dB = 1.00mW/g

#06 GSM1900_GPRS10_Bottom Side_1cm_Ch810_Battery4

DUT: 190794

Communication System: PCS 1900; Frequency: 1909.8 MHz; Duty Cycle: 1:4

Medium: MSL_1900_110913 Medium parameters used: $f = 1910$ MHz; $\sigma = 1.56$ mho/m; $\epsilon_r = 52.9$; $\rho = 1000$

kg/m³

Ambient Temperature : 22.3 ; Liquid Temperature : 21.3

DASY5 Configuration:

- Probe: EX3DV4 - SN3661; ConvF(7.72, 7.72, 7.72); Calibrated: 2011/1/24
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn495; Calibrated: 2011/4/28
- Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1029
- ; SEMCAD X Version 13.4 Build 125

Ch810/Area Scan (21x41x1): Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 1.59 mW/g


Ch810/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 31.2 V/m; Power Drift = 0.028 dB

Peak SAR (extrapolated) = 2.43 W/kg

SAR(1 g) = 1.4 mW/g; SAR(10 g) = 0.746 mW/g

Maximum value of SAR (measured) = 1.58 mW/g



0 dB = 1.58mW/g

#06 GSM1900_GPRS10_Bottom Side_1cm_Ch810_Battery4_2D

DUT: 190794

Communication System: PCS 1900; Frequency: 1909.8 MHz; Duty Cycle: 1:4

Medium: MSL_1900_110913 Medium parameters used: $f = 1910 \text{ MHz}$; $\sigma = 1.56 \text{ mho/m}$; $\epsilon_r = 52.9$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature : 22.3 ; Liquid Temperature : 21.3

DASY5 Configuration:

- Probe: EX3DV4 - SN3661; ConvF(7.72, 7.72, 7.72); Calibrated: 2011/1/24
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn495; Calibrated: 2011/4/28
- Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1029
- ; SEMCAD X Version 13.4 Build 125

Ch810/Area Scan (21x41x1): Measurement grid: $dx=20\text{mm}$, $dy=20\text{mm}$

Maximum value of SAR (interpolated) = 1.59 mW/g


Ch810/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 31.2 V/m; Power Drift = 0.028 dB

Peak SAR (extrapolated) = 2.43 W/kg

SAR(1 g) = 1.4 mW/g; SAR(10 g) = 0.746 mW/g

Maximum value of SAR (measured) = 1.58 mW/g



#13 GSM1900_GPRS10_Bottom Side_1cm_Ch512_Battery4

DUT: 190794

Communication System: PCS 1900; Frequency: 1850.2 MHz; Duty Cycle: 1:4

Medium: MSL_1900_110913 Medium parameters used: $f = 1850.2$ MHz; $\sigma = 1.49$ mho/m; $\epsilon_r = 53.1$; $\rho = 1000$

kg/m³

Ambient Temperature : 22.3 ; Liquid Temperature : 21.3

DASY5 Configuration:

- Probe: EX3DV4 - SN3661; ConvF(7.72, 7.72, 7.72); Calibrated: 2011/1/24
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn495; Calibrated: 2011/4/28
- Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1029
- ; SEMCAD X Version 13.4 Build 125

Ch512/Area Scan (21x41x1): Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 1.27 mW/g


Ch512/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 28.8 V/m; Power Drift = -0.018 dB

Peak SAR (extrapolated) = 1.96 W/kg

SAR(1 g) = 1.14 mW/g; SAR(10 g) = 0.617 mW/g

Maximum value of SAR (measured) = 1.28 mW/g



0 dB = 1.28mW/g

#14 GSM1900_GPRS10_Bottom Side_1cm_Ch661_Battery4

DUT: 190794

Communication System: PCS 1900; Frequency: 1880 MHz; Duty Cycle: 1:4

Medium: MSL_1900_110913 Medium parameters used: $f = 1880$ MHz; $\sigma = 1.53$ mho/m; $\epsilon_r = 53$; $\rho = 1000$

kg/m³

Ambient Temperature : 22.3 ; Liquid Temperature : 21.3

DASY5 Configuration:

- Probe: EX3DV4 - SN3661; ConvF(7.72, 7.72, 7.72); Calibrated: 2011/1/24
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn495; Calibrated: 2011/4/28
- Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1029
- ; SEMCAD X Version 13.4 Build 125

Ch661/Area Scan (21x41x1): Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 1.43 mW/g


Ch661/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 29.9 V/m; Power Drift = -0.016 dB

Peak SAR (extrapolated) = 2.19 W/kg

SAR(1 g) = 1.26 mW/g; SAR(10 g) = 0.673 mW/g

Maximum value of SAR (measured) = 1.43 mW/g



#15 GSM1900_GPRS10_Back_1cm_Ch810_Battery4

DUT: 190794

Communication System: PCS 1900; Frequency: 1909.8 MHz; Duty Cycle: 1:4

Medium: MSL_1900_110913 Medium parameters used: $f = 1910$ MHz; $\sigma = 1.56$ mho/m; $\epsilon_r = 52.9$; $\rho = 1000$

kg/m³

Ambient Temperature : 22.3 ; Liquid Temperature : 21.3

DASY5 Configuration:

- Probe: EX3DV4 - SN3661; ConvF(7.72, 7.72, 7.72); Calibrated: 2011/1/24
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn495; Calibrated: 2011/4/28
- Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1029
- ; SEMCAD X Version 13.4 Build 125

Ch810/Area Scan (41x81x1): Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 1.42 mW/g


Ch810/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 9.01 V/m; Power Drift = -0.149 dB

Peak SAR (extrapolated) = 1.95 W/kg

SAR(1 g) = 1.24 mW/g; SAR(10 g) = 0.709 mW/g

Maximum value of SAR (measured) = 1.48 mW/g



0 dB = 1.48mW/g

#15 GSM1900_GPRS10_Back_1cm_Ch810_Battery4_2D

DUT: 190794

Communication System: PCS 1900; Frequency: 1909.8 MHz; Duty Cycle: 1:4

Medium: MSL_1900_110913 Medium parameters used: $f = 1910$ MHz; $\sigma = 1.56$ mho/m; $\epsilon_r = 52.9$; $\rho = 1000$ kg/m³

Ambient Temperature : 22.3 ; Liquid Temperature : 21.3

DASY5 Configuration:

- Probe: EX3DV4 - SN3661; ConvF(7.72, 7.72, 7.72); Calibrated: 2011/1/24
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn495; Calibrated: 2011/4/28
- Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1029
- ; SEMCAD X Version 13.4 Build 125

Ch810/Area Scan (41x81x1): Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 1.42 mW/g


Ch810/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 9.01 V/m; Power Drift = -0.149 dB

Peak SAR (extrapolated) = 1.95 W/kg

SAR(1 g) = 1.24 mW/g; SAR(10 g) = 0.709 mW/g

Maximum value of SAR (measured) = 1.48 mW/g



#16 GSM1900_GPRS10_Back_1cm_Ch512_Battery4

DUT: 190794

Communication System: PCS 1900; Frequency: 1850.2 MHz; Duty Cycle: 1:4

Medium: MSL_1900_110913 Medium parameters used: $f = 1850.2$ MHz; $\sigma = 1.49$ mho/m; $\epsilon_r = 53.1$; $\rho = 1000$

kg/m³

Ambient Temperature : 22.3 ; Liquid Temperature : 21.3

DASY5 Configuration:

- Probe: EX3DV4 - SN3661; ConvF(7.72, 7.72, 7.72); Calibrated: 2011/1/24
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn495; Calibrated: 2011/4/28
- Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1029
- ; SEMCAD X Version 13.4 Build 125

Ch512/Area Scan (41x81x1): Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 1.26 mW/g


Ch512/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 8.67 V/m; Power Drift = -0.139 dB

Peak SAR (extrapolated) = 1.97 W/kg

SAR(1 g) = 1.19 mW/g; SAR(10 g) = 0.680 mW/g

Maximum value of SAR (measured) = 1.28 mW/g



0 dB = 1.28mW/g

#17 GSM1900_GPRS10_Back_1cm_Ch661_Battery4

DUT: 190794

Communication System: PCS 1900; Frequency: 1880 MHz; Duty Cycle: 1:4

Medium: MSL_1900_110913 Medium parameters used: $f = 1880$ MHz; $\sigma = 1.53$ mho/m; $\epsilon_r = 53$; $\rho = 1000$

kg/m³

Ambient Temperature : 22.3 ; Liquid Temperature : 21.3

DASY5 Configuration:

- Probe: EX3DV4 - SN3661; ConvF(7.72, 7.72, 7.72); Calibrated: 2011/1/24
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn495; Calibrated: 2011/4/28
- Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1029
- ; SEMCAD X Version 13.4 Build 125

Ch661/Area Scan (41x81x1): Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 1.3 mW/g


Ch661/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 8.37 V/m; Power Drift = -0.133 dB

Peak SAR (extrapolated) = 2.05 W/kg

SAR(1 g) = 1.23 mW/g; SAR(10 g) = 0.703 mW/g

Maximum value of SAR (measured) = 1.34 mW/g



0 dB = 1.34mW/g

#07 WCDMA IV_RMC12.2K_Bcem_1cm_Ch1513_Battery1

DUT: 190794


Communication System: WCDMA; Frequency: 1752.6 MHz; Duty Cycle: 1:1
Medium: MSL_1800_110919 Medium parameters used: $f = 1753$ MHz; $\sigma = 1.55$ mho/m; $\epsilon_r = 51.729$;
 $\rho = 1000$ kg/m³
Ambient Temperature : 22.3 °C ; Liquid Temperature : 21.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3792; ConvF(7.62, 7.62, 7.62); Calibrated: 2011/6/20
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn905; Calibrated: 2011/6/24
- Phantom: ELI v5.0; Type: QDOVA002AA; Serial: TP1127
- Measurement SW: DASY52, Version 52.6 (2); SEMCAD X Version 14.4.5 (3634)

Ch1513/Area Scan (41x81x1): Measurement grid: dx=20mm, dy=20mm
Maximum value of SAR (interpolated) = 1.569 mW/g

Ch1513/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 12.214 V/m; Power Drift = -0.18 dB
Peak SAR (extrapolated) = 2.173 W/kg
SAR(1 g) = 1.37 mW/g; SAR(10 g) = 0.835 mW/g
Maximum value of SAR (measured) = 1.488 mW/g



0 dB = 1.490mW/g

#07 WCDMA IV_RMC12.2K_Dcem_1cm_Ch1513_Battery1_2D

DUT: 190794


Communication System: WCDMA; Frequency: 1752.6 MHz; Duty Cycle: 1:1
Medium: MSL_1800_110919 Medium parameters used: $f = 1753$ MHz; $\sigma = 1.55$ mho/m; $\epsilon_r = 51.729$; $\rho = 1000$ kg/m³
Ambient Temperature : 22.3 °C ; Liquid Temperature : 21.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3792; ConvF(7.62, 7.62, 7.62); Calibrated: 2011/6/20
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn905; Calibrated: 2011/6/24
- Phantom: ELI v5.0; Type: QDOVA002AA; Serial: TP1127
- Measurement SW: DASY52, Version 52.6 (2); SEMCAD X Version 14.4.5 (3634)

Ch1513/Area Scan (41x81x1): Measurement grid: dx=20mm, dy=20mm
Maximum value of SAR (interpolated) = 1.569 mW/g

Ch1513/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 12.214 V/m; Power Drift = -0.18 dB
Peak SAR (extrapolated) = 2.173 W/kg
SAR(1 g) = 1.37 mW/g; SAR(10 g) = 0.835 mW/g
Maximum value of SAR (measured) = 1.488 mW/g



#09 WCDMA IV_RMC12.2K_Dcem_1cm_Ch1312_Battery1

DUT: 190794

Communication System: WCDMA; Frequency: 1712.4 MHz; Duty Cycle: 1:1

Medium: MSL_1800_110919 Medium parameters used: $f = 1712.4$ MHz; $\sigma = 1.504$ mho/m; $\epsilon_r =$

51.92 ; $\rho = 1000$ kg/m³

Ambient Temperature : 22.3 °C ; Liquid Temperature : 21.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3792; ConvF(7.62, 7.62, 7.62); Calibrated: 2011/6/20
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn905; Calibrated: 2011/6/24
- Phantom: ELI v5.0; Type: QDOVA002AA; Serial: TP1127
- Measurement SW: DASY52, Version 52.6 (2); SEMCAD X Version 14.4.5 (3634)

Ch1312/Area Scan (41x81x1): Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 1.313 mW/g


Ch1312/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 12.373 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 1.901 W/kg

SAR(1 g) = 1.21 mW/g; SAR(10 g) = 0.735 mW/g

Maximum value of SAR (measured) = 1.293 mW/g



0 dB = 1.290mW/g

#10 WCDMA IV_RMC12.2K_Dcem_1cm_Ch1413_Battery1

DUT: 190794


Communication System: WCDMA; Frequency: 1732.6 MHz; Duty Cycle: 1:1
Medium: MSL_1800_110919 Medium parameters used: $f = 1733$ MHz; $\sigma = 1.526$ mho/m; $\epsilon_r = 51.814$; $\rho = 1000$ kg/m³
Ambient Temperature : 22.3 °C ; Liquid Temperature : 21.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3792; ConvF(7.62, 7.62, 7.62); Calibrated: 2011/6/20
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn905; Calibrated: 2011/6/24
- Phantom: ELI v5.0; Type: QDOVA002AA; Serial: TP1127
- Measurement SW: DASY52, Version 52.6 (2); SEMCAD X Version 14.4.5 (3634)

Ch1413/Area Scan (41x81x1): Measurement grid: dx=20mm, dy=20mm
Maximum value of SAR (interpolated) = 1.375 mW/g

Ch1413/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 12.151 V/m; Power Drift = -0.01 dB
Peak SAR (extrapolated) = 2.021 W/kg
SAR(1 g) = 1.27 mW/g; SAR(10 g) = 0.775 mW/g
Maximum value of SAR (measured) = 1.372 mW/g



0 dB = 1.370mW/g

#08 802.11b_Back_1cm_Ch6_Battery4

DUT: 190794

Communication System: 802.11b ; Frequency: 2437 MHz;Duty Cycle: 1:1

Medium: MSL_2450_110910 Medium parameters used: $f = 2437 \text{ MHz}$; $\sigma = 1.95 \text{ mho/m}$; $\epsilon_r = 53.9$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature : 22.5 °C ; Liquid Temperature : 21.5 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3661; ConvF(7.55, 7.55, 7.55); Calibrated: 2011/1/24
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn495; Calibrated: 2011/4/28
- Phantom: ELI 4.0_Front; Type: QDOVA001BB; Serial: 1026
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Ch6/Area Scan (41x81x1): Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.346 mW/g


Ch6/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 5.93 V/m; Power Drift = -0.127 dB

Peak SAR (extrapolated) = 0.797 W/kg

SAR(1 g) = 0.406 mW/g; SAR(10 g) = 0.193 mW/g

Maximum value of SAR (measured) = 0.455 mW/g



#08 802.11b_Back_1cm_Ch6_Battery4_2D

DUT: 190794

Communication System: 802.11b ; Frequency: 2437 MHz;Duty Cycle: 1:1

Medium: MSL_2450_110910 Medium parameters used: $f = 2437$ MHz; $\sigma = 1.95$ mho/m; $\epsilon_r = 53.9$;

$\rho = 1000$ kg/m³

Ambient Temperature : 22.5 °C ; Liquid Temperature : 21.5 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3661; ConvF(7.55, 7.55, 7.55); Calibrated: 2011/1/24
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn495; Calibrated: 2011/4/28
- Phantom: ELI 4.0_Front; Type: QDOVA001BB; Serial: 1026
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Ch6/Area Scan (41x81x1): Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.346 mW/g

Ch6/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 5.93 V/m; Power Drift = -0.127 dB

Peak SAR (extrapolated) = 0.797 W/kg

SAR(1 g) = 0.406 mW/g; SAR(10 g) = 0.193 mW/g

Maximum value of SAR (measured) = 0.455 mW/g

