



Appendix B. SAR Plots of SAR Measurement

The plots for SAR measurement are shown as follows.

P01 CDMA2000 BC0_RC3+SO55_Right Cheek_Ch777_Battery1_Cover1

DUT: 111221C21


Communication System: CDMA2000; Frequency: 848.31 MHz; Duty Cycle: 1:1
Medium: H835_0107 Medium parameters used : $f = 848.31$ MHz; $\sigma = 0.936$ mho/m; $\epsilon_r = 42.863$; $\rho = 1000$ kg/m³
Ambient Temperature : 22.4 °C ; Liquid Temperature : 21.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3800; ConvF(8.7, 8.7, 8.7); Calibrated: 2011/08/05
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2011/07/29
- Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: TP:1653
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)

Ch777/Area Scan (41x81x1): Measurement grid: dx=20mm, dy=20mm
Maximum value of SAR (interpolated) = 0.564 mW/g

Ch777/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 4.871 V/m; Power Drift = -0.072 dB
Peak SAR (extrapolated) = 0.6090
SAR(1 g) = 0.485 mW/g; SAR(10 g) = 0.364 mW/g
Maximum value of SAR (measured) = 0.556 mW/g



P02 CDMA2000 BC0_RC3+SO55_Right Tilted_Ch777_Battery1_Cover1

DUT: 111221C21


Communication System: CDMA2000; Frequency: 848.31 MHz; Duty Cycle: 1:1
Medium: H835_0107 Medium parameters used : $f = 848.31$ MHz; $\sigma = 0.936$ mho/m; $\epsilon_r = 42.863$; $\rho = 1000$ kg/m³
Ambient Temperature : 22.4 °C; Liquid Temperature : 21.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3800; ConvF(8.7, 8.7, 8.7); Calibrated: 2011/08/05
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2011/07/29
- Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: TP:1653
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)

Ch777/Area Scan (41x81x1): Measurement grid: dx=20mm, dy=20mm
Maximum value of SAR (interpolated) = 0.349 mW/g

Ch777/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 9.305 V/m; Power Drift = -0.14 dB
Peak SAR (extrapolated) = 0.3440
SAR(1 g) = 0.285 mW/g; SAR(10 g) = 0.220 mW/g
Maximum value of SAR (measured) = 0.319 mW/g



P03 CDMA2000 BC0_RC3+SO55_Left Cheek_Ch777_Battery1_Cover1

DUT: 111221C21


Communication System: CDMA2000; Frequency: 848.31 MHz; Duty Cycle: 1:1
Medium: H835_0107 Medium parameters used: $f = 848.31 \text{ MHz}$; $\sigma = 0.936 \text{ mho/m}$; $\epsilon_r = 42.863$; $\rho = 1000 \text{ kg/m}^3$
Ambient Temperature : 22.4 °C ; Liquid Temperature : 21.3 °C

DASY5 Configuration:


- Probe: EX3DV4 - SN3800; ConvF(8.7, 8.7, 8.7); Calibrated: 2011/08/05
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2011/07/29
- Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: TP:1653
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)

Ch777/Area Scan (41x81x1): Measurement grid: $dx=20\text{mm}$, $dy=20\text{mm}$
Maximum value of SAR (interpolated) = 0.638 mW/g

Ch777/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$
Reference Value = 4.550 V/m; Power Drift = -0.16 dB
Peak SAR (extrapolated) = 0.6920
SAR(1 g) = 0.545 mW/g; SAR(10 g) = 0.408 mW/g
Maximum value of SAR (measured) = 0.631 mW/g



1g/10g Averaged SAR



P04 CDMA2000 BC0_RC3+SO55_Left Tilted_Ch777_Battery1_Cover1

DUT: 111221C21


Communication System: CDMA2000; Frequency: 848.31 MHz; Duty Cycle: 1:1
Medium: H835_0107 Medium parameters used: $f = 848.31 \text{ MHz}$; $\sigma = 0.936 \text{ mho/m}$; $\epsilon_r = 42.863$; $\rho = 1000 \text{ kg/m}^3$
Ambient Temperature : 22.4 °C ; Liquid Temperature : 21.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3800; ConvF(8.7, 8.7, 8.7); Calibrated: 2011/08/05
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2011/07/29
- Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: TP:1653
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)

Ch777/Area Scan (41x81x1): Measurement grid: $dx=20\text{mm}$, $dy=20\text{mm}$
Maximum value of SAR (interpolated) = 0.303 mW/g

Ch777/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$
Reference Value = 7.572 V/m; Power Drift = -0.14 dB
Peak SAR (extrapolated) = 0.3130
SAR(1 g) = 0.255 mW/g; SAR(10 g) = 0.097 mW/g
Maximum value of SAR (measured) = 0.289 mW/g



P05 CDMA2000 BC0_RC3+SO55_Left Cheek_Ch777_Battery2_Cover2

DUT: 111221C21

Communication System: CDMA2000; Frequency: 848.31 MHz; Duty Cycle: 1:1

Medium: H835_0115 Medium parameters used: $f = 848.31 \text{ MHz}$; $\sigma = 0.897 \text{ mho/m}$; $\epsilon_r = 41.831$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature : 21.8 °C; Liquid Temperature : 20.7 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3650; ConvF(8.87, 8.87, 8.87); Calibrated: 2011/10/26
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn579; Calibrated: 2011/09/23
- Phantom: SAM Phantom_Front; Type: SAM; Serial: TP-1485
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)

Ch777/Area Scan (41x81x1): Measurement grid: $dx=20\text{mm}$, $dy=20\text{mm}$

Maximum value of SAR (interpolated) = 0.616 mW/g


Ch777/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 5.137 V/m; Power Drift = -0.15 dB

Peak SAR (extrapolated) = 0.6260

SAR(1 g) = 0.505 mW/g; SAR(10 g) = 0.379 mW/g

Maximum value of SAR (measured) = 0.568 mW/g



P06 CDMA2000 BC1_RC3+SO55_Right Cheek_Ch600_Battery1_Cover1

DUT: 111221C21

Communication System: CDMA2000; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: H1900_0107 Medium parameters used: $f = 1880$ MHz; $\sigma = 1.371$ mho/m; $\epsilon_r = 40.651$; $\rho = 1000$ kg/m³

Ambient Temperature : 22.4 °C ; Liquid Temperature : 21.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3800; ConvF(7.46, 7.46, 7.46); Calibrated: 2011/08/05
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2011/07/29
- Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: TP:1653
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)

Ch600/Area Scan (41x81x1): Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.637 mW/g

Ch600/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 5.344 V/m; Power Drift = 0.15 dB

Peak SAR (extrapolated) = 0.7300

SAR(1 g) = 0.480 mW/g; SAR(10 g) = 0.303 mW/g

Maximum value of SAR (measured) = 0.612 mW/g



Ch600/Zoom Scan (5x5x7)/Cube 1: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 5.344 V/m; Power Drift = 0.15 dB

Peak SAR (extrapolated) = 0.5890

SAR(1 g) = 0.378 mW/g; SAR(10 g) = 0.249 mW/g

Maximum value of SAR (measured) = 0.473 mW/g



P07 CDMA2000 BC1_RC3+SO55_Right Tilted_Ch600_Battery1_Cover1

DUT: 111221C21

Communication System: CDMA2000; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: H1900_0107 Medium parameters used: $f = 1880$ MHz; $\sigma = 1.371$ mho/m; $\epsilon_r = 40.651$; $\rho = 1000$ kg/m³

Ambient Temperature : 22.2 °C; Liquid Temperature : 21.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3800; ConvF(7.46, 7.46, 7.46); Calibrated: 2011/08/05
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2011/07/29
- Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: TP:1653
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)

Ch600/Area Scan (41x81x1): Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.353 mW/g


Ch600/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 8.890 V/m; Power Drift = 0.16 dB

Peak SAR (extrapolated) = 0.3560

SAR(1 g) = 0.228 mW/g; SAR(10 g) = 0.141 mW/g

Maximum value of SAR (measured) = 0.290 mW/g



P08 CDMA2000 BC1_RC3+SO55_Left Cheek_Ch600_Battery1_Cover1

DUT: 111221C21

Communication System: CDMA2000; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: H1900_0107 Medium parameters used: $f = 1880$ MHz; $\sigma = 1.371$ mho/m; $\epsilon_r = 40.651$; $\rho = 1000$ kg/m³

Ambient Temperature : 22.3 °C; Liquid Temperature : 21.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3800; ConvF(7.46, 7.46, 7.46); Calibrated: 2011/08/05
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2011/07/29
- Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: TP:1653
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)

Ch600/Area Scan (41x81x1): Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.770 mW/g


Ch600/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.089 V/m; Power Drift = -0.07 dB


Peak SAR (extrapolated) = 0.8600

SAR(1 g) = 0.577 mW/g; SAR(10 g) = 0.360 mW/g

Maximum value of SAR (measured) = 0.724 mW/g



1g/10g Averaged SAR



P09 CDMA2000 BC1_RC3+SO55_Left Tilted_Ch600_Battery1_Cover1

DUT: 111221C21

Communication System: CDMA2000; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: H1900_0107 Medium parameters used: $f = 1880$ MHz; $\sigma = 1.371$ mho/m; $\epsilon_r = 40.651$; $\rho = 1000$ kg/m³

Ambient Temperature : 22.3 °C; Liquid Temperature : 21.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3800; ConvF(7.46, 7.46, 7.46); Calibrated: 2011/08/05
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2011/07/29
- Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: TP:1653
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)

Ch600/Area Scan (41x81x1): Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.242 mW/g


Ch600/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 9.292 V/m; Power Drift = 0.08 dB

Peak SAR (extrapolated) = 0.2930

SAR(1 g) = 0.185 mW/g; SAR(10 g) = 0.111 mW/g

Maximum value of SAR (measured) = 0.239 mW/g



P10 CDMA2000 BC1_RC3+SO55_Left Cheek_Ch600_Battery2_Cover2

DUT: 111221C21

Communication System: CDMA2000; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: H1900_0115 Medium parameters used: $f = 1880$ MHz; $\sigma = 1.366$ mho/m; $\epsilon_r = 40.561$; $\rho = 1000$ kg/m³

Ambient Temperature : 21.8 °C; Liquid Temperature : 20.7 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3650; ConvF(7.4, 7.4, 7.4); Calibrated: 2011/10/26
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn579; Calibrated: 2011/09/23
- Phantom: SAM Phantom_Left; Type: SAM; Serial: 1202
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)

Ch600/Area Scan (41x81x1): Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.757 mW/g


Ch600/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.945 V/m; Power Drift = 0.10 dB

Peak SAR (extrapolated) = 0.7930

SAR(1 g) = 0.500 mW/g; SAR(10 g) = 0.304 mW/g

Maximum value of SAR (measured) = 0.634 mW/g



P11 CDMA2000 BC0_RTAP153.6_Right Cheek_Ch777_Battery1_Cover1

DUT: 111221C21


Communication System: CDMA2000; Frequency: 848.31 MHz; Duty Cycle: 1:1
Medium: H835_0107 Medium parameters used : $f = 848.31$ MHz; $\sigma = 0.936$ mho/m; $\epsilon_r = 42.863$; $\rho = 1000$ kg/m³
Ambient Temperature : 22.4 °C ; Liquid Temperature : 21.3 °C

DASY5 Configuration:


- Probe: EX3DV4 - SN3800; ConvF(8.7, 8.7, 8.7); Calibrated: 2011/08/05
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2011/07/29
- Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: TP:1653
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)

Ch777/Area Scan (41x81x1): Measurement grid: dx=20mm, dy=20mm
Maximum value of SAR (interpolated) = 0.692 mW/g

Ch777/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 13.362 V/m; Power Drift = 0.04 dB
Peak SAR (extrapolated) = 0.9290
SAR(1 g) = 0.517 mW/g; SAR(10 g) = 0.313 mW/g
Maximum value of SAR (measured) = 0.702 mW/g



1g/10g Averaged SAR



P12 CDMA2000 BC0_RTAP153.6_Right Tilted_Ch777_Battery1_Cover1

DUT: 111221C21


Communication System: CDMA2000; Frequency: 848.31 MHz; Duty Cycle: 1:1
 Medium: H835_0107 Medium parameters used : $f = 848.31$ MHz; $\sigma = 0.936$ mho/m; $\epsilon_r = 42.863$; $\rho = 1000$ kg/m³
 Ambient Temperature : 22.4 °C ; Liquid Temperature : 21.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3800; ConvF(8.7, 8.7, 8.7); Calibrated: 2011/08/05
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2011/07/29
- Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: TP:1653
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)

Ch777/Area Scan (41x81x1): Measurement grid: dx=20mm, dy=20mm
 Maximum value of SAR (interpolated) = 0.327 mW/g

Ch777/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
 Reference Value = 12.194 V/m; Power Drift = -0.15 dB
 Peak SAR (extrapolated) = 0.4750
SAR(1 g) = 0.278 mW/g; SAR(10 g) = 0.167 mW/g
 Maximum value of SAR (measured) = 0.361 mW/g



P13 CDMA2000 BC0_RTAP153.6_Left Cheek_Ch777_Battery1_Cover1

DUT: 111221C21


Communication System: CDMA2000; Frequency: 848.31 MHz; Duty Cycle: 1:1
Medium: H835_0107 Medium parameters used : $f = 848.31$ MHz; $\sigma = 0.936$ mho/m; $\epsilon_r = 42.863$; $\rho = 1000$ kg/m³
Ambient Temperature : 22.4 °C; Liquid Temperature : 21.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3800; ConvF(8.7, 8.7, 8.7); Calibrated: 2011/08/05
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2011/07/29
- Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: TP:1653
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)

Ch777/Area Scan (41x81x1): Measurement grid: dx=20mm, dy=20mm
Maximum value of SAR (interpolated) = 0.427 mW/g

Ch777/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 14.918 V/m; Power Drift = -0.15 dB
Peak SAR (extrapolated) = 0.4820
SAR(1 g) = 0.332 mW/g; SAR(10 g) = 0.228 mW/g
Maximum value of SAR (measured) = 0.409 mW/g



P14 CDMA2000 BC0_RTAP153.6_Left Tilted_Ch777_Battery1_Cover1

DUT: 111221C21


Communication System: CDMA2000; Frequency: 848.31 MHz; Duty Cycle: 1:1
 Medium: H835_0107 Medium parameters used : $f = 848.31$ MHz; $\sigma = 0.936$ mho/m; $\epsilon_r = 42.863$; $\rho = 1000$ kg/m³
 Ambient Temperature : 22.4 °C ; Liquid Temperature : 21.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3800; ConvF(8.7, 8.7, 8.7); Calibrated: 2011/08/05
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2011/07/29
- Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: TP:1653
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)

Ch777/Area Scan (41x81x1): Measurement grid: dx=20mm, dy=20mm
 Maximum value of SAR (interpolated) = 0.211 mW/g

Ch777/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
 Reference Value = 11.783 V/m; Power Drift = -0.13 dB
 Peak SAR (extrapolated) = 0.2370
SAR(1 g) = 0.167 mW/g; SAR(10 g) = 0.113 mW/g
 Maximum value of SAR (measured) = 0.206 mW/g



P15 CDMA2000 BC0_RTAP153.6_Right Cheek_Ch777_Battery2_Cover2

DUT: 111221C21

Communication System: CDMA2000; Frequency: 848.31 MHz; Duty Cycle: 1:1

Medium: H835_0115 Medium parameters used: $f = 848.31$ MHz; $\sigma = 0.897$ mho/m; $\epsilon_r = 41.831$; $\rho = 1000$ kg/m³

Ambient Temperature : 21.8 °C; Liquid Temperature : 20.7 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3650; ConvF(8.87, 8.87, 8.87); Calibrated: 2011/10/26
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn579; Calibrated: 2011/09/23
- Phantom: SAM Phantom_Front; Type: SAM; Serial: TP-1485
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)

Ch777/Area Scan (41x81x1): Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.531 mW/g


Ch777/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 13.912 V/m; Power Drift = -0.13 dB

Peak SAR (extrapolated) = 0.7380

SAR(1 g) = 0.420 mW/g; SAR(10 g) = 0.251 mW/g

Maximum value of SAR (measured) = 0.566 mW/g



P16 CDMA2000 BC1_RTAP153.6_Right Cheek_Ch600_Battery1_Cover1

DUT: 111221C21

Communication System: CDMA2000; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: H1900_0107 Medium parameters used: $f = 1880$ MHz; $\sigma = 1.371$ mho/m; $\epsilon_r = 40.651$; $\rho = 1000$ kg/m³

Ambient Temperature : 22.4 °C ; Liquid Temperature : 21.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3800; ConvF(7.46, 7.46, 7.46); Calibrated: 2011/08/05
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2011/07/29
- Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: TP:1653
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)

Ch600/Area Scan (41x81x1): Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.748 mW/g


Ch600/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 20.880 V/m; Power Drift = 0.09 dB

Peak SAR (extrapolated) = 1.1950

SAR(1 g) = 0.599 mW/g; SAR(10 g) = 0.343 mW/g

Maximum value of SAR (measured) = 0.877 mW/g



P17 CDMA2000 BC1_RTAP153.6_Right Tilted_Ch600_Battery1_Cover1

DUT: 111221C21

Communication System: CDMA2000; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: H1900_0107 Medium parameters used: $f = 1880$ MHz; $\sigma = 1.371$ mho/m; $\epsilon_r = 40.651$; $\rho = 1000$ kg/m³

Ambient Temperature : 22.4 °C ; Liquid Temperature : 21.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3800; ConvF(7.46, 7.46, 7.46); Calibrated: 2011/08/05
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2011/07/29
- Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: TP:1653
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)

Ch600/Area Scan (41x81x1): Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.743 mW/g


Ch600/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 23.396 V/m; Power Drift = -0.09 dB

Peak SAR (extrapolated) = 1.0640

SAR(1 g) = 0.683 mW/g; SAR(10 g) = 0.394 mW/g

Maximum value of SAR (measured) = 0.920 mW/g



P18 CDMA2000 BC1_RTAP153.6_Left Cheek_Ch600_Battery1_Cover1

DUT: 111221C21

Communication System: CDMA2000; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: H1900_0107 Medium parameters used: $f = 1880$ MHz; $\sigma = 1.371$ mho/m; $\epsilon_r = 40.651$; $\rho = 1000$ kg/m³

Ambient Temperature : 22.4 °C ; Liquid Temperature : 21.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3800; ConvF(7.46, 7.46, 7.46); Calibrated: 2011/08/05
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2011/07/29
- Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: TP:1653
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)

Ch600/Area Scan (41x81x1): Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.742 mW/g


Ch600/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 21.653 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 0.8630

SAR(1 g) = 0.511 mW/g; SAR(10 g) = 0.320 mW/g

Maximum value of SAR (measured) = 0.704 mW/g



P19 CDMA2000 BC1_RTAP153.6_Left Tilted_Ch600_Battery1_Cover1

DUT: 111221C21

Communication System: CDMA2000; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: H1900_0107 Medium parameters used: $f = 1880$ MHz; $\sigma = 1.371$ mho/m; $\epsilon_r = 40.651$; $\rho = 1000$ kg/m³

Ambient Temperature : 22.4 °C; Liquid Temperature : 21.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3800; ConvF(7.46, 7.46, 7.46); Calibrated: 2011/08/05
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2011/07/29
- Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: TP:1653
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)

Ch600/Area Scan (41x81x1): Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.882 mW/g


Ch600/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 25.008 V/m; Power Drift = -0.05 dB


Peak SAR (extrapolated) = 1.1120

SAR(1 g) = 0.712 mW/g; SAR(10 g) = 0.417 mW/g

Maximum value of SAR (measured) = 0.946 mW/g



1g/10g Averaged SAR



P20 CDMA2000 BC1_RTAP153.6_Left Tilted_Ch600_Battery2_Cover2

DUT: 111221C21

Communication System: CDMA2000; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: H1900_0115 Medium parameters used: $f = 1880$ MHz; $\sigma = 1.366$ mho/m; $\epsilon_r = 40.561$; $\rho = 1000$ kg/m³

Ambient Temperature : 21.8 °C; Liquid Temperature : 20.7 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3650; ConvF(7.4, 7.4, 7.4); Calibrated: 2011/10/26
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn579; Calibrated: 2011/09/23
- Phantom: SAM Phantom_Left; Type: SAM; Serial: 1202
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)

Ch600/Area Scan (41x81x1): Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.979 mW/g


Ch600/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 25.564 V/m; Power Drift = 0.0076 dB

Peak SAR (extrapolated) = 1.0490

SAR(1 g) = 0.634 mW/g; SAR(10 g) = 0.359 mW/g

Maximum value of SAR (measured) = 0.861 mW/g



P101 LTE XIII_QPSK_10M_Right Cheek_Ch23230_Battery1_Cover1_25RB_Offset12

DUT: 111221C21

Communication System: LTE; Frequency: 782 MHz; Duty Cycle: 1:1

Medium: H750_0108 Medium parameters used: $f = 782 \text{ MHz}$; $\sigma = 0.928 \text{ mho/m}$; $\epsilon_r = 40.367$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature : 22.6 °C ; Liquid Temperature : 21.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3800; ConvF(9.02, 9.02, 9.02); Calibrated: 2011/08/05
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2011/07/29
- Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: TP:1653
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)

Ch23230/Area Scan (41x81x1): Measurement grid: $dx=20\text{mm}$, $dy=20\text{mm}$

Maximum value of SAR (interpolated) = 0.447 mW/g


Ch23230/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 15.871 V/m; Power Drift = -0.14 dB

Peak SAR (extrapolated) = 0.4650

SAR(1 g) = 0.338 mW/g; SAR(10 g) = 0.241 mW/g

Maximum value of SAR (measured) = 0.408 mW/g



P102 LTE XIII_QPSK_10M_Right Cheek_Ch23230_Battery1_Cover1_1RB_Offset0

DUT: 111221C21

Communication System: LTE; Frequency: 782 MHz; Duty Cycle: 1:1

Medium: H750_0108 Medium parameters used: $f = 782 \text{ MHz}$; $\sigma = 0.928 \text{ mho/m}$; $\epsilon_r = 40.367$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature : 22.5 °C; Liquid Temperature : 21.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3800; ConvF(9.02, 9.02, 9.02); Calibrated: 2011/08/05
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2011/07/29
- Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: TP:1653
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)

Ch23230/Area Scan (41x81x1): Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.656 mW/g


Ch23230/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 18.590 V/m; Power Drift = -0.18 dB

Peak SAR (extrapolated) = 0.6510

SAR(1 g) = 0.475 mW/g; SAR(10 g) = 0.339 mW/g

Maximum value of SAR (measured) = 0.575 mW/g



P103 LTE XIII_QPSK_10M_Right Cheek_Ch23230_Battery1_Cover1_1RB_Offset49

DUT: 111221C21

Communication System: LTE; Frequency: 782 MHz; Duty Cycle: 1:1

Medium: H750_0108 Medium parameters used: $f = 782 \text{ MHz}$; $\sigma = 0.928 \text{ mho/m}$; $\epsilon_r = 40.367$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature : 22.5 °C; Liquid Temperature : 21.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3800; ConvF(9.02, 9.02, 9.02); Calibrated: 2011/08/05
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2011/07/29
- Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: TP:1653
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)

Ch23230/Area Scan (41x81x1): Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.632 mW/g


Ch23230/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 18.237 V/m; Power Drift = -0.18 dB

Peak SAR (extrapolated) = 0.6380

SAR(1 g) = 0.466 mW/g; SAR(10 g) = 0.331 mW/g

Maximum value of SAR (measured) = 0.563 mW/g



P104 LTE XIII_QPSK_10M_Right Tilted_Ch23230_Battery1_Cover1_25RB_Offset12

DUT: 111221C21

Communication System: LTE; Frequency: 782 MHz; Duty Cycle: 1:1

Medium: H750_0108 Medium parameters used: $f = 782 \text{ MHz}$; $\sigma = 0.928 \text{ mho/m}$; $\epsilon_r = 40.367$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature : 22.6 °C ; Liquid Temperature : 21.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3800; ConvF(9.02, 9.02, 9.02); Calibrated: 2011/08/05
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2011/07/29
- Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: TP:1653
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)

Ch23230/Area Scan (41x81x1): Measurement grid: $dx=20\text{mm}$, $dy=20\text{mm}$

Maximum value of SAR (interpolated) = 0.307 mW/g


Ch23230/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 14.137 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.3430

SAR(1 g) = 0.235 mW/g; SAR(10 g) = 0.167 mW/g

Maximum value of SAR (measured) = 0.285 mW/g



P105 LTE XIII_QPSK_10M_Right Tilted_Ch23230_Battery1_Cover1_1RB_Offset0

DUT: 111221C21

Communication System: LTE; Frequency: 782 MHz; Duty Cycle: 1:1

Medium: H750_0108 Medium parameters used: $f = 782 \text{ MHz}$; $\sigma = 0.928 \text{ mho/m}$; $\epsilon_r = 40.367$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature : 22.5 °C; Liquid Temperature : 21.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3800; ConvF(9.02, 9.02, 9.02); Calibrated: 2011/08/05
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2011/07/29
- Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: TP:1653
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)

Ch23230/Area Scan (41x81x1): Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.462 mW/g


Ch23230/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 17.216 V/m; Power Drift = -0.16 dB

Peak SAR (extrapolated) = 0.5140

SAR(1 g) = 0.346 mW/g; SAR(10 g) = 0.246 mW/g

Maximum value of SAR (measured) = 0.417 mW/g



P106 LTE XIII_QPSK_10M_Right Tilted_Ch23230_Battery1_Cover1_1RB_Offset49

DUT: 111221C21

Communication System: LTE; Frequency: 782 MHz; Duty Cycle: 1:1

Medium: H750_0108 Medium parameters used: $f = 782 \text{ MHz}$; $\sigma = 0.928 \text{ mho/m}$; $\epsilon_r = 40.367$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature : 22.4 °C; Liquid Temperature : 21.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3800; ConvF(9.02, 9.02, 9.02); Calibrated: 2011/08/05
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2011/07/29
- Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: TP:1653
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)

Ch23230/Area Scan (41x81x1): Measurement grid: $dx=20\text{mm}$, $dy=20\text{mm}$

Maximum value of SAR (interpolated) = 0.417 mW/g


Ch23230/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 16.391 V/m; Power Drift = -0.12 dB

Peak SAR (extrapolated) = 0.4590

SAR(1 g) = 0.306 mW/g; SAR(10 g) = 0.214 mW/g

Maximum value of SAR (measured) = 0.369 mW/g



P107 LTE XIII_QPSK_10M_Left Cheek_Ch23230_Battery1_Cover1_25RB_Offset12

DUT: 111221C21

Communication System: LTE; Frequency: 782 MHz; Duty Cycle: 1:1

Medium: H750_0108 Medium parameters used: $f = 782 \text{ MHz}$; $\sigma = 0.928 \text{ mho/m}$; $\epsilon_r = 40.367$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature : 22.5 °C; Liquid Temperature : 21.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3800; ConvF(9.02, 9.02, 9.02); Calibrated: 2011/08/05
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2011/07/29
- Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: TP:1653
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)

Ch23230/Area Scan (41x81x1): Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.618 mW/g



Ch23230/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 16.216 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 0.8490

SAR(1 g) = 0.457 mW/g; SAR(10 g) = 0.298 mW/g

Maximum value of SAR (measured) = 0.595 mW/g



P108 LTE XIII_QPSK_10M_Left Cheek_Ch23230_Battery1_Cover1_1RB_Offset0

DUT: 111221C21

Communication System: LTE; Frequency: 782 MHz; Duty Cycle: 1:1

Medium: H750_0108 Medium parameters used: $f = 782 \text{ MHz}$; $\sigma = 0.928 \text{ mho/m}$; $\epsilon_r = 40.367$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature : 22.5 °C; Liquid Temperature : 21.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3800; ConvF(9.02, 9.02, 9.02); Calibrated: 2011/08/05
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2011/07/29
- Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: TP:1653
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)

Ch23230/Area Scan (41x81x1): Measurement grid: $dx=20\text{mm}$, $dy=20\text{mm}$

Maximum value of SAR (interpolated) = 0.771 mW/g


Ch23230/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 17.662 V/m; Power Drift = 0.11 dB

Peak SAR (extrapolated) = 1.0000

SAR(1 g) = 0.574 mW/g; SAR(10 g) = 0.400 mW/g

Maximum value of SAR (measured) = 0.727 mW/g



P109 LTE XIII_QPSK_10M_Left Cheek_Ch23230_Battery1_Cover1_1RB_Offset49

DUT: 111221C21

Communication System: LTE; Frequency: 782 MHz; Duty Cycle: 1:1

Medium: H750_0108 Medium parameters used: $f = 782 \text{ MHz}$; $\sigma = 0.928 \text{ mho/m}$; $\epsilon_r = 40.367$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature : 22.6 °C; Liquid Temperature : 21.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3800; ConvF(9.02, 9.02, 9.02); Calibrated: 2011/08/05
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2011/07/29
- Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: TP:1653
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)

Ch23230/Area Scan (41x81x1): Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 1.181 mW/g


Ch23230/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 19.797 V/m; Power Drift = -0.127 dB


Peak SAR (extrapolated) = 1.4120

SAR(1 g) = 0.799 mW/g; SAR(10 g) = 0.535 mW/g

Maximum value of SAR (measured) = 1.041 mW/g



1g/10g Averaged SAR



P110 LTE XIII_QPSK_10M_Left Tilted_Ch23230_Battery1_Cover1_25RB_Offset12

DUT: 111221C21

Communication System: LTE; Frequency: 782 MHz; Duty Cycle: 1:1

Medium: H750_0108 Medium parameters used: $f = 782 \text{ MHz}$; $\sigma = 0.928 \text{ mho/m}$; $\epsilon_r = 40.367$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature : 22.5 °C ; Liquid Temperature : 21.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3800; ConvF(9.02, 9.02, 9.02); Calibrated: 2011/08/05
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2011/07/29
- Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: TP:1653
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)

Ch23230/Area Scan (41x81x1): Measurement grid: $dx=20\text{mm}$, $dy=20\text{mm}$

Maximum value of SAR (interpolated) = 0.623 mW/g


Ch23230/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 15.414 V/m; Power Drift = 0.16 dB

Peak SAR (extrapolated) = 0.8810

SAR(1 g) = 0.402 mW/g; SAR(10 g) = 0.234 mW/g

Maximum value of SAR (measured) = 0.596 mW/g



P111 LTE XIII_QPSK_10M_Left Tilted_Ch23230_Battery1_Cover1_1RB_Offset0

DUT: 111221C21

Communication System: LTE; Frequency: 782 MHz; Duty Cycle: 1:1

Medium: H750_0108 Medium parameters used: $f = 782 \text{ MHz}$; $\sigma = 0.928 \text{ mho/m}$; $\epsilon_r = 40.367$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature : 22.5 °C ; Liquid Temperature : 21.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3800; ConvF(9.02, 9.02, 9.02); Calibrated: 2011/08/05
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2011/07/29
- Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: TP:1653
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)

Ch23230/Area Scan (41x81x1): Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.526 mW/g


Ch23230/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 17.927 V/m; Power Drift = -0.17 dB

Peak SAR (extrapolated) = 1.0420

SAR(1 g) = 0.466 mW/g; SAR(10 g) = 0.279 mW/g

Maximum value of SAR (measured) = 0.678 mW/g



P112 LTE XIII_QPSK_10M_Left Tilted_Ch23230_Battery1_Cover1_1RB_Offset49

DUT: 111221C21

Communication System: LTE; Frequency: 782 MHz; Duty Cycle: 1:1

Medium: H750_0108 Medium parameters used: $f = 782 \text{ MHz}$; $\sigma = 0.928 \text{ mho/m}$; $\epsilon_r = 40.367$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature : 22.5 °C ; Liquid Temperature : 21.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3800; ConvF(9.02, 9.02, 9.02); Calibrated: 2011/08/05
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2011/07/29
- Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: TP:1653
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)

Ch23230/Area Scan (41x81x1): Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.722 mW/g


Ch23230/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 19.398 V/m; Power Drift = -0.19 dB

Peak SAR (extrapolated) = 1.1670

SAR(1 g) = 0.591 mW/g; SAR(10 g) = 0.357 mW/g

Maximum value of SAR (measured) = 0.855 mW/g



P113 LTE XIII_16QAM_10M_Left Cheek_Ch23230_Battery1_Cover1_25RB_Offset12

DUT: 111221C21

Communication System: LTE; Frequency: 782 MHz; Duty Cycle: 1:1

Medium: H750_0116 Medium parameters used: $f = 782 \text{ MHz}$; $\sigma = 0.904 \text{ mho/m}$; $\epsilon_r = 41.101$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature : 21.8 °C ; Liquid Temperature : 20.9 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3590; ConvF(10.21, 10.21, 10.21); Calibrated: 2011/02/25
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2011/07/29
- Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: TP:1653
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)

Ch23230/Area Scan (41x81x1): Measurement grid: $dx=20\text{mm}$, $dy=20\text{mm}$

Maximum value of SAR (interpolated) = 0.416 mW/g


Ch23230/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 12.313 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 0.5990

SAR(1 g) = 0.341 mW/g; SAR(10 g) = 0.224 mW/g

Maximum value of SAR (measured) = 0.452 mW/g



P114 LTE XIII_16QAM_10M_Left Cheek_Ch23230_Battery1_Cover1_1RB_Offset0

DUT: 111221C21

Communication System: LTE; Frequency: 782 MHz; Duty Cycle: 1:1

Medium: H750_0118 Medium parameters used: $f = 782 \text{ MHz}$; $\sigma = 0.931 \text{ mho/m}$; $\epsilon_r = 40.503$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature : 20.7 °C ; Liquid Temperature : 20.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3650; ConvF(9.2, 9.2, 9.2); Calibrated: 2011/10/26
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn579; Calibrated: 2011/09/23
- Phantom: SAM Phantom_Left; Type: SAM; Serial: 1202
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)

Ch23230/Area Scan (41x81x1): Measurement grid: $dx=20\text{mm}$, $dy=20\text{mm}$

Maximum value of SAR (interpolated) = 0.799 mW/g


Configuration/Ch23230/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 18.862 V/m; Power Drift = 0.08 dB

Peak SAR (extrapolated) = 0.9090

SAR(1 g) = 0.516 mW/g; SAR(10 g) = 0.349 mW/g

Maximum value of SAR (measured) = 0.653 mW/g



P115 LTE XIII_16QAM_10M_Left Cheek_Ch23230_Battery1_Cover1_1RB_Offset49

DUT: 111221C21

Communication System: LTE; Frequency: 782 MHz; Duty Cycle: 1:1

Medium: H750_0118 Medium parameters used: $f = 782 \text{ MHz}$; $\sigma = 0.931 \text{ mho/m}$; $\epsilon_r = 40.503$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature : 20.7 °C ; Liquid Temperature : 20.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3650; ConvF(9.2, 9.2, 9.2); Calibrated: 2011/10/26
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn579; Calibrated: 2011/09/23
- Phantom: SAM Phantom_Left; Type: SAM; Serial: 1202
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)

Ch23230/Area Scan (41x81x1): Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 1.072 mW/g


Ch23230/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 20.338 V/m; Power Drift = 0.11 dB

Peak SAR (extrapolated) = 1.2560

SAR(1 g) = 0.630 mW/g; SAR(10 g) = 0.401 mW/g

Maximum value of SAR (measured) = 0.840 mW/g



P138 LTE XIII_QPSK_10M_Left Cheek_Ch23230_Battery2_Cover2_1RB_Offset49

DUT: 111221C21

Communication System: LTE; Frequency: 782 MHz; Duty Cycle: 1:1

Medium: H750_0116 Medium parameters used: $f = 782 \text{ MHz}$; $\sigma = 0.904 \text{ mho/m}$; $\epsilon_r = 41.101$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature : 21.8 °C; Liquid Temperature : 20.9 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3590; ConvF(10.21, 10.21, 10.21); Calibrated: 2011/02/25
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2011/07/29
- Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: TP:1653
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)

Ch23230/Area Scan (41x81x1): Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.395 mW/g


Ch23230/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 12.227 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 0.5320

SAR(1 g) = 0.309 mW/g; SAR(10 g) = 0.206 mW/g

Maximum value of SAR (measured) = 0.401 mW/g



P201 802.11b_Right Cheek_Ch6_Battery1_Cover1

DUT: 111221C21

Communication System: WLAN 2450; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium: H2450_0117 Medium parameters used: $f = 2437$ MHz; $\sigma = 1.828$ mho/m; $\epsilon_r = 38.125$; $\rho = 1000$ kg/m³

Ambient Temperature : 21.2 °C; Liquid Temperature : 20.6 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3650; ConvF(6.8, 6.8, 6.8); Calibrated: 2011/10/26
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn579; Calibrated: 2011/09/23
- Phantom: SAM Phantom_Front; Type: SAM; Serial: TP-1485
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)

Ch6/Area Scan (51x81x1): Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.110 mW/g


Ch6/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 1.664 V/m; Power Drift = 0.16 dB

Peak SAR (extrapolated) = 0.1440

SAR(1 g) = 0.074 mW/g; SAR(10 g) = 0.038 mW/g

Maximum value of SAR (measured) = 0.107 mW/g



P202 802.11b_Right Tilted_Ch6_Battery1_Cover1

DUT: 111221C21

Communication System: WLAN 2450; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium: H2450_0117 Medium parameters used: $f = 2437$ MHz; $\sigma = 1.828$ mho/m; $\epsilon_r = 38.125$; $\rho = 1000$ kg/m³

Ambient Temperature : 21.2 °C; Liquid Temperature : 20.6 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3650; ConvF(6.8, 6.8, 6.8); Calibrated: 2011/10/26
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn579; Calibrated: 2011/09/23
- Phantom: SAM Phantom_Front; Type: SAM; Serial: TP-1485
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)

Ch6/Area Scan (51x81x1): Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.056 mW/g


Ch6/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 4.411 V/m; Power Drift = -0.16 dB

Peak SAR (extrapolated) = 0.0800

SAR(1 g) = 0.042 mW/g; SAR(10 g) = 0.021 mW/g

Maximum value of SAR (measured) = 0.059 mW/g



P203 802.11b_Left Cheek_Ch6_Battery1_Cover1

DUT: 111221C21

Communication System: 802.11b; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium: H2450_0117 Medium parameters used: $f = 2437$ MHz; $\sigma = 1.828$ mho/m; $\epsilon_r = 38.125$; $\rho = 1000$ kg/m³

Ambient Temperature : 21.2 °C; Liquid Temperature : 20.6 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3650; ConvF(6.8, 6.8, 6.8); Calibrated: 2011/10/26
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn579; Calibrated: 2011/09/23
- Phantom: SAM Phantom_Front; Type: SAM; Serial: TP-1485
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)

Ch6/Area Scan (51x81x1): Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.181 mW/g


Ch6/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 2.435 V/m; Power Drift = 0.18 dB


Peak SAR (extrapolated) = 0.2770

SAR(1 g) = 0.129 mW/g; SAR(10 g) = 0.058 mW/g

Maximum value of SAR (measured) = 0.183 mW/g



1g/10g Averaged SAR



P204 802.11b_Left Tilted_Ch6_Battery1_Cover1

DUT: 111221C21

Communication System: WLAN 2450; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium: H2450_0117 Medium parameters used: $f = 2437$ MHz; $\sigma = 1.828$ mho/m; $\epsilon_r = 38.125$; $\rho = 1000$ kg/m³

Ambient Temperature : 21.2 °C; Liquid Temperature : 20.6 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3650; ConvF(6.8, 6.8, 6.8); Calibrated: 2011/10/26
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn579; Calibrated: 2011/09/23
- Phantom: SAM Phantom_Front; Type: SAM; Serial: TP-1485
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)

Ch6/Area Scan (51x81x1): Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.051 mW/g


Ch6/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 4.614 V/m; Power Drift = 0.18 dB

Peak SAR (extrapolated) = 0.0660

SAR(1 g) = 0.035 mW/g; SAR(10 g) = 0.018 mW/g

Maximum value of SAR (measured) = 0.050 mW/g



P205 802.11b_Left Cheek_Ch6_Battery2_Cover2

DUT: 111221C21

Communication System: 802.11b; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium: H2450_0117 Medium parameters used: $f = 2437$ MHz; $\sigma = 1.828$ mho/m; $\epsilon_r = 38.125$; $\rho = 1000$ kg/m³

Ambient Temperature : 21.2 °C ; Liquid Temperature : 20.6 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3650; ConvF(6.8, 6.8, 6.8); Calibrated: 2011/10/26
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn579; Calibrated: 2011/09/23
- Phantom: SAM Phantom_Front; Type: SAM; Serial: TP-1485
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)

Ch6/Area Scan (51x81x1): Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.275 mW/g


Ch6/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 3.695 V/m; Power Drift = 0.13 dB

Peak SAR (extrapolated) = 0.1930

SAR(1 g) = 0.097 mW/g; SAR(10 g) = 0.045 mW/g

Maximum value of SAR (measured) = 0.138 mW/g



P206 802.11a_Right Cheek_ch36_Battery1_Cover1

DUT: 111221C21

Communication System: 802.11a; Frequency: 5180 MHz; Duty Cycle: 1:1

Medium: H5G_0109 Medium parameters used: $f = 5180$ MHz; $\sigma = 4.69$ mho/m; $\epsilon_r = 35.4$; $\rho = 1000$ kg/m³

Ambient Temperature : 21.2 °C; Liquid Temperature : 20.8 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3590; ConvF(5.51, 5.51, 5.51); Calibrated: 2011/02/25
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn861; Calibrated: 2011/08/29
- Phantom: SAM Phantom_Front; Type: SAM V4.0; Serial: TP 1654
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Ch36/Area Scan (101x161x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.106 mW/g


Ch36/Zoom Scan (7x7x9)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2.5mm

Reference Value = 0.535 V/m; Power Drift = 0.126 dB

Peak SAR (extrapolated) = 0.250 W/kg

SAR(1 g) = 0.032 mW/g; SAR(10 g) = 0.011 mW/g

Maximum value of SAR (measured) = 0.067 mW/g



P207 802.11a_Right Tilted_ch36_Battery1_Cover1

DUT: 111221C21

Communication System: 802.11a; Frequency: 5180 MHz;Duty Cycle: 1:1

Medium: H5G_0109 Medium parameters used: $f = 5180$ MHz; $\sigma = 4.69$ mho/m; $\epsilon_r = 35.4$; $\rho = 1000$ kg/m³

Ambient Temperature : 21.2 °C; Liquid Temperature : 20.8 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3590; ConvF(5.51, 5.51, 5.51); Calibrated: 2011/02/25
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn861; Calibrated: 2011/08/29
- Phantom: SAM Phantom_Front; Type: SAM V4.0; Serial: TP 1654
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Ch36/Area Scan (101x161x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.061 mW/g


Ch36/Zoom Scan (7x7x9)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2.5mm

Reference Value = 0.877 V/m; Power Drift = -0.114 dB

Peak SAR (extrapolated) = 0.301 W/kg

SAR(1 g) = 0.029 mW/g; SAR(10 g) = 0.00756 mW/g

Maximum value of SAR (measured) = 0.126 mW/g



P208 802.11a_Left Cheek_ch36_Battery1_Cover1

DUT: 111221C21

Communication System: 802.11a; Frequency: 5180 MHz; Duty Cycle: 1:1

Medium: H5G_0109 Medium parameters used: $f = 5180$ MHz; $\sigma = 4.69$ mho/m; $\epsilon_r = 35.4$; $\rho = 1000$ kg/m³

Ambient Temperature : 21.3 °C; Liquid Temperature : 20.8 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3590; ConvF(5.51, 5.51, 5.51); Calibrated: 2011/02/25
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn861; Calibrated: 2011/08/29
- Phantom: SAM Phantom_Front; Type: SAM V4.0; Serial: TP 1654
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Ch36/Area Scan (121x161x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.250 mW/g


Ch36/Zoom Scan (7x7x9)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2.5mm

Reference Value = 0.000 V/m; Power Drift = 0.036 dB

Peak SAR (extrapolated) = 0.419 W/kg

SAR(1 g) = 0.102 mW/g; SAR(10 g) = 0.029 mW/g

Maximum value of SAR (measured) = 0.202 mW/g



P209 802.11a_Left Tilted_ch36_Battery1_Cover1

DUT: 111221C21

Communication System: 802.11a; Frequency: 5180 MHz; Duty Cycle: 1:1

Medium: H5G_0109 Medium parameters used: $f = 5180$ MHz; $\sigma = 4.69$ mho/m; $\epsilon_r = 35.4$; $\rho = 1000$ kg/m³

Ambient Temperature : 21.1 °C ; Liquid Temperature : 20.8 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3590; ConvF(5.51, 5.51, 5.51); Calibrated: 2011/02/25
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn861; Calibrated: 2011/08/29
- Phantom: SAM Phantom_Front; Type: SAM V4.0; Serial: TP 1654
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Ch36/Area Scan (101x161x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.023 mW/g

Ch36/Zoom Scan (7x7x9)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2.5mm

Reference Value = 0.439 V/m; Power Drift = 0.156 dB

Peak SAR (extrapolated) = 0.045 W/kg

SAR(1 g) = 0.0035 mW/g; SAR(10 g) = 0.000691 mW/g

Maximum value of SAR (measured) = 0.053 mW/g


Ch36/Zoom Scan (7x7x9)/Cube 1: Measurement grid: dx=4mm, dy=4mm, dz=2.5mm

Reference Value = 0.439 V/m; Power Drift = 0.156 dB

Peak SAR (extrapolated) = 0.007 W/kg

SAR(1 g) = 3.98e-005 mW/g; SAR(10 g) = 4.77e-006 mW/g

Maximum value of SAR (measured) = 0.139 mW/g



P210 802.11a_Left Cheek_Ch36_Battery2_Cover2

DUT: 111221C21

Communication System: WLAN 5G; Frequency: 5180 MHz; Duty Cycle: 1:1

Medium: H5G_0117 Medium parameters used: $f = 5180$ MHz; $\sigma = 4.781$ mho/m; $\epsilon_r = 36.816$; $\rho = 1000$ kg/m³

Ambient Temperature : 21 °C; Liquid Temperature : 20.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3650; ConvF(5.05, 5.05, 5.05); Calibrated: 2011/10/26
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn579; Calibrated: 2011/09/23
- Phantom: SAM Phantom_Left; Type: SAM; Serial: 1202
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)

Ch36/Area Scan (51x81x1): Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.197 mW/g


Ch36/Zoom Scan (7x7x9)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2.5mm

Reference Value = 0.018 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 0.2350

SAR(1 g) = 0.080 mW/g; SAR(10 g) = 0.030 mW/g

Maximum value of SAR (measured) = 0.148 mW/g



P211 802.11a_Right Cheek_ch52_Battery1_Cover1

DUT: 111221C21

Communication System: 802.11a; Frequency: 5260 MHz; Duty Cycle: 1:1

Medium: H5G_0109 Medium parameters used: $f = 5260$ MHz; $\sigma = 4.75$ mho/m; $\epsilon_r = 35.2$; $\rho = 1000$ kg/m³

Ambient Temperature : 21.3 °C; Liquid Temperature : 20.8 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3590; ConvF(5.17, 5.17, 5.17); Calibrated: 2011/02/25
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn861; Calibrated: 2011/08/29
- Phantom: SAM Phantom_Front; Type: SAM V4.0; Serial: TP 1654
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Ch52/Area Scan (121x161x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.063 mW/g


Ch52/Zoom Scan (7x7x9)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2.5mm

Reference Value = 0.000 V/m; Power Drift = 0.141 dB

Peak SAR (extrapolated) = 0.159 W/kg

SAR(1 g) = 0.039 mW/g; SAR(10 g) = 0.014 mW/g

Maximum value of SAR (measured) = 0.084 mW/g



P212 802.11a_Right Tilted_ch52_Battery1_Cover1

DUT: 111221C21

Communication System: 802.11a; Frequency: 5260 MHz; Duty Cycle: 1:1

Medium: H5G_0109 Medium parameters used: $f = 5260$ MHz; $\sigma = 4.75$ mho/m; $\epsilon_r = 35.2$; $\rho = 1000$ kg/m³

Ambient Temperature : 21.2 °C; Liquid Temperature : 20.8 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3590; ConvF(5.17, 5.17, 5.17); Calibrated: 2011/02/25
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn861; Calibrated: 2011/08/29
- Phantom: SAM Phantom_Front; Type: SAM V4.0; Serial: TP 1654
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Ch52/Area Scan (101x161x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.060 mW/g


Ch52/Zoom Scan (7x7x9)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2.5mm

Reference Value = 0.407 V/m; Power Drift = -0.113 dB

Peak SAR (extrapolated) = 0.101 W/kg

SAR(1 g) = 0.022 mW/g; SAR(10 g) = 0.00639 mW/g

Maximum value of SAR (measured) = 0.054 mW/g



P213 802.11a_Left Cheek_ch52_Battery1_Cover1

DUT: 111221C21

Communication System: 802.11a; Frequency: 5260 MHz; Duty Cycle: 1:1

Medium: H5G_0109 Medium parameters used: $f = 5260$ MHz; $\sigma = 4.75$ mho/m; $\epsilon_r = 35.2$; $\rho = 1000$ kg/m³

Ambient Temperature : 21.3 °C; Liquid Temperature : 20.8 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3590; ConvF(5.17, 5.17, 5.17); Calibrated: 2011/02/25
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn861; Calibrated: 2011/08/29
- Phantom: SAM Phantom_Front; Type: SAM V4.0; Serial: TP 1654
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Ch52/Area Scan (101x161x1): Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.283 mW/g


Ch52/Zoom Scan (7x7x9)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2.5mm

Reference Value = 0.000 V/m; Power Drift = 0.075 dB

Peak SAR (extrapolated) = 0.544 W/kg


SAR(1 g) = 0.148 mW/g; SAR(10 g) = 0.048 mW/g

Maximum value of SAR (measured) = 0.300 mW/g



1g/10g Averaged SAR

SAR; Zoom Scan: Value Along Z, X=3, Y=3



P214 802.11a_Left Tilted_ch52_Battery1_Cover1

DUT: 111221C21

Communication System: 802.11a; Frequency: 5260 MHz; Duty Cycle: 1:1

Medium: H5G_0109 Medium parameters used: $f = 5260$ MHz; $\sigma = 4.75$ mho/m; $\epsilon_r = 35.2$; $\rho = 1000$ kg/m³

Ambient Temperature : 21.3 °C; Liquid Temperature : 20.8 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3590; ConvF(5.17, 5.17, 5.17); Calibrated: 2011/02/25
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn861; Calibrated: 2011/08/29
- Phantom: SAM Phantom_Front; Type: SAM V4.0; Serial: TP 1654
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Ch52/Area Scan (101x161x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.016 mW/g


Ch52/Zoom Scan (7x7x9)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2.5mm

Reference Value = 0.463 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 0.022 W/kg

SAR(1 g) = 0.000585 mW/g; SAR(10 g) = 7.4e-005 mW/g

Maximum value of SAR (measured) = 0.015 mW/g



P215 802.11a_Left Cheek_Ch52_Battery2_Cover2

DUT: 111221C21

Communication System: 802.11a; Frequency: 5260 MHz; Duty Cycle: 1:1

Medium: H5G_0117 Medium parameters used: $f = 5260$ MHz; $\sigma = 4.839$ mho/m; $\epsilon_r = 36.714$; $\rho = 1000$ kg/m³

Ambient Temperature : 21.2 °C; Liquid Temperature : 20.6 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3650; ConvF(4.71, 4.71, 4.71); Calibrated: 2011/10/26
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn579; Calibrated: 2011/09/23
- Phantom: SAM Phantom_Left; Type: SAM; Serial: 1202
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)

Ch52/Area Scan (101x161x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.199 mW/g


Ch52/Zoom Scan (7x7x9)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2.5mm

Reference Value = 0 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 0.3430

SAR(1 g) = 0.100 mW/g; SAR(10 g) = 0.032 mW/g

Maximum value of SAR (measured) = 0.195 mW/g



P216 802.11a_Right Cheek_ch140_Battery1_Cover1

DUT: 111221C21

Communication System: 802.11a; Frequency: 5700 MHz; Duty Cycle: 1:1

Medium: H5G_0109 Medium parameters used: $f = 5700$ MHz; $\sigma = 5.01$ mho/m; $\epsilon_r = 34.7$; $\rho = 1000$ kg/m³

Ambient Temperature : 21.3 °C; Liquid Temperature : 20.8 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3590; ConvF(4.52, 4.52, 4.52); Calibrated: 2011/02/25
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn861; Calibrated: 2011/08/29
- Phantom: SAM Phantom_Front; Type: SAM V4.0; Serial: TP 1654
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Ch140/Area Scan (121x161x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.306 mW/g


Ch140/Zoom Scan (7x7x9)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2.5mm

Reference Value = 0.000 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.242 W/kg

SAR(1 g) = 0.044 mW/g; SAR(10 g) = 0.016 mW/g

Maximum value of SAR (measured) = 0.123 mW/g



P217 802.11a_Right Tilted_ch140_Battery1_Cover1

DUT: 111221C21

Communication System: 802.11a; Frequency: 5700 MHz; Duty Cycle: 1:1

Medium: H5G_0109 Medium parameters used: $f = 5700$ MHz; $\sigma = 5.01$ mho/m; $\epsilon_r = 34.7$; $\rho = 1000$ kg/m³

Ambient Temperature : 21.3 °C; Liquid Temperature : 20.8 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3590; ConvF(4.52, 4.52, 4.52); Calibrated: 2011/02/25
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn861; Calibrated: 2011/08/29
- Phantom: SAM Phantom_Front; Type: SAM V4.0; Serial: TP 1654
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Ch140/Area Scan (121x161x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.038 mW/g


Ch140/Zoom Scan (7x7x9)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2.5mm

Reference Value = 0.000 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 0.090 W/kg

SAR(1 g) = 0.020 mW/g; SAR(10 g) = 0.00566 mW/g

Maximum value of SAR (measured) = 0.049 mW/g



P218 802.11a_Left Cheek_ch140_Battery1_Cover1

DUT: 111221C21

Communication System: 802.11a; Frequency: 5700 MHz; Duty Cycle: 1:1

Medium: H5G_0109 Medium parameters used: $f = 5700$ MHz; $\sigma = 5.01$ mho/m; $\epsilon_r = 34.7$; $\rho = 1000$ kg/m³

Ambient Temperature : 21.3 °C; Liquid Temperature : 20.8 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3590; ConvF(4.52, 4.52, 4.52); Calibrated: 2011/02/25
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn861; Calibrated: 2011/08/29
- Phantom: SAM Phantom_Front; Type: SAM V4.0; Serial: TP 1654
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Ch140/Area Scan (121x161x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.173 mW/g


Ch140/Zoom Scan (7x7x9)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2.5mm

Reference Value = 0.000 V/m; Power Drift = 0.025 dB

Peak SAR (extrapolated) = 0.482 W/kg

SAR(1 g) = 0.115 mW/g; SAR(10 g) = 0.032 mW/g

Maximum value of SAR (measured) = 0.260 mW/g



P219 802.11a_Left Tilted_ch140_Battery1_Cover1

DUT: 111221C21

Communication System: 802.11a; Frequency: 5700 MHz; Duty Cycle: 1:1

Medium: H5G_0109 Medium parameters used: $f = 5700$ MHz; $\sigma = 5.01$ mho/m; $\epsilon_r = 34.7$; $\rho = 1000$ kg/m³

Ambient Temperature : 21.3 °C; Liquid Temperature : 20.8 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3590; ConvF(4.52, 4.52, 4.52); Calibrated: 2011/02/25
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn861; Calibrated: 2011/08/29
- Phantom: SAM Phantom_Front; Type: SAM V4.0; Serial: TP 1654
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Ch140/Area Scan (121x161x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.024 mW/g


Ch140/Zoom Scan (7x7x9)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2.5mm

Reference Value = 0.000 V/m; Power Drift = 0.075 dB

Peak SAR (extrapolated) = 0.263 W/kg

SAR(1 g) = 0.024 mW/g; SAR(10 g) = 0.00754 mW/g

Maximum value of SAR (measured) = 0.048 mW/g



P220 802.11a_Left Cheek_Ch140_Battery2_Cover2

DUT: 111221C21

Communication System: WLAN 5G; Frequency: 5700 MHz; Duty Cycle: 1:1

Medium: H5G_0117 Medium parameters used: $f = 5700$ MHz; $\sigma = 5.135$ mho/m; $\epsilon_r = 36.25$; $\rho = 1000$ kg/m³

Ambient Temperature : 21.1 °C ; Liquid Temperature : 20.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3650; ConvF(4.42, 4.42, 4.42); Calibrated: 2011/10/26
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn579; Calibrated: 2011/09/23
- Phantom: SAM Phantom_Left; Type: SAM; Serial: 1202
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)

Ch140/Area Scan (101x161x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.313 mW/g


Ch140/Zoom Scan (7x7x9)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2.5mm

Reference Value = 0.825 V/m; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 0.3980

SAR(1 g) = 0.111 mW/g; SAR(10 g) = 0.033 mW/g

Maximum value of SAR (measured) = 0.214 mW/g



P221 802.11a_Right Cheek_Ch161_Battery1_Cover1

DUT: 111221C21

Communication System: 802.11a; Frequency: 5805 MHz; Duty Cycle: 1:1

Medium: H5G_0109 Medium parameters used: $f = 5805$ MHz; $\sigma = 5.07$ mho/m; $\epsilon_r = 34.6$; $\rho = 1000$ kg/m³

Ambient Temperature : 21.3 °C; Liquid Temperature : 20.8 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3590; ConvF(4.53, 4.53, 4.53); Calibrated: 2011/02/25
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn861; Calibrated: 2011/08/29
- Phantom: SAM Phantom_Front; Type: SAM V4.0; Serial: TP 1654
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Ch161/Area Scan (121x161x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.087 mW/g


Ch161/Zoom Scan (7x7x9)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2.5mm

Reference Value = 0.000 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 0.276 W/kg

SAR(1 g) = 0.033 mW/g; SAR(10 g) = 0.013 mW/g

Maximum value of SAR (measured) = 0.076 mW/g



P222 802.11a_Right Tilted_ch161_Battery1_Cover1

DUT: 111221C21

Communication System: 802.11a; Frequency: 5805 MHz; Duty Cycle: 1:1

Medium: H5G_0109 Medium parameters used: $f = 5805$ MHz; $\sigma = 5.07$ mho/m; $\epsilon_r = 34.6$; $\rho = 1000$ kg/m³

Ambient Temperature : 21.3 °C ; Liquid Temperature : 20.8 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3590; ConvF(4.53, 4.53, 4.53); Calibrated: 2011/02/25
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn861; Calibrated: 2011/08/29
- Phantom: SAM Phantom_Front; Type: SAM V4.0; Serial: TP 1654
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Ch161/Area Scan (121x161x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.012 mW/g

Ch161/Zoom Scan (7x7x9)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2.5mm

Reference Value = 0.516 V/m; Power Drift = -0.14 dB

Peak SAR (extrapolated) = 0.030 W/kg

SAR(1 g) = 0.00107 mW/g; SAR(10 g) = 0.000263 mW/g

Maximum value of SAR (measured) = 0.013 mW/g


Ch161/Zoom Scan (7x7x9)/Cube 1: Measurement grid: dx=4mm, dy=4mm, dz=2.5mm

Reference Value = 0.516 V/m; Power Drift = -0.14 dB

Peak SAR (extrapolated) = 0.012 W/kg

SAR(1 g) = 0.000309 mW/g; SAR(10 g) = 8.84e-005 mW/g

Maximum value of SAR (measured) = 0.012 mW/g



P223 802.11a_Left Cheek_ch161_Battery1_Cover1

DUT: 111221C21

Communication System: 802.11a; Frequency: 5805 MHz; Duty Cycle: 1:1

Medium: H5G_0109 Medium parameters used: $f = 5805$ MHz; $\sigma = 5.07$ mho/m; $\epsilon_r = 34.6$; $\rho = 1000$ kg/m³

Ambient Temperature : 21.3 °C; Liquid Temperature : 20.8 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3590; ConvF(4.53, 4.53, 4.53); Calibrated: 2011/02/25
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn861; Calibrated: 2011/08/29
- Phantom: SAM Phantom_Front; Type: SAM V4.0; Serial: TP 1654
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Ch161/Area Scan (121x161x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.154 mW/g


Ch161/Zoom Scan (7x7x9)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2.5mm

Reference Value = 0.000 V/m; Power Drift = 0.045 dB

Peak SAR (extrapolated) = 0.324 W/kg

SAR(1 g) = 0.081 mW/g; SAR(10 g) = 0.026 mW/g

Maximum value of SAR (measured) = 0.175 mW/g



P225 802.11a_Right Cheek_Ch161_Battery2_Cover2

DUT: 111221C21

Communication System: WLAN 5G; Frequency: 5805 MHz; Duty Cycle: 1:1

Medium: H5G_0117 Medium parameters used: $f = 5805$ MHz; $\sigma = 5.205$ mho/m; $\epsilon_r = 36.167$; $\rho = 1000$ kg/m³

Ambient Temperature : 20.9 °C ; Liquid Temperature : 20.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3650; ConvF(4.3, 4.3, 4.3); Calibrated: 2011/10/26
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn579; Calibrated: 2011/09/23
- Phantom: SAM Phantom_Left; Type: SAM; Serial: 1202
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)

Ch161/Area Scan (101x161x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.121 mW/g


Ch161/Zoom Scan (7x7x9)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2.5mm

Reference Value = 0.439 V/m; Power Drift = 0.171 dB

Peak SAR (extrapolated) = 0.1870

SAR(1 g) = 0.029 mW/g; SAR(10 g) = 0.00977 mW/g

Maximum value of SAR (measured) = 0.057 mW/g



P41 CDMA2000 BC0_RC3+SO32_Front Face_1cm_Ch777_Battery1_Cover1

DUT: 111221C21


Communication System: CDMA2000; Frequency: 848.31 MHz; Duty Cycle: 1:1
 Medium: B835_0105 Medium parameters used : $f = 848.31 \text{ MHz}$; $\sigma = 1.005 \text{ mho/m}$; $\epsilon_r = 54.698$; $\rho = 1000 \text{ kg/m}^3$
 Ambient Temperature : $21.1 \text{ }^\circ\text{C}$; Liquid Temperature : $20.4 \text{ }^\circ\text{C}$

DASY5 Configuration:

- Probe: EX3DV4 - SN3800; ConvF(8.94, 8.94, 8.94); Calibrated: 2011/08/05
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2011/07/29
- Phantom: ELI v4.0; Type: QDOVA001BA; Serial: TP:1043
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)

Ch777/Area Scan (41x81x1): Measurement grid: $dx=20\text{mm}$, $dy=20\text{mm}$
 Maximum value of SAR (interpolated) = 0.647 mW/g

Ch777/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$
 Reference Value = 23.900 V/m ; Power Drift = -0.13 dB
 Peak SAR (extrapolated) = 0.6900
SAR(1 g) = 0.549 mW/g ; SAR(10 g) = 0.414 mW/g
 Maximum value of SAR (measured) = 0.632 mW/g



P42 CDMA2000 BC0_RC3+SO32_Rear Face_1cm_Ch777_Battery1_Cover1

DUT: 111221C21


Communication System: CDMA2000; Frequency: 848.31 MHz; Duty Cycle: 1:1
 Medium: B835_0105 Medium parameters used : $f = 848.31 \text{ MHz}$; $\sigma = 1.005 \text{ mho/m}$; $\epsilon_r = 54.698$; $\rho = 1000 \text{ kg/m}^3$
 Ambient Temperature : 21.1 °C ; Liquid Temperature : 20.4 °C

DASY5 Configuration:


- Probe: EX3DV4 - SN3800; ConvF(8.94, 8.94, 8.94); Calibrated: 2011/08/05
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2011/07/29
- Phantom: ELI v4.0; Type: QDOVA001BA; Serial: TP:1043
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)

Ch777/Area Scan (41x81x1): Measurement grid: dx=20mm, dy=20mm
 Maximum value of SAR (interpolated) = 1.419 mW/g

Ch777/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
 Reference Value = 29.443 V/m; Power Drift = -0.03 dB
 Peak SAR (extrapolated) = 1.6860
SAR(1 g) = 1.05 mW/g; SAR(10 g) = 0.722 mW/g
 Maximum value of SAR (measured) = 1.339 mW/g



1g/10g Averaged SAR



P43 CDMA2000 BC0_RC3+SO32_Left Side_1cm_Ch777_Battery1_Cover1

DUT: 111221C21

Communication System: CDMA2000; Frequency: 848.31 MHz; Duty Cycle: 1:1

Medium: B835_0105 Medium parameters used : $f = 848.31$ MHz; $\sigma = 1.005$ mho/m; $\epsilon_r = 54.698$; $\rho = 1000$ kg/m³

Ambient Temperature : 21.0 °C ; Liquid Temperature : 20.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3800; ConvF(8.94, 8.94, 8.94); Calibrated: 2011/08/05
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2011/07/29
- Phantom: ELI v4.0; Type: QDOVA001BA; Serial: TP:1043
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)

Ch777/Area Scan (31x81x1): Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.531 mW/g


Ch777/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 22.332 V/m; Power Drift = -0.08 dB

Peak SAR (extrapolated) = 0.6060

SAR(1 g) = 0.445 mW/g; SAR(10 g) = 0.316 mW/g

Maximum value of SAR (measured) = 0.535 mW/g



P44 CDMA2000 BC0_RC3+SO32_Right Side_1cm_Ch777_Battery1_Cover1

DUT: 111221C21

Communication System: CDMA2000; Frequency: 848.31 MHz; Duty Cycle: 1:1

Medium: B835_0105 Medium parameters used : $f = 848.31$ MHz; $\sigma = 1.005$ mho/m; $\epsilon_r = 54.698$; $\rho = 1000$ kg/m³

Ambient Temperature : 21.0 °C ; Liquid Temperature : 20.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3800; ConvF(8.94, 8.94, 8.94); Calibrated: 2011/08/05
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2011/07/29
- Phantom: ELI v4.0; Type: QDOVA001BA; Serial: TP:1043
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)

Ch777/Area Scan (31x81x1): Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.531 mW/g


Ch777/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 21.167 V/m; Power Drift = -0.12 dB

Peak SAR (extrapolated) = 0.5900

SAR(1 g) = 0.425 mW/g; SAR(10 g) = 0.295 mW/g

Maximum value of SAR (measured) = 0.516 mW/g



P45 CDMA2000 BC0_RC3+SO32_Bottom Side_1cm_Ch777

DUT: 111221C21

Communication System: CDMA2000; Frequency: 848.31 MHz; Duty Cycle: 1:1

Medium: B835_0105 Medium parameters used : $f = 848.31$ MHz; $\sigma = 1.005$ mho/m; $\epsilon_r = 54.698$; $\rho = 1000$ kg/m³

Ambient Temperature : 21.0 °C ; Liquid Temperature : 20.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3800; ConvF(8.94, 8.94, 8.94); Calibrated: 2011/08/05
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2011/07/29
- Phantom: ELI v4.0; Type: QDOVA001BA; Serial: TP:1043
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)

Ch777/Area Scan (51x71x1): Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.013 mW/g

Ch777/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 2.481 V/m; Power Drift = 0.134 dB

Peak SAR (extrapolated) = 0.0150

SAR(1 g) = 0.011 mW/g; SAR(10 g) = 0.00791 mW/g


Maximum value of SAR (measured) = 0.013 mW/g

Configuration/Ch777/Zoom Scan (5x5x7)/Cube 1: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 2.481 V/m; Power Drift = 0.134 dB

Peak SAR (extrapolated) = 0.0140

SAR(1 g) = 0.010 mW/g; SAR(10 g) = 0.00755 mW/g



P46 CDMA2000 BC0_RC3+SO32_Rear Face_1cm_Ch384_Battery1_Cover1

DUT: 111221C21

Communication System: CDMA2000; Frequency: 836.52 MHz; Duty Cycle: 1:1

Medium: B835_0105 Medium parameters used: $f = 837$ MHz; $\sigma = 0.99$ mho/m; $\epsilon_r = 54.779$; $\rho = 1000$ kg/m³

Ambient Temperature : 21.0 °C ; Liquid Temperature : 20.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3800; ConvF(8.94, 8.94, 8.94); Calibrated: 2011/08/05
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2011/07/29
- Phantom: ELI v4.0; Type: QDOVA001BA; Serial: TP:1043
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)

Ch384/Area Scan (41x81x1): Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 1.168 mW/g


Ch384/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 25.659 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 1.3660

SAR(1 g) = 0.869 mW/g; SAR(10 g) = 0.583 mW/g

Maximum value of SAR (measured) = 1.110 mW/g



P47 CDMA2000 BC0_RC3+SO32_Rear Face_1cm_Ch1013_Battery1_Cover1

DUT: 111221C21

Communication System: CDMA2000; Frequency: 824.7 MHz; Duty Cycle: 1:1

Medium: B835_0105 Medium parameters used: $f = 825 \text{ MHz}$; $\sigma = 0.974 \text{ mho/m}$; $\epsilon_r = 54.901$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature : $21.0 \text{ }^\circ\text{C}$; Liquid Temperature : $20.4 \text{ }^\circ\text{C}$

DASY5 Configuration:

- Probe: EX3DV4 - SN3800; ConvF(8.94, 8.94, 8.94); Calibrated: 2011/08/05
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2011/07/29
- Phantom: ELI v4.0; Type: QDOVA001BA; Serial: TP:1043
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)

Ch1013/Area Scan (41x81x1): Measurement grid: $dx=20\text{mm}$, $dy=20\text{mm}$

Maximum value of SAR (interpolated) = 0.876 mW/g


Ch1013/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 20.989 V/m ; Power Drift = 0.13 dB

Peak SAR (extrapolated) = 1.0930

SAR(1 g) = 0.683 mW/g ; SAR(10 g) = 0.440 mW/g

Maximum value of SAR (measured) = 0.871 mW/g



P49 CDMA2000 BC0_RC3+SO32_Rear Face_1cm_Ch777_Battery1_Cover1_Earphone

DUT: 111221C21


Communication System: CDMA2000; Frequency: 848.31 MHz; Duty Cycle: 1:1
 Medium: B835_0105 Medium parameters used : $f = 848.31 \text{ MHz}$; $\sigma = 1.005 \text{ mho/m}$; $\epsilon_r = 54.698$; $\rho = 1000 \text{ kg/m}^3$
 Ambient Temperature : $21.0 \text{ }^\circ\text{C}$; Liquid Temperature : $20.4 \text{ }^\circ\text{C}$

DASY5 Configuration:

- Probe: EX3DV4 - SN3800; ConvF(8.94, 8.94, 8.94); Calibrated: 2011/08/05
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2011/07/29
- Phantom: ELI v4.0; Type: QDOVA001BA; Serial: TP:1043
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)

Ch777/Area Scan (41x81x1): Measurement grid: $dx=20\text{mm}$, $dy=20\text{mm}$
 Maximum value of SAR (interpolated) = 1.175 mW/g

Ch777/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$
 Reference Value = 26.316 V/m ; Power Drift = 0.01 dB
 Peak SAR (extrapolated) = 1.4870
SAR(1 g) = 0.899 mW/g ; SAR(10 g) = 0.561 mW/g
 Maximum value of SAR (measured) = 1.161 mW/g



P48 CDMA2000 BC0_RC3+SO32_Rear Face_1cm_Ch777_Battery2_Cover2

DUT: 111221C21

Communication System: CDMA2000; Frequency: 848.31 MHz; Duty Cycle: 1:1

Medium: B835_0116 Medium parameters used : $f = 848.31$ MHz; $\sigma = 1.011$ mho/m; $\epsilon_r = 54.881$; $\rho = 1000$ kg/m³

Ambient Temperature : 21.6 °C; Liquid Temperature : 21.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3590; ConvF(10.32, 10.32, 10.32); Calibrated: 2011/02/25
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2011/07/29
- Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: TP:1653
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)

Ch777/Area Scan (41x81x1): Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.775 mW/g


Ch777/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 22.982 V/m; Power Drift = -0.13 dB

Peak SAR (extrapolated) = 0.8340

SAR(1 g) = 0.545 mW/g; SAR(10 g) = 0.380 mW/g

Maximum value of SAR (measured) = 0.685 mW/g



P50 CDMA2000 BC1_RC3+SO32_Front Face_1cm_Ch600_Battery1_Cover1

DUT: 111221C21

Communication System: CDMA2000; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: B1900_0105 Medium parameters used: $f = 1880.1$ MHz; $\sigma = 1.522$ mho/m; $\epsilon_r = 52.396$; $\rho = 1000$ kg/m³

Ambient Temperature : 22.2 °C ; Liquid Temperature : 21.6 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3800; ConvF(6.97, 6.97, 6.97); Calibrated: 2011/08/05
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2011/07/29
- Phantom: ELI v4.0; Type: QDOVA001BA; Serial: TP:1043
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)

Ch600/Area Scan (41x81x1): Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.972 mW/g


Ch600/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 11.540 V/m; Power Drift = -0.02 dB


Peak SAR (extrapolated) = 1.1170

SAR(1 g) = 0.714 mW/g; SAR(10 g) = 0.442 mW/g

Maximum value of SAR (measured) = 0.924 mW/g



1g/10g Averaged SAR



P51 CDMA2000 BC1_RC3+SO32_Rear Face_1cm_Ch600_Battery1_Cover1

DUT: 111221C21

Communication System: CDMA2000; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: B1900_0105 Medium parameters used: $f = 1880.1$ MHz; $\sigma = 1.522$ mho/m; $\epsilon_r = 52.396$; $\rho = 1000$ kg/m³

Ambient Temperature : 22.1 °C ; Liquid Temperature : 21.6 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3800; ConvF(6.97, 6.97, 6.97); Calibrated: 2011/08/05
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2011/07/29
- Phantom: ELI v4.0; Type: QDOVA001BA; Serial: TP:1043
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)

Ch600/Area Scan (41x81x1): Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.796 mW/g


Ch600/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 11.673 V/m; Power Drift = -0.0035 dB

Peak SAR (extrapolated) = 0.9210

SAR(1 g) = 0.570 mW/g; SAR(10 g) = 0.351 mW/g

Maximum value of SAR (measured) = 0.738 mW/g



P52 CDMA2000 BC1_RC3+SO32_Left Side_1cm_Ch600_Battery1_Cover1

DUT: 111221C21

Communication System: CDMA2000; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: B1900_0105 Medium parameters used: $f = 1880.1$ MHz; $\sigma = 1.522$ mho/m; $\epsilon_r = 52.396$; $\rho = 1000$ kg/m³

Ambient Temperature : 22.2 °C ; Liquid Temperature : 21.6 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3800; ConvF(6.97, 6.97, 6.97); Calibrated: 2011/08/05
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2011/07/29
- Phantom: ELI v4.0; Type: QDOVA001BA; Serial: TP:1043
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)

Ch600/Area Scan (41x81x1): Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.257 mW/g

Ch600/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 9.605 V/m; Power Drift = 0.0051 dB

Peak SAR (extrapolated) = 0.3090

SAR(1 g) = 0.193 mW/g; SAR(10 g) = 0.114 mW/g

Maximum value of SAR (measured) = 0.254 mW/g


Ch600/Zoom Scan (5x5x7)/Cube 1: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 9.605 V/m; Power Drift = 0.0051 dB

Peak SAR (extrapolated) = 0.2740

SAR(1 g) = 0.169 mW/g; SAR(10 g) = 0.103 mW/g

Maximum value of SAR (measured) = 0.225 mW/g



P53 CDMA2000 BC1_RC3+SO32_Right Side_1cm_Ch600_Battery1_Cover1

DUT: 111221C21

Communication System: CDMA2000; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: B1900_0105 Medium parameters used: $f = 1880.1$ MHz; $\sigma = 1.522$ mho/m; $\epsilon_r = 52.396$; $\rho = 1000$ kg/m³

Ambient Temperature : 22.1 °C ; Liquid Temperature : 21.6 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3800; ConvF(6.97, 6.97, 6.97); Calibrated: 2011/08/05
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2011/07/29
- Phantom: ELI v4.0; Type: QDOVA001BA; Serial: TP:1043
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)

Ch600/Area Scan (41x81x1): Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.353 mW/g

Ch600/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 12.804 V/m; Power Drift = -0.0042 dB

Peak SAR (extrapolated) = 0.4580

SAR(1 g) = 0.264 mW/g; SAR(10 g) = 0.145 mW/g

Maximum value of SAR (measured) = 0.358 mW/g


Ch600/Zoom Scan (5x5x7)/Cube 1: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 12.804 V/m; Power Drift = -0.0042 dB

Peak SAR (extrapolated) = 0.3130

SAR(1 g) = 0.188 mW/g; SAR(10 g) = 0.113 mW/g

Maximum value of SAR (measured) = 0.256 mW/g



P54 CDMA2000 BC1_RC3+SO32_Bottom Side_1cm_Ch600_Battery1_Cover1

DUT: 111221C21

Communication System: CDMA2000; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: B1900_0105 Medium parameters used: $f = 1880.1$ MHz; $\sigma = 1.522$ mho/m; $\epsilon_r = 52.396$; $\rho = 1000$ kg/m³

Ambient Temperature : 22.2 °C ; Liquid Temperature : 21.6 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3800; ConvF(6.97, 6.97, 6.97); Calibrated: 2011/08/05
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2011/07/29
- Phantom: ELI v4.0; Type: QDOVA001BA; Serial: TP:1043
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)

Ch600/Area Scan (41x81x1): Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.550 mW/g


Ch600/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 18.772 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 0.7020

SAR(1 g) = 0.434 mW/g; SAR(10 g) = 0.257 mW/g

Maximum value of SAR (measured) = 0.549 mW/g



P56 CDMA2000 BC1_RC3+SO32_Front Face_1cm_Ch600_Battery1_Cover1_Earphone

DUT: 111221C21


Communication System: CDMA2000; Frequency: 1880 MHz; Duty Cycle: 1:1
Medium: B1900_0105 Medium parameters used: $f = 1880.1$ MHz; $\sigma = 1.522$ mho/m; $\epsilon_r = 52.396$; $\rho = 1000$ kg/m³
Ambient Temperature : 22.2 °C ; Liquid Temperature : 21.6 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3800; ConvF(6.97, 6.97, 6.97); Calibrated: 2011/08/05
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2011/07/29
- Phantom: ELI v4.0; Type: QDOVA001BA; Serial: TP:1043
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)

Ch600/Area Scan (41x81x1): Measurement grid: dx=20mm, dy=20mm
Maximum value of SAR (interpolated) = 0.822 mW/g

Ch600/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 13.090 V/m; Power Drift = 0.09 dB
Peak SAR (extrapolated) = 0.9560
SAR(1 g) = 0.597 mW/g; SAR(10 g) = 0.367 mW/g
Maximum value of SAR (measured) = 0.781 mW/g



P55 CDMA2000 BC1_RC3+SO32_Front Face_1cm_Ch600_Battery2_Cover2

DUT: 111221C21

Communication System: CDMA2000; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: B1900_0116 Medium parameters used: $f = 1880$ MHz; $\sigma = 1.504$ mho/m; $\epsilon_r = 53.788$; $\rho = 1000$ kg/m³

Ambient Temperature : 21.6 °C; Liquid Temperature : 21.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3590; ConvF(8.49, 8.49, 8.49); Calibrated: 2011/02/25
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2011/07/29
- Phantom: ELI v4.0; Type: QDOVA001BA; Serial: TP:1043
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)

Ch600/Area Scan (41x81x1): Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.735 mW/g


Ch600/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 12.142 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.8450

SAR(1 g) = 0.533 mW/g; SAR(10 g) = 0.324 mW/g

Maximum value of SAR (measured) = 0.701 mW/g



P57 CDMA2000 BC0_RTAP153.6_Front Face_1cm_Ch777_Battery1_Cover1

DUT: 111221C21

Communication System: CDMA2000; Frequency: 848.31 MHz; Duty Cycle: 1:1

Medium: B835_0105 Medium parameters used : $f = 848.31$ MHz; $\sigma = 1.005$ mho/m; $\epsilon_r = 54.698$; $\rho = 1000$ kg/m³

Ambient Temperature : 21.0 °C ; Liquid Temperature : 20.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3800; ConvF(8.94, 8.94, 8.94); Calibrated: 2011/08/05
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2011/07/29
- Phantom: ELI v4.0; Type: QDOVA001BA; Serial: TP:1043
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)

Ch777/Area Scan (41x81x1): Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.226 mW/g


Ch777/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 14.476 V/m; Power Drift = -0.16 dB

Peak SAR (extrapolated) = 0.2560

SAR(1 g) = 0.191 mW/g; SAR(10 g) = 0.139 mW/g

Maximum value of SAR (measured) = 0.227 mW/g



P58 CDMA2000 BC0_RTAP153.6_Rear Face_1cm_Ch777_Battery1_Cover1

DUT: 111221C21

Communication System: CDMA2000; Frequency: 848.31 MHz; Duty Cycle: 1:1

Medium: B835_0105 Medium parameters used : $f = 848.31$ MHz; $\sigma = 1.005$ mho/m; $\epsilon_r = 54.698$; $\rho = 1000$ kg/m³

Ambient Temperature : 21.1 °C ; Liquid Temperature : 20.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3800; ConvF(8.94, 8.94, 8.94); Calibrated: 2011/08/05
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2011/07/29
- Phantom: ELI v4.0; Type: QDOVA001BA; Serial: TP:1043
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)

Ch777/Area Scan (41x81x1): Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.681 mW/g

Ch777/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 22.004 V/m; Power Drift = -0.13 dB

Peak SAR (extrapolated) = 0.7830

SAR(1 g) = 0.504 mW/g; SAR(10 g) = 0.309 mW/g

Maximum value of SAR (measured) = 0.663 mW/g


Ch777/Zoom Scan (5x5x7)/Cube 1: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 22.004 V/m; Power Drift = -0.13 dB

Peak SAR (extrapolated) = 0.5390

SAR(1 g) = 0.409 mW/g; SAR(10 g) = 0.299 mW/g

Maximum value of SAR (measured) = 0.483 mW/g



P59 CDMA2000 BC0_RTAP153.6_Left Side_1cm_Ch777_Battery1_Cover1

DUT: 111221C21

Communication System: CDMA2000; Frequency: 848.31 MHz; Duty Cycle: 1:1

Medium: B835_0105 Medium parameters used : $f = 848.31$ MHz; $\sigma = 1.005$ mho/m; $\epsilon_r = 54.698$; $\rho = 1000$ kg/m³

Ambient Temperature : 21.1 °C ; Liquid Temperature : 20.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3800; ConvF(8.94, 8.94, 8.94); Calibrated: 2011/08/05
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2011/07/29
- Phantom: ELI v4.0; Type: QDOVA001BA; Serial: TP:1043
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)

Ch777/Area Scan (31x81x1): Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.709 mW/g


Ch777/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 23.370 V/m; Power Drift = -0.10 dB


Peak SAR (extrapolated) = 0.7600

SAR(1 g) = 0.520 mW/g; SAR(10 g) = 0.345 mW/g

Maximum value of SAR (measured) = 0.652 mW/g



1g/10g Averaged SAR



P60 CDMA2000 BC0_RTAP153.6_Top Side_1cm_Ch777_Battery1_Cover1

DUT: 111221C21

Communication System: CDMA2000; Frequency: 848.31 MHz; Duty Cycle: 1:1

Medium: B835_0105 Medium parameters used : $f = 848.31$ MHz; $\sigma = 1.005$ mho/m; $\epsilon_r = 54.698$; $\rho = 1000$ kg/m³

Ambient Temperature : 21.2 °C ; Liquid Temperature : 20.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3800; ConvF(8.94, 8.94, 8.94); Calibrated: 2011/08/05
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2011/07/29
- Phantom: ELI v4.0; Type: QDOVA001BA; Serial: TP:1043
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)

Ch777/Area Scan (31x81x1): Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.071 mW/g


Ch777/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 7.021 V/m; Power Drift = 0.11 dB

Peak SAR (extrapolated) = 0.0840

SAR(1 g) = 0.057 mW/g; SAR(10 g) = 0.037 mW/g

Maximum value of SAR (measured) = 0.072 mW/g



P62 CDMA2000 BC0_RTAP153.6_Rear Face_1cm_Ch777_Battery1_Cover1_Earphone

DUT: 111221C21

Communication System: CDMA2000; Frequency: 848.31 MHz; Duty Cycle: 1:1

Medium: B835_0105 Medium parameters used : $f = 848.31$ MHz; $\sigma = 1.005$ mho/m; $\epsilon_r = 54.698$; $\rho = 1000$ kg/m³

Ambient Temperature : 21.0 °C ; Liquid Temperature : 20.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3800; ConvF(8.94, 8.94, 8.94); Calibrated: 2011/08/05
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2011/07/29
- Phantom: ELI v4.0; Type: QDOVA001BA; Serial: TP:1043
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)

Ch777/Area Scan (41x81x1): Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.660 mW/g


Ch777/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 16.610 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 0.7800

SAR(1 g) = 0.473 mW/g; SAR(10 g) = 0.276 mW/g

Maximum value of SAR (measured) = 0.580 mW/g



P61 CDMA2000 BC0_RTAP153.6_Left Side_1cm_Ch777_Battery2_Cover2

DUT: 111221C21

Communication System: CDMA2000; Frequency: 848.31 MHz; Duty Cycle: 1:1

Medium: B835_0116 Medium parameters used: $f = 848.31$ MHz; $\sigma = 1.011$ mho/m; $\epsilon_r = 54.881$; $\rho = 1000$ kg/m³

Ambient Temperature : 21.6 °C ; Liquid Temperature : 21.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3590; ConvF(10.32, 10.32, 10.32); Calibrated: 2011/02/25
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2011/07/29
- Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: TP:1653
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)

Ch777/Area Scan (41x81x1): Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.554 mW/g


Ch777/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 23.776 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 0.6400

SAR(1 g) = 0.434 mW/g; SAR(10 g) = 0.291 mW/g

Maximum value of SAR (measured) = 0.546 mW/g



P63 CDMA2000 BC1_RTAP153.6_Front Face_1cm_Ch600_Battery1_Cover1

DUT: 111221C21

Communication System: CDMA2000; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: B1900_0105 Medium parameters used: $f = 1880.1$ MHz; $\sigma = 1.522$ mho/m; $\epsilon_r = 52.396$; $\rho = 1000$ kg/m³

Ambient Temperature : 22.2 °C ; Liquid Temperature : 21.6 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3800; ConvF(6.97, 6.97, 6.97); Calibrated: 2011/08/05
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2011/07/29
- Phantom: ELI v4.0; Type: QDOVA001BA; Serial: TP:1043
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)

Ch600/Area Scan (41x81x1): Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.361 mW/g


Ch600/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 8.734 V/m; Power Drift = -0.135 dB

Peak SAR (extrapolated) = 0.4310

SAR(1 g) = 0.271 mW/g; SAR(10 g) = 0.168 mW/g

Maximum value of SAR (measured) = 0.351 mW/g



P64 CDMA2000 BC1_RTAP153.6_Rear Face_1cm_Ch600_Battery1_Cover1

DUT: 111221C21

Communication System: CDMA2000; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: B1900_0105 Medium parameters used: $f = 1880.1$ MHz; $\sigma = 1.522$ mho/m; $\epsilon_r = 52.396$; $\rho = 1000$ kg/m³

Ambient Temperature : 22.2 °C ; Liquid Temperature : 21.6 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3800; ConvF(6.97, 6.97, 6.97); Calibrated: 2011/08/05
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2011/07/29
- Phantom: ELI v4.0; Type: QDOVA001BA; Serial: TP:1043
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)

Ch600/Area Scan (41x81x1): Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.625 mW/g


Ch600/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 9.437 V/m; Power Drift = -0.08 dB


Peak SAR (extrapolated) = 0.9460

SAR(1 g) = 0.560 mW/g; SAR(10 g) = 0.321 mW/g

Maximum value of SAR (measured) = 0.738 mW/g



1g/10g Averaged SAR



P65 CDMA2000 BC1_RTAP153.6_Left Side_1cm_Ch600_Battery1_Cover1

DUT: 111221C21

Communication System: CDMA2000; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: B1900_0105 Medium parameters used: $f = 1880.1$ MHz; $\sigma = 1.522$ mho/m; $\epsilon_r = 52.396$; $\rho = 1000$ kg/m³

Ambient Temperature : 22.2 °C ; Liquid Temperature : 21.6 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3800; ConvF(6.97, 6.97, 6.97); Calibrated: 2011/08/05
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2011/07/29
- Phantom: ELI v4.0; Type: QDOVA001BA; Serial: TP:1043
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)

Ch600/Area Scan (41x81x1): Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.454 mW/g


Ch600/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.642 V/m; Power Drift = 0.09 dB

Peak SAR (extrapolated) = 0.7020

SAR(1 g) = 0.381 mW/g; SAR(10 g) = 0.194 mW/g

Maximum value of SAR (measured) = 0.537 mW/g



P66 CDMA2000 BC1_RTAP153.6_Top Side_1cm_Ch600_Battery1_Cover1

DUT: 111221C21

Communication System: CDMA2000; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: B1900_0105 Medium parameters used: $f = 1880.1$ MHz; $\sigma = 1.522$ mho/m; $\epsilon_r = 52.396$; $\rho = 1000$ kg/m³

Ambient Temperature : 22.2 °C; Liquid Temperature : 21.6 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3800; ConvF(6.97, 6.97, 6.97); Calibrated: 2011/08/05
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2011/07/29
- Phantom: ELI v4.0; Type: QDOVA001BA; Serial: TP:1043
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)

Ch600/Area Scan (41x81x1): Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.467 mW/g


Ch600/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 17.396 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 0.5600

SAR(1 g) = 0.352 mW/g; SAR(10 g) = 0.211 mW/g

Maximum value of SAR (measured) = 0.462 mW/g



P68 CDMA2000 BC1_RTAP153.6_Rear Face_1cm_Ch600_Battery1_Earphone

DUT: 111221C21

Communication System: CDMA2000; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: B1900_0105 Medium parameters used: $f = 1880.1$ MHz; $\sigma = 1.522$ mho/m; $\epsilon_r = 52.396$; $\rho = 1000$ kg/m³

Ambient Temperature : 22.2 °C ; Liquid Temperature : 21.6 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3800; ConvF(6.97, 6.97, 6.97); Calibrated: 2011/08/05
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2011/07/29
- Phantom: ELI v4.0; Type: QDOVA001BA; Serial: TP:1043
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)

Ch600/Area Scan (41x81x1): Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.562 mW/g


Ch600/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 8.078 V/m; Power Drift = -0.19 dB

Peak SAR (extrapolated) = 0.9290

SAR(1 g) = 0.517 mW/g; SAR(10 g) = 0.284 mW/g

Maximum value of SAR (measured) = 0.726 mW/g



P67 CDMA2000 BC1_RTAP153.6_Rear Face_1cm_Ch600_Battery2_Cover2

DUT: 111221C21

Communication System: CDMA2000; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: B1900_0116 Medium parameters used: $f = 1880$ MHz; $\sigma = 1.504$ mho/m; $\epsilon_r = 53.788$; $\rho = 1000$ kg/m³

Ambient Temperature : 21.6 °C; Liquid Temperature : 21.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3590; ConvF(8.49, 8.49, 8.49); Calibrated: 2011/02/25
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2011/07/29
- Phantom: ELI v4.0; Type: QDOVA001BA; Serial: TP:1043
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)

Ch600/Area Scan (41x81x1): Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.310 mW/g


Ch600/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.440 V/m; Power Drift = -0.13 dB

Peak SAR (extrapolated) = 0.3720

SAR(1 g) = 0.222 mW/g; SAR(10 g) = 0.132 mW/g

Maximum value of SAR (measured) = 0.299 mW/g



**P141 LTE XIII_QPSK_10M_Front
Face_1cm_Ch23230_Battery1_Cover1_25RB_Offset12**

DUT: 111221C21

Communication System: LTE; Frequency: 782 MHz; Duty Cycle: 1:1

Medium: B750_0108 Medium parameters used: $f = 782 \text{ MHz}$; $\sigma = 0.993 \text{ mho/m}$; $\epsilon_r = 55.125$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature : 22.3 °C ; Liquid Temperature : 21.2 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3800; ConvF(9.34, 9.34, 9.34); Calibrated: 2011/08/05
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2011/07/29
- Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: TP:1653
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)

Ch23230/Area Scan (41x81x1): Measurement grid: $dx=20\text{mm}$, $dy=20\text{mm}$

Maximum value of SAR (interpolated) = 0.255 mW/g


Ch23230/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 14.490 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.2710

SAR(1 g) = 0.209 mW/g; SAR(10 g) = 0.153 mW/g

Maximum value of SAR (measured) = 0.241 mW/g



**P144 LTE XIII_QPSK_10M_Rear
Face_1cm_Ch23230_Battery1_Cover1_25RB_Offset 12**

DUT: 111221C21

Communication System: LTE; Frequency: 782 MHz; Duty Cycle: 1:1

Medium: B750_0108 Medium parameters used: $f = 782 \text{ MHz}$; $\sigma = 0.993 \text{ mho/m}$; $\epsilon_r = 55.125$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature : $22.4 \text{ }^\circ\text{C}$; Liquid Temperature : $21.2 \text{ }^\circ\text{C}$

DASY5 Configuration:

- Probe: EX3DV4 - SN3800; ConvF(9.34, 9.34, 9.34); Calibrated: 2011/08/05
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2011/07/29
- Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: TP:1653
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)

Ch23230/Area Scan (41x81x1): Measurement grid: $dx=20\text{mm}$, $dy=20\text{mm}$

Maximum value of SAR (interpolated) = 0.401 mW/g


Ch23230/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 15.469 V/m ; Power Drift = -0.17 dB

Peak SAR (extrapolated) = 0.4100

SAR(1 g) = 0.282 mW/g ; SAR(10 g) = 0.204 mW/g

Maximum value of SAR (measured) = 0.350 mW/g



P147 LTE XIII_QPSK_10M_Right Side_1cm_Ch23230_Battery1_Cover1_25RB_Offset12

DUT: 111221C21


Communication System: LTE; Frequency: 782 MHz; Duty Cycle: 1:1
Medium: B750_0109 Medium parameters used: $f = 782$ MHz; $\sigma = 0.995$ mho/m; $\epsilon_r = 55.289$; $\rho = 1000$ kg/m³
Ambient Temperature : 22.3 °C ; Liquid Temperature : 20.9 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3800; ConvF(9.34, 9.34, 9.34); Calibrated: 2011/08/05
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2011/07/29
- Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: TP:1653
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)

Ch23230/Area Scan (31x81x1): Measurement grid: dx=20mm, dy=20mm
Maximum value of SAR (interpolated) = 0.382 mW/g

Ch23230/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 19.761 V/m; Power Drift = -0.14 dB
Peak SAR (extrapolated) = 0.4360
SAR(1 g) = 0.306 mW/g; SAR(10 g) = 0.210 mW/g
Maximum value of SAR (measured) = 0.379 mW/g



P150 LTE XIII_QPSK_10M_Top Side_1cm_Ch23230_Battery1_Cover1_25RB_Offset12

DUT: 111221C21

Communication System: LTE; Frequency: 782 MHz; Duty Cycle: 1:1

Medium: B750_0109 Medium parameters used: $f = 782 \text{ MHz}$; $\sigma = 0.995 \text{ mho/m}$; $\epsilon_r = 55.289$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature : 22.3 °C ; Liquid Temperature : 20.9 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3800; ConvF(9.34, 9.34, 9.34); Calibrated: 2011/08/05
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2011/07/29
- Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: TP:1653
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)


Ch23230/Area Scan (31x61x1): Measurement grid: $dx=20\text{mm}$, $dy=20\text{mm}$
Maximum value of SAR (interpolated) = 0.178 mW/g

Ch23230/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$
Reference Value = 12.317 V/m; Power Drift = 0.12 dB

Peak SAR (extrapolated) = 0.1930

SAR(1 g) = 0.133 mW/g; SAR(10 g) = 0.089 mW/g

Maximum value of SAR (measured) = 0.162 mW/g



**P157 LTE XIII_QPSK_10M_Rear
Face_Ch23230_Battery1_Cover1_25RB_Offset12_Earphone**

DUT: 111221C21

Communication System: LTE; Frequency: 782 MHz; Duty Cycle: 1:1

Medium: B750_0116 Medium parameters used: $f = 782 \text{ MHz}$; $\sigma = 0.998 \text{ mho/m}$; $\epsilon_r = 55.594$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature : $21.5 \text{ }^\circ\text{C}$; Liquid Temperature : $20.7 \text{ }^\circ\text{C}$

DASY5 Configuration:

- Probe: EX3DV4 - SN3590; ConvF(10.32, 10.32, 10.32); Calibrated: 2011/02/25
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2011/07/29
- Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: TP:1653
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)

Ch23230/Area Scan (41x81x1): Measurement grid: $dx=20\text{mm}$, $dy=20\text{mm}$

Maximum value of SAR (interpolated) = 0.357 mW/g


Ch23230/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 12.939 V/m ; Power Drift = -0.09 dB

Peak SAR (extrapolated) = 0.3530

SAR(1 g) = 0.238 mW/g ; SAR(10 g) = 0.166 mW/g

Maximum value of SAR (measured) = 0.295 mW/g



P142 LTE XIII_QPSK_10M_Front Face_1cm_Ch23230_Battery1_Cover1_1RB_Offset0

DUT: 111221C21

Communication System: LTE; Frequency: 782 MHz; Duty Cycle: 1:1

Medium: B750_0108 Medium parameters used: $f = 782$ MHz; $\sigma = 0.993$ mho/m; $\epsilon_r = 55.125$; $\rho = 1000$ kg/m³

Ambient Temperature : 22.3 °C ; Liquid Temperature : 21.2 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3800; ConvF(9.34, 9.34, 9.34); Calibrated: 2011/08/05
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2011/07/29
- Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: TP:1653
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)

Ch23230/Area Scan (41x81x1): Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.386 mW/g


Ch23230/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 18.028 V/m; Power Drift = -0.160 dB

Peak SAR (extrapolated) = 0.3730

SAR(1 g) = 0.287 mW/g; SAR(10 g) = 0.211 mW/g

Maximum value of SAR (measured) = 0.335 mW/g



**P145 LTE XIII_QPSK_10M_Rear
Face_1cm_Ch23230_Battery1_Cover1_1RB_Offset 0**

DUT: 111221C21

Communication System: LTE; Frequency: 782 MHz; Duty Cycle: 1:1

Medium: B750_0108 Medium parameters used: $f = 782 \text{ MHz}$; $\sigma = 0.993 \text{ mho/m}$; $\epsilon_r = 55.125$; $\rho =$

1000 kg/m^3

Ambient Temperature : $22.3 \text{ }^\circ\text{C}$; Liquid Temperature : $21.2 \text{ }^\circ\text{C}$

DASY5 Configuration:

- Probe: EX3DV4 - SN3800; ConvF(9.34, 9.34, 9.34); Calibrated: 2011/08/05

- Sensor-Surface: 2mm (Mechanical Surface Detection)

- Electronics: DAE4 Sn1277; Calibrated: 2011/07/29

- Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: TP:1653

- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)

Ch23230/Area Scan (41x81x1): Measurement grid: $dx=20\text{mm}$, $dy=20\text{mm}$

Maximum value of SAR (interpolated) = 0.582 mW/g


Ch23230/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 19.067 V/m ; Power Drift = -0.156 dB

Peak SAR (extrapolated) = 0.5360

SAR(1 g) = 0.368 mW/g ; SAR(10 g) = 0.272 mW/g

Maximum value of SAR (measured) = 0.462 mW/g



P148 LTE XIII_QPSK_10M_Right Side_1cm_Ch23230_Battery1_Cover1_1RB_Offset0

DUT: 111221C21

Communication System: LTE; Frequency: 782 MHz; Duty Cycle: 1:1

Medium: B750_0109 Medium parameters used: $f = 782 \text{ MHz}$; $\sigma = 0.995 \text{ mho/m}$; $\epsilon_r = 55.289$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature : 22.3 °C ; Liquid Temperature : 20.9 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3800; ConvF(9.34, 9.34, 9.34); Calibrated: 2011/08/05
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2011/07/29
- Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: TP:1653
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)

Ch23230/Area Scan (31x81x1): Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.543 mW/g


Ch23230/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 24.053 V/m; Power Drift = -0.08 dB


Peak SAR (extrapolated) = 0.6310

SAR(1 g) = 0.443 mW/g; SAR(10 g) = 0.304 mW/g

Maximum value of SAR (measured) = 0.549 mW/g



1g/10g Averaged SAR



P151 LTE XIII_QPSK_10M_Top Side_1cm_Ch23230_Battery1_Cover1_1RB_Offset0

DUT: 111221C21

Communication System: LTE; Frequency: 782 MHz; Duty Cycle: 1:1

Medium: B750_0109 Medium parameters used: $f = 782 \text{ MHz}$; $\sigma = 0.995 \text{ mho/m}$; $\epsilon_r = 55.289$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature : 22.3 °C ; Liquid Temperature : 20.9 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3800; ConvF(9.34, 9.34, 9.34); Calibrated: 2011/08/05
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2011/07/29
- Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: TP:1653
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)


Ch23230/Area Scan (31x61x1): Measurement grid: $dx=20\text{mm}$, $dy=20\text{mm}$
Maximum value of SAR (interpolated) = 0.270 mW/g

Ch23230/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$
Reference Value = 16.138 V/m; Power Drift = -0.14 dB

Peak SAR (extrapolated) = 0.2760

SAR(1 g) = 0.195 mW/g; SAR(10 g) = 0.135 mW/g

Maximum value of SAR (measured) = 0.233 mW/g



**P158 LTE XIII_QPSK_10M_Rear
Face_Ch23230_Battery1_Cover1_1RB_Offset0_Earphone**

DUT: 111221C21

Communication System: LTE; Frequency: 782 MHz; Duty Cycle: 1:1

Medium: B750_0116 Medium parameters used: $f = 782 \text{ MHz}$; $\sigma = 0.998 \text{ mho/m}$; $\epsilon_r = 55.594$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature : $21.5 \text{ }^\circ\text{C}$; Liquid Temperature : $20.7 \text{ }^\circ\text{C}$

DASY5 Configuration:

- Probe: EX3DV4 - SN3590; ConvF(10.32, 10.32, 10.32); Calibrated: 2011/02/25
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2011/07/29
- Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: TP:1653
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)

Ch23230/Area Scan (41x81x1): Measurement grid: $dx=20\text{mm}$, $dy=20\text{mm}$

Maximum value of SAR (interpolated) = 0.523 mW/g


Ch23230/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 16.878 V/m ; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 0.4990

SAR(1 g) = 0.345 mW/g ; SAR(10 g) = 0.243 mW/g

Maximum value of SAR (measured) = 0.417 mW/g



**P143 LTE XIII_QPSK_10M_Front
Face_1cm_Ch23230_Battery1_Cover1_1RB_Offset 49**

DUT: 111221C21

Communication System: LTE; Frequency: 782 MHz; Duty Cycle: 1:1

Medium: B750_0108 Medium parameters used: $f = 782 \text{ MHz}$; $\sigma = 0.993 \text{ mho/m}$; $\epsilon_r = 55.125$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature : $22.3 \text{ }^\circ\text{C}$; Liquid Temperature : $21.2 \text{ }^\circ\text{C}$

DASY5 Configuration:

- Probe: EX3DV4 - SN3800; ConvF(9.34, 9.34, 9.34); Calibrated: 2011/08/05
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2011/07/29
- Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: TP:1653
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)

Ch23230/Area Scan (41x81x1): Measurement grid: $dx=20\text{mm}$, $dy=20\text{mm}$

Maximum value of SAR (interpolated) = 0.284 mW/g


Ch23230/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 14.927 V/m ; Power Drift = 0.0038 dB

Peak SAR (extrapolated) = 0.3040

SAR(1 g) = 0.230 mW/g ; SAR(10 g) = 0.171 mW/g

Maximum value of SAR (measured) = 0.270 mW/g



**P146 LTE XIII_QPSK_10M_Rear
Face_1cm_Ch23230_Battery1_Cover1_1RB_Offset 49**

DUT: 111221C21

Communication System: LTE; Frequency: 782 MHz; Duty Cycle: 1:1

Medium: B750_0108 Medium parameters used: $f = 782 \text{ MHz}$; $\sigma = 0.993 \text{ mho/m}$; $\epsilon_r = 55.125$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature : 22.3 °C ; Liquid Temperature : 21.2 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3800; ConvF(9.34, 9.34, 9.34); Calibrated: 2011/08/05
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2011/07/29
- Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: TP:1653
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)

Ch23230/Area Scan (41x81x1): Measurement grid: $dx=20\text{mm}$, $dy=20\text{mm}$

Maximum value of SAR (interpolated) = 0.428 mW/g


Ch23230/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 15.136 V/m; Power Drift = 0.18 dB

Peak SAR (extrapolated) = 0.4580

SAR(1 g) = 0.309 mW/g; SAR(10 g) = 0.219 mW/g

Maximum value of SAR (measured) = 0.390 mW/g



P149 LTE XIII_QPSK_10M_Right Side_1cm_Ch23230_Battery1_Cover1_1RB_Offset49

DUT: 111221C21

Communication System: LTE; Frequency: 782 MHz; Duty Cycle: 1:1

Medium: B750_0109 Medium parameters used: $f = 782 \text{ MHz}$; $\sigma = 0.995 \text{ mho/m}$; $\epsilon_r = 55.289$; $\rho = 1000 \text{ kg/m}^3$


Ambient Temperature : 22.3 °C ; Liquid Temperature : 20.9 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3800; ConvF(9.34, 9.34, 9.34); Calibrated: 2011/08/05
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2011/07/29
- Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: TP:1653
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)

Ch23230/Area Scan (31x81x1): Measurement grid: dx=20mm, dy=20mm
Maximum value of SAR (interpolated) = 0.528 mW/g

Ch23230/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 22.990 V/m; Power Drift = -0.11 dB
Peak SAR (extrapolated) = 0.6220
SAR(1 g) = 0.437 mW/g; SAR(10 g) = 0.299 mW/g
Maximum value of SAR (measured) = 0.539 mW/g



P152 LTE XIII_QPSK_10M_Top Side_1cm_Ch23230_Battery1_Cover1_1RB_Offset49

DUT: 111221C21

Communication System: LTE; Frequency: 782 MHz; Duty Cycle: 1:1

Medium: B750_0109 Medium parameters used: $f = 782 \text{ MHz}$; $\sigma = 0.995 \text{ mho/m}$; $\epsilon_r = 55.289$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature : $22.3 \text{ }^\circ\text{C}$; Liquid Temperature : $20.9 \text{ }^\circ\text{C}$

DASY5 Configuration:

- Probe: EX3DV4 - SN3800; ConvF(9.34, 9.34, 9.34); Calibrated: 2011/08/05
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2011/07/29
- Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: TP:1653
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)

Ch23230/Area Scan (31x61x1): Measurement grid: $dx=20\text{mm}$, $dy=20\text{mm}$
Maximum value of SAR (interpolated) = 0.225 mW/g


Ch23230/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 14.238 V/m ; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 0.2420

SAR(1 g) = 0.166 mW/g ; SAR(10 g) = 0.112 mW/g

Maximum value of SAR (measured) = 0.203 mW/g



P159 LTE XIII_QPSK_10M_Rear Face_Ch23230_Battery1_Cover1_1RB_Offset49_Earphone

DUT: 111221C21

Communication System: LTE; Frequency: 782 MHz; Duty Cycle: 1:1

Medium: B750_0116 Medium parameters used: $f = 782 \text{ MHz}$; $\sigma = 0.998 \text{ mho/m}$; $\epsilon_r = 55.594$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature : $21.5 \text{ }^\circ\text{C}$; Liquid Temperature : $20.7 \text{ }^\circ\text{C}$

DASY5 Configuration:

- Probe: EX3DV4 - SN3590; ConvF(10.32, 10.32, 10.32); Calibrated: 2011/02/25
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2011/07/29
- Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: TP:1653
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)

Ch23230/Area Scan (41x81x1): Measurement grid: $dx=20\text{mm}$, $dy=20\text{mm}$

Maximum value of SAR (interpolated) = 0.405 mW/g


Ch23230/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 13.404 V/m ; Power Drift = -0.0037 dB

Peak SAR (extrapolated) = 0.4170

SAR(1 g) = 0.277 mW/g ; SAR(10 g) = 0.191 mW/g

Maximum value of SAR (measured) = 0.347 mW/g



**P153 LTE XIII_16QAM_10M_Right
Side_Ch23230_Battery1_Cover1_25RB_Offset12**

DUT: 111221C21

Communication System: LTE; Frequency: 782 MHz; Duty Cycle: 1:1

Medium: B750_0116 Medium parameters used: $f = 782 \text{ MHz}$; $\sigma = 0.998 \text{ mho/m}$; $\epsilon_r = 55.594$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature : $21.5 \text{ }^\circ\text{C}$; Liquid Temperature : $20.7 \text{ }^\circ\text{C}$

DASY5 Configuration:

- Probe: EX3DV4 - SN3590; ConvF(10.32, 10.32, 10.32); Calibrated: 2011/02/25
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2011/07/29
- Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: TP:1653
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)

Ch23230/Area Scan (31x81x1): Measurement grid: $dx=20\text{mm}$, $dy=20\text{mm}$

Maximum value of SAR (interpolated) = 0.316 mW/g


Ch23230/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 17.396 V/m ; Power Drift = -0.09 dB

Peak SAR (extrapolated) = 0.3790

SAR(1 g) = 0.267 mW/g ; SAR(10 g) = 0.184 mW/g

Maximum value of SAR (measured) = 0.328 mW/g



P154 LTE XIII_16QAM_10M_Right Side_Ch23230_Battery1_Cover1_1RB_Offset0

DUT: 111221C21

Communication System: LTE; Frequency: 782 MHz; Duty Cycle: 1:1

Medium: B750_0118 Medium parameters used: $f = 782 \text{ MHz}$; $\sigma = 0.991 \text{ mho/m}$; $\epsilon_r = 54.908$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature : 22.0 °C; Liquid Temperature : 21.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3650; ConvF(9.21, 9.21, 9.21); Calibrated: 2011/10/26
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn579; Calibrated: 2011/09/23
- Phantom: SAM Phantom_Front; Type: SAM; Serial: TP-1485
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)

Ch23230/Area Scan (31x81x1): Measurement grid: $dx=20\text{mm}$, $dy=20\text{mm}$

Maximum value of SAR (interpolated) = 0.509 mW/g


Configuration/Ch23230/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 21.735 V/m; Power Drift = -0.147 dB

Peak SAR (extrapolated) = 0.4230

SAR(1 g) = 0.313 mW/g; SAR(10 g) = 0.225 mW/g

Maximum value of SAR (measured) = 0.373 mW/g



P155 LTE XIII_16QAM_10M_Right Side_Ch23230_Battery1_Cover1_1RB_Offset49

DUT: 111221C21

Communication System: LTE; Frequency: 782 MHz; Duty Cycle: 1:1

Medium: B750_0118 Medium parameters used: $f = 782$ MHz; $\sigma = 0.991$ mho/m; $\epsilon_r = 54.908$; $\rho = 1000$ kg/m³


Ambient Temperature : 22.0 °C ; Liquid Temperature : 21.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3650; ConvF(9.21, 9.21, 9.21); Calibrated: 2011/10/26
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn579; Calibrated: 2011/09/23
- Phantom: SAM Phantom_Front; Type: SAM; Serial: TP-1485
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)

Ch23230/Area Scan (31x81x1): Measurement grid: dx=20mm, dy=20mm
Maximum value of SAR (interpolated) = 0.413 mW/g

Ch23230/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 19.305 V/m; Power Drift = -0.07 dB
Peak SAR (extrapolated) = 0.4740
SAR(1 g) = 0.343 mW/g; SAR(10 g) = 0.242 mW/g
Maximum value of SAR (measured) = 0.416 mW/g



P156 LTE XIII_QPSK_10M_Right Side_Ch23230_Battery2_Cover2_1RB_Offset 0

DUT: 111221C21

Communication System: LTE; Frequency: 782 MHz; Duty Cycle: 1:1

Medium: B750_0116 Medium parameters used: $f = 782 \text{ MHz}$; $\sigma = 0.998 \text{ mho/m}$; $\epsilon_r = 55.594$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature : 21.5 °C ; Liquid Temperature : 20.7 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3590; ConvF(10.32, 10.32, 10.32); Calibrated: 2011/02/25
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2011/07/29
- Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: TP:1653
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)

Ch23230/Area Scan (41x81x1): Measurement grid: $dx=20\text{mm}$, $dy=20\text{mm}$

Maximum value of SAR (interpolated) = 0.229 mW/g


Ch23230/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 14.631 V/m; Power Drift = -0.149 dB

Peak SAR (extrapolated) = 0.2550

SAR(1 g) = 0.179 mW/g; SAR(10 g) = 0.122 mW/g

Maximum value of SAR (measured) = 0.220 mW/g



P241 802.11b_Front Face_1cm_ch6_Battery1_Cover1

DUT: 111221C21

Communication System: 802.11b; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium: B2450_0108 Medium parameters used: $f = 2437$ MHz; $\sigma = 1.96$ mho/m; $\epsilon_r = 51.2$; $\rho = 1000$ kg/m³

Ambient Temperature : 21.8 °C ; Liquid Temperature : 20.7 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3590; ConvF(7.91, 7.91, 7.91); Calibrated: 2011/02/25
- Sensor-Surface: 3mm (Mechanical Surface Detection) Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn861; Calibrated: 2011/08/29
- Phantom: SAM Phantom_Front; Type: SAM V4.0; Serial: TP 1654
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Ch6/Area Scan (51x81x1): Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.033 mW/g

Ch6/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 2.44 V/m; Power Drift = -0.132 dB

Peak SAR (extrapolated) = 0.057 W/kg

SAR(1 g) = 0.030 mW/g; SAR(10 g) = 0.016 mW/g

Maximum value of SAR (measured) = 0.041 mW/g


Ch6/Zoom Scan (5x5x7)/Cube 1: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 2.44 V/m; Power Drift = -0.132 dB

Peak SAR (extrapolated) = 0.036 W/kg

SAR(1 g) = 0.021 mW/g; SAR(10 g) = 0.012 mW/g

Maximum value of SAR (measured) = 0.029 mW/g



P242 802.11b_Rear Face_1cm_ch6_Battery1_Cover1

DUT: 111221C21

Communication System: 802.11b; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium: B2450_0108 Medium parameters used: $f = 2437$ MHz; $\sigma = 1.96$ mho/m; $\epsilon_r = 51.2$; $\rho = 1000$ kg/m³

Ambient Temperature : 21.8 °C ; Liquid Temperature : 20.7 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3590; ConvF(7.91, 7.91, 7.91); Calibrated: 2011/02/25
- Sensor-Surface: 3mm (Mechanical Surface Detection) Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn861; Calibrated: 2011/08/29
- Phantom: SAM Phantom_Front; Type: SAM V4.0; Serial: TP 1654
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Ch6/Area Scan (51x81x1): Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.185 mW/g


Ch6/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.87 V/m; Power Drift = -0.051 dB

Peak SAR (extrapolated) = 0.325 W/kg


SAR(1 g) = 0.167 mW/g; SAR(10 g) = 0.085 mW/g

Maximum value of SAR (measured) = 0.247 mW/g



1g/10g Averaged SAR

SAR; Zoom Scan: Value Along Z, X=2, Y=2



P243 802.11b_Left Side_1cm_ch6_Battery1_Cover1

DUT: 111221C21

Communication System: 802.11b; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium: B2450_0108 Medium parameters used: $f = 2437$ MHz; $\sigma = 1.96$ mho/m; $\epsilon_r = 51.2$; $\rho = 1000$ kg/m³

Ambient Temperature : 21.8 °C ; Liquid Temperature : 20.7 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3590; ConvF(7.91, 7.91, 7.91); Calibrated: 2011/02/25
- Sensor-Surface: 3mm (Mechanical Surface Detection) Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn861; Calibrated: 2011/08/29
- Phantom: SAM Phantom_Front; Type: SAM V4.0; Serial: TP 1654
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Ch6/Area Scan (51x81x1): Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.188 mW/g


Ch6/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 7.88 V/m; Power Drift = 0.092 dB

Peak SAR (extrapolated) = 0.324 W/kg

SAR(1 g) = 0.163 mW/g; SAR(10 g) = 0.077 mW/g

Maximum value of SAR (measured) = 0.245 mW/g



P245 802.11b_Rear Face_1cm_ch6_Battery1_Cover1_Earphone

DUT: 111221C21

Communication System: 802.11b; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium: B2450_0108 Medium parameters used: $f = 2437$ MHz; $\sigma = 1.96$ mho/m; $\epsilon_r = 51.2$; $\rho = 1000$ kg/m³

Ambient Temperature : 21.8 °C ; Liquid Temperature : 20.7 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3590; ConvF(7.91, 7.91, 7.91); Calibrated: 2011/02/25
- Sensor-Surface: 3mm (Mechanical Surface Detection) Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn861; Calibrated: 2011/08/29
- Phantom: SAM Phantom_Front; Type: SAM V4.0; Serial: TP 1654
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Ch6/Area Scan (51x81x1): Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.053 mW/g


Ch6/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 2.98 V/m; Power Drift = -0.050 dB

Peak SAR (extrapolated) = 0.074 W/kg

SAR(1 g) = 0.039 mW/g; SAR(10 g) = 0.019 mW/g

Maximum value of SAR (measured) = 0.058 mW/g



P244 802.11b_Rear Face_1cm_Ch6_Battery2_Cover2

DUT: 111221C21

Communication System: 802.11b; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium: B2450_0117 Medium parameters used: $f = 2437$ MHz; $\sigma = 1.958$ mho/m; $\epsilon_r = 51.012$; $\rho = 1000$ kg/m³

Ambient Temperature : 21.2 °C ; Liquid Temperature : 20.6 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3650; ConvF(6.89, 6.89, 6.89); Calibrated: 2011/10/26
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn579; Calibrated: 2011/09/23
- Phantom: SAM Phantom_Left; Type: SAM; Serial: 1202
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)

Ch6/Area Scan (51x81x1): Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.143 mW/g


Ch6/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.332 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 0.1900

SAR(1 g) = 0.106 mW/g; SAR(10 g) = 0.060 mW/g

Maximum value of SAR (measured) = 0.147 mW/g



P246 802.11a_Front Face_1cm_ch36_Battery1_Cover1

DUT: 111221C21

Communication System: 802.11a; Frequency: 5180 MHz; Duty Cycle: 1:1

Medium: B5G_0107 Medium parameters used: $f = 5180$ MHz; $\sigma = 5.21$ mho/m; $\epsilon_r = 49.3$; $\rho = 1000$ kg/m³

Ambient Temperature : 21.6 °C ; Liquid Temperature : 21.3 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3650; ConvF(4.28, 4.28, 4.28); Calibrated: 2011/10/26
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn579; Calibrated: 2011/09/23
- Phantom: SAM Phantom_Left; Type: SAM V4.0; Serial: TP 1652
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Ch36/Area Scan (101x161x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.045 mW/g

Ch36/Zoom Scan (7x7x9)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2.5mm

Reference Value = 1.15 V/m; Power Drift = 0.126 dB

Peak SAR (extrapolated) = 0.100 W/kg

SAR(1 g) = 0.030 mW/g; SAR(10 g) = 0.012 mW/g

Maximum value of SAR (measured) = 0.055 mW/g


Ch36/Zoom Scan (7x7x9)/Cube 1: Measurement grid: dx=4mm, dy=4mm, dz=2.5mm

Reference Value = 1.15 V/m; Power Drift = 0.126 dB

Peak SAR (extrapolated) = 0.127 W/kg

SAR(1 g) = 0.021 mW/g; SAR(10 g) = 0.00809 mW/g

Maximum value of SAR (measured) = 0.041 mW/g



P247 802.11a_Rear Face_1cm_ch36_Battery1_Cover1

DUT: 111221C21

Communication System: 802.11a; Frequency: 5180 MHz; Duty Cycle: 1:1

Medium: B5G_0107 Medium parameters used: $f = 5180$ MHz; $\sigma = 5.21$ mho/m; $\epsilon_r = 49.3$; $\rho = 1000$ kg/m³

Ambient Temperature : 21.6 °C; Liquid Temperature : 21.3 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3650; ConvF(4.28, 4.28, 4.28); Calibrated: 2011/10/26
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn579; Calibrated: 2011/09/23
- Phantom: SAM Phantom_Left; Type: SAM V4.0; Serial: TP 1652
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Ch36/Area Scan (101x161x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.251 mW/g


Ch36/Zoom Scan (7x7x9)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2.5mm

Reference Value = 1.42 V/m; Power Drift = -0.169 dB

Peak SAR (extrapolated) = 0.522 W/kg

SAR(1 g) = 0.148 mW/g; SAR(10 g) = 0.045 mW/g

Maximum value of SAR (measured) = 0.280 mW/g



P248 802.11a_Left Side_1cm_ch36_Battery1_Cover1

DUT: 111221C21

Communication System: 802.11a; Frequency: 5180 MHz; Duty Cycle: 1:1

Medium: B5G_0107 Medium parameters used: $f = 5180$ MHz; $\sigma = 5.21$ mho/m; $\epsilon_r = 49.3$; $\rho = 1000$ kg/m³

Ambient Temperature : 21.5 °C; Liquid Temperature : 21.3 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3650; ConvF(4.28, 4.28, 4.28); Calibrated: 2011/10/26
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn579; Calibrated: 2011/09/23
- Phantom: SAM Phantom_Left; Type: SAM V4.0; Serial: TP 1652
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Ch36/Area Scan (81x161x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.325 mW/g


Ch36/Zoom Scan (7x7x9)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2.5mm

Reference Value = 3.88 V/m; Power Drift = 0.179 dB

Peak SAR (extrapolated) = 0.990 W/kg


SAR(1 g) = 0.288 mW/g; SAR(10 g) = 0.079 mW/g

Maximum value of SAR (measured) = 0.547 mW/g



1g/10g Averaged SAR

SAR; Zoom Scan: Value Along Z, X=5, Y=5



P250 802.11a_Rear Face_1cm_ch36_Battery1_Cover1_Earphone

DUT: 111221C21

Communication System: 802.11a; Frequency: 5180 MHz; Duty Cycle: 1:1

Medium: B5G_0107 Medium parameters used: $f = 5180$ MHz; $\sigma = 5.21$ mho/m; $\epsilon_r = 49.3$; $\rho = 1000$ kg/m³

Ambient Temperature : 21.6 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3650; ConvF(4.28, 4.28, 4.28); Calibrated: 2011/10/26
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn579; Calibrated: 2011/09/23
- Phantom: SAM Phantom_Left; Type: SAM V4.0; Serial: TP 1652
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Ch36/Area Scan (101x161x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.174 mW/g


Ch36/Zoom Scan (7x7x9)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2.5mm

Reference Value = 0.818 V/m; Power Drift = 0.168 dB

Peak SAR (extrapolated) = 0.453 W/kg

SAR(1 g) = 0.124 mW/g; SAR(10 g) = 0.040 mW/g

Maximum value of SAR (measured) = 0.226 mW/g



P249 802.11a_Left Side _Ch36_Battery2_Cover2

DUT: 111221C21

Communication System: WLAN 5G; Frequency: 5180 MHz; Duty Cycle: 1:1

Medium: H5G_0117 Medium parameters used: $f = 5180$ MHz; $\sigma = 4.781$ mho/m; $\epsilon_r = 36.816$; $\rho = 1000$ kg/m³

Ambient Temperature : 20.9 °C ; Liquid Temperature : 20.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3650; ConvF(5.05, 5.05, 5.05); Calibrated: 2011/10/26
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn579; Calibrated: 2011/09/23
- Phantom: SAM Phantom_Front; Type: SAM; Serial: TP-1485
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)

Ch36/Area Scan (51x81x1): Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.413 mW/g


Ch36/Zoom Scan (7x7x9)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2.5mm

Reference Value = 4.208 V/m; Power Drift = 0.161 dB

Peak SAR (extrapolated) = 0.9810

SAR(1 g) = 0.252 mW/g; SAR(10 g) = 0.085 mW/g

Maximum value of SAR (measured) = 0.465 mW/g



P251 802.11a_Front Face_1cm_ch52_Battery1_Cover1

DUT: 111221C21

Communication System: 802.11a; Frequency: 5260 MHz; Duty Cycle: 1:1

Medium: B5G_0107 Medium parameters used: $f = 5260 \text{ MHz}$; $\sigma = 5.34 \text{ mho/m}$; $\epsilon_r = 49.2$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature : 21.6 °C; Liquid Temperature : 21.3 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3650; ConvF(4.11, 4.11, 4.11); Calibrated: 2011/10/26
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn579; Calibrated: 2011/09/23
- Phantom: SAM Phantom_Left; Type: SAM V4.0; Serial: TP 1652
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Ch52/Area Scan (121x181x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.058 mW/g


Ch52/Zoom Scan (7x7x9)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2.5mm

Reference Value = 1.18 V/m; Power Drift = 0.138 dB

Peak SAR (extrapolated) = 0.118 W/kg

SAR(1 g) = 0.023 mW/g; SAR(10 g) = 0.00915 mW/g

Maximum value of SAR (measured) = 0.046 mW/g



P252 802.11a_Rear Face_1cm_ch52_Battery1_Cover1

DUT: 111221C21

Communication System: 802.11a; Frequency: 5260 MHz; Duty Cycle: 1:1

Medium: B5G_0107 Medium parameters used: $f = 5260$ MHz; $\sigma = 5.34$ mho/m; $\epsilon_r = 49.2$; $\rho = 1000$ kg/m³

Ambient Temperature : 21.4 °C; Liquid Temperature : 21.3 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3650; ConvF(4.11, 4.11, 4.11); Calibrated: 2011/10/26
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn579; Calibrated: 2011/09/23
- Phantom: SAM Phantom_Left; Type: SAM V4.0; Serial: TP 1652
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Ch52/Area Scan (101x161x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.246 mW/g


Ch52/Zoom Scan (7x7x9)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2.5mm

Reference Value = 1.12 V/m; Power Drift = 0.141 dB

Peak SAR (extrapolated) = 0.848 W/kg

SAR(1 g) = 0.227 mW/g; SAR(10 g) = 0.063 mW/g

Maximum value of SAR (measured) = 0.441 mW/g



P253 802.11a_Left Side_1cm_ch52_Battery1_Cover1

DUT: 111221C21

Communication System: 802.11a; Frequency: 5260 MHz; Duty Cycle: 1:1

Medium: B5G_0107 Medium parameters used: $f = 5260$ MHz; $\sigma = 5.34$ mho/m; $\epsilon_r = 49.2$; $\rho = 1000$ kg/m³

Ambient Temperature : 21.5 °C; Liquid Temperature : 21.3 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3650; ConvF(4.11, 4.11, 4.11); Calibrated: 2011/10/26
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn579; Calibrated: 2011/09/23
- Phantom: SAM Phantom_Left; Type: SAM V4.0; Serial: TP 1652
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Ch52/Area Scan (81x161x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.340 mW/g


Ch52/Zoom Scan (7x7x9)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2.5mm

Reference Value = 4.13 V/m; Power Drift = 0.187 dB

Peak SAR (extrapolated) = 1.22 W/kg


SAR(1 g) = 0.345 mW/g; SAR(10 g) = 0.103 mW/g

Maximum value of SAR (measured) = 0.647 mW/g



1g/10g Averaged SAR

SAR; Zoom Scan: Value Along Z, X=4, Y=4



P255 802.11a_Rear Face_1cm_ch52_Battery1_Cover1_Earphone

DUT: 111221C21

Communication System: 802.11a; Frequency: 5260 MHz; Duty Cycle: 1:1

Medium: B5G_0107 Medium parameters used: $f = 5260$ MHz; $\sigma = 5.34$ mho/m; $\epsilon_r = 49.2$; $\rho = 1000$ kg/m³

Ambient Temperature : 21.5 °C; Liquid Temperature : 21.3 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3650; ConvF(4.11, 4.11, 4.11); Calibrated: 2011/10/26
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn579; Calibrated: 2011/09/23
- Phantom: SAM Phantom_Left; Type: SAM V4.0; Serial: TP 1652
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Ch52/Area Scan (101x161x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.189 mW/g


Ch52/Zoom Scan (7x7x9)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2.5mm

Reference Value = 0.984 V/m; Power Drift = 0.148 dB

Peak SAR (extrapolated) = 0.700 W/kg

SAR(1 g) = 0.203 mW/g; SAR(10 g) = 0.057 mW/g

Maximum value of SAR (measured) = 0.379 mW/g



P254 802.11a_Left Side _Ch52_Battery2_Cover2

DUT: 111221C21

Communication System: WLAN 5G; Frequency: 5260 MHz; Duty Cycle: 1:1

Medium: H5G_0117 Medium parameters used: $f = 5260$ MHz; $\sigma = 4.839$ mho/m; $\epsilon_r = 36.714$; $\rho = 1000$ kg/m³

Ambient Temperature : 20.8 °C ; Liquid Temperature : 20.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3650; ConvF(4.71, 4.71, 4.71); Calibrated: 2011/10/26
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn579; Calibrated: 2011/09/23
- Phantom: SAM Phantom_Front; Type: SAM; Serial: TP-1485
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)

Ch52/Area Scan (51x81x1): Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.468 mW/g


Ch52/Zoom Scan (7x7x9)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2.5mm

Reference Value = 5.147 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 1.3910

SAR(1 g) = 0.303 mW/g; SAR(10 g) = 0.110 mW/g

Maximum value of SAR (measured) = 0.710 mW/g



P256 802.11a_Front Face_1cm_ch140_Battery1_Cover1

DUT: 111221C21

Communication System: 802.11a; Frequency: 5700 MHz; Duty Cycle: 1:1

Medium: B5G_0107 Medium parameters used: $f = 5700$ MHz; $\sigma = 6.03$ mho/m; $\epsilon_r = 48.4$; $\rho = 1000$ kg/m³

Ambient Temperature : 21.2 °C ; Liquid Temperature : 21.3 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3650; ConvF(3.57, 3.57, 3.57); Calibrated: 2011/10/26
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn579; Calibrated: 2011/09/23
- Phantom: SAM Phantom_Left; Type: SAM V4.0; Serial: TP 1652
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Ch140/Area Scan (101x161x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.094 mW/g


Ch140/Zoom Scan (7x7x9)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2.5mm

Reference Value = 0.795 V/m; Power Drift = 0.17 dB

Peak SAR (extrapolated) = 0.135 W/kg

SAR(1 g) = 0.044 mW/g; SAR(10 g) = 0.018 mW/g

Maximum value of SAR (measured) = 0.078 mW/g



P257 802.11a_Back Face_1cm_ch140_Battery1_Cover1

DUT: 111221C21

Communication System: 802.11a; Frequency: 5700 MHz; Duty Cycle: 1:1

Medium: B5G_0107 Medium parameters used: $f = 5700$ MHz; $\sigma = 6.03$ mho/m; $\epsilon_r = 48.4$; $\rho = 1000$ kg/m³

Ambient Temperature : 21.5 °C ; Liquid Temperature : 21.3 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3650; ConvF(3.57, 3.57, 3.57); Calibrated: 2011/10/26
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn579; Calibrated: 2011/09/23
- Phantom: SAM Phantom_Left; Type: SAM V4.0; Serial: TP 1652
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Ch140/Area Scan (101x161x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.180 mW/g


Ch140/Zoom Scan (7x7x9)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2.5mm

Reference Value = 1.36 V/m; Power Drift = -0.143 dB

Peak SAR (extrapolated) = 0.635 W/kg

SAR(1 g) = 0.181 mW/g; SAR(10 g) = 0.064 mW/g

Maximum value of SAR (measured) = 0.338 mW/g



P258 802.11a_Left Side_1cm_ch140_Battery1_Cover1

DUT: 111221C21

Communication System: 802.11a; Frequency: 5700 MHz; Duty Cycle: 1:1

Medium: B5G_0107 Medium parameters used: $f = 5700$ MHz; $\sigma = 6.03$ mho/m; $\epsilon_r = 48.4$; $\rho = 1000$ kg/m³

Ambient Temperature : 21.6 °C ; Liquid Temperature : 21.3 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3650; ConvF(3.57, 3.57, 3.57); Calibrated: 2011/10/26
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn579; Calibrated: 2011/09/23
- Phantom: SAM Phantom_Left; Type: SAM V4.0; Serial: TP 1652
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Ch140/Area Scan (61x161x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.414 mW/g


Ch140/Zoom Scan (7x7x9)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2.5mm

Reference Value = 5.09 V/m; Power Drift = -0.118 dB

Peak SAR (extrapolated) = 0.868 W/kg


SAR(1 g) = 0.251 mW/g; SAR(10 g) = 0.088 mW/g

Maximum value of SAR (measured) = 0.468 mW/g



1g/10g Averaged SAR

SAR; Zoom Scan: Value Along Z, X=4, Y=4



P260 802.11a_Back Face_1cm_ch140_Battery1_Cover1_Earphone

DUT: 111221C21

Communication System: 802.11a; Frequency: 5700 MHz; Duty Cycle: 1:1

Medium: B5G_0107 Medium parameters used: $f = 5700$ MHz; $\sigma = 6.03$ mho/m; $\epsilon_r = 48.4$; $\rho = 1000$ kg/m³

Ambient Temperature : 21.5 °C ; Liquid Temperature : 21.3 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3650; ConvF(3.57, 3.57, 3.57); Calibrated: 2011/10/26
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn579; Calibrated: 2011/09/23
- Phantom: SAM Phantom_Left; Type: SAM V4.0; Serial: TP 1652
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Ch140/Area Scan (101x161x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.229 mW/g


Ch140/Zoom Scan (7x7x9)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2.5mm

Reference Value = 1.70 V/m; Power Drift = -0.15 dB

Peak SAR (extrapolated) = 0.704 W/kg

SAR(1 g) = 0.190 mW/g; SAR(10 g) = 0.064 mW/g

Maximum value of SAR (measured) = 0.488 mW/g



P259 802.11a_Left Side_Ch140_Battery2_Cover2

DUT: 111221C21

Communication System: WLAN 5G; Frequency: 5700 MHz; Duty Cycle: 1:1

Medium: H5G_0117 Medium parameters used: $f = 5700$ MHz; $\sigma = 5.135$ mho/m; $\epsilon_r = 36.25$; $\rho = 1000$ kg/m³

Ambient Temperature : 20.8 °C ; Liquid Temperature : 20.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3650; ConvF(4.42, 4.42, 4.42); Calibrated: 2011/10/26
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn579; Calibrated: 2011/09/23
- Phantom: SAM Phantom_Front; Type: SAM; Serial: TP-1485
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)

Ch140/Area Scan (51x81x1): Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.744 mW/g

Ch140/Zoom Scan (7x7x9)/Cube 1: Measurement grid: dx=4mm, dy=4mm, dz=2.5mm

Reference Value = 12.053 V/m; Power Drift = -0.19 dB

Peak SAR (extrapolated) = 0.9790

SAR(1 g) = 0.226 mW/g; SAR(10 g) = 0.095 mW/g

Maximum value of SAR (measured) = 0.497 mW/g


Ch140/Zoom Scan (7x7x9)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2.5mm

Reference Value = 12.053 V/m; Power Drift = -0.19 dB

Peak SAR (extrapolated) = 1.6470

SAR(1 g) = 0.120 mW/g; SAR(10 g) = 0.024 mW/g

Maximum value of SAR (measured) = 0.883 mW/g



P261 802.11a_Front Face_1cm_ch161_Battery1_Cover1

DUT: 111221C21

Communication System: 802.11a; Frequency: 5805 MHz; Duty Cycle: 1:1

Medium: B5G_0107 Medium parameters used: $f = 5805$ MHz; $\sigma = 6.22$ mho/m; $\epsilon_r = 48.3$; $\rho = 1000$ kg/m³

Ambient Temperature : 21.7 °C; Liquid Temperature : 21.3 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3650; ConvF(3.81, 3.81, 3.81); Calibrated: 2011/10/26
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn579; Calibrated: 2011/09/23
- Phantom: SAM Phantom_Left; Type: SAM V4.0; Serial: TP 1652
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Ch161/Area Scan (101x161x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.071 mW/g


Ch161/Zoom Scan (7x7x9)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2.5mm

Reference Value = 0.970 V/m; Power Drift = 0.167 dB

Peak SAR (extrapolated) = 0.209 W/kg

SAR(1 g) = 0.033 mW/g; SAR(10 g) = 0.013 mW/g

Maximum value of SAR (measured) = 0.073 mW/g



P262 802.11a_Back Face_1cm_ch161_Battery1_Cover1

DUT: 111221C21

Communication System: 802.11a; Frequency: 5805 MHz; Duty Cycle: 1:1

Medium: B5G_0107 Medium parameters used: $f = 5805$ MHz; $\sigma = 6.22$ mho/m; $\epsilon_r = 48.3$; $\rho = 1000$ kg/m³

Ambient Temperature : 21.6 °C ; Liquid Temperature : 21.3 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3650; ConvF(3.81, 3.81, 3.81); Calibrated: 2011/10/26
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn579; Calibrated: 2011/09/23
- Phantom: SAM Phantom_Left; Type: SAM V4.0; Serial: TP 1652
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Ch161/Area Scan (101x161x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.263 mW/g


Ch161/Zoom Scan (7x7x9)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2.5mm

Reference Value = 1.08 V/m; Power Drift = 0.13 dB

Peak SAR (extrapolated) = 0.618 W/kg

SAR(1 g) = 0.169 mW/g; SAR(10 g) = 0.058 mW/g

Maximum value of SAR (measured) = 0.322 mW/g



P263 802.11a_Left Side_1cm_ch161_Battery1_Cover1

DUT: 111221C21

Communication System: 802.11a; Frequency: 5700 MHz; Duty Cycle: 1:1

Medium: B5G_0107 Medium parameters used: $f = 5700$ MHz; $\sigma = 6.03$ mho/m; $\epsilon_r = 48.4$; $\rho = 1000$

kg/m³

Ambient Temperature : 21.2 °C ; Liquid Temperature : 21.3 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3650; ConvF(3.57, 3.57, 3.57); Calibrated: 2011/10/26
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn579; Calibrated: 2011/09/23
- Phantom: SAM Phantom_Left; Type: SAM V4.0; Serial: TP 1652
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Ch161/Area Scan (61x161x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.402 mW/g


Ch161/Zoom Scan (7x7x9)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2.5mm

Reference Value = 4.96 V/m; Power Drift = -0.104 dB

Peak SAR (extrapolated) = 0.902 W/kg


SAR(1 g) = 0.230 mW/g; SAR(10 g) = 0.078 mW/g

Maximum value of SAR (measured) = 0.467 mW/g



1g/10g Averaged SAR

SAR; Zoom Scan: Value Along Z, X=2, Y=3



P265 802.11a_Back Face_1cm_ch161_Battery1_Cover1_Earphone

DUT: 111221C21

Communication System: 802.11a; Frequency: 5805 MHz; Duty Cycle: 1:1

Medium: B5G_0107 Medium parameters used: $f = 5805$ MHz; $\sigma = 6.22$ mho/m; $\epsilon_r = 48.3$; $\rho = 1000$ kg/m³

Ambient Temperature : 21.3 °C ; Liquid Temperature : 21.3 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3650; ConvF(3.81, 3.81, 3.81); Calibrated: 2011/10/26
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn579; Calibrated: 2011/09/23
- Phantom: SAM Phantom_Left; Type: SAM V4.0; Serial: TP 1652
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Ch161/Area Scan (101x161x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.207 mW/g


Ch161/Zoom Scan (7x7x9)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2.5mm

Reference Value = 1.26 V/m; Power Drift = -0.141 dB

Peak SAR (extrapolated) = 0.593 W/kg

SAR(1 g) = 0.163 mW/g; SAR(10 g) = 0.054 mW/g

Maximum value of SAR (measured) = 0.322 mW/g



P264 802.11a_Left Side _Ch161_Battery2_Cover2

DUT: 111221C21

Communication System: WLAN 5G; Frequency: 5805 MHz; Duty Cycle: 1:1

Medium: H5G_0117 Medium parameters used: $f = 5805$ MHz; $\sigma = 5.205$ mho/m; $\epsilon_r = 36.167$; $\rho = 1000$ kg/m³

Ambient Temperature : 20.9 °C ; Liquid Temperature : 20.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3650; ConvF(4.3, 4.3, 4.3); Calibrated: 2011/10/26
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn579; Calibrated: 2011/09/23
- Phantom: SAM Phantom_Front; Type: SAM; Serial: TP-1485
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.6.4 (4989)

Ch161/Area Scan (51x81x1): Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.404 mW/g

Ch161/Zoom Scan (7x7x9)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2.5mm

Reference Value = 9.823 V/m; Power Drift = -0.195 dB

Peak SAR (extrapolated) = 0.7970

SAR(1 g) = 0.222 mW/g; SAR(10 g) = 0.084 mW/g

Maximum value of SAR (measured) = 0.432 mW/g

