



FCC RF Test Report

APPLICANT : HTC Corporation
EQUIPMENT : Smartphone
MODEL NAME : PK76130
FCC ID : NM8PK76130
STANDARD : FCC 47 CFR Part 2, 22(H), 24(E)
CLASSIFICATION : PCS Licensed Transmitter Held to Ear (PCE)
Tx/Rx FREQUENCY RANGE : GSM850 : 824.2 ~ 848.8 MHz /
869.2 ~ 893.8 MHz
GSM1900 : 1850.2 ~ 1909.8 MHz /
1930.2 ~ 1989.8 MHz
WCDMA Band V : 826.4 ~ 846.6 MHz /
871.4 ~ 891.6 MHz

MAX. ERP/EIRP POWER : Sample 1:
GSM850 (GSM) : 0.4943 W
GSM850 (EDGE 8) : 0.1858 W
GSM1900 (GSM) : 0.5333 W
GSM1900 (EDGE 8) : 0.3428 W
WCDMA Band V (RMC 12.2Kbps) : 0.0525 W
Sample 2:
GSM850 (GSM) : 0.4295 W
GSM1900 (EDGE 8) : 0.4295 W

The product was received on Jan. 21, 2012 and completely tested on Mar. 01, 2012. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI / TIA / EIA-603-C-2004 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by:

Jones Tsai / Manager



SPORTON INTERNATIONAL INC.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.



TABLE OF CONTENTS

REVISION HISTORY.....3

SUMMARY OF TEST RESULT4

1 GENERAL DESCRIPTION.....5

 1.1 Applicant.....5

 1.2 Manufacturer5

 1.3 Feature of Equipment Under Test.....5

 1.4 Emission Designator and Maximum ERP/EIRP Power6

 1.5 Testing Site6

 1.6 Applied Standards7

 1.7 Ancillary Equipment List.....7

2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST.....8

 2.1 Test Mode.....8

 2.2 Connection Diagram of Test System 10

3 TEST RESULT.....11

 3.1 Conducted Output Power Measurement..... 11

 3.2 Effective Radiated Power and Effective Isotropic Radiated Power Measurement 13

 3.3 Occupied Bandwidth Measurement 19

 3.4 Band Edge Measurement.....25

 3.5 Conducted Emission Measurement31

 3.6 Field Strength of Spurious Radiation Measurement 44

 3.7 Frequency Stability Measurement.....60

4 LIST OF MEASURING EQUIPMENT65

5 UNCERTAINTY OF EVALUATION.....66

APPENDIX A. SETUP PHOTOGRAPHS



SUMMARY OF TEST RESULT

Report Section	FCC Rule	IC Rule	Description	Limit	Result	Remark
3.1	§2.1046	N/A	Conducted Output Power	N/A	PASS	-
3.2	§22.913(a)(2)	RSS-132(4.4) SRSP-503(5.1.3)	Effective Radiated Power	< 7 Watts	PASS	-
3.2	§24.232(c)	RSS-133 (6.4) SRSP-510(5.1.2)	Equivalent Isotropic Radiated Power	< 2 Watts	PASS	-
3.3	§2.1049 §22.917(a) §24.238(a)	N/A	Occupied Bandwidth	N/A	PASS	-
3.4	§2.1051 §22.917(a) §24.238(a)	RSS-132 (4.5.1) RSS-133 (6.5.1)	Band Edge Measurement	< 43+10log ₁₀ (P[Watts])	PASS	-
3.5	§2.1051 §22.917(a) §24.238(a)	RSS-132 (4.5.1) RSS-133 (6.5.1)	Conducted Emission	< 43+10log ₁₀ (P[Watts])	PASS	-
3.6	§2.1053 §22.917(a) §24.238(a)	RSS-132 (4.5.1) RSS-133 (6.5.1)	Field Strength of Spurious Radiation	< 43+10log ₁₀ (P[Watts])	PASS	Under limit 11.09 dB at 2509.000 MHz
3.7	§2.1055 §22.355 §24.235	RSS-132(4.3) RSS-133(6.3)	Frequency Stability for Temperature & Voltage	< 2.5 ppm	PASS	-

1 General Description

1.1 Applicant

HTC Corporation

No. 23, Xinghua Rd., Taoyuan City, Taoyuan County 330, Taiwan

1.2 Manufacturer

HTC Corporation

No. 23, Xinghua Rd., Taoyuan City, Taoyuan County 330, Taiwan

1.3 Feature of Equipment Under Test

Product Feature & Specification	
Equipment	Smartphone
Model Name	PK76130
FCC ID	NM8PK76130
Sample 1	EUT with LCM 1, Camera 1, and Battery 1
Sample 2	EUT with LCM 2, Camera 2, and Battery 2
Tx Frequency	GSM850 : 824 MHz ~ 849 MHz GSM1900 : 1850 MHz ~ 1910 MHz WCDMA Band V : 824 MHz ~ 849 MHz
Rx Frequency	GSM850 : 869 MHz ~ 894 MHz GSM1900 : 1930 MHz ~ 1990 MHz WCDMA Band V : 869 MHz ~ 894 MHz
Maximum Output Power to Antenna	GSM850 : 33.09 dBm GSM1900 : 29.72 dBm WCDMA Band V : 23.17 dBm
Antenna Type	Fixed Internal Antenna
Type of Modulation	GSM: GMSK GPRS: GMSK EDGE: GMSK / 8PSK WCDMA: QPSK (Uplink) HSDPA: QPSK (Uplink) HSUPA: QPSK (Uplink)
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Emission Designator and Maximum ERP/EIRP Power

Sample 1:

FCC Rule	System	Type of Modulation	Emission Designator	Maximum ERP/EIRP
Part 22	GSM850 GSM	GMSK	246KGXW	0.4943 W
Part 22	GSM850 EDGE 8	GMSK / 8PSK	240KG7W	0.1858 W
Part 22	WCDMA Band V RMC 12.2Kbps	QPSK	4M14F9W	0.0525 W
Part 24	GSM1900 GSM	GMSK	244KGXW	0.5333 W
Part 24	GSM1900 EDGE 8	GMSK / 8PSK	240KG7W	0.3428 W

Sample 2:

FCC Rule	System	Type of Modulation	Maximum ERP/EIRP
Part 22	GSM850 GSM	GMSK	0.4295 W
Part 24	GSM1900 GPRS 8	GMSK	0.4295 W

1.5 Testing Site

Test Site	SPORTON INTERNATIONAL INC.		
Test Site Location	No. 52, Hwa Ya 1 st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL: +886-3-327-3456 FAX: +886-3-328-4978		
Test Site No.	Sporton Site No.		FCC/IC Registration No.
	TH02-HY	03CH05-HY	722060/4086B-1



1.6 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ Preliminary Guidance for Receiving Applications for Certification of 3G Device. May 9, 2006.
- ♦ FCC 47 CFR Part 2, 22(H), 24(E)
- ♦ ANSI / TIA / EIA-603-C-2004
- ♦ IC RSS-132 Issue 2
- ♦ IC RSS-133 Issue 5

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

1.7 Ancillary Equipment List

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU200	N/A	N/A	Unshielded, 1.8 m

2 Test Configuration of Equipment Under Test

2.1 Test Mode

During all testing, EUT is in link mode with base station emulator at maximum power level. The spurious emission measurements were carried out in semi-anechoic chamber with 3-meter test range, and EUT is rotated on three test planes to find out the worst emission.

Frequency range investigated for radiated emission is as follows:

1. 30 MHz to 9000 MHz for GSM850 and WCDMA Band V.
2. 30 MHz to 19000 MHz for GSM1900

Test Modes		
Band	Radiated TCs	Conducted TCs
GSM 850	<ul style="list-style-type: none"> ■ GSM Link for Sample 1 ■ EDGE 8 Link for Sample 1 ■ GSM Link for Sample 2 	<ul style="list-style-type: none"> ■ GSM Link ■ EDGE 8 Link
GSM 1900	<ul style="list-style-type: none"> ■ GSM Link for Sample 1 ■ EDGE 8 Link for Sample 1 ■ GSM Link for Sample 2 	<ul style="list-style-type: none"> ■ GSM Link ■ EDGE 8 Link
WCDMA Band V	<ul style="list-style-type: none"> ■ RMC 12.2Kbps Link for Sample 1 	<ul style="list-style-type: none"> ■ RMC 12.2Kbps Link

Note:

1. The maximum power levels are GSM mode for GMSK link, EDGE multi-slot class 8 mode for 8PSK link, RMC 12.2Kbps mode for WCDMA band V, only these modes were used for all tests.
2. Because there are individual antennas for each WWAN, WLAN, and Bluetooth, the co-location test modes are not required.
3. All the Radiation tests were performance with USB Cable 1, Adapter 1, and Earphone 2.




The conducted power tables are as follows:

Conducted Power (*Unit: dBm)						
Band	GSM850			GSM1900		
Channel	128	189	251	512	661	810
Frequency	824.2	836.4	848.8	1850.2	1880.0	1909.8
GSM	32.97	33.09	32.97	29.65	29.68	29.72
GPRS 8	33.01	33.07	33.04	29.56	29.55	29.64
GPRS 10	31.02	31.16	31.20	26.43	26.56	26.32
GPRS 12	28.18	28.33	28.37	24.36	24.66	24.45
EGPRS 8	26.35	26.37	26.36	25.16	25.11	25.00
EGPRS 10	25.17	25.23	25.31	23.92	23.80	23.54
EGPRS 12	24.72	24.79	24.90	22.18	22.13	22.15

Conducted Power (*Unit: dBm)			
Band	WCDMA Band V		
Channel	4132	4182	4233
Frequency	826.4	836.4	846.6
RMC 12.2K	22.81	23.04	23.17
HSDPA Subtest-1	21.69	22.01	22.17
HSDPA Subtest-2	21.70	21.96	22.09
HSDPA Subtest-3	21.21	21.45	21.70
HSDPA Subtest-4	21.27	21.50	21.66
HSUPA Subtest-1	21.40	21.80	21.82
HSUPA Subtest-2	20.61	20.94	21.30
HSUPA Subtest-3	20.83	21.30	21.43
HSUPA Subtest-4	20.73	21.06	21.40
HSUPA Subtest-5	21.79	21.93	22.19

2.2 Connection Diagram of Test System



3 Test Result

3.1 Conducted Output Power Measurement

3.1.1 Description of the Conducted Output Power Measurement

A base station simulator was used to establish communication with the EUT. Its parameters were set to transmit the maximum power on the EUT. The measured power in the radio frequency on the transmitter output terminals shall be reported.


3.1.2 Measuring Instruments

See list of measuring instruments of this test report.

3.1.3 Test Procedures

1. The transmitter output port was connected to base station.
2. Set EUT at maximum power through base station.
3. Select lowest, middle, and highest channels for each band and different modulation.

3.1.4 Test Setup



3.1.5 Test Result of Conducted Output Power

Cellular Band									
Modes	GSM850 (GSM)			GSM850 (EDGE 8)			WCDMA Band V (RMC 12.2Kbps)		
Channel	128 (Low)	189 (Mid)	251 (High)	128 (Low)	189 (Mid)	251 (High)	4132 (Low)	4182 (Mid)	4233 (High)
Frequency (MHz)	824.2	836.4	848.8	824.2	836.4	848.8	826.4	836.4	846.6
Conducted Power (dBm)	32.97	33.09	32.97	26.35	26.37	26.36	22.81	23.04	23.17
Conducted Power (Watts)	1.98	2.04	1.98	0.43	0.43	0.43	0.19	0.20	0.21

PCS Band						
Modes	GSM1900 (GSM)			GSM1900 (EDGE 8)		
Channel	512 (Low)	661 (Mid)	810 (High)	512 (Low)	661 (Mid)	810 (High)
Frequency (MHz)	1850.2	1880	1909.8	1850.2	1880	1909.8
Conducted Power (dBm)	29.65	29.68	29.72	25.16	25.11	25.00
Conducted Power (Watts)	0.92	0.93	0.94	0.33	0.32	0.32

3.2 Effective Radiated Power and Effective Isotropic Radiated Power Measurement

3.2.1 Description of the ERP/EIRP Measurement

ERP/EIRP is measured by substitution method according to ANSI / TIA / EIA-603-C-2004. The ERP of mobile transmitters must not exceed 7 Watts and the EIRP of mobile transmitters are limited to 2 Watts.

3.2.2 Measuring Instruments

See list of measuring instruments of this test report.

3.2.3 Test Procedures

1. The EUT was placed on a turntable with 1.0 meter height in a fully anechoic chamber.
2. The EUT was set at 1.2 meters from the receiving antenna, which was mounted on the antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest radiated power.
4. The height of the receiving antenna is adjusted to look for the maximum ERP/EIRP.
5. Taking the record of maximum ERP/EIRP.
6. A dipole antenna was substituted in place of the EUT and was driven by a signal generator.
7. The conducted power at the terminal of the dipole antenna is measured.
8. Repeat step 3 to step 5 to get the maximum ERP/EIRP of the substitution antenna.
9. $ERP/EIRP = P_s + E_t - E_s + G_s = P_s + R_t - R_s + G_s$

P_s (dBm) : Input power to substitution antenna.

G_s (dBi or dBd) : Substitution antenna Gain.

$E_t = R_t + AF$


$E_s = R_s + AF$

AF (dB/m) : Receive antenna factor

R_t : The highest received signal in spectrum analyzer for EUT.

R_s : The highest received signal in spectrum analyzer for substitution antenna.

3.2.4 Test Setup



3.2.5 Test Result of ERP

<Sample 1>

GSM850 (GSM) Radiated Power ERP				
Horizontal Polarization				
Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	ERP (dBm)	ERP (W)
824.2	-2.82	30.8	25.83	0.3828
836.4	-2.42	31.21	26.64	0.4613
848.8	-2.44	31.53	26.94	0.4943
Vertical Polarization				
Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	ERP (dBm)	ERP (W)
824.2	-12.33	32.84	18.36	0.0685
836.4	-11.12	32.85	19.58	0.0908
848.8	-11.97	34.11	19.99	0.0998

* ERP = LVL (dBm) + Correction Factor (dB) – 2.15

GSM850 (EDGE 8) Radiated Power ERP				
Horizontal Polarization				
Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	ERP (dBm)	ERP (W)
824.2	-6.80	30.8	21.85	0.1531
836.4	-6.53	31.21	22.53	0.1791
848.8	-6.69	31.53	22.69	0.1858
Vertical Polarization				
Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	ERP (dBm)	ERP (W)
824.2	-16.32	32.84	14.37	0.0274
836.4	-15.32	32.85	15.38	0.0345
848.8	-16.20	34.11	15.76	0.0377

* ERP = LVL (dBm) + Correction Factor (dB) – 2.15



WCDMA Band V (RMC 12.2Kbps) Radiated Power ERP				
Horizontal Polarization				
Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	ERP (dBm)	ERP (W)
826.40	-13.10	30.8	15.55	0.0359
836.40	-11.86	31.21	17.20	0.0525
846.60	-12.59	31.53	16.79	0.0478
Vertical Polarization				
Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	ERP (dBm)	ERP (W)
826.40	-22.34	32.84	8.35	0.0068
836.40	-20.53	32.85	10.17	0.0104
846.60	-21.10	34.11	10.86	0.0122

* ERP = LVL (dBm) + Correction Factor (dB) – 2.15

<Sample 2>

GSM850 (GSM) Radiated Power ERP				
Horizontal Polarization				
Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	ERP (dBm)	ERP (W)
824.2	-2.73	30.8	25.92	0.3908
836.4	-2.73	31.21	26.33	0.4295
848.8	-3.08	31.53	26.30	0.4266
Vertical Polarization				
Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	ERP (dBm)	ERP (W)
824.2	-12.69	32.84	18.00	0.0631
836.4	-11.58	32.85	19.12	0.0817
848.8	-12.02	34.11	19.94	0.0986

3.2.6 Test Result of EIRP

<Sample 1>

GSM1900 (GSM) Radiated Power EIRP				
Horizontal Polarization				
Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (W)
1850.2	-13.99	40.03	26.04	0.4018
1880.0	-14.03	39.62	25.59	0.3622
1909.8	-14.42	41.69	27.27	0.5333
Vertical Polarization				
Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (W)
1850.2	-21.78	44.51	22.73	0.1875
1880.0	-23.15	43.16	20.01	0.1002
1909.8	-22.95	43.98	21.03	0.1268

* EIRP = LVL (dBm) + Correction Factor (dB)

GSM1900 (EDGE 8) Radiated Power EIRP				
Horizontal Polarization				
Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (W)
1850.2	-15.33	40.03	24.70	0.2951
1880.0	-15.99	39.62	23.63	0.2307
1909.8	-16.34	41.69	25.35	0.3428
Vertical Polarization				
Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (W)
1850.2	-23.55	44.51	20.96	0.1247
1880.0	-24.38	43.16	18.78	0.0755
1909.8	-24.41	43.98	19.57	0.0906

* EIRP = LVL (dBm) + Correction Factor (dB)



<Sample 2>

GSM1900 (GSM) Radiated Power EIRP				
Horizontal Polarization				
Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (W)
1850.2	-13.70	40.03	26.33	0.4295
1880.0	-15.51	39.62	24.11	0.2576
1909.8	-16.30	41.69	25.39	0.3459
Vertical Polarization				
Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (W)
1850.2	-22.00	44.51	22.51	0.1782
1880.0	-22.64	43.16	20.52	0.1127
1909.8	-22.85	43.98	21.13	0.1297

3.3 Occupied Bandwidth Measurement

3.3.1 Description of Occupied Bandwidth Measurement

The emission bandwidth is defined as the width of the signal between two points, located at the 2 sides of the carrier frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.


3.3.2 Measuring Instruments

See list of measuring instruments of this test report.

3.3.3 Test Procedures

1. The EUT was connected to Spectrum Analyzer and Base Station via power divider.
2. The 99% and 26 dB occupied bandwidth (BW) of the middle channel for the highest RF powers were measured.

3.3.4 Test Setup






3.3.5 Test Result (Plots) of Occupied Bandwidth


Band :	GSM 850	Power Stage :	High
Test Mode :	GSM Link		

99% Occupied Bandwidth Plot on Channel 189



Date: 6.FEB.2012 10:57:17

26dB Bandwidth Plot on Channel 189




Date: 6.FEB.2012 10:55:57




Band :	GSM 1900	Power Stage :	High
Test Mode :	GSM Link		

99% Occupied Bandwidth Plot on Channel 661



Date: 6.FEB.2012 11:47:00

26dB Bandwidth Plot on Channel 661




Date: 6.FEB.2012 11:45:40




Band :	GSM 1900	Power Stage :	High
Test Mode :	EDGE 8 Link		

99% Occupied Bandwidth Plot on Channel 661



Date: 6.FEB.2012 13:50:56

26dB Bandwidth Plot on Channel 661




Date: 6.FEB.2012 13:49:36




Band :	WCDMA Band V	Power Stage :	High
Test Mode :	RMC 12.2Kbps Link		

99% Occupied Bandwidth Plot on Channel 4182



Date: 6.FEB.2012 14:07:57

26dB Bandwidth Plot on Channel 4182



Date: 6.FEB.2012 14:06:38

3.4 Band Edge Measurement

3.4.1 Description of Band Edge Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.


3.4.2 Measuring Instruments

See list of measuring instruments of this test report.

3.4.3 Test Procedures

1. The EUT was connected to Spectrum Analyzer and Base Station via power divider.
2. The band edges of low and high channels for the highest RF powers were measured. Setting RBW as roughly $BW/100$.

3.4.4 Test Setup






3.4.5 Test Result (Plots) of Conducted Band Edge


Band :	GSM850	Power Stage :	High
Test Mode :	GSM Link		

Lower Band Edge Plot on Channel 128



Date: 6.FEB.2012 10:59:11

Higher Band Edge Plot on Channel 251




Date: 6.FEB.2012 10:59:38




Band :	GSM850	Power Stage :	High
Test Mode :	EDGE 8 Link		

Lower Band Edge Plot on Channel 128



Date: 6.FEB.2012 11:22:13

Higher Band Edge Plot on Channel 251




Date: 6.FEB.2012 11:22:40




Band :	GSM1900	Power Stage :	High
Test Mode :	GSM Link		

Lower Band Edge Plot on Channel 512



Date: 6.FEB.2012 11:48:53

Higher Band Edge Plot on Channel 810




Date: 6.FEB.2012 11:49:20




Band :	GSM1900	Power Stage :	High
Test Mode :	EDGE 8 Link		

Lower Band Edge Plot on Channel 512



Date: 6.FEB.2012 13:52:49

Higher Band Edge Plot on Channel 810




Date: 6.FEB.2012 13:53:16




Band :	WCDMA Band V	Power Stage :	High
Test Mode :	RMC 12.2Kbps Link		

Lower Band Edge Plot on Channel 4132



Date: 6.FEB.2012 14:09:53

Higher Band Edge Plot on Channel 4233



Date: 6.FEB.2012 14:10:21

3.5 Conducted Emission Measurement

3.5.1 Description of Conducted Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.


3.5.2 Measuring Instruments

See list of measuring instruments of this test report.

3.5.3 Test Procedures

1. The EUT was connected to spectrum analyzer and base station via power divider.
2. The middle channel for the highest RF power within the transmitting frequency was measured.
3. The conducted spurious emission for the whole frequency range was taken.


3.5.4 Test Setup



3.5.5 Test Result (Plots) of Conducted Emission


Band :	GSM850	Channel :	CH189
Test Mode :	GSM Link		

Conducted Emission Plot between 30MHz ~ 1GHz



Date: 6.FEB.2012 10:53:32


Conducted Emission Plot between 1GHz ~ 3GHz



Date: 6.FEB.2012 10:53:52




Conducted Emission Plot between 3GHz ~ 7GHz



Date: 6.FEB.2012 10:54:05

Conducted Emission Plot between 7GHz ~ 9GHz




Date: 6.FEB.2012 10:54:17




Band :	GSM850	Channel :	CH189
Test Mode :	EDGE 8 Link		

Conducted Emission Plot between 30MHz ~ 1GHz



Date: 6.FEB.2012 11:15:45


Conducted Emission Plot between 1GHz ~ 3GHz



Date: 6.FEB.2012 11:16:02




Conducted Emission Plot between 3GHz ~ 7GHz



Date: 6.FEB.2012 11:16:14

Conducted Emission Plot between 7GHz ~ 9GHz




Date: 6.FEB.2012 11:16:27




Band :	GSM1900	Channel :	CH661
Test Mode :	GSM Link		

Conducted Emission Plot between 30MHz ~ 1GHz



Date: 6.FEB.2012 11:41:59


Conducted Emission Plot between 1GHz ~ 3GHz



Date: 1.MAR.2012 21:04:53




Conducted Emission Plot between 3GHz ~ 7GHz



Date: 6.FEB.2012 11:44:05


Conducted Emission Plot between 7GHz ~ 13.6GHz



Date: 6.FEB.2012 11:44:18



Conducted Emission Plot between 13.6GHz ~ 19.1GHz




Date: 6.FEB.2012 11:44:31




Band :	GSM1900	Channel :	CH661
Test Mode :	EDGE 8 Link		

Conducted Emission Plot between 30MHz ~ 1GHz



Date: 6.FEB.2012 11:56:16


Conducted Emission Plot between 1GHz ~ 3GHz



Date: 1.MAR.2012 21:00:29




Conducted Emission Plot between 3GHz ~ 7GHz



Date: 6.FEB.2012 11:59:58


Conducted Emission Plot between 7GHz ~ 13.6GHz



Date: 6.FEB.2012 12:00:11



Conducted Emission Plot between 13.6GHz ~ 19.1GHz




Date: 6.FEB.2012 12:00:24




Band :	WCDMA Band V	Channel :	CH4182
Test Mode :	RMC 12.2Kbps Link		

Conducted Emission Plot between 30MHz ~ 1GHz



Date: 6.FEB.2012 14:04:46


Conducted Emission Plot between 1GHz ~ 3GHz



Date: 6.FEB.2012 14:05:05




Conducted Emission Plot between 3GHz ~ 7GHz



Date: 6.FEB.2012 14:05:18

Conducted Emission Plot between 7GHz ~ 9GHz



Date: 6.FEB.2012 14:05:30



3.6 Field Strength of Spurious Radiation Measurement

3.6.1 Description of Field Strength of Spurious Radiated Measurement

The radiated spurious emission was measured by substitution method according to ANSI / TIA / EIA-603-C-2004. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.


3.6.2 Measuring Instruments

See list of measuring instruments of this test report.

3.6.3 Test Procedures

1. The EUT was placed on a rotatable wooden table with 0.8 meter about ground.
2. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest spurious emission.
4. The height of the receiving antenna is varied between one meter and four meters to search the maximum spurious emission for both horizontal and vertical polarizations.
5. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, Sweep = 500ms, Taking the record of maximum spurious emission.
6. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
7. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
8. Taking the record of output power at antenna port.
9. Repeat step 7 to step 8 for another polarization.
10. $EIRP (dBm) = S.G. Power - Tx Cable Loss + Tx Antenna Gain$
11. $ERP (dBm) = EIRP - 2.15$


3.6.4 Test Setup





3.6.5 Test Result of Field Strength of Spurious Radiated

Band :	GSM850	Temperature :	21~23°C
Test Mode :	GSM Link for Sample 1	Relative Humidity :	49~51%
Test Engineer :	David Yang	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH05-HY
 Condition : FCC PART22H/24E HF_EIRP_101221 HORIZONTAL
 Project : FG 212120-01

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1672	-46.63	-13	-33.63	-52.64	-47.82	2.15	5.49	H	Pass
2509	-41.39	-13	-28.39	-51.09	-43.28	2.38	6.41	H	Pass
3345	-47.22	-13	-34.22	-58.95	-50.55	2.86	8.34	H	Pass



Band :	GSM850	Temperature :	21~23°C
Test Mode :	GSM Link for Sample 1	Relative Humidity :	49~51%
Test Engineer :	David Yang	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH05-HY
 Condition : FCC PART22H/24E HF_EIRP_101221 VERTICAL
 Project : FG 212120-01

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1672	-48.02	-13	-35.02	-53.97	-49.21	2.15	5.49	V	Pass
2509	-42.02	-13	-29.02	-51.26	-43.91	2.38	6.41	V	Pass
3345	-49.67	-13	-36.67	-61.26	-53	2.86	8.34	V	Pass



Band :	GSM850	Temperature :	21~23°C
Test Mode :	EDGE 8 Link for Sample 1	Relative Humidity :	49~51%
Test Engineer :	David Yang	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH05-HY
 Condition : FCC PART22H/24E HF_EIRP_101221 HORIZONTAL
 Project : FG 212120-01

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1672	-50.39	-13	-37.39	-56.33	-51.58	2.15	5.49	H	Pass
2509	-43.08	-13	-30.08	-52.4	-44.97	2.38	6.41	H	Pass
3345	-50.52	-13	-37.52	-62.16	-53.85	2.86	8.34	H	Pass



Band :	GSM850	Temperature :	21~23°C
Test Mode :	EDGE 8 Link for Sample 1	Relative Humidity :	49~51%
Test Engineer :	David Yang	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH05-HY
 Condition : FCC PART22H/24E HF_EIRP_101221 VERTICAL
 Project : FG 212120-01

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1672	-52.26	-13	-39.26	-58.44	-53.45	2.15	5.49	V	Pass
2509	-44.42	-13	-31.42	-54.14	-46.31	2.38	6.41	V	Pass
3345	-52.78	-13	-39.78	-64.32	-56.11	2.86	8.34	V	Pass



Band :	GSM850	Temperature :	21~23°C
Test Mode :	GSM Link for Sample 2	Relative Humidity :	49~51%
Test Engineer :	David Yang	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH05-HY
 Condition : FCC PART22H/24E HF_EIRP_101221 HORIZONTAL
 Project : FG 212120-01

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1672	-50.16	-13	-37.16	-56.68	-51.35	2.15	5.49	H	Pass
2509	-24.09	-13	-11.09	-33.38	-25.98	2.38	6.41	H	Pass
3345	-49.42	-13	-36.42	-61.18	-52.75	2.86	8.34	H	Pass
4182	-42.18	-13	-29.18	-57.59	-46.12	3.26	9.35	H	Pass



Band :	GSM850	Temperature :	21~23°C
Test Mode :	GSM Link for Sample 2	Relative Humidity :	49~51%
Test Engineer :	David Yang	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH05-HY
 Condition : FCC PART22H/24E HF_EIRP_101221 VERTICAL
 Project : FG 212120-01

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1672	-48.36	-13	-35.36	-54.28	-49.55	2.15	5.49	V	Pass
2509	-26.08	-13	-13.08	-35.32	-27.97	2.38	6.41	V	Pass
3345	-49.31	-13	-36.31	-60.85	-52.64	2.86	8.34	V	Pass
4182	-49.05	-13	-36.05	-64.25	-52.99	3.26	9.35	V	Pass



Band :	GSM1900	Temperature :	21~23°C
Test Mode :	GSM Link for Sample 1	Relative Humidity :	51~53%
Test Engineer :	David Yang	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH05-HY
 Condition : FCC PART22H/24E HF_EIRP_101221 HORIZONTAL
 Project : FG 212120-01

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-46.99	-13	-33.99	-60.35	-53.12	2.9292	9.06	H	Pass
5636	-36.70	-13	-23.70	-55.01	-43.62	3.9072	10.83	H	Pass



Band :	GSM1900	Temperature :	21~23°C
Test Mode :	GSM Link for Sample 1	Relative Humidity :	51~53%
Test Engineer :	David Yang	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH05-HY
 Condition : FCC PART22H/24E HF_EIRP_101221 VERTICAL
 Project : FG 212120-01

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-46.28	-13	-33.28	-59.53	-52.41	2.9292	9.06	V	Pass
5636	-33.33	-13	-20.33	-52	-40.25	3.9072	10.83	V	Pass



Band :	GSM1900	Temperature :	21~23°C
Test Mode :	EDGE 8 Link for Sample 1	Relative Humidity :	51~53%
Test Engineer :	David Yang	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH05-HY
 Condition : FCC PART22H/24E HF_EIRP_101221 HORIZONTAL
 Project : FG 212120-01

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-47.71	-13	-34.71	-61.03	-53.84	2.9292	9.06	H	Pass
5636	-41.77	-13	-28.77	-60.31	-48.69	3.9072	10.83	H	Pass



Band :	GSM1900	Temperature :	21~23°C
Test Mode :	EDGE 8 Link for Sample 1	Relative Humidity :	51~53%
Test Engineer :	David Yang	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH05-HY
 Condition : FCC PART22H/24E HF_EIRP_101221 VERTICAL
 Project : FG 212120-01

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-47.54	-13	-34.54	-60.96	-53.67	2.9292	9.06	V	Pass
5636	-40.59	-13	-27.59	-59.14	-47.51	3.9072	10.83	V	Pass



Band :	GSM1900	Temperature :	21~23°C
Test Mode :	GSM Link for Sample 2	Relative Humidity :	51~53%
Test Engineer :	David Yang	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH05-HY
 Condition : FCC PART22H/24E HF_EIRP_101221 HORIZONTAL
 Project : FG 212120-01

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-37.32	-13	-24.32	-50.81	-43.45	2.9292	9.06	H	Pass
5636	-36.24	-13	-23.24	-55.19	-43.16	3.9072	10.83	H	Pass
7520	-44.39	-13	-31.39	-66.42	-52.41	4.5988	12.62	H	Pass



Band :	GSM1900	Temperature :	21~23°C
Test Mode :	GSM Link for Sample 2	Relative Humidity :	51~53%
Test Engineer :	David Yang	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH05-HY
 Condition : FCC PART22H/24E HF_EIRP_101221 VERTICAL
 Project : FG 212120-01

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-40.42	-13	-27.42	-53.87	-46.55	2.9292	9.06	V	Pass
5636	-31.58	-13	-18.58	-50.74	-38.5	3.9072	10.83	V	Pass
7520	-44.03	-13	-31.03	-65.91	-52.05	4.5988	12.62	V	Pass



Band :	WCDMA Band V	Temperature :	21~23°C
Test Mode :	RMC 12.2Kbps Link for Sample 1	Relative Humidity :	49~51%
Test Engineer :	David Yang	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH05-HY
 Condition : FCC PART22H/24E HF_EIRP_101221 HORIZONTAL
 Project : FG 212120-01

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1672	-55.13	-13	-42.13	-61.36	-56.32	2.15	5.49	H	Pass
2509	-53.39	-13	-40.39	-63.08	-55.28	2.38	6.41	H	Pass
3345	-53.04	-13	-40.04	-64.63	-56.37	2.86	8.34	H	Pass



Band :	WCDMA Band V	Temperature :	21~23°C
Test Mode :	RMC 12.2Kbps Link for Sample 1	Relative Humidity :	49~51%
Test Engineer :	David Yang	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Site : 03CH05-HY
 Condition : FCC PART22H/24E HF_EIRP_101221 VERTICAL
 Project : FG 212120-01

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1672	-55.02	-13	-42.02	-61.12	-56.21	2.15	5.49	V	Pass
2509	-54.06	-13	-41.06	-63.3	-55.95	2.38	6.41	V	Pass
3345	-53.12	-13	-40.12	-64.85	-56.45	2.86	8.34	V	Pass

3.7 Frequency Stability Measurement

3.7.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency.

3.7.2 Measuring Instruments

See list of measuring instruments of this test report.


3.7.3 Test Procedures for Temperature Variation

1. The EUT was set up in the thermal chamber and connected with the base station.
2. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized for three hours. Power was applied and the maximum change in frequency was recorded within one minute.
3. With power OFF, the temperature was raised in 10°C step up to 50°C . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.
4. If the EUT cannot be turned on at -30°C , the testing lowest temperature will be raised in 10°C step until the EUT can be turned on.

3.7.4 Test Procedures for Voltage Variation

1. The EUT was placed in a temperature chamber at $25\pm 5^{\circ}\text{C}$ and connected with the base station.
2. The power supply voltage to the EUT was varied from BEP to 115% of the nominal value measured at the input to the EUT.
3. The variation in frequency was measured for the worst case.

3.7.5 Test Setup





3.7.6 Test Result of Temperature Variation

Band :	GSM 850	Channel :	189
Limit (ppm) :	2.5		

Temperature (°C)	GSM		EDGE 8		Result
	Freq. Dev. (Hz)	Deviation (ppm)	Freq. Dev. (Hz)	Deviation (ppm)	
-30	N/A	N/A	N/A	N/A	PASS
-20	-31	-0.04	-41	-0.05	
-10	-26	-0.03	-26	-0.03	
0	-21	-0.02	-50	-0.06	
10	-25	-0.03	-31	-0.04	
20	27	0.03	-42	-0.05	
30	-21	-0.02	-35	-0.04	
40	24	0.03	-38	-0.04	
50	-23	-0.03	-45	-0.05	

Note: The manufacturer declared that the EUT could work properly between temperatures -20°C~50°C.

Band :	GSM 1900	Channel :	661
Limit (ppm) :	2.5		

Temperature (°C)	GSM		EDGE 8		Result
	Freq. Dev. (Hz)	Deviation (ppm)	Freq. Dev. (Hz)	Deviation (ppm)	
-30	N/A	N/A	N/A	N/A	PASS
-20	41	0.02	31	0.02	
-10	36	0.02	21	0.01	
0	21	0.01	29	0.02	
10	34	0.02	24	0.01	
20	29	0.02	30	0.02	
30	31	0.02	26	0.01	
40	24	0.01	27	0.01	
50	23	0.01	23	0.01	

Note: The manufacturer declared that the EUT could work properly between temperatures -20°C~50°C.



Band :	WCDMA Band V	Channel :	4182
Limit (ppm) :	2.5		

Temperature (°C)	RMC 12.2Kbps		Result
	Freq. Dev. (Hz)	Deviation (ppm)	
-30	N/A	N/A	PASS
-20	-21	-0.02	
-10	-14	-0.02	
0	-18	-0.02	
10	-23	-0.03	
20	-11	-0.01	
30	-16	-0.02	
40	-15	-0.02	
50	-13	-0.02	

Note: The manufacturer declared that the EUT could work properly between temperatures -20°C~50°C.

3.7.7 Test Result of Voltage Variation

Band & Channel	Mode	Voltage (Volt)	Freq. Dev. (Hz)	Deviation (ppm)	Limit (ppm)	Result
GSM 850 CH189	GSM	3.8	-32	-0.04	2.5	PASS
		BEP	-21	-0.02		
		4.2	-24	-0.03		
	EDGE 8	3.8	-52	-0.06		
		BEP	-48	-0.06		
		4.2	-43	-0.05		
GSM 1900 CH661	GSM	3.8	37	0.02		
		BEP	33	0.02		
		4.2	20	0.01		
	EDGE 8	3.8	45	0.02		
		BEP	55	0.03		
		4.2	21	0.01		
WCDMA Band V CH4182	RMC 12.2Kbps	3.8	-16	-0.02		
		BEP	-15	-0.02		
		4.2	16	0.02		

Note:

1. Normal Voltage = 3.8V.
2. Battery End Point (BEP) = 3.6 V.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
System Simulator	R&S	CMU200	117995	N/A	Jul. 28, 2011	Feb. 06, 2012 ~ Mar. 01, 2012	Jul. 27, 2012	Conducted (TH02-HY)
Spectrum Analyzer	R&S	FSP40	100055	9kHz~40GHz	Jun. 13, 2011	Feb. 06, 2012 ~ Mar. 01, 2012	Jun. 12, 2012	Conducted (TH02-HY)
Thermal Chamber	Ten Billion	TTH-D35P	TBN-930701	N/A	Jul. 27, 2011	Feb. 06, 2012 ~ Mar. 01, 2012	Jul. 26, 2012	Conducted (TH02-HY)
Spectrum Analyzer	R&S	FSP30	101352	9KHz~30GHz	Nov. 03, 2011	Feb. 18, 2012 ~ Feb. 25, 2012	Nov. 02, 2012	Radiation (03CH05-HY)
COM-POWER	Double Ridge Horn	AH-118	701030	1GHz~18GHz	N/A	Feb. 18, 2012 ~ Feb. 25, 2012	N/A	Radiation (03CH05-HY)
Bilog Antenna	SCHAFFNER	CBL6111C	2725	30MHz~1GHz	Oct. 22, 2011	Feb. 18, 2012 ~ Feb. 25, 2012	Oct. 21, 2012	Radiation (03CH05-HY)
Turn Table	HD	Deis HD 2000	420/611	0 - 360 degree	N/A	Feb. 18, 2012 ~ Feb. 25, 2012	N/A	Radiation (03CH05-HY)
Antenna Mast	HD	MA 240	240/666	1 m~4 m	N/A	Feb. 18, 2012 ~ Feb. 25, 2012	N/A	Radiation (03CH05-HY)
Horn Antenna	ESCO	3117	66584	1GHz~18GHz	Aug. 04, 2011	Feb. 18, 2012 ~ Feb. 25, 2012	Aug. 03, 2012	Radiation (03CH05-HY)
COM-POWER	COM-POWER	PA-103	161075	1KHz~1GHz	Mar. 29, 2011	Feb. 18, 2012 ~ Feb. 25, 2012	Mar. 28, 2012	Radiation (03CH05-HY)
Pre Amplifier	EMCI	EMC051845	SN980048	1GHz~18GHz	Jul. 19, 2011	Feb. 18, 2012 ~ Feb. 25, 2012	Jul. 18, 2012	Radiation (03CH05-HY)
Pre Amplifier	Agilent	8449B	3008A01917	1GHz~26.5GHz	Apr. 14, 2011	Feb. 18, 2012 ~ Feb. 25, 2012	Apr. 13, 2012	Radiation (03CH05-HY)
System Simulator	R&S	CMU200	117995	N/A	Jul. 28, 2011	Feb. 18, 2012 ~ Feb. 25, 2012	Jul. 27, 2012	Radiation (03CH05-HY)

5 Uncertainty of Evaluation

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Contribution	Uncertainty of X_i		$u(X_i)$
	dB	Probability Distribution	
Receiver Reading	0.41	Normal (k=2)	0.21
Antenna Factor Calibration	0.83	Normal (k=2)	0.42
Cable Loss Calibration	0.25	Normal (k=2)	0.13
Pre-Amplifier Gain Calibration	0.27	Normal (k=2)	0.14
RCV/SPA Specification	2.50	Rectangular	0.72
Antenna Factor Interpolation for Frequency	1.00	Rectangular	0.29
Site Imperfection	1.43	Rectangular	0.83
Mismatch	+0.39 / -0.41	U-Shape	0.28
Combined Standard Uncertainty $U_c(y)$	1.27		
Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	2.54		

Uncertainty of Radiated Emission Measurement (1 GHz ~ 40 GHz)

Contribution	Uncertainty of X_i		$u(X_i)$	C_i	$C_i * u(X_i)$
	dB	Probability Distribution			
Receiver Reading	± 0.10	Normal (k=2)	0.10	1	0.10
Antenna Factor Calibration	± 1.70	Normal (k=2)	0.85	1	0.85
Cable Loss Calibration	± 0.50	Normal (k=2)	0.25	1	0.25
Receiver Correction	± 2.00	Rectangular	1.15	1	1.15
Antenna Factor Directional	± 1.50	Rectangular	0.87	1	0.87
Site Imperfection	± 2.80	Triangular	1.14	1	1.14
Mismatch Receiver VSWR $\Gamma_1 = 0.197$ Antenna VSWR $\Gamma_2 = 0.194$ Uncertainty = $20\text{Log}(1-\Gamma_1*\Gamma_2)$	+0.34 / -0.35	U-Shape	0.244	1	0.244
Combined Standard Uncertainty $U_c(y)$	2.36				
Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	4.72				