



FCC RF Test Report

APPLICANT : HTC Corporation
EQUIPMENT : Smartphone
MODEL NAME : PL80130
FCC ID : NM8PL80130
STANDARD : FCC 47 CFR Part 2, 22(H), 24(E)
CLASSIFICATION : PCS Licensed Transmitter Held to Ear (PCE)

The product was received on Oct. 18, 2012 and completely tested on Nov. 22, 2012. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI / TIA / EIA-603-C-2004 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by:

Jones Tsai / Manager



SPORTON INTERNATIONAL INC.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.

SPORTON INTERNATIONAL INC.

TEL : 886-3-327-3456

FAX : 886-3-328-4978

FCC ID : NM8PL80130

Page Number : 1 of 134

Report Issued Date : Nov. 30, 2012

Report Version : Rev. 01



TABLE OF CONTENTS

REVISION HISTORY..... 3

SUMMARY OF TEST RESULT 4

1 GENERAL DESCRIPTION 5

 1.1 Applicant..... 5

 1.2 Manufacturer 5

 1.3 Feature of Equipment Under Test..... 5

 1.4 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator 6

 1.5 Testing Site..... 6

 1.6 Applied Standards 7

 1.7 Ancillary Equipment List 7

2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST 8

 2.1 Test Mode..... 8

 2.2 Connection Diagram of Test System 10

3 TEST RESULT 11

 3.1 Conducted Output Power Measurement..... 11

 3.2 Peak-to-Average Ratio 13

 3.3 Effective Radiated Power and Effective Isotropic Radiated Power Measurement 24

 3.4 99% Occupied Bandwidth and 26dB Bandwidth Measurement..... 30

 3.5 Band Edge Measurement..... 68

 3.6 Conducted Spurious Emission Measurement..... 81

 3.7 Field Strength of Spurious Radiation Measurement 109

 3.8 Frequency Stability Measurement..... 128

4 LIST OF MEASURING EQUIPMENT 133

5 UNCERTAINTY OF EVALUATION 134

APPENDIX A. SETUP PHOTOGRAPHS



SUMMARY OF TEST RESULT

Report Section	FCC Rule	IC Rule	Description	Limit	Result	Remark
3.1	§2.1046	N/A	Conducted Output Power	N/A	PASS	-
3.2	§24.232(d)	N/A	Peak-to-Average Ratio	< 13 dB	PASS	-
3.3	§22.913(a)(2)	RSS-132(4.4) SRSP-503(5.1.3)	Effective Radiated Power	< 7 Watts	PASS	-
3.3	§24.232(c)	RSS-133 (6.4) SRSP-510(5.1.2)	Equivalent Isotropic Radiated Power	< 2 Watts	PASS	-
3.4	§2.1049 §22.917(a) §24.238(a)	N/A	Occupied Bandwidth	N/A	PASS	-
3.5	§2.1051 §22.917(a) §24.238(a)	RSS-132 (4.5.1) RSS-133 (6.5.1)	Band Edge Measurement	< 43+10log ₁₀ (P[Watts])	PASS	-
3.6	§2.1051 §22.917(a) §24.238(a)	RSS-132 (4.5.1) RSS-133 (6.5.1)	Conducted Spurious Emission	< 43+10log ₁₀ (P[Watts])	PASS	-
3.7	§2.1053 §22.917(a) §24.238(a)	RSS-132 (4.5.1) RSS-133 (6.5.1)	Field Strength of Spurious Radiation	< 43+10log ₁₀ (P[Watts])	PASS	Under limit 14.95 dB at 1675.000 MHz
3.8	§2.1055 §22.355 §24.235	RSS-132(4.3) RSS-133(6.3)	Frequency Stability for Temperature & Voltage	< 2.5 ppm	PASS	-

1 General Description

1.1 Applicant

HTC Corporation

No. 23, Xinghua Rd., Taoyuan City, Taoyuan County 330, Taiwan

1.2 Manufacturer

HTC Corporation

No. 23, Xinghua Rd., Taoyuan City, Taoyuan County 330, Taiwan

1.3 Feature of Equipment Under Test

Product Feature	
Equipment	Smartphone
Model Name	PL80130
FCC ID	NM8PL80130
Sample 1	EUT with LCD Panel 1, Camera Front 1, and 2nd Camera 1
Sample 2	EUT with LCD Panel 2, Camera Front 2, and 2nd Camera 2
EUT supports Radios application	GSM / EGPRS / WCDMA / HSPA / WLAN 11abgn / Bluetooth / NFC
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

Product Specification subjective to this standard	
Tx Frequency	GSM850: 824.2 MHz ~ 848.8 MHz GSM1900: 1850.2 MHz ~ 1909.8MHz WCDMA Band V: 826.4 MHz ~ 846.6 MHz WCDMA Band II: 1852.4 MHz ~ 1907.6 MHz
Rx Frequency	GSM850: 869.2 MHz ~ 893.8 MHz GSM1900: 1930.2 MHz ~ 1989.8 MHz WCDMA Band V: 871.4 MHz ~ 891.6 MHz WCDMA Band II: 1932.4 MHz ~ 1987.6 MHz
Maximum Output Power to Antenna	GSM850 : 33.17 dBm GSM1900 : 30.60 dBm WCDMA Band V : 23.44 dBm WCDMA Band II : 23.45 dBm
Antenna Type	Fixed Internal Antenna
Type of Modulation	GSM: GMSK GPRS: GMSK EDGE: 8PSK WCDMA: QPSK (Uplink) HSDPA: QPSK (Uplink) HSUPA: QPSK (Uplink)

1.4 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator

FCC Rule	System	Type of Modulation	Maximum ERP/EIRP (W)	Frequency Tolerance (% , Hz, ppm)	Emission Designator
Part 22	GSM850 GSM	GMSK	0.3304	0.06 ppm	246KGXW
Part 22	GSM850 EDGE 8	8PSK	0.1710	0.08 ppm	250KG7W
Part 22	WCDMA Band V RMC 12.2Kbps	QPSK	0.0822	0.01 ppm	4M18F9W
Part 24	GSM1900 GSM	GMSK	0.4150	0.04 ppm	250KGXW
Part 24	GSM1900 EDGE 8	8PSK	0.1977	0.04 ppm	246KG7W
Part 24	WCDMA Band II RMC 12.2Kbps	QPSK	0.1026	0.01 ppm	4M18F9W

1.5 Testing Site

Test Site	SPORTON INTERNATIONAL INC.		
Test Site Location	No. 52, Hwa Ya 1 st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL: +886-3-327-3456 FAX: +886-3-328-4978		
Test Site No.	Sporton Site No.		FCC/IC Registration No.
	TH02-HY	03CH05-HY	722060/4086B-1



1.6 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- Preliminary Guidance for Receiving Applications for Certification of 3G Device. May 9, 2006.
- FCC 47 CFR Part 2, 22(H), 24(E)
- ANSI / TIA / EIA-603-C-2004
- FCC KDB 971168 D01 Power Meas. License Digital Systems v01
- IC RSS-132 Issue 2
- IC RSS-133 Issue 5

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

1.7 Ancillary Equipment List

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU200	N/A	N/A	Unshielded, 1.8 m

2 Test Configuration of Equipment Under Test

2.1 Test Mode

During all testing, EUT is in link mode with base station emulator at maximum power level. The spurious emission measurements were carried out in semi-anechoic chamber with 3-meter test range, and EUT is rotated on three test planes to find out the worst emission.

Frequency range investigated for radiated emission is as follows:

1. 30 MHz to 9000 MHz for GSM850 and WCDMA Band V.
2. 30 MHz to 19000 MHz for GSM1900 and WCDMA Band II.

Test Modes		
Band	Radiated TCs	Conducted TCs
GSM 850	<ul style="list-style-type: none"> ■ GSM Link for Sample 1 ■ EDGE 8 Link for Sample 1 	<ul style="list-style-type: none"> ■ GSM Link ■ EDGE 8 Link
GSM 1900	<ul style="list-style-type: none"> ■ GSM Link for Sample 1 ■ EDGE 8 Link for Sample 1 ■ GSM Link for Sample 2 	<ul style="list-style-type: none"> ■ GSM Link ■ EDGE 8 Link
WCDMA Band V	<ul style="list-style-type: none"> ■ RMC 12.2Kbps Link for Sample 1 ■ RMC 12.2Kbps Link for Sample 2 	<ul style="list-style-type: none"> ■ RMC 12.2Kbps Link
WCDMA Band II	<ul style="list-style-type: none"> ■ RMC 12.2Kbps Link for Sample 1 	<ul style="list-style-type: none"> ■ RMC 12.2Kbps Link

Note:

1. The maximum power levels are GSM mode for GMSK link, EDGE multi-slot class 8 mode for 8PSK link, RMC 12.2Kbps mode for WCDMA band V, and RMC 12.2Kbps mode for WCDMA band II, only these modes were used for all tests.
2. Because there are individual antennas for each WWAN, WLAN, and Bluetooth, the co-location test modes are not required.




The conducted power tables are as follows:

Conducted Power (*Unit: dBm)						
Band	GSM850			GSM1900		
Channel	128	189	251	512	661	810
Frequency	824.2	836.4	848.8	1850.2	1880.0	1909.8
GSM	33.17	33.16	33.11	30.60	30.54	30.40
GPRS 8	33.10	33.12	33.05	30.40	30.46	30.32
GPRS 10	30.43	30.32	30.31	28.54	28.48	28.34
GPRS 12	27.91	28.05	28.06	26.69	26.66	26.53
EGPRS 8	27.26	27.37	27.34	26.85	26.84	26.89
EGPRS 10	26.11	26.03	26.11	25.71	25.70	25.69
EGPRS 12	24.91	24.77	24.84	23.90	23.58	23.31

Conducted Power (*Unit: dBm)						
Band	WCDMA Band V			WCDMA Band II		
Channel	4132	4182	4233	9262	9400	9538
Frequency	826.4	836.4	846.6	1852.4	1880.0	1907.6
RMC 12.2K	23.30	23.02	23.44	23.36	23.45	23.31
HSDPA Subtest-1	22.52	22.17	22.60	22.36	22.43	22.32
HSDPA Subtest-2	22.26	22.14	22.17	22.39	22.38	22.30
HSDPA Subtest-3	21.80	21.66	21.70	21.94	21.95	21.89
HSDPA Subtest-4	21.90	21.71	22.05	21.92	21.94	21.90
HSUPA Subtest-1	22.04	21.94	22.23	22.35	22.45	22.42
HSUPA Subtest-2	20.94	20.67	21.39	21.18	21.29	21.33
HSUPA Subtest-3	21.15	20.87	21.38	20.93	20.97	20.85
HSUPA Subtest-4	21.81	21.41	21.51	21.53	21.55	21.42
HSUPA Subtest-5	22.27	22.02	22.48	22.46	22.60	22.50

2.2 Connection Diagram of Test System



3 Test Result

3.1 Conducted Output Power Measurement

3.1.1 Description of the Conducted Output Power Measurement

A base station simulator was used to establish communication with the EUT. Its parameters were set to transmit the maximum power on the EUT. The measured power in the radio frequency on the transmitter output terminals shall be reported.


3.1.2 Measuring Instruments

See list of measuring instruments of this test report.

3.1.3 Test Procedures

1. The transmitter output port was connected to base station.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set EUT at maximum power through base station.
4. Select lowest, middle, and highest channels for each band and different modulation.
5. Measure the maximum burst average power for GSM and maximum average power for other modulation signal.

3.1.4 Test Setup



3.1.5 Test Result of Conducted Output Power

Cellular Band									
Modes	GSM850 (GSM)			GSM850 (EDGE 8)			WCDMA Band V (RMC 12.2Kbps)		
Channel	128 (Low)	189 (Mid)	251 (High)	128 (Low)	189 (Mid)	251 (High)	4132 (Low)	4182 (Mid)	4233 (High)
Frequency (MHz)	824.2	836.4	848.8	824.2	836.4	848.8	826.4	836.4	846.6
Conducted Power (dBm)	33.17	33.16	33.11	27.26	27.37	27.34	23.30	23.02	23.44
Conducted Power (Watts)	2.07	2.07	2.05	0.53	0.55	0.54	0.21	0.20	0.22

PCS Band									
Modes	GSM1900 (GSM)			GSM1900 (EDGE 8)			WCDMA Band II (RMC 12.2Kbps)		
Channel	512 (Low)	661 (Mid)	810 (High)	512 (Low)	661 (Mid)	810 (High)	9262 (Low)	9400 (Mid)	9538 (High)
Frequency (MHz)	1850.2	1880	1909.8	1850.2	1880	1909.8	1852.4	1880	1907.6
Conducted Power (dBm)	30.60	30.54	30.40	26.85	26.84	26.89	23.36	23.45	23.31
Conducted Power (Watts)	1.15	1.13	1.10	0.48	0.48	0.49	0.22	0.22	0.21

Note: maximum burst average power for GSM, and maximum average power for WCDMA.

3.2 Peak-to-Average Ratio

3.2.1 Description of the PAR Measurement

The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.


3.2.2 Measuring Instruments

See list of measuring instruments of this test report.

3.2.3 Test Procedures

1. The EUT was connected to Spectrum Analyzer and Base Station via power divider.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. For GSM/EGPRS operating modes:
 - a. Set the RBW = 1MHz, VBW = 1MHz, Peak detector in spectrum analyzer.
 - b. Set EUT in maximum power output, and triggered the burst signal.
 - c. Measured respectively the Peak level and Mean level, and the deviation was recorded as Peak to Average Ratio.
4. For UMTS operating modes:
 - a. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
 - b. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.

3.2.4 Test Setup






3.2.5 Test Result of Peak-to-Average Ratio

PCS Band									
Modes	GSM1900 (GSM)			GSM1900 (EDGE 8)			WCDMA Band II (RMC 12.2Kbps)		
Channel	512 (Low)	661 (Mid)	810 (High)	512 (Low)	661 (Mid)	810 (High)	9262 (Low)	9400 (Mid)	9538 (High)
Frequency (MHz)	1850.2	1880	1909.8	1850.2	1880	1909.8	1852.4	1880	1907.6
Peak-to-Average Ratio (dB)	0.20	0.21	0.30	0.58	0.56	0.59	3.24	3.08	2.96

3.2.6 Test Result (Plots) of Peak-to-Average Ratio

Band :	GSM 1900	Test Mode :	GSM Link
--------	----------	-------------	----------

Peak-to-Average Ratio on Channel 512 (1850.2 MHz)



Date: 31.OCT.2012 18:56:03


Note:

The total loss is 18.4dB of the RF cable and attenuator, and has been compensated to the spectrum analyzer by setting into the amplitude level offset. That means the measured result shown on the spectrum analyzer has added the total loss and been compliance with the limit line.

Example: the Peak-to-Average Ratio test item, the peak point of fundamental signal is 30.78dBm, has added (offset) with the total loss = attenuator factor + cable loss = 18.4dB, where, cable loss = 8.4dB and 10dB attenuator, and then the Peak-to-Average Ratio is measured and compliance with the limit line. Hereafter, each plot of spectrum analyzer has been added the total loss respectively and to demonstrate in compliance with the limit line.



Peak-to-Average Ratio on Channel 810 (1909.8 MHz)



Date: 31.OCT.2012 18:58:59


Note:

The total loss is 18.4dB of the RF cable and attenuator, and has been compensated to the spectrum analyzer by setting into the amplitude level offset. That means the measured result shown on the spectrum analyzer has added the total loss and been compliance with the limit line.



Band :	GSM 1900	Test Mode :	EDGE 8 Link
--------	----------	-------------	-------------

Peak-to-Average Ratio on Channel 512 (1850.2 MHz)




Date: 31.OCT.2012 16:55:11

Note:

The total loss is 18.4dB of the RF cable and attenuator, and has been compensated to the spectrum analyzer by setting into the amplitude level offset. That means the measured result shown on the spectrum analyzer has added the total loss and been compliance with the limit line.



Peak-to-Average Ratio on Channel 661 (1880.0 MHz)




Date: 31.OCT.2012 16:55:57

Note:

The total loss is 18.4dB of the RF cable and attenuator, and has been compensated to the spectrum analyzer by setting into the amplitude level offset. That means the measured result shown on the spectrum analyzer has added the total loss and been compliance with the limit line.



Peak-to-Average Ratio on Channel 810 (1909.8 MHz)



Date: 31.OCT.2012 16:56:26


Note:

The total loss is 18.4dB of the RF cable and attenuator, and has been compensated to the spectrum analyzer by setting into the amplitude level offset. That means the measured result shown on the spectrum analyzer has added the total loss and been compliance with the limit line.



Band :	WCDMA Band II	Test Mode :	RMC 12.2Kbps Link
---------------	---------------	--------------------	-------------------

Peak-to-Average Ratio on Channel 9262 (1852.4 MHz)



Complementary Cumulative Distribution Function (100000 samples)

```

Trace 1
Mean    21.58 dBm
Peak    25.16 dBm
Crest   3.59 dB

10 %    1.76 dB
1 %     2.68 dB
.1 %    3.24 dB
.01 %   3.44 dB

```


Date: 31.OCT.2012 18:37:11

Note:

The total loss is 18.4dB of the RF cable and attenuator, and has been compensated to the spectrum analyzer by setting into the amplitude level offset. That means the measured result shown on the spectrum analyzer has added the total loss and been compliance with the limit line.



Peak-to-Average Ratio on Channel 9400 (1880.0 MHz)



Complementary Cumulative Distribution Function (100000 samples)

Trace 1

Mean	21.76 dBm
Peak	25.16 dBm
Crest	3.40 dB
10 %	1.68 dB
1 %	2.56 dB
.1 %	3.08 dB
.01 %	3.24 dB


Date: 31.OCT.2012 18:37:23

Note:

The total loss is 18.4dB of the RF cable and attenuator, and has been compensated to the spectrum analyzer by setting into the amplitude level offset. That means the measured result shown on the spectrum analyzer has added the total loss and been compliance with the limit line.



Peak-to-Average Ratio on Channel 9538 (1907.6 MHz)



Complementary Cumulative Distribution Function (100000 samples)

Trace 1	
Mean	21.59 dBm
Peak	24.88 dBm
Crest	3.29 dB
10 %	1.68 dB
1 %	2.48 dB
.1 %	2.96 dB
.01 %	3.16 dB

Date: 31.OCT.2012 18:37:39

Note:

The total loss is 18.4dB of the RF cable and attenuator, and has been compensated to the spectrum analyzer by setting into the amplitude level offset. That means the measured result shown on the spectrum analyzer has added the total loss and been compliance with the limit line.



3.3 Effective Radiated Power and Effective Isotropic Radiated Power Measurement

3.3.1 Description of the ERP/EIRP Measurement

The substitution method, in ANSI / TIA / EIA-603-C-2004, was used for ERP/EIRP measurement, and the spectrum analyzer configuration follows KDB 971168 D01 Power Meas. License Digital Systems v01. The ERP of mobile transmitters must not exceed 7 Watts and the EIRP of mobile transmitters are limited to 2 Watts.

3.3.2 Measuring Instruments

See list of measuring instruments of this test report.

3.3.3 Test Procedures

1. The EUT was placed on a turntable with 1.5 meter height in a fully anechoic chamber.
2. The EUT was set at 3 meters from the receiving antenna, which was mounted on the antenna tower.
3. GSM operating modes: Set RBW= 1MHz, VBW= 3MHz, RMS detector over burst;
UMTS operating modes: Set RBW= 100 KHz, VBW= 300 KHz, RMS detector over frame, and use channel power option with bandwidth=5MHz, per section 4.0 of KDB 971168 D01.
4. The table was rotated 360 degrees to determine the position of the highest radiated power.
5. The height of the receiving antenna is adjusted to look for the maximum ERP/EIRP.
6. Taking the record of maximum ERP/EIRP.
7. A dipole antenna was substituted in place of the EUT and was driven by a signal generator.
8. The conducted power at the terminal of the dipole antenna is measured.
9. Repeat step 3 to step 5 to get the maximum ERP/EIRP of the substitution antenna.
10. $ERP/EIRP = P_s + E_t - E_s + G_s = P_s + R_t - R_s + G_s$

P_s (dBm) : Input power to substitution antenna.

G_s (dBi or dBd) : Substitution antenna Gain.

$E_t = R_t + AF$


$E_s = R_s + AF$

AF (dB/m) : Receive antenna factor

R_t : The highest received signal in spectrum analyzer for EUT.

R_s : The highest received signal in spectrum analyzer for substitution antenna.

3.3.4 Test Setup





3.3.5 Test Result of ERP

<Sample 1>

GSM850 (GSM) Radiated Power ERP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
824.20	-22.52	-48.12	0.00	-1.08	24.52	0.2831
836.40	-23.59	-48.28	0.00	-0.93	23.76	0.2377
848.80	-22.40	-48.35	0.00	-0.76	25.19	0.3304
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
824.20	-36.03	-47.97	0.00	-1.08	10.86	0.0122
836.40	-39.44	-48.01	0.00	-0.93	7.64	0.0058
848.80	-38.30	-48.05	0.00	-0.76	8.99	0.0079

GSM850 (EDGE 8) Radiated Power ERP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
824.20	-25.83	-48.12	0.00	-1.08	21.21	0.1321
836.40	-25.71	-48.28	0.00	-0.93	21.64	0.1459
848.80	-25.26	-48.35	0.00	-0.76	22.33	0.1710
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
824.20	-39.68	-47.97	0.00	-1.08	7.21	0.0053
836.40	-39.75	-48.01	0.00	-0.93	7.33	0.0054
848.80	-39.91	-48.05	0.00	-0.76	7.38	0.0055



WCDMA Band V (RMC 12.2Kbps) Radiated Power ERP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
826.40	-29.51	-48.12	0.00	-1.08	17.53	0.0566
836.40	-29.45	-48.28	0.00	-0.93	17.90	0.0617
846.60	-28.44	-48.35	0.00	-0.76	19.15	0.0822
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
826.40	-42.62	-47.97	0.00	-1.08	4.27	0.0027
836.40	-43.42	-48.01	0.00	-0.93	3.66	0.0023
846.60	-42.79	-48.05	0.00	-0.76	4.50	0.0028

<Sample 2>

GSM850 (GSM) Radiated Power ERP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
824.20	-23.23	-48.12	0.00	-1.08	23.81	0.2404
836.40	-23.77	-48.28	0.00	-0.93	23.58	0.2280
848.80	-23.58	-48.35	0.00	-0.76	24.01	0.2518
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
824.20	-36.82	-47.97	0.00	-1.08	10.07	0.0102
836.40	-36.58	-48.01	0.00	-0.93	10.50	0.0112
848.80	-35.58	-48.05	0.00	-0.76	11.71	0.0148



3.3.6 Test Result of EIRP

<Sample 1>

GSM1900 (GSM) Radiated Power EIRP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-31.81	-51.88	0.00	1.96	22.03	0.1596
1880.00	-31.31	-52.99	0.00	2.00	23.68	0.2333
1909.80	-30.09	-54.28	0.00	1.98	26.17	0.4140
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-31.72	-52.13	0.00	1.96	22.37	0.1726
1880.00	-30.79	-53.17	0.00	2.00	24.38	0.2742
1909.80	-29.93	-54.13	0.00	1.98	26.18	0.4150

GSM1900 (EDGE 8) Radiated Power EIRP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-34.08	-51.88	0.00	1.96	19.76	0.0946
1880.00	-33.10	-52.99	0.00	2.00	21.89	0.1545
1909.80	-33.64	-54.28	0.00	1.98	22.62	0.1828
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-34.04	-52.13	0.00	1.96	20.05	0.1012
1880.00	-32.21	-53.17	0.00	2.00	22.96	0.1977
1909.80	-33.31	-54.13	0.00	1.98	22.80	0.1905



WCDMA Band II (RMC 12.2Kbps) Radiated Power EIRP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1852.40	-35.24	-51.88	0.00	1.96	18.60	0.0724
1880.00	-36.36	-52.99	0.00	2.00	18.63	0.0729
1907.60	-36.47	-54.28	0.00	1.98	19.79	0.0953
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1852.40	-35.17	-52.13	0.00	1.96	18.92	0.0780
1880.00	-36.32	-53.17	0.00	2.00	18.85	0.0767
1907.60	-36.00	-54.13	0.00	1.98	20.11	0.1026

<Sample 2>

GSM1900 (GSM) Radiated Power EIRP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-30.02	-51.88	0.00	1.96	23.82	0.2410
1880.00	-31.75	-52.99	0.00	2.00	23.24	0.2109
1909.80	-32.74	-54.28	0.00	1.98	23.52	0.2249
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-30.04	-52.13	0.00	1.96	24.05	0.2541
1880.00	-31.74	-53.17	0.00	2.00	23.43	0.2203
1909.80	-32.56	-54.13	0.00	1.98	23.55	0.2265

3.4 99% Occupied Bandwidth and 26dB Bandwidth Measurement

3.4.1 Description of 99% Occupied Bandwidth and 26dB Bandwidth Measurement

The 99% occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The emission bandwidth is defined as the width of the signal between two points, located at the 2 sides of the carrier frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.


3.4.2 Measuring Instruments

See list of measuring instruments of this test report.

3.4.3 Test Procedures

1. The EUT was connected to Spectrum Analyzer and Base Station via power divider.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. The 99% occupied bandwidth and 26 dB bandwidth of the middle channel for the highest RF powers were measured.

3.4.4 Test Setup



3.4.5 Test Result of Occupied Bandwidth and 26dB Bandwidth

Cellular Band						
Modes	GSM850 (GSM)			GSM850 (EDGE 8)		
Channel	128 (Low)	189 (Mid)	251 (High)	128 (Low)	189 (Mid)	251 (High)
Frequency (MHz)	824.2	836.4	848.8	824.2	836.4	848.8
99% OBW (KHz)	246.00	244.00	246.00	246.00	250.00	246.00
26dB BW (KHz)	314.00	316.00	316.00	304.00	298.00	306.00

PCS Band						
Modes	GSM1900 (GSM)			GSM1900 (EDGE 8)		
Channel	512 (Low)	661 (Mid)	810 (High)	512 (Low)	661 (Mid)	810 (High)
Frequency (MHz)	1850.2	1880	1909.8	1850.2	1880	1909.8
99% OBW (KHz)	246.00	248.00	250.00	242.00	246.00	242.00
26dB BW (KHz)	314.00	314.00	292.00	310.00	306.00	304.00

Cellular Band			
Modes	WCDMA Band V (RMC 12.2Kbps)		
Channel	4132 (Low)	4182 (Mid)	4233 (High)
Frequency (MHz)	826.4	836.4	846.6
99% OBW (MHz)	4.18	4.18	4.16
26dB BW (MHz)	4.68	4.70	4.68


PCS Band			
Modes	WCDMA Band II (RMC 12.2Kbps)		
Channel	9262 (Low)	9400 (Mid)	9538 (High)
Frequency (MHz)	1852.4	1880	1907.6
99% OBW (MHz)	4.14	4.16	4.18
26dB BW (MHz)	4.68	4.68	4.68



3.4.6 Test Result (Plots) of Occupied Bandwidth and 26dB Bandwidth

Band :	GSM 850	Test Mode :	GSM Link
--------	---------	-------------	----------

99% Occupied Bandwidth Plot on Channel 128 (824.2 MHz)




Date: 31.OCT.2012 14:38:50

Note:

The total loss is 16.3dB of the RF cable and attenuator, and has been compensated to the spectrum analyzer by setting into the amplitude level offset. That means the measured result shown on the spectrum analyzer has added the total loss and been compliance with the limit line.



26dB Bandwidth Plot on Channel 128 (824.2 MHz)




Date: 31.OCT.2012 14:37:31

Note:

The total loss is 16.3dB of the RF cable and attenuator, and has been compensated to the spectrum analyzer by setting into the amplitude level offset. That means the measured result shown on the spectrum analyzer has added the total loss and been compliance with the limit line.



26dB Bandwidth Plot on Channel 189 (836.4 MHz)




Date: 31.OCT.2012 14:37:57

Note:

The total loss is 16.3dB of the RF cable and attenuator, and has been compensated to the spectrum analyzer by setting into the amplitude level offset. That means the measured result shown on the spectrum analyzer has added the total loss and been compliance with the limit line.



99% Occupied Bandwidth Plot on Channel 251 (848.8 MHz)




Date: 31.OCT.2012 14:39:42

Note:

The total loss is 16.3dB of the RF cable and attenuator, and has been compensated to the spectrum analyzer by setting into the amplitude level offset. That means the measured result shown on the spectrum analyzer has added the total loss and been compliance with the limit line.



26dB Bandwidth Plot on Channel 251 (848.8 MHz)



Date: 31.OCT.2012 14:38:23


Note:

The total loss is 16.3dB of the RF cable and attenuator, and has been compensated to the spectrum analyzer by setting into the amplitude level offset. That means the measured result shown on the spectrum analyzer has added the total loss and been compliance with the limit line.



Band :	GSM 850	Test Mode :	EDGE 8 Link
--------	---------	-------------	-------------

99% Occupied Bandwidth Plot on Channel 128 (824.2 MHz)




Date: 31.OCT.2012 15:11:05

Note:

The total loss is 16.3dB of the RF cable and attenuator, and has been compensated to the spectrum analyzer by setting into the amplitude level offset. That means the measured result shown on the spectrum analyzer has added the total loss and been compliance with the limit line.



26dB Bandwidth Plot on Channel 128 (824.2 MHz)




Date: 31.OCT.2012 15:09:46

Note:

The total loss is 16.3dB of the RF cable and attenuator, and has been compensated to the spectrum analyzer by setting into the amplitude level offset. That means the measured result shown on the spectrum analyzer has added the total loss and been compliance with the limit line.



99% Occupied Bandwidth Plot on Channel 189 (836.4 MHz)




Date: 31.OCT.2012 15:11:31

Note:

The total loss is 16.3dB of the RF cable and attenuator, and has been compensated to the spectrum analyzer by setting into the amplitude level offset. That means the measured result shown on the spectrum analyzer has added the total loss and been compliance with the limit line.



26dB Bandwidth Plot on Channel 189 (836.4 MHz)




Date: 31.OCT.2012 15:10:12

Note:

The total loss is 16.3dB of the RF cable and attenuator, and has been compensated to the spectrum analyzer by setting into the amplitude level offset. That means the measured result shown on the spectrum analyzer has added the total loss and been compliance with the limit line.



99% Occupied Bandwidth Plot on Channel 251 (848.8 MHz)




Date: 31.OCT.2012 15:11:56

Note:

The total loss is 16.3dB of the RF cable and attenuator, and has been compensated to the spectrum analyzer by setting into the amplitude level offset. That means the measured result shown on the spectrum analyzer has added the total loss and been compliance with the limit line.



26dB Bandwidth Plot on Channel 251 (848.8 MHz)



Date: 31.OCT.2012 15:10:38


Note:

The total loss is 16.3dB of the RF cable and attenuator, and has been compensated to the spectrum analyzer by setting into the amplitude level offset. That means the measured result shown on the spectrum analyzer has added the total loss and been compliance with the limit line.



Band :	GSM 1900	Test Mode :	GSM Link
--------	----------	-------------	----------

99% Occupied Bandwidth Plot on Channel 512 (1850.2 MHz)




Date: 31.OCT.2012 16:30:10

Note:

The total loss is 18.4dB of the RF cable and attenuator, and has been compensated to the spectrum analyzer by setting into the amplitude level offset. That means the measured result shown on the spectrum analyzer has added the total loss and been compliance with the limit line.



26dB Bandwidth Plot on Channel 512 (1850.2 MHz)




Date: 31.OCT.2012 16:28:51

Note:

The total loss is 18.4dB of the RF cable and attenuator, and has been compensated to the spectrum analyzer by setting into the amplitude level offset. That means the measured result shown on the spectrum analyzer has added the total loss and been compliance with the limit line.



99% Occupied Bandwidth Plot on Channel 661 (1880.0 MHz)




Date: 31.OCT.2012 16:30:36

Note:

The total loss is 18.4dB of the RF cable and attenuator, and has been compensated to the spectrum analyzer by setting into the amplitude level offset. That means the measured result shown on the spectrum analyzer has added the total loss and been compliance with the limit line.



26dB Bandwidth Plot on Channel 661 (1880.0 MHz)




Date: 31.OCT.2012 16:29:17

Note:

The total loss is 18.4dB of the RF cable and attenuator, and has been compensated to the spectrum analyzer by setting into the amplitude level offset. That means the measured result shown on the spectrum analyzer has added the total loss and been compliance with the limit line.



99% Occupied Bandwidth Plot on Channel 810 (1909.8 MHz)




Date: 31.OCT.2012 16:31:02

Note:

The total loss is 18.4dB of the RF cable and attenuator, and has been compensated to the spectrum analyzer by setting into the amplitude level offset. That means the measured result shown on the spectrum analyzer has added the total loss and been compliance with the limit line.



26dB Bandwidth Plot on Channel 810 (1909.8 MHz)



Date: 31.OCT.2012 16:29:43


Note:

The total loss is 18.4dB of the RF cable and attenuator, and has been compensated to the spectrum analyzer by setting into the amplitude level offset. That means the measured result shown on the spectrum analyzer has added the total loss and been compliance with the limit line.



Band :	GSM 1900	Test Mode :	EDGE 8 Link
--------	----------	-------------	-------------

99% Occupied Bandwidth Plot on Channel 512 (1850.2 MHz)




Date: 31.OCT.2012 17:14:32

Note:

The total loss is 18.4dB of the RF cable and attenuator, and has been compensated to the spectrum analyzer by setting into the amplitude level offset. That means the measured result shown on the spectrum analyzer has added the total loss and been compliance with the limit line.



26dB Bandwidth Plot on Channel 512 (1850.2 MHz)




Date: 31.OCT.2012 17:06:58

Note:

The total loss is 18.4dB of the RF cable and attenuator, and has been compensated to the spectrum analyzer by setting into the amplitude level offset. That means the measured result shown on the spectrum analyzer has added the total loss and been compliance with the limit line.



99% Occupied Bandwidth Plot on Channel 661 (1880.0 MHz)




Date: 31.OCT.2012 17:14:58

Note:

The total loss is 18.4dB of the RF cable and attenuator, and has been compensated to the spectrum analyzer by setting into the amplitude level offset. That means the measured result shown on the spectrum analyzer has added the total loss and been compliance with the limit line.



26dB Bandwidth Plot on Channel 661 (1880.0 MHz)




Date: 31.OCT.2012 17:07:24

Note:

The total loss is 18.4dB of the RF cable and attenuator, and has been compensated to the spectrum analyzer by setting into the amplitude level offset. That means the measured result shown on the spectrum analyzer has added the total loss and been compliance with the limit line.



99% Occupied Bandwidth Plot on Channel 810 (1909.8 MHz)




Date: 31.OCT.2012 17:15:24

Note:

The total loss is 18.4dB of the RF cable and attenuator, and has been compensated to the spectrum analyzer by setting into the amplitude level offset. That means the measured result shown on the spectrum analyzer has added the total loss and been compliance with the limit line.



26dB Bandwidth Plot on Channel 810 (1909.8 MHz)



Date: 31.OCT.2012 17:07:50


Note:

The total loss is 18.4dB of the RF cable and attenuator, and has been compensated to the spectrum analyzer by setting into the amplitude level offset. That means the measured result shown on the spectrum analyzer has added the total loss and been compliance with the limit line.



Band :	WCDMA Band V	Test Mode :	RMC 12.2Kbps Link
---------------	--------------	--------------------	-------------------

99% Occupied Bandwidth Plot on Channel 4132 (826.4 MHz)




Date: 31.OCT.2012 18:28:49

Note:

The total loss is 16.3dB of the RF cable and attenuator, and has been compensated to the spectrum analyzer by setting into the amplitude level offset. That means the measured result shown on the spectrum analyzer has added the total loss and been compliance with the limit line.



26dB Bandwidth Plot on Channel 4132 (826.4 MHz)




Date: 31.OCT.2012 18:27:30

Note:

The total loss is 16.3dB of the RF cable and attenuator, and has been compensated to the spectrum analyzer by setting into the amplitude level offset. That means the measured result shown on the spectrum analyzer has added the total loss and been compliance with the limit line.



99% Occupied Bandwidth Plot on Channel 4182 (836.4 MHz)




Date: 31.OCT.2012 18:29:15

Note:

The total loss is 16.3dB of the RF cable and attenuator, and has been compensated to the spectrum analyzer by setting into the amplitude level offset. That means the measured result shown on the spectrum analyzer has added the total loss and been compliance with the limit line.



26dB Bandwidth Plot on Channel 4182 (836.4 MHz)




Date: 31.OCT.2012 18:27:56

Note:

The total loss is 16.3dB of the RF cable and attenuator, and has been compensated to the spectrum analyzer by setting into the amplitude level offset. That means the measured result shown on the spectrum analyzer has added the total loss and been compliance with the limit line.



99% Occupied Bandwidth Plot on Channel 4233 (846.6 MHz)




Date: 31.OCT.2012 18:29:41

Note:

The total loss is 16.3dB of the RF cable and attenuator, and has been compensated to the spectrum analyzer by setting into the amplitude level offset. That means the measured result shown on the spectrum analyzer has added the total loss and been compliance with the limit line.



26dB Bandwidth Plot on Channel 4233 (846.6 MHz)



Date: 31.OCT.2012 18:28:23


Note:

The total loss is 16.3dB of the RF cable and attenuator, and has been compensated to the spectrum analyzer by setting into the amplitude level offset. That means the measured result shown on the spectrum analyzer has added the total loss and been compliance with the limit line.



Band :	WCDMA Band II	Test Mode :	RMC 12.2Kbps Link
--------	---------------	-------------	-------------------

99% Occupied Bandwidth Plot on Channel 9262 (1852.4 MHz)




Date: 31.OCT.2012 18:42:59

Note:

The total loss is 18.4dB of the RF cable and attenuator, and has been compensated to the spectrum analyzer by setting into the amplitude level offset. That means the measured result shown on the spectrum analyzer has added the total loss and been compliance with the limit line.



26dB Bandwidth Plot on Channel 9262 (1852.4 MHz)




Date: 31.OCT.2012 18:49:38

Note:

The total loss is 18.4dB of the RF cable and attenuator, and has been compensated to the spectrum analyzer by setting into the amplitude level offset. That means the measured result shown on the spectrum analyzer has added the total loss and been compliance with the limit line.



99% Occupied Bandwidth Plot on Channel 9400 (1880.0 MHz)




Date: 31.OCT.2012 18:43:25

Note:

The total loss is 18.4dB of the RF cable and attenuator, and has been compensated to the spectrum analyzer by setting into the amplitude level offset. That means the measured result shown on the spectrum analyzer has added the total loss and been compliance with the limit line.



26dB Bandwidth Plot on Channel 9400 (1880.0 MHz)




Date: 31.OCT.2012 18:42:06

Note:

The total loss is 18.4dB of the RF cable and attenuator, and has been compensated to the spectrum analyzer by setting into the amplitude level offset. That means the measured result shown on the spectrum analyzer has added the total loss and been compliance with the limit line.



99% Occupied Bandwidth Plot on Channel 9538 (1907.6 MHz)




Date: 31.OCT.2012 18:43:51

Note:

The total loss is 18.4dB of the RF cable and attenuator, and has been compensated to the spectrum analyzer by setting into the amplitude level offset. That means the measured result shown on the spectrum analyzer has added the total loss and been compliance with the limit line.



26dB Bandwidth Plot on Channel 9538 (1907.6 MHz)



Date: 31.OCT.2012 18:42:32

Note:

The total loss is 18.4dB of the RF cable and attenuator, and has been compensated to the spectrum analyzer by setting into the amplitude level offset. That means the measured result shown on the spectrum analyzer has added the total loss and been compliance with the limit line.

3.5 Band Edge Measurement

3.5.1 Description of Band Edge Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.


3.5.2 Measuring Instruments

See list of measuring instruments of this test report.

3.5.3 Test Procedures

1. The EUT was connected to Spectrum Analyzer and Base Station via power divider.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. The band edges of low and high channels for the highest RF powers were measured. Setting RBW as roughly $BW/100$.


3.5.4 Test Setup



3.5.5 Test Result (Plots) of Conducted Band Edge

Band :	GSM850	Test Mode :	GSM Link
Correction Factor :	0.23dB	Maximum 26dB Bandwidth :	0.316MHz
Band Edge :	-16.98dBm	Measurement Value :	-17.21dBm

Lower Band Edge Plot on Channel 128 (824.2 MHz)




Date: 31.OCT.2012 14:41:08

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)
 For example, $-17.21\text{dBm} + 0.23\text{dB} = -16.98\text{dBm}$
3. The total loss is 16.3 dB of the RF cable and attenuator, and has been compensated to the spectrum analyzer by setting into the amplitude level offset. That means the measured result shown on the spectrum analyzer has added the total loss and been compliance with the limit line.

Band :	GSM850	Test Mode :	GSM Link
Correction Factor :	0.23dB	Maximum 26dB Bandwidth :	0.316MHz
Band Edge :	-16.99dBm	Measurement Value :	-17.22dBm

Higher Band Edge Plot on Channel 251 (848.8 MHz)




Date: 31.OCT.2012 14:41:34

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)
3. The total loss is 16.3 dB of the RF cable and attenuator, and has been compensated to the spectrum analyzer by setting into the amplitude level offset. That means the measured result shown on the spectrum analyzer has added the total loss and been compliance with the limit line.

Band :	GSM850	Test Mode :	EDGE 8 Link
Correction Factor :	0.09dB	Maximum 26dB Bandwidth :	0.306MHz
Band Edge :	-26.64dBm	Measurement Value :	-26.73dBm

Lower Band Edge Plot on Channel 128 (824.2 MHz)




Date: 31.OCT.2012 15:13:22

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)
3. The total loss is 16.3 dB of the RF cable and attenuator, and has been compensated to the spectrum analyzer by setting into the amplitude level offset. That means the measured result shown on the spectrum analyzer has added the total loss and been compliance with the limit line.

Band :	GSM850	Test Mode :	EDGE 8 Link
Correction Factor :	0.09dB	Maximum 26dB Bandwidth :	0.306MHz
Band Edge :	-26.58dBm	Measurement Value :	-26.67dBm

Higher Band Edge Plot on Channel 251 (848.8 MHz)




Date: 31.OCT.2012 15:13:49

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)
3. The total loss is 16.3 dB of the RF cable and attenuator, and has been compensated to the spectrum analyzer by setting into the amplitude level offset. That means the measured result shown on the spectrum analyzer has added the total loss and been compliance with the limit line.

Band :	GSM1900	Test Mode :	GSM Link
Correction Factor :	0.20dB	Maximum 26dB Bandwidth :	0.314MHz
Band Edge :	-22.55dBm	Measurement Value :	-22.75dBm

Lower Band Edge Plot on Channel 512 (1850.2 MHz)




Date: 31.OCT.2012 16:40:41

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)
3. The total loss is 18.4 dB of the RF cable and attenuator, and has been compensated to the spectrum analyzer by setting into the amplitude level offset. That means the measured result shown on the spectrum analyzer has added the total loss and been compliance with the limit line.

Band :	GSM1900	Test Mode :	GSM Link
Correction Factor :	0.20dB	Maximum 26dB Bandwidth :	0.314MHz
Band Edge :	-21.10dBm	Measurement Value :	-21.30dBm

Higher Band Edge Plot on Channel 810 (1909.8 MHz)




Date: 31.OCT.2012 16:41:07

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)
3. The total loss is 18.4 dB of the RF cable and attenuator, and has been compensated to the spectrum analyzer by setting into the amplitude level offset. That means the measured result shown on the spectrum analyzer has added the total loss and been compliance with the limit line.



Band :	GSM1900	Test Mode :	EDGE 8 Link
Correction Factor :	0.14dB	Maximum 26dB Bandwidth :	0.310MHz
Band Edge :	-27.81dBm	Measurement Value :	-27.95dBm

Lower Band Edge Plot on Channel 512 (1850.2 MHz)




Date: 31.OCT.2012 17:10:34

1. Correction Factor(dB)= 10log(1% Emission BW/RBW)
2. Band Edge= Measurement Value + Correction Factor(dB)
3. The total loss is 18.4 dB of the RF cable and attenuator, and has been compensated to the spectrum analyzer by setting into the amplitude level offset. That means the measured result shown on the spectrum analyzer has added the total loss and been compliance with the limit line.

Band :	GSM1900	Test Mode :	EDGE 8 Link
Correction Factor :	0.14dB	Maximum 26dB Bandwidth :	0.310MHz
Band Edge :	-28.68dBm	Measurement Value :	-28.82dBm

Higher Band Edge Plot on Channel 810 (1909.8 MHz)




Date: 31.OCT.2012 17:11:00

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)
3. The total loss is 18.4 dB of the RF cable and attenuator, and has been compensated to the spectrum analyzer by setting into the amplitude level offset. That means the measured result shown on the spectrum analyzer has added the total loss and been compliance with the limit line.



Band :	WCDMA Band V	Test Mode :	RMC 12.2Kbps Link
Correction Factor :	-3.28dB	Maximum 26dB Bandwidth :	4.70MHz
Band Edge :	-31.22dBm	Measurement Value :	-27.94dBm

Lower Band Edge Plot on Channel 4132 (826.4 MHz)




Date: 31.OCT.2012 18:31:09

1. Correction Factor(dB)= 10log(1% Emission BW/RBW)
2. Band Edge= Measurement Value + Correction Factor(dB)
3. The total loss is 16.3 dB of the RF cable and attenuator, and has been compensated to the spectrum analyzer by setting into the amplitude level offset. That means the measured result shown on the spectrum analyzer has added the total loss and been compliance with the limit line.



Band :	WCDMA Band V	Test Mode :	RMC 12.2Kbps Link
Correction Factor :	-3.28dB	Maximum 26dB Bandwidth :	4.70MHz
Band Edge :	-31.50dBm	Measurement Value :	-28.22dBm

Higher Band Edge Plot on Channel 4233 (846.6 MHz)




Date: 31.OCT.2012 18:31:35

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)
3. The total loss is 16.3 dB of the RF cable and attenuator, and has been compensated to the spectrum analyzer by setting into the amplitude level offset. That means the measured result shown on the spectrum analyzer has added the total loss and been compliance with the limit line.



Band :	WCDMA Band II	Test Mode :	RMC 12.2Kbps Link
Correction Factor :	-3.30dB	Maximum 26dB Bandwidth :	4.68MHz
Band Edge :	-31.95dBm	Measurement Value :	-28.65dBm

Lower Band Edge Plot on Channel 9262 (1852.4 MHz)




Date: 31.OCT.2012 18:47:23

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)
3. The total loss is 18.4 dB of the RF cable and attenuator, and has been compensated to the spectrum analyzer by setting into the amplitude level offset. That means the measured result shown on the spectrum analyzer has added the total loss and been compliance with the limit line.



Band :	WCDMA Band II	Test Mode :	RMC 12.2Kbps Link
Correction Factor :	-3.30dB	Maximum 26dB Bandwidth :	4.68MHz
Band Edge :	-30.39dBm	Measurement Value :	-27.09dBm

Higher Band Edge Plot on Channel 9538 (1907.6 MHz)



Date: 31.OCT.2012 18:47:49

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)
3. The total loss is 18.4 dB of the RF cable and attenuator, and has been compensated to the spectrum analyzer by setting into the amplitude level offset. That means the measured result shown on the spectrum analyzer has added the total loss and been compliance with the limit line.

3.6 Conducted Spurious Emission Measurement

3.6.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.


3.6.2 Measuring Instruments

See list of measuring instruments of this test report.

3.6.3 Test Procedures

1. The EUT was connected to spectrum analyzer and base station via power divider.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. The middle channel for the highest RF power within the transmitting frequency was measured.
4. The conducted spurious emission for the whole frequency range was taken.


3.6.4 Test Setup



3.6.5 Test Result (Plots) of Conducted Spurious Emission

Band :	GSM850	Channel :	CH189
Test Mode :	GSM Link	Frequency :	836.4 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz




Date: 31.OCT.2012 14:34:39

Note:

The total loss is 17.0dB of the RF cable and attenuator, and has been compensated to the spectrum analyzer by setting into the amplitude level offset. That means the measured result shown on the spectrum analyzer has added the total loss and been compliance with the limit line.



Conducted Spurious Emission Plot between 1GHz ~ 3GHz




Date: 31.OCT.2012 14:34:56

Note:

The total loss is 19.4dB of the RF cable and attenuator, and has been compensated to the spectrum analyzer by setting into the amplitude level offset. That means the measured result shown on the spectrum analyzer has added the total loss and been compliance with the limit line.



Conducted Spurious Emission Plot between 3GHz ~ 7GHz




Date: 31.OCT.2012 14:35:09

Note:

The total loss is 24.2dB of the RF cable and attenuator, and has been compensated to the spectrum analyzer by setting into the amplitude level offset. That means the measured result shown on the spectrum analyzer has added the total loss and been compliance with the limit line.



Conducted Spurious Emission Plot between 7GHz ~ 9GHz



Date: 31.OCT.2012 14:35:21


Note:

The total loss is 25.7dB of the RF cable and attenuator, and has been compensated to the spectrum analyzer by setting into the amplitude level offset. That means the measured result shown on the spectrum analyzer has added the total loss and been compliance with the limit line.



Band :	GSM850	Channel :	CH189
Test Mode :	EDGE 8 Link	Frequency :	836.4 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz




Date: 31.OCT.2012 14:58:51

Note:

The total loss is 17.0dB of the RF cable and attenuator, and has been compensated to the spectrum analyzer by setting into the amplitude level offset. That means the measured result shown on the spectrum analyzer has added the total loss and been compliance with the limit line.



Conducted Spurious Emission Plot between 1GHz ~ 3GHz




Date: 31.OCT.2012 14:59:10

Note:

The total loss is 19.4dB of the RF cable and attenuator, and has been compensated to the spectrum analyzer by setting into the amplitude level offset. That means the measured result shown on the spectrum analyzer has added the total loss and been compliance with the limit line.

Conducted Spurious Emission Plot between 3GHz ~ 7GHz




Date: 31.OCT.2012 14:59:23

Note:

The total loss is 24.2dB of the RF cable and attenuator, and has been compensated to the spectrum analyzer by setting into the amplitude level offset. That means the measured result shown on the spectrum analyzer has added the total loss and been compliance with the limit line.



Conducted Spurious Emission Plot between 7GHz ~ 9GHz



Date: 31.OCT.2012 14:59:35


Note:

The total loss is 25.7dB of the RF cable and attenuator, and has been compensated to the spectrum analyzer by setting into the amplitude level offset. That means the measured result shown on the spectrum analyzer has added the total loss and been compliance with the limit line.



Band :	GSM1900	Channel :	CH661
Test Mode :	GSM Link	Frequency :	1880.0 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz




Date: 31.OCT.2012 16:26:34

Note:

The total loss is 17.2dB of the RF cable and attenuator, and has been compensated to the spectrum analyzer by setting into the amplitude level offset. That means the measured result shown on the spectrum analyzer has added the total loss and been compliance with the limit line.



Conducted Spurious Emission Plot between 1GHz ~ 3GHz




Date: 31.OCT.2012 16:26:46

Note:

The total loss is 19.6dB of the RF cable and attenuator, and has been compensated to the spectrum analyzer by setting into the amplitude level offset. That means the measured result shown on the spectrum analyzer has added the total loss and been compliance with the limit line.



Conducted Spurious Emission Plot between 3GHz ~ 7GHz




Date: 31.OCT.2012 16:27:05

Note:

The total loss is 23.9dB of the RF cable and attenuator, and has been compensated to the spectrum analyzer by setting into the amplitude level offset. That means the measured result shown on the spectrum analyzer has added the total loss and been compliance with the limit line.



Conducted Spurious Emission Plot between 7GHz ~ 13.6GHz




Date: 31.OCT.2012 16:27:17

Note:

The total loss is 30.5dB of the RF cable and attenuator, and has been compensated to the spectrum analyzer by setting into the amplitude level offset. That means the measured result shown on the spectrum analyzer has added the total loss and been compliance with the limit line.



Conducted Spurious Emission Plot between 13.6GHz ~ 19.1GHz



Date: 31.OCT.2012 16:27:30


Note:

The total loss is 33.6dB of the RF cable and attenuator, and has been compensated to the spectrum analyzer by setting into the amplitude level offset. That means the measured result shown on the spectrum analyzer has added the total loss and been compliance with the limit line.



Band :	GSM1900	Channel :	CH661
Test Mode :	EDGE 8 Link	Frequency :	1880.0 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz




Date: 31.OCT.2012 17:03:54

Note:

The total loss is 17.2dB of the RF cable and attenuator, and has been compensated to the spectrum analyzer by setting into the amplitude level offset. That means the measured result shown on the spectrum analyzer has added the total loss and been compliance with the limit line.



Conducted Spurious Emission Plot between 1GHz ~ 3GHz




Date: 31.OCT.2012 17:04:07

Note:

The total loss is 19.6dB of the RF cable and attenuator, and has been compensated to the spectrum analyzer by setting into the amplitude level offset. That means the measured result shown on the spectrum analyzer has added the total loss and been compliance with the limit line.



Conducted Spurious Emission Plot between 3GHz ~ 7GHz




Date: 31.OCT.2012 17:04:24

Note:

The total loss is 23.9dB of the RF cable and attenuator, and has been compensated to the spectrum analyzer by setting into the amplitude level offset. That means the measured result shown on the spectrum analyzer has added the total loss and been compliance with the limit line.



Conducted Spurious Emission Plot between 7GHz ~ 13.6GHz




Date: 31.OCT.2012 17:04:36

Note:

The total loss is 30.5dB of the RF cable and attenuator, and has been compensated to the spectrum analyzer by setting into the amplitude level offset. That means the measured result shown on the spectrum analyzer has added the total loss and been compliance with the limit line.



Conducted Spurious Emission Plot between 13.6GHz ~ 19.1GHz



Date: 31.OCT.2012 17:04:49


Note:

The total loss is 33.6dB of the RF cable and attenuator, and has been compensated to the spectrum analyzer by setting into the amplitude level offset. That means the measured result shown on the spectrum analyzer has added the total loss and been compliance with the limit line.



Band :	WCDMA Band V	Channel :	CH4182
Test Mode :	RMC 12.2Kbps Link	Frequency :	836.4 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz




Date: 31.OCT.2012 18:25:25

Note:

The total loss is 17.0dB of the RF cable and attenuator, and has been compensated to the spectrum analyzer by setting into the amplitude level offset. That means the measured result shown on the spectrum analyzer has added the total loss and been compliance with the limit line.



Conducted Spurious Emission Plot between 1GHz ~ 3GHz




Date: 31.OCT.2012 18:25:44

Note:

The total loss is 19.4dB of the RF cable and attenuator, and has been compensated to the spectrum analyzer by setting into the amplitude level offset. That means the measured result shown on the spectrum analyzer has added the total loss and been compliance with the limit line.



Conducted Spurious Emission Plot between 3GHz ~ 7GHz




Date: 31.OCT.2012 18:25:56

Note:

The total loss is 24.2dB of the RF cable and attenuator, and has been compensated to the spectrum analyzer by setting into the amplitude level offset. That means the measured result shown on the spectrum analyzer has added the total loss and been compliance with the limit line.



Conducted Spurious Emission Plot between 7GHz ~ 9GHz



Date: 31.OCT.2012 18:26:09


Note:

The total loss is 25.7dB of the RF cable and attenuator, and has been compensated to the spectrum analyzer by setting into the amplitude level offset. That means the measured result shown on the spectrum analyzer has added the total loss and been compliance with the limit line.



Band :	WCDMA Band II	Channel :	CH9400
Test Mode :	RMC 12.2Kbps Link	Frequency :	1880.0 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz




Date: 31.OCT.2012 18:40:06

Note:

The total loss is 17.2dB of the RF cable and attenuator, and has been compensated to the spectrum analyzer by setting into the amplitude level offset. That means the measured result shown on the spectrum analyzer has added the total loss and been compliance with the limit line.



Conducted Spurious Emission Plot between 1GHz ~ 3GHz




Date: 31.OCT.2012 18:40:18

Note:

The total loss is 19.6dB of the RF cable and attenuator, and has been compensated to the spectrum analyzer by setting into the amplitude level offset. That means the measured result shown on the spectrum analyzer has added the total loss and been compliance with the limit line.



Conducted Spurious Emission Plot between 3GHz ~ 7GHz




Date: 31.OCT.2012 18:40:34

Note:

The total loss is 23.9dB of the RF cable and attenuator, and has been compensated to the spectrum analyzer by setting into the amplitude level offset. That means the measured result shown on the spectrum analyzer has added the total loss and been compliance with the limit line.



Conducted Spurious Emission Plot between 7GHz ~ 13.6GHz




Date: 31.OCT.2012 18:40:46

Note:

The total loss is 30.5dB of the RF cable and attenuator, and has been compensated to the spectrum analyzer by setting into the amplitude level offset. That means the measured result shown on the spectrum analyzer has added the total loss and been compliance with the limit line.



Conducted Spurious Emission Plot between 13.6GHz ~ 19.1GHz



Date: 31.OCT.2012 18:40:59

Note:

The total loss is 33.6dB of the RF cable and attenuator, and has been compensated to the spectrum analyzer by setting into the amplitude level offset. That means the measured result shown on the spectrum analyzer has added the total loss and been compliance with the limit line.



3.7 Field Strength of Spurious Radiation Measurement

3.7.1 Description of Field Strength of Spurious Radiated Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

3.7.2 Measuring Instruments


See list of measuring instruments of this test report.

3.7.3 Test Procedures


1. The EUT was placed on a rotatable wooden table with 0.8 meter above ground.
2. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest spurious emission.
4. The height of the receiving antenna is varied between one meter and four meters to search the maximum spurious emission for both horizontal and vertical polarizations.
5. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
6. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
7. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
8. Taking the record of output power at antenna port.
9. Repeat step 7 to step 8 for another polarization.
10. $EIRP \text{ (dBm)} = S.G. \text{ Power} - Tx \text{ Cable Loss} + Tx \text{ Antenna Gain}$
11. $ERP \text{ (dBm)} = EIRP - 2.15$

3.7.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz




3.7.5 Test Results of Radiated Emissions (9 KHz ~ 30 MHz)

The low frequency, which started from 9 KHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.



3.7.6 Test Result of Field Strength of Spurious Radiated


Band :	GSM850	Temperature :	24~26°C
Test Mode :	GSM Link for Sample 1	Relative Humidity :	52~54%
Test Engineer :	David Yang	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1672	-40.74	-13	-27.74	-46.63	-42.5	1.35	5.25	H	Pass
2509	-48.62	-13	-35.62	-57.86	-51	1.58	6.11	H	Pass
3346	-53.15	-13	-40.15	-64.66	-57	1.94	7.94	H	Pass




Band :	GSM850	Temperature :	24~26°C
Test Mode :	GSM Link for Sample 1	Relative Humidity :	52~54%
Test Engineer :	David Yang	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1672	-39.04	-13	-26.04	-45.02	-40.8	1.35	5.25	V	Pass
2509	-50.62	-13	-37.62	-59.91	-53	1.58	6.11	V	Pass
3345	-53.15	-13	-40.15	-64.71	-57	1.94	7.94	V	Pass




Band :	GSM850	Temperature :	24~26°C
Test Mode :	EDGE 8 Link for Sample 1	Relative Humidity :	52~54%
Test Engineer :	David Yang	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1672	-46.24	-13	-33.24	-52.23	-48	1.35	5.25	H	Pass
2509	-52.72	-13	-39.72	-62.02	-55.1	1.58	6.11	H	Pass
3345	-52.85	-13	-39.85	-64.44	-56.7	1.94	7.94	H	Pass




Band :	GSM850	Temperature :	24~26°C
Test Mode :	EDGE 8 Link for Sample 1	Relative Humidity :	52~54%
Test Engineer :	David Yang	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1672	-43.74	-13	-30.74	-49.67	-45.5	1.35	5.25	V	Pass
2509	-54.42	-13	-41.42	-63.76	-56.8	1.58	6.11	V	Pass
3345	-53.65	-13	-40.65	-65.24	-57.5	1.94	7.94	V	Pass




Band :	GSM1900	Temperature :	24~26°C
Test Mode :	GSM Link for Sample 1	Relative Humidity :	52~54%
Test Engineer :	David Yang	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-51.79	-13	-38.79	-65.25	-58.5	2.00	8.71	H	Pass
5640	-48.16	-13	-35.16	-67.04	-56.8	2.13	10.77	H	Pass
11280	-36.78	-13	-23.78	-63.89	-47.5	2.64	13.36	H	Pass




Band :	GSM1900	Temperature :	24~26°C
Test Mode :	GSM Link for Sample 1	Relative Humidity :	52~54%
Test Engineer :	David Yang	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-51.69	-13	-38.69	-65.18	-58.4	2.00	8.71	V	Pass
5640	-48.86	-13	-35.86	-67.76	-57.5	2.13	10.77	V	Pass
11280	-37.78	-13	-24.78	-64.93	-48.5	2.64	13.36	V	Pass




Band :	GSM1900	Temperature :	24~26°C
Test Mode :	EDGE 8 Link for Sample 1	Relative Humidity :	52~54%
Test Engineer :	David Yang	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-51.89	-13	-38.89	-65.37	-58.6	2.00	8.71	H	Pass
5640	-48.36	-13	-35.36	-67.22	-57	2.13	10.77	H	Pass
11280	-38.78	-13	-25.78	-65.78	-49.5	2.64	13.36	H	Pass




Band :	GSM1900	Temperature :	24~26°C
Test Mode :	EDGE 8 Link for Sample 1	Relative Humidity :	52~54%
Test Engineer :	David Yang	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-50.89	-13	-37.89	-64.4	-57.6	2.00	8.71	V	Pass
5640	-47.86	-13	-34.86	-66.73	-56.5	2.13	10.77	V	Pass
11280	-38.48	-13	-25.48	-65.49	-49.2	2.64	13.36	V	Pass




Band :	GSM1900	Temperature :	24~26°C
Test Mode :	GSM Link for Sample 2	Relative Humidity :	52~54%
Test Engineer :	David Yang	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-50.11	-13	-37.11	-65.11	-56.82	2.00	8.71	H	Pass
5640	-46.65	-13	-33.65	-65.96	-55.29	2.13	10.77	H	Pass
7524	-43.87	-13	-30.87	-65.89	-53.41	2.68	12.22	H	Pass




Band :	GSM1900	Temperature :	24~26°C
Test Mode :	GSM Link for Sample 2	Relative Humidity :	52~54%
Test Engineer :	David Yang	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-50.03	-13	-37.03	-64.56	-56.74	2.00	8.71	V	Pass
5640	-46.02	-13	-33.02	-66.7	-54.66	2.13	10.77	V	Pass
7520	-43.25	-13	-30.25	-65.86	-52.79	2.68	12.22	V	Pass




Band :	WCDMA Band V	Temperature :	24~26°C
Test Mode :	RMC 12.2Kbps Link for Sample 1	Relative Humidity :	52~54%
Test Engineer :	David Yang	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1675	-32.34	-13	-19.34	-38.36	-34.1	1.35	5.25	H	Pass
2512	-47.32	-13	-34.32	-56.65	-49.7	1.58	6.11	H	Pass
3346	-48.25	-13	-35.25	-59.74	-52.1	1.94	7.94	H	Pass
4815	-48.86	-13	-35.86	-63.15	-53.9	1.96	9.15	H	Pass




Band :	WCDMA Band V	Temperature :	24~26°C
Test Mode :	RMC 12.2Kbps Link for Sample 1	Relative Humidity :	52~54%
Test Engineer :	David Yang	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1675	-29.74	-13	-16.74	-35.78	-31.5	1.35	5.25	V	Pass
2509	-49.52	-13	-36.52	-58.83	-51.9	1.58	6.11	V	Pass
3346	-48.75	-13	-35.75	-60.28	-52.6	1.94	7.94	V	Pass
4185	-45.56	-13	-32.56	-60.78	-50.6	1.96	9.15	V	Pass




Band :	WCDMA Band V	Temperature :	24~26°C
Test Mode :	RMC 12.2Kbps Link for Sample 2	Relative Humidity :	52~54%
Test Engineer :	David Yang	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1675	-30.67	-13	-17.67	-36.81	-32.43	1.35	5.25	H	Pass
2512	-46.74	-13	-33.74	-56.5	-49.12	1.58	6.11	H	Pass
3352	-46.63	-13	-33.63	-58.76	-50.48	1.94	7.94	H	Pass
4180	-41.62	-13	-28.62	-58.16	-46.66	1.96	9.15	H	Pass




Band :	WCDMA Band V	Temperature :	24~26°C
Test Mode :	RMC 12.2Kbps Link for Sample 2	Relative Humidity :	52~54%
Test Engineer :	David Yang	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1675	-27.95	-13	-14.95	-34.9	-29.71	1.35	5.25	V	Pass
2509	-48.45	-13	-35.45	-58.48	-50.83	1.58	6.11	V	Pass
3352	-48.94	-13	-35.94	-60.65	-52.79	1.94	7.94	V	Pass
4180	-42.23	-13	-29.23	-59.07	-47.27	1.96	9.15	V	Pass




Band :	WCDMA Band II	Temperature :	24~26°C
Test Mode :	RMC 12.2Kbps Link	Relative Humidity :	52~54%
Test Engineer :	David Yang	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-51.49	-13	-38.49	-64.92	-58.2	2.00	8.71	H	Pass
5640	-48.26	-13	-35.26	-67.12	-56.9	2.13	10.77	H	Pass
7520	-45.36	-13	-32.36	-67.3	-54.9	2.68	12.22	H	Pass



Band :	WCDMA Band II	Temperature :	24~26°C
Test Mode :	RMC 12.2Kbps Link	Relative Humidity :	52~54%
Test Engineer :	David Yang	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-51.79	-13	-38.79	-65.26	-58.5	2.00	8.71	V	Pass
5640	-47.66	-13	-34.66	-66.56	-56.3	2.13	10.77	V	Pass
7520	-45.36	-13	-32.36	-67.24	-54.9	2.68	12.22	V	Pass

3.8 Frequency Stability Measurement

3.8.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency.

3.8.2 Measuring Instruments

See list of measuring instruments of this test report.


3.8.3 Test Procedures for Temperature Variation

1. The EUT was set up in the thermal chamber and connected with the base station.
2. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
3. With power OFF, the temperature was raised in 10°C step up to 50°C . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.
4. If the EUT cannot be turned on at -30°C , the testing lowest temperature will be raised in 10°C step until the EUT can be turned on.

3.8.4 Test Procedures for Voltage Variation

1. The EUT was placed in a temperature chamber at $25\pm 5^{\circ}\text{C}$ and connected with the base station.
2. The power supply voltage to the EUT was varied from BEP to 115% of the nominal value measured at the input to the EUT.
3. The variation in frequency was measured for the worst case.

3.8.5 Test Setup





3.8.6 Test Result of Temperature Variation

Band :	GSM 850	Channel :	189
Limit (ppm) :	2.5	Frequency :	836.4 MHz

Temperature (°C)	GSM		EDGE 8		Result
	Freq. Dev. (Hz)	Deviation (ppm)	Freq. Dev. (Hz)	Deviation (ppm)	
-30	21	0.02	-62	-0.07	PASS
-20	22	0.03	-64	-0.08	
-10	12	0.01	-51	-0.06	
0	-19	-0.02	-31	-0.04	
10	-30	-0.04	35	0.04	
20	-44	-0.05	42	0.05	
30	-46	-0.05	39	0.05	
40	-24	-0.03	40	0.05	
50	-36	-0.04	41	0.05	

Band :	GSM 1900	Channel :	661
Limit (ppm) :	2.5	Frequency :	1880.0 MHz

Temperature (°C)	GSM		EDGE 8		Result
	Freq. Dev. (Hz)	Deviation (ppm)	Freq. Dev. (Hz)	Deviation (ppm)	
-30	-72	-0.04	-71	-0.04	PASS
-20	54	0.03	-61	-0.03	
-10	-51	-0.03	-59	-0.03	
0	-27	-0.01	-41	-0.02	
10	-36	-0.02	27	0.01	
20	-57	-0.03	44	0.02	
30	-63	-0.03	43	0.02	
40	-60	-0.03	40	0.02	
50	-42	-0.02	42	0.02	



Band :	WCDMA Band V	Channel :	4182
Limit (ppm) :	2.5	Frequency :	836.4 MHz

Temperature (°C)	RMC 12.2Kbps		Result
	Freq. Dev. (Hz)	Deviation (ppm)	
-30	-7	-0.01	PASS
-20	-6	-0.01	
-10	-5	-0.01	
0	-4	0.00	
10	-6	-0.01	
20	-5	-0.01	
30	-6	-0.01	
40	-9	-0.01	
50	-10	-0.01	

Band :	WCDMA Band II	Channel :	9400
Limit (ppm) :	2.5	Frequency :	1880.0 MHz

Temperature (°C)	RMC 12.2Kbps		Result
	Freq. Dev. (Hz)	Deviation (ppm)	
-30	-19	-0.01	PASS
-20	-16	-0.01	
-10	-15	-0.01	
0	-12	-0.01	
10	-11	-0.01	
20	-15	-0.01	
30	-18	-0.01	
40	-17	-0.01	
50	-11	-0.01	



3.8.7 Test Result of Voltage Variation

Band & Channel	Mode	Voltage (Volt)	Freq. Dev. (Hz)	Deviation (ppm)	Limit (ppm)	Result
GSM 850 CH189	GSM	3.8	-41	-0.05	2.5	PASS
		BEP	-45	-0.05		
		4.2	-55	-0.06		
	EDGE 8	3.8	39	0.05		
		BEP	32	0.04		
		4.2	45	0.05		
GSM 1900 CH661	GSM	3.8	-51	-0.03		
		BEP	-59	-0.03		
		4.2	-61	-0.03		
	EDGE 8	3.8	38	0.02		
		BEP	31	0.02		
		4.2	45	0.02		
WCDMA Band V CH4182	RMC 12.2Kbps	3.8	-8	-0.01		
		BEP	-10	-0.01		
		4.2	-6	-0.01		
WCDMA Band II CH9400	RMC 12.2Kbps	3.8	-12	-0.01		
		BEP	-14	-0.01		
		4.2	-16	-0.01		

Note:

1. Normal Voltage = 3.8V.
2. Battery End Point (BEP) = 3.6 V.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
System Simulator	R&S	CMU200	117995	N/A	Jul. 30, 2012	Oct. 31, 2012	Jul. 29, 2013	Conducted (TH02-HY)
Spectrum Analyzer	R&S	FSP40	100055	9kHz~40GHz	Jun. 06, 2012	Oct. 31, 2012	Jun. 05, 2013	Conducted (TH02-HY)
Thermal Chamber	Ten Billion	TTH-D3SP	TBN-930701	N/A	Jul. 23, 2012	Oct. 31, 2012	Jul. 22, 2013	Conducted (TH02-HY)
Spectrum Analyzer	R&S	ESU26	100390	20Hz ~ 26.5GHz	Dec. 22, 2011	Nov. 01, 2012 ~ Nov. 22, 2012	Dec. 21, 2012	Radiation (03CH05-HY)
Bilog Antenna	Schaffner	CBL6111C	2725	30MHz~2GHz	Oct. 06, 2012	Nov. 01, 2012 ~ Nov. 22, 2012	Oct. 05, 2013	Radiation (03CH05-HY)
Turn Table	HD	Deis HD 2000	420/611	0 ~ 360 degree	N/A	Nov. 01, 2012 ~ Nov. 22, 2012	N/A	Radiation (03CH05-HY)
Antenna Mast	HD	MA 240	240/666	1 m ~ 4 m	N/A	Nov. 01, 2012 ~ Nov. 22, 2012	N/A	Radiation (03CH05-HY)
Horn Antenna	ESCO	3117	66584	1GHz~18GHz	Aug. 10, 2012	Nov. 01, 2012 ~ Nov. 22, 2012	Aug. 09, 2013	Radiation (03CH05-HY)
Pre Amplifier	Agilent	8449B	3008A02665	1GHz~26.5GHz	Aug. 28, 2012	Nov. 01, 2012 ~ Nov. 22, 2012	Aug. 27, 2013	Radiation (03CH05-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA917025 1	15GHz ~ 40GHz	Sep. 28, 2012	Nov. 01, 2012 ~ Nov. 22, 2012	Sep. 27, 2013	Radiation (03CH05-HY)
Pre Amplifier	COM-POWER	PA-103	161075	10-1000MHz.32dB. GAIN	Feb. 27, 2012	Nov. 01, 2012 ~ Nov. 22, 2012	Feb. 26, 2013	Radiation (03CH05-HY)
Loop Antenna	R&S	HFH2-Z2	860004/001	9KHz ~ 30MHz	Jul. 03, 2012	Nov. 01, 2012 ~ Nov. 22, 2012	Jul. 02, 2014	Radiation (03CH05-HY)
System Simulator	R&S	CMU200	117591	N/A	Oct. 21, 2011	Nov. 01, 2012 ~ Nov. 22, 2012	Oct. 20, 2013	Radiation (03CH05-HY)



5 Uncertainty of Evaluation

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.54
---	------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.72
---	------

