



FCC TEST REPORT (15.407)

REPORT NO.: RF120713C03-5

MODEL NO.: PM36100

FCC ID: NM8PM36100

RECEIVED: Jul. 13, 2012

TESTED: Jul. 29 ~ Aug. 08, 2012

ISSUED: Aug. 08, 2012

APPLICANT: HTC Corporation

ADDRESS: 23, Xinghua Rd., Taoyuan 330, Taiwan, R.O.C.

ISSUED BY: Bureau Veritas Consumer Products Services
(H.K.) Ltd., Taoyuan Branch

LAB ADDRESS: No. 47, 14th Ling, Chia Pau Vil., Lin Kou Dist.,
New Taipei City, Taiwan (R.O.C)

TEST LOCATION: No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei
Shan Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.

This report should not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification

TABLE OF CONTENTS

RELEASE CONTROL RECORD	4
1. CERTIFICATION	5
2. SUMMARY OF TEST RESULTS	6
2.1 MEASUREMENT UNCERTAINTY	6
3. GENERAL INFORMATION	7
3.1 GENERAL DESCRIPTION OF EUT	7
3.2 DESCRIPTION OF TEST MODES	8
3.2.1 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL	9
3.3 DESCRIPTION OF SUPPORT UNITS	11
3.3.1 CONFIGURATION OF SYSTEM UNDER TEST	11
3.4 DUTY CYCLE OF TEST SIGNAL	12
3.5 GENERAL DESCRIPTION OF APPLIED STANDARDS	12
4. TEST TYPES AND RESULTS	13
4.1 RADIATED EMISSION AND BANDEDGE MEASUREMENT	13
4.1.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT	13
4.1.2 LIMITS OF UNWANTED EMISSION OUT OF THE RESTRICTED BANDS	13
4.1.3 TEST INSTRUMENTS	14
4.1.4 TEST PROCEDURES	15
4.1.5 DEVIATION FROM TEST STANDARD	15
4.1.6 TEST SETUP	16
4.1.7 EUT OPERATING CONDITION	16
4.1.8 TEST RESULTS	17
4.2 CONDUCTED EMISSION MEASUREMENT	43
4.2.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT	43
4.2.2 TEST INSTRUMENTS	43
4.2.3 TEST PROCEDURES	44
4.2.4 DEVIATION FROM TEST STANDARD	44
4.2.5 TEST SETUP	44
4.2.6 EUT OPERATING CONDITIONS	44
4.2.7 TEST RESULTS	45
4.3 PEAK TRANSMIT POWER MEASUREMENT	47
4.3.1 LIMITS OF PEAK TRANSMIT POWER MEASUREMENT	47
4.3.2 TEST SETUP	47
4.3.3 TEST INSTRUMENTS	47
4.3.4 TEST PROCEDURE	48
4.3.5 DEVIATION FROM TEST STANDARD	48
4.3.6 EUT OPERATING CONDITIONS	48
4.3.7 TEST RESULTS	49
4.4 PEAK POWER SPECTRAL DENSITY MEASUREMENT	51
4.4.1 LIMITS OF PEAK POWER SPECTRAL DENSITY MEASUREMENT	51
4.4.2 TEST SETUP	51
4.4.3 TEST INSTRUMENTS	51
4.4.4 TEST PROCEDURES	51
4.4.5 DEVIATION FROM TEST STANDARD	51
4.4.6 EUT OPERATING CONDITIONS	51
4.4.7 TEST RESULTS	52
4.5 PEAK POWER EXCURSION MEASUREMENT	53



A D T

4.5.1	LIMITS OF PEAK POWER EXCURSION MEASUREMENT	53
4.5.2	TEST SETUP	53
4.5.3	TEST INSTRUMENTS	53
4.5.4	TEST PROCEDURE	53
4.5.5	DEVIATION FROM TEST STANDARD	53
4.5.6	EUT OPERATING CONDITIONS	53
4.5.7	TEST RESULTS	54
4.6	FREQUENCY STABILITY	57
4.6.1	LIMITS OF FREQUENCY STABILITY MEASUREMENT	57
4.6.2	TEST SETUP	57
4.6.3	TEST INSTRUMENTS	57
4.6.4	TEST PROCEDURE	58
4.6.5	DEVIATION FROM TEST STANDARD	58
4.6.6	EUT OPERATING CONDITION	58
4.6.7	TEST RESULTS	59
5.	PHOTOGRAPHS OF THE TEST CONFIGURATION	60
6.	INFORMATION ON THE TESTING LABORATORIES	61
7.	APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB	62



A D T

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF120713C03-5	Original release	Aug. 08, 2012



1. CERTIFICATION

PRODUCT: Smart Phone
MODEL NO.: PM36100
BRAND: HTC
APPLICANT: HTC Corporation
TESTED: Jul. 29 ~ Aug. 08, 2012
TEST SAMPLE: Production Unit
STANDARDS: **FCC Part 15, Subpart E (Section 15.407)**
ANSI C63.10-2009

The above equipment (model: PM36100) has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : Andrea Hsia , DATE : Aug. 08, 2012
Andrea Hsia / Specialist

APPROVED BY : Gary Chang , DATE : Aug. 08, 2012
Gary Chang / Technical Manager

2. SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC PART 15, SUBPART E (SECTION 15.407)			
STANDARD SECTION	TEST TYPE	RESULT	REMARK
15.407(b)(6)	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -1.35dB at 13.55859MHz.
15.407(b/1/2/3) (b)(6)	Spurious Emissions	PASS	Meet the requirement of limit. Minimum passing margin is -4.7dB at 3780.00MHz.
15.407(a/1/2)	Peak Transmit Power	PASS	Meet the requirement of limit.
15.407(a)(6)	Peak Power Excursion	PASS	Meet the requirement of limit.
15.407(a/1/2)	Peak Power Spectral Density	PASS	Meet the requirement of limit.
15.407(g)	Frequency Stability	PASS	Meet the requirement of limit.
15.203	Antenna Requirement	PASS	No antenna connector is used.

2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	9kHz~30MHz	2.44 dB
Radiated emissions	30MHz ~ 200MHz	2.93 dB
	200MHz ~1000MHz	2.95 dB
	1GHz ~ 18GHz	2.26 dB
	18GHz ~ 40GHz	1.94 dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k = 2$.

3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

EUT	Smart Phone
MODEL NO.	PM36100
POWER SUPPLY	5.0Vdc (adapter or host equipment) 3.8Vdc (Li-ion battery)
MODULATION TYPE	64QAM, 16QAM, QPSK, BPSK
MODULATION TECHNOLOGY	OFDM
TRANSFER RATE	802.11a: 54.0/ 48.0/ 36.0/ 24.0/ 18.0/ 12.0/ 9.0/ 6.0Mbps 802.11n: up to 135.0Mbps
OPERATING FREQUENCY	5180 ~ 5240MHz, 5260 ~ 5320MHz & 5500 ~ 5700MHz
NUMBER OF CHANNEL	5180 ~ 5240MHz: 4 for 802.11a, 802.11n (20MHz) 2 for 802.11n (40MHz) 5260 ~ 5320MHz: 4 for 802.11a, 802.11n (20MHz) 2 for 802.11n (40MHz) 5500 ~ 5700MHz: 11 for 802.11a, 802.11n (20MHz) 5 for 802.11n (40MHz)
OUTPUT POWER	23.605mW for 5180 ~ 5240MHz 20.797mW for 5260 ~ 5320MHz 23.659mW for 5500 ~ 5700MHz
ANTENNA TYPE	PIFA antenna with -3dBi gain
ANTENNA CONNECTOR	NA
DATA CABLE	Refer to Note as below
I/O PORTS	Refer to user's manual
ACCESSORY DEVICES	Refer to Note as below

NOTE:

1. The EUT's accessories list refers to Ext Pho.pdf.
2. The EUT provides one completed transmitter and one receiver.

MODULATION MODE	TX FUNCTION
802.11b	1TX
802.11g	1TX
802.11a	1TX
802.11n (20MHz)	1TX
802.11n (40MHz)	1TX

3. The above EUT information is declared by the manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.

3.2 DESCRIPTION OF TEST MODES

FOR 5180 ~ 5240MHz

4 channels are provided for 802.11a, 802.11n (20MHz):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
36	5180 MHz	44	5220 MHz
40	5200 MHz	48	5240 MHz

2 channels are provided for 802.11n (40MHz):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
38	5190 MHz	46	5230 MHz

FOR 5260 ~ 5320MHz

4 channels are provided for 802.11a, 802.11n (20MHz):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
52	5260 MHz	60	5300 MHz
56	5280 MHz	64	5320 MHz

2 channels are provided for 802.11n (40MHz):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
54	5270 MHz	62	5310 MHz

FOR 5500 ~ 5700MHz

11 channels are provided for 802.11a, 802.11n (20MHz):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
100	5500MHz	124	5620MHz
104	5520MHz	128	5640MHz
108	5540MHz	132	5660MHz
112	5560MHz	136	5680MHz
116	5580MHz	140	5700MHz
120	5600MHz		

5 channels are provided for 802.11n (40MHz):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
102	5510MHz	126	5630MHz
110	5550MHz	134	5670MHz
118	5590MHz		

3.2.1 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

EUT CONFIGURE MODE	APPLICABLE TO				DESCRIPTION
	RE \geq 1G	RE<1G	PLC	APCM	
-	√	√	√	√	-

Where **RE \geq 1G:** Radiated Emission above 1GHz **RE<1G:** Radiated Emission below 1GHz
PLC: Power Line Conducted Emission **APCM:** Antenna Port Conducted Measurement

NOTE: The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on **Z-plane**.

RADIATED EMISSION TEST (ABOVE 1GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

MODE	FREQ. BAND (MHz)	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11a	5180-5240	36 to 48	36, 44, 48	OFDM	BPSK	6.0
802.11n (20MHz)		36 to 48	36, 44, 48	OFDM	BPSK	6.5
802.11n (40MHz)		38 to 46	38, 46	OFDM	BPSK	13.5
802.11a	5260-5320	52 to 64	52, 60, 64	OFDM	BPSK	6.0
802.11n (20MHz)		52 to 64	52, 60, 64	OFDM	BPSK	6.5
802.11n (40MHz)		54 to 62	54, 62	OFDM	BPSK	13.5
802.11a	5500-5700	100 to 140	100, 116, 140	OFDM	BPSK	6.0
802.11n (20MHz)		100 to 140	100, 116, 140	OFDM	BPSK	6.5
802.11n (40MHz)		102 to 134	102, 110, 134	OFDM	BPSK	13.5

RADIATED EMISSION TEST (BELOW 1GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

MODE	FREQ. BAND (MHz)	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11n (40MHz)	5500-5700	102 to 134	134	OFDM	BPSK	13.5

POWER LINE CONDUCTED EMISSION TEST:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

MODE	FREQ. BAND (MHz)	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11n (40MHz)	5500-5700	102 to 134	134	OFDM	BPSK	13.5

BANDEDGE MEASUREMENT:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

MODE	FREQ. BAND (MHz)	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11a	5180-5240	36 to 48	36, 48	OFDM	BPSK	6.0
802.11n (20MHz)		36 to 48	36, 48	OFDM	BPSK	6.5
802.11n (40MHz)		38 to 46	38, 46	OFDM	BPSK	13.5
802.11a	5260-5320	52 to 64	52, 64	OFDM	BPSK	6.0
802.11n (20MHz)		52 to 64	52, 64	OFDM	BPSK	6.5
802.11n (40MHz)		54 to 62	54, 62	OFDM	BPSK	13.5
802.11a	5500-5700	100 to 140	100, 140	OFDM	BPSK	6.0
802.11n (20MHz)		100 to 140	100, 140	OFDM	BPSK	6.5
802.11n (40MHz)		102 to 134	102, 134	OFDM	BPSK	13.5

ANTENNA PORT CONDUCTED MEASUREMENT:

- This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

MODE	FREQ. BAND (MHz)	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11a	5180-5240	36 to 48	36, 44, 48	OFDM	BPSK	6.0
802.11n (20MHz)		36 to 48	36, 44, 48	OFDM	BPSK	6.5
802.11n (40MHz)		38 to 46	38, 46	OFDM	BPSK	13.5
802.11a	5260-5320	52 to 64	52, 60, 64	OFDM	BPSK	6.0
802.11n (20MHz)		52 to 64	52, 60, 64	OFDM	BPSK	6.5
802.11n (40MHz)		54 to 62	54, 62	OFDM	BPSK	13.5
802.11a	5500-5700	100 to 140	100, 116, 140	OFDM	BPSK	6.0
802.11n (20MHz)		100 to 140	100, 116, 140	OFDM	BPSK	6.5
802.11n (40MHz)		102 to 134	102, 110, 134	OFDM	BPSK	13.5

TEST CONDITION:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
RE≥1G	25deg. C, 65%RH	120Vac, 60Hz	Anderson Hong
RE<1G	25deg. C, 65%RH	120Vac, 60Hz	Sun Lin
PLC	25deg. C, 65%RH	120Vac, 60Hz	David Huang
APCM	25deg. C, 65%RH	120Vac, 60Hz	Howard Kao

3.3 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.


NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	Earphone	Merry	HS S250	NA	NA

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	1.1m non-shielded cable

NOTE:

1. All power cords of the above support units are non shielded (1.8m).
2. Item 1 was provided by client.

3.3.1 CONFIGURATION OF SYSTEM UNDER TEST



3.4 DUTY CYCLE OF TEST SIGNAL

If duty cycle is < 98%, duty factor shall be considered.

802.11a: Duty cycle = $2.051/2.163 = 0.948$, Duty factor = $10 * \log(1/0.948) = 0.23$

802.11n (20MHz): Duty cycle = $1.915/2.019 = 0.949$, Duty factor = $10 * \log(1/0.949) = 0.23$

802.11n (40MHz): Duty cycle = $0.657/0.766 = 0.858$, Duty factor = $10 * \log(1/0.858) = 0.67$



3.5 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart E (15.407)

ANSI C63.10-2009

KDB 789033 D01 General UNII Test Procedures v01r01

All test items have been performed and recorded as per the above standards.

4. TEST TYPES AND RESULTS

4.1 RADIATED EMISSION AND BANDEDGE MEASUREMENT

4.1.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table:

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

4.1.2 LIMITS OF UNWANTED EMISSION OUT OF THE RESTRICTED BANDS

EIRP LIMIT (dBm)	EQUIVALENT FIELD STRENGTH AT 3m (dBµV/m)
PK	PK
-27	68.3

NOTE: The following formula is used to convert the equipment isotropic radiated power (eirp) to field strength:

$$E = \frac{1000000\sqrt{30P}}{3} \mu\text{V/m, where P is the eirp (Watts).}$$



4.1.3 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF CALIBRATION	DUE DATE OF CALIBRATION
Test Receiver ROHDE & SCHWARZ	ESCI	100744	Apr. 19, 2012	Apr. 18, 2013
Spectrum Analyzer ROHDE & SCHWARZ	FSP40	100269	Jan. 30, 2012	Jan. 29, 2013
BILOG Antenna SCHWARZBECK	VULB9168	9168-156	Apr. 03, 2012	Apr. 02, 2013
HORN Antenna SCHWARZBECK	BBHA 9120 D	9120D-563	Sep. 06, 2011	Sep. 05, 2012
HORN Antenna SCHWARZBECK	BBHA 9170	148	Jul. 11, 2012	Jul. 10, 2013
Loop Antenna	HFH2-Z2	100070	Jan. 31, 2012	Jan. 30, 2014
Preamplifier Agilent	8449B	3008A01911	Oct. 29, 2011	Oct. 28, 2012
Preamplifier Agilent	8447D	2944A10638	Oct. 29, 2011	Oct. 28, 2012
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	295013/4 283403/4	Aug. 19, 2011	Aug. 18, 2012
RF signal cable Worken	8D-FB	Cable-HYCH9-01	Aug. 13, 2011	Aug. 12, 2012
Software	ADT_Radiated_ V7.6.15.9.2	NA	NA	NA
Antenna Tower EMCO	2070/2080	512.835.4684	NA	NA
Turn Table EMCO	2087-2.03	NA	NA	NA
26GHz ~ 40GHz Amplifier	EM26400	815221	Oct. 29, 2011	Oct. 28, 2012
Antenna Tower & Turn Table Controller MF	MF-7802	NA	NA	NA
JFW 20dB attenuation	50HF-020-SMA	NA	NA	NA
High Speed Peak Power Meter	ML2495A	0842014	Apr. 28, 2012	Apr. 27, 2013
Power Sensor	MA2411B	0738404	Apr. 28, 2012	Apr. 27, 2013

- NOTE:**
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 2. The calibration interval of the loop antenna is 24 months and the calibrations are traceable to NML/ROC and NIST/USA.
 3. The test was performed in HwaYa Chamber 9.
 4. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
 5. The FCC Site Registration No. is 460141.
 6. The IC Site Registration No. is IC 7450F-4.

4.1.4 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.


NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Peak detection (PK) and Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 1kHz for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.

4.1.5 DEVIATION FROM TEST STANDARD

No deviation.

4.1.6 TEST SETUP



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.7 EUT OPERATING CONDITION

- Placed the EUT on a testing table.
- Use the software to control the EUT under transmission condition continuously at specific channel frequency.

4.1.8 TEST RESULTS

ABOVE 1GHz DATA:

802.11a

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 36	FREQUENCY RANGE	1 ~ 40GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 68%RH	TESTED BY	Anderson Hong

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5150.00	43.3 PK	74.0	-30.7	1.01 H	176	5.10	38.20
2	5150.00	31.4 AV	54.0	-22.6	1.01 H	176	-6.80	38.20
3	*5180.00	88.4 PK			1.01 H	176	50.20	38.20
4	*5180.00	77.4 AV			1.01 H	176	39.20	38.20
5	#10360.00	55.3 PK	68.3	-13.0	1.20 H	231	7.30	48.00
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5150.00	44.8 PK	74.0	-29.2	1.02 V	173	6.60	38.20
2	5150.00	32.4 AV	54.0	-21.6	1.02 V	173	-5.80	38.20
3	*5180.00	91.2 PK			1.02 V	173	53.00	38.20
4	*5180.00	79.8 AV			1.02 V	173	41.60	38.20
5	#10360.00	55.9 PK	68.3	-12.4	1.00 V	80	7.90	48.00

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * “: Fundamental frequency.
6. “#”:The radiated frequency is out the restricted band.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 44	FREQUENCY RANGE	1 ~ 40GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 68%RH	TESTED BY	Anderson Hong

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5220.00	89.1 PK			1.01 H	179	50.80	38.30
2	*5220.00	78.1 AV			1.01 H	179	39.80	38.30
3	#10440.00	55.6 PK	68.3	-12.7	1.23 H	233	7.50	48.10
4	15660.00	58.2 PK	74.0	-15.8	1.12 H	210	9.20	49.00
5	15660.00	45.7 AV	54.0	-8.3	1.12 H	210	-3.30	49.00
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5220.00	92.1 PK			1.00 V	186	53.80	38.30
2	5220.00	81.1 PK			1.00 V	186	42.80	38.30
3	#10440.00	56.2 PK	68.3	-12.1	1.00 V	83	8.10	48.10
4	15660.00	59.8 PK	74.0	-14.2	1.43 V	38	10.80	49.00
5	15660.00	46.1 AV	54.0	-7.9	1.43 V	38	-2.90	49.00

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.
6. "#": The radiated frequency is out the restricted band.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 48	FREQUENCY RANGE	1 ~ 40GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 68%RH	TESTED BY	Anderson Hong

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5240.00	90.4 PK			1.34 H	166	52.10	38.30
2	*5240.00	79.4 AV			1.34 H	166	41.10	38.30
3	5350.00	44.5 PK	74.0	-29.5	1.34 H	166	6.00	38.50
4	5350.00	32.5 AV	54.0	-21.5	1.34 H	166	-6.00	38.50
5	#10480.00	56.1 PK	68.3	-12.2	1.25 H	236	7.90	48.20

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5240.00	93.0 PK			1.00 V	185	54.70	38.30
2	*5240.00	82.0 AV			1.00 V	185	43.70	38.30
3	5350.00	45.0 PK	74.0	-29.0	1.00 V	185	6.50	38.50
4	5350.00	33.0 AV	54.0	-21.0	1.00 V	185	-5.50	38.50
5	#10480.00	56.7 PK	68.3	-11.6	1.00 V	81	8.50	48.20

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * “: Fundamental frequency.
6. “#”:The radiated frequency is out the restricted band.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 52	FREQUENCY RANGE	1 ~ 40GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 68%RH	TESTED BY	Anderson Hong

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5150.00	44.6 PK	74.0	-29.4	1.22 H	167	6.40	38.20
2	5150.00	31.4 AV	54.0	-22.6	1.22 H	167	-6.80	38.20
3	*5260.00	91.3 PK			1.22 H	167	53.00	38.30
4	*5260.00	80.3 AV			1.22 H	167	42.00	38.30
5	#10520.00	56.4 PK	68.3	-11.9	1.22 H	232	8.10	48.30
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5150.00	45.7 PK	74.0	-28.3	1.00 V	182	7.50	38.20
2	5150.00	32.6 AV	54.0	-21.4	1.00 V	182	-5.60	38.20
3	*5260.00	93.7 PK			1.00 V	182	55.40	38.30
4	*5260.00	82.6 AV			1.00 V	182	44.30	38.30
5	#10520.00	57.0 PK	68.3	-11.3	1.00 V	80	8.70	48.30

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * “: Fundamental frequency.
6. “#”:The radiated frequency is out the restricted band.



EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 60	FREQUENCY RANGE	1 ~ 40GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 68%RH	TESTED BY	Anderson Hong

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5300.00	92.0 PK			1.20 H	167	53.60	38.40
2	*5300.00	81.0 AV			1.20 H	167	42.60	38.40
3	10600.00	56.3 PK	74.0	-17.7	1.25 H	236	8.00	48.30
4	10600.00	42.5 AV	54.0	-11.5	1.25 H	236	-5.80	48.30
5	15900.00	58.2 PK	74.0	-15.8	1.10 H	213	9.80	48.40
6	15900.00	45.5 AV	54.0	-8.5	1.10 H	213	-2.90	48.40
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5300.00	94.9 PK			1.09 V	188	56.50	38.40
2	*5300.00	83.9 AV			1.09 V	188	45.50	38.40
3	10600.00	55.7 PK	74.0	-18.3	1.00 V	86	7.40	48.30
4	10600.00	42.5 AV	54.0	-11.5	1.00 V	86	-5.80	48.30
5	15900.00	59.1 PK	74.0	-14.9	1.40 V	35	10.70	48.40
6	15900.00	44.8 AV	54.0	-9.2	1.40 V	35	-3.60	48.40

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * “: Fundamental frequency.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 64	FREQUENCY RANGE	1 ~ 40GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 68%RH	TESTED BY	Anderson Hong

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5320.00	93.2 PK			1.21 H	168	54.80	38.40
2	*5320.00	82.2 AV			1.21 H	168	43.80	38.40
3	5350.00	46.9 PK	74.0	-27.1	1.21 H	168	8.40	38.50
4	5350.00	33.9 AV	54.0	-20.1	1.21 H	168	-4.60	38.50
5	10640.00	56.8 PK	74.0	-17.2	1.23 H	234	8.30	48.50
6	10640.00	43.1 AV	54.0	-10.9	1.23 H	234	-5.40	48.50
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5320.00	95.8 PK			1.10 V	183	57.40	38.40
2	*5320.00	84.8 AV			1.10 V	183	46.40	38.40
3	5350.00	47.2 PK	74.0	-26.8	1.10 V	183	8.70	38.50
4	5350.00	34.7 AV	54.0	-19.3	1.10 V	183	-3.80	38.50
5	10640.00	56.2 PK	74.0	-17.8	1.00 V	84	7.70	48.50
6	10640.00	42.9 AV	54.0	-11.1	1.00 V	84	-5.60	48.50

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * “: Fundamental frequency.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 100	FREQUENCY RANGE	1 ~ 40GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 68%RH	TESTED BY	Anderson Hong

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5460.00	46.1 PK	74.0	-27.9	1.00 H	240	7.40	38.70
2	5460.00	33.8 AV	54.0	-20.2	1.00 H	240	-4.90	38.70
3	#5470.00	46.6 PK	68.3	-21.7	1.00 H	240	7.90	38.70
4	*5500.00	94.8 PK			1.00 H	240	56.10	38.70
5	*5500.00	83.8 AV			1.00 H	240	45.10	38.70
6	11000.00	55.8 PK	74.0	-18.2	1.22 H	235	6.60	49.20
7	11000.00	43.3 AV	54.0	-10.7	1.22 H	235	-5.90	49.20

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5460.00	50.7 PK	74.0	-23.3	1.04 V	202	12.00	38.70
2	5460.00	37.9 AV	54.0	-16.1	1.04 V	202	-0.80	38.70
3	#5470.00	51.2 PK	68.3	-17.1	1.04 V	202	12.50	38.70
4	*5500.00	101.1 PK			1.04 V	202	62.40	38.70
5	*5500.00	90.2 AV			1.04 V	202	51.50	38.70
6	11000.00	56.2 PK	74.0	-17.8	1.00 V	83	7.00	49.20
7	11000.00	43.2 AV	54.0	-10.8	1.00 V	83	-6.00	49.20

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * “: Fundamental frequency.
6. “#”:The radiated frequency is out the restricted band.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 116	FREQUENCY RANGE	1 ~ 40GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 68%RH	TESTED BY	Anderson Hong

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	3720.00	53.8 PK	74.0	-20.2	1.26 H	201	19.10	34.70
2	3720.00	45.1 AV	54.0	-8.9	1.26 H	201	10.40	34.70
3	*5580.00	96.0 PK			1.03 H	257	57.10	38.90
4	*5580.00	85.0 AV			1.03 H	257	46.10	38.90
5	11160.00	56.2 PK	74.0	-17.8	1.25 H	238	6.90	49.30
6	11160.00	43.6 AV	54.0	-10.4	1.25 H	238	-5.70	49.30
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	3720.00	53.4 PK	74.0	-20.6	1.31 V	172	18.70	34.70
2	3720.00	43.4 AV	54.0	-10.6	1.31 V	172	8.70	34.70
3	*5580.00	102.2 PK			1.02 V	198	63.30	38.90
4	*5580.00	91.3 AV			1.02 V	198	52.40	38.90
5	11160.00	56.6 PK	74.0	-17.4	1.00 V	80	7.30	49.30
6	11160.00	43.6 AV	54.0	-10.4	1.00 V	80	-5.70	49.30

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * “: Fundamental frequency.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 140	FREQUENCY RANGE	1 ~ 40GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 68%RH	TESTED BY	Anderson Hong

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5700.00	95.9 PK			1.00 H	184	56.70	39.20
2	*5700.00	84.9 AV			1.00 H	184	45.70	39.20
3	#5725.00	55.4 PK	68.3	-12.9	1.00 H	184	16.20	39.20
4	11400.00	56.0 PK	74.0	-18.0	1.23 H	233	6.70	49.30
5	11400.00	43.4 AV	54.0	-10.6	1.23 H	233	-5.90	49.30
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5700.00	101.9 PK			1.00 V	194	62.70	39.20
2	*5700.00	90.7 AV			1.00 V	194	51.50	39.20
3	#5725.00	56.9 PK	68.3	-11.4	1.00 V	194	17.70	39.20
4	11400.00	56.4 PK	74.0	-17.6	1.00 V	87	7.10	49.30
5	11400.00	43.5 AV	54.0	-10.5	1.00 V	87	-5.80	49.30

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * “: Fundamental frequency.
6. “#”:The radiated frequency is out the restricted band.



A D T

802.11n (20MHz)

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 36	FREQUENCY RANGE	1 ~ 40GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 68%RH	TESTED BY	Anderson Hong

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5150.00	44.5 PK	74.0	-29.5	1.24 H	176	6.30	38.20
2	5150.00	31.8 AV	54.0	-22.2	1.24 H	176	-6.40	38.20
3	*5180.00	89.0 PK			1.24 H	176	50.80	38.20
4	*5180.00	78.0 AV			1.24 H	176	39.80	38.20
5	#10360.00	56.1 PK	68.3	-12.2	1.21 H	238	8.10	48.00

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5150.00	45.4 PK	74.0	-28.6	1.01 V	183	7.20	38.20
2	5150.00	32.1 AV	54.0	-21.9	1.01 V	183	-6.10	38.20
3	*5180.00	90.8 PK			1.01 V	183	52.60	38.20
4	*5180.00	79.8 AV			1.01 V	183	41.60	38.20
5	#10360.00	55.4 PK	68.3	-12.9	1.00 V	81	7.40	48.00

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * “: Fundamental frequency.
6. "#":The radiated frequency is out the restricted band.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 44	FREQUENCY RANGE	1 ~ 40GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 68%RH	TESTED BY	Anderson Hong

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5220.00	89.9 PK			1.10 H	177	51.60	38.30
2	*5220.00	89.9 AV			1.10 H	177	40.60	38.30
3	#10440.00	56.5 PK	68.3	-11.8	1.23 H	231	8.40	48.10
4	15660.00	58.5 PK	74.0	-15.5	1.11 H	207	9.50	49.00
5	15660.00	45.9 AV	54.0	-8.1	1.11 H	207	-3.10	49.00

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5220.00	92.0 PK			1.00 V	183	53.70	38.30
2	*5220.00	81.0 AV			1.00 V	183	42.70	38.30
3	#10440.00	55.8 PK	68.3	-12.5	1.00 V	84	7.70	48.10
4	15660.00	60.1 PK	74.0	-13.9	1.41 V	35	11.10	49.00
5	15660.00	46.5 AV	54.0	-7.5	1.41 V	35	-2.50	49.00

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
6. "#":The radiated frequency is out the restricted band.
4. Margin value = Emission level – Limit value.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 48	FREQUENCY RANGE	1 ~ 40GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 68%RH	TESTED BY	Anderson Hong

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5240.00	90.1 PK			1.23 H	168	51.80	38.30
2	*5240.00	79.1 AV			1.23 H	168	40.80	38.30
3	5350.00	44.4 PK	74.0	-29.6	1.23 H	168	5.90	38.50
4	5350.00	32.3 AV	54.0	-21.7	1.23 H	168	-6.20	38.50
5	#10480.00	56.8 PK	68.3	-11.5	1.25 H	236	8.60	48.20

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5240.00	93.1 PK			1.00 V	182	54.80	38.30
2	*5240.00	82.1 AV			1.00 V	182	43.80	38.30
3	5350.00	45.3 PK	74.0	-28.7	1.00 V	182	6.80	38.50
4	5350.00	33.2 AV	54.0	-20.8	1.00 V	182	-5.30	38.50
5	#10480.00	56.0 PK	68.3	-12.3	1.00 V	88	7.80	48.20

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * “: Fundamental frequency.
6. “#”:The radiated frequency is out the restricted band.



EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 52	FREQUENCY RANGE	1 ~ 40GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 68%RH	TESTED BY	Anderson Hong

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5150.00	44.3 PK	74.0	-29.7	1.23 H	164	6.10	38.20
2	5150.00	31.1 AV	54.0	-22.9	1.23 H	164	-7.10	38.20
3	*5260.00	91.1 PK			1.23 H	164	52.80	38.30
4	*5260.00	80.1 AV			1.23 H	164	41.80	38.30
5	#10520.00	57.2 PK	68.3	-11.1	1.21 H	241	8.90	48.30
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5150.00	45.5 PK	74.0	-28.5	1.00 V	189	7.30	38.20
2	5150.00	32.4 AV	54.0	-21.6	1.00 V	189	-5.80	38.20
3	*5260.00	93.6 PK			1.00 V	189	55.30	38.30
4	*5260.00	82.6 AV			1.00 V	189	44.30	38.30
5	#10520.00	56.3 PK	68.3	-12.0	1.00 V	82	8.00	48.30

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * “: Fundamental frequency.
6. “#”:The radiated frequency is out the restricted band.



EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 60	FREQUENCY RANGE	1 ~ 40GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 68%RH	TESTED BY	Anderson Hong

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5300.00	91.8 PK			1.31 H	167	53.40	38.40
2	*5300.00	80.8 AV			1.31 H	167	42.40	38.40
3	10600.00	56.0 PK	74.0	-18.0	1.24 H	233	7.70	48.30
4	10600.00	42.3 AV	54.0	-11.7	1.24 H	233	-6.00	48.30
5	15900.00	58.0 PK	74.0	-16.0	1.11 H	215	9.60	48.40
6	15900.00	45.3 AV	54.0	-8.7	1.11 H	215	-3.10	48.40
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5300.00	94.4 PK			1.00 V	187	56.00	38.40
2	*5300.00	83.4 AV			1.00 V	187	45.00	38.40
3	10600.00	55.4 PK	74.0	-18.6	1.00 V	84	7.10	48.30
4	10600.00	42.3 AV	54.0	-11.7	1.00 V	84	-6.00	48.30
5	15900.00	59.0 PK	74.0	-15.0	1.42 V	38	10.60	48.40
6	15900.00	44.6 AV	54.0	-9.4	1.42 V	38	-3.80	48.40

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * “: Fundamental frequency.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 64	FREQUENCY RANGE	1 ~ 40GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 68%RH	TESTED BY	Anderson Hong

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5320.00	92.3 PK			1.10 H	169	53.90	38.40
2	*5320.00	81.3 AV			1.10 H	169	42.90	38.40
3	5350.00	46.1 PK	74.0	-27.9	1.10 H	169	7.60	38.50
4	5350.00	33.5 AV	54.0	-20.5	1.10 H	169	-5.00	38.50
5	10640.00	56.3 PK	74.0	-17.7	1.22 H	230	7.80	48.50
6	10640.00	42.5 AV	54.0	-11.5	1.22 H	230	-6.00	48.50
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5320.00	94.7 PK			1.00 V	184	56.30	38.40
2	*5320.00	83.7 AV			1.00 V	184	45.30	38.40
3	5350.00	47.2 PK	74.0	-26.8	1.00 V	184	8.70	38.50
4	5350.00	34.4 AV	54.0	-19.6	1.00 V	184	-4.10	38.50
5	10640.00	55.7 PK	74.0	-18.3	1.00 V	87	7.20	48.50
6	10640.00	42.6 AV	54.0	-11.4	1.00 V	87	-5.90	48.50

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * “: Fundamental frequency.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 100	FREQUENCY RANGE	1 ~ 40GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 68%RH	TESTED BY	Anderson Hong

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5460.00	45.1 PK	74.0	-28.9	1.00 H	241	6.40	38.70
2	5460.00	33.5 AV	54.0	-20.5	1.00 H	241	-5.20	38.70
3	#5470.00	46.0 PK	68.3	-22.3	1.00 H	241	7.30	38.70
4	*5500.00	94.1 PK			1.00 H	241	55.40	38.70
5	*5500.00	83.0 AV			1.00 H	241	44.30	38.70
6	11000.00	55.5 PK	74.0	-18.5	1.21 H	231	6.30	49.20
7	11000.00	43.1 AV	54.0	-10.9	1.21 H	231	-6.10	49.20

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5460.00	48.5 PK	74.0	-25.5	1.05 V	176	9.80	38.70
2	5460.00	36.4 AV	54.0	-17.6	1.05 V	176	-2.30	38.70
3	#5470.00	49.8 PK	68.3	-18.5	1.05 V	176	11.10	38.70
4	*5500.00	100.5 PK			1.05 V	176	61.80	38.70
5	*5500.00	89.5 AV			1.05 V	176	50.80	38.70
6	11000.00	55.1 PK	74.0	-18.9	1.25 V	236	5.90	49.20
7	11000.00	42.7 AV	54.0	-11.3	1.25 V	236	-6.50	49.20

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * “: Fundamental frequency.
6. “#”:The radiated frequency is out the restricted band.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 116	FREQUENCY RANGE	1 ~ 40GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 68%RH	TESTED BY	Anderson Hong

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	3720.00	53.4 PK	74.0	-20.6	1.23 H	204	18.70	34.70
2	3720.00	44.8 AV	54.0	-9.2	1.23 H	204	10.10	34.70
3	*5580.00	94.3 PK			1.18 H	225	55.40	38.90
4	*5580.00	83.3 AV			1.18 H	225	44.40	38.90
5	11160.00	55.8 PK	74.0	-18.2	1.25 H	235	6.50	49.30
6	11160.00	43.4 AV	54.0	-10.6	1.25 H	235	-5.90	49.30
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	3720.00	53.1 PK	74.0	-20.9	1.35 V	175	18.40	34.70
2	3720.00	43.2 AV	54.0	-10.8	1.35 V	175	8.50	34.70
3	*5580.00	101.1 PK			1.02 V	195	62.20	38.90
4	*5580.00	90.1 AV			1.02 V	195	51.20	38.90
5	11160.00	55.5 PK	74.0	-18.5	1.28 V	230	6.20	49.30
6	11160.00	43.0 AV	54.0	-11.0	1.28 V	230	-6.30	49.30

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * “: Fundamental frequency.



EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 140	FREQUENCY RANGE	1 ~ 40GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 68%RH	TESTED BY	Anderson Hong

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5700.00	94.0 PK			1.07 H	216	54.80	39.20
2	*5700.00	83.0 AV			1.07 H	216	43.80	39.20
3	#5725.00	48.8 PK	68.3	-19.5	1.07 H	216	9.60	39.20
4	11400.00	55.6 PK	74.0	-18.4	1.29 H	239	6.30	49.30
5	11400.00	43.2 AV	54.0	-10.8	1.29 H	239	-6.10	49.30
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5700.00	101.4 PK			1.00 V	197	62.20	39.20
2	*5700.00	90.4 AV			1.00 V	197	51.20	39.20
3	#5725.00	55.3 PK	68.3	-13.0	1.00 V	197	16.10	39.20
4	11400.00	56.1 PK	74.0	-17.9	1.00 V	85	6.80	49.30
5	11400.00	43.2 AV	54.0	-10.8	1.00 V	85	-6.10	49.30

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * “: Fundamental frequency.
6. “#”:The radiated frequency is out the restricted band.



802.11n (40MHz)

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 38	FREQUENCY RANGE	1 ~ 40GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Anderson Hong

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5150.00	56.2 PK	74.0	-17.8	1.21 H	325	18.40	37.80
2	5150.00	43.6 AV	54.0	-10.4	1.21 H	325	5.80	37.80
3	*5190.00	89.4 PK			1.21 H	325	51.50	37.90
4	*5190.00	79.6 AV			1.21 H	325	41.70	37.90
5	#10380.00	59.0 PK	68.3	-9.3	1.15 H	324	9.90	49.10

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5150.00	56.0 PK	74.0	-18.0	1.00 V	4	17.80	38.20
2	5150.00	43.6 AV	54.0	-10.4	1.00 V	4	5.40	38.20
3	*5190.00	91.4 PK			1.00 V	4	53.20	38.20
4	*5190.00	82.5 AV			1.00 V	4	44.30	38.20
5	#10380.00	58.8 PK	68.3	-9.5	1.00 V	209	10.80	48.00

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * “: Fundamental frequency.
6. "#":The radiated frequency is out the restricted band.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 46	FREQUENCY RANGE	1 ~ 40GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Anderson Hong

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5150.00	56.5 PK	74.0	-17.5	1.00 H	320	18.70	37.80
2	5150.00	43.7 AV	54.0	-10.3	1.00 H	320	5.90	37.80
3	*5230.00	90.3 PK			1.00 H	318	52.40	37.90
4	*5230.00	81.0 AV			1.00 H	318	43.10	37.90
5	#10460.00	59.6 PK	68.3	-8.7	1.14 H	307	10.20	49.40

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5150.00	55.7 PK	74.0	-18.3	1.35 V	11	17.50	38.20
2	5150.00	43.5 AV	54.0	-10.5	1.35 V	11	5.30	38.20
3	*5230.00	93.8 PK			1.35 V	11	55.50	38.30
4	*5230.00	84.1 AV			1.35 V	11	45.80	38.30
5	#10460.00	59.0 PK	68.3	-9.3	1.00 V	214	10.80	48.20

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * “: Fundamental frequency.
6. “#”: The radiated frequency is out the restricted band.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 54	FREQUENCY RANGE	1 ~ 40GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Anderson Hong

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5270.00	92.6 PK			1.06 H	5	54.60	38.00
2	*5270.00	82.4 AV			1.06 H	5	44.40	38.00
3	5350.00	56.9 PK	74.0	-17.1	1.06 H	5	18.80	38.10
4	5350.00	44.5 AV	54.0	-9.5	1.06 H	5	6.40	38.10
5	#10540.00	60.0 PK	68.3	-8.3	1.19 H	324	10.40	49.60

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5270.00	94.3 PK			1.00 V	13	56.30	38.00
2	*5270.00	85.0 AV			1.00 V	13	47.00	38.00
3	5350.00	57.1 PK	74.0	-16.9	1.00 V	13	19.00	38.10
4	5350.00	44.5 AV	54.0	-9.5	1.00 V	13	6.40	38.10
5	#10540.00	59.5 PK	68.3	-8.8	1.00 V	224	9.90	49.60

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * “: Fundamental frequency.
6. “#”: The radiated frequency is out the restricted band.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 62	FREQUENCY RANGE	1 ~ 40GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Anderson Hong

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5310.00	91.7 PK			1.12 H	17	53.30	38.40
2	*5310.00	81.5 AV			1.12 H	17	43.10	38.40
3	5350.00	54.7 PK	74.0	-19.3	1.12 H	17	16.20	38.50
4	5350.00	42.8 AV	54.0	-11.2	1.12 H	17	4.30	38.50
5	10620.00	57.7 PK	74.0	-16.3	1.25 H	232	9.30	48.40
6	10620.00	43.2 AV	54.0	-10.8	1.25 H	232	-5.20	48.40
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5310.00	93.1 PK			1.00 V	210	54.70	38.40
2	*5310.00	83.4 AV			1.00 V	210	45.00	38.40
3	5350.00	56.8 PK	74.0	-17.2	1.07 V	209	18.30	38.50
4	5350.00	44.3 AV	54.0	-9.7	1.07 V	209	5.80	38.50
5	10620.00	58.9 PK	74.0	-15.1	1.08 V	182	10.50	48.40
6	10620.00	45.0 AV	54.0	-9.0	1.08 V	182	-3.40	48.40

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * “: Fundamental frequency.

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 102	FREQUENCY RANGE	1 ~ 40GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Anderson Hong

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	3673.00	54.9 PK	74.0	-19.1	1.10 H	197	20.30	34.60
2	3673.00	45.9 AV	54.0	-8.1	1.10 H	197	11.30	34.60
3	5460.00	59.5 PK	74.0	-14.5	1.26 H	195	20.80	38.70
4	5460.00	42.7 AV	54.0	-11.3	1.26 H	195	4.00	38.70
5	#5470.00	61.8 PK	68.3	-6.5	1.26 H	195	23.10	38.70
6	*5510.00	97.8 PK			1.24 H	192	59.00	38.80
7	*5510.00	87.4 AV			1.24 H	192	48.60	38.80
8	11000.00	55.2 PK	74.0	-18.8	1.34 H	228	6.00	49.20
9	11000.00	46.3 AV	54.0	-7.7	1.34 H	228	-2.90	49.20
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	3673.00	51.8 PK	74.0	-22.2	1.00 V	191	17.20	34.60
2	3673.00	41.5 AV	54.0	-12.5	1.00 V	191	6.90	34.60
3	5460.00	57.3 PK	74.0	-16.7	1.12 V	260	18.60	38.70
4	5460.00	40.0 AV	54.0	-14.0	1.12 V	260	1.30	38.70
5	#5470.00	59.3 PK	68.3	-9.0	1.12 V	260	20.60	38.70
6	*5510.00	98.5 PK			1.00 V	258	59.70	38.80
7	*5510.00	89.0 AV			1.00 V	258	50.20	38.80
8	11000.00	57.5 PK	74.0	-16.5	1.08 V	327	8.30	49.20
9	11000.00	46.0 AV	54.0	-8.0	1.08 V	327	-3.20	49.20

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * “: Fundamental frequency.
6. “#”:The radiated frequency is out the restricted band.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 110	FREQUENCY RANGE	1 ~ 40GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Anderson Hong

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	3700.00	57.2 PK	74.0	-16.8	1.07 H	193	22.60	34.60
2	3700.00	48.2 AV	54.0	-5.8	1.07 H	193	13.60	34.60
3	*5550.00	98.7 PK			1.23 H	190	59.90	38.80
4	*5550.00	88.5 AV			1.23 H	190	49.70	38.80
5	11100.00	56.0 PK	74.0	-18.0	1.36 H	225	6.80	49.20
6	11100.00	43.2 AV	54.0	-10.8	1.36 H	225	-6.00	49.20
7	#16650.00	62.1 PK	68.3	-6.2	1.23 H	320	11.00	51.10
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	3700.00	52.0 PK	74.0	-22.0	1.00 V	195	17.40	34.60
2	3700.00	41.8 AV	54.0	-12.2	1.00 V	195	7.20	34.60
3	*5550.00	99.0 PK			1.00 V	250	60.20	38.80
4	*5550.00	88.6 AV			1.00 V	250	49.80	38.80
5	11100.00	59.6 PK	74.0	-14.4	1.07 V	325	10.40	49.20
6	11100.00	44.6 AV	54.0	-9.4	1.07 V	325	-4.60	49.20
7	#16650.00	60.9 PK	68.3	-7.4	1.00 V	80	9.80	51.10

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * “: Fundamental frequency.
6. “#”: The radiated frequency is out the restricted band.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 134	FREQUENCY RANGE	1 ~ 40GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Anderson Hong

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	3780.00	55.4 PK	74.0	-18.6	1.00 H	208	20.50	34.90
2	3780.00	49.3 AV	54.0	-4.7	1.00 H	208	14.40	34.90
3	*5670.00	97.2 PK			1.09 H	192	58.10	39.10
4	*5670.00	87.2 AV			1.09 H	192	48.10	39.10
5	#5725.00	54.7 PK	68.3	-13.6	1.09 H	192	15.50	39.20
6	11340.00	55.7 PK	74.0	-18.3	1.35 H	223	6.40	49.30
7	11340.00	43.0 AV	54.0	-11.0	1.35 H	223	-6.30	49.30
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	3780.00	52.3 PK	74.0	-21.7	1.00 V	197	17.40	34.90
2	3780.00	42.0 AV	54.0	-12.0	1.00 V	197	7.10	34.90
3	*5670.00	100.5 PK			1.00 V	187	61.40	39.10
4	*5670.00	90.4 AV			1.00 V	187	51.30	39.10
5	#5725.00	57.5 PK	68.3	-10.8	1.00 V	187	18.30	39.20
6	11340.00	59.3 PK	74.0	-14.7	1.05 V	329	10.00	49.30
7	11340.00	44.2 AV	54.0	-9.8	1.05 V	329	-5.10	49.30

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
6. "#":The radiated frequency is out the restricted band.
4. Margin value = Emission level – Limit value.



A D T

BELOW 1GHz WORST-CASE DATA : 802.11n (40MHz)

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 134	FREQUENCY RANGE	Below 1000MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	25deg. C, 68%RH	TESTED BY	Sun Lin

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	99.84	30.6 QP	43.5	-12.9	2.00 H	350	21.20	9.40
2	165.80	31.1 QP	43.5	-12.4	1.50 H	103	17.40	13.70
3	239.52	31.6 QP	46.0	-14.4	1.25 H	305	18.90	12.70
4	336.52	29.4 QP	46.0	-16.6	1.25 H	17	13.60	15.80
5	664.38	32.8 QP	46.0	-13.2	1.25 H	38	10.10	22.70
6	722.58	33.6 QP	46.0	-12.4	1.00 H	294	10.30	23.30

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	99.84	27.9 QP	43.5	-15.6	1.25 V	17	18.50	9.40
2	165.80	27.3 QP	43.5	-16.2	1.00 V	0	13.60	13.70
3	189.08	28.0 QP	43.5	-15.5	1.25 V	17	16.00	12.00
4	336.52	27.0 QP	46.0	-19.0	2.00 V	17	11.20	15.80
5	431.58	29.9 QP	46.0	-16.1	1.00 V	242	11.60	18.30
6	666.32	28.6 QP	46.0	-17.4	1.25 V	313	5.90	22.70

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.

4.2 CONDUCTED EMISSION MEASUREMENT

4.2.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dB μ V)	
	Quasi-peak	Average
0.15 ~ 0.5	66 to 56	56 to 46
0.5 ~ 5	56	46
5 ~ 30	60	50

- NOTE:** 1. The lower limit shall apply at the transition frequencies.
 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.
 3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

4.2.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF CALIBRATION	DUE DATE OF CALIBRATION
Test Receiver ROHDE & SCHWARZ	ESCS30	100289	Nov. 19, 2011	Nov. 18, 2012
RF signal cable Woken	5D-FB	Cable-HYCO2-01	Dec. 29, 2011	Dec. 28, 2012
LISN ROHDE & SCHWARZ (EUT)	ESH2-Z5	100100	Dec. 30, 2011	Dec. 29, 2012
LISN ROHDE & SCHWARZ (Peripheral)	ESH3-Z5	100311	Jul. 06, 2012	Jul. 05, 2013
Software ADT	BV ADT_Cond_ V7.3.7.3	NA	NA	NA

- NOTE:** 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 2. The test was performed in HwaYa Shielded Room 2.
 3. The VCCI Site Registration No. is C-2047.

4.2.3 TEST PROCEDURES


- The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

NOTE: All modes of operation were investigated and the worst-case emissions are reported.

4.2.4 DEVIATION FROM TEST STANDARD

No deviation.

4.2.5 TEST SETUP



- Note:**
- Support units were connected to second LISN.
 - Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.2.6 EUT OPERATING CONDITIONS

Same as 4.1.6.

4.2.7 TEST RESULTS

CONDUCTED WORST-CASE DATA :


802.11n (40MHz)

PHASE	Line 1	6dB BANDWIDTH	9kHz
-------	--------	---------------	------

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.24375	0.15	53.84	37.43	53.99	37.58	61.97	51.97	-7.97	-14.38
2	0.38438	0.17	50.10	30.80	50.27	30.97	58.18	48.18	-7.92	-17.22
3	0.50156	0.17	46.71	26.53	46.88	26.70	56.00	46.00	-9.12	-19.30
4	0.61875	0.18	46.86	25.75	47.04	25.93	56.00	46.00	-8.96	-20.07
5	2.50781	0.28	42.39	22.35	42.67	22.63	56.00	46.00	-13.33	-23.37
6	13.55859	0.50	53.82	48.15	54.32	48.65	60.00	50.00	-5.68	-1.35

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




PHASE	Line 2	6dB BANDWIDTH	9kHz
-------	--------	---------------	------

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.25547	0.15	53.64	36.35	53.79	36.50	61.58	51.58	-7.79	-15.08
2	0.38438	0.16	49.92	30.03	50.08	30.19	58.18	48.18	-8.11	-18.00
3	0.50156	0.17	45.96	25.08	46.13	25.25	56.00	46.00	-9.87	-20.75
4	0.62266	0.17	46.86	25.57	47.03	25.74	56.00	46.00	-8.97	-20.26
5	2.50781	0.28	42.01	21.74	42.29	22.02	56.00	46.00	-13.71	-23.98
6	13.56250	0.57	53.72	47.95	54.29	48.52	60.00	50.00	-5.71	-1.48

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.



4.3 PEAK TRANSMIT POWER MEASUREMENT


4.3.1 LIMITS OF PEAK TRANSMIT POWER MEASUREMENT

FREQUENCY BAND	LIMIT
5.150 ~ 5.250GHz	The lesser of 50mW (17dBm) or 4dBm + 10logB
5.250 ~ 5.350GHz	The lesser of 250mW (24dBm) or 11dBm + 10logB
5.470 ~ 5.725GHz	The lesser of 250mW (24dBm) or 11dBm + 10logB


NOTE: Where B is the 26dB emission bandwidth in MHz.

4.3.2 TEST SETUP

FOR POWER OUTPUT MEASUREMENT



FOR 26dB BANDWIDTH



4.3.3 TEST INSTRUMENTS

Refer to section 4.1.3 to get information of above instrument.

4.3.4 TEST PROCEDURE

FOR AVERAGE POWER MEASUREMENT

Method PM is used to perform output power measurement, trigger and gating function of wide band power meter is enabled to measure max output power of TX on burst. Duty factor is not added to measured value.

FOR 26dB BANDWIDTH

- 1) Set RBW = approximately 1% of the emission bandwidth.
- 2) Set the VBW > RBW.
- 3) Detector = Peak.
- 4) Trace mode = max hold.
- 5) Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

4.3.5 DEVIATION FROM TEST STANDARD

No deviation.

4.3.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at specific channel frequencies individually.

4.3.7 TEST RESULTS

POWER OUTPUT: 802.11a

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (mW)	AVERAGE POWER (dBm)	POWER LIMIT (dBm)	PASS/FAIL
36	5180	21.281	13.28	17	PASS
44	5220	20.277	13.07	17	PASS
48	5240	19.999	13.01	17	PASS
52	5260	19.861	12.98	24	PASS
60	5300	19.588	12.92	24	PASS
64	5320	19.999	13.01	24	PASS
100	5500	23.067	13.63	24	PASS
116	5580	22.439	13.51	24	PASS
140	5700	21.928	13.41	24	PASS

802.11n (20MHz)

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (mW)	AVERAGE POWER (dBm)	POWER LIMIT (dBm)	PASS/FAIL
36	5180	21.086	13.24	17	PASS
44	5220	20.749	13.17	17	PASS
48	5240	20.512	13.12	17	PASS
52	5260	20.797	13.18	24	PASS
60	5300	20.701	13.16	24	PASS
64	5320	19.770	12.96	24	PASS
100	5500	19.143	12.82	24	PASS
116	5580	18.197	12.60	24	PASS
140	5700	17.660	12.47	24	PASS

802.11n (40MHz)

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (mW)	AVERAGE POWER (dBm)	POWER LIMIT (dBm)	PASS/FAIL
38	5190	23.605	13.73	17	PASS
46	5230	21.979	13.42	17	PASS
54	5270	20.749	13.17	24	PASS
62	5310	19.999	13.01	24	PASS
102	5510	21.577	13.34	24	PASS
110	5550	22.131	13.45	24	PASS
134	5670	23.659	13.74	24	PASS



26dB BANDWIDTH: 802.11a

CHANNEL	CHANNEL FREQUENCY (MHz)	26dBc BANDWIDTH (MHz)	PASS / FAIL
36	5180	23.83	PASS
44	5220	23.96	PASS
48	5240	23.22	PASS
52	5260	23.64	PASS
60	5300	23.45	PASS
64	5320	24.43	PASS
100	5500	23.99	PASS
116	5580	23.77	PASS
140	5700	23.95	PASS

802.11n (20MHz)

CHANNEL	CHANNEL FREQUENCY (MHz)	26dBc BANDWIDTH (MHz)	PASS / FAIL
36	5180	24.57	PASS
44	5220	24.00	PASS
48	5240	24.71	PASS
52	5260	24.32	PASS
60	5300	24.06	PASS
64	5320	24.03	PASS
100	5500	24.01	PASS
116	5580	24.19	PASS
140	5700	24.25	PASS

802.11n (40MHz)


CHANNEL	CHANNEL FREQUENCY (MHz)	26dBc BANDWIDTH (MHz)	PASS / FAIL
38	5190	65.23	PASS
46	5230	66.73	PASS
54	5270	69.39	PASS
62	5310	68.63	PASS
102	5510	68.10	PASS
110	5550	54.53	PASS
134	5670	53.21	PASS

4.4 PEAK POWER SPECTRAL DENSITY MEASUREMENT

4.4.1 LIMITS OF PEAK POWER SPECTRAL DENSITY MEASUREMENT

FREQUENCY BAND	LIMIT
5.150 ~ 5.250GHz	4dBm
5.250 ~ 5.350GHz	11dBm
5.470 ~ 5.725GHz	11dBm

4.4.2 TEST SETUP



4.4.3 TEST INSTRUMENTS

Refer to section 4.1.3 to get information of above instrument.

4.4.4 TEST PROCEDURES

Using method SA-2 alternative

- 1) Set span to encompass the entire emission bandwidth (EBW) of the signal.
- 2) Set RBW = 1 MHz, Set VBW \geq 3 MHz, Detector = RMS
- 3) Sweep time = 4second.
- 4) Perform a single sweep.
- 5) Record the max value and add 10 log (1/duty cycle)

4.4.5 DEVIATION FROM TEST STANDARD

No deviation.

4.4.6 EUT OPERATING CONDITIONS

Same as 4.3.6.



4.4.7 TEST RESULTS

802.11a

CHANNEL	FREQUENCY (MHz)	PSD W/O DUTY FACTOR (dBm)	DUTY FACTOR	PSD WITH DUTY FACTOR (dBm)	MAXIMUM LIMIT (dBm)	PASS/FAIL
36	5180	1.02	0.23	1.25	4	PASS
44	5220	0.93	0.23	1.16	4	PASS
48	5240	0.74	0.23	0.97	4	PASS
52	5260	0.80	0.23	1.03	11	PASS
60	5300	0.85	0.23	1.08	11	PASS
64	5320	0.95	0.23	1.18	11	PASS
100	5500	1.61	0.23	1.84	11	PASS
116	5580	1.45	0.23	1.68	11	PASS
140	5700	1.03	0.23	1.26	11	PASS

NOTE: Refer to section 3.3 for duty cycle spectrum plot.

802.11n (20MHz)

CHANNEL	FREQUENCY (MHz)	PSD W/O DUTY FACTOR (dBm)	DUTY FACTOR	PSD WITH DUTY FACTOR (dBm)	MAXIMUM LIMIT (dBm)	PASS/FAIL
36	5180	0.86	0.23	1.09	4	PASS
44	5220	0.71	0.23	0.94	4	PASS
48	5240	0.70	0.23	0.93	4	PASS
52	5260	0.91	0.23	1.14	11	PASS
60	5300	0.75	0.23	0.98	11	PASS
64	5320	0.74	0.23	0.97	11	PASS
100	5500	0.34	0.23	0.57	11	PASS
116	5580	0.54	0.23	0.77	11	PASS
140	5700	0.12	0.23	0.35	11	PASS

NOTE: Refer to section 3.3 for duty cycle spectrum plot.

802.11n (40MHz)

CHANNEL	FREQUENCY (MHz)	PSD W/O DUTY FACTOR (dBm)	DUTY FACTOR	PSD WITH DUTY FACTOR (dBm)	MAXIMUM LIMIT (dBm)	PASS/FAIL
38	5190	0.94	0.67	1.61	4	PASS
46	5230	0.78	0.67	1.45	4	PASS
54	5270	0.94	0.67	1.61	11	PASS
62	5310	0.81	0.67	1.48	11	PASS
102	5510	0.01	0.67	0.68	11	PASS
110	5550	0.16	0.67	0.83	11	PASS
134	5670	-0.31	0.67	0.36	11	PASS


NOTE: Refer to section 3.3 for duty cycle spectrum plot.

4.5 PEAK POWER EXCURSION MEASUREMENT

4.5.1 LIMITS OF PEAK POWER EXCURSION MEASUREMENT

Shall not exceed 13 dB.

4.5.2 TEST SETUP



4.5.3 TEST INSTRUMENTS

Refer to section 4.1.3 to get information of above instrument.

4.5.4 TEST PROCEDURE

- 1) Set RBW = 1 MHz, VBW \geq 3 MHz, Detector = peak.
- 2) Trace mode = max-hold. Allow the sweeps to continue until the trace stabilizes.
- 3) Use the peak search function to find the peak of the spectrum.
- 4) Measure the PPSD.
- 5) Compute the ratio of the maximum of the peak-max-hold spectrum to the PPSD.

4.5.5 DEVIATION FROM TEST STANDARD

No deviation.

4.5.6 EUT OPERATING CONDITIONS


Same as 4.2.6

4.5.7 TEST RESULTS

802.11a

CHAN.	CHANNEL FREQUENCY (MHz)	PEAK VALUE (dBm)	PPSD WITHOUT DUTY FACTOR (dBm)	PPSD WITH DUTY FACTOR (dBm)	PEAK POWER EXCURSION (dB)	PEAK to AVERAGE EXCURSION LIMIT (dB)	PASS /FAIL
36	5180	10.55	1.02	1.25	9.30	13	PASS
44	5220	10.86	0.93	1.16	9.70	13	PASS
48	5240	11.57	0.74	0.97	10.60	13	PASS
52	5260	9.87	0.80	1.03	8.84	13	PASS
60	5300	11.14	0.85	1.08	10.06	13	PASS
64	5320	11.18	0.95	1.18	10.00	13	PASS
100	5500	11.25	1.61	1.84	9.41	13	PASS
116	5580	11.68	1.45	1.68	10.00	13	PASS
140	5700	10.18	1.03	1.26	8.92	13	PASS


NOTE: Refer to section 3.3 for duty cycle spectrum plot.



802.11n (20MHz)

CHAN.	CHANNEL FREQUENCY (MHz)	PEAK VALUE (dBm)	PPSD WITHOUT DUTY FACTOR (dBm)	PPSD WITH DUTY FACTOR (dBm)	PEAK POWER EXCURSION (dB)	PEAK to AVERAGE EXCURSION LIMIT (dB)	PASS /FAIL
36	5180	10.16	0.86	1.09	9.07	13	PASS
44	5220	9.91	0.71	0.94	8.97	13	PASS
48	5240	10.12	0.70	0.93	9.19	13	PASS
52	5260	10.06	0.91	1.14	8.92	13	PASS
60	5300	10.84	0.75	0.98	9.86	13	PASS
64	5320	10.66	0.74	0.97	9.69	13	PASS
100	5500	10.00	0.34	0.57	9.43	13	PASS
116	5580	9.81	0.54	0.77	9.04	13	PASS
140	5700	9.15	0.12	0.35	8.80	13	PASS


NOTE: Refer to section 3.3 for duty cycle spectrum plot.



802.11n (40MHz)

CHAN.	CHANNEL FREQUENCY (MHz)	PEAK VALUE (dBm)	PPSD WITHOUT DUTY FACTOR (dBm)	PPSD WITH DUTY FACTOR (dBm)	PEAK POWER EXCURSION (dB)	PEAK to AVERAGE EXCURSION LIMIT (dB)	PASS /FAIL
38	5190	11.37	0.94	1.61	9.76	13	PASS
46	5230	11.13	0.78	1.45	9.68	13	PASS
54	5270	10.95	0.94	1.61	9.34	13	PASS
62	5310	11.00	0.81	1.48	9.52	13	PASS
102	5510	9.63	0.01	0.68	8.95	13	PASS
110	5550	10.13	0.16	0.83	9.3	13	PASS
134	5670	9.97	-0.31	0.36	9.61	13	PASS

NOTE: Refer to section 3.3 for duty cycle spectrum plot.




4.6 FREQUENCY STABILITY

4.6.1 LIMITS OF FREQUENCY STABILITY MEASUREMENT

The frequency of the carrier signal shall be maintained within band of operation

4.6.2 TEST SETUP



4.6.3 TEST INSTRUMENTS

Refer to section 4.1.3 to get information of above instrument.

4.6.4 TEST PROCEDURE

- a. To ensure emission at the band edge is maintained within the authorized band, those values shall be measured by radiation emissions at upper and lower frequency points, and finally compensated by frequency deviation as procedures below.
- b. The EUT was operated at the maximum output power, and connected to the spectrum analyzer, which is set to maximum hold function and peak detector. The peak value of the power envelope was measured and noted. The upper and lower frequency points were respectively measured relatively 10dB lower than the measured peak value.
- c. The frequency deviation was calculated by adding the upper frequency point and the lower frequency point divided by two. Those detailed values of frequency deviation are provided in table below.

4.6.5 DEVIATION FROM TEST STANDARD

No deviation.

4.6.6 EUT OPERATING CONDITION

Set the EUT transmit at un-modulation mode to test frequency stability.



A D T

4.6.7 TEST RESULTS

FREQUENCY STABILITY VERSUS TEMP.				
802.11a				
Channel	Frequency (MHz)	Low Frequency (Fl)	High Frequency (Fh)	Frequency Stability (ppm)
36	5180	5171.83	5188.20	2.41
40	5200	5211.80	5228.20	0.00
48	5240	5231.80	5248.20	0.00
52	5260	5251.80	5268.20	0.00
60	5300	5291.80	5308.20	0.00
64	5320	5311.80	5328.20	0.00
100	5500	5491.80	5508.20	0.00
116	5580	5571.80	5588.20	0.00
140	5700	5691.83	5708.20	2.19

FREQUENCY STABILITY VERSUS TEMP.				
802.11n (20MHz)				
Channel	Frequency (MHz)	Low Frequency (Fl)	High Frequency (Fh)	Frequency Stability (ppm)
36	5180	5171.20	5188.80	0.00
40	5200	5211.18	5228.83	0.00
48	5240	5231.18	5248.83	0.00
52	5260	5251.20	5268.80	0.00
60	5300	5291.20	5308.85	4.72
64	5320	5311.20	5328.85	4.70
100	5500	5491.20	5508.80	0.00
116	5580	5571.18	5588.83	0.00
140	5700	5691.18	5708.83	0.00

5. PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).



6. INFORMATION ON THE TESTING LABORATORIES

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab:

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF Lab:

Tel: 886-3-5935343

Fax: 886-3-5935342

Hwa Ya EMC/RF/Safety Telecom Lab:

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com

Web Site: www.adt.com.tw

The address and road map of all our labs can be found in our web site also.

7. APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No modifications were made to the EUT by the lab during the test.

---END---