



# RF EXPOSURE REPORT

**REPORT NO.:** SA 980106L05-2

**MODEL NO.:** RHOD500

**ACCORDING:** FCC Guidelines for Human Exposure  
IEEE C95.1

**APPLICANT:** HTC Corporation

**ADDRESS:** No. 23, Xinghua Rd., Taoyuan City, 330, Taiwan,  
R.O.C.

**ISSUED BY:** Bureau Veritas Consumer Products Services (H.K.)  
Ltd., Taoyuan Branch

**LAB ADDRESS:** No. 47, 14th Ling, Chia Pau Tsuen, Lin Kou Hsiang,  
Taipei Hsien 244, Taiwan, R.O.C.

**TEST LOCATION:** No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei  
Shan Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.



## 1. Conclusion

No Evaluation Required if power is below this threshold:

F(GHz)		mW
Low	2.402	24.585
High	2.480	

Maximum measured transmitter power:

	Pout (dBm)	Pout (mW)
Conducted Power	-0.03	0.933
EIRP Power	0.97	0.028

**\*Note:** The antenna is PIFA antenna with 1dBi gain.

Threshold for no SAR evaluation is 24.585mW

Transmitter power is 0.028mW

Conclusion: No SAR evaluation required since Transmitter Pout is below FCC threshold