

TEST REPORT

CERTIFICATE OF CONFORMITY

Standard: 47 CFR FCC Part 15, Subpart E (Section 15.407)

Report No.: RFBEMI-WTW-P25020703-3

FCC ID: NOIKBN367B

Product: Electronic Display Device

Brand: Rakuten kobo

Model No.: N367B

Received Date: 2025/2/28

Test Date: 2025/3/18 ~ 2025/3/27

Issued Date: 2025/6/3

Applicant: NETRONIX, INC.

Address: No. 945, Boai St., Jubei City, Hsin-Chu, 30265, Taiwan

Factory: (1) NETRONIX, INC.
(2) NTX Electronics YANGZHOU CO., LTD.

Address: (1) No. 945, Boai St., Jubei City, Hsin-Chu, 30265, Taiwan
(2) No. 8, Wuzhou West Road, Economic and technological Development Zone, Yangzhou, Jiangsu Province, 225009, China

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Lin Kou Laboratories

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City 33383, Taiwan

FCC Registration / 788550 / TW0003

Designation Number:

Approved by:

Jeremy Lin

Jeremy Lin / Project Engineer

, Date:

2025/6/3

This test report consists of 72 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The test results in the report only apply to the tested sample. The test results in this report are traceable to the national or international standards.



Prepared by : Polly Chien / Specialist

This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/>, and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

Table of Contents

Release Control Record	4
1 Certificate.....	5
2 Summary of Test Results	6
2.1 Measurement Uncertainty	6
2.2 Supplementary Information	6
3 General Information	7
3.1 General Description of EUT	7
3.2 Antenna Description of EUT	8
3.3 Channel List.....	9
3.4 Test Mode Applicability and Tested Channel Detail.....	10
3.5 Duty Cycle of Test Signal.....	11
3.6 Test Program Used and Operation Descriptions	13
3.7 Connection Diagram of EUT and Peripheral Devices	13
3.8 Configuration of Peripheral Devices and Cable Connections	13
4 Test Instruments	14
4.1 RF Output Power.....	14
4.2 Power Spectral Density	14
4.3 6 dB Bandwidth	14
4.4 Occupied Bandwidth.....	14
4.5 AC Power Conducted Emissions	15
4.6 Unwanted Emissions below 1 GHz	15
4.7 Unwanted Emissions above 1 GHz.....	16
5 Limits of Test Items.....	17
5.1 RF Output Power.....	17
5.2 Power Spectral Density	17
5.3 6 dB Bandwidth	17
5.4 Occupied Bandwidth.....	17
5.5 AC Power Conducted Emissions	17
5.6 Unwanted Emissions below 1 GHz	18
5.7 Unwanted Emissions above 1 GHz.....	19
6 Test Arrangements.....	20
6.1 RF Output Power.....	20
6.1.1 Test Setup	20
6.1.2 Test Procedure.....	20
6.2 Power Spectral Density	20
6.2.1 Test Setup	20
6.2.2 Test Procedure.....	20
6.3 6 dB Bandwidth	22
6.3.1 Test Setup	22
6.3.2 Test Procedure.....	22
6.4 Occupied Bandwidth.....	22
6.4.1 Test Setup	22
6.4.2 Test Procedure.....	22
6.5 AC Power Conducted Emissions	23
6.5.1 Test Setup	23
6.5.2 Test Procedure.....	23
6.6 Unwanted Emissions below 1 GHz	24
6.6.1 Test Setup	24
6.6.2 Test Procedure.....	25
6.7 Unwanted Emissions above 1 GHz.....	26
6.7.1 Test Setup	26
6.7.2 Test Procedure.....	26
7 Test Results of Test Item	27

7.1	RF Output Power.....	27
7.2	Power Spectral Density	29
7.3	6 dB Bandwidth	33
7.4	Occupied Bandwidth.....	35
7.5	AC Power Conducted Emissions	39
7.6	Unwanted Emissions below 1 GHz	41
7.7	Unwanted Emissions above 1 GHz.....	43
8	Pictures of Test Arrangements	71
9	Information of the Testing Laboratories	72

Release Control Record

Issue No.	Description	Date Issued
RFBEMI-WTW-P25020703-3	Original release.	2025/6/3

1 Certificate

Product: Electronic Display Device

Brand: Rakuten kobo

Test Model: N367B

Sample Status: Engineering sample

Applicant: NETRONIX, INC.

Test Date: 2025/3/18 ~ 2025/3/27

Standard: 47 CFR FCC Part 15, Subpart E (Section 15.407)

Measurement procedure: ANSI C63.10-2013
KDB 789033 D02 General UNII Test Procedure New Rules v02r01

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

2 Summary of Test Results

47 CFR FCC Part 15, Subpart E (Section 15.407)			
Clause	Test Item	Result	Remark
15.407(a)(1) 15.407(a)(3)	RF Output Power	Pass	Meet the requirement of limit.
15.407(a)(1) 15.407(a)(3)	Power Spectral Density	Pass	Meet the requirement of limit.
15.407(e)	6 dB Bandwidth	Pass	Meet the requirement of limit. (U-NII-3 Band only)
---	Occupied Bandwidth	-	Reference only.
15.407(b)(9)	AC Power Conducted Emissions	Pass	Minimum passing margin is -2.93 dB at 0.48600 MHz
15.407(b)(9)	Unwanted Emissions below 1 GHz	Pass	Minimum passing margin is -7.8 dB at 55.22 MHz
15.407(b) (1/10) 15.407(b) (4(i)/10)	Unwanted Emissions above 1 GHz	Pass	Minimum passing margin is -0.2 dB at 5150.00 MHz
15.203	Antenna Requirement	Pass	No antenna connector is used.

Notes: Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Parameter	Specification	Expanded Uncertainty (k=2) (±)
RF Output Power	-	1.371 dB
Power Spectral Density	-	1.017 dB
6 dB Bandwidth	-	206.5 Hz
Occupied Bandwidth	-	72 Hz
AC Power Conducted Emissions	9 kHz ~ 30 MHz	2.90 dB
Unwanted Emissions below 1 GHz	9 kHz ~ 30 MHz	3.59 dB
	30 MHz ~ 1 GHz	3.6 dB
Unwanted Emissions above 1 GHz	1 GHz ~ 18 GHz	2.29 dB
	18 GHz ~ 40 GHz	2.29 dB

The other instruments specified are routine verified to remain within the calibrated levels, no measurement uncertainty is required to be calculated.

2.2 Supplementary Information

There is not any deviation from the test standards for the test method, and no modifications required for compliance.

3 General Information

3.1 General Description of EUT

Product	Electronic Display Device
Brand	Rakuten kobo
Test Model	N367B
Status of EUT	Engineering sample
Power Supply Rating	3.87 Vdc from battery 5 Vdc from adapter or host equipment
Modulation Type	64QAM, 16QAM, QPSK, BPSK for OFDM 256QAM for OFDM in 11ac mode
Modulation Technology	OFDM
Transfer Rate	Up to 433.3 Mbps
Operating Frequency	5.18 GHz ~ 5.24 GHz 5.745 GHz ~ 5.825 GHz
Number of Channel	802.11a, 802.11n (HT20), 802.11ac (VHT20):9 802.11n (HT40), 802.11ac (VHT40):4 802.11ac (VHT80):2
Output Power	5.18 GHz ~ 5.24 GHz : 24.044 mW (13.81 dBm) 5.745 GHz ~ 5.825 GHz : 31.55 mW (14.99 dBm)
EUT Category	Client device

Note:

1. The EUT uses following accessories.

Item	Brand	Model	Supplier Model	Color	Specification	Material	TID number
1st source USB Cable	LUXSHARE-ICT	LB93US005-1H	-	Black	Signal Line : Shielded: Y, 1.0M, Core: N/A	TPE	-
		LB93US006-1H	-	White	Signal Line : Shielded: Y, 1.0M, Core: N/A	TPE	-
2nd source USB Cable	Yih Fone	SH-0846	YF-USB2-A-C-1M(K)	Black	Signal Line : Shielded: Y, 1.0M, Core: N/A	TPE	12574
		SH-0837	YF-USB2-A-C-1M-WH(K)	White	Signal Line : Shielded: Y, 1.0M, Core: N/A	TPE	12575

2. The EUT will be supported with the following eMMC and DRAM LP-DDR4 sources.

Item	Brand	Model
1st source eMMC	Phison	PTE7A0YJ-16GE
2nd source eMMC	Kingston	EMMC16G-PJ30-GA02
3rd source eMMC	FORESEE	FEMDNN016G-A3A55
1st source DRAM LP-DDR4	Nanya	NT6AN256M16AV-J2
2nd source DRAM LP-DDR4	Leahkinn	LTHS0005GS4-ZPI1
3rd source DRAM LP-DDR4	Micron	MT53E256M16D1DS-046

3. There are Bluetooth and WLAN (2.4 GHz & 5 GHz) technology used for the EUT.

4. Simultaneously transmission condition.

Condition	Technology	
1	WLAN (2.4 GHz)	Bluetooth
2	WLAN (5 GHz)	Bluetooth

Note: The emission of the simultaneous operation has been evaluated and no non-compliance was found.

5. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.

3.2 Antenna Description of EUT

1. The antenna information is listed as below.

Gain (dBi)	Antenna Type	Connector Type
3.41	Chip	N/A

*Detail antenna specification please refer to antenna datasheet and/or antenna measurement report.

2. The EUT provides 1 completed transmitter and 1 receiver.

5 GHz Band		
Modulation Mode	TX & RX Configuration	
802.11a	1TX	1RX
802.11n (HT20)	1TX	1RX
802.11n (HT40)	1TX	1RX
802.11ac (VHT20)	1TX	1RX
802.11ac (VHT40)	1TX	1RX
802.11ac (VHT80)	1TX	1RX

3.3 Channel List

For 5180 ~ 5240 MHz

4 channels are provided for 802.11a, 802.11n (HT20), 802.11ac (VHT20):

Channel	Frequency	Channel	Frequency
36	5180 MHz	44	5220 MHz
40	5200 MHz	48	5240 MHz

2 channels are provided for 802.11n (HT40), 802.11ac (VHT40):

Channel	Frequency	Channel	Frequency
38	5190 MHz	46	5230 MHz

1 channel is provided for 802.11ac (VHT80):

Channel	Frequency
42	5210 MHz

For 5745 ~ 5825 MHz:

5 channels are provided for 802.11a, 802.11n (HT20), 802.11ac (VHT20):

Channel	Frequency	Channel	Frequency
149	5745 MHz	161	5805 MHz
153	5765 MHz	165	5825 MHz
157	5785 MHz		

2 channels are provided for 802.11n (HT40), 802.11ac (VHT40):

Channel	Frequency	Channel	Frequency
151	5755 MHz	159	5795 MHz

1 channel is provided for 802.11ac (VHT80):

Channel	Frequency
155	5775 MHz

3.4 Test Mode Applicability and Tested Channel Detail

Pre-Scan:	1. For Radiated, pre-scan Power from AC Adapter via USB Cable / Laptop via USB Cable / Battery and find the worst case as a representative test condition. 2. For AC conduction, pre-scan Power from AC Adapter via USB Cable / Laptop via USB Cable and find the worst case as a representative test condition. 3. EUT can be used in the following ways: X-axis/ Y-axis/ Z-axis. Pre-scan these ways and find the worst case as a representative test condition. 4. The USB Cable has the following models: LB93US005-1H(Black) / SH-0846(Black). Pre-scan these models of USB Cables and find the worst case as a representative test condition. 5. The DRAM LP-DDR4 has the following models: NT6AN256M16AV-J2 / LTHS0005GS4-ZPI1 / MT53E256M16D1DS-046. Pre-scan these models of DRAM LP-DDR4 and find the worst case as a representative test condition. 6. The eMMC has the following models: PTE7A0YJ-16GE / EMMC16G-PJ30-GA02 / FEMDNN016G-A3A55. Pre-scan these models of eMMC and find the worst case as a representative test condition. 7. Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
Worst Case:	1. For Radiated Worst Condition: AC Adapter via USB Cable 2. For AC conduction Worst Condition: AC Adapter via USB Cable 3. X-axis/ Y-axis/ Z-axis Worst Condition: Y-axis 4. USB Cable Worst Condition: SH-0846(Black) 5. DRAM LP-DDR4 Worst Condition: MT53E256M16D1DS-046 6. eMMC Worst Condition: FEMDNN016G-A3A55

Note: Both USB cables are identical to each other except for exterior color and model names

Following channel(s) was (were) selected for the final test as listed below:

Test Item	Mode	Tested Channel	Modulation	Data Rate Parameter
RF Output Power	802.11a	36, 40, 48, 149, 157, 165	BPSK	6Mb/s
	802.11n (HT20)	36, 40, 48, 149, 157, 165	BPSK	MCS0
	802.11n (HT40)	38, 46, 151, 159	BPSK	MCS0
	802.11ac (VHT20)	36, 40, 48, 149, 157, 165	BPSK	MCS0
	802.11ac (VHT40)	38, 46, 151, 159	BPSK	MCS0
	802.11ac (VHT80)	42, 155	BPSK	MCS0
Power Spectral Density / Occupied Bandwidth	802.11a	36, 40, 48, 149, 157, 165	BPSK	6Mb/s
	802.11ac (VHT20)	36, 40, 48, 149, 157, 165	BPSK	MCS0
	802.11ac (VHT40)	38, 46, 151, 159	BPSK	MCS0
	802.11ac (VHT80)	42, 155	BPSK	MCS0
6 dB Bandwidth	802.11a	149, 157, 165	BPSK	6Mb/s
	802.11ac (VHT20)	149, 157, 165	BPSK	MCS0
	802.11ac (VHT40)	151, 159	BPSK	MCS0
	802.11ac (VHT80)	155	BPSK	MCS0
AC Power Conducted Emissions	802.11ac (VHT80)	155	BPSK	MCS0
Unwanted Emissions below 1 GHz	802.11ac (VHT80)	155	BPSK	MCS0
Unwanted Emissions above 1 GHz	802.11a	36, 40, 48, 149, 157, 165	BPSK	6Mb/s
	802.11ac (VHT20)	36, 40, 48, 149, 157, 165	BPSK	MCS0
	802.11ac (VHT40)	38, 46, 151, 159	BPSK	MCS0
	802.11ac (VHT80)	42, 155	BPSK	MCS0


3.5 Duty Cycle of Test Signal

802.11a: Duty cycle = 2.772 ms / 2.796 ms x 100% = 99.1%


802.11ac (VHT20): Duty cycle = 2.59 ms / 2.61 ms x 100% = 99.2%

802.11ac (VHT40): Duty cycle = 1.265 ms / 1.3 ms x 100% = 97.3%, duty factor = $10 \cdot \log(1/\text{Duty cycle}) = 0.12 \text{ dB}$

802.11ac (VHT80): Duty cycle = 0.609 ms / 0.645 ms x 100% = 94.4%, duty factor = $10 \cdot \log(1/\text{Duty cycle}) = 0.25 \text{ dB}$




802.11a




802.11ac (VHT20)

Duty Cycle Analysis



802.11ac (VHT40)

Duty Cycle Analysis




802.11ac (VHT80)

3.6 Test Program Used and Operation Descriptions

Controlling software Terminal version 2.10 has been activated to set the EUT under transmission condition continuously at specific channel frequency.

3.7 Connection Diagram of EUT and Peripheral Devices



3.8 Configuration of Peripheral Devices and Cable Connections

ID	Product	Brand	Model No.	Serial No.	FCC ID	Remarks
A.	Adapter	LITEON	PA-1050-39	N/A	N/A	Provided by Lab
B.	Laptop	Lenovo	L470	PF0U96K5	N/A	Provided by Lab
C.	Fixture Board	Netronix	N367B console board(1.8V)	N/A	N/A	Supplied by applicant

No.	Cable Descriptions	Qty.	Length (m)	Shielded (Yes/ No)	Cores (Qty.)	Remark
1.	USB Cable	1	1	Yes	0	Accessory of EUT
2.	USB Cable	1	1	Yes	0	Supplied by applicant
3.	Console Cable	1	0.6	No	0	Supplied by applicant, Attached on Fixture Board

4 Test Instruments

The calibration interval of the all test instruments are 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.1 RF Output Power

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
Peak Power Analyzer Keysight	8990B	MY51000538	2024/4/29	2025/4/28
Wideband Power Sensor Keysight	N1923A	MY58200003	2024/6/17	2025/6/16

Notes:

1. The test was performed in Oven room.
2. Tested Date: 2025/3/27

4.2 Power Spectral Density

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
Signal & Spectrum Analyzer R&S	FSV3044	101504	2024/6/18	2025/6/17
Software BV	ADT_RF Test Software V7.6.5.4	N/A	N/A	N/A

Notes:

1. The test was performed in Oven room.
2. Tested Date: 2025/3/27

4.3 6 dB Bandwidth

Refer to section 4.2 to get the tested date and information of the instruments.

4.4 Occupied Bandwidth

Refer to section 4.2 to get the tested date and information of the instruments.

4.5 AC Power Conducted Emissions

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
50 ohm terminal resistance	E1-011279	04	2024/11/28	2025/11/27
	E1-011280	05	2024/11/28	2025/11/27
	E1-011311	09	2024/11/28	2025/11/27
DC-LISN Schwarzbeck	NNBM 8126G	8126G-069	2024/11/5	2025/11/4
EMI Test Receiver R&S	ESR3	102783	2024/12/17	2025/12/16
Fixed Attenuator STI	BNC5W10dB	PAD-COND2-01	2024/8/25	2025/8/24
LISN R&S	ESH2-Z5	100100	2025/3/5	2026/3/4
	ESH3-Z5	100312	2024/9/9	2025/9/8
RF Coaxial Cable Woken	5D-FB	Cable-cond2-01	2024/8/25	2025/8/24
Software BVADT	BVADT_Cond_ V7.4.1.0	N/A	N/A	N/A
V-LISN Schwarzbeck	NNBL 8226-2	8226-142	2024/8/28	2025/8/27

Notes:

1. The test was performed in HY - Conduction 2.
2. Tested Date: 2025/3/19

4.6 Unwanted Emissions below 1 GHz

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
Antenna Tower & Turn BV ADT	AT100	AT93021705	N/A	N/A
Bi_Log Antenna Schwarzbeck	VULB 9168	9168-160	2024/10/9	2025/10/8
Loop Antenna TESEQ	HLA 6121	45745	2024/8/21	2025/8/20
MXE EMI Receiver Agilent	N9038A	MY51210203	2024/8/27	2025/8/26
Preamplifier Agilent	8447D	2944A10638	2024/5/1	2025/4/30
RF Coaxial Cable Woken	8D-FB	Cable-CH9-01	2024/5/1	2025/4/30
Signal & Spectrum Analyzer R&S	FSW43	101866	2024/3/26	2025/3/25
Software BV ADT	ADT_Radiated_ V7.6.15.9.5	N/A	N/A	N/A
Turn Table BV ADT	TT100	TT93021705	N/A	N/A
Turn Table Controller BV ADT	SC100	SC93021705	N/A	N/A

Notes:

1. The test was performed in HY - 966 chamber 4.
2. Tested Date: 2025/3/20

4.7 Unwanted Emissions above 1 GHz

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
Antenna Tower & Turn BV ADT	AT100	AT93021705	N/A	N/A
Boresight antenna tower fixture BV	BAF-02	5	N/A	N/A
Horn Antenna Schwarzbeck	BBHA 9120D	9120D-1169	2024/11/10	2025/11/9
	BBHA 9170	9170-480	2024/11/10	2025/11/9
		BBHA9170243	2024/11/10	2025/11/9
MXE EMI Receiver Agilent	N9038A	MY51210203	2024/8/27	2025/8/26
Preamplifier Agilent	8449B	3008A02367	2025/1/5	2026/1/4
Preamplifier EMCI	EMC 184045	980116	2024/9/24	2025/9/23
RF Coaxial Cable EMCI	EMC102-KM-KM-600	150928	2024/7/6	2025/7/5
	EMC102-KM-KM-3000	150929	2024/7/6	2025/7/5
RF Coaxial Cable HUBER+SUHNER	SUCOFLEX 104	CABLE-CH9-(250795/4)	2025/1/5	2026/1/4
RF Coaxial Cable HUBER+SUHNER&EMCI	SUCOFLEX 104& EMC104-SM-SM8000	CABLE-CH9-02 (248780+171006)	2025/1/5	2026/1/4
Signal & Spectrum Analyzer R&S	FSW43	101866	2024/3/26	2025/3/25
Software BV ADT	ADT_Radiated_ V7.6.15.9.5	N/A	N/A	N/A
Turn Table BV ADT	TT100	TT93021705	N/A	N/A
Turn Table Controller BV ADT	SC100	SC93021705	N/A	N/A

Notes:

1. The test was performed in HY - 966 chamber 4.
2. Tested Date: 2025/3/18

5 Limits of Test Items

5.1 RF Output Power

Operation Band	EUT Category	Limit
U-NII-1	Outdoor Access Point	1 Watt (30 dBm) (Max. e.i.r.p $\leq$ 125mW(21 dBm) at any elevation angle above 30 degrees as measured from the horizon)
	Fixed point-to-point Access Point	1 Watt (30 dBm)
	Indoor Access Point	1 Watt (30 dBm)
	Mobile and Portable client device	250mW (24 dBm)

Operation Band	Limit
U-NII-3	1 Watt (30 dBm)

5.2 Power Spectral Density

Operation Band	EUT Category	Limit
U-NII-1	Outdoor Access Point	17 dBm/MHz
	Fixed point-to-point Access Point	
	Indoor Access Point	
	Mobile and Portable client device	11 dBm/MHz

Operation Band	Limit
U-NII-3	30 dBm/500 kHz

5.3 6 dB Bandwidth

Within the 5.725-5.850 GHz band, the minimum 6 dB bandwidth of U-NII devices shall be at least 500 kHz.

5.4 Occupied Bandwidth

The results are for reference only.

5.5 AC Power Conducted Emissions

Frequency (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15 - 0.5	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50

Notes:

1. The lower limit shall apply at the transition frequencies.
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.

5.6 Unwanted Emissions below 1 GHz

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table.

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

Notes:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).

5.7 Unwanted Emissions above 1 GHz

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table.

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
Above 960	500	3

Notes:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000 MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20 dB under any condition of modulation.

Limits of unwanted emission out of the restricted bands

Applicable To	Limit	
789033 D02 General UNII Test Procedure New Rules v02r01	Field Strength at 3 m	
	PK: 74 (dBμV/m)	AV: 54 (dBμV/m)

For transmitters operating in the 5.15-5.25 GHz band:

Applicable To	EIRP Limit	Equivalent Field Strength at 3 m
15.407(b)(1)	PK: -27 (dBm/MHz)	PK: 68.2 (dBμV/m)

For transmitters operating in the 5.725-5.850 GHz band:

Applicable To	EIRP Limit	Equivalent Field Strength at 3 m
15.407(b)(4)(i)	PK: -27 (dBm/MHz) ^{*1} PK: 10 (dBm/MHz) ^{*2} PK: 15.6 (dBm/MHz) ^{*3} PK: 27 (dBm/MHz) ^{*4}	PK: 68.2 (dBμV/m) ^{*1} PK: 105.2 (dBμV/m) ^{*2} PK: 110.8 (dBμV/m) ^{*3} PK: 122.2 (dBμV/m) ^{*4}

^{*1} beyond 75 MHz or more above of the band edge.

^{*2} below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above.

^{*3} below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above.

^{*4} from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.


Note: The following formula is used to convert the equipment isotropic radiated power (eirp) to field strength:

$$E = \frac{1000000 \sqrt{30P}}{3} \mu\text{V/m, where } P \text{ is the eirp (Watts).}$$

6 Test Arrangements

6.1 RF Output Power

6.1.1 Test Setup




6.1.2 Test Procedure

Method PM is used to perform output power measurement, trigger and gating function of wide band power meter is enabled to measure max output power of TX on burst and set the detector to average. Duty factor is not added to measured value.

6.2 Power Spectral Density

6.2.1 Test Setup



6.2.2 Test Procedure

For specified measurement bandwidth 1 MHz:

Method SA-1

- Set span to encompass the entire emission bandwidth (EBW) of the signal.
- Set RBW = 1 MHz, Set VBW $\geq$ 3 MHz, Detector = RMS
- Sweep points $\geq [2 \times \text{span} / \text{RBW}]$. (This gives bin-to-bin spacing $\leq \text{RBW} / 2$, so that narrowband signals are not lost between frequency bins.)
- Sweep time = auto, trigger set to "free run".
- Trace average at least 100 traces in power averaging mode.
- Record the max value

For specified measurement bandwidth 1 MHz:

Method SA-2

- Set span to encompass the entire emission bandwidth (EBW) of the signal.
- Set RBW = 1 MHz, Set VBW $\geq$ 3 MHz, Detector = RMS
- Sweep points $\geq [2 \times \text{span} / \text{RBW}]$. (This gives bin-to-bin spacing $\leq \text{RBW} / 2$, so that narrowband signals are not lost between frequency bins.)
- Sweep time = auto, trigger set to "free run".
- Trace average at least 100 traces in power averaging mode.
- Use the peak search function on the instrument to find the peak of the spectrum and record its value.
- Record the max value and add $10 \log (1/\text{duty cycle})$.

For specified measurement bandwidth 500 kHz:

Method SA-1

- a. Set span to encompass the entire emission bandwidth (EBW) of the signal.
- b. Set RBW = 300 kHz, Set VBW $\geq$ 1 MHz, Detector = RMS
- c. Scale the observed power level to an equivalent value in 500 kHz by adjusting (increasing) the measured power by a bandwidth correction factor (BWCF) where $BWCF = 10\log(500 \text{ kHz}/300 \text{ kHz})$
- d. Sweep points $\geq [2 \times \text{span} / \text{RBW}]$. (This gives bin-to-bin spacing $\leq \text{RBW} / 2$, so that narrowband signals are not lost between frequency bins.)
- e. Sweep time = auto, trigger set to "free run".
- f. Trace average at least 100 traces in power averaging mode.
- g. Record the max value


For specified measurement bandwidth 500 kHz:

Method SA-2

- a. Set span to encompass the entire emission bandwidth (EBW) of the signal.
- b. Set RBW = 300 kHz, Set VBW $\geq$ 1 MHz, Detector = RMS
- c. Scale the observed power level to an equivalent value in 500 kHz by adjusting (increasing) the measured power by a bandwidth correction factor (BWCF) where $BWCF = 10\log(500 \text{ kHz}/300 \text{ kHz})$
- d. Sweep points $\geq [2 \times \text{span} / \text{RBW}]$. (This gives bin-to-bin spacing $\leq \text{RBW} / 2$, so that narrowband signals are not lost between frequency bins.)
- e. Sweep time = auto, trigger set to "free run".
- f. Trace average at least 100 traces in power averaging mode.
- g. Use the peak search function on the instrument to find the peak of the spectrum and record its value.
- h. Record the max value and add $10 \log (1/\text{duty cycle})$.

6.3 6 dB Bandwidth

6.3.1 Test Setup




6.3.2 Test Procedure

- Set resolution bandwidth (RBW) = 100 kHz.
- Set the video bandwidth (VBW) $\geq 3 \times$ RBW, Detector = Peak.
- Trace mode = max hold.
- Sweep = auto couple.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

6.4 Occupied Bandwidth

6.4.1 Test Setup




6.4.2 Test Procedure

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with resolution bandwidth in the range of 1% to 5% of the anticipated emission bandwidth, and a video bandwidth at least 3x the resolution bandwidth and set the detector to Sampling. The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean power of a given emission.

6.5 AC Power Conducted Emissions

6.5.1 Test Setup



Note: 1.Support units were connected to second LISN.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

6.5.2 Test Procedure


- The EUT was placed on a 0.8 meter to the top of table and placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50 uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The frequency range from 150 kHz to 30 MHz was searched. Emission levels under (Limit – 20 dB) was not recorded.

Note: The resolution bandwidth and video bandwidth of test receiver is 9 kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15 MHz-30 MHz.


6.6 Unwanted Emissions below 1 GHz

6.6.1 Test Setup

For Radiated emission below 30 MHz



For Radiated emission above 30 MHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

6.6.2 Test Procedure

For Radiated emission below 30 MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Parallel, perpendicular, and ground-parallel orientations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode, except for the frequency band (9 kHz to 90 kHz and 110 kHz to 490 kHz) set to average detect function and peak detect function.

Notes:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 200 Hz at frequency below 150 kHz.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9 kHz or 10 kHz at frequency (150 kHz to 30 MHz).
3. All modes of operation were investigated and the worst-case emissions are reported.

For Radiated emission above 30 MHz


- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.

Notes:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasi-peak detection (QP) at frequency below 1 GHz.
- 2.
3. All modes of operation were investigated and the worst-case emissions are reported.

6.7 Unwanted Emissions above 1 GHz

6.7.1 Test Setup



For the actual test configuration, please refer to the attached file (Test Setup Photo).

6.7.2 Test Procedure

- The EUT was placed on the top of a rotating table 1.5 meters above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to peak and average detects function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Notes:

- The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) and Average detection (AV) at frequency above 1 GHz.
- For fundamental and harmonic signal measurement, the resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is $\geq 1/T$ (Duty cycle $< 98\%$) or 10 Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1 GHz.
- All modes of operation were investigated and the worst-case emissions are reported.

7 Test Results of Test Item

7.1 RF Output Power

Input Power:	120 Vac, 60 Hz	Environmental Conditions:	25°C, 60% RH	Tested By:	Chris Lin
--------------	----------------	---------------------------	--------------	------------	-----------

802.11a

Chan.	Chan. Freq. (MHz)	Average Power (mW)	Average Power (dBm)	Power Limit (dBm)	Test Result
36	5180	23.659	13.74	24	Pass
40	5200	23.768	13.76	24	Pass
48	5240	23.388	13.69	24	Pass
149	5745	30.479	14.84	30	Pass
157	5785	30.761	14.88	30	Pass
165	5825	30.061	14.78	30	Pass

Notes:

1. For U-NII-1, the antenna gain is 3.41 dBi < 6 dBi, so the output power limit shall not be reduced.
2. For U-NII-3, the antenna gain is 3.41 dBi < 6 dBi, so the output power limit shall not be reduced.

802.11n (HT20)

Chan.	Chan. Freq. (MHz)	Average Power (mW)	Average Power (dBm)	Power Limit (dBm)	Test Result
36	5180	21.928	13.41	24	Pass
40	5200	22.646	13.55	24	Pass
48	5240	21.827	13.39	24	Pass
149	5745	28.907	14.61	30	Pass
157	5785	28.445	14.54	30	Pass
165	5825	28.249	14.51	30	Pass

Notes:

1. For U-NII-1, the antenna gain is 3.41 dBi < 6 dBi, so the output power limit shall not be reduced.
2. For U-NII-3, the antenna gain is 3.41 dBi < 6 dBi, so the output power limit shall not be reduced.

802.11n (HT40)

Chan.	Chan. Freq. (MHz)	Average Power (mW)	Average Power (dBm)	Power Limit (dBm)	Test Result
38	5190	22.594	13.54	24	Pass
46	5230	23.067	13.63	24	Pass
151	5755	29.107	14.64	30	Pass
159	5795	28.774	14.59	30	Pass

Notes:

1. For U-NII-1, the antenna gain is 3.41 dBi < 6 dBi, so the output power limit shall not be reduced.
2. For U-NII-3, the antenna gain is 3.41 dBi < 6 dBi, so the output power limit shall not be reduced.

802.11ac (VHT20)

Chan.	Chan. Freq. (MHz)	Average Power (mW)	Average Power (dBm)	Power Limit (dBm)	Test Result
36	5180	22.961	13.61	24	Pass
40	5200	23.227	13.66	24	Pass
48	5240	23.227	13.66	24	Pass
149	5745	29.992	14.77	30	Pass
157	5785	29.444	14.69	30	Pass
165	5825	29.512	14.70	30	Pass

Notes:

1. For U-NII-1, the antenna gain is 3.41 dBi < 6 dBi, so the output power limit shall not be reduced.
2. For U-NII-3, the antenna gain is 3.41 dBi < 6 dBi, so the output power limit shall not be reduced.

802.11ac (VHT40)

Chan.	Chan. Freq. (MHz)	Average Power (mW)	Average Power (dBm)	Power Limit (dBm)	Test Result
38	5190	23.121	13.64	24	Pass
46	5230	23.55	13.72	24	Pass
151	5755	30.13	14.79	30	Pass
159	5795	29.512	14.70	30	Pass

Notes:

1. For U-NII-1, the antenna gain is 3.41 dBi < 6 dBi, so the output power limit shall not be reduced.
2. For U-NII-3, the antenna gain is 3.41 dBi < 6 dBi, so the output power limit shall not be reduced.

802.11ac (VHT80)

Chan.	Chan. Freq. (MHz)	Average Power (mW)	Average Power (dBm)	Power Limit (dBm)	Test Result
42	5210	24.044	13.81	24	Pass
155	5775	31.55	14.99	30	Pass

Notes:

1. For U-NII-1, the antenna gain is 3.41 dBi < 6 dBi, so the output power limit shall not be reduced.
2. For U-NII-3, the antenna gain is 3.41 dBi < 6 dBi, so the output power limit shall not be reduced.

7.2 Power Spectral Density

Input Power:	120 Vac, 60 Hz	Environmental Conditions:	25°C, 60% RH	Tested By:	Chris Lin
--------------	----------------	---------------------------	--------------	------------	-----------

802.11a

Chan.	Chan. Freq. (MHz)	PSD (dBm/MHz)	Max. PSD Limit (dBm/MHz)	Test Result
36	5180	0.86	11	Pass
40	5200	0.74	11	Pass
48	5240	0.78	11	Pass

Note: For U-NII-1, the antenna gain is 3.41 dBi < 6dBi, so the power density limit shall not be reduced.

802.11ac (VHT20)

Chan.	Chan. Freq. (MHz)	PSD (dBm/MHz)	Max. PSD Limit (dBm/MHz)	Test Result
36	5180	0.67	11	Pass
40	5200	0.44	11	Pass
48	5240	0.62	11	Pass

Note: For U-NII-1, the antenna gain is 3.41 dBi < 6dBi, so the power density limit shall not be reduced.

802.11ac (VHT40)

Chan.	Chan. Freq. (MHz)	PSD w/o Duty Factor (dBm/MHz)	Duty Factor (dB)	PSD (dBm/MHz)	Max. PSD Limit (dBm/MHz)	Test Result
38	5190	-1.96	0.12	-1.84	11	Pass
46	5230	-2.01	0.12	-1.89	11	Pass

Note: For U-NII-1, the antenna gain is 3.41 dBi < 6dBi, so the power density limit shall not be reduced.

802.11ac (VHT80)

Chan.	Chan. Freq. (MHz)	PSD w/o Duty Factor (dBm/MHz)	Duty Factor (dB)	PSD (dBm/MHz)	Max. PSD Limit (dBm/MHz)	Test Result
42	5210	-5.13	0.25	-4.88	11	Pass

Note: For U-NII-1, the antenna gain is 3.41 dBi < 6dBi, so the power density limit shall not be reduced.

802.11a

Chan.	Chan. Freq. (MHz)	PSD (dBm/300kHz)	PSD (dBm/500kHz)	PSD Limit (dBm/500kHz)	Test Result
149	5745	-6.49	-4.27	30	Pass
157	5785	-6.47	-4.25	30	Pass
165	5825	-6.48	-4.26	30	Pass

Note: For U-NII-3, the antenna gain is 3.41 dBi < 6 dBi, so the power density limit shall not be reduced.

802.11ac (VHT20)

Chan.	Chan. Freq. (MHz)	PSD (dBm/300kHz)	PSD (dBm/500kHz)	PSD Limit (dBm/500kHz)	Test Result
149	5745	-6.37	-4.15	30	Pass
157	5785	-7.17	-4.95	30	Pass
165	5825	-6.68	-4.46	30	Pass

Note: For U-NII-3, the antenna gain is 3.41 dBi < 6 dBi, so the power density limit shall not be reduced.

802.11ac (VHT40)

Chan.	Chan. Freq. (MHz)	PSD w/o Duty Factor (dBm/300kHz)	Duty Factor (dB)	PSD (dBm/500kHz)	PSD Limit (dBm/500kHz)	Test Result
151	5755	-10.57	0.12	-8.23	30	Pass
159	5795	-10.93	0.12	-8.59	30	Pass


Note: For U-NII-3, the antenna gain is 3.41 dBi < 6 dBi, so the power density limit shall not be reduced.

802.11ac (VHT80)


Chan.	Chan. Freq. (MHz)	PSD w/o Duty Factor (dBm/300kHz)	Duty Factor (dB)	PSD (dBm/500kHz)	PSD Limit (dBm/500kHz)	Test Result
155	5775	-14.43	0.25	-11.96	30	Pass

Note: For U-NII-3, the antenna gain is 3.41 dBi < 6 dBi, so the power density limit shall not be reduced.


Spectrum Plot of Maximum Value




802.11a : CH 36




802.11ac (VHT20) : CH 36




802.11ac (VHT40) : CH 38



802.11ac (VHT80) : CH 42





802.11a : CH 157



802.11ac (VHT20) : CH 149

Spectrum Plot of Maximum Value



7.3 6 dB Bandwidth

Input Power:	120 Vac, 60 Hz	Environmental Conditions:	25°C, 60% RH	Tested By:	Chris Lin
--------------	----------------	---------------------------	--------------	------------	-----------

802.11a

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Minimum Limit (MHz)	Test Result
149	5745	15.18	0.5	Pass
157	5785	15.18	0.5	Pass
165	5825	15.18	0.5	Pass

802.11ac (VHT20)

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Minimum Limit (MHz)	Test Result
149	5745	15.16	0.5	Pass
157	5785	15.19	0.5	Pass
165	5825	15.17	0.5	Pass





802.11ac (VHT40)

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Minimum Limit (MHz)	Test Result
151	5755	35.15	0.5	Pass
159	5795	35.27	0.5	Pass

802.11ac (VHT80)

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Minimum Limit (MHz)	Test Result
155	5775	75.4	0.5	Pass

Spectrum Plot of Minimum Value



7.4 Occupied Bandwidth

Input Power:	120 Vac, 60 Hz	Environmental Conditions:	25°C, 60% RH	Tested By:	Chris Lin
--------------	----------------	---------------------------	--------------	------------	-----------

802.11a

Channel	Frequency (MHz)	Occupied Bandwidth (MHz)
36	5180	16.68
40	5200	16.68
48	5240	16.68
149	5745	16.8
157	5785	16.68
165	5825	16.68

802.11ac (VHT20)

Channel	Frequency (MHz)	Occupied Bandwidth (MHz)
36	5180	17.64
40	5200	17.64
48	5240	17.64
149	5745	17.76
157	5785	17.64
165	5825	17.64





802.11ac (VHT40)

Channel	Frequency (MHz)	Occupied Bandwidth (MHz)
38	5190	36.24
46	5230	36.24
151	5755	36.12
159	5795	36


802.11ac (VHT80)

Channel	Frequency (MHz)	Occupied Bandwidth (MHz)
42	5210	75.36
155	5775	75.36


Spectrum Plot of Maximum Value




Spectrum Plot for nearby DFS band (DFS is required, if 99% OCP straddle into U-NII-2A)




802.11a : CH 48



802.11ac (VHT20) : CH 48




802.11ac (VHT40) : CH 46




802.11ac (VHT80) : CH 42


Spectrum Plot for nearby DFS band (DFS is required, if 99% OCP straddle into U-NII-2C)




802.11a : CH 149



802.11ac (VHT20) : CH 149



802.11ac (VHT40) : CH 151



802.11ac (VHT80) : CH 155


7.5 AC Power Conducted Emissions

RF Mode	802.11ac (VHT80)	Channel	CH 155 : 5775 MHz
Frequency Range	150 kHz ~ 30 MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 67 % RH
Tested By	Adair Peng		

Phase Of Power : Line (L)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.47400	10.21	42.37	33.07	52.58	43.28	56.44	46.44	-3.86	-3.16
2	1.00600	10.27	25.42	15.04	35.69	25.31	56.00	46.00	-20.31	-20.69
3	1.41400	10.31	24.14	14.37	34.45	24.68	56.00	46.00	-21.55	-21.32
4	3.14200	10.42	21.95	13.11	32.37	23.53	56.00	46.00	-23.63	-22.47
5	4.10200	10.45	22.19	13.54	32.64	23.99	56.00	46.00	-23.36	-22.01
6	13.82200	10.54	22.93	10.45	33.47	20.99	60.00	50.00	-26.53	-29.01

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




RF Mode	802.11ac (VHT80)	Channel	CH 155 : 5775 MHz
Frequency Range	150 kHz ~ 30 MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 67 % RH
Tested By	Adair Peng		

Phase Of Power : Neutral (N)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.48600	10.24	43.07	32.93	53.31	43.17	56.24	46.24	-2.93	-3.07
2	0.73400	10.27	28.07	17.49	38.34	27.76	56.00	46.00	-17.66	-18.24
3	0.99000	10.31	29.66	19.91	39.97	30.22	56.00	46.00	-16.03	-15.78
4	1.37000	10.33	29.61	20.88	39.94	31.21	56.00	46.00	-16.06	-14.79
5	2.27400	10.39	26.46	18.45	36.85	28.84	56.00	46.00	-19.15	-17.16
6	14.51800	10.73	22.87	12.51	33.60	23.24	60.00	50.00	-26.40	-26.76

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




7.6 Unwanted Emissions below 1 GHz

RF Mode	802.11ac (VHT80)	Channel	CH 155 : 5775 MHz
Frequency Range	30 MHz ~ 1 GHz	Detector Function & Bandwidth	QP: RB=120kHz, DET=Quasi-Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	24.1 °C, 74.3 % RH
Tested By	Rex Wang		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	38.73	28.7 QP	40.0	-11.3	1.00 H	31	10.2	18.5
2	151.25	28.9 QP	43.5	-14.6	2.00 H	303	9.3	19.6
3	285.11	34.9 QP	46.0	-11.1	1.00 H	138	14.4	20.5
4	664.38	30.5 QP	46.0	-15.5	1.00 H	39	1.5	29.0
5	941.80	34.5 QP	46.0	-11.5	1.00 H	341	1.5	33.0
6	989.33	33.6 QP	54.0	-20.4	1.00 H	152	0.3	33.3

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The frequency range 9 kHz ~ 30 MHz: all emissions are more than 20 dB below the limit, therefore do not be recorded in this report.




RF Mode	802.11ac (VHT80)	Channel	CH 155 : 5775 MHz
Frequency Range	30 MHz ~ 1 GHz	Detector Function & Bandwidth	QP: RB=120kHz, DET=Quasi-Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	24.1 °C, 74.3 % RH
Tested By	Rex Wang		

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	55.22	32.2 QP	40.0	-7.8	1.00 V	193	13.0	19.2
2	183.26	31.8 QP	43.5	-11.7	1.00 V	333	14.0	17.8
3	272.50	32.6 QP	46.0	-13.4	1.00 V	117	12.6	20.0
4	493.66	31.2 QP	46.0	-14.8	1.00 V	181	5.5	25.7
5	803.09	31.4 QP	46.0	-14.6	1.00 V	130	0.0	31.4
6	988.36	34.5 QP	54.0	-19.5	1.00 V	35	1.2	33.3

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The frequency range 9 kHz ~ 30 MHz: all emissions are more than 20 dB below the limit, therefore do not be recorded in this report.



7.7 Unwanted Emissions above 1 GHz

RF Mode	802.11a	Channel	CH 36 : 5180 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 67 % RH
Tested By	Rex Wang		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	67.7 PK	74.0	-6.3	2.29 H	291	46.0	21.7
2	5150.00	51.5 AV	54.0	-2.5	2.29 H	291	29.8	21.7
3	*5180.00	108.8 PK			2.29 H	291	66.8	42.0
4	*5180.00	98.8 AV			2.29 H	291	56.8	42.0
5	#10360.00	63.5 PK	68.2	-4.7	2.02 H	345	39.1	24.4
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	73.2 PK	74.0	-0.8	1.20 V	62	51.5	21.7
2	5150.00	53.4 AV	54.0	-0.6	1.20 V	62	31.7	21.7
3	*5180.00	110.7 PK			1.20 V	62	68.7	42.0
4	*5180.00	100.6 AV			1.20 V	62	58.6	42.0
5	#10360.00	63.7 PK	68.2	-4.5	1.56 V	102	39.3	24.4

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.

RF Mode	802.11a	Channel	CH 40 : 5200 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 67 % RH
Tested By	Rex Wang		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	65.3 PK	74.0	-8.7	2.19 H	299	43.6	21.7
2	5150.00	51.3 AV	54.0	-2.7	2.19 H	299	29.6	21.7
3	*5200.00	112.5 PK			2.19 H	299	70.5	42.0
4	*5200.00	102.8 AV			2.19 H	299	60.8	42.0
5	#10400.00	63.4 PK	68.2	-4.8	2.00 H	347	38.7	24.7
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	67.3 PK	74.0	-6.7	1.09 V	65	45.6	21.7
2	5150.00	53.1 AV	54.0	-0.9	1.09 V	65	31.4	21.7
3	*5200.00	113.0 PK			1.09 V	65	71.0	42.0
4	*5200.00	103.2 AV			1.09 V	65	61.2	42.0
5	#10400.00	63.6 PK	68.2	-4.6	1.55 V	104	38.9	24.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.

RF Mode	802.11a	Channel	CH 48 : 5240 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 67 % RH
Tested By	Rex Wang		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5240.00	114.8 PK			2.19 H	299	73.1	41.7
2	*5240.00	104.8 AV			2.19 H	299	63.1	41.7
3	5350.00	60.9 PK	74.0	-13.1	2.19 H	299	39.5	21.4
4	5350.00	47.3 AV	54.0	-6.7	2.19 H	299	25.9	21.4
5	#10480.00	63.7 PK	68.2	-4.5	2.04 H	346	38.9	24.8
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5240.00	116.5 PK			1.31 V	97	74.8	41.7
2	*5240.00	106.4 AV			1.31 V	97	64.7	41.7
3	5350.00	61.1 PK	74.0	-12.9	1.31 V	97	39.7	21.4
4	5350.00	47.4 AV	54.0	-6.6	1.31 V	97	26.0	21.4
5	#10480.00	64.0 PK	68.2	-4.2	1.57 V	104	39.2	24.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.

RF Mode	802.11a	Channel	CH 149 : 5745 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 67 % RH
Tested By	Adair Peng		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5640.00	60.9 PK	68.2	-7.3	2.35 H	300	39.0	21.9
2	*5745.00	113.4 PK			2.35 H	300	71.1	42.3
3	*5745.00	103.5 AV			2.35 H	300	61.2	42.3
4	#5987.60	61.6 PK	68.2	-6.6	2.35 H	300	39.0	22.6
5	11490.00	65.0 PK	74.0	-9.0	1.97 H	350	38.8	26.2
6	11490.00	51.5 AV	54.0	-2.5	1.97 H	350	25.3	26.2
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5628.40	60.3 PK	68.2	-7.9	2.17 V	100	38.5	21.8
2	*5745.00	115.0 PK			2.17 V	100	72.7	42.3
3	*5745.00	105.2 AV			2.17 V	100	62.9	42.3
4	#5999.60	61.2 PK	68.2	-7.0	2.17 V	100	38.6	22.6
5	11490.00	65.2 PK	74.0	-8.8	1.60 V	115	39.0	26.2
6	11490.00	51.9 AV	54.0	-2.1	1.60 V	115	25.7	26.2

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.

RF Mode	802.11a	Channel	CH 157 : 5785 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 67 % RH
Tested By	Adair Peng		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5611.20	60.8 PK	68.2	-7.4	2.28 H	293	39.1	21.7
2	*5785.00	113.1 PK			2.28 H	293	70.8	42.3
3	*5785.00	102.9 AV			2.28 H	293	60.6	42.3
4	#5980.80	61.7 PK	68.2	-6.5	2.28 H	293	39.1	22.6
5	11570.00	64.5 PK	74.0	-9.5	2.00 H	349	38.6	25.9
6	11570.00	50.9 AV	54.0	-3.1	2.00 H	349	25.0	25.9
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5618.80	61.2 PK	68.2	-7.0	2.17 V	90	39.4	21.8
2	*5785.00	114.5 PK			2.17 V	90	72.2	42.3
3	*5785.00	104.5 AV			2.17 V	90	62.2	42.3
4	#5996.80	61.9 PK	68.2	-6.3	2.17 V	90	39.3	22.6
5	11570.00	64.7 PK	74.0	-9.3	1.57 V	119	38.8	25.9
6	11570.00	51.1 AV	54.0	-2.9	1.57 V	119	25.2	25.9

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.

RF Mode	802.11a	Channel	CH 165 : 5825 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 67 % RH
Tested By	Adair Peng		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5649.20	60.0 PK	68.2	-8.2	2.38 H	298	38.0	22.0
2	*5825.00	111.8 PK			2.38 H	298	69.4	42.4
3	*5825.00	102.0 AV			2.38 H	298	59.6	42.4
4	#5996.80	61.8 PK	68.2	-6.4	2.38 H	298	39.2	22.6
5	11650.00	64.3 PK	74.0	-9.7	2.05 H	346	38.7	25.6
6	11650.00	50.6 AV	54.0	-3.4	2.05 H	346	25.0	25.6
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5606.80	61.0 PK	68.2	-7.2	2.23 V	93	39.3	21.7
2	*5825.00	113.7 PK			2.23 V	93	71.3	42.4
3	*5825.00	103.8 AV			2.23 V	93	61.4	42.4
4	#5995.60	61.0 PK	68.2	-7.2	2.23 V	93	38.4	22.6
5	11650.00	64.4 PK	74.0	-9.6	1.54 V	115	38.8	25.6
6	11650.00	50.9 AV	54.0	-3.1	1.54 V	115	25.3	25.6

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	802.11ac (VHT20)	Channel	CH 36 : 5180 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 67 % RH
Tested By	Rex Wang		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	68.5 PK	74.0	-5.5	2.29 H	298	46.8	21.7
2	5150.00	52.3 AV	54.0	-1.7	2.29 H	298	30.6	21.7
3	*5180.00	109.8 PK			2.29 H	298	67.8	42.0
4	*5180.00	100.0 AV			2.29 H	298	58.0	42.0
5	#10360.00	63.1 PK	68.2	-5.1	2.03 H	344	38.7	24.4
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	71.8 PK	74.0	-2.2	1.16 V	74	50.1	21.7
2	5150.00	53.7 AV	54.0	-0.3	1.16 V	74	32.0	21.7
3	*5180.00	110.5 PK			1.16 V	74	68.5	42.0
4	*5180.00	100.4 AV			1.16 V	74	58.4	42.0
5	#10360.00	63.4 PK	68.2	-4.8	1.58 V	105	39.0	24.4

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	802.11ac (VHT20)	Channel	CH 40 : 5200 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 67 % RH
Tested By	Rex Wang		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	66.0 PK	74.0	-8.0	2.31 H	299	44.3	21.7
2	5150.00	52.3 AV	54.0	-1.7	2.31 H	299	30.6	21.7
3	*5200.00	112.7 PK			2.31 H	299	70.7	42.0
4	*5200.00	103.2 AV			2.31 H	299	61.2	42.0
5	#10400.00	63.3 PK	68.2	-4.9	2.04 H	344	38.6	24.7
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	68.5 PK	74.0	-5.5	1.17 V	50	46.8	21.7
2	5150.00	53.2 AV	54.0	-0.8	1.17 V	50	31.5	21.7
3	*5200.00	113.2 PK			1.17 V	50	71.2	42.0
4	*5200.00	103.7 AV			1.17 V	50	61.7	42.0
5	#10400.00	63.5 PK	68.2	-4.7	1.52 V	103	38.8	24.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	802.11ac (VHT20)	Channel	CH 48 : 5240 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 67 % RH
Tested By	Rex Wang		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5240.00	114.9 PK			2.21 H	296	73.2	41.7
2	*5240.00	104.6 AV			2.21 H	296	62.9	41.7
3	5350.00	60.8 PK	74.0	-13.2	2.21 H	296	39.4	21.4
4	5350.00	47.3 AV	54.0	-6.7	2.21 H	296	25.9	21.4
5	#10480.00	63.5 PK	68.2	-4.7	2.05 H	346	38.7	24.8
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5240.00	116.2 PK			1.16 V	98	74.5	41.7
2	*5240.00	106.2 AV			1.16 V	98	64.5	41.7
3	5350.00	61.0 PK	74.0	-13.0	1.16 V	98	39.6	21.4
4	5350.00	47.4 AV	54.0	-6.6	1.16 V	98	26.0	21.4
5	#10480.00	63.7 PK	68.2	-4.5	1.55 V	104	38.9	24.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.

RF Mode	802.11ac (VHT20)	Channel	CH 149 : 5745 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 67 % RH
Tested By	Adair Peng		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5631.20	60.9 PK	68.2	-7.3	2.45 H	303	39.1	21.8
2	*5745.00	113.0 PK			2.45 H	303	70.7	42.3
3	*5745.00	103.2 AV			2.45 H	303	60.9	42.3
4	#5937.20	61.5 PK	68.2	-6.7	2.45 H	303	39.2	22.3
5	11490.00	64.8 PK	74.0	-9.2	2.00 H	342	38.6	26.2
6	11490.00	51.5 AV	54.0	-2.5	2.00 H	342	25.3	26.2
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5643.20	60.8 PK	68.2	-7.4	2.67 V	77	38.8	22.0
2	*5745.00	114.8 PK			2.67 V	77	72.5	42.3
3	*5745.00	104.5 AV			2.67 V	77	62.2	42.3
4	#5986.40	61.2 PK	68.2	-7.0	2.67 V	77	38.6	22.6
5	11490.00	65.2 PK	74.0	-8.8	1.50 V	117	39.0	26.2
6	11490.00	51.7 AV	54.0	-2.3	1.50 V	117	25.5	26.2

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.

RF Mode	802.11ac (VHT20)	Channel	CH 157 : 5785 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 67 % RH
Tested By	Adair Peng		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5601.20	60.3 PK	68.2	-7.9	2.50 H	299	38.6	21.7
2	*5785.00	111.6 PK			2.50 H	299	69.3	42.3
3	*5785.00	101.6 AV			2.50 H	299	59.3	42.3
4	#5996.40	61.5 PK	68.2	-6.7	2.50 H	299	38.9	22.6
5	11570.00	64.6 PK	74.0	-9.4	1.93 H	347	38.7	25.9
6	11570.00	51.1 AV	54.0	-2.9	1.93 H	347	25.2	25.9
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5648.40	60.8 PK	68.2	-7.4	2.61 V	104	38.8	22.0
2	*5785.00	113.7 PK			2.61 V	104	71.4	42.3
3	*5785.00	103.3 AV			2.61 V	104	61.0	42.3
4	#5950.80	61.9 PK	68.2	-6.3	2.61 V	104	39.5	22.4
5	11570.00	64.7 PK	74.0	-9.3	1.48 V	112	38.8	25.9
6	11570.00	51.3 AV	54.0	-2.7	1.48 V	112	25.4	25.9

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.

RF Mode	802.11ac (VHT20)	Channel	CH 165 : 5825 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 67 % RH
Tested By	Adair Peng		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5612.40	61.7 PK	68.2	-6.5	2.25 H	306	40.0	21.7
2	*5825.00	110.9 PK			2.25 H	360	68.5	42.4
3	*5825.00	100.8 AV			2.25 H	360	58.4	42.4
4	#5986.00	61.6 PK	68.2	-6.6	2.25 H	306	39.0	22.6
5	11650.00	64.2 PK	74.0	-9.8	1.57 H	111	38.6	25.6
6	11650.00	50.5 AV	54.0	-3.5	1.57 H	111	24.9	25.6
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5622.00	60.8 PK	68.2	-7.4	2.14 V	75	39.0	21.8
2	*5825.00	112.3 PK			2.14 V	75	69.9	42.4
3	*5825.00	102.4 AV			2.14 V	75	60.0	42.4
4	#5967.60	61.7 PK	68.2	-6.5	2.14 V	75	39.3	22.4
5	11650.00	64.4 PK	74.0	-9.6	1.54 V	110	38.8	25.6
6	11650.00	50.8 AV	54.0	-3.2	1.54 V	110	25.2	25.6

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.

RF Mode	802.11ac (VHT40)	Channel	CH 38 : 5190 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=1 kHz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 67 % RH
Tested By	Rex Wang		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	70.1 PK	74.0	-3.9	2.32 H	296	48.4	21.7
2	5150.00	53.0 AV	54.0	-1.0	2.32 H	296	31.3	21.7
3	*5190.00	105.8 PK			2.32 H	296	63.8	42.0
4	*5190.00	95.7 AV			2.32 H	296	53.7	42.0
5	#10380.00	63.1 PK	68.2	-5.1	1.96 H	347	38.6	24.5
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	72.5 PK	74.0	-1.5	1.00 V	95	50.8	21.7
2	5150.00	53.8 AV	54.0	-0.2	1.00 V	95	32.1	21.7
3	*5190.00	106.5 PK			1.00 V	95	64.5	42.0
4	*5190.00	96.3 AV			1.00 V	95	54.3	42.0
5	#10380.00	63.4 PK	68.2	-4.8	1.57 V	104	38.9	24.5

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	802.11ac (VHT40)	Channel	CH 46 : 5230 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=1 kHz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 67 % RH
Tested By	Rex Wang		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	65.9 PK	74.0	-8.1	2.23 H	302	44.2	21.7
2	5150.00	52.9 AV	54.0	-1.1	2.23 H	302	31.2	21.7
3	*5230.00	110.1 PK			2.23 H	302	68.3	41.8
4	*5230.00	100.1 AV			2.23 H	302	58.3	41.8
5	5350.00	61.0 PK	74.0	-13.0	2.23 H	302	39.6	21.4
6	5350.00	48.5 AV	54.0	-5.5	2.23 H	302	27.1	21.4
7	#10460.00	63.5 PK	68.2	-4.7	2.03 H	345	38.7	24.8
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	68.2 PK	74.0	-5.8	1.16 V	74	46.5	21.7
2	5150.00	53.5 AV	54.0	-0.5	1.16 V	74	31.8	21.7
3	*5230.00	111.7 PK			1.16 V	74	69.9	41.8
4	*5230.00	101.3 AV			1.16 V	74	59.5	41.8
5	5350.00	62.2 PK	74.0	-11.8	1.16 V	74	40.8	21.4
6	5350.00	48.7 AV	54.0	-5.3	1.16 V	74	27.3	21.4
7	#10460.00	63.7 PK	68.2	-4.5	1.58 V	105	38.9	24.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	802.11ac (VHT40)	Channel	CH 151 : 5755 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=1 kHz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 67 % RH
Tested By	Adair Peng		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5647.60	64.3 PK	68.2	-3.9	2.28 H	297	42.3	22.0
2	*5755.00	110.8 PK			2.28 H	297	68.5	42.3
3	*5755.00	100.2 AV			2.28 H	297	57.9	42.3
4	#5942.00	61.6 PK	68.2	-6.6	2.28 H	297	39.3	22.3
5	11510.00	64.8 PK	74.0	-9.2	1.91 H	353	38.6	26.2
6	11510.00	51.2 AV	54.0	-2.8	1.91 H	353	25.0	26.2
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5650.00	65.6 PK	68.2	-2.6	2.51 V	85	43.6	22.0
2	*5755.00	112.2 PK			2.51 V	85	69.9	42.3
3	*5755.00	102.0 AV			2.51 V	85	59.7	42.3
4	#5987.60	62.0 PK	68.2	-6.2	2.51 V	85	39.4	22.6
5	11510.00	65.0 PK	74.0	-9.0	1.60 V	113	38.8	26.2
6	11510.00	51.5 AV	54.0	-2.5	1.60 V	113	25.3	26.2

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.

RF Mode	802.11ac (VHT40)	Channel	CH 159 : 5795 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=1 kHz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 67 % RH
Tested By	Adair Peng		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5643.20	61.3 PK	68.2	-6.9	2.39 H	298	39.3	22.0
2	*5795.00	110.1 PK			2.39 H	298	67.8	42.3
3	*5795.00	99.9 AV			2.39 H	298	57.6	42.3
4	#5933.20	61.7 PK	68.2	-6.5	2.39 H	298	39.4	22.3
5	11590.00	64.4 PK	74.0	-9.6	1.93 H	345	38.7	25.7
6	11590.00	50.8 AV	54.0	-3.2	1.93 H	345	25.1	25.7
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5647.60	61.9 PK	68.2	-6.3	2.59 V	93	39.9	22.0
2	*5795.00	112.6 PK			2.59 V	93	70.3	42.3
3	*5795.00	101.7 AV			2.59 V	93	59.4	42.3
4	#5928.00	62.8 PK	68.2	-5.4	2.59 V	93	40.5	22.3
5	11590.00	64.6 PK	74.0	-9.4	1.54 V	117	38.9	25.7
6	11590.00	51.0 AV	54.0	-3.0	1.54 V	117	25.3	25.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.

RF Mode	802.11ac (VHT80)	Channel	CH 42 : 5210 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=3 kHz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 67 % RH
Tested By	Rex Wang		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	68.4 PK	74.0	-5.6	2.10 H	301	46.7	21.7
2	5150.00	51.3 AV	54.0	-2.7	2.10 H	301	29.6	21.7
3	*5210.00	101.7 PK			2.10 H	301	59.7	42.0
4	*5210.00	91.4 AV			2.10 H	301	49.4	42.0
5	#10420.00	63.3 PK	68.2	-4.9	2.00 H	344	38.6	24.7
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	71.4 PK	74.0	-2.6	1.13 V	91	49.7	21.7
2	5150.00	53.0 AV	54.0	-1.0	1.13 V	91	31.3	21.7
3	*5210.00	104.3 PK			1.13 V	91	62.3	42.0
4	*5210.00	93.7 AV			1.13 V	91	51.7	42.0
5	#10420.00	63.4 PK	68.2	-4.8	1.54 V	103	38.7	24.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.

RF Mode	802.11ac (VHT80)	Channel	CH 155 : 5775 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=3 kHz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 67 % RH
Tested By	Adair Peng		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5645.60	65.3 PK	68.2	-2.9	2.46 H	296	43.3	22.0
2	*5775.00	105.1 PK			2.46 H	296	62.8	42.3
3	*5775.00	94.8 AV			2.46 H	296	52.5	42.3
4	#5934.40	62.1 PK	68.2	-6.1	2.46 H	296	39.8	22.3
5	11550.00	64.6 PK	74.0	-9.4	1.92 H	341	38.6	26.0
6	11550.00	51.6 AV	54.0	-2.4	1.92 H	341	25.6	26.0
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5642.80	67.2 PK	68.2	-1.0	2.49 V	56	45.2	22.0
2	*5775.00	106.9 PK			2.49 V	56	64.6	42.3
3	*5775.00	96.1 AV			2.49 V	56	53.8	42.3
4	#5929.20	63.5 PK	68.2	-4.7	2.49 V	56	41.2	22.3
5	11550.00	64.9 PK	74.0	-9.1	1.52 V	110	38.9	26.0
6	11550.00	51.9 AV	54.0	-2.1	1.52 V	110	25.9	26.0


Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.


Plot of Band Edge

Frequency Range	4.5 GHz ~ 5.46 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
-----------------	--------------------	-------------------------------	--


802.11a Channel 36




802.11a Channel 40




Horizontal (Peak)



Horizontal (Average)




Vertical (Peak)




Vertical (Average)


802.11a Channel 48




Horizontal (Peak)



Horizontal (Average)




Vertical (Peak)




Vertical (Average)

Frequency Range	5.6 GHz ~ 6 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak
-----------------	-----------------	-------------------------------	----------------------------------

802.11a Channel 149




Horizontal (Peak)




Vertical (Peak)

802.11a Channel 157




Horizontal (Peak)




Vertical (Peak)

802.11a Channel 165




Horizontal (Peak)




Vertical (Peak)

Frequency Range	4.5 GHz ~ 5.46 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
-----------------	--------------------	-------------------------------	--


802.11ac (VHT20) Channel 36




Horizontal (Peak)



Horizontal (Average)




Vertical (Peak)




Vertical (Average)


802.11ac (VHT20) Channel 40




Horizontal (Peak)



Horizontal (Average)




Vertical (Peak)




Vertical (Average)


802.11ac (VHT20) Channel 48




Horizontal (Peak)



Horizontal (Average)




Vertical (Peak)




Vertical (Average)

Frequency Range	5.6 GHz ~ 6 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak
-----------------	-----------------	-------------------------------	----------------------------------

802.11ac (VHT20) Channel 149




Horizontal (Peak)




Vertical (Peak)

802.11ac (VHT20) Channel 157




Horizontal (Peak)




Vertical (Peak)

802.11ac (VHT20) Channel 165




Horizontal (Peak)




Vertical (Peak)

Frequency Range	4.5 GHz ~ 5.46 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=1 kHz, DET=Peak
-----------------	--------------------	-------------------------------	--


802.11ac (VHT40) Channel 38




Horizontal (Peak)




Horizontal (Average)




Vertical (Peak)




Vertical (Average)

802.11ac (VHT40) Channel 46


Horizontal (Peak)



Horizontal (Average)




Vertical (Peak)




Vertical (Average)

Frequency Range	5.6 GHz ~ 6 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak
-----------------	-----------------	-------------------------------	----------------------------------

802.11ac (VHT40) Channel 151




Horizontal (Peak)




Vertical (Peak)

802.11ac (VHT40) Channel 159




Horizontal (Peak)




Vertical (Peak)

Frequency Range	4.5 GHz ~ 5.46 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=2 kHz, DET=Peak
-----------------	--------------------	-------------------------------	--


802.11ac (VHT80) Channel 42




Horizontal (Peak)



Horizontal (Average)




Vertical (Peak)




Vertical (Average)

Frequency Range	5.6 GHz ~ 6 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak
-----------------	-----------------	-------------------------------	----------------------------------

802.11ac (VHT80) Channel 155



Horizontal (Peak)



Vertical (Peak)

8 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo)

9 Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Lin Kou EMC/RF Lab

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-6668565

Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety Lab

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@bureauveritas.com

Web Site: <http://ee.bureauveritas.com.tw>

The address and road map of all our labs can be found in our web site also.

--- END ---