




Intermodulation iDEN_High SMR_800_MHz
Center: 815 MHz Span: 25 MHz RBW/VBW: 100 kHz




Intermodulation iDEN_High SMR_800_MHz
Span: 30 MHz to 1 GHz RBW/VBW: 100 kHz




Intermodulation iDEN_High SMR_800_MHz
Span: 1 GHz to 10 GHz RBW/VBW: 1 MHz




Intermodulation iDEN_Apart SMR_800_MHz
Center: 815 MHz Span: 75 MHz RBW/VBW: 100 kHz



Intermodulation iDEN_Apart SMR_800_MHz
Span: 30 MHz to 1 GHz RBW/VBW: 100 kHz




Intermodulation iDEN_Apart SMR_800_MHz
Span: 1 GHz to 10 GHz RBW/VBW: 1 MHz




Intermodulation
Center: 860 MHz


APCO25_C4FM_Low SMR_800_MHz
Span: 25 MHz RBW/VBW: 100 kHz



Intermodulation APCO25_C4FM_Low SMR_800_MHz
Span: 30 MHz to 1 GHz RBW/VBW: 300 kHz




Intermodulation APCO25_C4FM_Low SMR_800_MHz
Span: 1 GHz to 10 GHz RBW/VBW: 1 MHz




Intermodulation
Center: 860 MHz

APCO25_C4FM_High
Span: 25 MHz


SMR_800_MHz
RBW/VBW: 100 kHz



Intermodulation APCO25_C4FM_High SMR_800_MHz
Span: 30 MHz to 1 GHz RBW/VBW: 300 kHz




Intermodulation APCO25_C4FM_HighSMR_800_MHz
Span: 1 GHz to 10 GHz RBW/VBW: 1 MHz




Intermodulation
Center: 860 MHz

APCO25_C4FM_Apart
Span: 75 MHz


SMR_800_MHz
RBW/VBW: 100 kHz



Intermodulation APCO25_C4FM_Apart SMR_800_MHz
Span: 30 MHz to 1 GHz RBW/VBW: 300 kHz




Intermodulation APCO25_C4FM_Apart SMR_800_MHz
Span: 1 GHz to 10 GHz RBW/VBW: 1 MHz




Intermodulation
Center: 860 MHz

APCO25_CQPSK_Low
Span: 25 MHz


SMR_800_MHz
RBW/VBW: 100 kHz



Intermodulation APCO25_CQPSK_LowSMR_800_MHz
Span: 30 MHz to 1 GHz RBW/VBW: 300 kHz




Intermodulation APCO25_CQPSK_LowSMR_800_MHz
Span: 1 GHz to 10 GHz RBW/VBW: 1 MHz




Intermodulation
Center: 860 MHz

APCO25_CQPSK_High
Span: 25 MHz


SMR_800_MHz
RBW/VBW: 100 kHz



Intermodulation APCO25_CQPSK_High SMR_800_MHz
Span: 30 MHz to 1 GHz RBW/VBW: 300 kHz




Intermodulation APCO25_CQPSK_High SMR_800_MHz
Span: 1 GHz to 10 GHz RBW/VBW: 1 MHz




Intermodulation
Center: 860 MHz

APCO25_CQPSK_Apart
Span: 75 MHz


SMR_800_MHz
RBW/VBW: 100 kHz




Intermodulation APCO25_CQPSK_Apart SMR_800_MHz
Span: 30 MHz to 1 GHz RBW/VBW: 300 kHz




Intermodulation APCO25_CQPSK_Apart SMR_800_MHz
Span: 1 GHz to 10 GHz RBW/VBW: 1 MHz




Intermodulation FM_Low SMR_800_MHz
Center: 860 MHz Span: 25 MHz RBW/VBW: 100 kHz




Intermodulation FM_Low SMR_800_MHz
Span: 30 MHz to 1 GHz RBW/VBW: 300 kHz




Intermodulation FM_Low SMR_800_MHz
Span: 1 GHz to 10 GHz RBW/VBW: 1 MHz




Intermodulation FM_High SMR_800_MHz
Center: 860 MHz Span: 25 MHz RBW/VBW: 100 kHz




Intermodulation FM_High SMR_800_MHz
Span: 30 MHz to 1 GHz RBW/VBW: 300 kHz




Intermodulation FM_High
Span: 1 GHz to 10 GHz SMR_800_MHz
RBW/VBW: 1 MHz




Intermodulation FM_Apart SMR_800_MHz
Center: 860 MHz Span: 75 MHz RBW/VBW: 100 kHz




Intermodulation FM_Apart SMR_800_MHz
Span: 30 MHz to 1 GHz RBW/VBW: 300 kHz




Intermodulation FM_Apart SMR_800_MHz
Span: 1 GHz to 10 GHz RBW/VBW: 1 MHz




Intermodulation iDEN_Low SMR_800_MHz
Center: 860 MHz Span: 25 MHz RBW/VBW: 100 kHz




Intermodulation iDEN_Low SMR_800_MHz
Span: 30 MHz to 1 GHz RBW/VBW: 300 kHz




Intermodulation iDEN_Low SMR_800_MHz
Span: 1 GHz to 10 GHz RBW/VBW: 1 MHz




Intermodulation iDEN_High SMR_800_MHz
Center: 860 MHz Span: 25 MHz RBW/VBW: 100 kHz




Intermodulation iDEN_High SMR_800_MHz
Span: 30 MHz to 1 GHz RBW/VBW: 300 kHz




Intermodulation iDEN_High SMR_800_MHz
Span: 1 GHz to 10 GHz RBW/VBW: 1 MHz




Intermodulation iDEN_Apart SMR_800_MHz
Center: 860 MHz Span: 75 MHz RBW/VBW: 100 kHz



Intermodulation iDEN_Apart SMR_800_MHz
Span: 30 MHz to 1 GHz RBW/VBW: 300 kHz



Intermodulation iDEN_Apart SMR_800_MHz
Span: 1 GHz to 10 GHz RBW/VBW: 1 MHz



7.5 Occupied Bandwidth Modulation Test

[Table of Contents; Section 1.0](#)

[Back to Emission Limits; Section 5.1.3](#)

An input/output Occupied Bandwidth test was done with modulation types: APCO25_C4FM, APCO25_CQPSK, FM and iDEN. The purpose was to determine the amount of distortion added to different types of modulation schemes by the EUT. The following plots show input signals vs. output signals.


The resolution bandwidth is reduced to 1% of the estimated emission bandwidth and the video bandwidth is set to 3 times the resolution bandwidth. The markers are moved to the -20 dB points (from the previously established center frequency level) on either side of center frequency.

Results:

Pass (see plots)


Occupied Bandwidth
Span: 25 kHz

APCO25_C4FM_Signal_In
RBW: 300 Hz VBW: 1 kHz




Occupied Bandwidth
Span: 25 kHz

APCO25_C4FM_Signal_Out
RBW: 300 Hz VBW: 1 kHz




Occupied Bandwidth
Span: 25 kHz

APCO25_CQPSK_Signal_In
RBW: 300 Hz VBW: 1 kHz




Occupied Bandwidth
Span: 25 kHz


APCO25_CQPSK_Signal_Out
RBW: 300 Hz VBW: 1 kHz




Occupied Bandwidth FM_Signal_In
Span: 25 kHz RBW: 300 Hz VBW: 1 kHz




Occupied Bandwidth FM_Signal_Out
Span: 25 kHz RBW: 300 Hz VBW: 1 kHz



Occupied Bandwidth iDEN_Signal_In
Span: 25 kHz RBW: 300 Hz VBW: 1 kHz




Occupied Bandwidth iDEN_Signal_Out
Span: 25 kHz RBW: 300 Hz VBW: 1 kHz




Occupied Bandwidth
Span: 25 kHz

APCO25_C4FM_Signal_In
RBW: 300 Hz VBW: 1 kHz




Occupied Bandwidth
Span: 25 kHz

APCO25_C4FM_Signal_Out
RBW: 300 Hz VBW: 1 kHz




Occupied Bandwidth
Span: 25 kHz

APCO25_CQPSK_Signal_In
RBW: 300 Hz VBW: 1 kHz




Occupied Bandwidth
Span: 25 kHz


APCO25_CQPSK_Signal_Out
RBW: 300 Hz VBW: 1 kHz




Occupied Bandwidth FM_Signal_In
Span: 25 kHz RBW: 300 Hz VBW: 1 kHz




Occupied Bandwidth FM_Signal_Out
Span: 25 kHz RBW: 300 Hz VBW: 1 kHz



Occupied Bandwidth iDEN_Signal_In
Span: 25 kHz RBW: 300 Hz VBW: 1 kHz



Occupied Bandwidth iDEN_Signal_Out
Span: 25 kHz RBW: 300 Hz VBW: 1 kHz



8.0

APPENDIX B

Measurement Protocol

[Table of Contents; Section 1.0](#)

[Back to Emission Limits; Section 5.1.3](#)

Measurement Protocol

Environmental conditions of the lab, (ADC)

Temperature: 21 - 26° C

Relative Humidity: 21 - 24 %

Atmospheric Pressure: 97.8 - 100.0 kPa

Test Methodology:

Emission testing is performed according to the procedures in ANSI C63.4-2003.

Measurement Uncertainty

The test system for conducted emissions is defined as the signal generator(s), the power meter, the spectrum analyzer and the coaxial cable. The equipment comprising the test systems is calibrated prior to testing the EUT.

Justification

The Equipment Under Test (EUT) is configured in a typical user arrangement in accordance with the manufacturer's instructions. A cable is connected to each available port and either terminated with a peripheral into its characteristic impedance or left un-terminated. When appropriate, the cables are manually manipulated with respect to each other to obtain maximum emissions from the unit.

Radiated Emissions

The final level, in dBuV/m, equals the reading from the spectrum analyzer (Level dBuV), adding the antenna correction factor and cable loss factor (Factor dB) to it, and subtracting the preamp gain (and duty cycle correction factor, if applicable). This result then has the limit subtracted from it to provide the Delta, which gives the tabular data as shown in the data sheets in Appendix B.

Example:

FREQ (MHz)	LEVEL (dBuV)	CABLE/ANT/PREAMP (dB)	FINAL (dB/m)	POL/HGT/AZ (m) (deg)	DELTA1
60.80	42.5Qp +	1.2 + 10.9 - 25.5	= 29.1	V 1.0 0.0	-10.9

Substitution Method

A cabinet (or enclosure) radiated emission scan was also made, at Intertek, with the EUT's antenna replaced with a termination to demonstrate case radiation compliance to the -13 dBm requirement. Radiated emissions from the EUT are measured in the frequency range of 30 to 20,000 MHz using a spectrum analyzer and appropriate broadband linearly polarized antennas. Table top equipment is placed on a 1.0 X 1.5 meter non-conducting table 80 centimeters above the ground plane. Floor standing equipment is place directly on the turntable/ground plane. Interface cable that are closer than 40 centimeters to the ground plane are bundled in the center in a serpentine fashion so they are at least 40 centimeters from the ground plane. Cables to simulators/testers (if used in this test) are routed through the center of the table and to a screen room located outside the test area. The antenna is positioned 3 meters horizontally from the EUT. To locate maximum emissions from the test sample the antenna is varied in height from 1 to 4 meters, measurement scans are made with both horizontal and vertical antenna polarizations and the EUT are rotated 360 degrees. The field strength levels were measured per ANSI C63.4. The EUT is then replaced with a tuned dipole antenna (below 1GHz) or horn antenna (above 1 GHz). The substitute antenna was placed in the same polarization as the test antenna. A signal generator was used to generate a signal level that matched the highest level measured from the EUT. The signal generator level minus the cable loss from the signal generator to the substitute antenna plus the substitute antenna gain equals the spurious power level.

Test Equipment

All measurement instrumentation is traceable to the National Institute of Standards and Technology and is calibrated according to internal procedure.

Radiated Emissions Test Data

[Table of Contents; Section 1.0](#)

Document Name: *3150809MIN-003_Radiated_Emissions_Test_Report_Part_90*

Test Engineer: Norman Shpilsher

Date: 9 May, 2008

Test Procedure:

Test measurements were made in accordance with ANSI C63.4-2003, Standard Methods of Measurement of Radio Noise Emissions from Low-Voltage Electrical and Electronics Equipment in the Range of 9 kHz to 40 GHz.

Test Site Location:

The test site is a 3 meter Semi-Anechoic Chamber, constructed by Panashield™ Inc. and located inside the building at 7250 Hudson Blvd. Suite 100, Oakdale, MN 55128.

Test Site Description:

The 3 meter Semi-Anechoic Chamber is constructed of Panabolt™ modular RF shielding and self-supported with structural steel designed for the local seismic zone rating. The chamber has the nominal size of 20' wide x 29' long x 18' high. All walls and ceiling of the chamber are treated with FFG-1000 Ferrite Grid absorber which was developed specifically to meet international requirements for EMC anechoic chambers for emissions and immunity measurements. To meet high frequency testing white HY-35 hybrid absorber is mounted on the ferrites in specular regions of the chamber.

The chamber has a 2 meter diameter ANSI test volume area and meets the requirements of ANSI C63.4 (1992), EN55022, and FCC Part 15 standards for testing at a 3 meter path length.

FCC Registration Number: 90706

IC Registration Number: 4359