

Label set with static, pre-printed text only



Notes:

- Barcodes shown are example, dummy barcodes for illustration only.
- The barcodes MUST have a minimum x-dimension of 5 mils (0.125mm). This can only be achieved by using a 600dpi printer.
- The barcodes must be as wide as possible across the width of the label, while still including enough quiet zone to the left and right of the barcode to ensure an accurate scan.
- Colons (:) and hyphens (-) are to be used only in human-readable serial numbers. Do not include these in the barcoded serial numbers.
- The barcodes are made up of a printed white "background", so the black label material forms the black bars of the barcodes.
- The QR Code to be printed white - no need to reverse print.

Label set with example variable data.
Not for manufacture.



Blank Label Part	STA-L000259	Ribbon	STA-CDNP001	Pace	E406-PX022ANC-Product-Label			Rev A
Additional Notes				Model	PX022ANC	Drafted By	Nick Tonge	Sheet 1 of 1
See also: Serialistion specification for E406 PX022ANC (latest issue) Label Position Instructions 700-534039x				Model Part No	E4063419300	Date	26 Feb 2014	
				Additional Graphics (if required)		Approved by	Signature	Date
				Tech Pubs		M Heron		
				Project Team		Alastair Lusted		
				Approvals		Rob Turner		