

CHOMERICS

TEST SERVICES**TEST REPORT****FOR****LEXENT CORPORATION****COMPANY PRODUCT NAME****MODEL 2000****FCC PART 15 SUBPART C PARAGRAPH 15.231 CERTIFICATION****Submitted to:**


Michael D'Angelo
 Lexent Corporation
 111 Heywood Avenue
 Melrose, Massachusetts 02176

Prepared by: Robert Foster**Date:** December 1, 1998**Test Report:** TR1924A.98**Purchase Order:** Credit Card**Number of Pages:** 19


I attest to the accuracy of the test data in this report:



Technician/Test Engineer



Test Services Approved Signatory



Official responsible for marketing this equipment

This report shall not be reproduced except in full without the written approval of
 Chomerics Test Services.


TEST REPORT
 Accredited Laboratory

ADMINISTRATIVE DATA

Purpose of Test: FCC Part 15 Subpart C
Paragraph 15.231 Certification

Test Specification: FCC Part 15 Subpart C

Manufacturer: Lexent Corporation

Manufacturer's Type or Model Number: Model 2000

Number of Items Tested: One

Date of Test: November 12, 1998

Test Observed By: Michael D'Angelo

Affiliated With: Lexent Corporation

Test Location: Chomerics Open Area Test Site A

Tests Conducted By: Robert Foster

Condition of Test Equipment Upon Arrival: Good

Customer's Equipment Returned VIA: Hand Carried

TEST RESULTS

The Lexent Corporation Model 2000 meets FCC Part 15 Subpart C Paragraph 15.231.

The Lexent Corporation Model 2000 is an intelligent proximity sensor used for Personal Laptop Computer security.

Document #: TR1924A.98
Date: December 1, 1998

TEST SERVICES FACILITY INFORMATION

Chomerics Test Facility is recognized under the National Voluntary Laboratory Accreditation (NVLAP) Program for NVLAP Codes 12/C01 and 12/R01. Tests within this report not conforming to 12/C01 and 12/R01 NVLAP Codes are not covered under Chomerics NVLAP accreditation.

Chomerics Test Facility operates under the current revision of Chomerics Quality Assurance Manual Document Number QA002.

The QA manual has been constructed to reflect a quality program in accordance with the requirements of the National Institute of Standards and Technology (NIST), ISO 9002, ISO Guide 25, NIST Handbook 150, EN 45001, MIL-I-45208A, MIL-STD-461D, 462D and Chomerics Quality Assurance Program (QAP).

The QA manual outlines and describes the procedures for establishing and maintaining the quality of analysis, research, inspection, and testing within Chomerics Test Service (CTS).

— This test report does not represent an endorsement by the U.S. Government.

— The results and/or conclusions within this test report refer and/or apply only to the unit(s) tested as defined by this report.

— Measurements performed for this test are traceable to the National Institute of Standards and Technology (NIST) based on the fact that all test equipment used for the measurements were previously calibrated using standards traceable to NIST.

— No deviations, additions to, or exclusions from the test specification

— The system amplitude accuracy for the measurements made during the radiated emission tests was "3dB.

TEST SITE DESCRIPTIONS

The following is a description of Test Services Open Field Test Sites. Refer to Administrative Data on page 2, line 9 for the specific test site used for testing.

OPEN AREA TEST SITE A: Chomerics open area test site "A" is located in the parking lot behind the Seeger Building at Chomerics, 77 Dragon Court, Woburn, Massachusetts.

The open area test site "A" is a wooden "A" frame, bounded by Dragon Court, a one story brick building, and a paved area. Photographs of the site and site attenuation data are on file with the Federal Communications Commission.

The supporting structure used for support of the equipment under test is a wooden rotatable platform .8 meters high. A similar supporting structure is used for the measuring equipment. The mast supporting the antenna can be adjusted from one to four meters in height.

OPEN AREA TEST SITE B: Chomerics open area test site "B" is located in the lower parking lot behind the Seeger Building at Chomerics, 77 Dragon Court, Woburn, Massachusetts.

Photographs of the site and site attenuation data are on file with the Federal Communications Commission.

Parking is permitted on one side of test site "B" at a discrete distance from the imaginary ellipse.

The open area site B enclosure is a wooden structure measuring 56 X 30 X 25 feet in size with galvanized steel sheet metal used as the ground plane. The structure is sized to allow both 3 and 10 meter measurements and is heated and/or air conditioned.

The structure used to support equipment under test is a 14 foot diameter motorized turntable. The sheet metal surface is flush with the ground plane. To ground the turntable, 175 copper fingers (1" x 1.5") are mounted around the outer edge of the turntable using machine screws. The spring fingers are equally spaced and provide a uniform interface between the turntable metal surface and ground plane. When needed for table top equipment, a wooden table measuring 3 x 6 feet in size is positioned at the center of the turntable, at the proper height above the ground plane.

The addition at the end of the open area test site is the location for the test personnel and equipment to ensure they are outside the imaginary ellipse.

Both Test Site A and B are listed by the Federal Communications Commission (FCC).

Document #: TR1924A.98
Date: December 1, 1998

RADIATED EQUIPMENT LIST

Test Equipment		Asset #	Serial #	Cal Date
Tektronix 496	Spectrum Analyzer	1	B010559	10/98
H/P 8566B	Spectrum Analyzer	47	2637A04064	06/99
H/P 85685A	RF Preselector	48	2648A00483	06/99
H/P OPT462	Display Unit	46	2648A14289	06/99
Rhode and Schwartz	ESV Test Receiver	15	875931049	9/98
Hewlett Packard	8447D Pre Amp	12	2944A06414	1/99
EMCO 3120	Tuned Dipole Antenna B1	477	56	1/99
EMCO 3121	Tuned Dipole Antenna B2	478	176	1/99
EMCO 3121	Tuned Dipole Antenna B3	479	728	1/99
EMCO 3115	Microwave Horn Antenna	376	2796	1/99

Equipment Calibration: The calibration of Chomerics test facility equipment is controlled under the current revision of Chomerics Laboratory Test Equipment Calibration Manual Document Number QA001.

The test equipment used throughout this test sequence conforms to laboratory calibration standards, MIL-STD-45662A, traceable to the National Institute of Science and Technology. The date of the next due scheduled calibration is listed in the table above for Chomerics Test Services equipment used during testing.

All test equipment is calibrated annually.

Test Personnel: The test personnel used to perform or supervise the tests are accredited by the National Association of Radio and Telecommunications Engineers, Inc. (NARTE) as Certified Electromagnetic Compatibility Engineers (N.C.E.) and Technicians (N.C.T.).

**FIELD STRENGTH OF FUNDAMENTAL FREQUENCY
418MHz****Test No:** **ONE (1)****Equipment Tested:** Lexent Corporation Model 2000**Configuration:** The Lexent Model 2000 was set up on a wooden turntable 3 meters from the tunable dipole antenna.

No support equipment was needed to run the Model 2000 in its normal mode of operation.

Any emissions radiating from the Model 2000 were maximized by rotating the test table and placing the cables in their worst case configuration.

Test Mode: The test was performed in two modes of operation: (a) Model 2000 Controller on at high power; (b) Model 2000 Controller on at low power.**Results:** The Lexent Corporation Model 2000 meets the Spurious emission requirements of FCC Part 15 Subpart C Paragraph 15.213 as configured for testing.**Fixes:** NoneDocument #: TR1924A.98
Date: December 1, 1998

FIELD STRENGTH OF SPURIOUS EMISSIONS
30 MHz to 10 GHz

Test No: **TWO (2)**

Equipment Tested: Lexent Corporation Model 2000

Configuration: The Lexent Model 2000 was set up on a wooden turntable 3 meters from the tunable dipole antenna.

No support equipment was needed to run the Model 2000 in its normal mode of operation.

Any emissions radiating from the Model 2000 were maximized by rotating the test table and placing the cables in their worst case configuration.

Test Mode: The test was performed in two modes of operation: (a) Model 2000 Controller on at high power; (b) Model 2000 Controller on at low power.

Results: The Lexent Corporation Model 2000 meets the Spurious emission requirements of FCC Part 15 Subpart C Paragraph 15.213 as configured for testing.

Fixes: None

Document #: TR1924A.98
Date: December 1, 1998

**REQUIRED BANDWIDTH
418MHz**

Test No: **THREE (3)**

Equipment Tested: Lexent Corporation Model 2000

Configuration: The Lexent Model 2000 was set up on a wooden turntable 3 meters from the tunable dipole antenna.

No support equipment was needed to run the Model 2000 in its normal mode of operation.

Any emissions radiating from the Model 2000 were maximized by rotating the test table and placing the cables in their worst case configuration.

Test Mode: The test was performed in two modes of operation: (a) Model 2000 Controller on at high power; (b) Model 2000 Controller on at low power.

Results: The Lexent Corporation Model 2000 meets the Spurious emission requirements of FCC Part 15 Subpart C Paragraph 15.213 as configured for testing.

Fixes: None

**RADIATED EMISSIONS
30 MHz to 10 GHz****Test No:** **FOUR (4)****Equipment Tested:** Lexent Corporation Model 2000**Configuration:** The Lexent Model 2000 was set up on a wooden turntable 3 meters from the tunable dipole antenna.

No support equipment was needed to run the Model 2000 in its normal mode of operation.

Any emissions radiating from the Model 2000 were maximized by rotating the test table and placing the cables in their worst case configuration.

Test Mode: The test was performed with the transmitted turned off, in receive mode only.**Results:** The Lexent Corporation Model 2000 meets the radiated emission requirements of FCC Part 15 Subpart B Class B.**Fixes:** None

SUMMARY OF RECOMMENDATIONS

The Lexent Corporation Model 2000 will not require modifications in order to insure compliance with the FCC Part 15 Subpart C requirements.

Please note that if any modifications and or fixes were implemented to the EUT to achieve compliance, that other approaches to solving the problem may exist. In addition, any EMI/EMC shielding products listed in this report may be substituted with an equivalent.

Document #: TR1924A.98
Date: December 1, 1998

CHOMERICS

NW 267-26

APPENDIX A

TEST DATA

Document #: TR1924A.98
Date: December 1, 1998

TEST LOG

N4W 247-26

Customer: <u>Lexent Tech</u>		Program: _____				
EUT: <u>Model 2000</u>		S/N _____				
PRE-TEST CHECKLIST	DATE	COMMENTS				
		Test Plan/Procedure: <u>FCC Part 15</u>				
		Test Specification: <u>FCC Part 15 15.231</u>				
		Chomerics Procedure: <u>CHO TEVC T1</u>				
		EUT Power Requirement Verified:				
		Voltage <u>120 Hz</u>	Frequency _____	Phase _____		
		Voltage _____	Frequency _____	Phase _____		
		EUT Functional Operational Check: <input type="checkbox"/> Pass <input type="checkbox"/> Fail				
		Environmental: Ambient Temperature <u>72</u> °F				
		Humidity: <u>40</u> % Atmospheric Pressure: <u>30"</u>				
	Bonding / Grounding: <u>NA</u>		Safety Issues: <u>NA</u>			
IN-PROCESS TEST CHECKLIST	Date	Test Type	Test Equipment Calibrated	Test Performed Properly- Data Accepted	EUT Setup Check / Operational Check	EUT Pass/Fail
	11/10/98	Kad.	✓	✓	✓	Pass
	11/10/98	Bandwidth	✓	✓	✓	Pass
	11/10/98	Recover	—	✓	—	Pass
POST TEST CHECKLIST	Date: <u>11/12/98</u>	EUT Functional Operational Check: <input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail		<u>Kad</u> <u>Pass</u> <u>Pass</u> <u>Test Services Mgr</u> <u>10/24/98</u> <u>Test Services Mgr</u> <u>December 1, 1998</u>		

RADIATED E FIELD EMISSION MEASUREMENTS

CUSTOMER: Lexent Tech. Inc. DATE: 11/12/98
 EQUIPMENT: Model 2000 High Power TEST NUMBER: 1#2
 TESTED BY: R. Foster OPERATING MODE: High Power
 BANDWIDTH: 100 kHz (PEAK) / 120 kHz (QP) TEST SPEC: FCC Part 15 Subpart C
 OTHER (SPECIFY): ANSI C62.41
 FREQUENCY RANGE: 30MHz - 1GHz ANTENNA DISTANCE: 3 METERS 10 METERS
 OTHER (SPECIFY): 30MHz - 10GHz

Frequency MHz	Peak Measured Level -dBm	Quasi-Peak Measured Level dBuV	Antenna Height (Meters)	Turntable Azimuth (Degrees)	Antenna H/V	Antenna Fac/Cable Loss dB	Field Level dB uV/m **	Limit dBuV/m (QP)
410	56	-	1/2	0	HA	28.7	79.7	80.28
836	-	-	1	0	H	19.6	68.6	70.6
1254	90	-	1	0	H	24.9	41.9	70.6
1672	92	-	1	0	H	26.9	41.9	70.6
3090	96	-	1	0	H	27.3	38.3	70.6
3344	94	-	1	0	H	31.0	44.0	70.6
3762	94	-	1	0	H	32.7	45.7	70.6
4180	90	-	1	0	H	34.1	57.1	70.6
4548	92	-	1	0	H	33.2	48.2	70.6
5016	92	-	1	0	H	35.6	30.6	70.6
							No other signals detected	

** All signals greater than 3dB from the limit are calculated to the nearest whole number.

** Field Level (dBuV/m) = [107 - Measured Level (dBm)] + Antenna Factor/Cable Loss (dB)

Document #: TR1924A.98
Date: December 1, 1998

RADIATED E FIELD EMISSION MEASUREMENTS

CUSTOMER: Lexent Tech Inc.

EQUIPMENT: Model 2000 Low Power

TESTED BY: R. Foster

BANDWIDTH: [W] 100 kHz (PEAK) / 120 kHz (QP)

OTHER (SPECIFY) _____

FREQUENCY RANGE: [V] 30MHz - 1GHz

OTHER (SPECIFY) 30 MHz - 10 GHz

DATE: 11/12/98
TEST NUMBER: 1#2
OPERATING MODE: Low Power
TEST SPEC: FCC Part 15 Subpart C
PROCEDURE: ANSI C62.4

** All signals greater than 3dB from the limit are calculated to the nearest whole number.

** Field Level (dBuV/m) = [107 - Measured Level (dBm)] + Antenna Factor/Cable Loss (dB)

Document #: TR 1924A.98
Date: December 1, 1998

FORM CTSDS001R

Page 14 of 19

2400 267-26


High Power

HP REF -30.0 dBm ATTEN 0 dB +0 dB

MKR Δ 10.0 kHz
-20.20 dB

10 dB/

MARKER Δ
10.0 kHz
-20.20 dB



CENTER 418.080 MHz RES BW 10 kHz (1) VBW 100 kHz

SPAN 100 kHz SWP 48.0 msec

DOCUMENT # TR 1924 A. 98
DATE December 1, 1998

PAGE 15 OF 19

NGW 247-26

Low Power


HP REF -50.0 dBm ATTEN 0 dB +0 dB

MKR Δ-10.7 kHz
-20.30 dB

10 dB/

MARKER ▲

-10.7 kHz
-20.30 dB



DOCUMENT #: TR1924A.98
DATE: December 1, 1998

PAGE 16 OF 19

RADIATED E FIELD EMISSION MEASUREMENTS

CUSTOMER: Lerent Tech Inc
EQUIPMENT: Model 2000
TESTED BY: R. Foster
BANDWIDTH: 100 kHz (PEAK) / 120 kHz (QP)
OTHER (SPECIFY) _____

DATE: 11/20/98
TEST NUMBER: 4
OPERATING MODE: Receiving
TEST SPEC: IEC Part 15 Subpart
PROCEDURE: ANSI C63.4

FREQUENCY RANGE: 30MHz - 1GHz ANTENNA DISTANCE: 3 METERS 10 METERS
OTHER (SPECIFY) 30MHz - 1GHz

** All signals greater than 3dB from the limit are calculated to the nearest whole number.

** Field Level (dBuV/m) = [107 - Measured Level (dBm)] + Antenna Factor/Cable Loss (dB)

Document #: TR 1924A.98
Date: December 1, 1998

FORM CTSDS001R

Page 17 of 19

CHOMERICS

NAW 267-26

APPENDIX B

SETUP PHOTOGRAPHS

Document #: TR1924A.98
Date: December 1, 1998