



**Ecom Sertech Corp.**

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., ChuTung Chen, Hsinchu, Taiwan 310, R.O.C  
TEL:886-3-5918012 FAX: 886-3-5825720

FCC ID : NRQRMKT05  
Report No. : ER04-01-004FRF  
Page  1  of  46



## TEST REPORT

Product Name : Bluetooth Tablet

Model Number : RMK-T05

Applicant : AIPTEK International Inc.

Address : No. 19 Industry E. Rd. IV, Hsinchu Science Park,  
Hsin-Chu Taiwan, R.O.C. 300

Received Date : Jan. 02, 2004

Tested Date : Jan. 02 ~ 31, 2004

Notes :

1. This report will be invalid if duplicated or photocopied in part.
2. This report refers only to the specimen(s) submitted to testing, and be invalid as seperately used.
3. This report is invalid without examination stamp and signature of this institute.
4. The tested specimen(s) will be preserved for thirty days from the data issued.
5. The report must not be used to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government.





**Ecom Sertech Corp.**

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., ChuTung Chen, Hsinchu, Taiwan 310, R.O.C  
TEL:886-3-5918012 FAX : 886-3-5825720

FCC ID : NRQRMKT05  
Report No. : ER04-01-004FRF  
Page  2  of  46


# Test Report Certification

**Product Name** : Bluetooth Tablet  
**Model Number** : RMK-T05  
**Applicant** : AIPTEK International Inc.

**Measurement Standard :**

47 CFR Part 15, Subpart B and Subpart C (Section 15.247),  
ANSI C63.4-2001

**Tested By** :  Stan Peng , **Date** :  Jan. 30, 2004   
(Stan Peng)  
**Reviewed By** :  Roger Sheng , **Date** :  Jan. 30, 2004   
(Roger Sheng)  
**Approved By** :  Chieh-De Tsai , **Date** :  Jan. 30, 2004   
(Chieh-De Tsai, Manager)



WE HEREBY CERTIFY THAT: The measurements shown in the attachment were made in accordance with the procedures indicated, and the energy emitted by the equipment was found to be within the limits applicable. We assume full responsibility for the accuracy and completeness of these measurements and vouch for the qualifications of all persons taking them.



**TABLE OF CONTENTS**

TITLE	PAGE NO.
<b>1. GENERAL INFORMATION.....</b>	<b>5</b>
1.1 Description of EUT & Power .....	5
1.2 Description ff Peripherals .....	6
1.3 EUT & Peripherals Setup Diagram .....	7
1.4 EUT Operating Condition.....	7
1.5 Description of Test Site .....	8
1.6 Summary ff Test Results.....	8
<b>2. CONDUCTED POWERLINE TEST.....</b>	<b>9</b>
2.1 Test Equipments .....	9
2.2 Test Setup .....	9
2.3 Conducted Power Line Emission Limit.....	10
2.4 Test Procedure .....	10
2.5 Uncertainty of Conducted Emission .....	10
2.6 Line Conducted RF Voltage Measurement.....	11
2.7 Photos of Conduction Test.....	12
<b>3. 20dB Bandwidth for hopping .....</b>	<b>13</b>
3.1 Test Equipments .....	13
3.2 Test Setup .....	13
3.3 Limits of 20db Bandwidth Measurement .....	13
3.4 Test Procedure .....	13
3.5 Uncertainty of Conducted Emission .....	14
3.6 Test Results.....	14
3.7 Photo of 20db Bandwidth Measurement.....	15
<b>4. MAXIMUM PEAK OUTPUT POWER.....</b>	<b>16</b>
4.1 Test Equipments .....	16
4.2 Test Setup .....	16
4.3 Limits of Maximum Peak Output Power .....	16
4.4 Test Procedure .....	17
4.5 Uncertainty of Conducted Emission .....	17
4.6 Test Results.....	17
4.7 Photo of Maximum Peak Output Power .....	18
<b>5. HOPPING CHANNEL SEPARATION.....</b>	<b>19</b>
5.1 Test Equipments .....	19
5.2 Test Setup .....	19
5.3 Limits of Hopping Channel Separation .....	19
5.4 Test Procedure .....	20
5.5 Uncertainty of Conducted Emission .....	20
5.6 Test Results.....	20
5.7 Photo of Hopping Channel Separation .....	20
<b>6. NUMBER OF HOPPING FREQUENCY USED.....</b>	<b>21</b>
6.1 Test Equipments .....	21
6.2 Test Setup .....	21
6.3 Limits of Number of Hopping Frequency Used .....	21
6.4 Test Procedure .....	22
6.5 Uncertainty of Conducted Emission .....	22
6.6 Test Results.....	22
6.7 Photo of Number of Hopping Frequency Used .....	22



**TABLE OF CONTENTS**

TITLE	PAGE NO.
<b>7. DWELL TIME ON EACH CHANNEL .....</b>	<b>23</b>
7.1 Test Equipments .....	23
7.2 Test Setup .....	23
7.3 Limits of Dwell Time on Each Channel .....	23
7.4 Test Procedure .....	24
7.5 Uncertainty of Conducted Emission .....	24
7.6 Test Results.....	24
7.7 Photo of Dwell Time on Each Channel .....	25
<b>8. BAND EDGE SPURIOUS EMISSIONS -CONDUCTED MEASUREMENTS .....</b>	<b>26</b>
8.1 Test Equipments .....	26
8.2 Test Setup .....	26
8.3 Limits of Band edge Measurements .....	26
8.4 Test Procedure .....	27
8.5 Uncertainty of Conducted Emission .....	27
8.6 Test Results.....	28
8.7 Photo of Band edge Measurement .....	29-30
<b>9. OUT OF BAND SPURIOUS EMISSIONS -RADIATED MEASUREMENTS.....</b>	<b>31</b>
9.1 Test Equipments .....	31
9.2 Test Setup .....	31
9.3 Radiation Limit .....	32
9.4 Test Procedures.....	33
9.5 Uncertainty of Radiated Emission .....	33
9.6 Radiated RF Noise Measurement .....	34-41
9.7 Photos of Open Site .....	42-43
<b>10. ANTENNA REQUIREMENT .....</b>	<b>44</b>
10.1 Standard Applicable.....	44
10.2 Antenna Connected Construction .....	44
<b>11. RF EXPOSURE EVALUATION .....</b>	<b>45</b>
11.1 Friis Formula .....	45
11.2 EUT Operating Condition.....	45
11.3 Test Result of RF Exposure Evaluation.....	46
11.3.1 Antenna Gain .....	46
11.3.2 Output Power into Antenna & RF Exposure Evaluation Distance .....	46



## 1. GENERAL INFORMATION

### 1.1 Description of EUT & Power

MANUFACTURER : AIPTEK International Inc.

SAMPLE NAME : Bluetooth Tablet

MODEL NO : RMK-T05

EUT DESCRIPTION : 2.4GHz Frequency Hopping Spread Spectrum  
Data Transceiver for Bluetooth Tablet

FREQUENCY RANGE : 2402 MHz to 2480MHz

CHANNEL NUMBER : 79

CHANNEL Spacing : 1MHz

AIR DATA RATE : 723Kbps

TYPE OF MODULATION : Frequency Hopping Spread Spectrum

FEQUENCY SELECTION : BY SOFTWARE

ANTENNA TYPE : Printed Antenna on PCB, Antenna gain : 1.5dBi.

POWER SOURCE : 3VDC from Battery (AAx2) / 5VDC from USB port

NOTE : The EUT can be operated in Wireless (Bluetooth) and  
Wired (USB) mode. While the EUT is set to Wired mode,  
the Wireless function is disabled.



## **Ecom Sertech Corp.**

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., ChuTung Chen, Hsinchu, Taiwan 310, R.O.C  
TEL:886-3-5918012 FAX: 886-3-5825720

FCC ID : NRQRMKT05  
Report No. : ER04-01-004FRF  
Page 6 of 46

---

### **1.2 Description of Peripherals**

#### **(1) Notebook PC**

MANUFACTURER : COMPAQ CORP.  
MODEL NUMBER : EV0N800  
SERIAL NUMBER : 470052-787  
F.C.C. : DOC  
POWER CORD : Unshielded, Detachable, 1.8m

#### **Adapter**


MANUFACTURER : COMPAQ CORP.  
MODEL NUMBER : PPP009H  
SERIAL NUMBER : -----

#### **(2) Printer**


MANUFACTURER : HP CORP.  
MODEL NUMBER : C8952D  
SERIAL NUMBER : CN29B181H7  
FCC ID : DOC  
POWER SOURCE : 100-240VAC, 50/60Hz, 0.7A  
SIGNAL CABLE : Shielded , Undetachable , 1.8m

### 1.3 EUT & Peripherals Setup Diagram

For Wired mode :



For Wireless mode :



Test Software :

1. HCI Terminal – Brighton Technologies
2. Commands → `t t t 0 1 0 0 0 0x00`  
Set TX mode in CH1 (2402MHz) modulation,  
Set 0x4e is channel 79 (2480 MHz)

### 1.4 EUT Operating Procedure

1. The Brighton Technologies HCI terminal test software was configured to control the EUT during test.
2. Type “`t t t 0 1 0 0 0 0 0x00`” to set the EUT to channel 1 with DH1 package.
3. Type “`t t t 0 1 0 0 0 0 0x4e`” to set the EUT to channel 79 with DH1 package.
4. Three types of packages, DH1, DH3 and DH4 were used for the EUT, only DH1 package, the worst case, was selected while performing final test.



## Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., ChuTung Chen, Hsinchu, Taiwan 310, R.O.C  
TEL:886-3-5918012 FAX : 886-3-5825720

FCC ID : NRQRMKT05  
Report No. : ER04-01-004FRF  
Page 8 of 46

### 1.5 Description of Test Site

SITE DESCRIPTION : FCC Certificate NO. : 90585  
 BSMI Certificate NO. : SL2-IN-E-0002  
 NVLAP Lab code : 200118-0  
 CNLA Certificate NO. : CNLA-ZL97018  
 VCCI Certificate NO. : R-1189, C-1250

NAME OF SITE : Ecom Sertech Corp. Hsinchu  
 (Spin-off from ITRI / ERSO on Apr. 01, 2003)

SITE LOCATION : Rm.258, Bldg.17, NO.195 , Sec. 4, Chung Hsing Rd.,  
 Chu-Tung Chen. Hsin-Chu, Taiwan 310 R.O.C.

### 1.6 Summary of Test Results

The EUT has been tested according to the following specifications :

APPLIED STANDARD : 47 CFR Part 15, Subpart B and Subpart C			
Standard Section	Test Type and Limit	Result	REMARK
15.107 15.207	AC Power Conducted Emission Limit : Sec1.5.107	PASS	Meet the requirement of limit
15.109 15.205 15.209	Transmitter Radiated Emissions Limit : Table 15.209	PASS	Meet the requirement of limit
15.247(a) (1)(i)-(ii)	Transmitter 20dB Bandwidth Limit < 1MHz	PASS	Meet the requirement of limit
15.247(b)(1)	Maximum Peak Output Power Limit : max. 30dBm	PASS	Meet the requirement of limit
15.247(a)(1)	Carrier Frequency Separation	PASS	Meet the requirement of limit
15.247(a) (1)(ii)	Number of Hopping Frequency	PASS	Meet the requirement of limit
15.247(a) (1)(ii)	Time of Occupancy (dwell time)	PASS	Meet the requirement of limit
15.247(c)	Band Edge Compliens	PASS	Meet the requirement of limit
15.247(c)	Out of Band Measurements	PASS	Meet the requirement of limit





## 2. CONDUCTED POWERLINE TEST


For intentional device, according to § 15.207(a) Line Conducted Emission Limit is required to verify the EUT.

### 2.1 Test Equipments

The following test equipments are used during the conducted powerline tests :

Manufacturer or Type	Model No.	Serial No.	Date of Calibration	Calibration Period	Remark
HP SPECTRUM ANALYZER & DISPLAY	8568A	2235A02320	NOV. 14, 2003	1 Year	PRETEST
HP QUASI-PEAK ADAPTER	85650 A	2341A00672	NOV. 14, 2003	1 Year	PRETEST
SOLAR ISOLATION TRANSFORMER	7032-1	N/A	N/A	N/A	FINAL
EMCO L.I.S.N.	3850/2	9311-1025 9401-1028	JAN. 08, 2004 For Characteristic impedance	1 Year	FINAL
			MAY 18, 2003 For Insertion loss		
R & S TEST RECEIVER	ESCS 30	826547/004	JUN. 17, 2003	1 Year	FINAL
KEENE SHIELDED ROOM	5983	No.1	N/A	N/A	FINAL
R & S PULSE LIMIT	EHS3Z2	357.8810.52	JUL. 10, 2003	1 Year	FINAL
N TYPE COAXIAL CABLE	-----	-----	JUL. 10, 2003	1 Year	FINAL
50Ω TERMINATOR	-----	-----	JUL. 10, 2003	1 Year	FINAL

### 2.2 Test Setup





### 2.3 Conducted Power Line Emission Limit

For unintentional device, according to § 15.107(a) Line Conducted Emission Limits is as following :

Frequency (MHz)	Maximum RF Line Voltage (dB $\mu$ v)			
	CLASS A		CLASS B	
	Q.P.	Ave.	Q.P.	Ave.
0.15 - 0.50	79	66	66-56	56-46
0.50 - 5.00	73	60	56	46
5.00 - 30.0	73	60	60	50

For intentional device, according to § 15.207(a) Line Conducted Emission Limit is same as above table.

### 2.4 Test Procedure

The test procedure is performed in a 12ft×12ft×8ft(L×W×H) shielded room. the EUT along with its peripherals were placed on a 1.0m(W)× 1.5m(L) and 0.8m in height wooden table and the EUT was adjusted to maintain a 0.4 meter space from a vertical reference plane. The EUT was connected to power mains through a line impedance stabilization network (LISN) which provides 50 ohm coupling impedance for measuring instrument and the chasis ground was bounded to the horizontal ground plane of shielded room. All peripherals were connected to the second LISN and the chasis ground also bounded to the horizontal ground plane of shielded room. The excess power cable between the EUT and the LISN was bundled. The power cables of peripherals were unbundled. All connecting cables of EUT and peripherals were moved to find the maximum emission.

### 2.5 Uncertainty of Conducted Emission

The uncertainty of conducted emission is  $\pm 1.36$ dB.



## 2.6 Line Conducted RF Voltage Measurement

The frequency spectrum from 0.15 MHz to 30 MHz was investigated. All emissions not reported below are more than 35 dB below the prescribed limits.

Temperature : 26 °C

Humidity : 65 % RH

Frequency (MHz)	Loss(dB)		Measurement				L1 Emission (dBμV)		L2 Emission (dBμV)		Limits (dBμV)	
			L1(dBμV)		L2(dBμV)		Q.P.	Ave.	Q.P.	Ave.	Q.P.	Ave.
	L1	L2	Q.P.	Ave.	Q.P.	Ave.						
0.150	0.10	0.20	*	*	*	*	*	*	*	66.00	56.00	
0.198	0.10	0.20	*	*	42.60	*	*	*	42.80	63.69	53.69	
0.201	0.10	0.20	48.80	*	*	*	48.90	*	*	63.57	53.57	
0.396	0.10	0.20	*	*	36.90	*	*	*	37.10	57.94	47.94	
0.405	0.10	0.20	39.50	*	*	*	39.60	*	*	57.75	47.75	
0.530	0.10	0.20	*	*	34.60	*	*	*	34.80	56.00	46.00	
0.540	0.10	0.20	37.40	*	*	*	37.50	*	*	56.00	46.00	
2.090	0.11	0.20	36.00	*	*	*	36.11	*	*	56.00	46.00	
2.120	0.11	0.20	*	*	34.50	*	*	*	34.70	56.00	46.00	
3.180	0.20	0.20	*	*	34.50	*	*	*	34.70	56.00	46.00	
3.440	0.20	0.20	37.30	*	*	*	37.50	*	*	56.00	46.00	
4.910	0.20	0.20	23.10	*	*	*	23.30	*	*	56.00	46.00	
4.970	0.20	0.20	*	*	27.10	*	*	*	27.30	56.00	46.00	
13.000	0.50	0.50	*	*	34.50	*	*	*	35.00	60.00	50.00	
13.050	0.50	0.51	30.90	*	*	*	31.40	*	*	60.00	50.00	
15.600	0.66	0.66	34.30	*	*	*	34.96	*	*	60.00	50.00	
16.050	0.70	0.70	*	*	31.50	*	*	*	32.20	60.00	50.00	
30.000	1.40	1.80	*	*	*	*	*	*	*	60.00	50.00	

REMARKS : 1. \* Undetectable or the Q.P. value is lower than the limits of Ave.  
 2. For Wired mode.

## 2.7 Photos of Conduction Test



### 3. 20dB Bandwidth for hopping

#### Test Requirement: 15.247(a)(1)(ii)


#### 3.1 Test Equipments

Description & Manufacturer	Model No.	Serial No.	Date Of Calibration
ROHDE & SCHWARZ SPECTRUM ANALYZER	FSEK30	835253/002	JUN. 17, 2003
HP ATTENUATOR	8496B	3247A18505	Cal. on use
HP PLOTTER	7750A	725A 852141	N/A

NOTE :

1. The measurement uncertainty is less than +/- 2.6dB, which is calculated as per the NAMAS document NIS81.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

#### 3.2 Test Setup



#### 3.3 Limits of 20db Bandwidth Measurement

Limit: 20dB band width < 1MHz

#### 3.4 Test Procedure

The 20dB band width was measured with a spectrum analyzer connected to RF antenna connector(conducted measurement) while EUT was operating in transmit mode at the appropriate center frequency.

The analyzer center frequency was set to the EUT carrier frequency, using the analyzer. Display Line and Marker Delta functions, the 20dB band width of the emission was determined.



## Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., ChuTung Chen, Hsinchu, Taiwan 310, R.O.C  
TEL:886-3-5918012 FAX: 886-3-5825720

FCC ID : NRQRMKT05  
Report No. : ER04-01-004FRF  
Page 14 of 46

### 3.5 Uncertainty of Conducted Emission

The uncertainty of conducted emission is  $\pm 10\text{KHz}$ .

### 3.6 Test Results


Refer to attached spectrum analyzer data chart.

<b>Input Power (System)</b>	3VDC ( From Battery )	<b>Environmental Conditions</b>	26°C, 55%RH
<b>Tested By</b>	Stan Peng		

<b>Channel</b>	<b>Channel Frequency (MHz)</b>	<b>20dB Bandwidth (MHz)</b>	<b>Maximum Limit (MHz)</b>	<b>Pass / Fail</b>
01 ( Low )	2402	0.92685	<1	PASS
40 ( Mid )	2441	0.92184	<1	PASS
79 ( High )	2480	0.93186	<1	PASS




### 3.7 Photo of 20db Bandwidth Measurement




Date: 29.JAN.2004 16:03:30

#### Channel Low



Date: 29.JAN.2004 16:06:28

#### Channel Middle



Date: 29.JAN.2004 16:09:58

#### Channel High



## 4. MAXIMUM PEAK OUTPUT POWER

### Test Requirement: 15.247(b)(1)

#### 4.1 Test Equipments

Description & Manufacturer	Model No.	Serial No.	Date Of Calibration
ROHDE & SCHWARZ SPECTRUM ANALYZER	FSEK30	835253/002	JUN. 17, 2003
HP ATTENUATOR	8496B	3247A18505	Cal. on use
HP PLOTTER	7750A	725A 852141	N/A

NOTE :

1. The measurement uncertainty is less than +/- 2.6dB, which is calculated as per the NAMAS document NIS81.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

#### 4.2 Test Setup



#### 4.3 Limits of Maximum Peak Output Power

The Maximum Peak Output Power Measurement is 1W(30dBm) for frequency hopping systems operating in 2400~2483.5 MHz employing at least 75 hopping channels.





#### 4.4 Test Procedure

The RF power output was measured with a Power meter connected to the RF Antenna connector ( conducted measurement ) while EUT was operating in transmit mode at the appropriate center frequency, A spectrum analyzer was used to record the shape of the transmit signal see 4.7 for the measurement set up.

#### 4.5 Uncertainty of Conducted Emission

The uncertainty of conducted emission is  $\pm 1.82\text{dB}$ .

#### 4.6 Test Results

<b>Input Power (System)</b>	3VDC ( From Battery )	<b>Environmental Conditions</b>	26°C, 55%RH
<b>Tested By</b>	Stan Peng		

Cable loss = 1.5dB

<b>Channel</b>	<b>Channel Frequency (MHz)</b>	<b>Peak Power Output (dBm)</b>	<b>Peak Power Limit (dBm)</b>	<b>Pass / Fail</b>
01 ( Low )	2402	0.34	30	PASS
40 ( Mid )	2441	0.07	30	PASS
79 ( High )	2480	-0.51	30	PASS

Note : The result was calculated as follow :

$$\text{Peak Power Output} = \text{Peak Power Reading} + \text{Cable loss}$$




# Ecom Sertech Corp.


Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., ChuTung Chen, Hsinchu, Taiwan 310, R.O.C  
TEL:886-3-5918012 FAX: 886-3-5825720

FCC ID : NRQRMKT05  
Report No. : ER04-01-004FRF  
Page 18 of 46


## 4.7 Photo of Maximum Peak Output Power



### Channel Low



### Channel Middle



### Channel High

## 5. HOPPING CHANNEL SEPARATION

### Test Requirement: 15.247(a)(1)


#### 5.1 Test Equipments

Description & Manufacturer	Model No.	Serial No.	Date Of Calibration
ROHDE & SCHWARZ SPECTRUM ANALYZER	FSEK30	835253/002	JUN. 17, 2003
HP ATTENUATOR	8496B	3247A18505	Cal. on use
HP PLOTTER	7750A	725A 852141	N/A

NOTE :

1. The measurement uncertainty is less than +/- 2.6dB, which is calculated as per the NAMAS document NIS81.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

#### 5.2 Test Setup



#### 5.3 Limits of Hopping Channel Separation

According to 15.247(a)(1), frequency hopping system shall have, hopping channel carrier frequencies separated by a minimum of 25kHz or the 20dB bandwidth of the hopping channel, whichever is greater.

### 5.4 Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT as shown in test setup without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range.
3. Because of the property of test software and hardware, the TX signal can not be modulated while test.
4. By using the MaxHold function record the separation of adjacent channels.
5. Measure the frequency difference of these two adjacent channels by spectrum analyzer MARK function. And then plot the result on spectrum analyzer screen.

Repeat above procedures until all frequencies measured were complete.

### 5.5 Uncertainty of Conducted Emission


The uncertainty of conducted emission is  $\pm 10$ KHz.

### 5.6 Test Results

Refer to section 3, 20dB bandwidth measurement, the measured channel separation should be greater than 20dB bandwidth or Minimum bandwidth.

Channel	Adjacent Hopping Channel Separation (kHz)	20dB bandwidth (kHz)	Minimum Bandwidth	Result
2441MHz (Mid)	991.98 kHz	921.84 kHz	25 kHz	Pass

### 5.7 Photo of Hopping Channel Separation



## 6. NUMBER OF HOPPING FREQUENCY USED

Test Requirement: 15.247(a)(1)(ii)


### 6.1 Test Equipments

Description & Manufacturer	Model No.	Serial No.	Date Of Calibration
ROHDE & SCHWARZ SPECTRUM ANALYZER	FSEK30	835253/002	JUN. 17, 2003
HP ATTENUATOR	8496B	3247A18505	Cal. on use
HP PLOTTER	7750A	725A 852141	N/A

NOTE :

1. The measurement uncertainty is less than +/- 2.6dB, which is calculated as per the NAMAS document NIS81.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

### 6.2 Test Setup



### 6.3 Limits of Number of Hopping Frequency Used

According to 15.247(a)(1)(ii), for frequency hopping system operating in the 2400-2483.5MHz and 5725-5850 MHz bands shall use at least 75 hopping frequencies

## 6.4 Test Procedure

1. Check the calibration of the measuring instrument (spectrum analyzer) using either an internal calibrator or a known signal from an external generator.
2. Position the EUT as shown in test setup without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
3. Set the spectrum analyzer on MaxHold Mode, and then keep the EUT in hopping mode. Record all the signals from each channel until each one has been recorded.
4. Set the spectrum analyzer on View mode and then plot the result on spectrum analyzer screen.
5. Repeat above procedures until all frequencies measured were complete.

## 6.5 Uncertainty of Conducted Emission


The uncertainty is not applicable.

## 6.6 Test Results

Refer to the attached graph.

There are 79 hopping frequencies in a hopping sequence.

## 6.7 Photo of Number of Hopping Frequency Used



## 7. DWELL TIME ON EACH CHANNEL

### Test Requirement: 15.247(a)(1)(ii)


#### 7.1 Test Equipments

Description & Manufacturer	Model No.	Serial No.	Date Of Calibration
ROHDE & SCHWARZ SPECTRUM ANALYZER	FSEK30	835253/002	JUN. 17, 2003
HP ATTENUATOR	8496B	3247A18505	Cal. on use
HP PLOTTER	7750A	725A 852141	N/A

NOTE :

1. The measurement uncertainty is less than +/- 2.6dB, which is calculated as per the NAMAS document NIS81.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

#### 7.2 Test Setup



#### 7.3 Limits of Dwell Time on Each Channel

According to 15.247(a)(1)(ii), for frequency hopping system operating in the 2400-2483.5MHz and 5725-5850 MHz band, the average time of occupancy on any frequency shall not be greater than **0.4** second within a 30-second period



### 7.4 Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT as shown in test setup without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
3. Adjust the center frequency of spectrum analyzer on any frequency be measured and set spectrum analyzer to zero span mode. And then, set RBW and VBW of spectrum analyzer to proper value.
4. Measure the time duration of one transmission on the measured frequency. And then plot the result with time difference of this time duration.
5. Repeat above procedures until all frequencies measured were complete.
6. The Bluetooth Tablet has 3 type of payload, DH1. The hopping rate is 1600 per second. The longer the payload is, the slower the hopping rate is.

### 7.5 Uncertainty of Conducted Emission

The uncertainty of time is  $\pm 5.25\text{ms}$ .

### 7.6 Test Results

Time of occupancy on the TX channel in 30sec = time domain slot length  $\times$  hop rate  $\div$  number of hop per channel  $\times 30$

Refer to the attached graph.

The hopping rates of Bluetooth devices change with different types of payload. The longer the payload is, the slower the hopping rate. The hopping rate scenario is defined in Bluetooth core specification.

Transmitting Frequency	Packet type	Dwell time (ms)	Time of occupancy on the TX channel in 30sec (ms)	Limit for Time of occupancy on the TX channel in 30sec (ms)	Results
2441MHz	DH1	0.450	273.42	400	Pass

Note : 1. Time of occupancy on the TX channel in 30sec (DH1) =  $450 \mu s \times 1600 \div 79 \times 30 = 273.417721518$  (msec)

2. Three type of package DH1, DH3 and DH5 were used for the EUT. The DH1 was selected as representative for final test results.






# Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., ChuTung Chen, Hsinchu, Taiwan 310, R.O.C  
TEL:886-3-5918012 FAX: 886-3-5825720

FCC ID : NRQRMKT05  
Report No. : ER04-01-004FRF  
Page 25 of 46

## 7.7 Photo of Dwell Time on Each Channel



## 8. BAND EDGE SPURIOUS EMISSIONS

Test Requirement: 15.247(c)


### 8.1 Test Equipments

Description & Manufacturer	Model No.	Serial No.	Date Of Calibration
ROHDE & SCHWARZ SPECTRUM ANALYZER	FSEK30	835253/002	JUN. 17, 2003
HP ATTENUATOR	8496B	3247A18505	Cal. on use
HP PLOTTER	7750A	725A 852141	N/A

Note :

1. The measurement uncertainty is less than +/- 2.6dB, which is calculated as per the NAMAS document NIS81.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

### 8.2 Test Setup



### 8.3 Limits of Band edge Measurements

1. Below -20dB of the highest emission level of operating band (in 100KHz Resolution Bandwidth).
2. Fall in the restricted bands listed in section 15.205. The maximum permitted average field strength is listed in section 15.209.



## **8.4 Test Procedure**

Section 15.247(c): Spurious emissions. The following tests are required:

Set the span wide enough to capture the peak level of the emission operating on the channel closest to the band edge. Set the RBW and VBW and maxhold the trace. Allow the trace to stabilize. Enable the marker-delta function, then use the marker-delta value function to move the marker to the peak of the in-band emission submit the plot.

## **8.5 Uncertainty of Conducted Emission**

The uncertainty of Frequency :  $\pm 100\text{kHz}$ .

The uncertainty of Amplitude :  $\pm 2\text{dB}$ .



### 8.6 Test Results

Band edge		Measured radiated band edge field strength (dBuV/m)		Radiated band edge field strength limit (dBuV/m)		Test result
		Horizontal	Vertical	Horizontal	Vertical	
2399.90	PK	34.79	37.48	68.94	71.63	Pass
	AVG	34.17	36.93	68.32	71.08	
2483.50	PK	26.88	29.68	74.00	74.00	Pass
	AVG	26.20	29.14	54.00	54.00	

NOTE : Radiated band edge field strength is measured with FCC recommended mark-delta method.


Measured radiated band edge field strength Test Results = Radiated fundamental emission field strength - DELTA.

DELTA = Relative measurement between conducted measured peak level of fundamental emission and relevant band edge emission. Please refer to 8.7 photo of band edge Measurement.




### 8.7 Photo of Band edge Measurement

#### Band edge Compliance of RF Conducted Emissions



FRONT



REAR



# Ecom Sertech Corp.



Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., ChuTung Chen, Hsinchu, Taiwan 310, R.O.C  
TEL:886-3-5918012 FAX: 886-3-5825720

FCC ID : H8N-DPR2320G

Report No. : ER03-11-049FRF

Page 30 of 46

## Out-of-band Spurious Emissions-conducted measurement



## 9. OUT OF BAND SPURIOUS EMISSIONS -RADIATED MEASUREMENTS

Test Requirement: 15.247(c)


### 9.1 Test Equipments

The following test equipments are utilized in making the measurements contained in this report.

Manufacturer or Type	Model No	Serial No	Date of Calibration	Calibration Period	Remark
CHASE BI-LOG ANTENNA	CBL6112B	2421	MAY 07, 2003	1 Year	FINAL
R/S SPECTRUM ANALYZER	FSEK30	835253/002	JUN. 17, 2003	1 Year	FINAL
OPEN SITE	-----	No.2	MAY. 09, 2003	1 Year	FINAL
N TYPE COAXIAL CABLE	CHA9525	4	JUL. 13, 2003	1 Year	FINAL
Horn Antenna	AH-118	10089	FEB. 25, 2003	1 Year	FINAL
HP Pre-amplifier	8449B	3008A01471	OCT. 11, 2002	1 Year	FINAL
HP High pass filter	84300/80038	011	cal. on use	1 Year	FINAL
Horn Antenna	AH-840	03077	FEB. 25, 2003	1 Year	FINAL


### 9.2 Test Setup

The diagram below shows the test setup that is utilized to make the measurements for emission from 30 to 1GHz.



Antenna Elevation Variable

The diagram below shows the test setup that is utilized to make the measurements for emission above 1GHz.



Antenna Elevation Variable

### 9.3 Radiation Limit

For unintentional device, according to § 15.109(a), except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values :

Frequency (MHz)	Distance (Meters)	Radiated (dB $\mu$ V/M)	Radiated ( $\mu$ V/M)
30-230	10	30	-----
230-1000	10	37	-----
Above 1000	3	54.0	500

For intentional device, according to § 15.209(a), the general requirement of field strength of radiated emissions from intentional radiators at a distance of 3 meters shall not exceed the above table.





## 9.4 Test Procedures

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 10 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10 dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

### NOTE :

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 KHz for Peak detection (PK) and Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz for Peak detection and frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 10 Hz for Average detection (AV) at frequency above 1GHz.

## 9.5 Uncertainty of Radiated Emission

The uncertainty of radiated emission is  $\pm 2.72\text{dB}$ .



## Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., ChuTung Chen, Hsinchu, Taiwan 310, R.O.C  
TEL:886-3-5918012 FAX: 886-3-5825720

FCC ID : NRQRMKT05  
Report No. : ER04-01-004FRF  
Page 34 of 46

### 9.6 Radiated RF Noise Measurement

Test Requirement: 15.109, 15.209

The frequency spectrum from 30 MHz to 1000 MHz was investigated. All emissions not reported below are more than 20 dB below the prescribed limits.

All readings are quasi-peak values.

Temperature : 21.9 °C

Humidity : 47 % RH

Frequency (MHz)	Antenna Factor (dB)	Cable Loss (dB)	Meter Reading at 10m(dB $\mu$ V/M)		Limits at 10m (dB $\mu$ V/M)	Emission Level at 10m(dB $\mu$ V/M)	
			Horizontal	Vertical		Horizontal	Vertical
30.00	17.98	0.90	*	*	30.00	*	*
120.00	12.48	2.00	8.90	11.40	30.00	23.38	25.88
240.00	12.37	3.12	7.30	8.50	37.00	22.79	23.99
359.99	15.40	3.96	7.10	7.80	37.00	26.46	27.16
479.99	17.74	4.76	8.10	7.30	37.00	30.60	29.80
599.99	19.26	5.40	6.50	6.40	37.00	31.16	31.06
719.98	20.03	6.00	6.20	6.20	37.00	32.23	32.23
839.98	20.64	6.48	5.70	5.80	37.00	32.82	32.92
1000.00	21.30	7.00	*	*	37.00	*	*

REMARKS : 1. \* Undetectable

2. Emission level (dB  $\mu$  V/M) = Antenna Factor (dB/m) + Cable loss (dB)  
+ Meter Reading (dB  $\mu$  V).

3. For Wired mode.



## Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., ChuTung Chen, Hsinchu, Taiwan 310, R.O.C  
TEL:886-3-5918012 FAX : 886-3-5825720

FCC ID : NRQRMKT05  
Report No. : ER04-01-004FRF  
Page 35 of 46

Test Requirement: 15.109, 15.209

The frequency spectrum from 30 MHz to 1000 MHz was investigated. All emissions not reported below are more than 20 dB below the prescribed limits.

All readings are quasi-peak values.

Temperature : 21.9 °C

Humidity : 47 % RH

Frequency (MHz)	Antenna Factor (dB)	Cable Loss (dB)	Meter Reading at 10m(dB $\mu$ V/M)		Limits at 10m (dB $\mu$ V/M)	Emission Level at 10m(dB $\mu$ V/M)	
			Horizontal	Vertical		Horizontal	Vertical
30.00	17.98	0.90	*	*	30.00	*	*
120.00	12.48	2.00	10.50	11.30	30.00	24.98	25.78
240.00	12.37	3.12	8.50	6.80	37.00	23.99	22.29
359.99	15.40	3.96	7.50	7.40	37.00	26.86	26.76
479.99	17.74	4.76	10.10	8.50	37.00	32.60	31.00
599.99	19.26	5.40	7.90	6.70	37.00	32.56	31.36
719.98	20.03	6.00	7.60	6.20	37.00	33.63	32.23
839.98	20.64	6.48	6.00	5.80	37.00	33.12	32.92
1000.00	21.30	7.00	*	*	37.00	*	*

REMARKS : 1. \* Undetectable

2. Emission level (dB  $\mu$  V/M) = Antenna Factor (dB/m) + Cable loss (dB)  
+ Meter Reading (dB  $\mu$  V).

3. For Wireless mode.



## Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., ChuTung Chen, Hsinchu, Taiwan 310, R.O.C  
 TEL:886-3-5918012 FAX : 886-3-5825720

FCC ID : NRQRMKT05  
 Report No. : ER04-01-004FRF  
 Page 36 of 46

Test Requirement: 15.205

The frequency spectrum above 1 GHz was investigated. All emissions not reported below are more than 40 dB below the prescribed limits. Readings are both peak and average values.

Company	AIPTEK International Inc.	Test Date :	2004/01/29
Product Name	Bluetooth Tablet	Test By:	Stan Peng
Model Name	RMK-T05	Temp& Humidity :	14.9°C , 84%

CH01 (2402 MHz) TX (Low)				Measurement Distance at 1m				Horizontal polarity			
Freq.	Reading	AF	Cable	Pre-amp	Dist	Filter	Level	Limit	Margin	Mark	Height
(MHz)	(dBμV)	(dBμV)	(dB)	(dB)	dB	dB	(dBμV/m)	(dBμV/m)	(dB)	(P/Q/A)	(Meter)
* 2353.89	27.38	31.85	4.11	0.00	9.50	0.00	53.84	74	-20.16	P	1.00
* 2353.89	15.38	31.85	4.11	0.00	9.50	0.00	41.84	54	-12.16	A	1.00
2401.73	62.89	31.80	3.75	0.00	9.50	0.00	88.94	Fundamental Frequency		P	1.00
2401.73	62.27	31.80	3.75	0.00	9.50	0.00	88.32			A	1.00
* 4804.02	43.59	34.31	2.85	35.14	9.50	2.08	38.19	74	-35.81	P	1.00
* 4804.02	33.45	34.31	2.85	35.14	9.50	2.08	28.05	54	-25.95	A	1.00
7206.31	42.68	39.82	4.78	35.66	9.50	2.00	44.12	74	-29.88	P	1.00
7206.31	31.56	39.82	4.78	35.66	9.50	2.00	33.00	54	-21.00	A	1.00
9608.05	44.87	38.54	5.90	36.37	9.50	0.64	44.07	74	-29.93	P	1.00
9608.05	33.61	38.54	5.90	36.37	9.50	0.64	32.81	54	-21.19	A	1.00
* 12008.65	-----	-----	-----	-----	9.50	0.80	-----	-----	-----	-----	1.00
14410.38	-----	-----	-----	-----	9.50	0.59	-----	-----	-----	-----	1.00
16812.11	-----	-----	-----	-----	9.50	0.62	-----	-----	-----	-----	1.00
* 19213.84	-----	-----	-----	-----	9.50	2.41	-----	-----	-----	-----	1.00
21615.57	-----	-----	-----	-----	9.50	0.70	-----	-----	-----	-----	1.00
24017.30	-----	-----	-----	-----	9.50	2.28	-----	-----	-----	-----	1.00

Note :

- The measurement was searched to 10th harmonic, Remark “---” means that the emissions level is too low to be measured.
- AF: Antenna Factor, Closs: Cable Loss, Pre-Amp: Preamplifier gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
- Analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
- Remark “\*” means that Restricted band.
- Dist : correction to extra plate reading to 3m specification distance 1m measurement distance = -9.5dB
- The result basic equation calculation is as follow:  
 $Level=Reading+AF+Closs-Preamp+Filter-Dist, Margin=Level-Limit$
- The other emission levels were very low against the limit
- The test limit distance is 3M limit.



## Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., ChuTung Chen, Hsinchu, Taiwan 310, R.O.C  
 TEL:886-3-5918012 FAX : 886-3-5825720

FCC ID : NRQRMKT05  
 Report No. : ER04-01-004FRF  
 Page 37 of 46

Test Requirement: 15.205

The frequency spectrum above 1 GHz was investigated. All emissions not reported below are more than 40 dB below the prescribed limits. Readings are both peak and average values.

Company	AIPTEK International Inc.	Test Date :	2004/01/29
Product Name	Bluetooth Tablet	Test By:	Stan Peng
Model Name	RMK-T05	Temp& Humidity :	14.9°C , 84%

CH01 (2402 MHz) TX (Low)				Measurement Distance at 1m					Vertical polarity			
Freq.	Reading	AF	Cable	Pre-amp	Dist	Filter	Level	Limit	Margin	Mark	Height	
(MHz)	(dBμV)	(dBμV)	(dB)	(dB)	dB	dB	(dBμV/m)	(dBμV/m)	(dB)	(P/Q/A)	(Meter)	
* 2353.89	26.95	31.85	4.11	0.00	9.50	0.00	53.41	74	-20.59	P	1.00	
* 2353.89	15.09	31.85	4.11	0.00	9.50	0.00	41.55	54	-12.45	A	1.00	
2401.78	65.59	31.80	3.75	0.00	9.50	0.00	91.63	Fundamental Frequency		P	1.00	
2401.78	65.04	31.80	3.75	0.00	9.50	0.00	91.08			A	1.00	
* 4804.02	40.28	34.31	2.85	35.14	9.50	2.08	34.88	74	-39.12	P	1.00	
* 4804.02	31.42	34.31	2.85	35.14	9.50	2.08	26.02	54	-27.98	A	1.00	
7206.23	42.38	39.82	4.78	35.66	9.50	2.00	43.82	74	-30.18	P	1.00	
7206.23	33.17	39.82	4.78	35.66	9.50	2.00	34.61	54	-19.39	A	1.00	
9608.05	46.05	38.54	5.90	36.37	9.50	0.64	45.25	74	-28.75	P	1.00	
9608.05	34.84	38.54	5.90	36.37	9.50	0.64	34.04	54	-19.96	A	1.00	
* 12008.90	-----	-----	-----	-----	9.50	0.80	-----	-----	-----	-----	1.00	
14410.68	-----	-----	-----	-----	9.50	0.59	-----	-----	-----	-----	1.00	
16812.46	-----	-----	-----	-----	9.50	0.62	-----	-----	-----	-----	1.00	
* 19214.24	-----	-----	-----	-----	9.50	2.41	-----	-----	-----	-----	1.00	
21616.02	-----	-----	-----	-----	9.50	0.70	-----	-----	-----	-----	1.00	
24017.80	-----	-----	-----	-----	9.50	2.28	-----	-----	-----	-----	1.00	

Note :

- The measurement was searched to 10th harmonic, Remark “---” means that the emissions level is too low to be measured.
- AF: Antenna Factor, Closs: Cable Loss, Pre-Amp: Preamplifier gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
- Analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
- Remark “\*” means that Restricted band.
- Dist : correction to extra plate reading to 3m specification distance 1m measurement distance = -9.5dB
- The result basic equation calculation is as follow:  
 $Level=Reading+AF+Closs-Preamp+Filter-Dist, Margin=Level-Limit$
- The other emission levels were very low against the limit
- The test limit distance is 3M limit.



**Ecom Sertech Corp.**

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., ChuTung Chen, Hsinchu, Taiwan 310, R.O.C  
 TEL:886-3-5918012 FAX : 886-3-5825720

FCC ID : NRQRMKT05  
 Report No. : ER04-01-004FRF  
 Page 38 of 46

Test Requirement: 15.205

The frequency spectrum above 1 GHz was investigated. All emissions not reported below are more than 40 dB below the prescribed limits. Readings are both peak and average values.

Company	AIPTEK International Inc.	Test Date :	2004/01/29
Product Name	Bluetooth Tablet	Test By:	Stan Peng
Model Name	RMK-T05	Temp& Humidity :	14.9°C , 84%

CH40 (2441 MHz) TX (Mid)				Measurement Distance at 1m				Horizontal polarity			
Freq.	Reading	AF	Cable	Pre-amp	Dist	Filter	Level	Limit	Margin	Mark	Height
(MHz)	(dBμV)	(dBμV)	(dB)	(dB)	dB	dB	(dBμV/m)	(dBμV/m)	(dB)	(P/Q/A)	(Meter)
2440.79	62.59	31.76	3.45	0.00	9.50	0.00	88.30	Fundamental Frequency		P	1.00
2440.79	62.03	31.76	3.45	0.00	9.50	0.00	87.74			A	1.00
* 4882.02	42.69	34.82	2.71	35.21	9.50	1.77	37.29	74	-36.71	P	1.00
* 4882.02	32.46	34.82	2.71	35.21	9.50	1.77	27.06	54	-26.94	A	1.00
* 7323.05	43.58	39.77	4.83	35.64	9.50	2.00	45.04	74	-28.96	P	1.00
* 7323.05	32.42	39.77	4.83	35.64	9.50	2.00	33.88	54	-20.12	A	1.00
9764.05	45.97	38.52	5.90	36.62	9.50	0.54	44.81	74	-29.19	P	1.00
9764.05	35.12	38.52	5.90	36.62	9.50	0.54	33.96	54	-20.04	A	1.00
* 12203.95	-----	-----	-----	-----	9.50	0.80	-----	-----	-----	-----	1.00
14644.74	-----	-----	-----	-----	9.50	0.58	-----	-----	-----	-----	1.00
17085.53	-----	-----	-----	-----	9.50	0.77	-----	-----	-----	-----	1.00
* 19526.32	-----	-----	-----	-----	9.50	2.87	-----	-----	-----	-----	1.00
21967.11	-----	-----	-----	-----	9.50	0.70	-----	-----	-----	-----	1.00
24407.90	-----	-----	-----	-----	9.50	1.73	-----	-----	-----	-----	1.00

Note :

- The measurement was searched to 10th harmonic, Remark “---” means that the emissions level is too low to be measured.
- AF: Antenna Factor, Closs: Cable Loss, Pre-Amp: Preamplifier gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
- Analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
- Remark “\*” means that Restricted band.
- Dist : correction to extra plate reading to 3m specification distance 1m measurement distance = -9.5dB
- The result basic equation calculation is as follow:  
 $Level=Reading+AF+Closs-Preamp+Filter-Dist, Margin=Level-Limit$
- The other emission levels were very low against the limit
- The test limit distance is 3M limit.



**Ecom Sertech Corp.**

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., ChuTung Chen, Hsinchu, Taiwan 310, R.O.C  
 TEL:886-3-5918012 FAX : 886-3-5825720

FCC ID : NRQRMKT05  
 Report No. : ER04-01-004FRF  
 Page 39 of 46

Test Requirement: 15.205

The frequency spectrum above 1 GHz was investigated. All emissions not reported below are more than 40 dB below the prescribed limits. Readings are both peak and average values.

Company	AIPTEK International Inc.	Test Date :	2004/01/29
Product Name	Bluetooth Tablet	Test By:	Stan Peng
Model Name	RMK-T05	Temp& Humidity :	14.9°C , 84%

CH40 (2441 MHz) TX (Mid)				Measurement Distance at 1m				Vertical polarity			
Freq.	Reading	AF	Cable	Pre-amp	Dist	Filter	Level	Limit	Margin	Mark	Height
(MHz)	(dBμV)	(dBμV)	(dB)	(dB)	dB	dB	(dBμV/m)	(dBμV/m)	(dB)	(P/Q/A)	(Meter)
2440.76	66.39	31.76	3.45	0.00	9.50	0.00	92.10	Fundamental Frequency		P	1.00
2440.76	65.77	31.76	3.45	0.00	9.50	0.00	91.48			A	1.00
* 4882.01	42.32	34.82	2.71	35.21	9.50	1.77	36.92	74	-37.08	P	1.00
* 4882.01	31.52	34.82	2.71	35.21	9.50	1.77	26.12	54	-27.88	A	1.00
* 7323.05	43.25	39.77	4.83	35.64	9.50	2.00	44.71	74	-29.29	P	1.00
* 7323.05	33.17	39.77	4.83	35.64	9.50	2.00	34.63	54	-19.37	A	1.00
9764.05	46.23	38.52	5.90	36.62	9.50	0.54	45.07	74	-28.93	P	1.00
9764.05	35.04	38.52	5.90	36.62	9.50	0.54	33.88	54	-20.12	A	1.00
* 12203.80	-----	-----	-----	-----	9.50	0.80	-----	-----	-----	-----	1.00
14644.56	-----	-----	-----	-----	9.50	0.58	-----	-----	-----	-----	1.00
17085.32	-----	-----	-----	-----	9.50	0.77	-----	-----	-----	-----	1.00
* 19526.08	-----	-----	-----	-----	9.50	2.87	-----	-----	-----	-----	1.00
21966.84	-----	-----	-----	-----	9.50	0.70	-----	-----	-----	-----	1.00
24407.60	-----	-----	-----	-----	9.50	1.73	-----	-----	-----	-----	1.00

- Note :
- The measurement was searched to 10th harmonic, Remark “---” means that the emissions level is too low to be measured.
  - AF: Antenna Factor, Closs: Cable Loss, Pre-Amp: Preamplifier gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
  - Analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
  - Remark “\*” means that Restricted band.
  - Dist : correction to extra plate reading to 3m specification distance 1m measurement distance = -9.5dB
  - The result basic equation calculation is as follow:  
 $Level=Reading+AF+Closs-Preamp+Filter-Dist, Margin=Level-Limit$
  - The other emission levels were very low against the limit
  - The test limit distance is 3M limit.



**Ecom Sertech Corp.**

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., ChuTung Chen, Hsinchu, Taiwan 310, R.O.C  
 TEL:886-3-5918012 FAX : 886-3-5825720

FCC ID : NRQRMKT05  
 Report No. : ER04-01-004FRF  
 Page 40 of 46

Test Requirement: 15.205

The frequency spectrum above 1 GHz was investigated. All emissions not reported below are more than 40 dB below the prescribed limits. Readings are both peak and average values.

Company	AIPTEK International Inc.	Test Date :	2004/01/29
Product Name	Bluetooth Tablet	Test By:	Stan Peng
Model Name	RMK-T05	Temp& Humidity :	14.9°C , 84%

CH79 (2480 MHz) TX (High)				Measurement Distance at 1m				Horizontal polarity			
Freq.	Reading	AF	Cable	Pre-amp	Dist	Filter	Level	Limit	Margin	Mark	Height
(MHz)	(dBμV)	(dBμV)	(dB)	(dB)	dB	dB	(dBμV/m)	(dBμV/m)	(dB)	(P/Q/A)	(Meter)
2479.74	62.14	31.72	3.15	0.00	9.50	0.00	87.51	Fundamental Frequency		P	1.00
2479.74	61.46	31.72	3.15	0.00	9.50	0.00	86.83			A	1.00
2504.03	27.51	31.70	3.00	0.00	9.50	0.00	52.71	74	-21.29	P	1.00
2504.03	15.98	31.70	3.00	0.00	9.50	0.00	41.18	54	-12.82	A	1.00
* 4960.02	43.25	35.34	2.57	35.27	9.50	1.46	37.85	74	-36.15	P	1.00
* 4960.02	32.39	35.34	2.57	35.27	9.50	1.46	26.99	54	-27.01	A	1.00
* 7440.12	43.05	39.72	4.88	35.61	9.50	2.00	44.54	74	-29.46	P	1.00
* 7440.12	33.78	39.72	4.88	35.61	9.50	2.00	35.27	54	-18.73	A	1.00
9920.14	46.24	38.51	5.90	36.87	9.50	0.45	44.72	74	-29.28	P	1.00
9920.14	34.58	38.51	5.90	36.87	9.50	0.45	33.06	54	-20.94	A	1.00
* 12398.70	-----	-----	-----	-----	9.50	0.80	-----	-----	-----	-----	1.00
14878.44	-----	-----	-----	-----	9.50	0.40	-----	-----	-----	-----	1.00
17358.18	-----	-----	-----	-----	9.50	0.99	-----	-----	-----	-----	1.00
* 19837.92	-----	-----	-----	-----	9.50	4.90	-----	-----	-----	-----	1.00
* 22317.66	-----	-----	-----	-----	9.50	0.70	-----	-----	-----	-----	1.00
24797.40	-----	-----	-----	-----	9.50	1.54	-----	-----	-----	-----	1.00

Note :

- The measurement was searched to 10th harmonic, Remark “---” means that the emissions level is too low to be measured.
- AF: Antenna Factor, Closs: Cable Loss, Pre-Amp: Preamplifier gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
- Analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
- Remark “\*” means that Restricted band.
- Dist : correction to extra plate reading to 3m specification distance 1m measurement distance = -9.5dB
- The result basic equation calculation is as follow:  
 $Level=Reading+AF+Closs-Preamp+Filter-Dist, Margin=Level-Limit$
- The other emission levels were very low against the limit
- The test limit distance is 3M limit.





## Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., ChuTung Chen, Hsinchu, Taiwan 310, R.O.C  
 TEL:886-3-5918012 FAX : 886-3-5825720

FCC ID : NRQRMKT05  
 Report No. : ER04-01-004FRF  
 Page 41 of 46

Test Requirement: 15.205

The frequency spectrum above 1 GHz was investigated. All emissions not reported below are more than 40 dB below the prescribed limits. Readings are both peak and average values.

Company	AIPTEK International Inc.	Test Date :	2004/01/29
Product Name	Bluetooth Tablet	Test By:	Stan Peng
Model Name	RMK-T05	Temp& Humidity :	14.9°C , 84%

CH79 (2480 MHz) TX (High)				Measurement Distance at 1m				Vertical polarity			
Freq.	Reading	AF	Cable	Pre-amp	Dist	Filter	Level	Limit	Margin	Mark	Height
(MHz)	(dBμV)	(dBμV)	(dB)	(dB)	dB	dB	(dBμV/m)	(dBμV/m)	(dB)	(P/Q/A)	(Meter)
2479.79	64.94	31.72	3.15	0.00	9.50	0.00	90.31	Fundamental Frequency		P	1.00
2479.79	64.40	31.72	3.15	0.00	9.50	0.00	89.77			A	1.00
2504.03	27.19	31.70	3.00	0.00	9.50	0.00	52.39	74	-21.61	P	1.00
2504.03	15.98	31.70	3.00	0.00	9.50	0.00	41.18	54	-12.82	A	1.00
* 4960.02	42.28	35.34	2.57	35.27	9.50	1.46	36.88	74	-37.12	P	1.00
* 4960.02	31.68	35.34	2.57	35.27	9.50	1.46	26.28	54	-27.72	A	1.00
* 7440.05	43.28	39.72	4.88	35.61	9.50	2.00	44.77	74	-29.23	P	1.00
* 7440.05	32.74	39.72	4.88	35.61	9.50	2.00	34.23	54	-19.77	A	1.00
9920.12	45.96	38.51	5.90	36.87	9.50	0.45	44.44	74	-29.56	P	1.00
9920.12	34.48	38.51	5.90	36.87	9.50	0.45	32.96	54	-21.04	A	1.00
* 12398.95	-----	-----	-----	-----	9.50	0.80	-----	-----	-----	-----	1.00
14878.74	-----	-----	-----	-----	9.50	0.40	-----	-----	-----	-----	1.00
17358.53	-----	-----	-----	-----	9.50	0.99	-----	-----	-----	-----	1.00
* 19838.32	-----	-----	-----	-----	9.50	4.90	-----	-----	-----	-----	1.00
* 22318.11	-----	-----	-----	-----	9.50	0.70	-----	-----	-----	-----	1.00
24797.90	-----	-----	-----	-----	9.50	1.54	-----	-----	-----	-----	1.00

Note :

- The measurement was searched to 10th harmonic, Remark “---” means that the emissions level is too low to be measured.
- AF: Antenna Factor, Closs: Cable Loss, Pre-Amp: Preamplifier gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
- Analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
- Remark “\*” means that Restricted band.
- Dist : correction to extra plate reading to 3m specification distance 1m measurement distance = -9.5dB
- The result basic equation calculation is as follow:  
 $Level = Reading + AF + Closs - Preamp + Filter - Dist$ ,  $Margin = Level - Limit$
- The other emission levels were very low against the limit
- The test limit distance is 3M limit.

## 9.7 Photos of Open Site





**Ecom Sertech Corp.**

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., ChuTung Chen, Hsinchu, Taiwan 310, R.O.C  
TEL:886-3-5918012 FAX : 886-3-5825720

FCC ID : NRQRMKT05  
Report No. : ER04-01-004FRF  
Page 43 of 46





## **10. ANTENNA REQUIREMENT**

### **10.1 Standard Applicable**

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

### **10.2 Antenna Connected Construction**

The antenna used in this product is PCB antenna. The antenna connector is directly soldered on PCB. And the maximum Gain of this antenna is only 1.5dBi MAX.



## 11. RF EXPOSURE EVALUATION

According to FCC 1.1310 : The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)  
LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Average Time
(A) Limits for Occupational / Control Exposures				
300-1,500	--	--	F/300	6
1,500-100,000	--	--	5	6
(B) Limits for General Population / Uncontrol Exposures				
300-1,500	--	--	F/1500	6
1,500-100,000	--	--	1	30

### 11.1 Friis Formula

Friis transmission formula :  $Pd = (Pout * G) / (4 * \pi * r^2)$

Where

Pd = power density in mW/cm<sup>2</sup>

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

Pd is the limit of MPE, 1 mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

### 11.2 EUT Operating Condition

A software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.



### 11.3 Test Result of RF Exposure Evaluation

Test Item : RF Exposure Evaluation Data

Test Mode : Normal Operation

#### 11.3.1 Antenna Gain

Antenna Gain : The maximum Gain measured in fully anechoic chamber is 1.5dBi linear scale.

#### 11.3.2 Output Power into Antenna & RF Exposure Evaluation Distance

Channel	Channel Frequency (MHz)	Output Power to Antenna (dBm)	Antenna Gain	Power Density at 20cm (mW/cm <sup>2</sup> )	LIMITS (mW/cm <sup>2</sup> )
CH01 (Low)	2402.00	-0.77	1.5	0.000235	1
CH40 (Mid)	2441.00	-1.15	1.5	0.000216	1
CH79 (High)	2480.00	-1.57	1.5	0.000196	1

The power density Pd (4<sup>th</sup> column) at a distance of 20cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm<sup>2</sup>. The EUT is classified as portable product and the output power is lower than the FCC low threshold. So, RF exposure limit warning or SAR test are not required.