



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AF016128-001

Date : 2005 July 19

Application No. : LF209271(0)

Client : Manley Toys Ltd
8/F., Hong Kong Spinners Industries Building,
818 Cheung Sha Wan Road,
Kowloon, Hong Kong

Sample Description : One(1) submitted sample stated to be:

Item Name	Model No.
Hydro Xtreme Raceway (red, blue, green, orange)	18134
Hydro Xtreme Racer (green, yellow, black)	17243

Rating : 1 x 1.2V rechargeable battery

No. of submitted sample : Two (2) piece(2)***

Date Received : 2005 June 08

Test Period : 2005 June 08 – 2005 June 17

Test Requested : FCC Part 15 Certification

Test Method : FCC Rules and Regulations Part 15 – July 2004
ANSI C63.4 – 2003

Test Result : See attached sheet(s) from page 2 to 11.

Conclusion : The submitted sample was found to comply with requirement of FCC Part 15 Subpart B.

Remark : All two models are the same in circuitry and components and construction, and therefore model 18134 (Hydro Xtreme Raceway) was chosen to be the representative of the test sample.

For and on behalf of
CMA Testing and Certification Laboratories

Authorized Signature : _____

Danny Chui
EMC Engineer - EL. Division

Page 1 of 11

FCC ID : NS618134-49RX

This document shall not be reproduced either in full or in part except with written approval by the Authorized Representative of CMA Testing.

Room 1302, Yan Hing Centre, 9-13 Wong Chuk Yeung St., Fo Tan, Shatin, Hong Kong.

Tel: (852) 2698 8198 Fax: (852) 2695 4177 E-mail: info@cmactl.com Web Site: <http://www.cmactl.com>



TEST REPORT

Report No. : AF016128-001

Date : 2005 July 19

Table of Contents

1	General Information	3
1.1	General Description	3
1.2	Location of the test site	4
1.3	List of measuring equipment.....	5
2	Description of the radiated emission test	6
2.1	Test Procedure.....	6
2.2	Test Result.....	6
2.3	Radiated Emission Measurement Data	7
3	Description of the Line-conducted Test	8
3.1	Test Procedure.....	8
3.2	Test Result.....	8
3.3	Graph and Table of Conducted Emission Measurement Data	8
4	Photograph.....	9
4.1	Photographs of the Test Setup for Radiated Emission and Conduction Emission	9
4.2	Photographs of the External and Internal Configurations of the EUT.....	9
5	Supplementary document	10
5.1	Bandwidth	10
5.2	Duty Cycle.....	10
6	Appendices	11



TEST REPORT

Report No. : AF016128-001

Date : 2005 July 19

1 General Information

1.1 General Description

The equipment under test (EUT) is a superregenerative for operating at 49.860MHz which is controlled by a LRC circuit. The EUT is powered by a 1.2V rechargeable battery while switch on, it can receive radio signal from the transmitter continuously.

The brief circuit description is listed as follows :

- RX 2C and associated circuit act as signal decoder.
- Q1 and associated circuit act as RF receiver.
- Q2 – Q9 and associated circuit act as motor driving.



TEST REPORT

Report No. : AF016128-001

Date : 2005 July 19

1.2 Location of the test site

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 – 2003. A Semi-Anechoic Chamber Testing Site is set up for investigation and located at :

Ground Floor, Yan Hing Centre,
9 – 13 Wong Chuk Yeung Street,
Fo Tan, Shatin,
New Territories,
Hong Kong.

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 – 2003. A shielded room is located at :

Ground Floor, Yan Hing Centre,
9 – 13 Wong Chuk Yeung Street,
Fo Tan, Shatin,
New Territories,
Hong Kong.



TEST REPORT

Report No. : AF016128-001

Date : 2005 July 19

1.3 List of measuring equipment

Equipment	Manufacturer	Model No.	Serial No.	Calibration Certification No.
EMI Test Receiver	R&S	ESCS30	100001	S43284
Broadband Antenna	Schaffner	CBL6112B	2692	CA3025
Signal Generator	IFR	2023B	202302/938	S43098
LISN	R&S	ESH3-Z5	100038	S43377
LISN	R&S	ESH3-Z5	100010	S43101
Pulse Limiter	R&S	ESH3-Z2	100001	S43325
Biconical Antenna	R&S	HK116	837414/004	2GB05000535-0001
Loop Antenna	EMCO	6502	00056620	49906



TEST REPORT

Report No. : AF016128-001

Date : 2005 July 19

2 Description of the radiated emission test

2.1 Test Procedure

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 – 2003.

The equipment under test (EUT) was placed on a non-conductive turntable with dimensions of 1.5m x 1m and 0.8m high above the ground. 3m from the EUT, a broadband antenna mounting on the mast received the signal strength. The turntable was rotated to maximize the emission level. The antenna was then moving along the mast from 1m up to 4m until no more higher value was found. Both horizontal and vertical polarization of the antenna were placed and investigated.

For below 30MHz, a loop antenna with its vertical plane is placed 3m from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. And the centre of the loop shall be 1 m above the ground.

A signal generator was used to radiate an unmodulated continuous wave (CW) signal to the EUT (superregenerative receiver) at its operating frequency in order to “cohere” the characteristic broadband emissions from the receiver.

2.2 Test Result

All operation modes had been tested.

All other measurements are well below the limit. Thus, those highest emissions were presented in next page.

The harmonic emissions meeting the requirement of section 15.109 are based on measurements employing the CISPR quasi-peak detector.

It was found that the EUT meet the FCC requirement.



TEST REPORT

Report No. : AF016128-001

Date : 2005 July 19

2.3 Radiated Emission Measurement Data

**Radiated emission
pursuant to
the requirement of FCC Part 15 subpart B**

Frequency (MHz)	Polarity (H/V)	Reading at 3m (dB μ V/m)	Antenna and Cable factor (dB)	Field Strength (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
48.562	V	14.5	10.3	24.8	40.0	-15.2
49.012	V	15.5	10.3	25.8	40.0	-14.2
49.319	V	15.8	10.3	26.1	40.0	-13.9
49.400	V	13.9	10.3	24.2	40.0	-15.8
50.594	V	15.0	8.1	23.1	40.0	-16.9
98.452	V	13.4	9.2	22.6	43.5	-20.9
99.629	V	13.7	9.2	22.9	43.5	-20.6
101.420	V	12.1	11.0	23.1	43.5	-20.4
148.072	V	11.6	11.9	23.5	43.5	-20.0
149.579	V	12.1	11.9	24.0	43.5	-19.5



TEST REPORT

Report No. : AF016128-001

Date : 2005 July 19

3 Description of the Line-conducted Test

3.1 Test Procedure

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 – 2003. The EUT was setup as described in the procedures, and both lines were measured.

3.2 Test Result

No measurement is required as the EUT is a battery-operated product.

3.3 Graph and Table of Conducted Emission Measurement Data

Not Applicable



TEST REPORT

Report No. : AF016128-001

Date : 2005 July 19

4 Photograph

4.1 Photographs of the Test Setup for Radiated Emission and Conduction Emission

For electronic filing, the photos are saved with filename TSup1.jpg to TSup2.jpg

4.2 Photographs of the External and Internal Configurations of the EUT

For electronic filing, the photos are saved with filename ExPho1.jpg to ExPho2.jpg and InPho1.jpg to InPho2.jpg.



TEST REPORT

Report No. : AF016128-001

Date : 2005 July 19

5 Supplementary document

The following document were submitted by applicant, and for electronic filing, the document are saved with the following filenames:

Document	Filename
ID Label/Location	LabelSmp.jpg
Block Diagram	BlkDia.pdf
Schematic Diagram	Schem.pdf
Users Manual	UserMan.pdf
Operational Description	OpDes.pdf

5.1 Bandwidth

N/A

5.2 Duty Cycle

N/A



TEST REPORT

Report No. : AF016128-001

Date : 2005 July 19

6 Appendices

A1	Photos of the set-up of Radiated Emissions	1 page
A2	Photos of External Configurations	1 page
A3	Photos of Internal Configurations	1 page
A4	ID Label/Location	1 page
A5	Block Diagram	1 page
A6	Schematics Diagram	1 page
A7	User Manual	3 pages
A8	Operation Description	1 page

***** End of Report *****