

ALLEGRO REPEATER (2WREPEATER), FCC ID:NTA2WREP1

23 April 2016

RF Exposure calculation

Based on FCC 1.1307 & 2.1091, FCC OET Bulletin 65

1. Categorically Exclusion from exposure Evaluation:

According to FCC regulation, RF exposure evaluation is Categorically Excluded if transmitter's operation frequency is less than 1.5GHz and ERP is less than 1.5W.

2. Absolute maximum specification of 2WREPEATER transmitter

- Operational frequency band **450MHz to 470MHz**
- The 2WREPEATER transmitter is measured for **MAX RF Power 19.95W**
- Absolute **Maximum transmission time(duration)** for any 2WREPEATER transmitters does not exceed **0.32 s**
- Transmission period-absolute maximum is **3 transmission per hour**
- ALL 2WREPEATER transmitters utilize 4GFSK modulation

3. Average RF Power Calculation

FCC regulation on permissible RF exposure are not based on the peak envelope power, but on average power (P_{ave}) over a 30-minute time period for uncontrolled environments.

As mentioned in (2), during any 30 minutes 2WMMR can transmit 1.5 times. Duration is 0.32 second.

With maximum RF radiation equal to 19.95W, the average RF Power over 30 minutes is:

$$P_{ave}(\text{worst case}) \text{ at 30 minute} = 19.95 \times 1.5 \times 0.32 / 30 \times 60 = 5.3 \text{ mW}$$

4. Maximum radiated Power Density prediction (S):

The predict power density (S) at distance **R=20cm** from transmitter with $P_{ave} = 5.3 \text{ mW}$, next formula is used:

$$S=P_{ave}/(4\pi R^2)$$

For the worst case prediction of power density at or near a transmitter surface let's use:

$$S=P_{ave}/(4\pi R^2) =$$

$$5.3\text{mW}/(4\pi \times 3.14 \times 20\text{cm} \times 20\text{cm}) = 0.11\text{uW/cm}^2$$

This is the worst case of the near field power density of 2WREPEATER transmitter.

5. Maximum Permissible Exposure (MPE) from 2WREPEATER

As FCC require, the maximum permissible exposure for general public in "uncontrolled situation" at 20cm is:

$$MPE=frequency[\text{MHz}]/1500=460\text{MHz}/1500=0.307\text{mW/cm}^2$$

Compare results in (4) and (5),

$$S=0.11\text{uW/cm}^2 < MPE=0.307\text{mW/cm}^2$$

We see that 2WREPEATER fully complies with RF safety at a distance 20cm.

Dr. Slava Snitkovsky

Telematics-Wireless

