

USER'S GUIDE

THE TEXT OF THIS INSTRUCTIONS WILL BE PRINTED ON THE SURFACE OF THE INDIVIDUAL BOX AT THE TIME OF MASS PRODUCTION.

1. PRODUCT SPECIFICATION

MODEL NO.	VOLTAGE(V)	FREQUENCY(Hz)	POWER(W)	CURRENT(A)	LIFE(Hrs)
EQUR1235AP	120	60	35	0.5	10,000

2. USER'S GUIDE

ELECTRONIC BALLAST

INSTANT ON, FLICKER-FREE AND LIGHT WEIGHT

RELIABLE OPERATING TEMPERATURE RANGE : -10 TO 40

1) CAUTION

NOT FOR USE WITH DIMMERS.

NOT FOR USE WITH TOTALLY ENCLOSED RECESSED FIXTURES.

RISK OF ELECTRIC SHOCK - USE ONLY IN DRY LOCATIONS.

THIS DEVICE IS NOT INTENDED FOR USE WITH EMERGENCY EXIT FIXTURES OR
EMERGENCY EXIT LIGHTS.

NOT FOR USE WHERE EXPOSED TO THE WEATHER.

2) NOTE

This product may cause interference to radio equipment and should not be installed near maritime safety communications equipment or other critical navigation or communication equipment operating between 0.45-30MHz.

Do not touch the lamp as soon as turn off because it is very hot.