

## USER'S GUIDE

THE TEXT OF THIS INSTRUCTIONS WILL BE PRINTED ON THE SURFACE OF THE INDIVIDUAL BOX AT THE TIME OF MASS PRODUCTION.

### 1. PRODUCT SPECIFICATION

MODEL NO.	VOLTAGE(V)	FREQUENCY(Hz)	POWER(W)	CURRENT(A)	LIFE(Hrs)
ES1215N	120	60	15	0.25	10,000

### 2. USER'S GUIDE

ELECTRONIC BALLAST

INSTANT ON, FLICKER-FREE AND LIGHT WEIGHT

RELIABLE OPERATING TEMPERATURE RANGE : -10 TO 40

#### 1)CAUTION

NOT FOR USE WITH DIMMERS.

NOT FOR USE WITH TOTALLY ENCLOSED RECESSED FIXTURES.

RISK OF ELECTRIC SHOCK - USE ONLY IN DRY LOCATIONS.

THIS DEVICE IS NOT INTENDED FOR USE WITH EMERGENCY EXIT FIXTURES OR EMERGENCY EXIT LIGHTS.

NOT FOR USE WHERE EXPOSED TO THE WEATHER.

#### 2) NOTE

This product may cause interference to radio equipment and should not be installed near maritime safety communications equipment or other critical navigation or communication equipment operating between 0.45-30MHz.

Do not touch the lamp as soon as turn off because it is very hot.