

## USER'S GUIDE

THE TEXT OF THIS INSTRUCTIONS WILL BE PRINTED ON THE SURFACE OF THE INDIVIDUAL BOX AT THE TIME OF MASS PRODUCTION.

### 1. PRODUCT SPECIFICATION

MODEL NO.	VOLTAGE(V)	FREQUENCY(Hz)	POWER(W)	CURRENT(A)
ES1235AF	120	60	35	0.48

### 2. USER ' S GUIDE

ELECTRONIC BALLAST

INSTANT ON, FLICKER-FREE

RELIABLE OPERATING TEMPERATURE RANGE : - 10 TO 40

#### 1) CAUTION

NOT FOR USE WITH DIMMERS.

NOT FOR USE WITH TOTALLY ENCLOSED RECESSED FIXTURES.

RISK OF ELECTRIC SHOCK - USE ONLY IN DRY LOCATIONS.

THIS DEVICE IS NOT INTENDED FOR USE WITH EMERGENCY EXIT FIXTURES OR EMERGENCY EXIT LIGHTS.

NOT FOR USE WHERE EXPOSED TO THE WEATHER.

#### 2) NOTE

THIS PRODUCT MAY CAUSE RADIO INTERFERENCE WITH RADIOS, CORDLESS PHONES OR REMOTE CONTROL DEVICE. IF INTERFERENCE OCCURS, RELOCATED THIS PRODUCT AWAY FROM THE DEVICE OR REMOVE THIS PRODUCT OUT OF THE LINE OF SIGHT WITH THE REMOTE CONTROL RECEIVER.

DO NOT TOUCH THE LAMP AS SOON AS TURN OFF BECAUSE IT IS VERY HOT.

#### FCC NOTICE

THIS PRODUCT MAY CAUSE INTERFERENCE TO RADIO EQUIPMENT AND SHOULD NOT BE INSTALLED NEAR MARITIME SAFETY COMMUNICATIONS EQUIPMENT OR OTHER CRITICAL NAVIGATION OR COMMUNICATION EQUIPMENT OPERATING BETWEEN .45-30 MHZ.