

## USER'S GUIDE

① THE TEXT OF THIS INSTRUCTIONS WILL BE PRINTED ON THE SURFACE OF THE INDIVIDUAL BOX AT THE TIME OF MASS PRODUCTION.

### 1. PRODUCT SPECIFICATION

MODEL NO.	VOLTAGE(V)	FREQUENCY(Hz)	POWER(W)	CURRENT(A)	LIFE(Hrs)
ETU1209GOB	120	60	9	0.16	10,000
ETU1211GOB	120	60	11	0.18	10,000

### 2. USER'S GUIDE

- ELECTRONIC BALLAST
- INSTANT ON, FLICKER-FREE AND LIGHT WEIGHT
- RELIABLE OPERATING TEMPERATURE RANGE : -10 °C TO 40 °C

#### 1) CAUTION

- ① NOT FOR USE WITH DIMMERS.
- ② NOT FOR USE WITH TOTALLY ENCLOSED RECESSED FIXTURES.
- ③ RISK OF ELECTRIC SHOCK - USE ONLY IN DRY LOCATIONS.
- ④ THIS DEVICE IS NOT INTENDED FOR USE WITH EMERGENCY EXIT FIXTURES OR EMERGENCY EXIT LIGHTS.
- ⑤ NOT FOR USE WHERE EXPOSED TO THE WEATHER.

#### 2) NOTE

- ① THIS PRODUCT MAY CAUSE INTERFERENCE TO RADIO EQUIPMENT AND SHOULD NOT BE INSTALLED NEAR MARITIME SAFETY COMMUNICATIONS EQUIPMENT OR OTHER CRITICAL NAVIGATION OR COMMUNICATION EQUIPMENT OPERATING BETWEEN 0.45-30MHz
- ② DO NOT TOUCH THE LAMP AS SOON AS TURN OFF BECAUSE IT IS VERY HOT.