



TEST REPORT

Report No. : AC003352-1

Date : 2002 April 17

Client : Yuen Tat Electronic Toys Manufactory Ltd.
9A, 9/F., Merit Ind. Centre,
94 Tokwawan Road,
Kowloon, Hong Kong.

Sample Description : Sample stated to be B/O Walkie Talkie.
Model No. : YT-998A
Rating : 1 x 9 V size battery
No. of sample(s) : Two(2) sets ***

Date Received : 2002 March 15.

Test Period : 2002 March 15 – 2002 April 16.

Test Requested : FCC Part 15 Certification

Test Method : FCC Rules and Regulations Part 15 – May 2001
ANSI C63.4 – 1992

Test Result : See attached sheet(s) from page 2 to 10.

Conclusion : The submitted sample was found to comply with requirement of FCC
Part 15 Subpart C.

For and on behalf of
CMA Testing and Certification Laboratories

Authorized Signature :

Danny Chui
EMC Engineer - EL. Division

FCC ID : NUY-YT-998A

Page 1 of 10



TEST REPORT

Report No. : AC003352-1

Date : 2002 April 17

Table of Contents

1	General Information	3
1.1	General Description	3
1.2	Related Submittal Grants	3
1.3	Location of the test site	4
1.4	List of measuring equipment	5
2	Description of the radiated emission test	6
2.1	Test Procedure	6
2.2	Test Result	6
2.3	Radiated Emission Measurement Data	7
3	Description of the Line-conducted Test	8
3.1	Test Procedure	8
3.2	Test Result	8
3.3	Graph and Table of Conducted Emission Measurement Data	8
4	Photograph.....	9
4.1	Photographs of the Test Setup for Radiated Emission and Conduction Emission	9
4.2	Photographs of the External and Internal Configurations of the EUT	9
5	Supplementary document	9
5.1	Bandwidth.....	9
6	Appendices	10

FCC ID : NUY-YT-998A

Page 2 of 10

This document shall not be reproduced either in full or in part except with written approval by the Authorized Representative of CMA Testing.

Room 1401-3, Yan Hing Centre, 9-13 Wong Chuk Yeung St., Fo Tan, Shatin, Hong Kong.

Tel: (852) 2698 8198 Fax: (852) 2695 4177 E-mail: info@cmatcl.com Web Site: <http://www.cmatcl.com>



TEST REPORT

Report No. : AC003352-1

Date : 2002 April 17

1 General Information

1.1 General Description

The equipment under test (EUT) is a transmitter for B/O Walkie Talkie operating at 49.860 MHz which is controlled by a crystal. The EUT is powered by a 9 V size battery. The EUT has an ON/OFF volume control for switching to the ON, OFF and volume level. It also has a “PUSH-TO-TALK” button for transmitting and receiving voice signal and a “MORSE CODE KEY” for transmitting morse code signals.

The brief circuit description is listed as follows :

- XTAL 49.860, Q1 and associated circuit act as Oscillation / RF & DET. STAGE
- Q2 and associated circuit act as Driver Amplification
- Q3, Q4 and associated circuit act as Power Amplification

1.2 Related Submittal Grants

This is a single application for certification of a transmitter. The receiver for this transmitter is authorized by Verification procedure.

FCC ID : NUY-YT-998A

Page 3 of 10



TEST REPORT

Report No. : AC003352-1

Date : 2002 April 17

1.3 Location of the test site

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 – 1992. An Open Area Testing Site is set up for investigation and located at :

Top of the Roof, Yan Hing Centre,
9 – 13 Wong Chuk Yeung Street,
Fo Tan, Shatin,
New Territories,
Hong Kong.

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 – 1992. A double shielded room is located at :

Roof Floor, Yan Hing Centre,
9 – 13 Wong Chuk Yeung Street,
Fo Tan, Shatin,
New Territories,
Hong Kong.

FCC ID : NUY-YT-998A

Page 4 of 10



TEST REPORT

Report No. : AC003352-1

Date : 2002 April 17

1.4 List of measuring equipment

Equipment	Manufacturer	Model No.	Serial No.	Calibration Certification No.	Calibration Date	Calibration Due Date
EMI Test Receiver	R&S	ESCS30	100001	20-69223	Mar. 21, 2001	Sept. 20, 2002
Broadband Antenna	Schaffner	CBL6113B	2718	AC1753	Dec. 15, 2000	Jun. 14, 2002
Signal Generator	IFR	2023B	202302/938	Nil	Oct. 23, 2000	Apr. 22, 2002
LISN	R&S	ESH3-Z5	100010	20-70405	Mar. 29, 2001	Sept. 28, 2002
Pulse Limiter	R&S	ESH3-Z2	100001	20-73194	May 2, 2001	Nov. 1, 2002
Biconical Antenna	R&S	HK116	837414/004	4000.7752.02	Oct. 23, 2000	Apr. 22, 2002

FCC ID : NUY-YT-998A

Page 5 of 10

This document shall not be reproduced either in full or in part except with written approval by the Authorized Representative of CMA Testing.

Room 1401-3, Yan Hing Centre, 9-13 Wong Chuk Yeung St., Fo Tan, Shatin, Hong Kong.

Tel: (852) 2698 8198 Fax: (852) 2695 4177 E-mail: info@cmatcl.com Web Site: <http://www.cmatcl.com>



TEST REPORT

Report No. : AC003352-1

Date : 2002 April 17

2 Description of the radiated emission test

2.1 Test Procedure

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 – 1992.

The equipment under test (EUT) was placed on a non-conductive turntable with dimensions of 1.5m x 1m and 0.8m high above the ground. 3m from the EUT, a broadband antenna mounting on the mast received the signal strength. The turntable was rotated to maximize the emission level. The antenna was then moving along the mast from 1m up to 4m until no more higher value was found. Both horizontal and vertical polarization of the antenna were placed and investigated.

2.2 Test Result

The fundamental emission was based on measurements employing the peak detector on the open area test site.

The harmonic emissions meeting the requirement of section 15.209 are based on measurements employing the CISPR quasipeak detector.

* Emissions appearing within the restricted bands shall follow the requirement of section 15.205.

It was found that the EUT meet the FCC requirement.

FCC ID : NUY-YT-998A

Page 6 of 10

This document shall not be reproduced either in full or in part except with written approval by the Authorized Representative of CMA Testing.

Room 1401-3, Yan Hing Centre, 9-13 Wong Chuk Yeung St., Fo Tan, Shatin, Hong Kong.

Tel: (852) 2698 8198 Fax: (852) 2695 4177 E-mail: info@cmatcl.com Web Site: <http://www.cmatcl.com>



TEST REPORT

Report No. : AC003352-1

Date : 2002 April 17

2.3 Radiated Emission Measurement Data

Radiated emission
pursuant to
the requirement of FCC Part 15 subpart C

Frequency (MHz)	Polarity (H/V)	Reading at 3m (dB μ V/m)	Antenna and Cable factor (dB)	Field Strength (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
49.849	V	37.2	12.9	50.1	80.0	-29.9
99.698	V	14.7	12.1	26.8	43.5	-16.7
149.547	V	13.0	14.5	27.5	43.5	-16.0
199.396	V	16.1	13.4	29.5	43.5	-14.0
*249.245	V	20.4	14.2	34.6	46.0	-11.4
299.094	V	9.0	17.5	26.5	46.0	-19.5
348.943	V	14.6	19.7	34.3	46.0	-11.7
398.792	V	15.5	19.7	35.2	46.0	-10.8
448.641	V	12.9	24.2	37.1	46.0	-8.9
498.490	V	15.2	24.2	39.4	46.0	-6.6

FCC ID : NUY-YT-998A

Page 7 of 10



TEST REPORT

Report No. : AC003352-1

Date : 2002 April 17

3 Description of the Line-conducted Test

3.1 Test Procedure

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 – 1992. The EUT was setup as described in the procedures, and both lines were measured.

3.2 Test Result

No measurement is required as the EUT is a battery-operated product.

3.3 Graph and Table of Conducted Emission Measurement Data

Not Applicable

FCC ID : NUY-YT-998A

Page 8 of 10



TEST REPORT

Report No. : AC003352-1

Date : 2002 April 17

4 Photograph

4.1 Photographs of the Test Setup for Radiated Emission and Conduction Emission

For electronic filing, the photos are saved with filename TSup1.jpg to TSup2.jpg

4.2 Photographs of the External and Internal Configurations of the EUT

For electronic filing, the photos are saved with filename ExtPho1.jpg to ExtPho2.jpg and IntPho1.jpg to IntPho2.jpg.

5 Supplementary document

The following document were submitted by applicant, and for electronic filing, the document are saved with the following filenames:

Document	Filename
ID Label/Location	LabelSmpl.pdf
Block Diagram	BlkDia.pdf
Schematic Diagram	Schem.pdf
Users Manual	UserMan.pdf
Operational Description	OpDes.pdf

5.1 Bandwidth

The plot on saved in TestRpt2 and TestRpt3.pdf shows the fundamental emission is confined in the specified band. The field strength of any emission appearing between the band edges and up to 10 kHz above and below the band edges (49.81 and 49.91 MHz) is at least 26 dB below the carrier level. It meets the requirement of Section 15.235(b).

FCC ID : NUY-YT-998A

Page 9 of 10



TEST REPORT

Report No. : AC003352-1

Date : 2002 April 17

6 Appendices

A1	Photos of the set-up of Radiated Emissions	1 page
A2	Photos of External Configurations	1 page
A3	Photos of Internal Configurations	1 page
A4	ID Label/Location	1 page
A5	Block Diagram	1 page
A6	Schematics	1 page
A7	User Manual	1 page
A8	Operation Description	1 page
A9	Bandwidth Plot	2 pages

***** End of Report *****

FCC ID : NUY-YT-998A

Page 10 of 10