



RF EXPOSURE REPORT

REPORT NO.: SA951204L02

MODEL NO.: CS8025

ACCORDING: FCC Guidelines for Human Exposure
IEEE C95.1

APPLICANT: In-Tech Electronics Ltd.

ADDRESS: 207-210, 2/F, Century Centre 44-46 Hung To Road,
Kwun Tong , Kowloon, Hong Kong

ISSUED BY: Advance Data Technology Corporation

LAB ADDRESS: No. 47, 14th Ling, Chia Pau Tsuen, Lin Kou
Hsiang 244, Taipei Hsien, Taiwan, R.O.C.

TEST LOCATION: No. 19, Hwa Ya 2nd Rd., Wen Hwa Tsuen, Kwei
Shan Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.



No Evaluation Required if power is below this threshold:

F(GHz)		mW
Low	2.402	24.58
High	2.480	

Maximum measured transmitter power:

Pout (dBm)		Pout (mW)
Conducted Power	-0.350	0.923
EIRP Power	-0.350	0.923

***Note:** The antenna is PCB antenna with 0dBi gain

Threshold for no SAR evaluation is 24.58mW

Transmitter power is 0.923mW

Conclusion: No SAR evaluation required since Transmitter Pout is below FCC threshold