

RETLIF TESTING LABORATORIES

EMISSIONS DATA SHEET

Test Method:	Spurious Radiated Emissions (ERP) 30 MHz to 20 GHz		
Customer:	Cellular Specialties, Inc.	Job No:	R-4132N
Test Sample:	Bidirectional Amplifier		
Model No:	150PCS	Serial No:	n/a
Test Specification:	FCC Part 2.1053\Part 24 Paragraph: n/a		
Operating Mode:	Amplifying input signal		
Technician:	T. Firkowski	Date:	5/30/03
Notes:	Uplink Frequency Range:1850-1910 MHz Tested at 1880 MHz Peak Detector		

[illegible]

No EUT emissions observed within 20 dB of the limit.

RETLIF TESTING LABORATORIES

EMISSIONS DATA SHEET

Test Method:	Spurious Radiated Emissions (ERP) 30 MHz to 20 GHz		
Customer:	Cellular Specialties, Inc.	Job No:	R-4132N
Test Sample:	Bidirectional Amplifier		
Model No:	150PCS	Serial No:	n/a
Test Specification:	FCC Part 2.1053\Part 24 Paragraph: n/a		
Operating Mode:	Amplifying input signal		
Technician:	T. Firkowski	Date:	5/30/03
Notes:	Uplink Frequency Range:1930-1990 MHz Tested at 1960 MHz Peak Detector		

[illegible]