

EMISSIONS DATA SHEET

Spurious Emissions at the Antenna Terminals 30 MHz to 9 GHz

Cellular Specialties, Inc.

R-4416N3

Dual Band Bidirectional Amplifier

CSI510-S89

	n/a
--	-----

FCC Part 2

Paragraph: 2.1051

Amplifying input signal

T. Firkowski

4/6/2005

Uplink Frequency Range: 806 - 824MHz

Downlink Frequency Range: 851 - 869MHz

TDMA Modulation

[illegible]

No EUT emissions observed within 20dB of the limit

RETLIF TESTING LABORATORIES

EMISSIONS DATA SHEET

Test Method:

Spurious Emissions at the Antenna Terminals 30 MHz to 9.5 GHz

Customer:

Cellular Specialties, Inc.

Job No:

R-4416N3

Test Sample:

Dual Band Bidirectional Amplifier

Model No:

CSI510-S89

Serial No:

n/a

Test Specification:

FCC Part 2

Paragraph: 2.1051

Operating Mode:

Amplifying input signal

Technician:

T. Firkowski

Date:

4/6/2005

Notes:

Uplink Frequency Range: 896 to 901 MHz

Downlink Frequency Range: 935 to 940 MHz

TDMA Modulation

[illegible]

No EUT emissions observed within 20dB of the limit