

RETLIF TESTING LABORATORIES

TABULAR DATA SHEET

Test Method:

RF Power Output

Customer:

Cellular Specialties, Inc.

Job No:

R-4416N1

Test Sample:

Dual Band Bidirectional Amplifier

Model No:

CSI510-S89

Serial No:

n/a

Test Specification:

FCC Part 2

Paragraph: 2.1046

Operating Mode:

Amplifying input signal

Technician:

T. Firkowski

Date:

4/1/2005

Notes:

Low Band - Uplink Frequency Range: 806-824 MHz Downlink Frequency Range: 851-869 MHz

RF Power output data taken from the two tone test combined power

[illegible]

RETLIF TESTING LABORATORIES

TABULAR DATA SHEET

Test Method:

RF Power Output

Customer:

Cellular Specialties, Inc.

Job No:

R-4416N1

Test Sample:

Dual Band Bidirectional Amplifier

Model No:

CS1510-S89

Serial No:

n/a

Test Specification:

FCC Part 2

Paragraph: 2.1046

Operating Mode:

Amplifying input signal

Technician:

T. Firkowski

22

Date:

4/1/2005

Notes:

High Band - Uplink Frequency Range: 896-901 GHz	Downlink Frequency Range: 935-940 GHz
---	---------------------------------------

RF Power output data taken from the two tone test combined power

[illegible]