

EMISSIONS DATA SHEET

Test Method:	Spurious Radiated Emissions (ERP) 30 MHz to 10 GHz		
Customer:	Cellular Specialties, Inc.	Job No:	R-4412N3
Test Sample:	Bidirectional Amplifier		
Model No:	610-S9	Serial No:	n/a
Test Specification:	FCC Part 2 Paragraph: 2.1053		
Operating Mode:	Amplifying input signal		
Technician:	T. Firkowski	Date:	3/28/2005
Notes:	Uplink Frequency Range: 896-901 MHz 3 Input Frequencies Tested, 896MHz, 898MHz, 901MHz Peak Detector Modulation: CW		

[illegible]

No EUT emissions observed within 20 dB of the limit.

RETLIF TESTING LABORATORIES

EMISSIONS DATA SHEET

Test Method:	Spurious Radiated Emissions (ERP) 30 MHz to 10 GHz		
Customer:	Cellular Specialties, Inc.	Job No:	R-4412N3
Test Sample:	Bidirectional Amplifier		
Model No:	610-S9	Serial No:	n/a
Test Specification:	FCC Part 2 Paragraph: 2.1053		
Operating Mode:	Amplifying input signal		
Technician:	T. Firkowski	Date:	3/28/2005
Notes:	Downlink Frequency Range: 935-940 MHz 3 Input Frequencies Tested, 935MHz, 937MHz, 940MHz Peak Detector Modulation: CW		

[illegible]

No EUT emissions observed within 20 dB of the limit.