

EXHIBIT B - TEST REPORT NO 3793/1686 FROM TRLEMC

BRAIN BOXES LIMITED
UNIT 3c WAVERTREE BOULEVARD SOUTH
WAVERTREE TECHNOLOGY PARK
LIVERPOOL L7 9PF
TEL: 0151 220 2500
FAX: 0151 252 0446
Registered in England: No. 3245094

TEST REPORT NO: 3793/1686

COPY NO: 1

ISSUE NO: 1

**REPORT ON THE RFI TESTING OF A
BRAIN BOXES
PCI 4- PORT RS 232 CARD
WITH RESPECT TO
THE FCC RULES CFR 47: JULY 1996
PART 15 LIMIT B**

TEST DATE: 16TH - 19TH MARCH 1998

TESTED BY: *John Charters* J CHARTERSAPPROVED BY: *S Hayes* S HAYES

DATE: 14/4/98

**THIS DOCUMENT MAY BE REPRODUCED ONLY IN ITS
ENTIRETY AND WITHOUT CHANGE**

Distribution:

Copy Nos: 1 BRAIN BOXES
2 TRL EMC Ltd

TRL EMC Ltd

MOSS VIEW NIPE LANE UP HOLLAND WEST LANCASHIRE WN8 9PY UNITED KINGDOM

TELEPHONE +44(0)1695 556666 FACSIMILE +44(0)1695 557077

E-MAIL info@trl-emc.co.uk WWW <http://www.trl-emc.co.uk>

QUALITY SYSTEM CERTIFIED TO
BS EN ISO 9001 (1994)
REGISTRATION FS 21805



TESTING
No. 0728
No. 0728 SI
No. 1359

SUMMARY

TEST REPORT NO: 3793/1686

TRL EMC LTD WO: 3793

PURPOSE OF TEST: Radio Frequency Interference Emissions Certification

TEST SPECIFICATION: FCC Rules CFR 47 (JULY 1996) Part 15 LIMIT B

EQUIPMENT UNDER TEST: PCI 4- PORT RS 232 CARD

EQUIPMENT SERIAL NO: PR-9

TEST RESULT: Measured as Compliant
(Note uncertainty values in Appendix B)

MANUFACTURER/AGENT: BRAIN BOXES
UNIT 3, WAVERTREE BOULEVARD SOUTH
WAVERTREE TECHNOLOGY PARK
LIVERPOOL
L7 9PF

ORDER NO: 2994

TESTED BY: TRL EMC LTD

DATE OF TEST: 16TH - 19TH MARCH 1998

CONTENTS

1	INTRODUCTION
2	SYSTEM UNDER TEST
	2.1 Equipment Under Test (EUT)
	2.2 System Equipment
	2.3 Modes of Operation of EUT During Testing
	2.4 Block Diagram of EUT Configuration
3	TEST CONDITIONS
	3.1 Power Line Conducted Emissions
	3.2 Radiated E-Field Emissions
4	RESULTS OF TEST
	4.1 Sample Calculations
5	LIST OF RFI MODIFICATIONS
6	CONCLUSIONS
	6.1 Result of Testing
	6.2 Conformity in Production
APPENDIX A	GRAPHS
	A1 POWER LINE CONDUCTED EMISSIONS
	A2 RADIATED E-FIELD EMISSIONS
APPENDIX B	MEASUREMENT UNCERTAINTY
APPENDIX C	PHOTOGRAPHS
	C1 POWER LINE CONDUCTED EMISSIONS
	C2 RADIATED E-FIELD EMISSIONS
APPENDIX D	ADDITIONAL INFORMATION

1 INTRODUCTION

This report presents the results of Radio Frequency Interference (RFI) tests carried out in accordance with the FCC Rules CFR 47: JULY 1996 Part 15, LIMIT B, specification on equipment type PCI 4- PORT RS 232 CARD.

The testing was carried out for BRAIN BOXES by TRL EMC Ltd, an independent test house, at their EMC test facility located at Up Holland, West Lancashire, England.

The test site is FCC listed and is calibrated as recommended in Document ANSI C63.4 1992.

This report also details the configuration of the equipment under test, the test methods used and any relevant modifications where appropriate.

The equipment and peripherals were operated as specified in ANSI C63.4: 1992 Document.

2 SYSTEM UNDER TEST

2.1 Equipment Under Test (EUT)

BRAIN BOXES

PCI 4- PORT RS 232 CARD

Serial No: PR-9

Model No: CC-268

2.2 System Equipment

IBM Keyboard
FCC ID: 13914OC

Microsoft Mouse
FCC ID: C3KK S8
Serial No: 00766211

Printer Canon BJ30
FCC ID AZDK10152
Serial No: XAM28294


PC Dell Dimension P100t
FCC ID: E2KHN TRDMT

Monitor DA1565VA
FCC ID: H7 9DA-1565
Serial No: BD1649 D28783

2.3 Modes of Operation of EUT During Testing

During the test the PC was running EMC test 5 software. This software made the card transmit RS 232 data to each port in turn. At the RS 232 output port the cable split 4 ways, each was terminated with a loop back connector so that the data returned to the card.

2.4 Block Diagram of EUT Configuration



NOTE: All cables unshielded unless otherwise stated.
Cable lengths are as shown in diagram.

3 TEST CONDITIONS

3.1 Power Line Conducted Emissions

Measurement Freq Range	: -	450kHz - 30MHz
Line Voltage	: -	110 V AC
Line Frequency	: -	60 Hz
Artificial Mains Network (AMN) Impedance	: -	50 ohm/50 μ H
Receiver bandwidth detectors	: -	9kHz Quasi-Peak (CISPR Time Constants) and Average
Configuration	: -	Conforming to ANSI C63.4: 1992 Document
EUT Height	: -	0.8m
Remarks	: -	All initial measurements were carried out using "Peak" and "Average" detectors. Any disturbances found to be within 6dB of the relevant limit were then re-measured using the "Quasi-Peak" and "Average" detectors and compared against the relevant limit over a one second period.
Measurement Uncertainty	: -	See Appendix B

3.1 **Power Line Conducted Emissions** continued..

Test equipment used for the Power Line Conduction measurement was:

TYPE OF EQUIPMENT	MAKER/ SUPPLIER	MODEL No	SERIAL No	TRL EMC No	ACTUAL EQUIPMENT USED
LISN/AMN	R & S	ESH3-Z5	863906/018	UH05	X
LISN/AMN	SCHWARZBECK	NSLK8128	164	UH76	
RECEIVER	R & S	ESHS 10	830051/001	UH03	X
RECEIVER	R & S	ESPC	843756/007	UH101	
SOFTWARE	R & S	ESXS-K1 V2.03b	840.913/162	N/A	X

3.2 Radiated E-Field Emissions

Measurement Freq Range	:=	30MHz - 1000MHz
Measurement Distance	:=	10 metres
Antenna Height	:=	1 - 4 metres
Antenna Polarisation	:=	Vertical and Horizontal
Receiver bandwidths detectors	:=	120kHz Quasi-peak (CISPR Time constants)
Ambient Conditions	:=	16°C WET
EUT Height	:=	0.8 metre
Remarks	:=	All measurements were carried out on an open field test site constructed and calibrated in accordance with ANSI C63.4: 1992 Document. All significant emissions were maximised by: a) rotating the EUT b) elevating antenna c) polarising antenna Horizontal and Vertical d) manipulation and placement of system and power cables.
Measurement Uncertainty	:=	See Appendix B

3.2 Radiated E-Field Emissions continued..

Test equipment used for this radiated emission measurement was:

TYPE OF EQUIPMENT	MAKER/ SUPPLIER	MODEL No	SERIAL No	TRL EMC No	ACTUAL EQUIPMENT USED
OATS	TRL EMC	3m	N/A	UH06	
OATS	TRL EMC	10M	N/A	UH07	X
BICONE ANT	SCHWARZBECK	VHBA 9123		UH29	
LOG. P. ANT		UHALP9108		UH28	
BILOG ANT	CHASE EMC	CBL 6111	1519	UH70	
BILOG ANT	CHASE EMC	CBL 6112	2006	UH93	X
RECEIVER	R & S	ESVS10	825892/06	UH04	X
RECEIVER	R & S	ESPC	843756/007	UH101	
SOFTWARE	R & S	ESXS-K1 V2.02.06a	840.913/032	N/A	X

4 RESULTS OF TESTS

All measurements were taken with the EUT operating in a mode that activates all components of the equipment see Section 2.3. All external interface cables were connected and loaded with the appropriate terminations.

Significant emissions are shown on the following graphs:

GRAPH A1: Power Line Conducted Emissions

GRAPH A2: Radiated E-Field Emissions

The results recorded on Graph 2 are maximum values recorded with respect to EUT azimuth, receiver antenna polarisation and height.

The table below summarises worst case results.

MEASUREMENT	FREQUENCY	EMISSION LEVEL	LIMIT VALUE
Power Line Conduction Quasi Peak Detector (Graph A1)	NO SIGNIFICANT	EMISSIONS WITHIN	6 dB μ V OF LIMIT
Power Line Conduction Average Detector (Graph A1)	1.535 MHz	43.99 dB μ V	48 dB μ V
Radiated E-Field Emissions (Graph A2)	34.1 MHz	24.3 dB μ V/m	30 dB μ V/m

4.1 Sample Calculation

The radiated emission levels used in the report are calculated thus:

FREQUENCY (MHz)	MEASURED VALUE (dB μ V)	ANTENNA VALUE (dBV/m)	EMISSION LEVEL (dB μ V/m)
34.1	8.5	15.8	24.3

5 LIST OF RFI MODIFICATIONS

During the test there were no EMC modifications incorporated into the equipment .

6 CONCLUSIONS

6.1 Result of Testing

The BRAIN BOXES , PCI 4- PORT RS 232 CARD meets the requirements of FCC Rules CFR 47 (JULY 1996) Part 15, LIMIT B in the configuration tested defined in section 2 of this report and incorporating any modifications detailed in section 5 of this report.

Note should be taken of modifications (if any) as described in section 5 of this report.

6.2 Conformity in Production


TRL EMC Ltd has based this test report on results from the equipment sample(s) provided.


The manufacturer is advised that they may have an obligation to demonstrate that production samples are in conformity with the Standards noted.

APPENDIX A
GRAPHS

Graph A1:

POWER LINE CONDUCTED EMISSIONS





APPENDIX B
MEASUREMENT UNCERTAINTY

PROC NO	RF109
ISSUE	2
DATE	15.10.96

**EMC TEST MEASUREMENT UNCERTAINTY
SCHEDULE A**

LABORATORY TESTS

MEASUREMENT	EXPANDED UNCERTAINTY		
	LONG GREEN	UP HOLLAND	
E-FIELD STRENGTH 10m	$\leq 300\text{MHz}$ $\geq 300\text{MHz}$	$\pm 4.45\text{dB}$ $\pm 4.45\text{dB}$	$\pm 2.4\text{dB}$ $\pm 2.4\text{dB}$
E-FIELD STRENGTH 3m	$\leq 300\text{MHz}$ $\geq 300\text{MHz}$	$\pm 4.13\text{dB}$ $\pm 4.03\text{dB}$	$\pm 3.4\text{dB}$ $\pm 3.4\text{dB}$
CONDUCTED EMISSIONS AC Power Line	PROBE LISN/AMN	$\pm 1.19\text{dB}$ $\pm 1.26\text{dB}$	$\pm 1.19\text{dB}$ $\pm 0.98\text{dB}$
H-FIELD STRENGTH		$\pm 2.25\text{dB}$	$\pm 2.14\text{dB}$
RFS	3V/m 10V/m	$\pm 0.83\text{V}$ $\pm 1.87\text{V}$	$\pm 0.83\text{V}$ $\pm 1.5\text{V}$
ESD	$\leq 10\text{kV}$ $\geq 10\text{kV}$	$\pm 220\text{V}$ $\pm 320\text{V}$	$\pm 220\text{V}$ $\pm 320\text{V}$
FAST BURST TRANSIENTS	$\leq 2\text{kV}$ $\geq 2\text{kV}$	$\pm 100\text{V}$ $\pm 110\text{V}$	$\pm 100\text{V}$ $\pm 110\text{V}$
DIPS AND VARIATIONS		$\pm 3.39\%$	$\pm 3.39\%$

SITE TESTS

MEASUREMENT	MOBILE 1	MOBILE 2	
E-FIELD STRENGTH Manufacturers Site	$\leq 300\text{MHz}$ $\geq 300\text{MHz}$	$\pm 6.38\text{dB}$ $\pm 5.99\text{dB}$	$\pm 6.38\text{dB}$ $\pm 5.99\text{dB}$
E-FIELD STRENGTH User Site	$\leq 300\text{MHz}$ $\geq 300\text{MHz}$	$\pm 1.68\text{dB}$ $\pm 1.68\text{dB}$	$\pm 1.68\text{dB}$ $\pm 1.68\text{dB}$
CONDUCTED EMISSIONS AC Power Line	PROBE LISN/AMN	$\pm 1.19\text{dB}$ $\pm 1.26\text{dB}$	$\pm 1.19\text{dB}$ $\pm 1.26\text{dB}$

FULL MEASUREMENT UNCERTAINTY BUDGETS AND CALCULATIONS APPEAR IN PROCEDURE 54-P015.

APPENDIX C
PHOTOGRAPHS

APPENDIX D
ADDITIONAL INFORMATION

ADDITIONAL INFORMATION

Power Line Conduction Scan Data.
TRL EMC LTD

20 Mar 1998 04:21

POWERLINE CONDUCTION

EUT: 4port rs232 pci card
 Manuf: BRAIN BOXES
 Op Cond: ESH3-Z5 LISN, TRLUH21
 Operator: J CHARTERS
 Test Spec: EN55022 CLASS B (OR VARIANT)
 Comment: NEUTRAL


File: pc2.dat : BAIN BOXES NEUTRAL

Scan Settings (1 Range)

Scan Settings	Frequencies			Receiver Settings					
	Start	Stop	Step	IF BW	Detector	M-Time	Atten	Preamp	OpRge
	150kHz	30MHz	5kHz	10kHz	PK+AV	10msec	Auto	OFF	60dB
Transducer	No.	Start	Stop		Name				
	1	9kHz	30MHz		UH21				

Final Measurement: X QP / + AV

Meas Time: 2sec
 Subranges: 25
 Acc Margin: 6 dB



PAGE 1

TRL EMC LTD
POWERLINE CONDUCTION

20 Mar 1998 04:21

EUT: 4port rs232 pci card
Manuf: BRAIN BOXES
Op Cond: ESH3-Z5 LISN, TRLUH21
Operator: J CHARTERS
Test Spec: EN55022 CLASS B (OR VARIANT)
Comment: NEUTRAL

File: pc2.dat : BAIN BOXES NEUTRAL

Scan Settings		(1 Range)			Receiver Settings					
		Start	Stop	Step	IF BW	Detector	M-Time	Atten	Preamp	OpRge
		150kHz	30MHz	5kHz	10kHz	PK+AV	10msec	Auto	OFF	60dB
Transducer	No.		Start		Stop		Name			
	1		9kHz		30MHz		UH21			

Final Measurement: X QP / + AV
Meas Time: 2sec
Subranges: 25
Acc Margin: 6 dB

Final Measurement Results:

Frequency MHz	QP Level dB μ V	QP Limit dB μ V	QP Delta dB
------------------	------------------------	------------------------	----------------

No results

Frequency MHz	AV Level dB μ V	AV Limit dB μ V	AV Delta dB
0.28	47.96	50.82	2.86
0.315	47.85	49.84	1.99
0.375	44.65	48.39	3.74
1.535	43.99	46.00	2.01
1.565	43.48	46.00	2.52
5.995	40.26	50.00	9.74

* limit exceeded

TRL EMC LIMITED
RADIANTE EMISSIONS

19 Mar 1998 10:41

EUT: PCI QUAD RS232 CARD
Manuf: BRAIN BOXES
Op Cond: PRESCAN (INDOOR) AT 3m
Operator: J CHARTERS
Test Spec: FCC PT. 15 LIMIT B
Comment: NEW PRINTER CABLE - BACK TO INITIAL PRINTER

File: 6.dat : New Measurement


Scan Settings (1 Range)

Scan Settings	Frequencies			Receiver Settings					
	Start	Stop	Step	IF BW	Detector	M-Time	Atten	Preamp	OpRge
	30MHz	1GHz	50kHz	120kHz	PK	1msec	Auto	ON	60dB

Transducer	No.	Start	Stop	Name
1	15	30MHz	1GHz	TRLUH72
	21	30MHz	1GHz	CBL6112

Final Measurement:

X QP
Meas Time: 1sec
Subranges: 50
dB μ V/m Acc Margin: 6dB FCCb3M



* (7)

TRL EMC LIMITED
RADIATED EMISSIONS

19 Mar 1998 10:41

EUT: PCI QUAD RS232 CARD
 Manuf: BRAIN BOXES
 Op Cond: PRESCAN (INDOOR) AT 3m
 Operator: J CHARTERS
 Test Spec: FCC PT. 15 LIMIT B
 Comment: NEW PRINTER CABLE - BACK TO INITIAL PRINTER

File: 6.dat : New Measurement

Scan Settings (1 Range)

Transducer	No.	Frequencies		Receiver Settings					Preamp ON	OpRge 60dB
		Start 30MHz	Stop 1GHz	Step 50kHz	IF BW 120kHz	Detector PK	M-Time 1msec	Atten Auto		
1	15	30MHz	1GHz	50kHz	120kHz	PK	1msec	Auto		
	21	30MHz	1GHz	50kHz	120kHz	PK	1msec	Auto		

Final Measurement: X QP
 Meas Time: 1sec
 Subranges: 50
 Acc Margin: 6 dB

Final Measurement Results:

Frequency MHz	QP Level dB μ V/m	QP Limit dB μ V/m	QP Delta dB
34.2	29.43	39.50	10.07 <i>OUT</i>
35.75	30.32	39.50	9.18 <i>OUT</i>
37.5	30.83	39.50	8.67 <i>OUT</i>
44.3	33.57	39.50	5.93 <i>OUT</i>
60.0	33.38	39.50	6.12 <i>OUT</i>
62.3	30.26	39.50	9.24 <i>OUT</i>
72.3	32.73	39.50	6.77 <i>OUT</i>
77.45	34.04	39.50	5.46 <i>OUT</i>
988.2	35.40	47.00	11.60 <i>A</i>

* limit exceeded

PAGE 2