

ELECTROMAGNETIC EMISSION COMPLIANCE REPORT FOR SUPERHETRODYNE RECEIVER

Test Report No. : E113R-055
AGR No. : A113A-065
Applicant : Shinchang Electrics Co., Ltd.
Address : 734-2, Wonshi-dong, Danwon-gu, Ansan-si, Kyungki-do, 425-090, Korea
Manufacturer : Shinchang Electrics Co., Ltd.
Address : 734-2, Wonshi-dong, Danwon-gu, Ansan-si, Kyungki-do, 425-090, Korea
Type of Equipment : Remote Keyless Entry System
FCC ID : NYOSEKS-SL11ARX
Model No. : SEKS-SL11ARx
Serial number : N/A
Total page of Report : 9 pages (including this page)
Date of Incoming : March 07, 2011
Date of issuing : March 22, 2011

SUMMARY

The equipment complies with the regulation; **FCC CFR 47 PART 15 SUBPART B, Section 15.101**.


This test report contains only the result of a single test of the sample supplied for the examination. It is not a general valid assessment of the features of the respective products of the mass-production.

Prepared by:



Young-Min, Choi / Chief Engineer
EMC/RF Center
ONETECH Corp.

Reviewed by:


Y. K. Kwon / Exe. Managing Director
EMC/RF Center
ONETECH Corp.

This report shall not be reproduced except in full without our written approval.

EMC-003 (Rev.1)

HEAD OFFICE : #505 SK Apt. Factory, 223-28 Sangdaewon 1-dong, Jungwon-gu, Seongnam-si, Gyeonggi-do 462-121 Korea
(TEL: 82-31-746-8500 FAX: 82-31-746-8700)

EMC Testing Dept : 307-51 Daessangnyeong-ri, Chowol-eup, Gwangju-si, Gyeonggi-do 464-862 Korea (TEL: 82-31-765-8289 FAX: 82-31-766-2904)

CONTENTS

	Page
1. VERIFICATION OF COMPLIANCE.....	3
2. GENERAL INFORMATION.....	4
2.1 PRODUCT DESCRIPTION.....	4
2.2 MODEL DIFFERENCES:	4
2.3 RELATED SUBMITTAL(S) / GRANT(S)	4
2.4 PURPOSE OF THE TEST	4
2.5 TEST METHODOLOGY	4
2.6 TEST FACILITY	4
3. SYSTEM TEST CONFIGURATION.....	5
3.1 JUSTIFICATION	5
3.2 PERIPHERAL EQUIPMENT.....	5
3.3 MODE OF OPERATION DURING THE TEST.....	5
3.4 EQUIPMENT MODIFICATIONS	5
3.5 CONFIGURATION OF TEST SYSTEM	6
4. PRELIMINARY TEST	6
4.1 AC POWER LINE CONDUCTED EMISSIONS TESTS.....	6
4.2 RADIATED EMISSIONS TESTS.....	6
5. FINAL RESULT OF MEASURMENT	7
5.1 RADIATED EMISSION TEST	7
6. FIELD STRENGTH CALCULATION	8
7. LIST OF TEST EQUIPMENT.....	9

1. VERIFICATION OF COMPLIANCE

APPLICANT : Shinchang Electrics Co., Ltd.
ADDRESS : 734-2, Wonshi-dong, Danwon-gu, Ansan-si, Kyungki-do, 425-090, Korea
CONTACT PERSON : Mr. Jae-Ik, Jo / Quality Control Staff
TELEPHONE NO : +82-41-901-0487
FCC ID : NYOSEKS-SL11ARX
MODEL NAME : SEKS-SL11ARx
BRAND NAME : SL BCM / KIA
SERIAL NUMBER : N/A
DATE : March 22, 2011

EQUIPMENT CLASS	CYY - Communications Receiver used w/ Pt 15 Tx
E.U.T. DESCRIPTION	Remote Keyless Entry System - SUPERHETRODYNE RECEIVER
THIS REPORT CONCERNS	Original Grant
MEASUREMENT PROCEDURES	ANSI C63.4: 2009
TYPE OF EQUIPMENT TESTED	Pre-Production
KIND OF EQUIPMENT AUTHORIZATION REQUESTED	Certification
EQUIPMENT WILL BE OPERATED UNDER FCC RULES PART(S)	FCC PART 15 § 15.101
MODIFICATIONS ON THE EQUIPMENT TO ACHIEVE COMPLIANCE	No
FINAL TEST WAS CONDUCTED ON	3 m open area test site

The above equipment was tested by ONETECH Corp. for compliance with the requirement set forth in the FCC Rules and Regulations. This said equipment in the configuration described in this report, shows the maximum emission levels emanating from equipment are within the compliance requirements.

2. GENERAL INFORMATION

2.1 Product Description

The SHINCHANG ELECTRICS CO., LTD., Model SEKS-SL11ARx (referred to as the EUT in this report) is a receiver that is fixed inside the vehicle and receives the signal from the transmitter, Model: SEKS-AM11ATx and FCC ID: NYOSEKSAM11ATX, which was manufactured by Shingchang Electrics Co., Ltd. and then decided locking and unlocking the door of the vehicle. The product specification described herein was obtained from product data sheet or user's manual.

CHASSIS TYPE	Plastic
RECEIVING FREQUENCY	315.00 MHz
LIST OF EACH OSC. OR CRY. FREQ.(FREQ. \geq 1 MHz)	4 MHz
ANTENNA TYPE	External Antenna
RATED SUPPLY VOLTAGE	DC 12 V
OPERATING VOLTAGE	DC 9 V ~ 16 V
NUMBER OF LAYERS	2 Layers

2.2 Model Differences:

- None

2.3 Related Submittal(s) / Grant(s)

Original submittal only

2.4 Purpose of the test

To determine whether the equipment under test fulfills the requirements of the regulation stated in section 15.101.

2.5 Test Methodology

Radiated testing was performed according to the procedures in ANSI C63.4: 2009 at a distance of 3 m from EUT to the antenna.

2.6 Test Facility

The open area test site and conducted measurement facilities are located on at 307-51 Daessangnyeong-ri, Chowol-eup, Gwangju-si, Gyeonggi-do, 464-862, Korea. Description details of test facilities were submitted to the Commission on August 21, 2008. (Registration Number: 340658)

3. SYSTEM TEST CONFIGURATION

3.1 Justification

This device was configured for testing in a typical way as a normal customer is supposed to be used. During the test, the following components were installed inside of the EUT.

DEVICE TYPE	MANUFACTURER	MODEL/PART NUMBER	FCC ID
Main Board	N/A	SL11MY BCM-P1.0	N/A
RF Board	N/A	RFM_T_V3.0	N/A

3.2 Peripheral equipment

The EUT was tested with the following all equipment used in the tested systems are:

Model	Manufacturer	FCC ID	Description	Connected to
SEKS-SL11ARx	Shinchang Electrics Co., Ltd.	NYOSEKS-SL11ARX	Receiver (EUT)	Battery
N/A	N/A	N/A	Battery	EUT
N/A	N/A	N/A	Jig Box	EUT
SEKS-AM11ATx	Shinchang Electrics Co., Ltd.	NYOSEKSAM11ATX	Transmitter	N/A

3.3 Mode of operation during the test

- To get a maximum radiated emission from the EUT, the button on the transmitter was continuously pressed to transmit the signal. To activate continuous transmission, place a small plastic block between rubber band and the push button on the transmitter.

3.4 Equipment Modifications

- None

3.5 Configuration of Test System

Line Conducted Emission Test:

It is not need to test this requirement, because the power of the EUT supplies from a car battery.

Radiated Emission Test:

Preliminary radiated emissions tests were conducted using the procedure in ANSI C63.4: 2003, 8.3.1.1 to determine the worse operating conditions. Final radiated emission tests were conducted at 3 meters open area test site.

Coherent Test:

During Radiated Emission Tests, use a transmitter, model SEKS-AM11ATx, to emit a frequency of 315.00 MHz to touch off the EUT. Then take down the highest readings.

Antenna Power Conduction Test:

This equipment was only with a permanently attached antenna, so the radiated emission measurement was performed with the antenna attached.

4. PRELIMINARY TEST

4.1 AC Power line Conducted Emissions Tests

During Preliminary Tests, the following operating mode was investigated

Operation Mode	The Worse operating condition (Please check one only)
It is not need to test this requirement, because the power of the EUT is supplied from a car battery.	

4.2 Radiated Emissions Tests

During Preliminary Tests, the following operating modes were investigated

Operation Mode	The Worse operating condition (Please check one only)
RX mode	X

5. FINAL RESULT OF MEASURMENT

Preliminary test was done in normal operation mode. And the final measurement was selected for the maximized emission level.

5.1 Radiated Emission Test

The following table shows the highest levels of radiated emission on both polarizations of horizontal and vertical.

Humidity Level	: <u>38 % R.H.</u>	Temperature: <u>16 °C</u>
Limits apply to	: <u>FCC CFR 47, Part 15, Subpart B (Section: 15.109)</u>	
Detector	: CISPR Quasi-Peak (6 dB Bandwidth: 120 kHz)	
Type of Test	: <u>Unintentional Radiator</u>	
Result	: <u>PASSED BY -16.85 dB at 33.96 MHz</u>	

EUT : Remote Keyless Entry System Date: March 10, 2011
Operating Condition : RX mode
Distance : 3 m

Frequency (MHz)	Reading (dB μ V)	Ant. Pol. (H/V)	Ant. Height (m)	Angle (°)	Ant. Factor (dB/m)	Cable Loss	Emission Level(dB μ V/m)	Limits (dB μ V/m)	Margin (dB)
33.96	5.40	H	1.00	120.00	16.75	1.00	23.15	40.00	-16.85
68.95	6.20	H	1.00	150.00	6.96	2.06	15.22	40.00	-24.78
91.99	6.30	H	1.00	260.00	8.86	2.10	17.26	43.52	-26.26
129.60	5.20	H	1.00	280.00	14.12	2.50	21.82	43.52	-21.70
223.00	4.90	H	1.00	190.00	17.21	3.38	25.49	46.02	-20.53
451.30	4.70	H	1.00	300.00	18.44	4.31	27.45	46.02	-18.57

Other frequencies were not observed any emissions up to 2 GHz.

Radiated Emission Tabulated Data

Tested by: Young-Cheol, Park / Engineer

6. FIELD STRENGTH CALCULATION

Meter readings are compared to the specification limit correcting for antenna and cable losses

+ Meter reading	(dB μ V)
+ Cable Loss	(dB)
<u>+ Antenna Factor (Loss)</u>	<u>(dB/m)</u>
= Corrected Reading	(dB μ V/m)
<u>- Specification Limit</u>	<u>(dBμV/m)</u>
= dB Relative to Spec	(\pm dB)

7. LIST OF TEST EQUIPMENT

No.	EQUIPMENTS	MFR.	MODEL	SER. NO.	LAST CAL	DUE CAL	USE
1.	Test receiver	R/S	ESVD	838453/018	OCT/10	12MONTH	■
2.	Test receiver	R/S	ESHS 10	834467/007	MAY/10	12MONTH	
3.	Spectrum analyzer	HP	8566B	3407A08547	JUN/10	12MONTH	■
4.	TRILOG Broadband Antenna	Schwarzbeck	VULB9163	VULB9163-202	MAY/10	24MONTH	
5.	Biconical antenna	EMCO	3110	9003-1121	FEB/10	24MONTH	■
		Schwarzbeck	VHA9103	91031852	MAR/10		
6.	Log Periodic antenna	EMCO	3146	9001-2614	FEB/10	24MONTH	■
		Schwarzbeck	9108-A(494)	62281001	MAR/10		
7.	LISN	EMCO	3825/2	9109-1867	JUN/10	12MONTH	
				9109-1869	JUN/10		
		Schwarzbeck	NSLK 8128	8128-216	JUN/10		
8.	Position Controller	HD GmbH	HD100	N/A	N/A	N/A	■
9.	Turn Table	HD GmbH	DS420S	N/A	N/A	N/A	■
10.	Antenna Master	HD GmbH	MA240	N/A	N/A	N/A	■
11.	RF Amplifier	HP	8447D	2944A06539	JUN/10	12MONTH	■
12.	Horn Antenna	Schwarzbeck	BBHA9120D	BBHA9120D294	JUN/09	24MONTH	■
13.	Spectrum Analyzer	HP	8564E	3650A00756	JUN/10	12MONTH	■
14.	Isolation Transformer	Digitek Power	DPT	DPF-22027	N/A	N/A	■
15.	Isolation Transformer	Digitek Power	DPT	DPF-22028	N/A	N/A	■
16.	Frequency Converter	Digitek Power	VFS/DEFC	N/A	N/A	N/A	■