

FCC Part 15C Measurement and Test Report

For

Winstars Technology Limited

Block 4, TaiSong Industrial Park, Dalang Street, LongHua Town,

Bao'an district, Shenzhen, China

FCC ID: NZ3WS-WN565N1

FCC Rule(s):	<u>FCC Part 15C</u>
Product Description:	<u>Wireless N Travel AP/Router</u>
Tested Model:	<u>WS-WN565N1</u>
Report No.:	<u>STR16018223I-1</u>
Tested Date:	<u>2016-02-02 to 2016-02-25</u>
Issued Date:	<u>2016-02-25</u>
Tested By:	<u>Leo Lee / Engineer</u>
Reviewed By:	<u>Silin Chen / EMC Manager</u>
Approved & Authorized By:	<u>Jandy so / PSQ Manager</u>
Prepared By:	

Leo Lee
Silin Chen
Jandyso

Shenzhen SEM.Test Technology Co., Ltd.

1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road,
Bao'an District, Shenzhen, P.R.C. (518101)

Tel.: +86-755-33663308 Fax.: +86-755-33663309 Website: www.semtest.com.cn

Note: This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Shenzhen SEM.Test Technology Co., Ltd.

TABLE OF CONTENTS

1. GENERAL INFORMATION	4
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
1.2 TEST STANDARDS	5
1.3 TEST METHODOLOGY	5
1.4 TABLE FOR PARAMETERS OF TEST SOFTWARE SETTING	5
1.5 EUT OPERATING DURING TEST	5
1.6 TEST FACILITY	6
1.7 EUT SETUP AND TEST MODE	6
1.8 TEST EQUIPMENT LIST AND DETAILS	7
2. SUMMARY OF TEST RESULTS	8
3. RF EXPOSURE	9
3.1 STANDARD APPLICABLE	9
3.2 TEST RESULT	9
4. ANTENNA REQUIREMENT	10
4.1 STANDARD APPLICABLE	10
4.2 EVALUATION INFORMATION	10
5. POWER SPECTRAL DENSITY	11
5.1 STANDARD APPLICABLE	11
5.2 TEST PROCEDURE	11
5.3 ENVIRONMENTAL CONDITIONS	11
5.4 SUMMARY OF TEST RESULTS/PLOTS	12
6. 6DB BANDWIDTH	19
6.1 STANDARD APPLICABLE	19
6.2 TEST PROCEDURE	19
6.3 ENVIRONMENTAL CONDITIONS	19
6.4 SUMMARY OF TEST RESULTS/PLOTS	19
7. RF OUTPUT POWER	26
7.1 STANDARD APPLICABLE	26
7.2 TEST PROCEDURE	26
7.3 ENVIRONMENTAL CONDITIONS	26
7.4 SUMMARY OF TEST RESULTS/PLOTS	27
8. FIELD STRENGTH OF SPURIOUS EMISSIONS	34
8.1 MEASUREMENT UNCERTAINTY	34
8.2 STANDARD APPLICABLE	34
8.3 TEST PROCEDURE	34
8.4 CORRECTED AMPLITUDE & MARGIN CALCULATION	36
8.5 ENVIRONMENTAL CONDITIONS	36
8.6 SUMMARY OF TEST RESULTS/PLOTS	36
9. OUT OF BAND EMISSIONS	65
9.1 STANDARD APPLICABLE	65
9.2 TEST PROCEDURE	65
9.3 ENVIRONMENTAL CONDITIONS	66
9.4 SUMMARY OF TEST RESULTS/PLOTS	66
10. CONDUCTED EMISSIONS	74
10.1 MEASUREMENT UNCERTAINTY	74
10.2 TEST PROCEDURE	74
10.3 BASIC TEST SETUP BLOCK DIAGRAM	74
10.4 ENVIRONMENTAL CONDITIONS	74
10.5 TEST RECEIVER SETUP	75
10.6 SUMMARY OF TEST RESULTS/PLOTS	75
10.7 CONDUCTED EMISSIONS TEST DATA	75

History of this report		
Version	Description	Date
1.0	First Edition	2016-02-25
Rev1	Second Edition	2016-03-17

1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

Client Information

Applicant: Winstars Technology Limited
Address of applicant: Block 4, TaiSong Industrial Park, Dalang Street,
LongHua Town, Bao'an district, Shenzhen, China

Manufacturer: Winstars Technology Limited
Address of manufacturer: Block 4, TaiSong Industrial Park, Dalang Street,
LongHua Town, Bao'an district, Shenzhen, China

General Description of EUT	
Product Name:	Wireless N Travel AP/Router
Trade Name:	/
Model No.:	WS-WN565N1
Rated Voltage:	DC 5V
Hardware Version:	WS-WN565N1-A V1
Software Version:	TRN-A2.3463.1.20140520
<i>Note: The test data is gathered from a production sample provided by the manufacturer.</i>	

Technical Characteristics of EUT	
Support Standards:	802.11b, 802.11g, 802.11n
Frequency Range:	2412-2462MHz for 802.11b/g/n(HT20) 2422-2452MHz for 802.11n(HT40)
RF Output Power:	16.33 dBm (Conducted)
Type of Modulation:	CCK, OFDM, QPSK, BPSK, 16QAM, 64QAM
Data Rate:	1-11Mbps, 6-54Mbps, up to 150Mbps
Quantity of Channels:	11
Channel Separation:	5MHz
Type of Antenna:	Integral antenna
Antenna Gain:	3.0dBi
Lowest Internal Frequency	40MHz

1.2 Test Standards

The following report is prepared on behalf of the Winstars Technology Limited in accordance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 of the Federal Communication Commissions rules.

The objective is to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 of the Federal Communication Commissions rules.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard for Testing Unlicensed Wireless Devices, and ANSI C63.4-2014, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz. The measurement guide KDB 558074 D01 v03r04 for digital transmission systems shall be performed also.

1.4 Table for parameters of Test Software setting

The test utility software used during testing was “RPTA1-71W.M4300.01.GD.2015Sep1”. During testing, Channel and Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

Mode	Test Frequency (MHz)		
	NCB: 20MHz		
	2412	2437	2462
802.11b-1Mbps	17	17	17
802.11g-6Mbps	17	17	17
802.11n-HT20-MCS0	17	17	17
Mode	Test Frequency (MHz)		
	NCB: 40MHz		
	2422	2437	2452
802.11n-HT40-MCS0	17	17	17

1.5 EUT Operating during test

EUT was programmed to be in continuously transmitting mode. During the test, EUT operation to normal function and programs under WIN XP were executed.

1.6 Test Facility

FCC – Registration No.: 934118

Shenzhen SEM.Test Technology Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files and the Registration is 934118.

Industry Canada (IC) Registration No.: 11464A

The 3m Semi-anechoic chamber of Shenzhen SEM.Test Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A.

CNAS Registration No.: L4062

Shenzhen SEM.Test Technology Co., Ltd. is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L4062. All measurement facilities used to collect the measurement data are located at 1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road, Bao'an District, Shenzhen, P.R.C (518101).

1.7 EUT Setup and Test Mode

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, and to measure its highest possible emissions level, more detailed description as follows:

Test Mode List		
Test Mode	Description	Remark
TM1	802.11b	2412MHz, 2437MHz, 2462MHz
TM2	802.11g	2412MHz, 2437MHz, 2462MHz
TM3	802.11n-HT20	2412MHz, 2437MHz, 2462MHz
TM4	802.11n-HT40	2422MHz, 2437MHz, 2452MHz

EUT Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
USB cable	0.2	Unshielded	Without Ferrite

Special Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Auxiliary Equipment List and Details			
Description	Manufacturer	Model	Remark
Notebook	Lenovo	E10	Supplied by SEM
Adapter	\	XHY050200UECH	Supplied by SEM

1.8 Test Equipment List and Details

Description	Manufacturer	Model	Serial Number	Cal Date	Due Date
Spectrum Analyzer	Agilent	E4407B	MY41440400	2015-06-17	2016-06-16
Spectrum Analyzer	Rohde & Schwarz	FSP	836079/035	2015-06-17	2016-06-16
EMI Test Receiver	Rohde & Schwarz	ESVB	825471/005	2015-06-17	2016-06-16
Amplifier	Agilent	8447F	3113A06717	2015-06-17	2016-06-16
Amplifier	C&D	PAP-1G18	2002	2015-06-17	2016-06-16
Broadband Antenna	Schwarz beck	VULB9163	9163-333	2015-06-17	2016-06-16
Horn Antenna	ETS	3117	00086197	2015-06-17	2016-06-16
Horn Antenna	ETS	3116B	00088203	2015-06-17	2016-06-16
Loop Antenna	Schwarz beck	FMZB 1516	9773	2015-06-17	2016-06-16
EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2015-06-17	2016-06-16
L.I.S.N	Schwarz beck	NSLK8126	8126-224	2015-06-17	2016-06-16
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100911	2015-06-17	2016-06-16

2. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test Item	Result
§ 2.1093	RF Exposure	Compliant
§ 15.203; § 15.247(b)(4)(i)	Antenna Requirement	Compliant
§ 15.207(a)	Conducted Emission	Compliant
§ 15.247(e)	Power Spectral Density	Compliant
§ 15.247(a)(2)	6 dB Bandwidth	Compliant
§ 15.247(b)(3)	RF Output Power	Compliant
§ 15.209(a)	Radiated Emission	Compliant
§ 15.247(d)	Band Edge (Out of Band Emissions)	Compliant

N/A: not applicable

3. RF Exposure

3.1 Standard Applicable

According to § 1.1307 and § 2.1093, the portable transmitter must comply the RF exposure requirements.

3.2 Test Result

This product complied with the requirement of the RF exposure, please see the RF Exposure Report.

4. Antenna Requirement

4.1 Standard Applicable

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

4.2 Evaluation Information

This product has an integral antenna, fulfill the requirement of this section.

5. Power Spectral Density

5.1 Standard Applicable

According to 15.247(a)(1)(iii), For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

5.2 Test Procedure

According to the KDB 558074 D01 v03r04, such specifications require that the same method as used to determine the conducted output power shall also be used to determine the power spectral density. The test method of power spectral density as below:

- a) Set instrument center frequency to DTS channel center frequency.
- b) Set span to at least 1.5 times the OBW.
- c) Set RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- d) Set VBW $\geq 3 \times \text{RBW}$.
- e) Detector = power averaging (RMS) or sample detector (when RMS not available).
- f) Ensure that the number of measurement points in the sweep $\geq 2 \times \text{span/RBW}$.
- g) Sweep time = auto couple.
- h) Employ trace averaging (RMS) mode over a minimum of 100 traces.
- i) Use the peak marker function to determine the maximum amplitude level.
- j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat (note that this may require zooming in on the emission of interest and reducing the span in order to meet the minimum measurement point requirement as the RBW is reduced).

5.3 Environmental Conditions


Temperature:	26° C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

5.4 Summary of Test Results/Plots


Test Mode	Test Channel MHz	Power Spectral Density dBm/3kHz	Limit dBm/3kHz
802.11b	2412	-3.833	8
	2437	-2.525	8
	2462	-3.317	8
802.11g	2412	-9.817	8
	2437	-8.983	8
	2462	-8.390	8
802.11n HT20	2412	-9.825	8
	2437	-8.832	8
	2462	-7.888	8
802.11n HT40	2422	-14.610	8
	2437	-12.670	8
	2452	-15.610	8

Please refer to the following test plots:


802.11b-Low Channel




802.11b-Middle Channel




802.11b-High Channel




802.11g-Low Channel




802.11g-Middle Channel




802.11g-High Channel




802.11n-HT20-Low Channel




802.11n-HT20-Middle Channel




802.11n-HT20-High Channel




802.11n-HT40-Low Channel



802.11n-HT40-Middle Channel



802.11n-HT40-High Channel



6. 6dB Bandwidth

6.1 Standard Applicable

According to 15.247(a)(2). Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

6.2 Test Procedure

- Set RBW = 100 kHz.
- Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- Detector = Peak.
- Trace mode = max hold.
- Sweep = auto couple.
- Allow the trace to stabilize.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

6.3 Environmental Conditions


Temperature:	25° C
Relative Humidity:	53%
ATM Pressure:	1018 mbar

6.4 Summary of Test Results/Plots


Test Mode	Test Channel MHz	6 dB Bandwidth kHz	99% Bandwidth kHz	Limit kHz
802.11b	2412	9611	12154.6	≥ 500
	2437	10078	12157.2	≥ 500
	2462	10090	12182.6	≥ 500
802.11g	2412	16383	16440.6	≥ 500
	2437	16451	16401.8	≥ 500
	2462	16403	16448.4	≥ 500
802.11n-HT20	2412	17544	17572.9	≥ 500
	2437	17588	17554.6	≥ 500
	2462	17525	17524.8	≥ 500
802.11n-HT40	2422	36027	36066.9	≥ 500
	2437	36334	36090.1	≥ 500
	2452	36345	36108.4	≥ 500

Please refer to the following test plots:


802.11b-Low Channel




802.11b-Middle Channel




802.11b-High Channel




802.11g-Low Channel




802.11g-Middle Channel




802.11g-High Channel




802.11n-HT20-Low Channel




802.11n-HT20-Middle Channel




802.11n-HT20-High Channel




802.11n-HT40-Low Channel



802.11n-HT40-Middle Channel



802.11n-HT40-High Channel



7. RF Output Power

7.1 Standard Applicable

According to 15.247(b)(3). For systems using digital modulation in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands: 1 Watt.

7.2 Test Procedure

According to the KDB-558074 D01 v03r04, 9.2.2.2, when this option is exercised, the measured power is to be referenced to the OBW rather than the DTS bandwidth

- a) Set span to at least 1.5 times the OBW.
- b) Set RBW = 1-5% of the OBW, not to exceed 1 MHz.
- c) Set VBW $\geq 3 \times$ RBW.
- d) Number of points in sweep $\geq 2 \times \text{span} / \text{RBW}$. (This gives bin-to-bin spacing $\leq \text{RBW}/2$, so that narrowband signals are not lost between frequency bins.)
- e) Sweep time = auto.
- f) Detector = RMS (i.e., power averaging), if available. Otherwise, use sample detector mode.
- g) If transmit duty cycle $< 98\%$, use a sweep trigger with the level set to enable triggering only on full power pulses. The transmitter shall operate at maximum power control level for the entire duration of every sweep. If the EUT transmits continuously (i.e., with no off intervals) or at duty cycle $\geq 98\%$, and if each transmission is entirely at the maximum power control level, then the trigger shall be set to “free run”.
- h) Trace average at least 100 traces in power averaging (i.e., RMS) mode.
- i) Compute power by integrating the spectrum across the OBW of the signal using the instrument’s band power measurement function, with band limits set equal to the OBW band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at intervals equal to the RBW extending across the entire OBW of the spectrum.

7.3 Environmental Conditions


Temperature:	26° C
Relative Humidity:	57%
ATM Pressure:	1011 mbar

7.4 Summary of Test Results/Plots


Test Mode	Frequency MHz	Reading dBm	Output Power mW	Limit mW
802.11b_11Mbps	2412	16.33	42.95	1000
	2437	15.50	35.48	1000
	2462	15.41	34.75	1000
802.11g_54Mbps	2412	13.53	22.54	1000
	2437	13.08	20.32	1000
	2462	12.82	19.14	1000
802.11n HT20_MCS7	2412	12.76	18.88	1000
	2437	12.00	15.85	1000
	2462	12.03	15.96	1000
802.11n HT40_MCS7	2422	8.65	7.33	1000
	2437	8.92	7.80	1000
	2452	8.76	7.52	1000

Please refer to the following test plots:


802.11b-11Mbps-Low Channel




802.11b -11Mbps-Middle Channel




802.11b -11Mbps-High Channel




802.11g-54Mbps-Low Channel




802.11g-54Mbps-Middle Channel




802.11g-54Mbps-High Channel




802.11n-HT20-MCS7-Low Channel




802.11n-HT20-MCS7-Middle Channel




802.11n-HT20-MCS7-High Channel




802.11n-HT40-MCS7-Low Channel



802.11n-HT40-MCS7-Middle Channel



802.11n-HT40-MCS7-High Channel



8. Field Strength of Spurious Emissions

8.1 Measurement Uncertainty

Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of a radiation emissions measurement is ± 5.10 dB.

8.2 Standard Applicable

According to §15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).



The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply. Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.

8.3 Test Procedure

The setup of EUT is according with per ANSI C63.4-2014 measurement procedure. The specification used was with the FCC Part 15.205 15.247(a) and FCC Part 15.209 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.



Frequency :9kHz-30MHz
 RBW=10KHz,
 VBW =30KHz
 Sweep time= Auto
 Trace = max hold
 Detector function = peak

Frequency :30MHz-1GHz
 RBW=120KHz,
 VBW=300KHz
 Sweep time= Auto
 Trace = max hold
 Detector function = peak, QP

Frequency :Above 1GHz
 RBW=1MHz,
 VBW=3MHz(Peak), 10Hz(AV)
 Sweep time= Auto
 Trace = max hold
 Detector function = peak, AV

8.4 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Ant. Factor} + \text{Cable Loss} - \text{Ampl. Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -6dB μ V means the emission is 6dB μ V below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{FCC Part 15 Limit}$$

8.5 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	52%
ATM Pressure:	1012 mbar


8.6 Summary of Test Results/Plots

According to the data below, the FCC Part 15.205, 15.209 and 15.247 standards, and had the worst cases:

Note: this EUT was tested in 3 orthogonal positions and the worst case position data was reported.


Plot of Radiated Emissions Test Data (30MHz to 1GHz)

EUT: Wireless N Travel AP/Router
Tested Model: WS-WN565N1
Operating Condition: 802.11b Transmitting Low Channel-2412MHz
(worst mode: Router mode)
Comment: AC 120V/60Hz; Adapter DC 5V
Test Specification: Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	38.3462	17.43	6.81	24.24	40.00	-15.76	254	100	peak
2	78.9652	21.11	1.12	22.23	40.00	-17.77	113	100	peak
3	260.1444	21.56	7.04	28.60	46.00	-17.40	284	100	peak

Test Specification: Vertical




No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	(°)	(cm)	
1	37.6798	15.95	8.85	24.80	40.00	-15.20	114	100	peak
2	260.1444	18.85	7.04	25.89	46.00	-20.11	270	100	peak
3	884.5029	16.28	16.83	33.11	46.00	-12.89	360	100	peak

Operating Condition: 802.11b Transmitting Middle Channel-2437MHz
(worst mode: Router mode)


Comment: AC 120V/60Hz; Adapter DC 5V

Test Specification: Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	73.6170	22.80	1.76	24.56	40.00	-15.44	178	100	peak
2	260.1444	21.32	7.04	28.36	46.00	-17.64	224	100	peak
3	903.3094	16.34	16.79	33.13	46.00	-12.87	160	100	peak

Test Specification: Vertical




No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	(°)	(cm)	
1	40.4172	15.23	9.12	24.35	40.00	-15.65	256	100	peak
2	61.7781	18.89	4.81	23.70	40.00	-16.30	360	100	peak
3	896.9965	16.41	16.85	33.26	46.00	-12.74	360	100	peak

Operating Condition: 802.11b Transmitting High Channel-2462MHz
(worst mode: Router mode)


Comment: AC 120V/60Hz; Adapter DC 5V

Test Specification: Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	38.3462	17.38	6.81	24.19	40.00	-15.81	176	100	peak
2	260.1444	19.97	7.04	27.01	46.00	-18.99	255	100	peak
3	916.0687	17.16	16.56	33.72	46.00	-12.28	360	100	peak


Test Specification: Vertical



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	39.1616	16.27	9.10	25.37	40.00	-14.63	360	100	peak
2	318.8170	15.52	9.28	24.80	46.00	-21.20	225	100	peak
3	742.2587	16.80	15.45	32.25	46.00	-13.75	160	100	peak


Plot of Radiated Emissions Test Data (30MHz to 1GHz)

EUT: Wireless N Travel AP/Router
 Tested Model: WS-WN565N1
 Operating Condition: 802.11g Transmitting Low Channel-2412MHz
 (worst mode: Router mode)
 Comment: AC 120V/60Hz; Adapter DC 5V
 Test Specification: Horizontal



No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	(°)	(cm)	
1	39.0245	17.18	6.99	24.17	40.00	-15.83	174	100	peak
2	75.7114	22.37	1.51	23.88	40.00	-16.12	160	100	peak
3	260.1444	19.69	7.04	26.73	46.00	-19.27	320	100	peak

Test Specification: Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	38.3462	16.05	8.97	25.02	40.00	-14.98	177	100	peak
2	57.9993	17.47	5.55	23.02	40.00	-16.98	90	100	peak
3	909.6667	16.73	16.68	33.41	46.00	-12.59	336	100	peak

Operating Condition: 802.11g Transmitting Middle Channel-2437MHz
(worst mode: Router mode)


Comment: AC 120V/60Hz; Adapter DC 5V

Test Specification: Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	43.0504	17.24	6.94	24.18	40.00	-15.82	270	100	peak
2	75.9772	23.27	1.48	24.75	40.00	-15.25	164	100	peak
3	742.2586	18.75	13.67	32.42	46.00	-13.58	228	200	peak

Test Specification: Vertical




No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	(°)	(cm)	
1	41.2765	15.92	8.87	24.79	40.00	-15.21	360	100	peak
2	260.1444	16.40	7.04	23.44	46.00	-22.56	255	100	peak
3	975.7529	17.44	16.61	34.05	54.00	-19.95	270	100	peak

Operating Condition: 802.11g Transmitting High Channel-2462MHz
(worst mode: Router mode)


Comment: AC 120V/60Hz; Adapter DC 5V

Test Specification: Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	76.2442	22.73	1.45	24.18	40.00	-15.82	270	100	peak
2	260.1444	18.96	7.04	26.00	46.00	-20.00	51	200	peak
3	900.1474	16.14	16.85	32.99	46.00	-13.01	360	200	peak


Test Specification: Vertical



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	37.4165	14.89	8.81	23.70	40.00	-16.30	360	100	peak
2	109.4116	16.94	5.13	22.07	43.50	-21.43	180	100	peak
3	903.3094	16.79	16.79	33.58	46.00	-12.42	225	100	peak


Plot of Radiated Emissions Test Data (30MHz to 1GHz)

EUT: Wireless N Travel AP/Router
 Tested Model: WS-WN565N1
 Operating Condition: 802.11n-HT20 Transmitting Low Channel-2412MHz
 (worst mode: Router mode)
 Comment: AC 120V/60Hz; Adapter DC 5V
 Test Specification: Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	76.2442	23.05	1.45	24.50	40.00	-15.50	260	100	peak
2	260.1444	18.10	7.04	25.14	46.00	-20.86	131	200	peak
3	903.3094	16.38	16.79	33.17	46.00	-12.83	285	200	peak

Test Specification: Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	39.0245	15.47	9.08	24.55	40.00	-15.45	155	100	peak
2	110.5687	16.04	5.02	21.06	43.50	-22.44	197	100	peak
3	260.1444	16.92	7.04	23.96	46.00	-22.04	310	100	peak

Operating Condition: 802.11n-HT20 Transmitting Middle Channel-2437MHz
(worst mode: Router mode)


Comment: AC 120V/60Hz; Adapter DC 5V

Test Specification: Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	79.5209	22.88	1.06	23.94	40.00	-16.06	274	100	peak
2	260.1444	18.52	7.04	25.56	46.00	-20.44	116	100	peak
3	900.1474	17.36	16.85	34.21	46.00	-11.79	82	100	peak

Test Specification: Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	39.4371	15.62	9.16	24.78	40.00	-15.22	264	100	peak
2	406.0880	16.94	9.91	26.85	46.00	-19.15	110	100	peak
3	942.1305	17.12	16.23	33.35	46.00	-12.65	136	100	peak

Operating Condition: 802.11n-HT20 Transmitting High Channel-2462MHz
(worst mode: Router mode)


Comment: AC 120V/60Hz; Adapter DC 5V

Test Specification: Horizontal




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	79.5208	23.61	1.06	24.67	40.00	-15.33	360	100	peak
2	260.1444	17.77	7.04	24.81	46.00	-21.19	112	100	peak
3	919.2866	16.16	16.50	32.66	46.00	-13.34	180	200	peak

Test Specification: Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	40.8446	15.42	9.00	24.42	40.00	-15.58	267	100	peak
2	78.9652	23.86	1.12	24.98	40.00	-15.02	116	100	peak
3	289.0021	16.81	8.75	25.56	46.00	-20.44	360	100	peak

EUT: Wireless N Travel AP/Router
Tested Model: WS-WN565N1
Operating Condition: 802.11n-HT40 Transmitting Low Channel-2422MHz
(worst mode: Router mode)
Comment: AC 120V/60Hz; Adapter DC 5V
Test Specification: Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	40.2757	17.33	7.22	24.55	40.00	-15.45	267	100	peak
2	260.1444	20.25	7.04	27.29	46.00	-18.71	114	200	peak
3	909.6667	16.43	16.68	33.11	46.00	-12.89	35	200	peak

Test Specification: Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	33.0950	18.74	8.10	26.84	40.00	-13.16	360	100	peak
2	260.1444	18.96	7.04	26.00	46.00	-20.00	258	100	peak
3	893.8567	16.62	16.85	33.47	46.00	-12.53	347	100	peak

Operating Condition: 802.11n-HT40 Transmitting Middle Channel-2437MHz
(worst mode: Router mode)


Comment: AC 120V/60Hz; Adapter DC 5V

Test Specification: Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	75.4464	22.52	1.55	24.07	40.00	-15.93	251	100	peak
2	260.1444	18.30	7.04	25.34	46.00	-20.66	167	100	peak
3	909.6667	17.59	16.68	34.27	46.00	-11.73	44	100	peak

Test Specification: Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	36.3814	15.18	8.64	23.82	40.00	-16.18	47	100	peak
2	59.8588	17.49	5.39	22.88	40.00	-17.12	264	100	peak
3	909.6667	18.12	16.68	34.80	46.00	-11.20	225	100	peak

Operating Condition: 802.11n-HT40 Transmitting High Channel-2452MHz
(worst mode: Router mode)


Comment: AC 120V/60Hz; Adapter DC 5V

Test Specification: Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	76.2442	23.42	1.45	24.87	40.00	-15.13	360	100	peak
2	260.1444	18.73	7.04	25.77	46.00	-20.23	287	100	peak
3	916.0687	17.13	16.56	33.69	46.00	-12.31	168	100	peak

Test Specification: Vertical



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	39.1616	14.32	9.10	23.42	40.00	-16.58	78	100	peak
2	304.6100	15.45	9.19	24.64	46.00	-21.36	136	100	peak
3	909.6667	16.64	16.68	33.32	46.00	-12.68	284	100	peak

Spurious Emissions Above 1GHz

Test Mode: 802.11b

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	H/V	
Low Channel-2412MHz(worst mode: Router mode)							
4824.000	56.13	-3.87	52.26	74	-21.74	H	PK
4824.000	39.18	-3.87	35.31	54	-18.69	H	AV
7236.000	44.95	1.14	46.09	74	-27.91	H	PK
7236.000	33.21	1.19	34.4	54	-19.6	H	AV
4824.000	53.84	-3.86	49.98	74	-24.02	V	PK
4824.000	44.53	-3.86	40.67	54	-13.33	V	AV
7236.000	45.66	1.1	46.76	74	-27.24	V	PK
7236.000	40.73	1.1	41.83	54	-12.17	V	AV
Middle Channel-2437MHz(worst mode: Router mode)							
4874.000	51.85	-3.74	48.11	74	-25.89	H	PK
4874.000	42.61	-3.74	38.87	54	-15.13	H	AV
7311.000	44.82	1.47	46.29	74	-27.71	H	PK
7311.000	31.97	1.47	33.44	54	-20.56	H	AV
4874.000	56.14	-3.74	52.4	74	-21.6	V	PK
4874.000	43.52	-3.74	39.78	54	-14.22	V	AV
7311.000	55.79	1.47	57.26	74	-16.74	V	PK
7311.000	31.59	1.47	33.06	54	-20.94	V	AV
High Channel-2462MHz(worst mode: Router mode)							
4924.000	56.91	-3.59	53.32	74	-20.68	H	PK
4924.000	46.37	-3.59	42.78	54	-11.22	H	AV
7386.000	42.98	1.79	44.77	74	-29.23	H	PK
7386.000	36.59	1.79	38.38	54	-15.62	H	AV
4924.000	51.62	-3.59	48.03	74	-25.97	V	PK
4924.000	41.93	-3.59	38.34	54	-15.66	V	AV
7386.000	44.92	1.79	46.71	74	-27.29	V	PK
7386.000	38.59	1.79	40.38	54	-13.62	V	AV

Test Mode: 802.11g

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	H/V	
Low Channel-2412MHz(worst mode: Router mode)							
4824.000	54	-3.87	50.13	74	-23.87	H	PK
4824.000	40.75	-3.87	36.88	54	-17.12	H	AV
7236.000	47.18	1.14	48.32	74	-25.68	H	PK
7236.000	34.73	1.19	35.92	54	-18.08	H	AV
4824.000	56.11	-3.86	52.25	74	-21.75	V	PK
4824.000	42.69	-3.86	38.83	54	-15.17	V	AV
7236.000	48.58	1.1	49.68	74	-24.32	V	PK
7236.000	35.95	1.1	37.05	54	-16.95	V	AV
Middle Channel-2437MHz(worst mode: Router mode)							
4874.000	55.6	-3.74	51.86	74	-22.14	H	PK
4874.000	40.54	-3.74	36.8	54	-17.2	H	AV
7311.000	47.26	1.47	48.73	74	-25.27	H	PK
7311.000	34.44	1.47	35.91	54	-18.09	H	AV
4874.000	56.71	-3.74	52.97	74	-21.03	V	PK
4874.000	43.18	-3.74	39.44	54	-14.56	V	AV
7311.000	49.21	1.47	50.68	74	-23.32	V	PK
7311.000	35.77	1.47	37.24	54	-16.76	V	AV
High Channel-2462MHz(worst mode: Router mode)							
4924.000	55.5	-3.59	51.91	74	-22.09	H	PK
4924.000	42.23	-3.59	38.64	54	-15.36	H	AV
7386.000	48.42	1.79	50.21	74	-23.79	H	PK
7386.000	34.4	1.79	36.19	54	-17.81	H	AV
4924.000	55.99	-3.59	52.4	74	-21.6	V	PK
4924.000	42.65	-3.59	39.06	54	-14.94	V	AV
7386.000	49.22	1.79	51.01	74	-22.99	V	PK
7386.000	35.54	1.79	37.33	54	-16.67	V	AV

Test Mode: 802.11n-HT20

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	H/V	
Low Channel-2412MHz(worst mode: Router mode)							
4824.000	51.85	-3.87	47.98	74	-26.02	H	PK
4824.000	42.61	-3.87	38.74	54	-15.26	H	AV
7236.000	44.82	1.14	45.96	74	-28.04	H	PK
7236.000	31.97	1.19	33.16	54	-20.84	H	AV
4824.000	56.14	-3.86	52.28	74	-21.72	V	PK
4824.000	43.52	-3.86	39.66	54	-14.34	V	AV
7236.000	55.79	1.1	56.89	74	-17.11	V	PK
7236.000	31.59	1.1	32.69	54	-21.31	V	AV
Middle Channel-2437MHz(worst mode: Router mode)							
4874.000	53.9	-3.74	50.16	74	-23.84	H	PK
4874.000	43.23	-3.74	39.49	54	-14.51	H	AV
7311.000	48.31	1.47	49.78	74	-24.22	H	PK
7311.000	36.1	1.47	37.57	54	-16.43	H	AV
4874.000	55.7	-3.74	51.96	74	-22.04	V	PK
4874.000	41.48	-3.74	37.74	54	-16.26	V	AV
7311.000	48.55	1.47	50.02	74	-23.98	V	PK
7311.000	35.36	1.47	36.83	54	-17.17	V	AV
High Channel-2462MHz(worst mode: Router mode)							
4924.000	56.13	-3.59	52.54	74	-21.46	H	PK
4924.000	39.18	-3.59	35.59	54	-18.41	H	AV
7386.000	44.95	1.79	46.74	74	-27.26	H	PK
7386.000	33.21	1.79	35	54	-19	H	AV
4924.000	53.84	-3.59	50.25	74	-23.75	V	PK
4924.000	44.53	-3.59	40.94	54	-13.06	V	AV
7386.000	45.66	1.79	47.45	74	-26.55	V	PK
7386.000	40.73	1.79	42.52	54	-11.48	V	AV

Test Mode: 802.11n-HT40

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	H/V	
Low Channel-2422MHz(worst mode: Router mode)							
4844.000	55.1	-3.9	51.2	74	-22.8	H	PK
4824.000	43.28	-3.9	39.38	54	-14.62	H	AV
7266.000	47.38	1.06	48.44	74	-25.56	H	PK
7266.000	35.27	1.06	36.33	54	-17.67	H	AV
4844.000	57.07	-3.9	53.17	74	-20.83	V	PK
4824.000	43.86	-3.9	39.96	54	-14.04	V	AV
7266.000	48.4	1.06	49.46	74	-24.54	V	PK
7266.000	35.33	1.06	36.39	54	-17.61	V	AV
Middle Channel-2437MHz(worst mode: Router mode)							
4874.000	56.91	-3.74	53.17	74	-20.83	H	PK
4874.000	46.37	-3.74	42.63	54	-11.37	H	AV
7311.000	42.98	1.47	44.45	74	-29.55	H	PK
7311.000	36.59	1.47	38.06	54	-15.94	H	AV
4874.000	51.62	-3.74	47.88	74	-26.12	V	PK
4874.000	41.93	-3.74	38.19	54	-15.81	V	AV
7311.000	44.92	1.47	46.39	74	-27.61	V	PK
7311.000	38.59	1.47	40.06	54	-13.94	V	AV
High Channel-2452MHz(worst mode: Router mode)							
4904.000	54.16	-3.63	50.53	74	-23.47	H	PK
4904.000	42.48	-3.63	38.85	54	-15.15	H	AV
7356.000	48.74	1.62	50.36	74	-23.64	H	PK
7356.000	33.1	1.62	34.72	54	-19.28	H	AV
4904.000	54.92	-3.63	51.29	74	-22.71	V	PK
4904.000	42.62	-3.63	38.99	54	-15.01	V	AV
7356.000	48.49	1.62	50.11	74	-23.89	V	PK
7356.000	35.2	1.62	36.82	54	-17.18	V	AV

Note: Testing is carried out with frequency rang 30MHz to the tenth harmonics, which above 3th Harmonics are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

9. Out of Band Emissions

9.1 Standard Applicable

According to §15.247 (d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

9.2 Test Procedure

According to the KDB 558074D01 v03r04, the band-edge radiated test method as follows:

Set span = wide enough to capture the peak level of the emission operating on the channel closest to the bandedge, as well as any modulation products which fall outside of the authorized band of operation (2310MHz to 2420MHz for low bandedge, 2460MHz to 2500MHz for the high bandedge)

RBW = 1MHz, VBW = 1MHz for peak value measured

RBW = 1MHz, VBW = 10Hz for average value measured

Sweep = auto; Detector function = peak/average; Trace = max hold

All the trace to stabilize, set the marker on the emission at the bandedge, or on the highest modulation product outside of the band, if this level is greater than that at the bandedge. Enable the marker-delta function, then use the marker-to-peak function to move the marker to the peak of the in-band emission. Those emission must comply with the 15.209 limit for fall in the restricted bands listed in section 15.205. Note that the method of measurement KDB publication number: 913591 may be used for the radiated bandedge measurements.

According to the KDB 558074 D01 v03r04, the conducted spurious emissions test method as follows:

1. Set start frequency to DTS channel edge frequency.
2. Set stop frequency so as to encompass the spectrum to be examined.
3. Set RBW = 100 kHz.
4. Set VBW $\geq$ 300 kHz.
5. Detector = peak.
6. Trace Mode = max hold.
7. Sweep = auto couple.
8. Allow the trace to stabilize (this may take some time, depending on the extent of the span).
9. Use peak marker function to determine maximum amplitude of all unwanted emissions within any 100 kHz bandwidth.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements specified in section 8.1. Report the three highest emissions relative to the limit.


9.3 Environmental Conditions

Temperature:	23°C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

9.4 Summary of Test Results/Plots

802.11b-Lowest Bandedge


Vertical (Worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	18.68	16.34	35.02	54.00	-18.98	Average Detector
	2310.000	31.80	16.34	48.14	74.00	-25.86	Peak Detector
2	2390.000	18.58	17.03	35.61	54.00	-18.39	Average Detector
	2390.000	32.56	17.03	49.59	74.00	-24.41	Peak Detector
3	2400.000	20.30	17.11	37.41	Delta=44.98dBc		Average Detector
4	2411.040	65.20	17.19	82.39			Average Detector

802.11b-Highest Bandedge

Vertical (Worst case)




802.11g-Lowest Bandedge
Vertical (Worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	18.85	16.34	35.19	54.00	-18.81	Average Detector
	2310.000	30.04	16.34	46.38	74.00	-27.62	Peak Detector
2	2390.000	24.15	17.03	41.18	54.00	-12.82	Average Detector
	2390.000	34.76	17.03	51.79	74.00	-22.21	Peak Detector
3	2400.000	30.16	17.11	47.27	Delta=32.80dBc		Average Detector
4	2410.800	62.88	17.19	80.07			Average Detector


802.11g-Highest Bandedge

Vertical (Worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
2	2460.850	61.58	17.56	79.14	/	/	Average Detector
	2461.250	82.48	17.57	100.05	/	/	Peak Detector
1	2483.500	Delta = 44.83dBc		40.26	54.00	-13.74	Average Detector
	2483.500			58.37	74.00	-15.63	Peak Detector
3	2500.000	18.71	17.86	36.57	54.00	-17.43	Average Detector
	2500.000	30.32	17.86	48.18	74.00	-25.82	Peak Detector

802.11n-HT20-Lowest Bandedge
Vertical (Worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	32.26	-3.71	28.55	54.00	-25.45	Average Detector
	2310.000	45.44	-3.71	41.73	74.00	-32.27	Peak Detector
2	2390.000	39.64	-3.54	36.10	54.00	-17.90	Average Detector
	2390.000	57.67	-3.54	54.13	74.00	-19.87	Peak Detector
3	2400.000	53.71	-3.51	50.20	Delta=36.44dBc		Average Detector
4	2407.320	90.13	-3.49	86.64			Average Detector

802.11n-HT20-Highest Bandedge
Vertical (Worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2457.350	88.34	-3.38	84.96	/	/	Average Detector
	2459.000	99.44	-3.38	96.06	/	/	Peak Detector
2	2483.500	Delta = 47.46dBc		33.55	54.00	-20.45	Average Detector
	2483.500			53.04	74.00	-20.96	Peak Detector
3	2500.000	32.22	-3.28	28.94	54.00	-25.06	Average Detector
	2500.000	44.54	-3.28	41.26	74.00	-32.74	Peak Detector

802.11n-HT40-Lowest Bandedge
Vertical (Worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	31.89	-3.71	28.18	54.00	-25.82	Average Detector
	2310.000	44.45	-3.71	40.74	74.00	-33.26	Peak Detector
2	2390.000	37.74	-3.54	34.20	54.00	-19.80	Average Detector
	2390.000	53.88	-3.54	50.34	74.00	-23.66	Peak Detector
3	2398.480	55.35	-3.51	51.84	54.00	-2.16	Average Detector
4	2400.000	51.98	-3.51	48.47	Delta=32.12dBc		Average Detector
5	2420.320	84.05	-3.46	80.59			Average Detector

802.11n-HT40-Highest Bandedge
Vertical (Worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2448.690	82.73	-3.40	79.33	/	/	Average Detector
	2455.130	94.23	-3.38	90.85	/	/	Peak Detector
2	2483.500	Delta = 40.73dBc		32.99	54.00	-21.01	Average Detector
	2483.500			46.37	74.00	-27.63	Peak Detector
3	2500.000	32.97	-3.28	29.69	54.00	-24.31	Average Detector
	2500.000	47.05	-3.28	43.77	74.00	-30.23	Peak Detector

10. Conducted Emissions

10.1 Measurement Uncertainty

Base on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of any conducted emissions measurement is ± 2.88 dB.


10.2 Test Procedure

The setup of EUT is according with per ANSI C63.4-2014 measurement procedure. The specification used was with the FCC Part 15.207 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

10.3 Basic Test Setup Block Diagram



10.4 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	52%
ATM Pressure:	1012 mbar

10.5 Test Receiver Setup

During the conducted emission test, the test receiver was set with the following configurations:

Start Frequency	150 kHz
Stop Frequency.....	30 MHz
Sweep Speed	Auto
IF Bandwidth.....	10 kHz
Quasi-Peak Adapter Bandwidth	9 kHz
Quasi-Peak Adapter Mode	Normal

10.6 Summary of Test Results/Plots

According to the data in section 10.7, the EUT complied with the FCC Part 15.207 Conducted margin for this device, with the *worst* margin reading of:


-15.86 dB at 0.1540 MHz in the **Line** mode, **Peak** detector, **0.15-30MHz**

10.7 Conducted Emissions Test Data

Plot of Conducted Emissions Test Data


EUT: Wireless N Travel AP/Router
 Tested Model: WS-WN565N1
 Operating Condition: Transmitting(Wi-Fi) (worst mode: Router mode)
 Comment: AC 120V/60Hz; Adapter DC 5V

Test Specification: Neutral



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1*	0.1620	37.81	9.78	47.59	65.36	-17.77	peak
2	0.1660	19.01	9.54	28.55	55.16	-26.61	AVG
3	0.5220	27.18	7.65	34.83	56.00	-21.17	peak
4	0.5300	11.00	7.71	18.71	46.00	-27.29	AVG
5	1.9500	7.52	11.00	18.52	46.00	-27.48	AVG
6	2.0540	22.47	11.04	33.51	56.00	-22.49	peak

Test Specification: Live



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1*	0.1540	39.66	10.26	49.92	65.78	-15.86	peak
2	0.1580	22.39	10.02	32.41	55.57	-23.16	AVG
3	1.5700	20.66	11.00	31.66	56.00	-24.34	peak
4	1.6100	9.25	11.00	20.25	46.00	-25.75	AVG
5	19.9500	20.32	11.99	32.31	60.00	-27.69	peak
6	19.9500	9.07	11.99	21.06	50.00	-28.94	AVG

***** END OF REPORT *****