

TEST REPORT

ACCORDING TO: FCC 47 CFR PART 15 subpart C, section 15.249;
RSS-310 issue 4

FOR:
CERAGON Networks Inc.
IP-20 all outdoor unit
Model: FibeAir IP-20C 24
FCC ID:NZ4IP20C24

This report is in conformity with ISO/ IEC 17025. The "A2LA Accredited" symbol endorsement applies only to the tests and calibrations that are listed in the scope of Hermon Laboratories accreditation. The test results relate only to the items tested. This test report shall not be reproduced in any form except in full with the written approval of Hermon Laboratories Ltd.



Table of contents

1	Applicant information.....	3
2	Equipment under test attributes	3
3	Manufacturer information	3
4	Test details	3
5	Tests summary.....	4
6	EUT description.....	5
6.1	General information.....	5
6.2	Ports and lines	5
6.3	Support and test equipment.....	5
6.4	Changes made in the EUT	5
6.5	Test configuration.....	6
6.6	Transmitter characteristics	7
7	Transmitter tests according to 47CFR part 15 subpart C and RSS-310 issue 4 requirements.....	8
7.1	Field strength of emissions with 42.4 dBi antenna gain.....	8
7.2	Field strength of emissions with 37.1 dBi antenna gain.....	57
7.3	Occupied bandwidth test.....	136
7.4	Band edge emission with 42.4 dBi antenna gain.....	149
7.5	Band edge emission with 37.1 dBi antenna gain.....	173
7.6	Conducted emissions	197
7.7	Antenna requirements	200
8	APPENDIX A Test equipment and ancillaries used for tests.....	201
9	APPENDIX B Measurement uncertainties.....	203
10	APPENDIX C Test laboratory description	204
11	APPENDIX D Specification references	204
12	APPENDIX E Test equipment correction factors.....	205
13	APPENDIX F Abbreviations and acronyms.....	217



1 Applicant information

Client name: CERAGON Networks Ltd.
Address: 24 Raoul Wallenberg Street, Tel Aviv 69719, Israel
Telephone: +972 3543 1653
Fax: +972 3543 1008
E-mail: sergeys@ceragon.com
Contact name: Mr. Sergey Shkolnik

2 Equipment under test attributes

Product name: IP-20 all outdoor unit
Product type: Transceiver
Model(s): FibeAir IP-20C 24
Serial number: F107T02707
Hardware version: FCN
Software release: 9.0.0.0.0.296
Receipt date 08-Aug-17

3 Manufacturer information

Manufacturer name: Flex Ltd.

4 Test details

Project ID: 29773
Location: Hermon Laboratories Ltd. P.O. Box 23, Binyamina 3055001, Israel
Test started: 08-Aug-17
Test completed: 21-Feb-18
Test specification(s): FCC 47 CFR Part 15, subpart C, §15.249; RSS-310 issue 4

5 Tests summary

Test	Status
Transmitter characteristics	
FCC section 15.249(a)(d) / RSS-310, section 3.10, Field strength of emissions	Pass
FCC section 15.215(c) / RSS-Gen, section 6.6, Occupied bandwidth	Pass
FCC section 15.249(d) / RSS-310, section 3.10, Band edge emissions	Pass
FCC section 15.207(a) / RSS-Gen, section 8.8, Conducted emission	Pass
FCC section 15.203/ RSS-Gen, section 8.3, Antenna requirement	Pass

Testing was completed against all relevant requirements of the test standard. The results obtained indicate that the product under test complies in full with the requirements tested.

The test results relate only to the items tested. Pass/ fail decision was based on nominal values.

This test report supersedes the previously issued test report identified by Doc ID:CERRAD_FCC.29773_20C.

	Name and Title	Date	Signature
Tested by:	Mr. S. Samokha, test engineer	February 11, 2018	
Reviewed by:	Mrs. M. Cherniavsky, certification engineer	February 21, 2018	
Approved by:	Mr. M. Nikishin, EMC and Radio group manager	April 25, 2018	

6 EUT description

6.1 General information

The EUT, IP-20C 24 is an all outdoor unit of point to point radio terminal with dual carrier. The IP-20C 24 is powered from -48 VDC.

The IP-20C 24 is designed to support the MultiCore 2+0 Single/Dual Polarization.

A MultiCore 2+0 direct mount configuration. For single polarization, a splitter is used to combine the two cores at the different channels.

For dual polarization, an OMT (orthomode transducer) is used to combine the two cores at the same channel.

When operating with two cores in a single IP-20C unit, users can configure different scripts independently for each core. Configuring a script in one core has no impact on the other core's traffic.

Two power measurements were performed with two mediation devices Splitter and OMT to find worst case configuration.

The configuration with OMT was defined as worst configuration, therefore all other tests were performed accordingly.

6.2 Ports and lines

Port type	Port description	Connected from	Connected to	Qty.	Cable type	Cable length
Telecom&power	Ethernet (ETH1/PoE)	EUT	Not connected	1	FTP	10 m*
Telecom	Ethernet (ETH2)	EUT	Not connected	1	NA	NA
Signal	MGT**	EUT	Laptop	1	FTP	10 m
GND	GND	EUT	GND	1	Unshielded	1 m
Telecom	Ethernet (ETH3)	EUT	Not connected	1	NA	NA
Power	DC	-48 VDC	EUT	1	Unshielded	5 m

* May be longer than 10 m.

** For maintenance only.


6.3 Support and test equipment

Description	Manufacturer	Model number	Serial number
Laptop	Dell	Latitude E6400	F553CA00
Power supply 48VDC/7AMP	Advice	ASB-4807T	AD8844, AD18659
Ethernet Switch	D-Link	DES-108A	QSOV1C-1858

6.4 Changes made in the EUT

No changes were implemented in the EUT during testing.

6.5 Test configuration





6.6 Transmitter characteristics

Type of equipment							
V	Stand-alone (Equipment with or without its own control provisions)						
	Combined equipment (Equipment where the radio part is fully integrated within another type of equipment)						
	Plug-in card (Equipment intended for a variety of host systems)						
Assigned frequency range		24000 – 24250 MHz					
Operating frequency range		24012.6 – 24236.7 MHz					
RF channel spacing		20/30/40/50/60 MHz					
Maximum field strength of carrier at 3 m distance		120.96 dB μ V/m (peak) at 20 MHz BW, with 37.1 dBi antenna gain 107.89 dB μ V/m (average) at 20 MHz BW with 42.4 dBi antenna gain					
Is transmitter output power variable?		No					
		V	Yes	continuous variable			
				V stepped variable with stepsize	1.0 dB		
				minimum RF power			
				maximum RF power			
Antenna connection							
V	unique coupling	standard connector	Integral	with temporary RF connector			
				without temporary RF connector			
Antenna/s technical characteristics							
Type	Manufacturer	Model number	Gain				
External	Ceragon	Am-1-26-CR	37.1 dBi				
External	Ceragon	Am-1-26-CR1	37.0 dBi				
External	Ceragon	Am-2-26-CR1	42.4 dBi				
External	Ceragon	Am-2-26-CR	41.8 dBi				
Transmitter aggregate data rate/s, Mbps							
BW	Type of modulation						
	QPSK	8 QAM	16QAM	32QAM	64QAM		
20 MHz	28.520	42.319	57.456	75.511	92.601		
30 MHz	43.389	62.566	87.496	114.825	141.114		
40 MHz	58.224	86.310	117.129	153.976	188.840		
50 MHz	70.683	109.035	147.476	185.059	238.579		
60 MHz	87.122	126.513	175.249	230.251	282.473		
Type of multiplexing							
Modulating test signal (baseband)		PRBS					
Maximum transmitter duty cycle in normal use		100 %					
Transmitter power source							
V	DC	Nominal rated voltage	-48 VDC				
V	AC	Nominal rated voltage	NA				
Common power source for transmitter and receiver		V	Yes	no			



HERMON LABORATORIES

Test specification: Section 15.249(a)(d)/RSS-310, section 3.10, Field strength of emissions			
Test procedure: ANSI C63.10 sections 6.5, 6.6			
Test mode: Compliance			Verdict: PASS
Date(s):	10-Aug-17 - 22-Aug-17		
Temperature: 24.3 °C	Relative Humidity: 39 %	Air Pressure: 1011 hPa	Power: 48 VDC
Remarks: EUT with 42.4 dBi antenna gain			

7 Transmitter tests according to 47CFR part 15 subpart C and RSS-310 issue 4 requirements

7.1 Field strength of emissions with 42.4 dBi antenna gain

7.1.1 General

This test was performed to measure field strength of fundamental and spurious emissions from the EUT. Specification test limits are given in Table 7.1.1, Table 7.1.2, Table 7.1.3, and Table 7.1.4 .

Table 7.1.1 Radiated fundamental emission limits

Fundamental frequency, MHz	Field strength at 3 m, dB(µV/m)		
	Peak	Average	Quasi-Peak
24000 – 24250*	128.0	108.0	NA

* The band is not used according to RSS-210 section A2.9

Table 7.1.2 Harmonics limits

Fundamental frequency, MHz	Field strength at 3 m, dB(µV/m)	
	Peak	Average
24000 – 24250*	88.0	68.0

* The band is not used according to RSS-210 section A2.9

Table 7.1.3 Radiated spurious emissions limits (other than harmonics)

Frequency, MHz	Field strength at 3 m, dB(µV/m)*			
	Peak	Quasi Peak	Average	Attenuation below carrier
0.009 – 0.090	148.5 – 128.5	NA	128.5 – 108.5**	50 dBc (whichever is the less stringent)
0.090 – 0.110	NA	108.5 – 106.8**	NA	
0.110 – 0.490	126.8 – 113.8	NA	106.8 – 93.8**	
0.490 – 1.705		73.8 – 63.0**		
1.705 – 30.0*		69.5		
30 – 88	NA	40.0		
88 – 216		43.5		
216 – 960		46.0		
960 – 1000		54.0		
Above 1000	74.0	NA	54.0	

*- The limit for 3 m test distance was calculated using the inverse square distance extrapolation factor as follows:

$$\text{Lim}_{S_2} = \text{Lim}_{S_1} + 20 \log (S_1/S_2),$$

where S_1 and S_2 – standard defined and test distance respectively in meters.

**- The limit decreases linearly with the logarithm of frequency.

Note: The above field strength limits applied from the lowest radio frequency generated in the device, without going below 9 kHz up to the tenth harmonic of the highest fundamental frequency but not exceeding 40 GHz for intentional radiators operated below 10 GHz and up to the fifth harmonic of the highest fundamental frequency but not exceeding 100 GHz for intentional radiators operated above 10 GHz.



HERMON LABORATORIES

Test specification:	Section 15.249(a)(d)/RSS-310, section 3.10, Field strength of emissions		
Test procedure:	ANSI C63.10 sections 6.5, 6.6		
Test mode:	Compliance		
Date(s):	10-Aug-17 - 22-Aug-17		
Temperature: 24.3 °C	Relative Humidity: 39 %	Air Pressure: 1011 hPa	Power: 48 VDC
Remarks: EUT with 42.4 dBi antenna gain			

Table 7.1.4 Radiated spurious emissions limits (other than harmonics)

Frequency, GHz	Distance, m	Field strength dB(µV/m)*, peak	Field strength dB(µV/m)*, average
40 - 60	0.50	89.56*	69.56*
60 - 75	0.10	103.54*	83.54*
75 - 100	0.05	109.60*	89.60*

*- The limit for other test distance was calculated using the inverse distance extrapolation factor as follows:

$$\text{LimS2} = \text{LimS1} + 20 \log (\text{S1}/\text{S2}),$$

where S1 and S2 – standard defined and test distance respectively in meters.



HERMON LABORATORIES

Test specification: Section 15.249(a)(d)/RSS-310, section 3.10, Field strength of emissions		
Test procedure: ANSI C63.10 sections 6.5, 6.6		
Test mode: Compliance		Verdict: PASS
Date(s): 10-Aug-17 - 22-Aug-17		
Temperature: 24.3 °C	Relative Humidity: 39 %	Air Pressure: 1011 hPa
Remarks: EUT with 42.4 dBi antenna gain		Power: 48 VDC


7.1.2 Test procedure for spurious emission field strength measurements in 9 kHz to 30 MHz band

- 7.1.2.1 The EUT was set up as shown in Figure 7.1.1, energized and the performance check was conducted.
- 7.1.2.2 The measurements were performed in the typical position.
- 7.1.2.3 The specified frequency range was investigated with antenna connected to spectrum analyzer/ EMI receiver. To find maximum radiation the turntable was rotated 360° and the measuring antenna was rotated around its vertical axis.
- 7.1.2.4 The worst test results (the lowest margins) were found in in typical position, recorded in the associated tables and shown in the associated plots.

7.1.3 Test procedure for spurious emission field strength measurements above 30 MHz

- 7.1.3.1 The EUT was set up as shown in Figure 7.1.2, Figure 7.1.3, energized and the performance check was conducted.
- 7.1.3.2 The measurements were performed in the typical position.
- 7.1.3.3 The specified frequency range was investigated with antenna connected to spectrum analyzer/ EMI receiver. To find maximum radiation the turntable was rotated 360°, the measuring antenna height was changed from 1 to 4 m, its polarization was switched from vertical to horizontal.
- 7.1.3.4 The worst test results (the lowest margins) were found in in typical position, recorded in the associated tables and shown in the associated plots

Figure 7.1.1 Setup for spurious emission field strength measurements below 30 MHz





HERMON LABORATORIES

Test specification: Section 15.249(a)(d)/RSS-310, section 3.10, Field strength of emissions		
Test procedure: ANSI C63.10 sections 6.5, 6.6		
Test mode: Compliance		Verdict: PASS
Date(s): 10-Aug-17 - 22-Aug-17		
Temperature: 24.3 °C	Relative Humidity: 39 %	Air Pressure: 1011 hPa
Remarks: EUT with 42.4 dBi antenna gain		Power: 48 VDC

Figure 7.1.2 Setup for spurious emission field strength measurements in 30 -1000 MHz





Figure 7.1.3 Setup for spurious emission field strength measurements above 1000 MHz





HERMON LABORATORIES

Test specification: Section 15.249(a)(d)/RSS-310, section 3.10, Field strength of emissions			
Test procedure:	ANSI C63.10 sections 6.5, 6.6		
Test mode:	Compliance		
Date(s):	10-Aug-17 - 22-Aug-17		
Temperature: 24.3 °C	Relative Humidity:	39 %	Air Pressure: 1011 hPa
Remarks: EUT with 42.4 dBi antenna gain		Power: 48 VDC	

Table 7.1.5 Field strength of fundamental emission

TEST DISTANCE:	3 m
EUT POSITION:	Typical
MODULATING SIGNAL:	PRBS
TRANSMITTER OUTPUT POWER SETTINGS:	Maximum
INVESTIGATED FREQUENCY RANGE:	0.009 – 100 000 MHz
DETECTOR USED:	Peak
RESOLUTION BANDWIDTH:	1.0 kHz (9 kHz – 150 kHz) 9.0 kHz (150 kHz – 30 MHz) 120 kHz (30 MHz – 1000 MHz) 1.0 MHz (above 1000 MHz) ≥ Resolution bandwidth
VIDEO BANDWIDTH:	
TEST ANTENNA TYPE:	Double ridged guide (above 1000 MHz)
<u>Fundamental emission</u>	

Frequency, MHz	Antenna		Azimuth, degrees*	Peak field strength			Avr factor, dB	Average field strength			Verdict			
	Pol.	Height, m		Measured, dB(µV/m)	Limit, dB(µV/m)	Margin, dB**		Measured, dB(µV/m)	Limit, dB(µV/m)	Margin, dB**				
Channel bandwidth 20 MHz														
Modulation QPSK														
24010.0	Vert	1.5	0	120.33	128.0	-7.67	0	107.44	108.0	-0.56	Pass			
24070.0	Vert	1.5	0	119.96	128.0	-8.04	0	107.28	108.0	-0.72				
24180.0	Vert	1.5	0	120.42	128.0	-7.58	0	107.68	108.0	-0.32				
24240.0	Vert	1.5	0	120.77	128.0	-7.23	0	107.89	108.0	-0.11				
Modulation 2048 QAM														
24010.0	Vert	1.5	0	120.22	128.0	-7.78	0	107.49	108.0	-0.51	Pass			
24070.0	Vert	1.5	0	118.85	128.0	-9.15	0	107.46	108.0	-0.54				
24180.0	Vert	1.5	0	118.86	128.0	-9.14	0	107.44	108.0	-0.56				
24240.0	Vert	1.5	0	119.82	128.0	-8.18	0	107.47	108.0	-0.53				
Modulation QPSK														
24010.0	Hor	1.5	0	120.71	128.0	-7.29	0	107.35	108.0	-0.65	Pass			
24070.0	Hor	1.5	0	120.37	128.0	-7.63	0	107.02	108.0	-0.98				
24180.0	Hor	1.5	0	120.38	128.0	-7.62	0	107.21	108.0	-0.79				
24240.0	Hor	1.5	0	120.84	128.0	-7.16	0	106.94	108.0	-1.06				
Modulation 2048 QAM														
24010.0	Hor	1.5	0	118.70	128.0	-9.30	0	107.31	108.0	-0.69	Pass			
24070.0	Hor	1.5	0	118.15	128.0	-9.85	0	107.43	108.0	-0.57				
24180.0	Hor	1.5	0	118.76	128.0	-9.24	0	107.36	108.0	-0.64				
24240.0	Hor	1.5	0	118.18	128.0	-9.82	0	106.98	108.0	-1.02				



HERMON LABORATORIES

Test specification: Section 15.249(a)(d)/RSS-310, section 3.10, Field strength of emissions			
Test procedure: ANSI C63.10 sections 6.5, 6.6			
Test mode: Compliance		Verdict: PASS	
Date(s): 10-Aug-17 - 22-Aug-17			
Temperature: 24.3 °C	Relative Humidity: 39 %	Air Pressure: 1011 hPa	Power: 48 VDC
Remarks: EUT with 42.4 dBi antenna gain			

Table 7.1.6 Field strength of fundamental emission

TEST DISTANCE:	3 m
EUT POSITION:	Typical
MODULATING SIGNAL:	PRBS
TRANSMITTER OUTPUT POWER SETTINGS:	Maximum
INVESTIGATED FREQUENCY RANGE:	0.009 – 100 000 MHz
DETECTOR USED:	Peak
RESOLUTION BANDWIDTH:	1.0 kHz (9 kHz – 150 kHz) 9.0 kHz (150 kHz – 30 MHz) 120 kHz (30 MHz – 1000 MHz) 1.0 MHz (above 1000 MHz) ≥ Resolution bandwidth
VIDEO BANDWIDTH:	
TEST ANTENNA TYPE:	Double ridged guide (above 1000 MHz)
<u>Fundamental emission</u>	

Frequency, MHz	Antenna		Azimuth, degrees*	Peak field strength			Avr factor, dB	Average field strength			Verdict			
	Pol.	Height, m		Measured, dB(µV/m)	Limit, dB(µV/m)	Margin, dB**		Measured, dB(µV/m)	Limit, dB(µV/m)	Margin, dB**				
Channel bandwidth 30 MHz														
Modulation QPSK														
24015.0	Vert	1.5	0	119.66	128.0	-8.34	0	106.45	108.0	-1.55	Pass			
24065.0	Vert	1.5	0	118.99	128.0	-9.01	0	106.78	108.0	-1.22				
24185.0	Vert	1.5	0	119.66	128.0	-8.34	0	106.22	108.0	-1.78				
24235.0	Vert	1.5	0	119.63	128.0	-8.37	0	106.64	108.0	-1.36				
Modulation 2048 QAM														
24015.0	Vert	1.5	0	117.46	128.0	-10.54	0	106.35	108.0	-1.65	Pass			
24065.0	Vert	1.5	0	117.44	128.0	-10.56	0	106.45	108.0	-1.55				
24185.0	Vert	1.5	0	117.66	128.0	-10.34	0	106.41	108.0	-1.59				
24235.0	Vert	1.5	0	117.64	128.0	-10.36	0	106.64	108.0	-1.36				
Modulation QPSK														
24015.0	Hor	1.5	0	119.06	128.0	-8.94	0	105.82	108.0	-2.18	Pass			
24065.0	Hor	1.5	0	118.48	128.0	-9.52	0	105.13	108.0	-2.87				
24185.0	Hor	1.5	0	118.27	128.0	-9.73	0	104.89	108.0	-3.11				
24235.0	Hor	1.5	0	119.11	128.0	-8.89	0	105.74	108.0	-2.26				
Modulation 2048 QAM														
24015.0	Hor	1.5	0	116.91	128.0	-11.09	0	105.73	108.0	-2.27	Pass			
24065.0	Hor	1.5	0	116.50	128.0	-11.50	0	105.91	108.0	-2.09				
24185.0	Hor	1.5	0	116.92	128.0	-11.08	0	105.64	108.0	-2.36				
24235.0	Hor	1.5	0	116.37	128.0	-11.63	0	105.25	108.0	-2.75				



HERMON LABORATORIES

Test specification: Section 15.249(a)(d)/RSS-310, section 3.10, Field strength of emissions			
Test procedure:	ANSI C63.10 sections 6.5, 6.6		
Test mode:	Compliance		
Date(s):	10-Aug-17 - 22-Aug-17		
Temperature: 24.3 °C	Relative Humidity:	39 %	Air Pressure: 1011 hPa
Remarks: EUT with 42.4 dBi antenna gain		Power: 48 VDC	

Table 7.1.7 Field strength of fundamental emission

TEST DISTANCE:	3 m
EUT POSITION:	Typical
MODULATING SIGNAL:	PRBS
TRANSMITTER OUTPUT POWER SETTINGS:	Maximum
INVESTIGATED FREQUENCY RANGE:	0.009 – 100 000 MHz
DETECTOR USED:	Peak
RESOLUTION BANDWIDTH:	1.0 kHz (9 kHz – 150 kHz) 9.0 kHz (150 kHz – 30 MHz) 120 kHz (30 MHz – 1000 MHz) 1.0 MHz (above 1000 MHz) ≥ Resolution bandwidth
VIDEO BANDWIDTH:	
TEST ANTENNA TYPE:	Double ridged guide (above 1000 MHz)
<u>Fundamental emission</u>	

Frequency, MHz	Antenna		Azimuth, degrees*	Peak field strength			Avr factor, dB	Average field strength			Verdict			
	Pol.	Height, m		Measured, dB(µV/m)	Limit, dB(µV/m)	Margin, dB**		Measured, dB(µV/m)	Limit, dB(µV/m)	Margin, dB**				
Channel bandwidth 40 MHz														
Modulation QPSK														
24020.0	Vert	1.5	0	119.82	128.0	-8.18	0	105.64	108.0	-2.36	Pass			
24060.0	Vert	1.5	0	119.63	128.0	-8.37	0	105.54	108.0	-2.46				
24190.0	Vert	1.5	0	118.76	128.0	-9.24	0	104.55	108.0	-3.45				
24230.0	Vert	1.5	0	119.58	128.0	-8.42	0	104.45	108.0	-3.55				
Modulation 2048 QAM														
24020.0	Vert	1.5	0	116.44	128.0	-11.56	0	105.23	108.0	-2.77	Pass			
24060.0	Vert	1.5	0	116.55	128.0	-11.45	0	105.46	108.0	-2.54				
24190.0	Vert	1.5	0	115.55	128.0	-12.45	0	104.69	108.0	-3.31				
24230.0	Vert	1.5	0	115.52	128.0	-12.48	0	104.8	108.0	-3.20				
Modulation QPSK														
24020.0	Hor	1.5	0	117.83	128.0	-10.17	0	104.05	108.0	-3.95	Pass			
24060.0	Hor	1.5	0	118.35	128.0	-9.65	0	104.21	108.0	-3.79				
24190.0	Hor	1.5	0	118.26	128.0	-9.74	0	104.47	108.0	-3.53				
24230.0	Hor	1.5	0	117.72	128.0	-10.28	0	103.99	108.0	-4.01				
Modulation 2048 QAM														
24020.0	Hor	1.5	0	114.70	128.0	-13.30	0	104.05	108.0	-3.95	Pass			
24060.0	Hor	1.5	0	115.55	128.0	-12.45	0	104.16	108.0	-3.84				
24190.0	Hor	1.5	0	116.02	128.0	-11.98	0	104.64	108.0	-3.36				
24230.0	Hor	1.5	0	115.35	128.0	-12.65	0	104.72	108.0	-3.28				



HERMON LABORATORIES

Test specification: Section 15.249(a)(d)/RSS-310, section 3.10, Field strength of emissions			
Test procedure: ANSI C63.10 sections 6.5, 6.6			
Test mode: Compliance		Verdict: PASS	
Date(s): 10-Aug-17 - 22-Aug-17			
Temperature: 24.3 °C	Relative Humidity: 39 %	Air Pressure: 1011 hPa	Power: 48 VDC
Remarks: EUT with 42.4 dBi antenna gain			

Table 7.1.8 Field strength of fundamental emission

TEST DISTANCE:	3 m
EUT POSITION:	Typical
MODULATING SIGNAL:	PRBS
TRANSMITTER OUTPUT POWER SETTINGS:	Maximum
INVESTIGATED FREQUENCY RANGE:	0.009 – 100 000 MHz
DETECTOR USED:	Peak
RESOLUTION BANDWIDTH:	1.0 kHz (9 kHz – 150 kHz) 9.0 kHz (150 kHz – 30 MHz) 120 kHz (30 MHz – 1000 MHz) 1.0 MHz (above 1000 MHz) ≥ Resolution bandwidth
VIDEO BANDWIDTH:	
TEST ANTENNA TYPE:	Double ridged guide (above 1000 MHz)
<u>Fundamental emission</u>	

Frequency, MHz	Antenna		Azimuth, degrees*	Peak field strength			Avr factor, dB	Average field strength			Verdict			
	Pol.	Height, m		Measured, dB(µV/m)	Limit, dB(µV/m)	Margin, dB**		Measured, dB(µV/m)	Limit, dB(µV/m)	Margin, dB**				
Channel bandwidth 50 MHz														
Modulation QPSK														
24025.0	Vert	1.5	0	118.99	128.0	-9.01	0	104.77	108.0	-3.23	Pass			
24055.0	Vert	1.5	0	119.24	128.0	-8.76	0	104.58	108.0	-3.42				
24195.0	Vert	1.5	0	117.99	128.0	-10.01	0	103.97	108.0	-4.03				
24225.0	Vert	1.5	0	119.22	128.0	-8.78	0	103.89	108.0	-4.11				
Modulation 2048 QAM														
24025.0	Vert	1.5	0	114.66	128.0	-13.34	0	104.53	108.0	-3.47	Pass			
24055.0	Vert	1.5	0	115.56	128.0	-12.44	0	104.34	108.0	-3.66				
24195.0	Vert	1.5	0	114.44	128.0	-13.56	0	103.83	108.0	-4.17				
24225.0	Vert	1.5	0	114.84	128.0	-13.16	0	103.55	108.0	-4.45				
Modulation QPSK														
24025.0	Hor	1.5	0	118.32	128.0	-9.68	0	103.45	108.0	-4.55	Pass			
24055.0	Hor	1.5	0	117.70	128.0	-10.30	0	103.51	108.0	-4.49				
24195.0	Hor	1.5	0	118.59	128.0	-9.41	0	104.41	108.0	-3.59				
24225.0	Hor	1.5	0	117.75	128.0	-10.25	0	104.05	108.0	-3.95				
Modulation 2048 QAM														
24025.0	Hor	1.5	0	113.95	128.0	-14.05	0	103.37	108.0	-4.63	Pass			
24055.0	Hor	1.5	0	114.96	128.0	-13.04	0	103.31	108.0	-4.69				
24195.0	Hor	1.5	0	114.76	128.0	-13.24	0	103.97	108.0	-4.03				
24225.0	Hor	1.5	0	114.59	128.0	-13.41	0	103.50	108.0	-4.50				



HERMON LABORATORIES

Test specification: Section 15.249(a)(d)/RSS-310, section 3.10, Field strength of emissions									
Test procedure:	ANSI C63.10 sections 6.5, 6.6								
Test mode:	Compliance				Verdict:	PASS			
Date(s):	10-Aug-17 - 22-Aug-17								
Temperature: 24.3 °C	Relative Humidity: 39 %		Air Pressure: 1011 hPa		Power: 48 VDC				
Remarks: EUT with 42.4 dBi antenna gain									

Table 7.1.9 Field strength of fundamental emission

TEST DISTANCE:	3 m
EUT POSITION:	Typical
MODULATING SIGNAL:	PRBS
TRANSMITTER OUTPUT POWER SETTINGS:	Maximum
INVESTIGATED FREQUENCY RANGE:	0.009 – 100 000 MHz
DETECTOR USED:	Peak
RESOLUTION BANDWIDTH:	1.0 kHz (9 kHz – 150 kHz) 9.0 kHz (150 kHz – 30 MHz) 120 kHz (30 MHz – 1000 MHz) 1.0 MHz (above 1000 MHz) ≥ Resolution bandwidth
VIDEO BANDWIDTH:	Double ridged guide (above 1000 MHz)
TEST ANTENNA TYPE:	

Fundamental emission

Frequency, MHz	Antenna		Azimuth, degrees*	Peak field strength			Avr factor, dB	Average field strength			Verdict			
	Pol.	Height, m		Measured, dB(µV/m)	Limit, dB(µV/m)	Margin, dB**		Measured, dB(µV/m)	Limit, dB(µV/m)	Margin, dB**				
Channel bandwidth 60 MHz														
Modulation QPSK														
24030.0	Vert	1.5	0	117.40	128.0	-10.60	0	103.57	108.0	-4.43	Pass			
24050.0	Vert	1.5	0	117.68	128.0	-10.32	0	103.45	108.0	-4.55				
24200.0	Vert	1.5	0	116.97	128.0	-11.03	0	103.54	108.0	-4.46				
24220.0	Vert	1.5	0	117.22	128.0	-10.78	0	103.34	108.0	-4.66				
Modulation 2048 QAM														
24030.0	Vert	1.5	0	113.38	128.0	-14.62	0	103.57	108.0	-4.43	Pass			
24050.0	Vert	1.5	0	113.38	128.0	-14.62	0	103.48	108.0	-4.52				
24200.0	Vert	1.5	0	113.89	128.0	-14.11	0	103.28	108.0	-4.72				
24220.0	Vert	1.5	0	113.66	128.0	-14.34	0	103.46	108.0	-4.54				
Modulation QPSK														
24030.0	Hor	1.5	0	116.69	128.0	-11.31	0	102.84	108.0	-5.16	Pass			
24050.0	Hor	1.5	0	116.59	128.0	-11.41	0	102.68	108.0	-5.32				
24200.0	Hor	1.5	0	117.00	128.0	-11.00	0	103.25	108.0	-4.75				
24220.0	Hor	1.5	0	116.72	128.0	-11.28	0	102.72	108.0	-5.28				
Modulation 2048 QAM														
24030.0	Hor	1.5	0	113.51	128.0	-14.49	0	102.52	108.0	-5.48	Pass			
24050.0	Hor	1.5	0	113.65	128.0	-14.35	0	102.51	108.0	-5.49				
24200.0	Hor	1.5	0	113.46	128.0	-14.54	0	102.67	108.0	-5.33				
24220.0	Hor	1.5	0	113.17	128.0	-14.83	0	102.66	108.0	-5.34				

Table 7.1.10 Average factor calculation

Transmission pulse		Transmission burst		Transmission train duration, ms	Average factor, dB
Duration, ms	Period, ms	Duration, ms	Period, ms		
NA	NA	NA	NA	NA	0

*- Average factor was calculated as follows

for pulse train shorter than 100 ms:

$$\text{Average factor} = 20 \times \log_{10} \left(\frac{\text{Pulse duration} \times \text{Burst duration}}{\text{Pulse period} \times \text{Train duration}} \times \text{Number of bursts within pulse train} \right)$$

Reference numbers of test equipment used

HL 0446	HL 0604	HL 0770	HL 0771	HL 0772	HL 1299	HL 1300	HL 2909
HL 3235	HL 3294	HL 3297	HL 3305	HL 3433	HL 3434	HL 3818	HL 4280
HL 4353	HL 4933	HL 4956	HL 5112				

Full description is given in Appendix A.



HERMON LABORATORIES

Test specification: Section 15.249(a)(d)/RSS-310, section 3.10, Field strength of emissions		
Test procedure:	ANSI C63.10 sections 6.5, 6.6	
Test mode:	Compliance	
Date(s):	10-Aug-17 - 22-Aug-17	
Temperature: 24.3 °C	Relative Humidity: 39 %	Air Pressure: 1011 hPa
Remarks: EUT with 42.4 dBi antenna gain		Power: 48 VDC

Plot 7.1.1 Radiated emission measurements at the fundamental frequency

TEST SITE:

OATS

TEST DISTANCE:

3 m

ANTENNA POLARIZATION:

Vertical

EUT POSITION:

Typical (Vertical)

EMISSION BANDWIDTH:

20 MHz

MODULATION:



QPSK

CARRIER FREQUENCY:

Low

DETECTOR: Peak

DETECTOR: Average





CARRIER FREQUENCY:

Mid

DETECTOR: Peak

DETECTOR: Average





HERMON LABORATORIES

Test specification: Section 15.249(a)(d)/RSS-310, section 3.10, Field strength of emissions		
Test procedure: ANSI C63.10 sections 6.5, 6.6		
Test mode: Compliance		Verdict: PASS
Date(s):	10-Aug-17 - 22-Aug-17	
Temperature: 24.3 °C	Relative Humidity: 39 %	Air Pressure: 1011 hPa
Remarks: EUT with 42.4 dBi antenna gain		

Plot 7.1.2 Radiated emission measurements at the fundamental frequency

TEST SITE:

OATS

TEST DISTANCE:

3 m

ANTENNA POLARIZATION:

Vertical

EUT POSITION:

Typical (Vertical)

EMISSION BANDWIDTH:

20 MHz

MODULATION:

QPSK

CARRIER FREQUENCY:

Mid



DETECTOR: Peak

DETECTOR: Average

Agilent

Agilent

Agilent



CARRIER FREQUENCY:

High



DETECTOR: Peak

DETECTOR: Average

Agilent

Agilent

Agilent






HERMON LABORATORIES

Test specification: Section 15.249(a)(d)/RSS-310, section 3.10, Field strength of emissions		
Test procedure:	ANSI C63.10 sections 6.5, 6.6	
Test mode:	Compliance	Verdict: PASS
Date(s):	10-Aug-17 - 22-Aug-17	
Temperature: 24.3 °C	Relative Humidity: 39 %	Air Pressure: 1011 hPa
Remarks: EUT with 42.4 dBi antenna gain		Power: 48 VDC


Plot 7.1.3 Radiated emission measurements at the fundamental frequency

TEST SITE: OATS
 TEST DISTANCE: 3 m
 ANTENNA POLARIZATION: Horizontal
 EUT POSITION: Typical (Vertical)
 EMISSION BANDWIDTH: 20 MHz
 MODULATION: QPSK


CARRIER FREQUENCY:
 DETECTOR: Peak




Low
 DETECTOR: Average



CARRIER FREQUENCY:
 DETECTOR: Peak



Mid
 DETECTOR: Average





HERMON LABORATORIES

Test specification: Section 15.249(a)(d)/RSS-310, section 3.10, Field strength of emissions		
Test procedure:	ANSI C63.10 sections 6.5, 6.6	
Test mode:	Compliance	Verdict: PASS
Date(s):	10-Aug-17 - 22-Aug-17	
Temperature: 24.3 °C	Relative Humidity: 39 %	Air Pressure: 1011 hPa
Remarks: EUT with 42.4 dBi antenna gain		Power: 48 VDC

Plot 7.1.4 Radiated emission measurements at the fundamental frequency

TEST SITE:

OATS

TEST DISTANCE:

3 m

ANTENNA POLARIZATION:

Horizontal

EUT POSITION:

Typical (Vertical)

EMISSION BANDWIDTH:

20 MHz

MODULATION:

QPSK

CARRIER FREQUENCY:

Mid

DETECTOR: Peak

DETECTOR: Average




CARRIER FREQUENCY:

High

DETECTOR: Peak

DETECTOR: Average





HERMON LABORATORIES

Test specification: Section 15.249(a)(d)/RSS-310, section 3.10, Field strength of emissions		
Test procedure:	ANSI C63.10 sections 6.5, 6.6	
Test mode:	Compliance	Verdict: PASS
Date(s):	10-Aug-17 - 22-Aug-17	
Temperature: 24.3 °C	Relative Humidity: 39 %	Air Pressure: 1011 hPa
Remarks: EUT with 42.4 dBi antenna gain		Power: 48 VDC

Plot 7.1.5 Radiated emission measurements at the fundamental frequency

TEST SITE:

OATS

TEST DISTANCE:

3 m

ANTENNA POLARIZATION:

Vertical

EUT POSITION:

Typical (Vertical)

EMISSION BANDWIDTH:

20 MHz

MODULATION:

2048QAM


CARRIER FREQUENCY:

Low

DETECTOR: Peak

DETECTOR: Average

* Agilent




CARRIER FREQUENCY:

Mid


DETECTOR: Peak

DETECTOR: Average

* Agilent



* Agilent





HERMON LABORATORIES

Test specification: Section 15.249(a)(d)/RSS-310, section 3.10, Field strength of emissions		
Test procedure: ANSI C63.10 sections 6.5, 6.6		
Test mode: Compliance	Verdict: PASS	
Date(s): 10-Aug-17 - 22-Aug-17		
Temperature: 24.3 °C	Relative Humidity: 39 %	Air Pressure: 1011 hPa
Remarks: EUT with 42.4 dBi antenna gain		Power: 48 VDC

Plot 7.1.6 Radiated emission measurements at the fundamental frequency

TEST SITE:

OATS

TEST DISTANCE:

3 m

ANTENNA POLARIZATION:

Vertical

EUT POSITION:

Typical (Vertical)

EMISSION BANDWIDTH:

20 MHz

MODULATION:

2048QAM

CARRIER FREQUENCY:

Mid



DETECTOR: Peak

DETECTOR: Average

Agilent

Agilent

Agilent



CARRIER FREQUENCY:

High



DETECTOR: Peak

DETECTOR: Average

Agilent

Agilent

Agilent






HERMON LABORATORIES

Test specification: Section 15.249(a)(d)/RSS-310, section 3.10, Field strength of emissions		
Test procedure:	ANSI C63.10 sections 6.5, 6.6	
Test mode:	Compliance	Verdict: PASS
Date(s):	10-Aug-17 - 22-Aug-17	
Temperature: 24.3 °C	Relative Humidity: 39 %	Air Pressure: 1011 hPa
Remarks: EUT with 42.4 dBi antenna gain		Power: 48 VDC


Plot 7.1.7 Radiated emission measurements at the fundamental frequency

TEST SITE: OATS
 TEST DISTANCE: 3 m
 ANTENNA POLARIZATION: Horizontal
 EUT POSITION: Typical (Vertical)
 EMISSION BANDWIDTH: 20 MHz
 MODULATION: 2048QAM


CARRIER FREQUENCY:
 DETECTOR: Peak




Low
 DETECTOR: Average



CARRIER FREQUENCY:
 DETECTOR: Peak



Mid
 DETECTOR: Average





HERMON LABORATORIES

Test specification: Section 15.249(a)(d)/RSS-310, section 3.10, Field strength of emissions		
Test procedure:	ANSI C63.10 sections 6.5, 6.6	
Test mode:	Compliance	
Date(s):	10-Aug-17 - 22-Aug-17	
Temperature: 24.3 °C	Relative Humidity: 39 %	Air Pressure: 1011 hPa
Remarks: EUT with 42.4 dBi antenna gain		Power: 48 VDC

Plot 7.1.8 Radiated emission measurements at the fundamental frequency

TEST SITE:

OATS

TEST DISTANCE:

3 m

ANTENNA POLARIZATION:

Horizontal

EUT POSITION:

Typical (Vertical)

EMISSION BANDWIDTH:

20 MHz

MODULATION:


2048QAM

CARRIER FREQUENCY:

Mid

DETECTOR: Peak

DETECTOR: Average




CARRIER FREQUENCY:

High

DETECTOR: Peak

DETECTOR: Average





HERMON LABORATORIES

Test specification: Section 15.249(a)(d)/RSS-310, section 3.10, Field strength of emissions		
Test procedure:	ANSI C63.10 sections 6.5, 6.6	
Test mode:	Compliance	
Date(s):	10-Aug-17 - 22-Aug-17	
Temperature: 24.3 °C	Relative Humidity: 39 %	Air Pressure: 1011 hPa
Remarks: EUT with 42.4 dBi antenna gain		Power: 48 VDC

Plot 7.1.9 Radiated emission measurements at the fundamental frequency

TEST SITE:

OATS

TEST DISTANCE:

3 m

ANTENNA POLARIZATION:

Vertical

EUT POSITION:

Typical (Vertical)

EMISSION BANDWIDTH:

30 MHz

MODULATION:

QPSK

CARRIER FREQUENCY:

Low


DETECTOR: Peak

DETECTOR: Average

Agilent

R T


Mkr1 24.016 92 GHz

119.66 dB μ V/m

Agilent

R T

Mkr1 24.019 76 GHz

106.446 dB μ V/m

CARRIER FREQUENCY:

Mid

DETECTOR: Peak

DETECTOR: Average

Agilent

R T


Mkr1 24.065 92 GHz

118.99 dB μ V/m

Agilent

R T

Mkr1 24.068 57 GHz

106.776 dB μ V/m



HERMON LABORATORIES

Test specification: Section 15.249(a)(d)/RSS-310, section 3.10, Field strength of emissions		
Test procedure:	ANSI C63.10 sections 6.5, 6.6	
Test mode:	Compliance	Verdict: PASS
Date(s):	10-Aug-17 - 22-Aug-17	
Temperature: 24.3 °C	Relative Humidity: 39 %	Air Pressure: 1011 hPa
Remarks: EUT with 42.4 dBi antenna gain		Power: 48 VDC

Plot 7.1.10 Radiated emission measurements at the fundamental frequency

TEST SITE:

OATS

TEST DISTANCE:

3 m

ANTENNA POLARIZATION:

Vertical

EUT POSITION:

Typical (Vertical)

EMISSION BANDWIDTH:

30 MHz

MODULATION:


QPSK

CARRIER FREQUENCY:

Mid

DETECTOR: Peak


DETECTOR: Average



CARRIER FREQUENCY:

DETECTOR: Average

DETECTOR: Peak





HERMON LABORATORIES

Test specification: Section 15.249(a)(d)/RSS-310, section 3.10, Field strength of emissions		
Test procedure:	ANSI C63.10 sections 6.5, 6.6	
Test mode:	Compliance	Verdict: PASS
Date(s):	10-Aug-17 - 22-Aug-17	
Temperature: 24.3 °C	Relative Humidity: 39 %	Air Pressure: 1011 hPa
Remarks: EUT with 42.4 dBi antenna gain		Power: 48 VDC

Plot 7.1.11 Radiated emission measurements at the fundamental frequency

TEST SITE:

OATS

TEST DISTANCE:

3 m

ANTENNA POLARIZATION:

Horizontal

EUT POSITION:

Typical (Vertical)

EMISSION BANDWIDTH:

30 MHz

MODULATION:



QPSK

CARRIER FREQUENCY:

Low

DETECTOR: Peak

DETECTOR: Average





CARRIER FREQUENCY:

Mid

DETECTOR: Peak

DETECTOR: Average





HERMON LABORATORIES

Test specification: Section 15.249(a)(d)/RSS-310, section 3.10, Field strength of emissions		
Test procedure:	ANSI C63.10 sections 6.5, 6.6	
Test mode:	Compliance	Verdict: PASS
Date(s):	10-Aug-17 - 22-Aug-17	
Temperature: 24.3 °C	Relative Humidity: 39 %	Air Pressure: 1011 hPa
Remarks: EUT with 42.4 dBi antenna gain		Power: 48 VDC

Plot 7.1.12 Radiated emission measurements at the fundamental frequency

TEST SITE:

OATS

TEST DISTANCE:

3 m

ANTENNA POLARIZATION:

Horizontal

EUT POSITION:

Typical (Vertical)

EMISSION BANDWIDTH:

30 MHz

MODULATION:


QPSK

CARRIER FREQUENCY:

Mid

DETECTOR: Peak

DETECTOR: Average




CARRIER FREQUENCY:

High

DETECTOR: Peak

DETECTOR: Average







Test specification:	Section 15.249(a)(d)/RSS-310, section 3.10, Field strength of emissions		
Test procedure:	ANSI C63.10 sections 6.5, 6.6		
Test mode:	Compliance	Verdict:	PASS
Date(s):	10-Aug-17 - 22-Aug-17		
Temperature: 24.3 °C	Relative Humidity: 39 %	Air Pressure: 1011 hPa	Power: 48 VDC
Remarks: EUT with 42.4 dBi antenna gain			



Plot 7.1.13 Radiated emission measurements at the fundamental frequency

TEST SITE:	OATS
TEST DISTANCE:	3 m
ANTENNA POLARIZATION:	Vertical
EUT POSITION:	Typical (Vertical)
EMISSION BANDWIDTH:	30 MHz
MODULATION:	2048QAM

CARRIER FREQUENCY:
DETECTOR: Peak



CARRIER FREQUENCY:
DETECTOR: Peak





HERMON LABORATORIES

Test specification: Section 15.249(a)(d)/RSS-310, section 3.10, Field strength of emissions		
Test procedure:	ANSI C63.10 sections 6.5, 6.6	
Test mode:	Compliance	Verdict: PASS
Date(s):	10-Aug-17 - 22-Aug-17	
Temperature: 24.3 °C	Relative Humidity: 39 %	Air Pressure: 1011 hPa
Remarks: EUT with 42.4 dBi antenna gain		Power: 48 VDC

Plot 7.1.14 Radiated emission measurements at the fundamental frequency

TEST SITE:

OATS

TEST DISTANCE:

3 m

ANTENNA POLARIZATION:

Vertical

EUT POSITION:

Typical (Vertical)

EMISSION BANDWIDTH:

30 MHz

MODULATION:


2048QAM

CARRIER FREQUENCY:

Mid

DETECTOR: Peak

DETECTOR: Average




CARRIER FREQUENCY:

High

DETECTOR: Peak

DETECTOR: Average





HERMON LABORATORIES

Test specification: Section 15.249(a)(d)/RSS-310, section 3.10, Field strength of emissions		
Test procedure:	ANSI C63.10 sections 6.5, 6.6	
Test mode:	Compliance	Verdict: PASS
Date(s):	10-Aug-17 - 22-Aug-17	
Temperature: 24.3 °C	Relative Humidity: 39 %	Air Pressure: 1011 hPa
Remarks: EUT with 42.4 dBi antenna gain		Power: 48 VDC

Plot 7.1.15 Radiated emission measurements at the fundamental frequency

TEST SITE:

OATS

TEST DISTANCE:

3 m

ANTENNA POLARIZATION:

Horizontal

EUT POSITION:

Typical (Vertical)

EMISSION BANDWIDTH:

30 MHz

MODULATION:



2048QAM

CARRIER FREQUENCY:

Low

DETECTOR: Peak

DETECTOR: Average





CARRIER FREQUENCY:

Mid

DETECTOR: Peak

DETECTOR: Average





HERMON LABORATORIES

Test specification: Section 15.249(a)(d)/RSS-310, section 3.10, Field strength of emissions		
Test procedure:	ANSI C63.10 sections 6.5, 6.6	
Test mode:	Compliance	
Date(s):	10-Aug-17 - 22-Aug-17	
Temperature: 24.3 °C	Relative Humidity: 39 %	Air Pressure: 1011 hPa
Remarks: EUT with 42.4 dBi antenna gain		Power: 48 VDC

Plot 7.1.16 Radiated emission measurements at the fundamental frequency

TEST SITE:

OATS

TEST DISTANCE:

3 m

ANTENNA POLARIZATION:

Horizontal

EUT POSITION:

Typical (Vertical)

EMISSION BANDWIDTH:

30 MHz

MODULATION:

2048QAM

CARRIER FREQUENCY:



Mid

DETECTOR: Peak

DETECTOR: Average

Agilent

Agilent



CARRIER FREQUENCY:



High

DETECTOR: Peak

DETECTOR: Average

Agilent

Agilent





HERMON LABORATORIES


Test specification: Section 15.249(a)(d)/RSS-310, section 3.10, Field strength of emissions			
Test procedure: ANSI C63.10 sections 6.5, 6.6			
Test mode: Compliance			Verdict: PASS
Date(s): 10-Aug-17 - 22-Aug-17			
Temperature: 24.3 °C	Relative Humidity: 39 %	Air Pressure: 1011 hPa	Power: 48 VDC
Remarks: EUT with 42.4 dBi antenna gain			

Plot 7.1.17 Radiated emission measurements at the fundamental frequency


TEST SITE:
TEST DISTANCE:
ANTENNA POLARIZATION:
EUT POSITION:
EMISSION BANDWIDTH:
MODULATION:

OATS
3 m
Vertical
Typical (Vertical)
40 MHz
QPSK


CARRIER FREQUENCY:
DETECTOR: Peak




Low
DETECTOR: Average



CARRIER FREQUENCY:
DETECTOR: Peak



Mid
DETECTOR: Average





HERMON LABORATORIES

Test specification: Section 15.249(a)(d)/RSS-310, section 3.10, Field strength of emissions		
Test procedure:	ANSI C63.10 sections 6.5, 6.6	
Test mode:	Compliance	
Date(s):	10-Aug-17 - 22-Aug-17	
Temperature: 24.3 °C	Relative Humidity: 39 %	Air Pressure: 1011 hPa
Remarks: EUT with 42.4 dBi antenna gain		Power: 48 VDC

Plot 7.1.18 Radiated emission measurements at the fundamental frequency

TEST SITE:

OATS

TEST DISTANCE:

3 m

ANTENNA POLARIZATION:

Vertical

EUT POSITION:

Typical (Vertical)

EMISSION BANDWIDTH:

40 MHz

MODULATION:

QPSK



CARRIER FREQUENCY:

Mid

DETECTOR: Peak

DETECTOR: Average

Agilent





CARRIER FREQUENCY:

High

DETECTOR: Peak

DETECTOR: Average

Agilent







Test specification:	Section 15.249(a)(d)/RSS-310, section 3.10, Field strength of emissions		
Test procedure:	ANSI C63.10 sections 6.5, 6.6		
Test mode:	Compliance	Verdict:	PASS
Date(s):	10-Aug-17 - 22-Aug-17		
Temperature: 24.3 °C	Relative Humidity: 39 %	Air Pressure: 1011 hPa	Power: 48 VDC
Remarks: EUT with 42.4 dBi antenna gain			



Plot 7.1.19 Radiated emission measurements at the fundamental frequency

TEST SITE:	OATS
TEST DISTANCE:	3 m
ANTENNA POLARIZATION:	Horizontal
EUT POSITION:	Typical (Vertical)
EMISSION BANDWIDTH:	40 MHz
MODULATION:	QPSK

CARRIER FREQUENCY:
DETECTOR: Peak



CARRIER FREQUENCY:
DETECTOR: Peak





HERMON LABORATORIES

Test specification: Section 15.249(a)(d)/RSS-310, section 3.10, Field strength of emissions		
Test procedure:	ANSI C63.10 sections 6.5, 6.6	
Test mode:	Compliance	Verdict: PASS
Date(s):	10-Aug-17 - 22-Aug-17	
Temperature: 24.3 °C	Relative Humidity: 39 %	Air Pressure: 1011 hPa
Remarks: EUT with 42.4 dBi antenna gain		Power: 48 VDC

Plot 7.1.20 Radiated emission measurements at the fundamental frequency

TEST SITE:

OATS

TEST DISTANCE:

3 m

ANTENNA POLARIZATION:

Horizontal

EUT POSITION:

Typical (Vertical)

EMISSION BANDWIDTH:

40 MHz

MODULATION:

QPSK



CARRIER FREQUENCY:

Mid

DETECTOR: Peak

DETECTOR: Average

* Agilent





CARRIER FREQUENCY:

High

DETECTOR: Peak

DETECTOR: Average

* Agilent





HERMON LABORATORIES

Test specification: Section 15.249(a)(d)/RSS-310, section 3.10, Field strength of emissions		
Test procedure:	ANSI C63.10 sections 6.5, 6.6	
Test mode:	Compliance	Verdict: PASS
Date(s):	10-Aug-17 - 22-Aug-17	
Temperature: 24.3 °C	Relative Humidity: 39 %	Air Pressure: 1011 hPa
Remarks: EUT with 42.4 dBi antenna gain		Power: 48 VDC

Plot 7.1.21 Radiated emission measurements at the fundamental frequency

TEST SITE:

OATS

TEST DISTANCE:

3 m

ANTENNA POLARIZATION:

Vertical

EUT POSITION:

Typical (Vertical)

EMISSION BANDWIDTH:



40 MHz 2048QAM

CARRIER FREQUENCY:

Low

DETECTOR: Peak

DETECTOR: Average





CARRIER FREQUENCY:

Mid

DETECTOR: Peak

DETECTOR: Average





HERMON LABORATORIES

Test specification: Section 15.249(a)(d)/RSS-310, section 3.10, Field strength of emissions		
Test procedure:	ANSI C63.10 sections 6.5, 6.6	
Test mode:	Compliance	Verdict: PASS
Date(s):	10-Aug-17 - 22-Aug-17	
Temperature: 24.3 °C	Relative Humidity: 39 %	Air Pressure: 1011 hPa
Remarks: EUT with 42.4 dBi antenna gain		Power: 48 VDC

Plot 7.1.22 Radiated emission measurements at the fundamental frequency

TEST SITE:

OATS

TEST DISTANCE:

3 m

ANTENNA POLARIZATION:

Vertical

EUT POSITION:

Typical (Vertical)

EMISSION BANDWIDTH:

40 MHz 2048QAM



CARRIER FREQUENCY:

Mid

DETECTOR: Peak

DETECTOR: Average

Agilent





CARRIER FREQUENCY:

High

DETECTOR: Peak

DETECTOR: Average

Agilent






HERMON LABORATORIES

Test specification: Section 15.249(a)(d)/RSS-310, section 3.10, Field strength of emissions		
Test procedure: ANSI C63.10 sections 6.5, 6.6		
Test mode: Compliance		Verdict: PASS
Date(s):	10-Aug-17 - 22-Aug-17	
Temperature: 24.3 °C	Relative Humidity: 39 %	Air Pressure: 1011 hPa
Remarks: EUT with 42.4 dBi antenna gain		


Plot 7.1.23 Radiated emission measurements at the fundamental frequency

TEST SITE: OATS
 TEST DISTANCE: 3 m
 ANTENNA POLARIZATION: Horizontal
 EUT POSITION: Typical (Vertical)
 EMISSION BANDWIDTH: 40 MHz
 MODULATION: 2048QAM


CARRIER FREQUENCY:
 DETECTOR: Peak




Low
 DETECTOR: Average



CARRIER FREQUENCY:
 DETECTOR: Peak



Mid
 DETECTOR: Average





HERMON LABORATORIES

Test specification: Section 15.249(a)(d)/RSS-310, section 3.10, Field strength of emissions		
Test procedure: ANSI C63.10 sections 6.5, 6.6		
Test mode: Compliance	Verdict: PASS	
Date(s): 10-Aug-17 - 22-Aug-17		
Temperature: 24.3 °C	Relative Humidity: 39 %	Air Pressure: 1011 hPa
Remarks: EUT with 42.4 dBi antenna gain		Power: 48 VDC

Plot 7.1.24 Radiated emission measurements at the fundamental frequency

TEST SITE:

OATS

TEST DISTANCE:

3 m

ANTENNA POLARIZATION:

Horizontal

EUT POSITION:

Typical (Vertical)

EMISSION BANDWIDTH:

40 MHz

MODULATION:



2048QAM

CARRIER FREQUENCY:

Mid

DETECTOR: Peak

DETECTOR: Average





CARRIER FREQUENCY:

High

DETECTOR: Peak

DETECTOR: Average






HERMON LABORATORIES

Test specification: Section 15.249(a)(d)/RSS-310, section 3.10, Field strength of emissions		
Test procedure:	ANSI C63.10 sections 6.5, 6.6	
Test mode:	Compliance	Verdict: PASS
Date(s):	10-Aug-17 - 22-Aug-17	
Temperature: 24.3 °C	Relative Humidity: 39 %	Air Pressure: 1011 hPa
Remarks: EUT with 42.4 dBi antenna gain		Power: 48 VDC


Plot 7.1.25 Radiated emission measurements at the fundamental frequency

TEST SITE: OATS
 TEST DISTANCE: 3 m
 ANTENNA POLARIZATION: Vertical
 EUT POSITION: Typical (Vertical)
 EMISSION BANDWIDTH: 50 MHz
 MODULATION: QPSK


CARRIER FREQUENCY:
 DETECTOR: Peak




Low
 DETECTOR: Average



CARRIER FREQUENCY:
 DETECTOR: Peak



Mid
 DETECTOR: Average





HERMON LABORATORIES

Test specification: Section 15.249(a)(d)/RSS-310, section 3.10, Field strength of emissions		
Test procedure:	ANSI C63.10 sections 6.5, 6.6	
Test mode:	Compliance	
Date(s):	10-Aug-17 - 22-Aug-17	
Temperature: 24.3 °C	Relative Humidity: 39 %	Air Pressure: 1011 hPa
Remarks: EUT with 42.4 dBi antenna gain		Power: 48 VDC

Plot 7.1.26 Radiated emission measurements at the fundamental frequency

TEST SITE:

OATS

TEST DISTANCE:

3 m

ANTENNA POLARIZATION:

Vertical

EUT POSITION:

Typical (Vertical)

EMISSION BANDWIDTH:

50 MHz

MODULATION:

QPSK



CARRIER FREQUENCY:

Mid

DETECTOR: Peak

DETECTOR: Average

Agilent





CARRIER FREQUENCY:

High

DETECTOR: Peak

DETECTOR: Average

Agilent







Test specification:	Section 15.249(a)(d)/RSS-310, section 3.10, Field strength of emissions		
Test procedure:	ANSI C63.10 sections 6.5, 6.6		
Test mode:	Compliance	Verdict:	PASS
Date(s):	10-Aug-17 - 22-Aug-17		
Temperature: 24.3 °C	Relative Humidity: 39 %	Air Pressure: 1011 hPa	Power: 48 VDC
Remarks: EUT with 42.4 dBi antenna gain			



Plot 7.1.27 Radiated emission measurements at the fundamental frequency

TEST SITE:	OATS
TEST DISTANCE:	3 m
ANTENNA POLARIZATION:	Horizontal
EUT POSITION:	Typical (Vertical)
EMISSION BANDWIDTH:	50 MHz
MODULATION:	QPSK

CARRIER FREQUENCY:
DETECTOR: Peak



CARRIER FREQUENCY:
DETECTOR: Peak





HERMON LABORATORIES

Test specification: Section 15.249(a)(d)/RSS-310, section 3.10, Field strength of emissions			
Test procedure:	ANSI C63.10 sections 6.5, 6.6		
Test mode:	Compliance		
Date(s):	10-Aug-17 - 22-Aug-17		
Temperature: 24.3 °C	Relative Humidity: 39 %	Air Pressure: 1011 hPa	Power: 48 VDC
Remarks: EUT with 42.4 dBi antenna gain			

Plot 7.1.28 Radiated emission measurements at the fundamental frequency

TEST SITE:

OATS

TEST DISTANCE:

3 m

ANTENNA POLARIZATION:

Horizontal

EUT POSITION:

Typical (Vertical)

EMISSION BANDWIDTH:

50 MHz

MODULATION:

QPSK

CARRIER FREQUENCY:

Mid



DETECTOR: Peak

DETECTOR: Average

Agilent

Agilent

Agilent



CARRIER FREQUENCY:

High


DETECTOR: Peak

DETECTOR: Average

Agilent

Agilent

Agilent





HERMON LABORATORIES

Test specification: Section 15.249(a)(d)/RSS-310, section 3.10, Field strength of emissions		
Test procedure:	ANSI C63.10 sections 6.5, 6.6	
Test mode:	Compliance	Verdict: PASS
Date(s):	10-Aug-17 - 22-Aug-17	
Temperature: 24.3 °C	Relative Humidity: 39 %	Air Pressure: 1011 hPa
Remarks: EUT with 42.4 dBi antenna gain		Power: 48 VDC

Plot 7.1.29 Radiated emission measurements at the fundamental frequency

TEST SITE:

OATS

TEST DISTANCE:

3 m

ANTENNA POLARIZATION:

Vertical

EUT POSITION:

Typical (Vertical)

EMISSION BANDWIDTH:


50 MHz

MODULATION:

2048QAM


CARRIER FREQUENCY:

DETECTOR: Peak




Low

DETECTOR: Average




CARRIER FREQUENCY:

DETECTOR: Peak



Mid

DETECTOR: Average





HERMON LABORATORIES

Test specification: Section 15.249(a)(d)/RSS-310, section 3.10, Field strength of emissions			
Test procedure:	ANSI C63.10 sections 6.5, 6.6		
Test mode:	Compliance		
Date(s):	10-Aug-17 - 22-Aug-17		
Temperature: 24.3 °C	Relative Humidity: 39 %	Air Pressure: 1011 hPa	Power: 48 VDC
Remarks: EUT with 42.4 dBi antenna gain			

Plot 7.1.30 Radiated emission measurements at the fundamental frequency

TEST SITE:

OATS

TEST DISTANCE:

3 m

ANTENNA POLARIZATION:

Vertical

EUT POSITION:

Typical (Vertical)

EMISSION BANDWIDTH:

50 MHz

MODULATION:

2048QAM

CARRIER FREQUENCY:

Mid



DETECTOR: Peak

DETECTOR: Average

Agilent

Agilent

Agilent



CARRIER FREQUENCY:

High


DETECTOR: Peak

DETECTOR: Average

Agilent

Agilent

Agilent





HERMON LABORATORIES

Test specification: Section 15.249(a)(d)/RSS-310, section 3.10, Field strength of emissions		
Test procedure:	ANSI C63.10 sections 6.5, 6.6	
Test mode:	Compliance	Verdict: PASS
Date(s):	10-Aug-17 - 22-Aug-17	
Temperature: 24.3 °C	Relative Humidity: 39 %	Air Pressure: 1011 hPa
Remarks: EUT with 42.4 dBi antenna gain		Power: 48 VDC

Plot 7.1.31 Radiated emission measurements at the fundamental frequency

TEST SITE:

OATS

TEST DISTANCE:

3 m

ANTENNA POLARIZATION:

Horizontal

EUT POSITION:

Typical (Vertical)

EMISSION BANDWIDTH:

50 MHz

MODULATION:



2048QAM

CARRIER FREQUENCY:

Low

DETECTOR: Peak

DETECTOR: Average





CARRIER FREQUENCY:

Mid

DETECTOR: Peak

DETECTOR: Average





HERMON LABORATORIES

Test specification: Section 15.249(a)(d)/RSS-310, section 3.10, Field strength of emissions		
Test procedure:	ANSI C63.10 sections 6.5, 6.6	
Test mode:	Compliance	Verdict: PASS
Date(s):	10-Aug-17 - 22-Aug-17	
Temperature: 24.3 °C	Relative Humidity: 39 %	Air Pressure: 1011 hPa
Remarks: EUT with 42.4 dBi antenna gain		Power: 48 VDC

Plot 7.1.32 Radiated emission measurements at the fundamental frequency

TEST SITE:

OATS

TEST DISTANCE:

3 m

ANTENNA POLARIZATION:

Horizontal

EUT POSITION:

Typical (Vertical)

EMISSION BANDWIDTH:

50 MHz

MODULATION:

2048QAM

CARRIER FREQUENCY:

Mid



DETECTOR: Peak

DETECTOR: Average

Agilent

Agilent

Agilent



CARRIER FREQUENCY:

High



DETECTOR: Peak

DETECTOR: Average

Agilent

Agilent

Agilent





HERMON LABORATORIES

Test specification: Section 15.249(a)(d)/RSS-310, section 3.10, Field strength of emissions		
Test procedure:	ANSI C63.10 sections 6.5, 6.6	
Test mode:	Compliance	Verdict: PASS
Date(s):	10-Aug-17 - 22-Aug-17	
Temperature: 24.3 °C	Relative Humidity: 39 %	Air Pressure: 1011 hPa
Remarks: EUT with 42.4 dBi antenna gain		Power: 48 VDC

Plot 7.1.33 Radiated emission measurements at the fundamental frequency

TEST SITE:

OATS

TEST DISTANCE:

3 m

ANTENNA POLARIZATION:

Vertical

EUT POSITION:

Typical (Vertical)

EMISSION BANDWIDTH:

60 MHz

MODULATION:

QPSK

CARRIER FREQUENCY:



Low

DETECTOR: Peak

DETECTOR: Average

* Agilent

* Agilent



CARRIER FREQUENCY:



Mid

DETECTOR: Peak

DETECTOR: Average

* Agilent

* Agilent





HERMON LABORATORIES

Test specification: Section 15.249(a)(d)/RSS-310, section 3.10, Field strength of emissions			
Test procedure: ANSI C63.10 sections 6.5, 6.6			
Test mode: Compliance			Verdict: PASS
Date(s): 10-Aug-17 - 22-Aug-17			
Temperature: 24.3 °C	Relative Humidity: 39 %	Air Pressure: 1011 hPa	Power: 48 VDC
Remarks: EUT with 42.4 dBi antenna gain			

Plot 7.1.34 Radiated emission measurements at the fundamental frequency

TEST SITE:

OATS

TEST DISTANCE:

3 m

ANTENNA POLARIZATION:

Vertical

EUT POSITION:

Typical (Vertical)

EMISSION BANDWIDTH:

60 MHz

MODULATION:

QPSK


CARRIER FREQUENCY:

Mid

DETECTOR: Peak


DETECTOR: Average

Agilent



R T

Agilent



R T

Mkr1 24.193 95 GHz
103.544 dBµV/m

Center 24.200 00 GHz

Span 100 MHz

#Res BW 1 MHz

VBW 3 MHz

Sweep 20 ms (2001 pts)

Center 24.200 00 GHz

Span 100 MHz

#Res BW 1 MHz

VBW 3 MHz

Sweep 20 ms (2001 pts)

Center 24.200 00 GHz

Span 100 MHz

#Res BW 1 MHz

VBW 3 MHz

Sweep 20 ms (2001 pts)

Center 24.200 00 GHz

Span 100 MHz

#Res BW 1 MHz

VBW 3 MHz

Sweep 20 ms (2001 pts)

Center 24.200 00 GHz

Span 100 MHz

#Res BW 1 MHz

VBW 3 MHz

Sweep 20 ms (2001 pts)

Center 24.200 00 GHz

Span 100 MHz

#Res BW 1 MHz

VBW 3 MHz

Sweep 20 ms (2001 pts)

Center 24.200 00 GHz

Span 100 MHz

#Res BW 1 MHz

VBW 3 MHz

Sweep 20 ms (2001 pts)

Center 24.200 00 GHz

Span 100 MHz

#Res BW 1 MHz

VBW 3 MHz

Sweep 20 ms (2001 pts)

Center 24.200 00 GHz

Span 100 MHz

#Res BW 1 MHz

VBW 3 MHz

Sweep 20 ms (2001 pts)

Center 24.200 00 GHz

Span 100 MHz

#Res BW 1 MHz

VBW 3 MHz

Sweep 20 ms (2001 pts)

Center 24.200 00 GHz

Span 100 MHz

#Res BW 1 MHz

VBW 3 MHz

Sweep 20 ms (2001 pts)

Center 24.200 00 GHz

Span 100 MHz

#Res BW 1 MHz

VBW 3 MHz

Sweep 20 ms (2001 pts)

Center 24.200 00 GHz

Span 100 MHz

#Res BW 1 MHz

VBW 3 MHz

Sweep 20 ms (2001 pts)

Center 24.200 00 GHz

Span 100 MHz

#Res BW 1 MHz

VBW 3 MHz

Sweep 20 ms (2001 pts)

Center 24.200 00 GHz

Span 100 MHz

#Res BW 1 MHz

VBW 3 MHz

Sweep 20 ms (2001 pts)

Center 24.200 00 GHz

Span 100 MHz

#Res BW 1 MHz

VBW 3 MHz

Sweep 20 ms (2001 pts)

Center 24.200 00 GHz

Span 100 MHz

#Res BW 1 MHz

VBW 3 MHz

Sweep 20 ms (2001 pts)

Center 24.200 00 GHz

Span 100 MHz

#Res BW 1 MHz

VBW 3 MHz

Sweep 20 ms (2001 pts)

Center 24.200 00 GHz

Span 100 MHz

#Res BW 1 MHz

VBW 3 MHz

Sweep 20 ms (2001 pts)

Center 24.200 00 GHz

Span 100 MHz

#Res BW 1 MHz

VBW 3 MHz

Sweep 20 ms (2001 pts)

Center 24.200 00 GHz

Span 100 MHz

#Res BW 1 MHz

VBW 3 MHz

Sweep 20 ms (2001 pts)

Center 24.200 00 GHz

Span 100 MHz

#Res BW 1 MHz

VBW 3 MHz

Sweep 20 ms (2001 pts)

Center 24.200 00 GHz

Span 100 MHz

#Res BW 1 MHz

VBW 3 MHz

Sweep 20 ms (2001 pts)

Center 24.200 00 GHz

Span 100 MHz

#Res BW 1 MHz

VBW 3 MHz

Sweep 20 ms (2001 pts)

Center 24.200 00 GHz

Span 100 MHz

#Res BW 1 MHz

VBW 3 MHz

Sweep 20 ms (2001 pts)

Center 24.200 00 GHz

Span 100 MHz

#Res BW 1 MHz

VBW 3 MHz

Sweep 20 ms (2001 pts)

Center 24.200 00 GHz

Span 100 MHz

#Res BW 1 MHz

VBW 3 MHz

Sweep 20 ms (2001 pts)

Center 24.200 00 GHz

Span 100 MHz

#Res BW 1 MHz

VBW 3 MHz

Sweep 20 ms (2001 pts)

Center 24.200 00 GHz

Span 100 MHz

#Res BW 1 MHz

VBW 3 MHz

Sweep 20 ms (2001 pts)

Center 24.200 00 GHz

Span 100 MHz

#Res BW 1 MHz

VBW 3 MHz

Sweep 20 ms (2001 pts)

Center 24.200 00 GHz

Span 100 MHz

#Res BW 1 MHz

VBW 3 MHz

Sweep 20 ms (2001 pts)

Center 24.200 00 GHz

Span 100 MHz

#Res BW 1 MHz

VBW 3 MHz

Sweep 20 ms (2001 pts)

Center 24.200 00 GHz

Span 100 MHz

#Res BW 1 MHz

VBW 3 MHz

Sweep 20 ms (2001 pts)

Center 24.200 00 GHz

Span 100 MHz

#Res BW 1 MHz

VBW 3 MHz

Sweep 20 ms (2001 pts)

Center 24.200 00 GHz

Span 100 MHz

#Res BW 1 MHz

VBW 3 MHz

Sweep 20 ms (2001 pts)

Center 24.200 00 GHz

Span 100 MHz

#Res BW 1 MHz

VBW 3 MHz

Sweep 20 ms (2001 pts)

Center 24.200 00 GHz

Span 100 MHz

#Res BW 1 MHz

VBW 3 MHz

Sweep 20 ms (2001 pts)

Center 24.200 00 GHz

Span 100 MHz

#Res BW 1 MHz

VBW 3 MHz

Sweep 20 ms (2001 pts)

Center 24.200 00 GHz

Span 100 MHz

#Res BW 1 MHz

VBW 3 MHz

Sweep 20 ms (2001 pts)

Center 24.200 00 GHz

Span 100 MHz

#Res BW 1 MHz

VBW 3 MHz

Sweep 20 ms (2001 pts)

Center 24.200 00 GHz

Span 100 MHz

#Res BW 1 MHz

VBW 3 MHz

Sweep 20 ms (2001 pts)

Center 24.200 00 GHz

Span 100 MHz

#Res BW 1 MHz

VBW 3 MHz

Sweep 20 ms (2001 pts)

Center 24.200 00 GHz

Span 100 MHz

#Res BW 1 MHz

VBW 3 MHz

Sweep 20 ms (2001 pts)

Center 24.200 00 GHz

Span 100 MHz

#Res BW 1 MHz

VBW 3 MHz

Sweep 20 ms (2001 pts)

Center 24.200 00 GHz

Span 100 MHz

#Res BW 1 MHz

VBW 3 MHz

Sweep 20 ms (2001 pts)

Center 24.200 00 GHz

Span 100 MHz

#Res BW 1 MHz

VBW 3 MHz

Sweep 20 ms (2001 pts)

Center 24.200 00 GHz

Span 100 MHz

#Res BW 1 MHz

VBW 3 MHz

Sweep 20 ms (2001 pts)

Center 24.200 00 GHz

Span 100 MHz

#Res BW 1 MHz

VBW 3 MHz

Sweep 20 ms (2001 pts)

Center 24.200 00 GHz

Span 100 MHz

#Res BW 1 MHz

VBW 3 MHz

Sweep 20 ms (2001 pts)

Center 24.200 00 GHz



HERMON LABORATORIES

Test specification: Section 15.249(a)(d)/RSS-310, section 3.10, Field strength of emissions		
Test procedure:	ANSI C63.10 sections 6.5, 6.6	
Test mode:	Compliance	Verdict: PASS
Date(s):	10-Aug-17 - 22-Aug-17	
Temperature: 24.3 °C	Relative Humidity: 39 %	Air Pressure: 1011 hPa
Remarks: EUT with 42.4 dBi antenna gain		Power: 48 VDC

Plot 7.1.35 Radiated emission measurements at the fundamental frequency

TEST SITE:

OATS

TEST DISTANCE:

3 m

ANTENNA POLARIZATION:

Horizontal

EUT POSITION:

Typical (Vertical)

EMISSION BANDWIDTH:

60 MHz

MODULATION:



QPSK

CARRIER FREQUENCY:

Low

DETECTOR: Peak

DETECTOR: Average





CARRIER FREQUENCY:

Mid

DETECTOR: Peak

DETECTOR: Average





HERMON LABORATORIES

Test specification: Section 15.249(a)(d)/RSS-310, section 3.10, Field strength of emissions		
Test procedure:	ANSI C63.10 sections 6.5, 6.6	
Test mode:	Compliance	Verdict: PASS
Date(s):	10-Aug-17 - 22-Aug-17	
Temperature: 24.3 °C	Relative Humidity: 39 %	Air Pressure: 1011 hPa
Remarks: EUT with 42.4 dBi antenna gain		Power: 48 VDC

Plot 7.1.36 Radiated emission measurements at the fundamental frequency

TEST SITE:

OATS

TEST DISTANCE:

3 m

ANTENNA POLARIZATION:

Horizontal

EUT POSITION:

Typical (Vertical)

EMISSION BANDWIDTH:

60 MHz

MODULATION:


QPSK

CARRIER FREQUENCY:

Mid

DETECTOR: Peak

DETECTOR: Average




CARRIER FREQUENCY:

High

DETECTOR: Peak

DETECTOR: Average





HERMON LABORATORIES

Test specification: Section 15.249(a)(d)/RSS-310, section 3.10, Field strength of emissions		
Test procedure:	ANSI C63.10 sections 6.5, 6.6	
Test mode:	Compliance	Verdict: PASS
Date(s):	10-Aug-17 - 22-Aug-17	
Temperature: 24.3 °C	Relative Humidity: 39 %	Air Pressure: 1011 hPa
Remarks: EUT with 42.4 dBi antenna gain		Power: 48 VDC

Plot 7.1.37 Radiated emission measurements at the fundamental frequency

TEST SITE:

OATS

TEST DISTANCE:

3 m

ANTENNA POLARIZATION:

Vertical

EUT POSITION:

Typical (Vertical)

EMISSION BANDWIDTH:

60 MHz

MODULATION:


2048QAM

CARRIER FREQUENCY:

Low

DETECTOR: Peak

DETECTOR: Average




CARRIER FREQUENCY:

Mid

DETECTOR: Peak

DETECTOR: Average





HERMON LABORATORIES

Test specification: Section 15.249(a)(d)/RSS-310, section 3.10, Field strength of emissions		
Test procedure:	ANSI C63.10 sections 6.5, 6.6	
Test mode:	Compliance	
Date(s):	10-Aug-17 - 22-Aug-17	
Temperature: 24.3 °C	Relative Humidity: 39 %	Air Pressure: 1011 hPa
Remarks: EUT with 42.4 dBi antenna gain		Power: 48 VDC

Plot 7.1.38 Radiated emission measurements at the fundamental frequency

TEST SITE:

OATS

TEST DISTANCE:

3 m

ANTENNA POLARIZATION:

Vertical

EUT POSITION:

Typical (Vertical)

EMISSION BANDWIDTH:

60 MHz

MODULATION:

2048QAM



CARRIER FREQUENCY:

Mid

DETECTOR: Peak

DETECTOR: Average

* Agilent





CARRIER FREQUENCY:

High

DETECTOR: Peak

DETECTOR: Average

* Agilent





HERMON LABORATORIES

Test specification: Section 15.249(a)(d)/RSS-310, section 3.10, Field strength of emissions		
Test procedure:	ANSI C63.10 sections 6.5, 6.6	
Test mode:	Compliance	Verdict: PASS
Date(s):	10-Aug-17 - 22-Aug-17	
Temperature: 24.3 °C	Relative Humidity: 39 %	Air Pressure: 1011 hPa
Remarks: EUT with 42.4 dBi antenna gain		Power: 48 VDC

Plot 7.1.39 Radiated emission measurements at the fundamental frequency

TEST SITE:

OATS

TEST DISTANCE:

3 m

ANTENNA POLARIZATION:

Horizontal

EUT POSITION:

Typical (Vertical)

EMISSION BANDWIDTH:

60 MHz

MODULATION:

2048QAM


CARRIER FREQUENCY:

Low


DETECTOR: Peak

DETECTOR: Average

* Agilent



* Agilent




CARRIER FREQUENCY:

Mid


DETECTOR: Peak

DETECTOR: Average

* Agilent



* Agilent





HERMON LABORATORIES

Test specification: Section 15.249(a)(d)/RSS-310, section 3.10, Field strength of emissions		
Test procedure:	ANSI C63.10 sections 6.5, 6.6	
Test mode:	Compliance	Verdict: PASS
Date(s):	10-Aug-17 - 22-Aug-17	
Temperature: 24.3 °C	Relative Humidity: 39 %	Air Pressure: 1011 hPa
Remarks: EUT with 42.4 dBi antenna gain		Power: 48 VDC

Plot 7.1.40 Radiated emission measurements at the fundamental frequency

TEST SITE:

OATS

TEST DISTANCE:

3 m

ANTENNA POLARIZATION:

Horizontal

EUT POSITION:

Typical (Vertical)

EMISSION BANDWIDTH:

60 MHz

MODULATION:


2048QAM

CARRIER FREQUENCY:

Mid

DETECTOR: Peak

DETECTOR: Average



CARRIER FREQUENCY:

High

DETECTOR: Peak

DETECTOR: Average

