



Shenzhen Certification Technologh Service Co., Ltd
2F, Building B, East Area of Nanchang Second Industrial Zone,
Gushu 2nd Road, Bao'an District, Shenzhen 518126, P.R. China

TEST REPORT

FCC ID: O26-H479

Applicant **Microboards Technology, LLC (doing business as Afinia)**
Address **8150 Mallory Court, Chanhassen, MN 55317, U.S.A.**

Equipment under Test (EUT):

Name : Afinia 3D Printer

Model : H479

Standards : FCC PART 15, Subpart B Class B 2011

Report No. : STE120605696

Date of Test : June 7-June 9, 2012

Date of Issue : June 11, 2012

Test Result :	PASS *
----------------------	---------------

* In the configuration tested, the EUT complied with the standards specified above

Authorized Signature

A handwritten signature in black ink that reads 'Mark Zhu'.

(Mark Zhu)
General Manager

The manufacture should ensure that all the products in series production are in conformity with the product sample detailed in this report.

If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of Shenzhen Certification Technology Service Co., Ltd. Or test done by Shenzhen Certification Technology Service Co., Ltd. Approvals in connection with, distribution or use of the product described in this report must be approved by Shenzhen Certification Technology Service Co., Ltd. Approvals in writing.

TABLE OF CONTENTS

<u>Description</u>	<u>Page</u>
Test Report Declaration	3
1. Summary of standards and results	4
1.1. Description of Standards and Results.....	4
2. GENERAL INFORMATION	5
2.1. Description of Device (EUT)	5
2.2. Tested Supporting System Details	6
2.3. Block Diagram of connection between EUT and simulators	6
2.4. Test Facility	7
2.5. Measurement Uncertainty	7
3. POWER LINE CONDUCTED Emission test	8
3.1. Test Equipment.....	8
3.2. Block Diagram of Test Setup	8
3.3. Power Line Conducted Emission Test Limits	8
3.4. Configuration of EUT on Test.....	9
3.5. Operating Condition of EUT	9
3.6. Test Procedure	9
3.7. Conducted Disturbance at Mains Terminals Test Results.....	9
4. Radiated emission Test	14
4.1. Test Equipment.....	14
4.2. Block Diagram of Test Setup	14
4.3. Radiated Emission Limit	15
4.4. EUT Configuration on Test	15
4.5. Operating Condition of EUT	16
4.6. Test Procedure	16
4.7. Radiated Disturbance Test Results.....	16
5. Photograph	21
5.1. Photos of Power Line Conducted Emission Test	21
5.2. Photos of Radiated Emission Test (In Anechoic Chamber).....	22
6. Photos of the EUT	23

TEST REPORT VERIFICATION

Applicant : Microboards Technology, LLC (doing business as Afinia)

Manufacturer : Delta Micro Factory Corporation

EUT Description : Afinia 3D Printer

(A) Model No. : H479

(B) Trademark : N/A

(C) Serial No. : N/A

(D) Power Supply : DC 19V From Adapter

(E) Test Voltage : DC 19V From Adapter With AC
120V/60Hz

Measurement Standard Used:

FCC Rules and Regulations Part 15 Subpart B Class B 2011

The device described above is tested by Shenzhen Certification Technology Service Co., Ltd. to determine the maximum emission levels emanating from the device. The maximum emission levels are compared to the FCC Part 15 Subpart B Class B limits both conducted and radiated emissions. The test results are contained in this test report and Shenzhen Certification Technology Service Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these tests.

After the test, our opinion is that EUT compliance with the requirement of the above standards.

This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Shenzhen Certification Technology Service Co., Ltd.

1. SUMMARY OF STANDARDS AND RESULTS

1.1. Description of Standards and Results

The EUT have been tested according to the applicable standards as referenced below.

EMISSION				
Description of Test Item	Standard	Limits	Results	
Power Line Conducted Emission Test	FCC Part 15: 2011 ANSI C63.4: 2003	Class B	PASS	Minimargin with respect to the limits: -5.62 dB at 0.307MHz
Radiated Emission Test	FCC Part 15: 2011 ANSI C63.4: 2003	Class B	PASS	Minimargin with respect to the limits: -3.27 dB at 107.60 MHz

2. GENERAL INFORMATION

2.1. Description of Device (EUT)

Description : Afinia 3D Printer

Model Number : H479

Trademark : N/A

Power Supply : DC 19V From Adapter
Adapter : Manufacturer: HP
Model: series HSTNN-LA03

Highest frequency : Crystal frequency: 8MHz

Applicant : Microboards Technology, LLC (doing business as Afinia)
8150 Mallory Court, Chanhassen, MN 55317, U.S.A.

Manufacturer : Rm 1008, Tower A, Third Property Building, No.1 Shuguang Xili,
Chaoyang District, Beijing, 100028, P.R.China
Rm 1008, Tower A, Third Property Building, No.1 Shuguang Xili,


Date of Test : June 7-June 9, 2012

Sample Type : Series production

2.2. Tested Supporting System Details

No.	Description	Manufacturer	Model	Serial Number
1.	Personal Computer	ACER	ASPIRE M1830	PTSF90C00305005CAC3000
2.	Monitor	ACER	G205HV	SNID:10306738385
3.	USB Keyboard	ACER	SK-9625	KBUSB1580500037E0100
4.	USB Mouse	ACER	MS.11200.014	M-UAY-ACR2
5.	Printer	HP	HP1020	CNCJ410726

2.3. Block Diagram of connection between EUT and simulators



※ EUT: Afinia 3D Printer

2.4. Test Facility

JAN 13, 2012 File on Federal Communication Commission
Registration Number: 197647

October 11, 2011 Certificated by IC
Registration Number: 8528B

2.5. Measurement Uncertainty

(95% confidence levels, k=2)


Test Item	Uncertainty
Uncertainty for Conduction emission test	2.50dB
Uncertainty for Radiation Emission test	3.04 dB (Distance: 3m Polarize: V)
	3.02 dB (Distance: 3m Polarize: H)
Uncertainty for test site temperature and humidity	0.6°C
	3%

3. POWER LINE CONDUCTED EMISSION TEST

3.1. Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Test Receiver	Rohde&Schwarz	ESCI	1166.5950K03 -1011	Oct. 17, 11	1 Year
2.	L.I.S.N.	Schwarzbeck	NSLK8126	8126466	Oct. 17, 11	1 Year
3.	L.I.S.N.-2	Kyoritsu	KNW-407	8-1628-5	Oct. 17, 11	1 Year
4.	Terminator	Hubersuhner	50Ω	No. 1	Oct. 17, 11	1 Year
5.	RF Cable	Schwarzbeck	9111505/20 0	5995-12-161-6 890#	Oct. 17, 11	1 Year
6.	Coaxial Switch	Schwarzbeck	CX-210	N/A	Oct. 17, 11	1 Year
7.	Pulse Limiter	Schwarzbeck	VTSD9516 F	9618	Oct. 17, 11	1 Year

3.2. Block Diagram of Test Setup



3.3. Power Line Conducted Emission Test Limits

Frequency	Maximum RF Line Voltage	
	Quasi-Peak Level dB(µV)	Average Level dB(µV)
150kHz ~ 500kHz	66 ~ 56*	56 ~ 46*
500kHz ~ 5MHz	56	46
5MHz ~ 30MHz	60	50

Notes: 1. Emission level=Read level+ LISN factor+Preamp factor+ Cable loss

2* Decreasing linearly with logarithm of frequency.

3. The lower limit shall apply at the transition frequencies.

3.4. Configuration of EUT on Test

The following equipment are installed on Power Line Conducted Emission Test to meet the commission requirement and operating regulations in a manner which tends to maximize its emission characteristics in a normal application.

Support Equipments : As Tested Supporting System Detail, in Section 2.2.

3.5. Operating Condition of EUT

- 3.5.1. Setup the EUT and simulator as shown as Section 3.2.
- 3.5.2. Turn on the power of all equipment.
- 3.5.3. Let the EUT work in test mode (Link PC) and measure it.

3.6. Test Procedure

The EUT was placed on a non-metallic table, 80cm above the ground plane. The EUT Power connected to the power mains through a line impedance stabilization network (L.I.S.N. 1#). The other peripheral devices power cord connected to the power mains through a line impedance stabilization network (L.I.S.N. #2), this provided a 50-ohm coupling impedance for the EUT (Please refer to the block diagram of the test setup and photographs). Both sides of power line were checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipments and all of the interface cables were changed according to ANSI C63.4-2003 on conducted Emission test.

The bandwidth of test receiver (R&S TEST RECEIVER ESCI) is set at 10kHz.

The frequency range from 150KHz to 30MHz is checked. The test result are reported on Section 3.7.

3.7. Conducted Disturbance at Mains Terminals Test Results


PASS. (All emissions not reported below are too low against the prescribed limits.)

The EUT with the following test mode was tested and read Q.P values and average values, the test results are listed in next pages.

Temperature: 29.5°C Humidity: 55%

The details of test mode is as follows :

No.	Test Mode
1.	Transmission data
2.	Print data




Condition : FCC PART 15 B QP
 EUT : Afinia 3D Printer
 Model No. : H479
 Test Mode : Copy Data
 Power : AC 120V/60Hz
 Test Engineer: Store
 Remark :

POL: LINE

Item	Freq	Read	LISN	Preamp	Cable	Level	Limit	Margin	Remark
			Factor	Factor	Lose				
	MHz	dBuV	dB	dB	dB	dBuV	dBuV	dBuV	
1	0.150	34.93	0.03	-9.72	0.10	44.78	66.00	-21.22	QP
2	0.150	16.31	0.03	-9.72	0.10	26.16	56.00	-29.84	Average
3	0.259	26.90	0.03	-9.72	0.10	36.75	61.47	-24.72	QP
4	0.259	13.07	0.03	-9.72	0.10	22.92	51.47	-28.55	Average
5	0.461	21.75	0.03	-9.72	0.10	31.60	56.67	-25.07	QP
6	0.461	8.45	0.03	-9.72	0.10	18.30	46.67	-28.37	Average
7	1.503	23.47	0.05	-9.71	0.10	33.33	56.00	-22.67	QP
8	1.503	9.78	0.05	-9.71	0.10	19.64	46.00	-26.36	Average
9	4.952	27.24	0.10	-9.68	0.12	37.14	56.00	-18.86	QP
10	4.952	10.44	0.10	-9.68	0.12	20.34	46.00	-25.66	Average
11	18.820	28.60	0.31	-9.46	0.33	38.70	60.00	-21.30	QP
12	18.820	12.98	0.31	-9.46	0.33	23.08	50.00	-26.92	Average



Shenzhen Certification Technology Service Co., Ltd.
2F, Building B, East Area of Nanchang Second Industrial Zone,
Gushu 2nd Road, Bao'an District, Shenzhen 518126, P.R. China
Tel: 4006786199 Fax: +86-755-26736857
Website: <http://www.cessz.com> Email: Service@cessz.com




Condition : FCC PART 15 B QP
 EUT : Afinia 3D Printer
 Model No. : H479
 Test Mode : Copy Data
 Power : AC 120V/60Hz
 Test Engineer: Store
 Remark :

Item	Freq	Read	LISN	Preamp	Cable	Level	Limit	Margin	Remark
	MHz	dBuV	Factor	Factor	dB	dB	dBuV	dBuV	
1	0.150	34.84	0.03	-9.72	0.10	44.69	66.00	-21.31	QP
2	0.150	13.39	0.03	-9.72	0.10	23.24	56.00	-32.76	Average
3	0.192	31.63	0.03	-9.72	0.10	41.48	63.93	-22.45	QP
4	0.192	13.30	0.03	-9.72	0.10	23.15	53.93	-30.78	Average
5	1.628	23.57	0.05	-9.71	0.10	33.43	56.00	-22.57	QP
6	1.628	9.77	0.05	-9.71	0.10	19.63	46.00	-26.37	Average
7	4.549	29.12	0.09	-9.68	0.12	39.01	56.00	-16.99	QP
8	4.549	13.44	0.09	-9.68	0.12	23.33	46.00	-22.67	Average
9	14.828	30.98	0.24	-9.39	0.23	40.84	60.00	-19.16	QP
10	14.828	15.24	0.24	-9.39	0.23	25.10	50.00	-24.90	Average
11	18.820	28.79	0.30	-9.46	0.33	38.88	60.00	-21.12	QP
12	18.820	12.80	0.30	-9.46	0.33	22.89	50.00	-27.11	Average




Shenzhen Certification Technology Service Co., Ltd.
2F, Building B, East Area of Nanchang Second Industrial Zone,
Gushu 2nd Road, Bao'an District, Shenzhen 518126, P.R. China
Tel: 4006786199 Fax: +86-755-26736857
Website: <http://www.cessz.com> Email: Service@cessz.com



Condition : FCC PART 15 B QP POL: NEUTRAL
 EUT : Afinia 3D Printerr
 Model No. : H479
 Test Mode : Print
 Power : AC 120V/60Hz
 Test Engineer: Store
 Remark :

Item	Freq	Read	LISN	Preamp	Cable	Level	Limit	Margin	Remark
	MHz	dBuV	Factor	Factor	dB	dB	dBuV	dBuV	
1	0.307	44.59	0.03	-9.72	0.10	54.44	60.06	-5.62	QP
2	0.307	20.85	0.03	-9.72	0.10	30.70	50.06	-19.36	Average
3	0.611	39.94	0.03	-9.72	0.10	49.79	56.00	-6.21	QP
4	0.611	25.45	0.03	-9.72	0.10	35.30	46.00	-10.70	Average
5	0.871	36.39	0.04	-9.71	0.10	46.24	56.00	-9.76	QP
6	0.871	20.84	0.04	-9.71	0.10	30.69	46.00	-15.31	Average
7	1.236	36.29	0.04	-9.71	0.10	46.14	56.00	-9.86	QP
8	1.236	19.89	0.04	-9.71	0.10	29.74	46.00	-16.26	Average
9	17.755	39.69	0.29	-9.44	0.31	49.73	60.00	-10.27	QP
10	17.755	22.89	0.29	-9.44	0.31	32.93	50.00	-17.07	Average
11	26.139	38.12	0.46	-9.65	0.52	48.75	60.00	-11.25	QP
12	26.139	24.02	0.46	-9.65	0.52	34.65	50.00	-15.35	Average



Condition : FCC PART 15 B QP
 EUT : Afinia 3D Printer
 Model No. : H479
 Test Mode : Print
 Power : AC 120V/60Hz
 Test Engineer: Store
 Remark :

Item	Freq	Read	LISN	Preamp	Cable	Level	Limit	Margin	Remark
	MHz	dBuV	Factor	Factor	dB	dB	dBuV	dBuV	
1	0.307	44.59	0.03	-9.72	0.10	54.44	60.06	-5.62	QP
2	0.307	18.85	0.03	-9.72	0.10	28.70	50.06	-21.36	Average
3	0.611	39.94	0.03	-9.72	0.10	49.79	56.00	-6.21	QP
4	0.611	20.50	0.03	-9.72	0.10	30.35	46.00	-15.65	Average
5	0.871	36.39	0.04	-9.71	0.10	46.24	56.00	-9.76	QP
6	0.871	20.84	0.04	-9.71	0.10	30.69	46.00	-15.31	Average
7	1.236	36.29	0.04	-9.71	0.10	46.14	56.00	-9.86	QP
8	1.236	20.88	0.04	-9.71	0.10	30.73	46.00	-15.27	Average
9	2.201	32.16	0.06	-9.70	0.10	42.02	56.00	-13.98	QP
10	2.201	18.56	0.06	-9.70	0.10	28.42	46.00	-17.58	Average
11	17.755	39.69	0.30	-9.44	0.31	49.74	60.00	-10.26	QP
12	17.755	22.09	0.30	-9.44	0.31	32.14	50.00	-17.86	Average

4. RADIATED EMISSION TEST

4.1. Test Equipment


Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1	Test Receiver	Rohde&Schwarz	ESCI	1166.5950K06-1012	Oct. 17, 11	1 Year
2	Amplifier	Schwarzbeck	BBV9743	9743-019	Oct. 17, 11	1 Year
3	Bilog Antenna	Schwarzbeck	VULB 9168	VULB9168-438	Feb. 10, 12	1 Year
4	RF Cable	Schwarzbeck	AK9515E	95891-2m	Oct. 17, 11	1 Year
5	RF Cable	Schwarzbeck	AK9515E	95891-11m	Oct. 17, 11	1 Year
6	RF Cable	Schwarzbeck	AK9515E	95891-0.5m	Oct. 17, 11	

For frequency range 1GHz~5GHz (At Semi Anechoic Chamber)


Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1	Spectrum Analyzer	Agilent	E4446A	US44300459	Oct. 17, 11	1 Year
2	Horn Antenna	EMCO	BBV9743	9743-019	Feb. 10, 12	1 Year
3	Amplifier	Schwarzbeck	SCHWARZBEC K	N/A	Oct. 17, 11	1 Year
4	RF Cable	Hubersuhner	SUCOFLEX102	28620/2	Oct. 17, 11	1 Year
5	RF Cable	Hubersuhner	SUCOFLEX102	271471/4	Oct. 17, 11	1 Year
6	RF Cable	Hubersuhner	SUCOFLEX102	29086/2	Oct. 17, 11	1 Year

4.2. Block Diagram of Test Setup

4.2.1. In Semi Anechoic Chamber (3m) Test Setup Diagram for 30MHz~1000MHz



4.2.2. In Semi Anechoic Chamber (3m) Test Setup Diagram for 1-5GHz



4.3. Radiated Emission Limit

Frequency MHz	Distance (Meters)	Field Strengths Limits dB(μ V)/m
30 ~ 88	3	40.0
88 ~ 216	3	43.5
216 ~ 960	3	46.0
960 ~ 1000	3	54.0
1000 ~ 5000	3	74(Peak) 54(Average)

Remark: (1) Emission level = Read level + Antenna Factor + Preamp Factor + Cable Loss
 (2) The smaller limit shall apply at the cross point between two frequency bands.
 (3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.

4.4. EUT Configuration on Test

The following equipment are installed on Radiated Emission Test to meet the commission requirements and operating regulations in a manner that tends to maximize its emission characteristics in normal application.

4.4.1. Support Equipments : As Tested Supporting System Detail, in Section 2.2.

4.5. Operating Condition of EUT

- 4.5.1. Setup the EUT as shown in Section 4.2.
- 4.5.2. Turn on the power of all equipment.
- 4.5.3. Let the EUT work in test mode (Link PC) and test it.

4.6. Test Procedure

The EUT was placed on a non-metallic table, 80 cm above the ground plane inside a semi-anechoic chamber. An antenna was located 3m from the EUT on an adjustable mast. A pre-scan was first performed in order to find prominent radiated emissions. For final emissions measurements at each frequency of interest, the EUT were rotated and the antenna height was varied between 1m and 4m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. In order to find the maximum emission, the relative positions of equipments and all of the interface cables were changed according to ANSI C63.4-2003 on Radiated Emission test.

The bandwidth setting on the test receiver (ROHDE&SCHWARZ TEST RECEIVER ESCI) is 120 kHz.

The resolution bandwidth of the Agilent Spectrum Analyzer E4446A was set at 1MHz. (For above 1GHz)

The frequency range from 30MHz to 1000MHz was pre-scanned with a peak detector and all final readings of measurement from Test Receiver are Quasi-Peak values.

The frequency range from 1GHz to 5GHz was checked with peak and average detector, measurement distance is 3m in 3m chamber.

Finally, selected operating situations at Anechoic Chamber measurement, all the test results are listed in section 4.7.

4.7. Radiated Disturbance Test Results

PASS. (All emissions not reported below are too low against the prescribed limits.)

For frequency range 30MHz~1000MHz

The EUT with the following test mode was tested and read Q.P values, all the test results listed in next pages.

Temperature: 24°C Humidity: 56%

The details of test mode is as follows :


NO.	Test Mode
1.	Transmission data
2.	Print data

For frequency range above 1GHz

The highest frequency of the internal sources of the EUT is Crystal frequency is 8 MHz less than 108 MHz, the measurement shall only be made up to 1 GHz. So the frequency above 1GHz radiation test not applicable.



Shenzhen Certification Technology Service Co., Ltd.
2F, Building B, East Area of Nanchang Second Industrial Zone,
Gushu 2nd Road, Bao'an District, Shenzhen 518126, P.R. China
Tel: 4006786199 FAX: +86-755-26736857
Website: <http://www.cessz.com> Email: Service@cessz.com




Condition : FCC PART 15 B 3m POL: VERTICAL
 EUT : Afinia 3D Printer
 Model No. : H479
 Test Mode : Copy Data
 Power : AC 120V/60Hz
 Test Engineer : Store
 Remark :

Item	Freq	Read Level	Antenna Factor	Preamp Factor	Cable Lose	Level	Limit	Margin	Remark
	MHz	dBuV	dB	dB	dB	dBuV	dBuV	dBuV	
1	109.54	48.85	11.13	26.86	0.92	34.04	43.50	-9.46	QP
2	198.78	49.98	10.01	26.97	1.39	34.41	43.50	-9.09	QP
3	431.58	40.99	15.53	27.46	2.63	31.69	46.00	-14.31	QP
4	485.90	44.17	16.33	27.58	2.92	35.84	46.00	-10.16	QP
5	597.45	35.13	18.28	27.82	3.19	28.78	46.00	-17.22	QP
6	771.08	35.12	20.50	27.67	3.54	31.49	46.00	-14.51	QP



Shenzhen Certification Technology Service Co., Ltd.
2F, Building B, East Area of Nanchang Second Industrial Zone,
Gushu 2nd Road, Bao'an District, Shenzhen 518126, P.R. China
Tel: 4006786199 FAX: +86-755-26736857
Website: <http://www.cessz.com> Email: Service@cessz.com




Condition : FCC PART 15 B 3m POL: HORIZONTAL
EUT : Afinia 3D Printer
Model No. : H479
Test Mode : Copy Data
Power : AC 120V/60Hz
Test Engineer : Store
Remark :

Item	Freq	Read Level	Antenna Factor	Preamp Factor	Cable Loss	Level	Limit	Margin	Remark
	MHz	dBuV	dB	dB	dB	dBuV	dBuV	dBuV	
1	99.84	39.53	10.15	26.84	0.86	23.70	43.50	-19.80	QP
2	198.78	48.23	10.01	26.97	1.39	32.66	43.50	-10.84	QP
3	369.50	43.36	14.24	27.33	2.30	32.57	46.00	-13.43	QP
4	485.90	40.76	16.33	27.58	2.92	32.43	46.00	-13.57	QP
5	540.22	39.44	17.22	27.69	3.08	32.05	46.00	-13.95	QP
6	710.94	38.56	19.79	27.74	3.42	34.03	46.00	-11.97	QP



Shenzhen Certification Technology Service Co., Ltd.
2F, Building B, East Area of Nanchang Second Industrial Zone,
Gushu 2nd Road, Bao'an District, Shenzhen 518126, P.R. China
Tel: 4006786199 FAX: +86-755-26736857
Website: <http://www.cessz.com> Email: Service@cessz.com




Condition : FCC PART 15 B 3m POL: HORIZONTAL
EUT : Afinia 3D Printer
Model No. : H479
Test Mode : Print
Power : AC 120V/60Hz
Test Engineer: Store
Remark :

Item	Freq	Read Level	Antenna Factor	Preamp Factor	Cable Lose	Level	Limit	Margin	Remark
	MHz	dBuV	dB	dB	dB	dBuV	dBuV	dBuV	
1	103.72	45.54	10.54	26.85	0.88	30.11	43.50	-13.39	QP
2	184.23	42.01	11.20	26.94	1.31	27.58	43.50	-15.92	QP
3	298.69	41.80	12.80	27.19	1.92	29.33	46.00	-16.67	QP
4	335.55	42.78	13.58	27.24	2.12	31.24	46.00	-14.76	QP
5	528.58	37.76	17.03	27.68	3.06	30.17	46.00	-15.83	QP
6	816.67	31.45	20.80	27.67	3.63	28.21	46.00	-17.79	QP



Shenzhen Certification Technology Service Co., Ltd.
2F, Building B, East Area of Nanchang Second Industrial Zone,
Gushu 2nd Road, Bao'an District, Shenzhen 518126, P.R. China
Tel: 4006786199 FAX: +86-755-26736857
Website: <http://www.cessz.com> Email: Service@cessz.com



Condition : FCC PART 15 B 3m POL: VERTICAL
 EUT : Afinia 3D Printer
 Model No. : H479
 Test Mode : Print
 Power : AC 120V/60Hz
 Test Engineer : Store
 Remark :


Item	Freq	Read Level	Antenna Factor	Preamp Factor	Cable Lose	Level	Limit	Margin	Remark
	MHz	dBuV	dB	dB	dB	dBuV	dBuV	dBuV	
1	42.61	42.50	13.93	27.81	0.56	29.18	40.00	-10.82	QP
2	107.50	55.25	10.93	26.86	0.91	40.23	43.50	-3.27	QP
3	231.76	39.65	11.26	27.08	1.57	25.40	46.00	-20.60	QP
4	335.55	41.10	13.58	27.24	2.12	29.56	46.00	-16.44	QP
5	499.48	39.48	16.51	27.62	2.99	31.36	46.00	-14.64	QP
6	900.09	30.11	21.64	27.64	3.80	27.91	46.00	-18.09	QP

5. PHOTOGRAPH

5.1. Photos of Power Line Conducted Emission Test




5.2.Photos of Radiated Emission Test (In Anechoic Chamber)




6. PHOTOS OF THE EUT

Full View




Top View




Bottom View




Rear View




Left View




Right View







Front View



Inside View







-----THE END OF REPORT-----