

RF Test Report:

Airspan AirSynergy A25a

FCC ID:O2J-255AS

SC_TR_87_B

Prepared for:
Airspan Communications Ltd
Capital Point,
33 Bath Road
Slough,
Berkshire
SL1 3UF

Contents

1	Revision History	4
2	Purpose.....	4
3	Reference Documents	4
4	Test Information	5
4.1	Client.....	5
4.2	Test personnel.....	5
4.3	Test sample.....	5
5	Product Description.....	6
6	Test Configuration	7
6.1	Test sample and Operating mode	7
6.2	Support equipment.....	7
6.3	Test equipment (sections 8 to 12)	7
6.4	Test equipment (section 13 and 14)	8
6.5	Equipment set-up.....	9
7	Summary of Tests performed.....	10
8	Transmit Power 47CFR25.50(h).....	11
8.1	Requirement and test method.....	11
8.2	Test results	12
9	Spectral Power Density 27.50(h)(4).....	13
9.1	Requirement and test method.....	13
9.2	Test results	13
10	Conducted Band Edge 27.53(m)(2)	15
10.1	Requirement and test method.....	15
10.2	Results	15
11	Conducted Spurious Emissions	20
11.1	Requirement and test method.....	20
11.2	Results	20
12	Occupied Bandwidth	23
13	Radiated Spurious Emissions.....	24
13.1	Requirement and test method.....	24
13.2	Results	24
14	Mains Conducted Emissions	31

Tables

Table 1: Equipment under test	7
Table 2: Support Equipment	7
Table 3: Test Equipment for conducted tests.....	7
Table 4: Summary of tests performed	10
Table 5: Transmit power	12
Table 6: Transmit power spectral density	13
Table 7: Conducted Emissions masks results.....	15
Table 8: Conducted spurious emissions RF-3.....	20
Table 9: Occupied Bandwidth test results	23
Table 10: Radiated Spurious Emissions	24

Figures

Figure 1: Airsynergy configuration for test	9
Figure 2: Transmit Power plots.....	12
Figure 3: Transmit power spectral density plots.....	14
Figure 4: Conducted Emissions masks plots: 2305 MHz (5 MHz channels).....	16
Figure 5: Conducted Emissions masks plots: 2369 MHz (5 MHz channels).....	17
Figure 6: Conducted Emissions masks plots; 2506 MHz (10 MHz channels).....	18
Figure 7: Conducted Emissions masks plots; 2566 MHz (10 MHz channels).....	19
Figure 8: Conducted Spurious Emissions, 5 MHz channels.....	21
Figure 9: Conducted Spurious Emissions, 10 MHz channels	22
Figure 10: Occupied Bandwidths.....	23
Figure 11: RSE Plots, 5 MHz channels, pt1.....	25
Figure 12: RSE Plots, 5 MHz channels, pt2.....	26
Figure 13: RSE Plots, 5 MHz channels, pt3.....	27
Figure 14: RSE Plots, 10 MHz channels, pt1	28
Figure 15: RSE Plots, 10 MHz channels, pt2	29
Figure 16: RSE Plots, 10 MHz channels, pt3	30
Figure 17: Mains conducted emissions test set-up	31
Figure 18: Mains conducted emissions; Live line scan	32
Figure 19: Mains conducted emissions; Live line final measurements	33
Figure 20: Mains conducted emissions; Neutral line scan	34
Figure 21: Mains conducted emissions; Neutral line scan final measurements	35

1 Revision History

Revision	Originator	Date	Comment
A	C Blackham	07 June 2013	1 st release
B	C Blackham	20 June 2013	Added radiated emissions and mains conducted emissions results

2 Purpose

This document details the Airspan AirSynergy base station, model number SYN-CN-00-0A25A-000, designed for operation in the 2500 – 2572 MHz band.

3 Reference Documents

[Ref 1]	47CFR2	Title 47 Code of Federal Regulations Part 2: frequency allocations and radio treaty matters; general rules and regulations
[Ref 2]	47 CRF27	Title 47 Code of Federal Regulations Part 27: Miscellaneous wireless communication services
[Ref 3]	TIA-603-C	Land Mobile FM or PM – Communications Equipment – Measurement and Performance Standards
[Ref 4]	KDB 662911 D01 v01r02	Federal Communications Commission Office of Engineering and Technology Laboratory Division; Emissions Testing of Transmitters with Multiple Outputs in the Same Band (e.g., MIMO, Smart Antenna, etc)

4 Test Information

4.1 Client

Airspan Communications Ltd
Capital Point,
33 Bath Road
Slough,
SL1 3UF
UK

4.2 Test personnel

Conducted Emissions (sections 8 to 12)

Testing was performed by Charlie Blackham of Sulis Consultants Ltd at Airspan Communications offices on 6th June 2013.

Radiated Emissions and Mains Conducted emissions (sections 13 and 14)

Testing was performed by Dan Winstanley of TRaC Global Ltd at:

Chamber No.1, TRaC Global Ltd, Unit 1, Pendle Place, Skelmersdale, WN8 9PN, United Kingdom
FCC Registration number 444512

4.3 Test sample

The results herein only refer to sample detailed in section 6

5 Product Description

The Airsynergy unit supports operation with 5 and 10^1 MHz bandwidths, comprising 1024 subcarriers. Each of these subcarriers can be modulated in a number of modes:

- BPSK 1/2
- QPSK 1/2 and 3/4
- 16 QAM 1/2 and 3/4
- 64 QAM 1/2 and 3/4
- 256QAM

Based on pre-testing, the following modulation schemes will be used during testing:

- 256 QAM 5/6

The unit is fitted with two RF transceiver RF ports, RF-1 and RF-3. These support MIMO operation and are connected to a variety of external cross-polarised sectored antennas having gains of up to 18.0 dBi.

Frequency of operation is aligned with EBS channels and operates within the 2500 – 2572 MHz band

5 MHz channels: Centre frequencies of 2503 to 2569 MHz

10 MHz channels Centre frequencies of 2506 to 2566 MHz

¹ BRS/ERS equipment in 2500-2690 MHz band may use channel bandwidths greater than 6 MHz as permitted in 27.1220, i.e. 2x 6 MHz blocks or 12 MHz for 10 MHz channels.

6 Test Configuration

6.1 Test sample and Operating mode

The equipment under test (EUT) was:

Manufacturer	Name	Model Number	Serial Number
Airspan	AirSynergy	SYN-CN-00-0A25A-000	BB board A050CAFFF4F8

Table 1: Equipment under test

6.2 Support equipment

The support equipment was:

Description	Manufacturer	Name	Serial Number
Laptop	Dell	Latitude	Airspan 005837
Mains – 48 V PSU	Powerbox	PBUS-LUV-54V/100W-SN-QNA	P1131CV022587

Table 2: Support Equipment

6.3 Test equipment (sections 8 to 12)

Description	Manufacturer	Name	Serial Number	Calibration certificate
Receiver	Rohde & Schwarz	FSQ 26	200108	R&S Ref 38232
Signal Generator	Rohde & Schwarz	SMB100A03	175535	R&S 20-400919 16 Dec 2012
Attenuator	MCL	BW-N10W20+	1224	Calibrated in-situ and loaded as Transducer Factor
RF cable	Sucoflex	104	5884/4	

Table 3: Test Equipment for conducted tests

6.4 Test equipment (section 13 and 14)

TRaC No	Equipment Type	Equipment Description	Manufacturer	Due For Cal ²
UH387	ATS	Chamber 1	Rainford EMC	24/06/2013
UH403	ESCI 7	Recevier	R&S	27/06/2013
UH420	CBL6112	Bilog	Chase	06/07/2014
REF909	FSU26	Spectrum Analyser	R&S	04/02/2014
L138	3115	1-18GHz Horn	EMCO	08/11/2013
L572	8449B	Pre Amp	Agilent	12/12/2014
L300	20240-20	Horn 18-26GHz (&UH330)	Flann	17/11/2013
UH330	N/A	K type transition	Maury M'wave	Calibrated with L300
UH03	ESHS10	EMI receiver	R&S	08/05/1014
UH396	ENV216	LISN	R&S	30/04/2014
Eirp Substitution				
L139	3115	1-18GHz Horn	EMCO	14/09/2013
UH345	83711B	Signal Generator	HP	Not Calibrated ³

² Calibration records maintained by TRaC under UKAS accreditation.

³ Transmit signal level is measured at input to antenna using calibrated spectrum analyser

6.5 Equipment set-up

Equipment was configured as per figure 1:

- A “putty” sessions running on the laptop allows the Airsynergy unit to be controlled and set to required frequency, bandwidth, modulation and power.
- The insertion loss of the Attenuator and Co-ax cable were measured using a Signal Generator and the FSQ and their combined path-loss was programmed into the FSQ as a Transducer Factor.




Figure 1: Airsynergy configuration for test

14 Mains Conducted Emissions

Test method as per 15.107.



Figure 17: Mains conducted emissions test set-up

TRaC Global

20 Jun 2013

Powerline Conduction 150kHz - 30MHz

EUT: Airspan AirSynergy
 Manuf: Sulis Consultants
 Op Cond: LISN UH396, cable UH21 & Receiver UH03
 Operator: DW
 Test Spec: FCC
 Comment: Live Line, 110V, 60Hz
 EUT in normal operation (TXing) 5MHz bandwidth
 Result File: AS-LL.dat : New Measurement

Scan Settings		(1 Range)			Receiver Settings				
Start	Stop	Step	IF BW	Detector	M-Time	Atten	Preamp	OpRge	
150kHz	30MHz	5kHz	10kHz	PK+AV	50msec	Auto	OFF	60dB	
Transducer	No.	Start	Stop	Name					
1	1	9kHz	30MHz	UH21					
	2	9kHz	30MHz	UH396					
Final Measurement:		Detectors:	X QP / + AV						
		Meas Time:	2sec						
		Subranges:	25						
		Acc Margin:	20 dB						




Figure 18: Mains conducted emissions; Live line scan

TRaC Global

20 Jun 2013 13:32

Powerline Conduction 150kHz - 30MHz

EUT: Airspan AirSynergy
 Manuf: Sulis Consultants
 Op Cond: LISN UH396, cable UH21 & Receiver UH03
 Operator: DW
 Test Spec: FCC
 Comment: Live Line, 110V, 60Hz
 EUT in normal operation (TXing) 5MHz bandwidth
 Result File: AS-LL.dat : New Measurement

Scan Settings		(1 Range)				Receiver Settings				
Start	Stop	Step	IF BW	Detector	M-Time	Atten	Preamp	OpRge		
150kHz	30MHz	5kHz	10kHz	PK+AV	50msec	Auto	OFF	60dB		
Transducer	No.	Start	Stop	Name						
1	1	9kHz	30MHz	UH21						
	2	9kHz	30MHz	UH396						
Final Measurement:		Detectors:	X QP / + AV							
		Meas Time:	2sec							
		Subranges:	25							
		Acc Margin:	20 dB							

Final Measurement Results

Frequency MHz	QP Level dB μ V	QP Limit dB μ V	QP Delta dB
0.275	43.00	60.97	17.97
0.35	41.81	58.96	17.15
0.385	42.82	58.17	15.35
0.505	35.05	56.00	20.95
0.605	41.55	56.00	14.45
0.815	39.30	56.00	16.70
0.83	40.43	56.00	15.57
1.115	36.46	56.00	19.54
1.355	37.96	56.00	18.04
1.79	37.25	56.00	18.75
1.935	31.22	56.00	24.78
2.47	32.07	56.00	23.93
3.035	33.20	56.00	22.80
3.705	28.76	56.00	27.24

Frequency MHz	AV Level dB μ V	AV Limit dB μ V	AV Delta dB
0.275	37.30	50.97	13.67
0.365	34.45	48.61	14.16
0.605	30.18	46.00	15.82
0.69	28.59	46.00	17.41
0.835	28.21	46.00	17.79
1.08	25.07	46.00	20.93

Figure 19: Mains conducted emissions; Live line final measurements

TRaC Global

20 Jun 2013 13:51

Powerline Conduction 150kHz - 30MHz

EUT: Airspan AirSynergy
 Manuf: Sulis Consultants
 Op Cond: LISN UH396, cable UH21 & Receiver UH03
 Operator: DW
 Test Spec: FCC
 Comment: Neutral Line, 110V, 60Hz
 EUT in normal operation (TXing) 5MHz bandwidth
 Result File: AS-LL.dat : New Measurement

Scan Settings		(1 Range)			Receiver Settings							
Start	Stop	Step	IF BW	Detector	M-Time	Atten	Preamp	OpRge				
150kHz	30MHz	5kHz	10kHz	PK+AV	50msec	Auto	OFF	60dB				
Transducer		No.	Start	Stop	Name							
1		1	9kHz	30MHz	UH21							
		2	9kHz	30MHz	UH396							
Final Measurement:		Detectors:		X QP / + AV								
		Meas Time:		2sec								
		Subranges:		25								
		Acc Margin:		20 dB								




Figure 20: Mains conducted emissions; Neutral line scan

TRaC Global

20 Jun 2013 13:51

Powerline Conduction 150kHz - 30MHz

EUT: Airspan AirSynergy
 Manuf: Sulis Consultants
 Op Cond: LISN UH396, cable UH21 & Receiver UH03
 Operator: DW
 Test Spec: FCC
 Comment: Neutral Line, 110V, 60Hz
 Result File: EUT in normal operation (TXing) 5MHz bandwidth
 AS-LL.dat : New Measurement

Scan Settings		(1 Range)				Receiver Settings				
		Frequencies		Step	IF BW	Detector	M-Time	Atten	Preamp	OpRge
Start	Stop	Start	Stop	5kHz	10kHz	PK+AV	50msec	Auto	OFF	60dB
Transducer	No.	Start	Stop			Name				
1	1	9kHz	30MHz			UH21				
	2	9kHz	30MHz			UH396				
Final Measurement:		Detectors:	X QP / + AV							
		Meas Time:	2sec							
		Subranges:	25							
		Acc Margin:	20 dB							

Final Measurement Results

Frequency MHz	QP Level dB μ V	QP Limit dB μ V	QP Delta dB
0.275	40.42	60.97	20.55
0.35	41.87	58.96	17.09
0.38	43.22	58.28	15.06
0.505	35.30	56.00	20.70
0.6	41.91	56.00	14.09
0.815	39.64	56.00	16.36
0.82	40.37	56.00	15.63
1.075	37.79	56.00	18.21
1.385	35.96	56.00	20.04
1.625	37.15	56.00	18.85
1.93	31.74	56.00	24.26
2.615	32.33	56.00	23.67
2.975	32.39	56.00	23.61
3.65	31.82	56.00	24.18
Frequency MHz	AV Level dB μ V	AV Limit dB μ V	AV Delta dB
0.275	34.10	50.97	16.87
0.35	29.73	48.96	19.23
0.36	34.92	48.73	13.81
0.595	30.43	46.00	15.57
0.69	28.59	46.00	17.41
0.835	27.05	46.00	18.95
1.085	28.33	46.00	17.67

Figure 21: Mains conducted emissions; Neutral line scan final measurements