



www.timcoengr.com

849 NW STATE ROAD 45
NEWBERRY, FL 32669 USA
PH: 888.472.2424 OR
352.472.5500
FAX: 352.472.2030
EMAIL: INFO@TIMCOENGR.COM
[HTTP://WWW.TIMCOENGR.COM](http://WWW.TIMCOENGR.COM)

RF Exposure Evaluation Report

APPLICANT	WORLDCAST SYSTEMS, INC.
	19595 NE 10TH AVENUE SUITE A MIAMI FL 33179 USA
FCC ID	O35EFM0300W
IC	10552A-EFM0300W
MODEL NUMBER	EFM0300W
PRODUCT DESCRIPTION	300W FM BROADCAST TRANSMITTER
STANDARD APPLIED	CFR 47 Part 2.1091
PREPARED BY	Cory Leverett

We, TIMCO ENGINEERING, INC. would like to declare that the device has been evaluated in accordance with 47 CFR Part 2.1091 and meets the requirements.

The attached report shall not be reproduced except in full without the written approval of TIMCO ENGINEERING, INC.

Applicant: WORLDCAST SYSTEMS, INC.

FCC ID: O35EFM0300W

IC: 10552A-EFM0300W

Report: V:\W\WORLDCAST\1448AUT16\1448AUT16RF EXP MPE RPT.DOCX

GENERAL REMARKS

Attestations

This equipment has been evaluated in accordance with the standards identified in this report. To the best of my knowledge and belief, these evaluations were performed using the procedures described in this report.

I attest that the necessary evaluations were made, under my supervision, at:

Timco Engineering Inc.
849 NW State Road 45
Newberry, FL 32669


A handwritten signature in blue ink, appearing to read "Cory Leverett". Below the signature is a circular red stamp with the text "CORY LEVERETT" and "TENNESSEE" around the perimeter.

Authorized Signatory Name:

Cory Leverett, Engineering Project Manager

Date: October 24, 2016

Applicant: WORLDCAST SYSTEMS, INC.
FCC ID: 035EFM0300W
IC: 10552A-EFM0300W
Report: V:\W\WORLDCAST\1448AUT16\1448AUT16RF EXP MPE RPT.DOCX

RF Exposure Requirements

General information

Device type: 300W FM BROADCAST TRANSMITTER

Devices that operate under Part 73 of this chapter are subject to RF exposure evaluation prior to equipment authorization or use.

Antenna

The manufacturer does not specify an antenna, but a typical antenna has a gain of 0 dBi.

Configuration	Antenna p/n	Type	Max. Gain (dBi)
Fixed mounted	Any	omni	0

MPE Calculation:

The minimum separation distance is calculated as follows:

$$E(V/m) = \frac{\sqrt{30 \times P \times G}}{d}$$
$$\text{Power density: } P_d(mW/cm^2) = \frac{E^2}{3770}$$

The limit for general uncontrolled exposure environment is shown in FCC rule Part 1.11310, Table 1.

Applicant: WORLDCAST SYSTEMS, INC.

FCC ID: 035EFM0300W

IC: 10552A-EFM0300W

Report: V:\W\WORLDCAST\1448AUT16\1448AUT16RF EXP MPE RPT.DOCX

Minimum Separation Distance for Mobile or Fixed Devices
Controlled Exposure

Insert values in yellow highlighted boxes to determine Minimum Separation Distance

Max Power	300	W	equals	Max Power	300000	mW
Duty Cycle	100	%	equals	Duty Factor	1	numeric
Antenna Gain	0	dBi	equals	Gain numeric	1	numeric
Coax Loss	0	dB		Gain - Coax Loss	1	numeric
Power Density	0.4	mW/cm ²				

Enter power Density from the chart to the right

Frequency 108 MHz

Rule Part 1.1310, Table 1 (A)

Freq range	Power density	Enter this value
		mW/cm ²
0.3 - 3	100	100
3 - 30	900/f ²	0.1
30-300	1	1
300-1,500	f/300	0.4
1,500-100,000	5	5

f = frequency in MHz

Minimum Separation Distance

244 cm

2.44 m

Minimum Separation in Inches

96.10811 Inches

Applicant: WORLDCAST SYSTEMS, INC.

FCC ID: 035EFM0300W

IC: 10552A-EFM0300W

Report: V:\W\WORLDCAST\1448AUT16\1448AUT16RF EXP MPE RPT.DOCX