

198 Kezhu Road, Scientech Park, Guangzhou Economic & Technological Development District, Guangzhou, China 510663
Telephone: +86 (0) 20 82155555
Fax: +86 (0) 20 82075059
Email: ee.guangzhou@sgs.com

Report No.: GZEM110600230701
Page: 1 of 56
FCC ID: O3A-HM315U

TEST REPORT

Application No.:	GZEM1106002307RF
Applicant:	Techworld Industries Limited
FCC ID:	O3A-HM315U
Product Name:	Multi-way Wall Switch
Product Description:	Wireless control switch
Model No.:	HM-315U
Trade Mark:	
Standards:	FCC PART 15 Subpart C: 2010 section 15.247
Date of Receipt:	2012-02-02
Date of Test:	2012-05-09 to 2012-05-14
Date of Issue:	2013-03-14
Test Result :	Pass*

* In the configuration tested, the EUT detailed in this report complied with the standards specified above. Please refer to section 3 of this report for further detail.

Authorized Signature



Strong Yao
Manager


The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

2 Version

Revision Record				
Version	Chapter	Date	Modifier	Remark
00		2013-03-14		Original

Authorized for issue by:			
Tested By		 (Daniel He) /Signature	2012-05-09 to 2012-05-14 Date
Prepared By		 (Daniel He) /Signature	2012-05-23 Date
Checked By		 (Strong Yao) /Reviewer	2013-03-14 Date

3 Test Summary

Test	Test Requirement	Test method	Result
Antenna Requirement	FCC PART 15 C section 15.247 (c) and Section 15.203	FCC PART 15 C section 15.247 (c) and Section 15.203	PASS
6 dB Bandwidth	FCC PART 15 C section 15.247 (a)(2)	ANSI C63.10: Clause 6.9.1	PASS
Maximum Peak Output Power	FCC PART 15 C section 15.247(b)(3)	ANSI C63.10: Clause 6.10.3.1	PASS
Peak Power Spectral Density	FCC PART 15 C section 15.247(e)	ANSI C63.10: Clause 6.11.2.3	PASS
Conducted Spurious Emission (30MHz to 25GHz)	FCC PART 15 C section 15.209 &15.247(d)	ANSI C63.10: Clause 6.7	PASS
Radiated Spurious Emission 30 MHz to 25 GHz)	FCC PART 15 C section 15.209 &15.247(d)	ANSI C63.10: Clause 6.4, 6.5 and 6.6	PASS
Band Edges Measurement	FCC PART 15 C section 15.247 (d) &15.205	ANSI C63.10: Clause 6.9.2	PASS
Conducted Emissions at Mains Terminals	FCC PART 15 C section 15.207	ANSI C63.10: Clause 6.2	PASS

Remark:

N/A: not applicable. Refer to the relative section for the details.

EUT: In this whole report EUT means Equipment Under Test.

Tx: In this whole report Tx (or tx) means Transmitter.

Rx: In this whole report Rx (or rx) means Receiver.

RF: In this whole report RF means Radio Frequency.

ANSI C63.10: the detail version is ANSI C63.10:2009 in the whole report.

4 Contents

1 COVER PAGE	1
2 VERSION.....	2
3 TEST SUMMARY	3
4 CONTENTS.....	4
5 GENERAL INFORMATION	5
5.1 Client Information	5
5.2 General Description of E.U.T.	5
5.3 Details of E.U.T.	5
5.4 Description of Support Units	5
5.5 Deviation from Standards	5
5.6 Abnormalities from Standard Conditions	5
5.7 Other Information Requested by the Customer	5
5.8 Test Location	6
5.9 Test Facility	7
6 EQUIPMENT USED DURING TEST.....	8
7 TEST RESULTS	10
7.1 E.U.T. test conditions.....	10
7.2 Antenna Requirement	12
7.3 6 dB Bandwidth.....	13
7.4 Maximum Peak Output Power.....	17
7.5 Peak Power Spectral Density	22
7.5 Conducted Spurious Emissions	27
7.6 Radiated Spurious Emissions	33
7.7 Band Edges Requirement	50
7.8 Conducted Emissions at Mains Terminals 150 kHz to 30MHz.....	53

5 General Information

5.1 Client Information

Applicant: Techworld Industries Limited
Address of Applicant: Unit 1705, 17/F., Nanyang Plaza, 57 Hung To Road, Kwun Tong, Kowloon, Hong Kong China

5.2 General Description of E.U.T.

Product Name: Multi-Way Wall Switch
Product Description: Wireless control switch
Model No.: HM-315U
Trade Mark:



5.3 Details of E.U.T.

Operating Frequency	2405MHz to 2480MHz
Type of Modulation:	DSSS(O-QPSK)
Transmit Data Rate:	200Kbps
Number of Channels	17 Channels
Channel Separation:	5 MHz
Antenna Type	Integrate
Antenna gain:	2dBi
Function:	Wireless control switch
Power Supply:	AC 120V 50/60Hz
Power cord:	0.5 m x 2 wires unscreened AC cable

5.4 Description of Support Units

The EUT has been tested with Lamp and Lamp Holder supplied by testing lab.

5.5 Deviation from Standards

Biconical and log periodic antennas were used instead of dipole antennas.

5.6 Abnormalities from Standard Conditions

None.

5.7 Other Information Requested by the Customer

None.

5.8 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Guangzhou EMC Laboratory,
198 Kezhu Road, Scientech Park, Guangzhou Economic & Technology Development District,
Guangzhou, China 510663

Tel: +86 20 82155555 Fax: +86 20 82075059

No tests were sub-contracted.

5.9 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **NVLAP (Lab Code: 200611-0)**

SGS-CSTC Standards Technical Services Co., Ltd., Guangzhou EMC Laboratory is recognized under the National Voluntary Laboratory Accreditation Program (NVLAP/NIST). NVLAP Code: 200611-0.

- **ACMA**

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory can also perform testing for the Australian C-Tick mark as a result of our NVLAP accreditation.

- **SGS UK(Certificate No.: 32), SGS-TUV SAARLAND and SGS-FIMKO**

Have approved SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory as a supplier of EMC TESTING SERVICES and SAFETY TESTING SERVICES.

- **CNAS (Lab Code: L0167)**

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory has been assessed and in compliance with CNAS-CL01:2006 accreditation criteria for testing laboratories (identical to ISO/IEC 17025:2005 General Requirements) for the Competence of Testing Laboratories.

- **FCC (Registration No.: 282399)**

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 282399, May 31, 2002.

- **Industry Canada (Registration No.: 4620B-1)**

The 3m/10m Alternate Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd. has been registered by Certification and Engineering of Industry Canada for radio equipment testing with Registration No. 4620B-1.

- **VCCI (Registration No.: R-2460, C-2584, G-449 and T-1179)**

The 10m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-2460, C-2584, G-449 and T-1179 respectively.

- **CBTL (Lab Code: TL129)**

SGS-CSTC Standards Technical Services Co., Ltd., E&E Laboratory has been assessed and fully comply with the requirements of ISO/IEC 17025:2005, the Basic Rules, IECEE 01:2006-10 and Rules of procedure IECEE 02:2006-10, and the relevant IECEE CB-Scheme Operational documents.

6 Equipment Used during Test

RE in Chamber						
No.	Test Equipment	Manufacturer	Model No.	Serial No.	Cal.Due date (YYYY-MM-DD)	Calibration Interval
EMC0525	Compact Semi-Anechoic Chamber	ChangZhou ZhongYu	N/A	N/A	2012-09-06	2Y
EMC0522	EMI Test Receiver	Rohde & Schwarz	ESIB26	100283	2012-11-11	1Y
EMC0056	EMI Test Receiver	Rohde & Schwarz	ESCI	10036	2013-03-12	1Y
EMC0528	RI High frequency Cable	SGS	20 m	N/A	2012-06-09	1Y
EMC2025	Trilog Broadband Antenna 30-3000MHz	SCHWARZBECK MESS-ELEKTRONIK	VULB 9163	9163-450	2012-10-20	1Y
EMC0524	Bi-log Type Antenna	Schaffner -Chase	CBL6112B	2966	2012-11-28	1Y
EMC0519	Bilog Type Antenna	Schaffner -Chase	CBL6143	5070	2012-11-28	1Y
EMC2026	Horn Antenna 1-18GHz	R&S	BBHA 9120D	9120D-841	2012-10-20	1Y
EMC0518	Horn Antenna	Rohde & Schwarz	HF906	100096	2012-08-29	1Y
EMC0521	1-26.5 GHz Pre-Amplifier	Agilent	8449B	3008A01649	2012-08-29	1Y
EMC0049	Amplifier	Agilent	8447D	2944A10862	2013-03-12	1Y
EMC0075	310N Amplifier	Sonama	310N	272683	2012-08-29	1Y
EMC0523	Active Loop Antenna	EMCO	6502	42963	2012-11-17	1Y
EMC2041	Broad-Band Horn Antenna (14)15-26.5(40)GHz	SCHWARZBECK MESS-ELEKTRONI	BBHA 9170	9170-375	2014-06-01	3Y
EMC0530	10m Semi-Anechoic Chamber	ETS	N/A	N/A	2014-04-27	2Y

Conducted Emission						
No.	Test Equipment	Manufacturer	Model No.	Serial No.	Cal.Due date (YYYY-MM-DD)	Calibration Interval
EMC0306	Shielding Room	Zhong Yu	8 x 3 x 3.8 m ³	N/A	N/A	N/A
EMC0118	Two-line v-netwok	R&S	ENV216	100359	2012-08-29	1Y
EMC0102	LISN	SCHAFFNER CHASE	MN2050D/1	1421	2012-11-23	1Y
EMC2046	Artificial Mains Network (LISN)	AFJ Instruments	LT32C	S.N.320311201 50	2013-03-12	1Y
EMC0506	EMI Test Receiver	Rohde & Schwarz	ESCS30	100085	2012-11-24	1Y
EMC0107	Coaxial Cable	SGS	2m	N/A	2012-07-18	1Y
EMC0106	Voltage Probe	SGS	N/A	N/A	N/A	1Y
EMC0120	8 Line ISN	Fischer Custom Communications Inc.	FCC-TLISN-T8-02	20550	2012-11-11	1Y
EMC0121	4 Line ISN	Fischer Custom Communications Inc.	FCC-TLISN-T4-02	20549	2012-11-11	1Y
EMC0122	2 Line ISN	Fischer Custom Communications Inc.	FCC-TLISN-T2-02	20548	2012-11-11	1Y
EMC167	Conical metal housing	SGS-EMC	N/A	N/A	2013-02-16	1Y



SGS-CSTC Standards Technical Services Co., Ltd.

Report No.: GZEM110600230701

Page: 9 of 56

FCC ID: O3A-HM315U

General used equipment						
No.	Test Equipment	Manufacturer	Model No.	Serial No.	Cal.Due date (YYYY-MM-DD)	Calibration Interval
EMC0006	DMM	Fluke	73	70681569	2012-11-14	1Y
EMC0007	DMM	Fluke	73	70671122	2012-11-14	1Y

7 Test Results

7.1 E.U.T. test conditions

Test Voltage:	AC 120V, 60 Hz
Temperature:	20.0 -25.0 °C
Humidity:	38-50 % RH
Atmospheric Pressure:	1000 -1010 mbar
Requirements:	15.31(e): For intentional radiators, measurements of the variation of the input power or the radiated signal level of the fundamental frequency component of the emission, as appropriate, shall be performed with the supply voltage varied between 85% and 115% of the nominal rated supply voltage. For battery operated equipment, the equipment tests shall be performed using a new battery. 15.32: Power supplies and CPU boards used with personal computers and for which separate authorizations are required to be obtained shall be tested as follows: Testing shall be in accordance with the procedures specified in Section 15.31 of this part. According to the 15.31(m) Measurements on intentional radiators or receivers, other than TV broadcast receivers, shall be performed and, if required, reported for each band in which the device can be operated with the device operating at the number of frequencies in each band specified in the following table: According to the 15.33 (a) For an intentional radiator, the spectrum shall be investigated from the lowest radio frequency signal generated in the device, without going below 9 kHz, up to at least the frequency shown in the following table:
Test frequencies and frequency range:	

Number of fundamental frequencies to be tested in EUT transmit band

Frequency range in which device operates	Number of frequencies	Location in frequency range of operation
1 MHz or less	1	Middle
1 MHz to 10 MHz	2	1 near top and 1 near bottom
More than 10 MHz	3	1 near top, 1 near middle and 1 near bottom

Frequency range of radiated emission measurements

Lowest frequency generated in the device	Upper frequency range of measurement
9 kHz to below 10 GHz	10th harmonic of highest fundamental frequency or to 40 GHz, whichever is lower
At or above 10 GHz to below 30 GHz	5th harmonic of highest fundamental frequency or to 100 GHz, whichever is lower
At or above 30 GHz	5th harmonic of highest fundamental frequency or to 200 GHz, whichever is lower, unless otherwise specified

EUT channels and frequencies list:

Channel	Frequency (MHz)
1	2405
2	2410
3	2415
4	2420
5	2425
6	2430
7	2435
8	2440
9	2445
10	2450
11	2455
13	2460
14	2465
15	2470
16	2475
17	2480

Test frequencies are the lowest channel: 1 channel(2405MHz), middle channel: 8 channel(2440 MHz) and highest channel: 17 channel(2480 MHz)

7.2 Antenna Requirement

Standard requirement

15.203 requirement:

For intentional device. According to 15.203. an intentional radiator shall be designed to Ensure that no antenna other than that furnished by the responsible party shall be used with the device.

15.247(c) (1)(i) requirement:

(i) Systems operating in the 2400-2483.5 MHz bands that are used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

EUT Antenna

The antenna is an Integrate and no consideration of replacement. The best case gain of the antenna is 2dBi.

Test result: The unit does meet the FCC requirements.


7.3 6 dB Bandwidth

Test Requirement: FCC Part 15 C section 15.247
(a)(2)Systems using digital modulation techniques may operate in the 902-928 MHz, 2400-2483.5MHz, and 5725-5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Method: ANSI C63.10: Clause 6.9.1

Test Status: Test the EUT in continuous transmitting with modulation at lowest, middle and highest channel.

Test Configuration:



Test Procedure:

1. Remove the antenna from the EUT and then connect a low attention attenuation RF cable (cable loss =4.0dB) from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW=100KHz. VBW = 300KHz. Sweep = auto; Detector Function = Peak. Trace = Max Hold, Set span to encompass the entire emission bandwidth of the signal.
3. Mark the peak power frequency and -6dB (upper and lower) power frequency.
4. Repeat until all the test status is investigated.
5. Report the worse case.


Channel No.	Frequency (MHz)	Mode	Data Rate	Measured 6dB bandwidth (MHz)	Limit	Result
1	2405	DSSS (O-QPSK)	200Kbps	1.6433	≥500KHz	Pass
8	2440		200Kbps	1.6433		Pass
17	2480		200Kbps	1.6032		Pass

Test result: The unit does meet the FCC requirements.


Result plot as follows:

DSSS mode with 200Kbps data rate


Channel 1:2.405GHz:



Channel 8:2.440GHz:



Channel 17:2.480GHz:



7.4 Maximum Peak Output Power

Test Requirement:

FCC Part 15 C section 15.247

(b)(3) For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt.

Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b) (1), (b) (2), and (b) (3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.


Test Method:

ANSI C63.10: Clause 6.10.3.1 (Method 1—spectral trace averaging).

Test Status:

Test the EUT in continuous transmitting with modulation at lowest, middle and highest channel.

Test Configuration:



Test Procedure:

1. Remove the antenna from the EUT and then connect a low attention attenuation RF cable (Cable loss =4dB) from the antenna port to the spectrum.
2. Set span to encompass the entire emission bandwidth (EBW) of the signal.
3. Set RBW = 1 MHz.
4. Set VBW ≥ 3 MHz.
5. Use sample detector mode if bin width (i.e., span/number of points in spectrum display) < 0.5 RBW. Otherwise use peak detector mode.
6. Use a video trigger with the trigger level set to enable triggering only on full power pulses. Transmitter must operate at full control power for entire sweep of every sweep.
If the device transmits continuously, with no off intervals or reduced power intervals, the trigger may be set to "free run".
7. Trace average 100 traces in power averaging mode.
8. Compute power by integrating the spectrum across the 26 dB EBW of the signal. The integration can be performed using the spectrum analyzer's band power measurement function with band limits set equal to the EBW band edges or by summing power levels in each 1 MHz band in linear power terms. The 1 MHz band power levels to be summed can be obtained by averaging, in linear power terms, power levels in each frequency bin across the 1 MHz.
9. Measure the channel power of the test frequency with special test status.
10. Repeat until all the test status is investigated.
11. Report the worse case.

Test result:


Channel No.	Frequency (MHz)	Mode	Data Rate	Measured Channel Power (dBm)	Limit	Result
1	2405	DSSS (O-QPSK)	200Kbps	4.89	1W(30dBm)	Pass
8	2440		200Kbps	5.92		Pass
17	2480		200Kbps	3.93		Pass

Remark: Level = Read Level + Cable Loss.**The unit does meet the FCC requirements.**


Result plot as follows:

DSSS mode with 200Kbps data rate


Channel 1:2.405GHz:



Channel 8:2.440GHz:



Channel 17:2.480GHz:



7.5 Peak Power Spectral Density


Test Requirement: FCC Part 15 C section 15.247
(e) For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Method: ANSI C63.10: Clause 6.11.2.3

Test Status: Test the EUT in continuous transmitting with modulation at lowest, middle and highest channel.

Test Configuration:



Test Procedure:

1. Remove the antenna from the EUT and then connect a low attention attenuation RF cable (cable loss =4dB) from the antenna port to the spectrum analyzer or power meter.
2. Set the spectrum analyzer:
 - a) Set CENTER FREQUENCY = Frequency from Power Spectral Density Test Matrix (see 6.10.2)
 - b) Set SPAN = 20 MHz (For devices with a nominal 40 MHz BW, 50 MHz span will be needed)
 - c) Set REFERENCE LEVEL = 20 dBm
 - d) Set ATTENUATION = 0 dB (add internal attenuation, if necessary)
 - e) Set SWEEP TIME = Coupled
 - f) Set RBW = 3 kHz
 - g) Set VBW = 10 kHz
 - h) Set DETECTOR = Peak
 - i) Set MKR = Center Frequency
 - j) Set TRACE = CLEAR WRITE

Place the radio in continuous transmit mode. Set the TRACE to MAX HOLD, and after the trace stabilizes, the TRACE to VIEW. Set the marker on the peak of the signal and then adjust the center frequency of the spectrum analyzer to the marker frequency.

After viewing the EUT waveform on the spectrum analyzer, perform the following spectrum analyzer functions to capture the trace:

Set SPAN = 300 kHz
Set SWEEP TIME = 100 s
Set TRACE = MAX HOLD
Set MKR = PEAK SEARCH

3. Measure the Power Spectral Density of the test frequency with special test status.
4. Repeat until all the test status is investigated.
5. Report the worse case.

Channel No.	Frequency (MHz)	Mode	Data Rate	Measured Peak Power Spectral Density (dBm/3KHz)	Limit	Result
1	2405	DSSS (O-QPSK)	200Kbps	-10.79	8dBm/3KHz	Pass
8	2440		200Kbps	-10.83		Pass
17	2480		200Kbps	-12.49		Pass


Test result: Level = Read Level + Cable Loss.

The unit does meet the FCC requirements.


Result plot as follows:

DSSS mode with 200Kbps data rate


Channel 1:2.405 GHz:



Channel 8:2.440 GHz:



Channel 17:2.480 GHz:



7.5 Conducted Spurious Emissions


Test Requirement: FCC Part 15 C section 15.247

(d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power. Based on either an RF conducted or a radiated measurement. Provided the transmitter demonstrates compliance with the peak conducted power limits.

Test Method: ANSI C63.10: Clause 6.7

Test Status: Test the EUT in continuous transmitting with modulation at lowest, middle and highest channel.

Test Configuration:



Test Procedure:


1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum analyzer or power meter.
2. Set the spectrum analyzer: RBW=100 KHz, VBW = 300KHz. Sweep = auto; Detector Function = Peak. Trace = Max Hold, Scan up through 10th harmonic.
3. Measure the Conducted Spurious Emissions of the test frequency with special test status.
4. Repeat until all the test status is investigated.
5. Report the worse case.

Result plot as follows:


DSSS mode with 200Kbps data rate



Channel 1: 2.405 GHz



30 MHz to 1 GHz



1 G to 5 GHz




5 G to 25 GHz

Channel 8:2.440 GHz
30 M to 1 GHz



1 G to 5 GHz

5 G to 25 GHz



Channel17:2.480 GHz

30 M to 1 GHz



1 G to 5 GHz



5 G to 25 GHz

7.6 Radiated Spurious Emissions

Test Requirement: FCC Part 15 C section 15.247
(d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating. The radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that Contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, and provided the transmitter demonstrates compliance with the peak conducted power limits.

Test Method: ANSI C63.10: Clause 6.4, 6.5 and 6.6

Test Status: Test the EUT in continuous transmitting with modulation at lowest, middle and highest channel.


Detector: For PK value:
RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz
VBW \geq RBW
Sweep = auto
Detector function = peak
Trace = max hold

For AV value:
RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz
VBW = 10Hz
Sweep = auto
Detector function = peak
Trace = max hold


15.209 Limit:
40.0 dB μ V/m between 30MHz & 88MHz
43.5 dB μ V/m between 88MHz & 216MHz
46.0 dB μ V/m between 216MHz & 960MHz
54.0 dB μ V/m above 960MHz

Test Configuration:

- 1) 30 MHz to 1 GHz emissions:



- 2) 1 GHz to 40 GHz emissions:



Test Procedure: The receiver was scanned from 30MHz to 25GHz. When an emission was found, the table was rotated to produce the maximum signal strength. An initial pre-scan was performed for in peak detection mode using the receiver. The EUT was measured for both the Horizontal and Vertical polarities and performed a pre-test three orthogonal planes. For intentional radiators, measurements of the variation of the input power or the radiated signal level of the fundamental frequency component of the emission, as appropriate, shall be performed with the supply voltage varied between 85% and 115% of the nominal rated supply voltage. The worst case emissions were reported.

From 30MHz to 1GHz, read the Quasi-Peak field strength of the emissions with receiver QP detector RBW=120KHz.

Above 1GHz, read the Peak field strength and Average field strength.

Read the Peak field strength through RBW=1MHz, VBW=3MHz in spectrum analyzer setting;

Read the Average field strength through RBW=1MHz, VBW=10Hz in spectrum analyzer setting;

While maintaining all of the other instrument settings. This peak level, once corrected, must comply with the limit specified in Section 15.209. If the dwell time per channel of the hopping signal is less than 100 ms, then the average field strength reading obtained with the 10 Hz VBW may be further adjusted by a "duty cycle correction factor", derived from $20\log(\text{dwell time}/100 \text{ ms})$, in an effort to demonstrate compliance with the 15.209 limit.

7.6.1 Harmonic and other spurious emissions

7.6.1.1 DSSS mode with 200Kbps data rate


Test at Channel 1 (2.405 GHz) in transmitting status

30 MHz~1 GHz Spurious Emissions .Quasi-Peak Measurement

Vertical:

Peak scan

Level (dB μ V/m)




Quasi-peak measurement

Freq MHz	ReadAntenna Level Factor		Cable Preamp Loss Factor		Level dB	Over Limit dB	Line Remark
	MHz	dBuV	dB/m	dB	dBuV/m		
140.580	30.98	10.83	1.17	27.46	15.52	-27.98	43.50 QP
242.430	27.27	11.20	1.56	27.16	12.87	-33.13	46.00 QP
343.310	28.66	14.07	1.94	27.40	17.27	-28.73	46.00 QP
524.700	26.75	17.66	2.45	28.13	18.73	-27.27	46.00 QP
708.030	27.25	19.20	2.81	27.86	21.40	-24.60	46.00 QP
899.120	27.94	20.70	3.50	26.73	25.41	-20.59	46.00 QP

Horizontal:

Peak scan

Level (dB μ V/m)

Quasi-peak measurement

Freq MHz	ReadAntenna		Cable		Preamp Level	Over Limit	Limit	Line Remark
	Level	Factor	Loss	Factor				
MHz	dB μ V	dB/m	dB	dB	dB μ V/m	dB	dB μ V/m	
140.580	37.42	10.83	1.17	27.46	21.96	-21.54	43.50	QP
243.400	31.02	11.23	1.57	27.16	16.66	-29.34	46.00	QP
271.530	33.52	12.26	1.70	27.11	20.37	-25.63	46.00	QP
480.080	27.95	17.30	2.32	27.99	19.58	-26.42	46.00	QP
646.920	27.19	18.73	2.69	28.13	20.48	-25.52	46.00	QP
903.970	28.35	20.77	3.50	26.74	25.88	-20.12	46.00	QP

1~25 GHz Harmonics & Spurious Emissions. Peak & Average Measurement

Peak Measurement:

Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Reading Level (dB μ V)	Emission Level (dB μ V/m)	Limit (dB μ V/m)	Antenna polarization
4810.000	31.53	8.81	34.30	46.13	52.17	74.00	V
7215.000	36.47	12.32	34.30	44.74	59.23	74.00	V
4810.000	31.53	8.81	34.30	45.15	51.19	74.00	H
7215.000	36.47	12.32	34.30	44.32	58.81	74.00	H

Average Measurement:


Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Reading Level (dB μ V)	Emission Level (dB μ V/m)	Limit (dB μ V/m)	Antenna polarization
4810.000	31.53	8.81	34.30	39.61	45.65	54.00	V
7215.000	36.47	12.32	34.30	35.42	49.91	54.00	V
4810.000	31.53	8.81	34.30	37.74	43.78	54.00	H
7215.000	36.47	12.32	34.30	35.60	50.09	54.00	H

Test at Channel8 (2.440 GHz) in transmitting status

30 MHz~1 GHz Spurious Emissions .Quasi-Peak Measurement

Vertical:

Peak scan


Level (dB μ V/m)

Quasi-peak measurement

Freq	ReadAntenna		Cable Preamp		Over Limit	Limit	Line Remark
	Level	Factor	Loss	Factor			
MHz	dB μ V	dB/m	dB	dB	dB	dB μ V/m	
136.700	31.32	11.38	1.15	27.48	16.37	-27.13	43.50 QP
267.650	26.91	12.30	1.68	27.12	13.77	-32.23	46.00 QP
413.150	27.96	16.34	2.12	27.81	18.61	-27.39	46.00 QP
614.910	25.89	18.50	2.64	28.29	18.74	-27.26	46.00 QP
801.150	26.87	20.12	3.10	27.63	22.46	-23.54	46.00 QP
910.760	28.19	20.90	3.52	26.75	25.86	-20.14	46.00 QP

Horizontal:

Peak scan

Level (dB μ V/m)

Quasi-peak measurement

Freq MHz	ReadAntenna		Cable Preamp		Over Limit dB	Line Remark
	Level dB μ V	Factor dB/m	Loss dB	Factor dB μ V/m		
135.730	28.88	11.62	1.15	27.48	14.17	-29.33
241.460	29.37	11.17	1.56	27.16	14.94	-31.06
288.990	30.68	12.62	1.77	27.08	17.99	-28.01
450.010	26.00	16.20	2.20	27.91	16.49	-29.51
580.960	25.15	18.50	2.56	28.32	17.89	-28.11
739.070	26.23	20.00	2.88	27.78	21.33	-24.67
						46.00 QP

1~25 GHz Harmonics & Spurious Emissions. Peak & Average Measurement

Peak Measurement:

Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Reading Level (dB μ V)	Emission Level (dB μ V/m)	Limit (dB μ V/m)	Antenna polarization
4880.00	31.57	8.63	34.30	46.71	52.61	74.00	V
7320.00	36.50	12.23	34.30	45.20	59.63	74.00	V
4880.00	31.57	8.63	34.30	43.83	49.73	74.00	H
7320.00	36.50	12.23	34.30	45.50	59.93	74.00	H

Average Measurement:


Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Reading Level (dB μ V)	Emission Level (dB μ V/m)	Limit (dB μ V/m)	Antenna polarization
4880.00	31.57	8.63	34.30	37.78	43.68	54.00	V
7320.00	36.50	12.23	34.30	36.21	50.64	54.00	V
4880.00	31.57	8.63	34.30	37.51	43.41	54.00	H
7320.00	36.50	12.23	34.30	35.53	49.96	54.00	H

Test at Channel17 (2.480 GHz) in transmitting status

30 MHz~1 GHz Spurious Emissions .Quasi-Peak Measurement

Vertical:

Peak scan


Level (dB μ V/m)

Quasi-peak measurement

Freq	ReadAntenna		Cable Preamp		Over Limit	Line	Remark
	Level	Factor	Loss	Factor			
MHz	dB μ V	dB/m	dB	dB	dB μ V/m	dB	dB μ V/m
138.640	31.29	11.06	1.16	27.47	16.04	-27.46	43.50 QP
323.910	27.35	13.59	1.88	27.26	15.56	-30.44	46.00 QP
419.940	28.40	16.20	2.13	27.83	18.90	-27.10	46.00 QP
534.400	28.03	18.02	2.47	28.17	20.35	-25.65	46.00 QP
700.270	27.13	18.90	2.80	27.88	20.95	-25.05	46.00 QP
845.770	26.90	20.45	3.27	27.21	23.41	-22.59	46.00 QP

Horizontal:

Peak scan

Level (dB μ V/m)

Quasi-peak measurement

Freq MHz	Read		Antenna		Cable		Preamp	Over Limit dB	Limit Line Remark
	Level	Factor	Loss	Factor	Level	dBuV/m	dBuV/m		
	dBuV	dB/m		dB	dBuV/m		dBuV/m		
132.820	31.79	11.84	1.14	27.50	17.27	-26.23	43.50	QP	
266.680	32.60	12.30	1.68	27.12	19.46	-26.54	46.00	QP	
412.180	27.09	16.37	2.12	27.80	17.78	-28.22	46.00	QP	
556.710	26.62	18.48	2.52	28.24	19.38	-26.62	46.00	QP	
727.430	25.78	19.60	2.86	27.81	20.43	-25.57	46.00	QP	
889.420	27.93	20.20	3.44	26.82	24.75	-21.25	46.00	QP	

1~25 GHz Harmonics & Spurious Emissions. Peak & Average Measurement

Peak Measurement:

Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Reading Level (dB μ V)	Emission Level (dB μ V/m)	Limit (dB μ V/m)	Antenna polarization
4960.00	31.70	8.28	34.30	44.59	50.27	74.00	V
7440.00	36.60	12.14	34.30	44.12	58.56	74.00	V
4960.00	31.70	8.28	34.30	44.79	50.47	74.00	H
7440.00	36.60	12.14	34.30	44.11	58.55	74.00	H

Average Measurement:

Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Reading Level (dB μ V)	Emission Level (dB μ V/m)	Limit (dB μ V/m)	Antenna polarization
4960.00	31.70	8.28	34.30	39.30	44.98	54.00	V
7440.00	36.60	12.14	34.30	36.13	50.57	54.00	V
4960.00	31.70	8.28	34.30	38.45	44.13	54.00	H
7440.00	36.60	12.14	34.30	35.68	50.12	54.00	H

The field strength is calculated by adding the Antenna Factor. Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Loss – Preamplifier Factor.

As shown in Section, for frequencies above 1000 MHz. the above field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

No any other emissions level which are attenuated less than 20dB below the limit.

According to 15.31(o), The amplitude of spurious emissions from intentional radiators and emissions from unintentional radiators which are attenuated more than 20 dB below the permissible value need not be reported unless specifically required elsewhere in this Part.

Hence there no other emissions have been reported.

Remark:

- 1) For this intentional radiator operates below 25 GHz. The spectrum shall be investigated to the tenth harmonics of the highest fundamental frequency. And above the third harmonic of this intentional radiator, the disturbance is very low. So the test result only displays to 3rd harmonic.
- 2). As shown in Section, for frequencies above 1000 MHz. the above field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.
- 3). The test only perform the EUT in transmitting status since the test frequencies were over 1GHz only required transmitting status.

Test result: The unit does meet the FCC requirements.

7.6.2 Radiated Emissions which fall in the restricted bands

Test Requirement: FCC Part 15 C section 15.247
(d) In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

Test Method: ANSI C63.10: Clause 6.4, 6.5 and 6.6

Test Status: Test the EUT in continuous transmitting with modulation at lowest, middle and highest channel.

Test site: Measurement Distance: 3m (Semi-Anechoic Chamber)

Limit: 40.0 dB μ V/m between 30MHz & 88MHz;
43.5 dB μ V/m between 88MHz & 216MHz;
46.0 dB μ V/m between 216MHz & 960MHz;
54.0 dB μ V/m above 960MHz.

Detector: For PK value:
RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz
VBW \geq RBW
Sweep = auto
Detector function = peak
Trace = max hold
For AV value:
RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz
VBW = 10Hz
Sweep = auto
Detector function = peak
Trace = max hold

Section 15.205 Restricted bands of operation.

(a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 -	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.52525	2655 - 2900	22.01 - 23.12
8.41425 - 8.41475	156.7 - 156.9	3260 - 3267	23.6 - 24.0
12.29 - 12.293	162.0125 - 167.17	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	167.72 - 173.2	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	240 - 285	3600 - 4400	
13.36 - 13.41	322 - 335.4		

7.6.2.1 DSSS mode with 200Kbps data rate

Test Result:

Test at Channel 1 (2.405 GHz) in transmitting status

Peak Measurement:

Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Reading Level (dB μ V)	Emission Level (dB μ V/m)	Limit (dB μ V/m)	Antenna polarization
2310.000	27.93	5.98	35.10	46.48	45.29	74.00	Vertical
2390.000	27.61	6.14	35.05	47.43	46.13	74.00	V
2483.500	27.55	6.30	34.99	46.36	45.22	74.00	V
2500.000	27.55	6.30	34.98	46.51	45.38	74.00	V
2310.000	27.93	5.98	35.10	46.05	44.86	74.00	Horizontal
2390.000	27.61	6.14	35.05	48.65	47.35	74.00	H
2483.500	27.55	6.30	34.99	46.12	44.98	74.00	H
2500.000	27.55	6.30	34.98	46.47	45.34	74.00	H

Average Measurement:

Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Reading Level (dB μ V)	Emission Level (dB μ V/m)	Limit (dB μ V/m)	Antenna polarization
2310.000	27.93	5.98	35.10	24.38	23.19	54.00	Vertical
2390.000	27.61	6.14	35.05	24.46	23.16	54.00	V
2483.500	27.55	6.30	34.99	24.16	23.02	54.00	V
2500.000	27.55	6.30	34.98	24.82	23.69	54.00	V
2310.000	27.93	5.98	35.10	25.32	24.13	54.00	Horizontal
2390.000	27.61	6.14	35.05	25.38	24.08	54.00	H
2483.500	27.55	6.30	34.99	24.57	23.43	54.00	H
2500.000	27.55	6.30	34.98	25.42	24.29	54.00	H

Test at Channel 8 (2.440 GHz) in transmitting status

Peak Measurement:

Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Reading Level (dB μ V)	Emission Level (dB μ V/m)	Limit (dB μ V/m)	Antenna polarization
2310.000	27.93	5.98	35.10	45.58	44.39	74.00	Vertical
2390.000	27.61	6.14	35.05	47.31	46.01	74.00	V
2483.500	27.55	6.30	34.99	46.35	45.21	74.00	V
2500.000	27.55	6.30	34.98	46.68	45.55	74.00	V
2310.000	27.93	5.98	35.10	46.09	44.90	74.00	Horizontal
2390.000	27.61	6.14	35.05	46.18	44.88	74.00	H
2483.500	27.55	6.30	34.99	46.74	45.60	74.00	H
2500.000	27.55	6.30	34.98	46.52	45.39	74.00	H

Average Measurement:

Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Reading Level (dB μ V)	Emission Level (dB μ V/m)	Limit (dB μ V/m)	Antenna polarization
2310.000	27.93	5.98	35.10	24.05	22.86	54.00	Vertical
2390.000	27.61	6.14	35.05	24.49	23.19	54.00	V
2483.500	27.55	6.30	34.99	24.13	22.99	54.00	V
2500.000	27.55	6.30	34.98	24.47	23.34	54.00	V
2310.000	27.93	5.98	35.10	26.24	25.05	54.00	Horizontal
2390.000	27.61	6.14	35.05	25.66	24.36	54.00	H
2483.500	27.55	6.30	34.99	26.38	25.24	54.00	H
2500.000	27.55	6.30	34.98	25.41	24.28	54.00	H

Test at Channel 17 (2.480 GHz) in transmitting status

Peak Measurement:

Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Reading Level (dB μ V)	Emission Level (dB μ V/m)	Limit (dB μ V/m)	Antenna polarization
2310.000	27.93	5.98	35.10	46.18	44.99	74.00	Vertical
2390.000	27.61	6.14	35.05	45.87	44.57	74.00	V
2483.500	27.55	6.30	34.99	46.39	45.25	74.00	V
2500.000	27.55	6.30	34.98	46.47	45.34	74.00	V
2310.000	27.93	5.98	35.10	46.18	44.99	74.00	Horizontal
2390.000	27.61	6.14	35.05	46.37	45.07	74.00	H
2483.500	27.55	6.30	34.99	46.42	45.28	74.00	H
2500.000	27.55	6.30	34.98	46.57	45.44	74.00	H

Average Measurement:

Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Reading Level (dB μ V)	Emission Level (dB μ V/m)	Limit (dB μ V/m)	Antenna polarization
2310.000	27.93	5.98	35.10	24.04	22.85	54.00	Vertical
2390.000	27.61	6.14	35.05	24.81	23.51	54.00	V
2483.500	27.55	6.30	34.99	25.32	24.18	54.00	V
2500.000	27.55	6.30	34.98	24.83	23.70	54.00	V
2310.000	27.93	5.98	35.10	24.22	23.03	54.00	Horizontal
2390.000	27.61	6.14	35.05	26.17	24.87	54.00	H
2483.500	27.55	6.30	34.99	24.39	23.25	54.00	H
2500.000	27.55	6.30	34.98	24.72	23.59	54.00	H

7.7 Band Edges Requirement

Test Requirement: FCC Part 15 C section 15.247


(d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating. The radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power. Based on either an RF conducted or a radiated measurement. Provided the transmitter demonstrates compliance with the peak conducted power limits.

Frequency Band: 2400 MHz to 2483.5 MHz

Test Method: ANSI C63.10: Clause 6.9.2

Test Status: Test the EUT in continuous transmitting with modulation at lowest, middle and highest channel.

Test Configuration:



Test Procedure:

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum analyzer or power meter.
2. Set RBW=100 kHz , VBW=100KHz ,suitable frequency span including 100 kHz bandwidth from band edge..
3. Measure the Conducted Spurious Emissions and Radiated Emissions of the test frequency with special test status.
4. Repeat until all the test status is investigated.
5. Report the worse.

Test result with plots as follows:

The band edges was measured and recorded Result:


The Lower Edges attenuated more than 20dB.

The Upper Edges attenuated more than 20dB.


Result plot as follows:

DSSS mode with 200Kbps data rate

Channel1: 2.405 GHz



Channel 17: 2.480 GHz



7.8 Conducted Emissions at Mains Terminals 150 kHz to 30MHz

Test Requirement: FCC Part 15 C section 15.207

Test Method: ANSI C63.10: Clause 6.2

Frequency Range: 150 kHz to 30 MHz

Detector: Peak for pre-scan (9kHz Resolution Bandwidth)

Test Limit

Limits for conducted disturbance at the mains ports of class B


Frequency Range (MHz)	Class B Limit (dBuV)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56	56 to 46
0.50 to 5	56	46
5 to 30	60	50

NOTE 1 The limit decreases linearly with the logarithm of the frequency in the range 0,15 MHz to 0,50 MHz.

EUT Operation: Test in normal operating mode. For intentional radiators, measurements of the variation of the input power or the radiated signal level of the fundamental frequency component of the emission, as appropriate, shall be performed with the supply voltage varied between 85% and 115% of the nominal rated supply voltage.

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Test Configuration:



Test procedure:

1. The mains terminal disturbance voltage test was conducted in a shielded room.
2. The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a $50\Omega/50\mu\text{H} + 5\Omega$ linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
3. The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane, but separated from metallic contact with the ground reference plane by 0.1m of insulation.
4. The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0,4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0,8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0,8 m from the LISN 2.

7.8.1 Measurement Data


An initial pre-scan was performed on the live and neutral lines with peak detector.

Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission were detected. For EUT the communicating was worst case mode.

The following Quasi-Peak and Average measurements were performed on the EUT:

Neutral Line


Level(dB μ V)



Measure data:

Freq MHz	Read Level dBuV	Cable Loss dB	LISN Factor dB	Level dBuV	Limit Line dBuV	Over Limit dB	Over Limit Remark	
							Line	Remark
0.163	44.71	0.08	9.65	54.44	65.30	-10.86	QP	
0.163	29.34	0.08	9.65	39.07	55.30	-16.23	AVERAGE	
0.192	42.69	0.12	9.64	52.45	63.93	-11.48	QP	
0.192	27.14	0.12	9.64	36.90	53.93	-17.03	AVERAGE	
0.244	37.53	0.11	9.64	47.28	61.95	-14.68	QP	
0.244	22.14	0.11	9.64	31.89	51.95	-20.07	AVERAGE	
0.336	30.76	0.06	9.63	40.45	59.31	-18.86	QP	
0.336	18.37	0.06	9.63	28.06	49.31	-21.25	AVERAGE	
2.144	14.08	0.07	9.70	23.85	56.00	-32.15	QP	
2.144	3.29	0.07	9.70	13.06	46.00	-32.94	AVERAGE	
22.535	11.26	0.27	10.47	22.00	60.00	-38.00	QP	
22.535	5.67	0.27	10.47	16.41	50.00	-33.59	AVERAGE	

Live Line

Level(dB μ V)

Measure result:

Freq MHz	Read Level dBuV	Cable Loss dB	LISN Factor dB	Level dBuV	Limit Line dBuV	Over Limit dB	Remark
0.152	46.14	0.06	9.63	55.83	65.91	-10.08	QP
0.152	29.95	0.06	9.63	39.64	55.91	-16.27	AVERAGE
0.169	43.45	0.09	9.63	53.17	64.99	-11.82	QP
0.169	28.50	0.09	9.63	38.22	54.99	-16.77	AVERAGE
0.207	39.09	0.13	9.62	48.84	63.32	-14.48	QP
0.207	24.50	0.13	9.62	34.25	53.32	-19.07	AVERAGE
0.259	35.89	0.10	9.63	45.62	61.47	-15.85	QP
0.259	19.79	0.10	9.63	29.52	51.47	-21.95	AVERAGE
2.167	14.13	0.07	9.67	23.87	56.00	-32.13	QP
2.167	4.17	0.07	9.67	13.91	46.00	-32.09	AVERAGE
21.946	10.98	0.27	10.33	21.57	60.00	-38.43	QP
21.946	3.82	0.27	10.33	14.41	50.00	-35.59	AVERAGE

--End of Report--