

FCC RF EXPOSURE REPORT

For

Bluetooth/Wi-Fi Gateway

MODEL NUMBER: HCGA30CWB

REPORT NUMBER: 4791676133.1-RF-1

ISSUE DATE: March 4, 2025

FCC ID: O3I-HCGA30CWB

Prepared for

**Taiwan Fu Hsing Industrial Co., Ltd.
No.88, Yucai Rd., Gangshan Dist., Kaohsiung City 820, Taiwan**

Prepared by

UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch

Building 10, Innovation Technology Park, No. 1, Li Bin Road, Song Shan Lake Hi-Tech Development Zone Dongguan, 523808, People's Republic of China

Tel: +86 769 22038881

Fax: +86 769 33244054

Website: www.ul.com

Revision History

| Rev. | Issue Date | Revisions | Revised By |
|------|---------------|---------------|------------|
| V0 | March 4, 2025 | Initial Issue | |

TABLE OF CONTENTS

| | |
|---------------------------------------|---|
| 1. ATTESTATION OF TEST RESULTS | 4 |
| 2. TEST METHODOLOGY | 5 |
| 3. FACILITIES AND ACCREDITATION | 5 |
| 4. REQUIREMENT | 6 |

1. ATTESTATION OF TEST RESULTS

Applicant Information

Company Name: Taiwan Fu Hsing Industrial Co., Ltd.
Address: No.88, Yucai Rd., Gangshan Dist., Kaohsiung City 820, Taiwan

Manufacturer Information

Company Name: Taiwan Fu Hsing Industrial Co., Ltd.
Address: No.88, Yucai Rd., Gangshan Dist., Kaohsiung City 820, Taiwan

EUT Information

EUT Name: Bluetooth/Wi-Fi Gateway
Model: HCGA30CWB
Sample Received Date: February 17, 2025
Sample Status: Normal
Sample ID: 8170642
Date of Tested: February 18, 2025 to March 4, 2025

| APPLICABLE STANDARDS | |
|---|--------------|
| STANDARD | TEST RESULTS |
| 447498 D04 Interim General RF Exposure Guidance v01 | PASS |

Prepared By:



Johnson Liu
Laboratory Engineer

Checked By:



Kebo Zhang
Senior Project Engineer

Approved By:



Stephen Guo
Operations Manager

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with 47 CFR FCC Part 1 Subpart I, section 1.1307 and KDB 447498 D04 Interim General RF Exposure Guidance v01.

3. FACILITIES AND ACCREDITATION

| | |
|---------------------------|---|
| Accreditation Certificate | <p>A2LA (Certificate No.: 4102.01) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with A2LA.</p> <p>FCC (FCC Designation No.: CN1187) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. Has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules</p> <p>ISED (Company No.: 21320) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been registered and fully described in a report filed with ISED. The Company Number is 21320 and the test lab Conformity Assessment Body Identifier (CABID) is CN0046.</p> |
|---------------------------|---|

Note 1: All tests measurement facilities use to collect the measurement data are located at Building 10, Innovation Technology Park, Song Shan Lake Hi tech Development Zone, Dongguan, 523808, China

Note 2: The test anechoic chamber in UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch had been calibrated and compared to the open field sites and the test anechoic chamber is shown to be equivalent to or worst case from the open field site.

Note 3: For below 30MHz, lab had performed measurements at test anechoic chamber and comparing to measurements obtained on an open field site. And these measurements below 30MHz had been correlated to measurements performed on an OFS.

4. REQUIREMENT

LIMIT AND CALCULATION METHOD

According to 447498 D04 Interim General RF Exposure Guidance v01,

2.1.4 MPE-Based Exemption

An alternative to the SAR-based exemption is provided in § 1.1307(b)(3)(i)(C), for a much wider frequency range, from 300 kHz to 100 GHz, applicable for separation distances greater or equal to $\lambda/2\pi$, where λ is the free-space operating wavelength in meters. The MPE-based test exemption condition is in terms of ERP, defined as the product of the maximum antenna gain and the delivered maximum time-averaged power. For this case, a RF source is an RF exempt device if its ERP (watts) is no more than a frequency-dependent value, as detailed tabular form in Appendix B. These limits have been derived based on the basic specifications on Maximum Permissible Exposure (MPE) considered for the FCC rules in § 1.1310(e)(1).

MPE-based Exemption

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases} \quad (\text{B.1})$$

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}}(d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases} \quad (\text{B.2})$$

where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$$

and f is in GHz, d is the separation distance (cm), and $ERP_{20\text{cm}}$ is per Formula (B.1).

CALCULATED RESULTS**For Single RF Source**

| Operating Mode | Max. Tune up Power | Max. Antenna Gain | EIRP | ERP | ERP | Distance | Limit Threshold |
|----------------|--------------------|-------------------|-------|-------|--------|----------|-----------------|
| | (dBm) | (dBi) | (dBm) | (dBm) | (mW) | (cm) | (mW) |
| BLE | 8.0 | -0.3 | 7.7 | 5.55 | 3.589 | 20 | 3060 |
| WIFI2.4G | 18.0 | -0.3 | 17.7 | 15.55 | 35.892 | 20 | 3060 |

Note:

1. The calculated distance is 20 cm.
2. The power comes from operation description.
3. The EUT does not support simultaneous operation.

END OF REPORT