

May 25, 2012

Federal Communication Commission
Office of Engineering and Technology
Equipment Authorization Division
7345 Oakland Mills Road
Columbia, Maryland 21046

REQUEST FOR MODULAR APPROVAL

Dear Application Examiner:

RE: FCC ID: O46RY12M01

Rexense is seeking application for modular approval of its ZigBee transceiver module (referred to below as “the module”).

The module meets the requirements for modular approval as detailed in FCC Public Notice DA00-1407. Compliance to each of the requirements is described below:

1. The modular transmitter must have its own RF shielding.

The radio portion of the module is contained in its own RF shielding. See external photos in Exhibits.

2. The modular transmitter must have buffered modulation/data inputs

The module has buffered data inputs to insure compliance with Part 15 requirements under conditions of excessive data rates or over-modulation.

3. The modular transmitter must have its own power supply regulation

The module contains an onboard supply voltage regulator.

4. The modular transmitter must comply with the antenna requirements of Section 15.203 and 15.204c.

The transmitter shall only be used with the tested integral antenna or with an antenna that has less antenna gain. Requirements for the use of external antennas are specified in Exhibit—page 37 of User’s manual.

5. The modular transmitter must be tested in a stand-alone configuration.

The module was tested in a stand-alone configuration. See test photo Exhibit.

6. The modular transmitter must be labeled with its own FCC ID number.

The module will be labeled with its own FCC ID number. See related exhibit. If the module is installed inside of an end-product, the label will not be Visible. In this case the OEM customer will be instructed to how to apply the exterior label.


7. The modular transmitter must comply any specific rule or operating requirements applicable to the transmitter and the manufacturer must provide adequate instructions along with the module to explain any such requirements.

The module is compliance with all applicable FCC rules. Detail instructions are given in the Users Manual.

8. The modular transmitter must comply with any applicable RF exposure requirement.

The module complies to FCC Part 15.247 and has a measured maximum measured power output of 4.56mW (6.59dBm) EIRP. See Test report exhibit. The Module is compliance with all applicable FCC RF exposure requirement. End-users and OEM operators must take necessary precaution so that the final product complies with transmitter operating conditions for satisfy RF exposure compliance.

Sincerely,



Jessie Shen / Engineer

ZHEJIANG REXENSE TECHNOLOGY CO., LTD.

Tel: 86-571-28081057

Fax: 86-571-87987620